

MOTOR TYPE	POWER		U _N	n _N	I _N	I _A	η - EFFICIENCY			Cosφ - POWER FACTOR			τ _N	τ _N	AXIAL LOAD
							η - VERİMLİLİK			Cosφ - GÜÇ FAKTÖRÜ					
	GÜÇ						at % load / % yükte			at % load / % yükte					EKSENEL YÜK
MOTOR TİPİ	HP	kW	V	rpm	A	A	50	75	100	50	75	100	Nm	Nm	kN
KM8-35	35	26.5	380	2890	50	193.0	86	86	84	0.85	0.88	0.88	86	109	45
			400	2892	52.4	202.3	86	87	85	0.84	0.88	0.88	86	122	
			415	2895	54.9	211.9	87	87	85	0.84	0.88	0.88	85	131	
KM8-40	40	30	380	2890	60.6	233.9	87	87	85	0.85	0.88	0.88	98	125	45
			400	2905	56.8	219.2	87	88	87	0.82	0.87	0.88	98	140	
			415	2914	54.3	209.6	87	88	87	0.81	0.87	0.88	97	149	
KM8-50	50	37	380	2886	74	285.6	88	88	86	0.84	0.88	0.88	121	155	45
			400	2902	69.4	267.9	88	88	87	0.82	0.87	0.88	121	175	
			415	2911	66.4	256.3	88	89	88	0.81	0.86	0.88	120	188	
KM8-60	60	45	380	2889	88.3	340.8	88	88	87	0.83	0.88	0.89	147	215	45
			400	2904	83	320.4	89	89	88	0.81	0.87	0.89	147	239	
			415	2912	79.7	307.6	89	89	89	0.79	0.86	0.88	146	259	
KM8-70	70	52	380	2892	101.5	391.8	89	89	88	0.82	0.87	0.89	170	276	45
			400	2905	95.8	369.8	89	89	89	0.79	0.86	0.88	169	307	
			415	2914	92.2	355.9	89	90	89	0.78	0.85	0.88	169	335	
KM8-75	75	55	380	2883	107.9	416.5	89	89	87	0.83	0.88	0.89	180	298	45
			400	2898	101.5	391.8	89	89	88	0.81	0.87	0.89	180	338	
			415	2908	97.4	376.0	89	90	89	0.79	0.86	0.88	179	362	
KM8-80	80	60	380	2882	117.9	455.1	89	89	87	0.82	0.88	0.89	196	298	45
			400	2898	110.9	428.1	89	89	88	0.8	0.87	0.89	196	317	
			415	2907	106.5	411.1	89	90	89	0.79	0.86	0.88	195	353	
KM8-90	90	67	380	2877	130.8	504.9	89	89	88	0.82	0.87	0.88	220	352	45
			400	2893	123.1	475.2	89	90	89	0.8	0.86	0.88	219	393	
			415	2902	118.3	456.6	89	90	90	0.79	0.86	0.88	219	427	
KM8-100	100	75	380	2869	147.1	567.8	90	90	88	0.82	0.87	0.88	246	417	55
			400	2886	138.3	533.8	90	90	89	0.8	0.86	0.88	246	472	
			415	2896	132.7	512.2	90	91	90	0.79	0.85	0.88	245	510	
KM8-110	110	81	380	2874	158	609.9	90	90	88	0.81	0.87	0.88	266	467	55
			400	2890	148.9	574.8	90	90	89	0.79	0.86	0.88	265	528	
			415	2900	143.3	553.1	91	91	90	0.77	0.85	0.87	265	569	
KM8-125	125	92	380	2878	183.9	709.9	90	90	89	0.77	0.84	0.87	305	555	55
			400	2893	174.3	672.8	90	90	89	0.74	0.83	0.86	305	626	
			415	2902	168.3	649.6	90	91	90	0.73	0.81	0.85	304	674	
KM8-135	135	100	380	2873	200.6	774.3	89	89	88	0.77	0.84	0.86	330	601	55
			400	2884	187.7	724.5	89	89	88	0.74	0.83	0.86	330	677	
			415	2899	182.1	702.9	89	90	89	0.74	0.81	0.85	329	729	
KM8-150	150	110	380	2868	225.6	870.8	88	88	88	0.77	0.85	0.86	368	670	55
			400	2876	207.7	801.7	89	89	88	0.75	0.83	0.86	368	755	
			415	2896	203	783.6	89	89	88	0.75	0.82	0.86	367	813	