

SimpleLogging Package

Version 1.9
January 2022

Gray Watson

This manual is licensed by Gray Watson under the Creative Commons Attribution-Share Alike 3.0 License.

Permission is granted to make and distribute verbatim copies of this manual provided this license notice and this permission notice are preserved on all copies.

Table of Contents

SimpleLogging	1
1 Start Using Quickly	2
2 Using SimpleLogging	3
2.1 Downloading Jar	3
2.2 Depending on SimpleLogging in Your Library	3
2.3 Logging Messages with {} Arguments	3
2.4 Setting Log Level or Disabling Logging	5
2.5 How SimpleLogging Discovers the Logging Backend	5
2.6 More Usage Examples	6
2.7 Using With Maven	6
3 Open Source License	8
Index of Concepts	9

SimpleLogging

Version 1.9 – January 2022

The goal of this library is to be a small logging facade that backends to a number of standard logging packages and that can be copied into another project. This allows you to write your code and include log messages without having a fixed dependency on any one logging package. I include this code into my libraries and so they can stay agnostic. This logging code allows you to write messages with the slf4j-style `{}` argument support and then backend to a number of other logging libraries or you can easily implement your own. It also handles arrays appropriately and supports up to 4 arguments before forcing the caller to pass in an object array or calling a different `logArgs(...)` method for variable arguments.

I understand that this facade is similar to other logging systems which separate their API from the implementation. I think SimpleLogging is better than the others because it doesn't use the classpath order to satisfy the connection between the API and the backend. SimpleLogging includes calls directly to specific backend APIs which can be chosen through code or configuration. This direct calling allows for more control over the backend selection and possibly fewer dependencies.

SimpleLogging is also designed to be copied into your open source project so you don't have to add a maven dependency. Just copy the java files from `src/main/java` into your source tree and rename the packages as necessary. Please also copy the `SIMPLELOGGING_LICENSE.txt` file which is the very permissive ISC license.

To get started quickly using SimpleLogging, see [Chapter 1 \[Quick Start\]](#), page 2. There is also a [HTML version of this documentation](#).

Gray Watson <http://256stuff.com/gray/>

1 Start Using Quickly

To use SimpleLogging in your code is similar to other logging libraries that you are used to.

```
// usually a logger will be per-class
// getLogger() also can take a String label
private static final Logger logger =
    LoggerFactory.getLogger(MyClass.class);
...

// log trace message with arguments
// toString() on the args only called if trace messages enabled
logger.trace("some trace information: {} and {}", arg1, arg2);
...

// NOTE: exception argument comes _before_ the
// message format to not confuse the arguments
logger.error(exception, "http client threw getting URL: {}", url);
```

For more extensive instructions, see [Chapter 2 \[Using\]](#), page 3.

2 Using SimpleLogging

2.1 Downloading Jar

To get started with SimpleLogging, you will need to download the jar file. The [SimpleLogging release page](#) is the default repository but the jars are also available from the [central maven repository](#).

The code works with Java 6 or later.

2.2 Depending on SimpleLogging in Your Library

To use the SimpleLogging code in your library, you can either depend on the jar or just copy the classes into a logging package in your code and rename the package as necessary. You may want to tune the order of discovery in the `LogBackendType` enumerated class or remove support for certain loggers that your library doesn't need to support.

SimpleLogging is designed to be copied into your open source project so you don't have to add a dependency. Just copy the java files from `src/main/java` into your source tree and rename the packages as necessary. Please also copy the `SIMPLELOGGING_LICENSE.txt` file which is the very permissive ISC license.

2.3 Logging Messages with {} Arguments

SimpleLogging supports "slf4j" type of arguments. Whenever the {} characters appear in your logging message, the library will look for arguments to substitute into the {}. For example:

```
String host = "server1";  
...  
logger.info("connected to host {}", host);
```

If info messages are being displayed then the following message will be logged:

```
connection to host server1 failed
```

This can be accomplished with a simple `StringBuilder` but the big difference is that no unnecessary objects will be created *unless* the log message is to be written. If the logger is limited to warning messages and above, no `StringBuilder` will be created and the `toString()` method for the arguments will never be called if the above info log call is made.

By default the various log methods (`logger.trace(...)`, `logger.debug(...)`, ...) take 0 to 4 arguments with no objects being created (aside from some possible auto-boxing of numbers). If you need more arguments you can use the argument-array with a explicit `new Object[] { ... }` pattern or use variable arguments with a call to `logger.traceArgs(...)`, `logger.debugArgs(...)`, etc.. The variable arguments also creates an `Object[]` regardless of whether or not the log message will be logged so SimpleLogging wants you to be explicit about creating it. It is recommended that you test for the log level with an `if` statement when you are logging with the `Object[]` or variable arguments.

```

if (logger.isLevelEnabled(Level.TRACE)) {
    // here's with an explicit object array
    logger.trace("Method args: {}, {}, {}, {}, {}",
        new Object[] { schema, host, port, path, query });
    // here's with a variable arguments with traceArgs()
    logger.traceArgs("Method args: {}, {}, {}, {}, {}",
        schema, host, port, path, query);
}

```

Here's how the arguments are turned into strings in the log message:

1. if you pass no arguments to the logger call, then any {} patterns will be displayed with no substitution
2. if you have more {} patterns in the message than arguments, then any extras will output the empty string
3. if you have more arguments than you have {} patterns in the message then they will be ignored
4. null values will output the string null
5. arrays will be displayed as [ele1, ele2, ...] with each element going through the same logic here
6. if the argument implements LogArgumentCreator then the results of arg.createArg() will be displayed
7. by default arg.toString() will be displayed

Here are examples of these rules.

```

// no arguments but a {} pattern
logger.info("connected to host '{}');
// outputs: connected to host ''

// missing port argument is empty
String host = "host1";
logger.info("connected to host '{}' port {}", host);
// outputs: connected to host 'host1' port

// extra port argument is ignored
String host = "host1";
int port = 443;
logger.info("connected to host '{}' port {}", host, port);
// outputs: connected to host 'host1'

// null argument
String host = null;
logger.info("connected to host '{}' failed", host);
// outputs: connected to host 'null'

// arguments that are arrays
String[] hosts = new String[] { "srv1", "srv2" };

```

```
logger.info("connected to hosts {} failed", hosts);
// outputs: connected to hosts [srv1, srv2]

// logging of host which implements LogArgumentCreator where
// host.createArg() returns the string: host4
Host host = new Host();
logger.info("connected to host '{}'", host);
// outputs: connected to host 'host4'

// logging of server where server.toString() returns: srv3
Server server = new Server();
logger.info("connected to host '{}'", server);
// outputs: connected to host 'srv3'
```

2.4 Setting Log Level or Disabling Logging

By default the choice of whether or not to log, for example, a trace log message is up to the specific log backend. For example, if you are using LOG4J, your LOG4J properties file determines whether or not trace logging is enabled for a particular package. That said, there are some ways that you can impact in code which messages will get logged with calls to the SimpleLogging methods regardless of the log backend.

```
// have all INFO or above messages to be logged
// regardless of the backend configurations
Logger.setGlobalLogLevel(Level.INFO);
```

You can also disable all log messages by using the OFF level:

```
// force all messages to be disabled
Logger.setGlobalLogLevel(Level.OFF);
```

Another way to not have any log messages show would be use use the NULL log backend.

```
// set the backend type to be the null logger
LoggerFactory.setLogBackendType(LogBackendType.NULL);
```

2.5 How SimpleLogging Discovers the Logging Backend

Built into the `LoggerFactory` class is a `LogBackendType` enumerated type which SimpleLogging uses to try to locate what logging packages are on the classpath and therefore should be used.

The following logging implementations will be discovered on the classpath in this order.

1. SLF4J – (often paired with logback)
2. ANDROID – Android native Log
3. LOGBACK – Logback direct without SLF4J
4. COMMONS_LOGGING – Apache Commons Logging
5. LOG4J2 – version 2+

6. LOG4J – older
7. LAMBDA – AWS Lambda systems logging
8. LOCAL – log implementation that can write to a simple file
9. CONSOLE – log writing to `System.out` or `System.err`
10. JAVA_UTIL – Java util logging which is usually available in the JRE but never chosen directly
11. NULL – null logger to log no messages

If you need to force the logging type, you can use the following static methods.

```
// used to set a specific LoggerFactory.LogBackendType
LoggerFactory.setLogBackendType(LogBackendType.LOGBACK);
```

Or to specify a specifically factory class including custom ones:

```
// used to set a specific LoggerFactory or custom
LoggerFactory.setLogBackendFactory(new LogbackLogBackendFactory());
```

You can also set the `com.j256.simplelogger.backend` Java property to one of the `LogBackendType` values in the above list. For example: `java -Dcom.j256.simplelogger.backend=LOGBACK`

2.6 More Usage Examples

Usually the logger is defined per-class as a `static` field.

```
private static final Logger logger =
    LoggerFactory.getLogger(MyClass.class);
```

The logger handles trace, debug, info, warn, error, and fatal messages. Not all of these message types are supported by all of the logger backends so SimpleLogging tries to map where appropriate.

```
logger.trace("read '{}' bytes", readCount);
logger.debug("host '{}', port-number {}", host, port);
logger.info("connecting to: {}:{}", host, port);
logger.warn("retry connect to host '{}', port {}", host, port);
logger.error("connect failed to host '{}', port {}", host, port);
logger.fatal(exception, "host '{}' threw exception", host);
```

If you want to use more than 4 arguments, you will either need to pass in an `Object[]` or call the methods with the `Args` suffix. This is a specific design decision because in either case, an `Object[]` is created even if the message is never logged.

```
logger.debug("schema '{}', host '{}', port {}, path {}, query {}",
    new Object[] { schema, host, port, path, query });
```

Or with variable arguments with methods that have an `Args` suffix such as `debugArgs(...)`.

```
logger.debugArgs("scheme '{}', host '{}', port {}, path: {}",
    schema, host, port, path);
```

2.7 Using With Maven

To use SimpleLogging with maven, include the following dependency in your ‘pom.xml’ file:

```
<dependency>
  <groupId>com.j256.simplelogging</groupId>
  <artifactId>simplelogging</artifactId>
  <version>1.9</version>
</dependency>
```

3 Open Source License

ISC License. This document is part of the SimpleLogging project.

Copyright 2022, Gray Watson

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Index of Concepts

{		
{ } arguments	3	
A		
android logging, use with	5	
arguments in the message	3	
array argument logging	4	
author	1	
aws lambda logging, use with	5	
C		
commons logging, use with	5	
copying code	3	
D		
disable all messages	5	
discovering backend	5	
downloading the jars	3	
G		
getting started	2	
H		
how to download the jars	3	
how to get started	2	
how to use	3	
I		
introduction	1	
isc license	8	
J		
java util logging, use with	5	
L		
lambda logging, use with	5	
license	8	
log backend discovery	5	
log level, setting	5	
log type of backends	3	
log4j, use with	5	
log4j2, use with	5	
logback direct, use with	5	
Logger	2	
logging facade	1	
LogMessageCreator	4	
M		
Maven, use with	7	
message arguments	3	
N		
null argument logging	4	
O		
open source license	8	
P		
pom.xml dependency	7	
Q		
quick start	2	
R		
remove all messages	5	
S		
setting log level	5	
simple logging	1	
slf4j, use with	5	
T		
toString, don't use	4	
turn off all messages	5	
U		
using in your library	3	
using SimpleLogging	3	
V		
varargs, use with	6	
variable arguments, use with	6	
W		
where to get new jars	3	