This script is used to manage infrastructure resources using Terraform, specifically creating or deleting resources, based on the given arguments. Here's a detailed explanation of its functionality:

### Overview

The script helps you manage the lifecycle of Terraform-managed infrastructure resources with options for creating (create) or deleting (delete). It accepts a set of arguments to configure the specific settings needed for the Terraform configuration.

## Key Features Explained

## 1. Command Argument Handling (create or delete):

- o create: Deploy the infrastructure using Terraform.
- delete: Tear down the infrastructure that was previously deployed.
- If neither create nor delete is supplied, the script exits with an error and displays the correct usage.

## 2. Argument Parsing:

- Parses multiple required arguments, including:
  - --profile: The AWS SSO profile name.
  - --confluent-api-key & --confluent-api-secret: The API key and secret for connecting to Confluent (likely for Kafka integration).
  - --snowflake-warehouse: The Snowflake warehouse name.
  - --service-account-user: The service account username.
  - --day-count: Number of days for some specific configuration.
  - --auto-offset-reset: Kafka offset reset behavior (earliest or latest).
  - --number-of-api-keys-to-retain: Number of Confluent API keys to retain.

### 3. Validation Checks:

- Validates that all required arguments are supplied.
- If any argument is missing, the script provides an appropriate error message and terminates.

#### 4. AWS SSO Login:

- Logs in using the specified AWS SSO profile to get temporary AWS credentials.
- Uses aws2-wrap to export AWS credentials (AWS\_ACCESS\_KEY\_ID, AWS\_SECRET\_ACCESS\_KEY, AWS\_SESSION\_TOKEN, AWS\_REGION, AWS\_ACCOUNT\_ID) for further use by Terraform.

## 5. Creating the terraform. tfvars File:

- A terraform.tfvars file is generated dynamically using the supplied arguments.
- The file contains all the necessary variables to deploy infrastructure using Terraform, such as AWS credentials, Confluent API information, Snowflake warehouse details, and other configuration settings.

## 6. Terraform Actions:

- Initialize: Runs terraform init to initialize the working directory.
- Create:
  - Uses terraform plan to preview changes and terraform apply to create/update resources.
- o Delete:
  - Uses terraform destroy to delete all resources managed by the configuration.
  - Deletes associated AWS Secrets Manager secrets used by Confluent and Snowflake.

# Usage Example

The script should be run with the following syntax:

- create: Deploy infrastructure using Terraform.
- **delete**: Remove infrastructure managed by Terraform.
- --profile=<SSO\_PROFILE\_NAME>: The AWS SSO profile to use.
- --confluent-api-key & --confluent-api-secret: Credentials for Confluent API.
- -- snowflake-warehouse: The Snowflake warehouse to use.
- --service-account-user: The service account username.
- --day-count: Number of days for some retention or lifecycle policy.
- --auto-offset-reset=<earliest | latest>: Specify Kafka offset reset strategy.
- --number-of-api-keys-to-retain: Specify the number of API keys to retain.

## Summary

- Lifecycle Management: The script allows you to create and delete infrastructure with Terraform.
- **AWS Integration**: Uses AWS SSO for secure access and manages credentials through environment variables.
- Confluent and Snowflake Configuration: Integrates with Confluent (Kafka) and Snowflake, and dynamically generates the necessary configuration files for Terraform.
- **Secrets Management**: Deletes associated secrets in AWS Secrets Manager when tearing down the infrastructure.

This script provides a streamlined way to manage infrastructure resources with Terraform, ensuring all configurations and credentials are correctly handled throughout the infrastructure lifecycle.