

End-to-end operational guide for running the `confluent-kafka-isotope` reports on **Confluent Cloud for Apache Flink (CCAF)**: provision → deploy reports → drive traffic → observe → teardown. Unlike the [Confluent Platform + Flink on Minikube](#), this is **Terraform-driven** — no local cluster — and everything runs in a fresh Confluent Cloud environment under [terraform/](#).

This is the **managed CCAF** path. The self-managed **Confluent Platform + Flink on Minikube** path is in [docs/runbook-minikube.md](#). Both runtimes run the same seven reports from the same PTF JAR — see [README §4.5](#) for the format-by-runtime split.

- **1.0 Prerequisites**
- **2.0 Provision + deploy the reports**
- **3.0 What gets created**
- **4.0 Useful outputs**
- **5.0 Drive traffic**
- **6.0 Observe**
- **7.0 Teardown**
- **8.0 Troubleshooting**

- **Terraform** `>= 1.13` installed locally.
- A **Cloud-level** Confluent Cloud API key (not cluster-scoped) with permission to create environments, Kafka clusters, Flink compute pools, service accounts, role bindings, Flink artifacts, and statements. Generate via Console → Settings → Cloud API keys.

```
make cc-flink-reports-up CONFLUENT_API_KEY=$CONFLUENT_API_KEY  
CONFLUENT_API_SECRET=$CONFLUENT_API_SECRET
```

- **First run takes ~6–8 minutes** (Kafka cluster provisioning dominates).
- **Re-applies are idempotent** — `CREATE ... IF NOT EXISTS` plus `lifecycle { ignore_changes = [compute_pool] }` on every statement.
- Optional retention override: the script accepts `--day-count=<DAYS>` (default `30`); both `make` targets require `CONFLUENT_API_KEY / CONFLUENT_API_SECRET` or they fail fast with a clear message.

[illegible]

Resource	Name	Notes
<code>confluent_environment</code>	<code>confluent-kafka-isotope</code>	ESSENTIALS stream-governance package
<code>confluent_kafka_cluster</code>	<code>kafka-isotope</code>	Standard, single-zone, AWS us-east-1 by default
<code>confluent_kafka_topic</code> × 4	<code>orders.</code> <code>{placed,enriched,fulfilled}</code> + <code>isotope_consume_edge_markers</code>	Only the event + consume-marker topics are pre-created. The 7 <code>isotope_report_*_1m</code> sink topics are created on first deploy by their <code>CREATE TABLE</code> (pre-creating them would make CCAF's Topic Catalog auto-import them as <code>(key BYTES, val BYTES)</code> and silently no-op the typed DDL).
<code>confluent_service_account</code> + 6 role bindings	<code>isotope-flink-sql-runner</code>	FlinkDeveloper (org) + ResourceOwner on topic/transactional-id/group/SR-subject * + Assigner
<code>confluent_flink_compute_pool</code>	<code>isotope-flink-statement-runner</code>	10 CFU; headroom for 7 INSERTs + ad-hoc SELECTs
<code>confluent_flink_artifact</code>	<code>isotope-flink-udf</code>	Uploads <code>ptf/build/libs/isotope-flink-udf.jar</code>
<code>confluent_flink_statement</code> × 25	(see file)	4 ALTER TABLE + 3 VIEW + 7 sink CREATE TABLE + 2 CREATE FUNCTION (both PTFs) + 7 INSERT INTO (23 long-lived) + 2 transient DROP FUNCTION
<code>confluent_flink_statement</code> × 3 (optional)	(see terraform/setup-ccaf-ai.tf)	Optional AI trace-RCA report — <code>CREATE MODEL trace_rca</code> + 1 Protobuf sink + 1 <code>INSERT ... ML_PREDICT</code> . Gated on <code>var.enable_trace_rca</code> (default <code>false</code>) , so a normal apply skips them entirely. Set <code>rca_model_api_key</code> (and <code>rca_model_provider/_version/_endpoint</code> for a non-OpenAI provider) to enable. See README § 4.5.

Two rotating service-account API key pairs (one Kafka, one Schema Registry) are managed by `module.kafka_api_key_rotation` and `module.sr_api_key_rotation` in [terraform/setup-confluent-kafka.tf](#).

4.0 Useful outputs

```
terraform -chdir=terraform output environment_id
terraform -chdir=terraform output kafka_bootstrap_servers
terraform -chdir=terraform output schema_registry_url
terraform -chdir=terraform output -raw kafka_api_key      # sensitive
terraform -chdir=terraform output -raw kafka_api_secret   # sensitive
```

5.0 Drive traffic (required to see report rows)

The demo app runs **on your host** and talks to Confluent Cloud over SASL_SSL. You don't export credentials manually: `scripts/cc-app-run.sh` sources `scripts/cc-cli-env.sh`, which pulls the Kafka + Schema-Registry credentials from `terraform output`, builds the JAAS string, and invokes `./gradlew :app:run` with the six `-D` flags. It hard-fails if any of the seven required values is missing.

Run the 4-stage demo, one verb per terminal (same A/B/C/D order as the local demo):

```
scripts/cc-app-run.sh place 'hello'    # A – kick the chain off (orders.placed)
scripts/cc-app-run.sh enrich          # B – orders.placed → orders.enriched
scripts/cc-app-run.sh fulfill         # C – orders.enriched → orders.fulfilled
scripts/cc-app-run.sh ship            # D – terminal consume orders.fulfilled (emits
marker)
```

`cc-app-run.sh` also accepts the generic `send` / `hop` / `consume` / `sink` passthrough for ad-hoc topics — run it with no args for the full verb list.

Sustained traffic. The report jobs aggregate over `TUMBLE(event_time, INTERVAL '1' MINUTE)` windows, which only emit once the watermark advances past `window_end`. A burst inside a single 1-minute interval sits in one open window forever — spread records across **multiple** windows:

```
# 30 records, 5s apart ≈ 2.5 min of event-time → spans 3+ windows
for i in {1..30}; do scripts/cc-app-run.sh place "burst-$i"; sleep 5; done
```

Wait ~90s after the **last** record before checking results — that's the watermark catching up. `stuck_trace_alerts_1m` only fires for a trace that goes ≥60s of event time without a fresh hop; to exercise it, send one record to `orders.placed`, skip the `enrich/fulfill` hops, and keep sending unrelated records so the watermark crosses `event_time + 60s`.

6.0 Observe

In the Cloud Console **Flink SQL workspace**, query the report tables:

```
SELECT * FROM isotope_report_latency_1m;
SELECT * FROM isotope_report_bipartite_topology_1m;  -- all 6 edges: 3 produce + 3
consume
SELECT * FROM isotope_report_hop_distribution_1m;
-- ...coverage, stuck_trace, topology, latency_percentiles
```

Terminal D prints the same `trace_id` across all three hops. CCAF report topics ride **Protobuf+SR** (`proto-registry`), versus Avro+SR on the CP path.

7.0 Teardown

```
make cc-flink-reports-down CONFLUENT_API_KEY=$CONFLUENT_API_KEY
CONFLUENT_API_SECRET=$CONFLUENT_API_SECRET
```

Runs `terraform destroy -auto-approve` — deletes **every** resource above, including the environment itself (the report sink topics are cleaned up via the environment cascade). Safe to run repeatedly.

Cost note: the Kafka cluster and compute pool bill while they exist. Teardown when you're done rather than leaving the environment running.

8.0 Troubleshooting

- **CONFLUENT_API_KEY ... must be set.** The `make` target requires both vars on the command line (or exported and passed through) — see [§1.0 Prerequisites](#).
- **aggregate functions are not supported.** Expected if you try to add a UDAF — CCAF rejects user-defined aggregates, which is why percentiles is a PTF — see [README §4.5](#).
- **Typed CREATE TABLE silently no-ops.** A report sink topic was pre-created, so the Topic Catalog auto-imported it as (`key BYTES, val BYTES`) — don't pre-create the `isotope_report_*_1m` topics — see [§3.0 What gets created](#).

- **No report rows.** Almost always the watermark — traffic must span multiple 1-minute windows; wait ~90s after the last record — see [§5.0 Drive traffic](#).
- **App can't authenticate.** `cc-cli-env.sh` couldn't read `terraform output` — re-run `make cc-flink-reports-up` so the rotated keys exist, then retry.