

End-to-end operational guide for running the `confluent-kafka-isotope` reports on **Confluent Cloud for Apache Flink (CCAF)**: provision → deploy reports → drive traffic → observe → teardown. Unlike the [Confluent Platform + Flink on Minikube](#), this is **Terraform-driven** — no local cluster — and everything runs in a fresh Confluent Cloud environment under [terraform/](#).

This is the **managed CCAF** path. The self-managed **Confluent Platform + Flink on Minikube** path is in [docs/runbook-minikube.md](#). Both runtimes run the same seven reports from the same PTF JAR — see [root README §3.3](#) for the format-by-runtime split.

- **1.0 Prerequisites**
- **2.0 Provision + deploy the reports**
- **3.0 What gets created**
- **4.0 Useful outputs**
- **5.0 Drive traffic**
- **6.0 Observe**
- **7.0 Teardown**
- **8.0 Troubleshooting**

- **Terraform** `>= 1.13` installed locally.
- A **Cloud-level** Confluent Cloud API key (not cluster-scoped) with permission to create environments, Kafka clusters, Flink compute pools, service accounts, role bindings, Flink artifacts, and statements. Generate via Console → Settings → Cloud API keys.

```
make cc-flink-reports-up CONFLUENT_API_KEY=$CONFLUENT_API_KEY  
CONFLUENT_API_SECRET=$CONFLUENT_API_SECRET
```

- **First run takes ~6–8 minutes** (Kafka cluster provisioning dominates).
- **Re-applies are idempotent** — `CREATE ... IF NOT EXISTS` plus `lifecycle { ignore_changes = [compute_pool] }` on every statement.
- Optional retention override: the script accepts `--day-count=<DAYS>` (default `30`); both `make` targets require `CONFLUENT_API_KEY / CONFLUENT_API_SECRET` or they fail fast with a clear message.

[illegible]

Resource	Name	Notes
<code>confluent_environment</code>	<code>confluent-kafka-isotope</code>	ESSENTIALS stream-governance package
<code>confluent_kafka_cluster</code>	<code>kafka-isotope</code>	Standard, single-zone, AWS us-east-1 by default
<code>confluent_kafka_topic</code> × 4	<code>orders.</code> <code>{placed,enriched,fulfilled}</code> + <code>isotope_consume_edge_markers</code>	Only the event + consume-marker topics are pre-created. The 7 <code>isotope_report*_1m</code> sink topics are created on first deploy by their <code>CREATE TABLE</code> (pre-creating them would make CCAF's Topic Catalog auto-import them as <code>(key BYTES, val BYTES)</code> and silently no-op the typed DDL).
<code>confluent_service_account</code> + 6 role bindings	<code>isotope-flink-sql-runner</code>	FlinkDeveloper (org) + ResourceOwner on topic/transactional-id/group/SR-subject * + Assigner
<code>confluent_flink_compute_pool</code>	<code>isotope-flink-statement-runner</code>	10 CFU; headroom for 7 INSERTs + ad-hoc SELECTs
<code>confluent_flink_artifact</code>	<code>isotope-flink-udf</code>	Uploads <code>ptf/build/libs/isotope-flink-udf.jar</code>
<code>confluent_flink_statement</code> × 25	(see file)	4 ALTER TABLE + 3 VIEW + 7 sink CREATE TABLE + 2 CREATE FUNCTION (both PTFs) + 7 INSERT INTO (23 long-lived) + 2 transient DROP FUNCTION
<code>confluent_flink_statement</code> × 3 (optional)	(see terraform/setup-ccaf-ai.tf)	Optional AI trace-RCA report — <code>CREATE MODEL trace_rca</code> + 1 Protobuf sink + 1 <code>INSERT ... ML_PREDICT</code> . Gated on <code>var.enable_trace_rca</code> (default <code>false</code>) , so a normal apply skips them entirely. Set <code>rca_model_api_key</code> (and <code>rca_model_provider/_version/_endpoint</code> for a non-OpenAI provider) to enable. See root README §3.3.

Two rotating service-account API key pairs (one Kafka, one Schema Registry) are managed by `module.kafka_api_key_rotation` and `module.sr_api_key_rotation` in [terraform/setup-confluent-kafka.tf](#).

4.0 Useful outputs

```

terraform -chdir=terraform output environment_id
terraform -chdir=terraform output kafka_bootstrap_servers
terraform -chdir=terraform output schema_registry_url
terraform -chdir=terraform output -raw kafka_api_key      # sensitive
terraform -chdir=terraform output -raw kafka_api_secret   # sensitive

```

5.0 Drive traffic (required to see report rows)

The demo app runs **on your host** and talks to Confluent Cloud over SASL_SSL. You don't export credentials manually: `scripts/cc-app-run.sh` sources `scripts/cc-cli-env.sh`, which pulls the Kafka + Schema-Registry credentials from `terraform output`, builds the JAAS string, and invokes `./gradlew :app:run` with the six `-D` flags. It hard-fails if any of the seven required values is missing.

Run the 4-stage demo, one verb per terminal (same A/B/C/D order as the local demo):

```
scripts/cc-app-run.sh place 'hello'      # A – kick the chain off (orders.placed)
scripts/cc-app-run.sh enrich             # B – orders.placed → orders.enriched
scripts/cc-app-run.sh fulfill            # C – orders.enriched → orders.fulfilled
scripts/cc-app-run.sh ship               # D – terminal consume orders.fulfilled (emits
marker)
```

`cc-app-run.sh` also accepts the generic `send` / `hop` / `consume` / `sink` passthrough for ad-hoc topics — run it with no args for the full verb list.

Sustained traffic. The report jobs aggregate over `TUMBLE(event_time, INTERVAL '1' MINUTE)` windows, which only emit once the watermark advances past `window_end`. A burst inside a single 1-minute interval sits in one open window forever — spread records across **multiple** windows:

```
# 30 records, 5s apart ≈ 2.5 min of event-time → spans 3+ windows
for i in {1..30}; do scripts/cc-app-run.sh place "burst-$i"; sleep 5; done
```

Wait ~90s after the **last** record before checking results — that's the watermark catching up. `stuck_trace_alerts_1m` only fires for a trace that goes ≥60s of event time without a fresh hop; to exercise it, send one record to `orders.placed`, skip the `enrich/fulfill` hops, and keep sending unrelated records so the watermark crosses `event_time + 60s`.

6.0 Observe

In the Cloud Console **Flink SQL workspace**, query the report tables:

```
SELECT * FROM isotope_report_latency_1m;
SELECT * FROM isotope_report_bipartite_topology_1m;  -- all 6 edges: 3 produce + 3
consume
SELECT * FROM isotope_report_hop_distribution_1m;
-- ...coverage, stuck_trace, topology, latency_percentiles
```

Terminal D prints the same `trace_id` across all three hops. CCAF report topics ride **Protobuf+SR** (`proto-registry`), versus Avro+SR on the CP path.

7.0 Teardown

```
make cc-flink-reports-down CONFLUENT_API_KEY=$CONFLUENT_API_KEY
CONFLUENT_API_SECRET=$CONFLUENT_API_SECRET
```

Runs `terraform destroy -auto-approve` — deletes **every** resource above, including the environment itself (the report sink topics are cleaned up via the environment cascade). Safe to run repeatedly.

Cost note: the Kafka cluster and compute pool bill while they exist. Teardown when you're done rather than leaving the environment running.

8.0 Troubleshooting

- **CONFLUENT_API_KEY ... must be set.** The `make` target requires both vars on the command line (or exported and passed through) — see [§1.0 Prerequisites](#).
- **Aggregate functions are not supported.** Expected if you try to add a UDAF — CCAF rejects user-defined aggregates, which is why percentiles is a PTF — see [root README §3.3](#).
- **Typed CREATE TABLE silently no-ops.** A report sink topic was pre-created, so the Topic Catalog auto-imported it as (`key BYTES, val BYTES`) — don't pre-create the `isotope_report_*_1m` topics — see [§3.0 What gets created](#).

- **No report rows.** Almost always the watermark — traffic must span multiple 1-minute windows; wait ~90s after the last record — see §5.0 Drive traffic.
- **Column headers already exists in the table.** The four `ALTER TABLE ... ADD (headers ...)` statements are not idempotent and CCAF has no per-column `IF NOT EXISTS`; the column belongs to the topic's catalog entry and outlives the statement resource, so a re-created statement fails and leaves the resource tainted, blocking everything downstream. `make cc-flink-reports-up` now untaints them automatically before applying. Running terraform by hand? Do it yourself first: `terraform state list | grep _add_headers$ | xargs -n1 terraform untaint`.
- **error reading Flink Statement ... 401 Unauthorized.** Terraform reads a statement back with the API key recorded in `state`, and `module.flink_api_key_rotation` keeps only `number_of_api_keys_to_retain` keys — so a statement that outlives that many rotations points at a deleted key, and refresh fails on **both** apply and destroy (the environment becomes un-destroyable). `make cc-flink-reports-up/-down` now runs `scripts/tf-repair-flink-credentials.py` first, which re-points those statements at a key that still exists. Run it by hand if you drive terraform yourself: `python3 scripts/tf-repair-flink-credentials.py terraform/terraform.tfstate`.
- **Request is malformed. name needs to contain lowercase alphanumeric characters and hyphens only.** A `statement_name` used underscores. Statement names are Kubernetes-style (`isotope-report-latency-1m`); the sink `table` names keep their underscores (`isotope_report_latency_1m`) — the two are not the same string.
- **"stopped" or "properties_sensitive" attribute must be updated for Flink Statement.** A statement resource changed in a way the provider cannot apply in place — edited SQL, a new `statement_name`, different properties. Terraform plans it as an in-place update and the API rejects it; it has to be a destroy-and-recreate. `make cc-flink-reports-up` detects these from the plan and re-runs them as `-replace=` automatically; by hand, pass `-replace=confluent_flink_statement.<name>` to terraform apply.
- **App can't authenticate.** `cc-cli-env.sh` couldn't read terraform output — re-run `make cc-flink-reports-up` so the rotated keys exist, then retry.