

Kafka Topics Partition Count Recommender Application

The **Kafka Cluster Topics Partition Count Recommender Application** offers data-driven accuracy for Kafka topic sizing. By analyzing past consumption trends, that is, the average consumption records in bytes, it uses this information to determine consumer throughput. Then, over a rolling seven-day period, it identifies the peak consumption of records in bytes, scaling that number by a factor of X to forecast future demand and calculate the required throughput. Next, it divides the required throughput by the consumer throughput and rounds the result to the nearest whole number to determine the optimal number of partitions. The result is an intelligent, automated recommendation system that ensures each Kafka topic has the appropriate number of partitions to handle current workload and support future growth effectively.

Table of Contents

- **1.0 To get started**
 - **1.1 Setup the Application**
 - **1.2 Run the Application**
 - **1.2.1 Did you notice we prefix `uv run to python src/app.py`?**
 - **1.2.2 Troubleshoot Connectivity Issues (if any)**
- **2.0 How the app calculates the recommended partition count**
- **3.0 What is meant by the Kafka Consumer throughput?**
 - **3.1 Key Factors Affecting Kafka Consumer Throughput**
 - **3.2 Typical Kafka Consumer Throughput**
 - **3.3 Strategies to Improve Consumer Throughput**
- **4.0 Resources**
 - **4.1 Optimization Guides**
 - **4.2 Confluent Cloud Telemetry API**
 - **4.3 Confluent Kafka Python Client**

1.0 To get started

1.1 Setup the Application

1. Clone the repo:

```
git clone https://github.com/j3-signalroom/kafka-cluster-topics-partition_count_recommender-app.git
```

2. Since this project was built using `uv`, please `install` it, and then run the following command to install all the project dependencies:

```
uv sync
```

3. Create the `.env` file and add the following environment variables, filling them with your Confluent Cloud credentials and other required values:

```
BOOTSTRAP_SERVER_URI=<YOUR_BOOTSTRAP_SERVER_URI>
CONFLUENT_CLOUD_API_KEY=<YOUR_CONFLUENT_CLOUD_API_KEY>
CONFLUENT_CLOUD_API_SECRET=<YOUR_CONFLUENT_CLOUD_API_SECRET>
INCLUDE_INTERNAL_TOPICS=False
KAFKA_API_KEY=<YOUR_KAFKA_API_KEY>
KAFKA_API_SECRET=<YOUR_KAFKA_API_SECRET>
KAFKA_CLUSTER_ID=<YOUR_KAFKA_CLUSTER_ID>
REQUIRED_CONSUMPTION_THROUGHPUT_FACTOR=
<YOUR_REQUIRED_CONSUMPTION_THROUGHPUT_FACTOR>
SAMPLE_RECORDS=<True|False>
SAMPLE_SIZE=1000
TOPIC_FILTER=

USE_AWS_SECRETS_MANAGER=<True|False>
AWS_REGION_NAME=<YOUR_AWS_REGION_NAME>
CONFLUENT_CLOUD_API_KEY_AWS_SECRETS=
<YOUR_CONFLUENT_CLOUD_API_KEY_AWS_SECRETS>
KAFKA_API_KEY_AWS_SECRETS=<YOUR_KAFKA_API_KEY_AWS_SECRETS>
```

If you use **AWS Secrets Manager** to handle your secrets, set the `USE_AWS_SECRETS_MANAGER` variable to `True` and provide the required AWS details. Otherwise, set it to `False` and include the secrets directly in the `.env` file. For example, if you set `USE_AWS_SECRETS_MANAGER` to `True`, the application will retrieve secrets from AWS Secrets Manager using the names specified in `CONFLUENT_CLOUD_API_KEY_AWS_SECRETS` and `KAFKA_API_KEY_AWS_SECRETS`. The code expects `CONFLUENT_CLOUD_API_KEY_AWS_SECRETS` to be stored in JSON format with keys `confluent_cloud_api_key` and `confluent_cloud_api_secret`, and `KAFKA_API_KEY_AWS_SECRETS` to be in JSON format with keys `kafka_cluster_id`, `bootstrap.servers`, `sasl.username`, and `sasl.password`.

1.2 Run the Application

Navigate to the Project Root Directory Open your Terminal and navigate to the root folder of the `kafka-cluster-topics-partition_count_recommender-app/` repository that you have cloned. You can do this by executing:

```
cd path/to/kafka-cluster-topics-partition_count_recommender-app/
```

Replace `path/to/` with the actual path where your repository is located.

Then enter the following command below to run the application:

```
uv run python src/app.py
```

```
(base) jeffreyjonathanjennings@Mac kafka-cluster-topics-partition_count_recommender-app % uv run python src/app.py
2025-09-14 14:07:41 - INFO - load - Found credentials in environment variables.
2025-09-14 14:07:42 - INFO - load - Found credentials in environment variables.
2025-09-14 14:07:42 - INFO - analyze_all_topics - Connecting to Kafka cluster and fetching metadata...
2025-09-14 14:07:43 - INFO - analyze_all_topics - Found 2 topics to analyze
2025-09-14 14:07:43 - INFO - _analyze_topic -
Analyzing topic: stock_trades_with_totals
%6[1757855264.673][GETSUBSCRIPTIONS][rdkafka#producer-1] [thrd:main]: Telemetry client instance id changed from AAAAAAAAAAAAAAAAAAAAAA to c+J+A+B8pSrCYN6QoUeBBcA
%6[1757855265.536][GETSUBSCRIPTIONS][rdkafka#consumer-2] [thrd:main]: Telemetry client instance id changed from AAAAAAAAAAAAAAAAAAAAAA to Tk5l0U1PrdGcJ0xEv0bTw
2025-09-14 14:07:46 - INFO - _analyze_topic - Partitions: 6
2025-09-14 14:07:46 - INFO - _analyze_topic - Total messages: 179,444
2025-09-14 14:07:46 - INFO - _analyze_topic -
Analyzing topic: stock_trades
%6[1757855267.914][GETSUBSCRIPTIONS][rdkafka#consumer-3] [thrd:main]: Telemetry client instance id changed from AAAAAAAAAAAAAAAAAAAAAA to i+Lg+EVDSjSHPJ34Ad+0OLA
2025-09-14 14:07:48 - INFO - _analyze_topic - Partitions: 6
2025-09-14 14:07:48 - INFO - _analyze_topic - Total messages: 177,007
2025-09-14 14:07:48 - INFO - main -
=====
2025-09-14 14:07:48 - INFO - main - KAFKA TOPICS ANALYSIS RESULTS
2025-09-14 14:07:48 - INFO - main - Analysis Timestamp: 2025-09-14T14:07:48.421514
2025-09-14 14:07:48 - INFO - main - Kafka Cluster ID: lkc-0v8y16
2025-09-14 14:07:48 - INFO - main - Required Consumption Throughput Factor: 3
2025-09-14 14:07:48 - INFO - main -
=====
2025-09-14 14:07:48 - INFO - main -


| Topic Name               | Messages | Partitions | Required Throughput | Consumer Throughput | Recommended Partitions | Status |
|--------------------------|----------|------------|---------------------|---------------------|------------------------|--------|
| stock_trades             | 177,007  | 6          | 44,508,147          | 12,950,551          | 3                      | Active |
| stock_trades_with_totals | 179,444  | 6          | 31,984,046          | 9,229,736           | 3                      | Active |


=====
2025-09-14 14:07:51 - INFO - main - SUMMARY STATISTICS
2025-09-14 14:07:51 - INFO - main -
=====
2025-09-14 14:07:51 - INFO - main - Total Topics: 2
2025-09-14 14:07:51 - INFO - main - Active Topics: 2 (100.0%)
2025-09-14 14:07:51 - INFO - main - Total Partitions: 12
2025-09-14 14:07:51 - INFO - main - Total Recommended Partitions: 6
2025-09-14 14:07:51 - INFO - main - Total Messages: 356,451
2025-09-14 14:07:51 - INFO - main - Average Partitions per Topic: 6
2025-09-14 14:07:51 - INFO - main - Average Recommended Partitions per Topic: 3
2025-09-14 14:07:51 - INFO - main -
Detailed results exported to: kafka-cluster-topics-partition-count-recommender-app.json
(base) jeffreyjonathanjennings@Mac kafka-cluster-topics-partition_count_recommender-app %
```

You maybe asking yourself why. Well, **uv** is an incredibly fast Python package installer and dependency resolver, written in **Rust**, and designed to seamlessly replace **pip**, **pipx**, **poetry**, **pyenv**, **twine**, **virtualenv**, and more in your workflows. By prefixing **uv run** to a command, you're ensuring that the command runs in an optimal Python environment.

- When you use it with a file ending in `.py` or an HTTP(S) URL, `uv` treats it as a script and runs it with a Python interpreter. In other words, `uv run file.py` is equivalent to `uv run python file.py`. If you're working with a URL, `uv` even downloads it temporarily to execute it. Any inline dependency metadata is installed into an isolated, temporary environment—meaning zero leftover mess! When used with `-`, the input will be read from `stdin`, and treated as a Python script.
- If used in a project directory, `uv` will automatically create or update the project environment before running the command.
- Outside of a project, if there's a virtual environment present in your current directory (or any parent directory), `uv` runs the command in that environment. If no environment is found, it uses the interpreter's environment.

- Documentation: Learn about [uv](#).
- Video: [uv IS THE FUTURE OF PYTHON PACKING!](#)

3 / 6

To verify connectivity to your Kafka cluster, you can use the `kafka-topics.sh` command-line tool. First, create a `client.properties` file with your Kafka credentials:

```
# For SASL_SSL (most common for cloud services)
security.protocol=SASL_SSL
sasl.mechanism=PLAIN
sasl.jaas.config=org.apache.kafka.common.security.plain.PlainLoginModule
required \
  username="<YOUR_KAFKA_API_KEY>" \
  password="<YOUR_KAFKA_API_SECRET>";

# Additional SSL settings if needed
ssl.endpoint.identification.algorithm=https
```

```
./kafka-topics.sh --list --bootstrap-server <YOUR_BOOTSTRAP_SERVER_URI> --
command-config ./client.properties
```

2.0 How the app calculates the recommended partition count

For example, you have a consumer that consumes at **25MB/s**, but the the consumer requirement is a throughput of **1GB/s**. How many partitions should you have?

To determine the number of partitions needed to support a throughput of **1GB/s** for a Kafka consumer that can only consume at **25MB/s**, you can calculate it as follows:

1. Convert the target throughput to the same units:
 - **1GB/s = 1024MB/s**
2. Divide the target throughput by the consumer's capacity:

$$\text{Number of partitions} = \frac{\text{Required throughput}}{\text{Consumer throughput}} = \frac{1024\text{MB/s}}{25\text{MB/s}} = 40.96$$

3. Since you can only have a whole number of partitions, you should round up to the nearest whole number:

$$\text{Number of partitions} = 41$$

The **41 partitions** ensure that the consumer can achieve the required throughput of **1GB/s** while consuming at a rate of **25MB/s** per partition. This will allow the workload to be distributed across partitions so that multiple consumers can work in parallel to meet the throughput requirement.

3.0 What is meant by the Kafka Consumer throughput?

The throughput of a **Kafka consumer** refers to the rate at which it can read data from Kafka topics, typically measured in terms of **megabytes per second (MB/s)** or **messages per second**. Consumer throughput depends on several factors, including the configuration of Kafka, the consumer application, and the underlying infrastructure.

3.1 Key Factors Affecting Kafka Consumer Throughput:

1. Partitions

- Throughput scales with the number of partitions assigned to the consumer. A consumer can read from multiple partitions concurrently, but the total throughput is bounded by the number of partitions and their data production rates.
- Increasing the number of partitions can improve parallelism and consumer throughput.

2. Consumer Parallelism

- A single consumer instance reads from one or more partitions, but it can be overwhelmed if the data rate exceeds its capacity.
- Adding more consumers in a consumer group increases parallelism, as Kafka reassigns partitions to balance the load.

3. Fetch Configuration

- **fetch.min.bytes**: Minimum amount of data (in bytes) the broker returns for a fetch request. Larger values reduce fetch requests but may introduce latency.
- **fetch.max.bytes**: Maximum amount of data returned in a single fetch response. A higher value allows fetching larger batches of messages, improving throughput.
- **fetch.max.wait.ms**: Maximum time the broker waits before responding to a fetch request. A higher value can increase batch sizes and throughput but may increase latency.

4. Batch Size

- Consumers process messages in batches for better efficiency. Larger batches reduce processing overhead but require sufficient memory.
- Configuration: **max.poll.records** controls the number of records fetched in a single poll.

5. Message Size

- Larger messages can reduce throughput if the network or storage systems are bottlenecks. Use compression (e.g., **gzip**, **snappy**) to optimize data transfer.

6. Network Bandwidth

- Network speed between Kafka brokers and consumers is critical. A consumer running on a limited-bandwidth network will see reduced throughput.

7. Deserialization Overhead

- The time required to deserialize records impacts throughput. Efficient deserialization methods (e.g., Avro, Protobuf with optimized schemas) can help.

8. Broker Load

- Broker performance and replication overhead impact the throughput seen by consumers. If brokers are under heavy load, consumer throughput may decrease.

9. Consumer Poll Frequency

- Consumers must frequently call `poll()` to fetch messages. If the consumer spends too much time processing messages between polls, throughput can drop.

10. System Resources

- CPU, memory, and disk I/O on the consumer's machine affect how fast it can process data.

3.2 Typical Kafka Consumer Throughput:

- **Single Partition Throughput:** A single consumer reading from a single partition can typically achieve **10-50 MB/s** or higher, depending on message size, compression, and hardware.
- **Multi-Partition Throughput:** For a consumer group reading from multiple partitions, throughput can scale linearly with the number of partitions (subject to other system limits).

3.3 Strategies to Improve Consumer Throughput:

1. **Increase Partitions:** Scale partitions to allow more parallelism.
2. **Add Consumers:** Add more consumers in the consumer group to distribute the load.
3. **Optimize Fetch Settings:** Tune `fetch.min.bytes`, `fetch.max.bytes`, and `fetch.max.wait.ms`.
4. **Batch Processing:** Use `max.poll.records` to fetch and process larger batches.
5. **Compression:** Enable compression to reduce the amount of data transferred.
6. **Efficient Serialization:** Use optimized serializers and deserializers.
7. **Allocate Resources:** Ensure consumers run on high-performance hardware with sufficient network bandwidth.

By optimizing these factors, Kafka consumers can achieve higher throughput tailored to the specific use case and infrastructure.

4.0 Resources

4.1 Optimization Guides

- [Optimize Confluent Cloud Clients for Throughput](#)
- [Choose and Change the Partition Count in Kafka](#)

4.2 Confluent Cloud Telemetry API

- [Confluent Cloud Telemetry API](#)
- [Confluent Cloud Telemetry API - Datasets](#)
- [Confluent Cloud Telemetry API - Metrics](#)

4.3 Confluent Kafka Python Client

- [Confluent Kafka Python Client Documentation](#)