



Search



Write



# Guide to Time Series Analysis with Python — 3: Autoregressive Process



Buse Köseoğlu · Follow

4 min read · Aug 8, 2023



117



In the previous article, we examined the moving average process. This time we will examine another statistical model, the autoregressive process.

You can find previous articles below.

[1. Guide to Time Series Analysis with Python — 1: Analysis Techniques and Baseline Model](#)

[2. Guide to Time Series Analysis with Python — 2: Moving Average Process](#)

If you're ready, let's start.

## What is Autoregressive Process (AR)?

Autoregressive process is a statistical model used for time series to predict the future by looking at historical data. Just as the moving average process uses the effect of past errors, the autoregressive process says that the past values in the time series affect the present. We can see how this is used in the equation below. Here, the parameter we want to determine is the “p” parameter. This p-value decides how far back we go. It is important to find the optimum number.

$$y_t = C + \phi_1 y_{t-1} + \phi_2 y_{t-2} + \dots + \phi_p y_{t-p} + \epsilon_t$$

Constant

The magnitude of influence of past values on present ones


present error term

## Specifying the p Parameter

We use a method like the method in the moving average process to determine this parameter. But this time we will use PACF (Partial

Autocorrelation Function) plot instead of ACF plot. PACF gives the partial correlation of the time series with its lagged values.

If we examine the roadmap below, we can see how we can reach the result step by step. Here, first of all, we need to see if the data fits the moving average process. If it does not fit, then we need to check whether it is suitable for the autoregressive process with the PACF graph.







Figure from Time series forecasting in python — Marco Peixerio

Let's say we have stationary data. Then, let's draw an ACF plot with this data, and as a result, we get the following graph.

```
plot_acf(ar2_process)


plt.tight_layout()
```



When the above ACF graph is examined, we can see that there are coefficients that are significant after lag 0. When examining this graph in the moving average process, we expected only 1 significant coefficient and the other coefficients to remain within the confidence interval (blue area). Since there is no such situation here, we can say that this data is not suitable for the moving average process and draw the PACF graph.

```
plot_pacf(ar2_process, lags=20)
```

```
plt.tight_layout()
```



If we examine the PACF graph above, we can see that the coefficients after lag 2 are non-significant. At the same time, with this graph, we determine that the “p” parameter is also 2, and we have the AR(2) process.

## Modeling AR(2)

The next processes are very similar to the moving average process. We can implement the AR(2) process with only minor changes. After separating the data as train and test, we can use the following function for modeling.

```
def rolling_forecast(df: pd.DataFrame, train_len: int, horizon: int, window: int):  
  
    total_len = train_len + horizon  
    end_idx = train_len  
  
    if method == 'mean':  
        pred_mean = []  
  
        for i in range(train_len, total_len, window):  
            mean = np.mean(df[:i].values)  
            pred_mean.extend(mean for _ in range(window))  
  
        return pred_mean  
  
    elif method == 'last':  
        pred_last_value = []  
  
        for i in range(train_len, total_len, window):  
            last_value = df[:i].iloc[-1].values[0]  
            pred_last_value.extend(last_value for _ in range(window))
```



```
    return pred_last_value


elif method == 'AR':
    pred_AR = []

    for i in range(train_len, total_len, window):
        model = SARIMAX(df[:i], order=(2,0,0))
        res = model.fit(dispatch=False)
        predictions = res.get_prediction(0, i + window - 1)
        oos_pred = predictions.predicted_mean.iloc[-window:]
        pred_AR.extend(oos_pred)

    return pred_AR
```

The important part here is the `SARIMAX(df[:i], order=(2,0,0))` part in the “AR” condition. In the MA(2) process, the order was written as (0,0,2). In AR(2), it is written as (2,0,0).

Actually, the process is that simple. Both MA and AR contain very similar implementations. You can find the codes for both in the [github repo](#). If we examine the AR model and base model results, we can see the graph below. Here we can see that the autoregressive process captures highs and lows better than the base models and works better than the base model as we expected.



Thank you for reading. See you in the next article.

## References

- Time series forecasting in python — Marco Peixerio
- Tan,Y.-F.;Ong,L.-Y.;Leow, M.-C.; Goh, Y.-X. Exploring Time-Series Forecasting Models for Dynamic Pricing in Digital Signage Advertising.

Future Internet 2021, 13, 241. <https://doi.org/10.3390/fi13100241>

- Machine learning with time series — Markus Löning
- <https://www.influxdata.com/time-series-forecasting-methods/>
- <https://builtin.com/data-science/time-series-forecasting-python>
- <https://www.machinelearningplus.com/time-series/time-series-analysis-python/>
- <https://towardsdatascience.com/interpreting-acf-and-pacf-plots-for-time-series-forecasting-af0d6db4061c>
- [https://en.wikipedia.org/wiki/Partial\\_autocorrelation\\_function](https://en.wikipedia.org/wiki/Partial_autocorrelation_function)

Time Series Forecasting

Autoregressive

Autoregressive Model

Time Series Analysis

Correlation



## Written by Buse Köseoğlu

448 Followers

BAU Software Engineering | Data Science | <https://www.linkedin.com/in/busekoseoglu/>

Follow

### More from Buse Köseoğlu

- The formula for  $R^2$  is

$$R^2 = 1 - \frac{SS_{Residual}}{SS_{Total}}$$


while the formula for adjusted  $R^2$  is

$$R^2_{adj} = 1 - \frac{MS_{Residual}}{MS_{Total}}$$

Buse Köseoğlu in BAU Yazılım ve Bilişim Kulübü

### Model Performansını Değerlendirmek: Regresyon

Regresyonda bağımlı X değişkenlerini alarak bağımsız Y değişkenini tahmin etmeye...



Buse Köseoğlu

### One Layer Neural Network From Scratch—Classification

Classification is a supervised learning method. In supervised learning, we have...

3 min read · Feb 11, 2021

7 min read · Jul 28, 2023



136



2



222



2



Buse Köseoğlu

## TEMEL SWITCH KONFIGÜRASYONU

Bu yazımda iki switch ve iki bilgisayar ile kurulmuş bir topolojide çalışacağız....

6 min read · Aug 28, 2020



60



231

[See all from Buse Köseoğlu](#)


Buse Köseoğlu in BAU Yazılım ve Bilişim Kulübü


## SQL Nedir? Temel SQL Komutları

SQL (Structured Query Language—Yapılandırılmış Sorgu Dili) veritabanı yöneti...

3 min read · Dec 15, 2020

## Recommended from Medium



 Roshmita Dey

### Time Series Decomposition

Time series decomposition is a vital technique that helps in understanding the...

5 min read · Jan 13, 2024



118



1



 Kaan Aslan

### Time Series Forecasting with a Basic Transformer Model in...

Time series forecasting is an essential topic that's both challenging and rewarding, with ...

10 min read · Jan 12, 2024



130



2



## Lists



## Practical Guides to Machine Learning

10 stories · 1528 saves



## Predictive Modeling w/ Python

20 stories · 1271 saves



## ChatGPT prompts

48 stories · 1654 saves



 Zaki Nurkholis

## A Practical Guide on Scikit-learn for Time Series Forecasting


While most machine learning algorithms available in scikit-learn (and various other...

14 min read · Dec 12, 2023



96



 MindsDB team in MindsDB


## How to pick the best-performing time-series AI model for your...



This practical guide will help you easily set up an automated framework to evaluate time-...

13 min read · Apr 27, 2024



28





Vansh Jatana in The Deep Hub

## Mastering Time Series Forecasting

Time series forecasting is an important aspect of Data science and is used in differe...

8 min read · Feb 18, 2024

87 2



Max Zhang

## A guide to time series forecasting with arima in python 3

Introduction

★ · 14 min read · Jan 21, 2024

135



See more recommendations

[Help](#) [Status](#) [About](#) [Careers](#) [Press](#) [Blog](#) [Privacy](#) [Terms](#) [Text to speech](#) [Teams](#)