



Search

Write



★ Get unlimited access to the best of Medium for less than \$1/week. [Become a member](#)



# The Guide to AR, MA, ARIMA, SARIMA Forecasting Method

Rohit Umredkar · [Follow](#)

7 min read · Jan 10, 2024



4



ARIMA models provide another approach to time series forecasting. Exponential smoothing and ARIMA models are the two most widely used approaches to time series forecasting, and provide complementary approaches to the problem. While exponential smoothing models (ESM) are based on a description of the trend and seasonality in the data, ARIMA models aim to describe the autocorrelations in the data.

*Before we introduce ARIMA models, Please go through the discuss concept of stationarity and the technique of differencing time series [here](#).*

## **Autoregressive (AR) Models**

In an autoregression model, we forecast the variable of interest using a linear combination of *past values of the variable*. The term *autoregression* indicates that it is a regression of the variable against itself.

Thus, an autoregressive model of order  $p$  can be written as:

$$y_t = c + \phi_1 y_{t-1} + \phi_2 y_{t-2} + \dots + \phi_p y_{t-p} + \varepsilon_t,$$

where  $\varepsilon_t$  is white noise. It is **AR( $p$ ) model** of order  $p$ .

For an AR(1) model, i.e.  $p=1$ , *AR model of order 1*.

$$\underline{Y}_t = c + \phi_1 * y_{t-1} + \underline{\varepsilon}_t$$

when  $\phi_1=0$ ,  $y_t$  is equivalent to *white noise*;

when  $\phi_1=1$  and  $c=0$ ,  $y_t$  is equivalent to a *random walk*;

when  $\phi_1=1$  and  $c \neq 0$ ,  $y_t$  is equivalent to a *random walk with drift*;

when  $\phi_1 < 0$ ,  $y_t$  tends to *oscillate around the mean*.

## Moving average (MA) models

Rather than using past values of the forecast variable in a regression, a moving average model uses past forecast errors in a regression-like model.

$$y_t = c + \varepsilon_t + \theta_1 \varepsilon_{t-1} + \theta_2 \varepsilon_{t-2} + \dots + \theta_q \varepsilon_{t-q},$$

where  $\varepsilon_t$  is white noise. It is an **MA(q) model** of order  $q$ . Of course, we do not *observe* the values of  $\varepsilon_t$ , so it is not really a regression in the usual sense.

Notice that each value of  $y_t$  can be thought of as a weighted moving average of the past few forecast errors.

It is possible to write any stationary AR(p) model as an MA( $\infty$ ) model. For example, using repeated substitution, we can demonstrate this for an AR(1) model:

$$\begin{aligned}
 y_t &= \phi_1 y_{t-1} + \varepsilon_t \\
 &= \phi_1 (\phi_1 y_{t-2} + \varepsilon_{t-1}) + \varepsilon_t \\
 &= \phi_1^2 y_{t-2} + \phi_1 \varepsilon_{t-1} + \varepsilon_t \\
 &= \phi_1^3 y_{t-3} + \phi_1^2 \varepsilon_{t-2} + \phi_1 \varepsilon_{t-1} + \varepsilon_t
 \end{aligned}$$

Provided  $-1 < \phi_1 < 1$ , the value of  $\phi_1^k$  will get smaller as  $k$  gets larger. So eventually we obtain:

$$y_t = \varepsilon_t + \phi_1 \varepsilon_{t-1} + \phi_1^2 \varepsilon_{t-2} + \phi_1^3 \varepsilon_{t-3} + \dots,$$

## Non-seasonal ARIMA models

If we combine differencing with autoregression and a moving average model, we obtain a non-seasonal ARIMA model. ARIMA is an acronym for AutoRegressive Integrated Moving Average.

$$y'_t = c + \phi_1 y'_{t-1} + \dots + \phi_p y'_{t-p} + \theta_1 \varepsilon_{t-1} + \dots + \theta_q \varepsilon_{t-q} + \varepsilon_t,$$

where  $y'_t$  is the differenced series (can be differenced more than once). The “predictors” on the right hand side include both lagged values of  $y_t$  and lagged errors.

We call this an  $ARIMA(p,d,q)$  model, where

$p$ = order of the autoregressive part


$d$ = degree of first differencing involved

$q$ = order of the moving average part

The same stationarity and invertibility conditions that are used for autoregressive and moving average models also apply to an ARIMA model.

### Special cases of ARIMA models.

White noise	$ARIMA(0,0,0)$
Random walk	$ARIMA(0,1,0)$ with no constant
Random walk with drift	$ARIMA(0,1,0)$ with a constant
Autoregression	$ARIMA(p,0,0)$
Moving average	$ARIMA(0,0,q)$



## Understanding ARIMA models

The `auto.arima()` function is useful, but anything automated can be a little dangerous, and it is worth understanding something of the behaviour of the models.

The constant `c` has an important effect on the long-term forecasts obtained from these models:

*If  $c=0$  and  $d=0$ , the long-term forecasts will go to zero.*

*If  $c=0$  and  $d=1$ , the long-term forecasts will go to a non-zero constant.*

*If  $c=0$  and  $d=2$ , the long-term forecasts will follow a straight line.*

*If  $c \neq 0$  and  $d=0$ , the long-term forecasts will go to the mean of the data.*

*If  $c \neq 0$  and  $d=1$ , the long-term forecasts will follow a straight line.*

*If  $c \neq 0$  and  $d=2$ , the long-term forecasts will follow a quadratic trend.*

## **Estimation and order selection**

### **Information Criteria**

*Akaike's Information Criterion (AIC)*, which was useful in selecting predictors for regression, is also useful for determining the order of an ARIMA model.

It can be written as:

$$AIC = -2 \log(L) + 2(p + q + k + 1),$$

where  $L$  is the likelihood of the data,  $k = 1$  if  $c \neq 0$  and  $k = 0$  if  $c = 0$ .

*For ARIMA models, the corrected AIC can be written as*

$$AIC_c = AIC + \frac{2(p + q + k + 1)(p + q + k + 2)}{T - p - q - k - 2},$$

and the Bayesian Information Criterion can be written as

$$BIC = AIC + [\log(T) - 2](p + q + k + 1).$$

Good models are obtained by *minimising the AIC, AICc or BIC*. Our preference is to use the AICc.

*AIC should not be used to select order of differencing(d)* of a model, but only for selecting the values of p and q. Because the differencing changes the data on which the likelihood is computed, So we need to use some other approach to choose d, and then we can use the AICc to select p and q.


## Seasonal ARIMA models (SARIMA)

A seasonal ARIMA model is formed by including additional seasonal terms in the ARIMA models we have seen so far. It is written as follows:







The data are clearly non-stationary, with some seasonality.



so, we take first seasonal difference, with lag =4, quarterly.



After 1st Seasonal difference (lag=4), the series appear to be non-stationary in above fig, so we take an additional first difference.




Our aim now is to find an appropriate ARIMA model based on the ACF and PACF shown in above fig.

*The significant spike at lag 1 in the ACF suggests a non-seasonal MA(1) component.*

*The significant spike at lag 4 in the ACF suggests a seasonal MA(1) component.*

Consequently, we begin with an  $ARIMA(0,1,1)(0,1,1)_4$  model, indicating a first and seasonal difference, and non-seasonal and seasonal MA(1) components.


The residuals for the fitted  $ARIMA(0,1,1)(0,1,1)_4$  model are shown below.



Both the ACF and PACF show significant spikes at lag 2, and almost significant spikes at lag 3, indicating that some additional non-seasonal terms need to be included in the model.


The AICc of the  $ARIMA(0,1,2)(0,1,1)_4$  model is 74.36, while that for the  $ARIMA(0,1,3)(0,1,1)_4$  model is 68.53.

The author tried other models with AR terms as well, but none that gave a smaller AICc value. Consequently, we choose the  $\text{ARIMA}(0,1,3)(0,1,1)_4$  model and residuals are plotted in below fig.



All the spikes are now within the significance limits, so the residuals appear to be white noise. The Ljung-Box test also shows that the residuals have no remaining autocorrelations.

we now have a seasonal ARIMA model that passes the required checks and is ready for forecasting.



Forecasts from the model for the next three years are shown in above fig. The forecasts follow the recent trend in the data, because of the double differencing. The large and rapidly increasing prediction intervals show that the retail trade index could start increasing or decreasing at any time — while the point forecasts trend downwards.

In conclusion, ARIMA and SARIMA are powerful tools for time series forecasting, especially when dealing with non-stationary data and seasonal patterns. Choosing between ARIMA and SARIMA depends on the nature of the data and whether there are clear seasonal patterns present. These models can be useful for making predictions and understanding trends in various fields, including finance, economics, and environmental science.

Forecasting

Data Science

Time Series Forecasting

Data Analytics

**Written by Rohit Umredkar**

2 Followers

Ads Analytics - Airtel Digital


Follow





## More from Rohit Umredkar



 Rohit Umredkar


### Unlocking Efficiency with Postman Flow: To Test & Automate API


Excited to share my recent experiences with Postman-Flow used in one of the use-case a...

1 min read · Jan 1, 2024



1



 Rohit Umredkar

### “A Guide to Simple Univariate Time Series Forecasting Techniques”

Some forecasting methods are extremely simple and surprisingly effective. We will us...

6 min read · Jan 7, 2024



1





Rohit Umredkar

## SQL Data Types: A Quick Guide to Database Fields 🗄️ 🔍

In the realm of databases, understanding SQL data types is akin to wielding a master key....

3 min read · Jan 1, 2024



Rohit Umredkar

## Unlocking the Power of SQL in Data Science 🚀



Whether you're a seasoned data scientist or just stepping into the world of data,...


3 min read · Jan 1, 2024



See all from Rohit Umredkar

## Recommended from Medium



 Vansh Jatana in The Deep Hub

## Mastering Time Series Forecasting

Time series forecasting is an important aspect of Data science and is used in differ...

8 min read · Feb 18, 2024

 87  2

 Dr. Vipul Joshi in Time Series Using Python

## Introduction to Time Series Analysis—Part 1.1: Stationarity

In Part 1 of the time series, we introduced What is Time Series and Why is Time Series...

10 min read · Apr 18, 2024

 22 

### Lists



#### Predictive Modeling w/ Python

20 stories · 1271 saves



#### Practical Guides to Machine Learning

10 stories · 1528 saves






#### Coding & Development

11 stories · 647 saves



#### ChatGPT prompts

48 stories · 1655 saves




 sophiamsac

## ARIMA vs. SARIMA vs. SARIMAX

Exploring Time Series Forecasting Models

5 min read · Apr 11, 2024



 Aniket Hingane

## Build ARIMA model from scratch | Part 1


Unraveling the Symphony of AR + I + MA (p, d, q) on the Harmonious Stage of Stationary...

6 min read · Jan 3, 2024



 Tapas

## Time Series Accuracy Test: sMAPE vs MAPE



 Hazal Gültekin

## Time Series Analysis and Forecasting with ARIMA

In predictive model performance analysis, several metrics are used to assess the...

5 min read · May 28, 2024



In this article, I will make a time series analysis and forecasting example using the ARIMA...

6 min read · Mar 25, 2024



See more recommendations

[Help](#) [Status](#) [About](#) [Careers](#) [Press](#) [Blog](#) [Privacy](#) [Terms](#) [Text to speech](#) [Teams](#)