

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 6.10
Revision Date 10.09.2020
Print Date 09.10.2020**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Ethyl acetate

Product Number : 270989

Brand : Sigma-Aldrich

Index-No. : 607-022-00-5

REACH No. : 01-2119475103-46-XXXX

CAS-No. : 141-78-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Merck Life Science UK Limited
New Road
The Old Brickyard
GILLINGHAM
Dorset
SP8 4XT
UNITED KINGDOM

Telephone : +44 (0)1747 833-000
Fax : +44 (0)1747 833-313

1.4 Emergency telephone

Emergency Phone # : +44 (0)870 8200418 (CHEMTREC)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Flammable liquids (Category 2), H225

Eye irritation (Category 2), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements**Labelling according Regulation (EC) No 1272/2008**

Pictogram



Signal word

Danger

Hazard statement(s)	
H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precautionary statement(s)	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use non-sparking tools.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: C ₄ H ₈ O ₂
Molecular weight	: 88.11 g/mol
CAS-No.	: 141-78-6
EC-No.	: 205-500-4
Index-No.	: 607-022-00-5

Component	Classification	Concentration
ethyl acetate		
	Flam. Liq. 2; Eye Irrit. 2; STOT SE 3; H225, H319, H336 Concentration limits: 20 %: STOT SE 3, H336;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible liquid.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb®).

Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid generation of vapours/aerosols.

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
ethyl acetate	141-78-6	STEL	400 ppm 1,468 mg/m ³	Commission Directive (EU) 2017/164 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU
	Remarks	Indicative		
		TWA	200 ppm 734 mg/m ³	Commission Directive (EU) 2017/164 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU
		Indicative		
		TWA	200 ppm 734 mg/m ³	UK. EH40 WEL - Workplace Exposure Limits
		STEL	400 ppm 1,468 mg/m ³	UK. EH40 WEL - Workplace Exposure Limits

Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Inhalation	Acute systemic effects	1468 mg/m ³
Workers	Inhalation	Acute local effects	1468 mg/m ³
Workers	Skin contact	Long-term systemic effects	63mg/kg BW/d
Workers	Inhalation	Long-term systemic effects	734 mg/m ³
Workers	Inhalation	Long-term local effects	734 mg/m ³
Consumers	Inhalation	Acute local effects, Acute systemic effects	734 mg/m ³
Consumers	Skin contact	Long-term systemic effects	37mg/kg BW/d

Consumers	Inhalation	Long-term systemic effects	367 mg/m ³
Consumers	Ingestion	Long-term systemic effects	4.5mg/kg BW/d
Consumers	Inhalation	Long-term local effects	367 mg/m ³

Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0.24 mg/kg
Sea water	0.026 mg/l
Fresh water	0.26 mg/l
Sea sediment	0.125 mg/kg
Fresh water sediment	1.25 mg/kg

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 120 min

Material tested: Butoject® (KCL 898)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|-------------------|---|
| a) Appearance | Form: clear, liquid
Color: colorless |
| b) Odor | No data available |
| c) Odor Threshold | No data available |

d) pH	No data available
e) Melting point/freezing point	Melting point/range: -84 °C
f) Initial boiling point and boiling range	76.5 - 77.5 °C
g) Flash point	-4 °C - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Lower explosion limit: 2.2 %(V)
k) Vapor pressure	No data available
l) Vapor density	No data available
m) Relative density	No data available
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	No data available
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Other decomposition products - No data available

Hazardous decomposition products formed under fire conditions. - Carbon oxides

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 5,620 mg/kg

Remarks: (RTECS)

LD50 Dermal - Rabbit - male - > 20,000 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks: (IUCLID)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: slight irritation

(OECD Test Guideline 405)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

UDS (Unscheduled DNA synthesis assay)

Escherichia coli

Result: negative

Ames test

Salmonella typhimurium

Result: negative

Chromosome aberration test in vitro

Chinese hamster ovary cells

Result: negative

OECD Test Guideline 474

Chinese hamster - male and female - Red blood cells (erythrocytes)

Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 92 Days - NOAEL (No observed adverse effect level) - 900 mg/kg - LOAEL (Lowest observed adverse effect level) - 3,600 mg/kg
RTECS: AH5425000

Inhalation of high concentrations may cause:, Headache, Drowsiness, Dizziness, Vomiting, narcosis, anemia, Central nervous system depression
To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 230 mg/l - 96 h (US-EPA)
Toxicity to algae	static test NOEC - Desmodesmus subspicatus (green algae) - > 100 mg/l - 72 h (OECD Test Guideline 201)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 20 d Result: ca.69 % - Readily biodegradable. Remarks: (ECHA)
Theoretical oxygen demand	1,820 mg/g Remarks: (Lit.)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local No mixing with other waste. Handle uncleaned containers like the product See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions. Notice Directive on waste 2008/98/EC.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1173

IMDG: 1173

IATA: 1173

14.2 UN proper shipping name

ADR/RID: ETHYL ACETATE

IMDG: ETHYL ACETATE

IATA: Ethyl acetate

14.3 Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA: 3

14.4 Packaging group

ADR/RID: II

IMDG: II

IATA: II

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Other regulations

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to

appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Annex: Exposure scenario

Identified uses:

Use: Manufacturing and on-site use

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
PC19: Intermediate
PROC1: Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC15: Use as laboratory reagent
ERC1: Manufacture of substances

Use: Formulation of preparations

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 10: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)
PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC15: Use as laboratory reagent
ERC2: Formulation of preparations

Use: Industrial use of processing aids in processes and products, not becoming part of articles

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
PC20: Products such as pH-regulators, flocculants, precipitants, neutralization agents
PC21: Laboratory chemicals
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC10: Roller application or brushing
PROC13: Treatment of articles by dipping and pouring
PROC15: Use as laboratory reagent
ERC4, ERC6b, ERC1: Industrial use of processing aids in processes and products, not

becoming part of articles, Industrial use of reactive processing aids, Manufacture of substances
--

Use: Used as laboratory reagent.

SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
--

SU 3, SU 22, SU24: Industrial uses: Uses of substances as such or in preparations at industrial sites, Professional uses: Public domain (administration, education, entertainment, services, craftsmen), Scientific research and development

PC21: Laboratory chemicals

PROC15: Use as laboratory reagent
--

ERC4, ERC8a: Industrial use of processing aids in processes and products, not becoming part of articles, Wide dispersive indoor use of processing aids in open systems

1. Short title of Exposure Scenario: Manufacturing and on-site use

Main User Groups	: SU 3
Sectors of end-use	: SU 3, SU9
Chemical product category	: PC19
Process categories	: PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9, PROC15
Environmental Release Categories	: ERC1:

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC1

Product characteristics

Concentration of the Substance in Mixture/Article	: Covers the percentage of the substance in the product up to 100 % (unless stated differently).
---	--

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9, PROC15, PC19

Product characteristics

Concentration of the Substance in Mixture/Article	: Covers the percentage of the substance in the product up to 100 % (unless stated differently).
---	--

Physical Form (at time of use)	: Medium volatile liquid
--------------------------------	--------------------------

Frequency and duration of use

Application duration	: > 4 h
Frequency of use	: 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor	: Indoor
------------------	----------

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source**Environment**

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC1	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	0.026 mg/m ³	0
PROC1	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.034 mg/kg BW/d	0.001
PROC2	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	1.371 mg/kg BW/d	0.022
PROC2	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	12.849 mg/m ³	0.018
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	25.699 mg/m ³	0.035
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.686 mg/kg BW/d	0.011
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.857 mg/kg BW/d	0.109
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	128.494 mg/m ³	0.175
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	13.714 mg/kg BW/d	0.218
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	64.247 mg/m ³	0.088
PROC9	ECETOC TRA	Without Local	Inhalation	128.494	0.175

		Exhaust Ventilation		mg/m ³	
PROC9	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.857 mg/kg BW/d	0.109
PROC15	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.343 mg/kg BW/d	0.005
PROC15	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	25.699 mg/m ³	0.035

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Formulation of preparations

Main User Groups : **SU 3**
 Sectors of end-use : **SU 10**
 Process categories : **PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9, PROC15**
 Environmental Release Categories : **ERC2:**

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC2

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9, PROC15

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : Medium volatile liquid

Frequency and duration of use

Application duration : > 4 h

Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC2	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	12.849 mg/m ³	0.018
PROC2	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	1.371 mg/kg BW/d	0.022
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	25.699 mg/m ³	0.035
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.686 mg/kg BW/d	0.011
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.857 mg/kg BW/d	0.109
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	128.494 mg/m ³	0.175
PROC5	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	13.714 mg/kg BW/d	0.218
PROC5	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	256.988 mg/m ³	0.35
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	13.714 mg/kg BW/d	0.218
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	64.247 mg/m ³	0.088
PROC9	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.857 mg/kg BW/d	0.109
PROC9	ECETOC TRA	Without Local	Inhalation	128.494	0.175

		Exhaust Ventilation		mg/m ³	
PROC15	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	25.699 mg/m ³	0.035
PROC15	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.343 mg/kg BW/d	0.005

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Industrial use of processing aids in processes and products, not becoming part of articles

Main User Groups : **SU 3**
 Sectors of end-use : **SU 3, SU9**
 Chemical product category : **PC20, PC21**
 Process categories : **PROC3, PROC4, PROC8b, PROC9, PROC10, PROC13, PROC15**
 Environmental Release Categories : **ERC4, ERC6b, ERC1:**

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC4, ERC6b, ERC1

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC3, PROC4, PROC8b, PROC9, PROC10, PROC13, PROC15, PC20, PC21

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : Medium volatile liquid

Frequency and duration of use

Application duration : > 4 h
 Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	25.699 mg/m ³	0.035
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.686 mg/kg BW/d	0.011
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	128.494 mg/m ³	0.175
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.857 mg/kg BW/d	0.109
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	64.247 mg/m ³	0.088
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	13.714 mg/kg BW/d	0.218
PROC9	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	128.494 mg/m ³	0.175
PROC9	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.857 mg/kg BW/d	0.109
PROC10	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	256.988 mg/m ³	0.35
PROC10	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	27.429 mg/kg BW/d	0.435
PROC13	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	13.714 mg/kg BW/d	0.218
PROC13	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	256.988 mg/m ³	0.35

PROC15	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	25.699 mg/m ³	0.035
PROC15	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.343 mg/kg BW/d	0.005

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Used as laboratory reagent.

Main User Groups : **SU 22**
 Sectors of end-use : **SU 3, SU 22, SU24**
 Chemical product category : **PC21**
 Process categories : **PROC15**
 Environmental Release Categories : **ERC4, ERC8a:**

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC4, ERC8a

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC15, PC21

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
 Physical Form (at time of use) : Medium volatile liquid

Frequency and duration of use

Application duration : > 4 h
 Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC15	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.343 mg/kg BW/d	0.005
PROC15	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	25.699 mg/m ³	0.035

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).