

# Comparison of semiconducting and superconducting hardware for optoelectronic neuromorphic systems

Bryce Primavera and Jeff Shainline

*National Institute of Standards and Technology  
325 Broadway, Boulder, CO, USA, 80305*

Thursday 28<sup>th</sup> May, 2020

## Abstract

## Contents

	<b>1</b>	<b>Introduction</b>
<b>1</b>	<b>2</b>	<b>Device requirements for neuromorphic systems</b>
<b>2</b>	<b>2</b>	<b>Light Sources</b>
<b>3</b>	<b>2</b>	<b>Detectors</b>
<b>4</b>	<b>2</b>	<b>Interconnection network and fan-out</b>
<b>5</b>	<b>2</b>	<b>Synaptic circuits and weighting</b>
<b>6</b>	<b>2</b>	<b>Dendrites and fan-in</b>
<b>7</b>	<b>2</b>	<b>Neural integration and threshold</b>
<b>8</b>	<b>2</b>	<b>Transmitter driver circuits</b>
<b>9</b>	<b>2</b>	<b>Time constants and subthreshold oscillations</b>
<b>10</b>	<b>2</b>	<b>Biasing</b>
<b>11</b>	<b>2</b>	<b>Power consumption, cooling, and system considerations</b>
<b>12</b>	<b>2</b>	<b>Acknowledgements</b>
<b>A</b>	<b>3</b>	<b>Appendix One</b>

# A Appendix One

Appendix One