

# Network Layer Part 4

Mark Allman mallman@case.edu

EECS 325/425 Fall 2018

"You work nine to five ...


And, somehow you survive ...
...'til the NIGHT"

These slides are more-or-less directly from the slide set developed by Jim Kurose and Keith Ross for their book "Computer Networking: A Top Down Approach, 5th edition".

The slides have been lightly adapted for Mark Allman's EECS 325/425 Computer Networks class at Case Western Reserve University.

All material copyright 1996-2010 J.F Kurose and K.W. Ross, All Rights Reserved

## Reading Along ...




- Network layer is chapters 4 & 5
  - IPv4 addressing

#### IP Addressing: introduction

- \*IP address: 32-bit identifier for host, router interface
- \*interface:
  - connection between host/router and physical link
    - router's typically have multiple interfaces
    - host typically has one interface
  - IP addresses
     associated with each
     interface


#### IP Addressing: introduction


- \*IP address: 32-bit identifier for host, router interface
- \*interface:
  - connection between host/router and physical link
    - router's typically have multiple interfaces
    - host typically has one interface
    - IP addresses
       associated with each
       interface



#### IP Addressing: introduction


- \*IP address: 32-bit identifier for host, router interface
- \*interface:
  - connection between host/router and physical link
    - router's typically have multiple interfaces
    - host typically has one interface
    - IP addresses
       associated with each
       interface





#### \*IP address:

- network part (high order bits)
- subnet part (middle bits)
- host part (low order bits)




#### \*IP address:

- network part (high order bits)
- subnet part (middle bits)
- host part (low order bits)

#### \*What's a subnet?


- device interfaces with same subnet part of IP address
- can physically reach each other without intervening router



network consisting of 3 subnets


#### Recipe


- to determine the subnets, detach each interface from its host or router, creating islands of isolated networks
- each isolated network is called a subnet.





223.1.3.0/24


Subnet mask: /24

















#### Classful Address Allocation

Class A: /8

0 netid subnet / hostid
-------------------------

16.7M addrs

Class B: /16

10	netid	subnet / hostid
----	-------	-----------------

64K addrs

Class C: /24

110 netid	subnet/hostid
-----------	---------------

256 addrs