



Network Security

Mark Allman

mark.allman@case.edu

EECS 325/425

*“The warden threw a party in the county jail,
The prison band was there and they began to wail”*

Network Security

Network Security

- Network opens a whole raft of security issues

Network Security

- Network opens a whole raft of security issues
- Highlights the disconnect between ...
 - ...the world in which the core technology was developed
 - ...the world that has emerged

Network Security

- Network opens a whole raft of security issues
- Highlights the disconnect between ...
 - ...the world in which the core technology was developed
 - ...the world that has emerged
- Security issues are part of the Internet's "success disaster"

“Drive By” Issues

“Drive By” Issues

- E.g., auth DNS servers lying + prefetching is an instance “drive by” issues
- I.e., if we can coax a client to access some host in some way that can be used as an attack vector

“Drive By” Issues

- E.g., auth DNS servers lying + prefetching is an instance “drive by” issues
- I.e., if we can coax a client to access some host in some way that can be used as an attack vector
- E.g., “drive by malware” distributed via mere web page visits

In The Eye of the Beholder...

In The Eye of the Beholder...

- Sometimes one activity is viewed as both ...
 - ... an attack
 - ... a legitimate business practice

In The Eye of the Beholder...

- Sometimes one activity is viewed as both ...
 - ... an attack
 - ... a legitimate business practice
- E.g., an RDNS re-writing error messages

In The Eye of the Beholder...

- Sometimes one activity is viewed as both ...
 - ... an attack
 - ... a legitimate business practice
- E.g., an RDNS re-writing error messages
- This is an example of a “tussle” in networks

Surveillance

- Watching network traffic can provide a fine-grain view into “private” activity
- Even “meta data”—such as DNS lookups—can provide a clear window into users’ activities

Surveillance

Surveillance

- How much is OK? How much is too much?

Surveillance

- How much is OK? How much is too much?
- By law, ISPs allowed to look at your traffic to engineer their network

Surveillance

- How much is OK? How much is too much?
- By law, ISPs allowed to look at your traffic to engineer their network
- By your agreement, Google can delve into your activity for their profit

Surveillance

- How much is OK? How much is too much?
- By law, ISPs allowed to look at your traffic to engineer their network
- By your agreement, Google can delve into your activity for their profit
- Drawing general lines is difficult ...
- ...yet, the lines we choose impacts how we develop and deploy technology

Surveillance

Surveillance

- What to do?

Surveillance

- What to do?
- IPsec
 - encrypt most of the IP layer and everything above

Surveillance

- What to do?
- IPsec
 - encrypt most of the IP layer and everything above
- TLS
 - encrypt application payload, but nothing below

Surveillance

- What to do?
- IPsec
 - encrypt most of the IP layer and everything above
- TLS
 - encrypt application payload, but nothing below
- VPN, anonymization networks (e.g., Tor)
 - tunnel traffic through untrusted networks to some trusted place

Interposing

Interposing

- DNS shows us that the Internet's core protocols that send information in clear text are susceptible to fraudulent forgery of all kinds
 - e.g., providing bogus answers to questions we don't like
 - e.g., entities that mimic the roots

Interposing

- DNS shows us that the Internet's core protocols that send information in clear text are susceptible to fraudulent forgery of all kinds
 - e.g., providing bogus answers to questions we don't like
 - e.g., entities that mimic the roots
- What to do?

Interposing

- DNS shows us that the Internet's core protocols that send information in clear text are susceptible to fraudulent forgery of all kinds
 - e.g., providing bogus answers to questions we don't like
 - e.g., entities that mimic the roots
- What to do?
 - sign and/or encrypt

Cache Poisoning

Cache Poisoning

- Inserting a fraudulent entry into a cache
- Doesn't directly attack a particular transaction
- But, aims to plant a trap of sorts for all subsequent transactions

Cache Poisoning

- Inserting a fraudulent entry into a cache
- Doesn't directly attack a particular transaction
- But, aims to plant a trap of sorts for all subsequent transactions
- What to do?

Cache Poisoning

- Inserting a fraudulent entry into a cache
 - Doesn't directly attack a particular transaction
 - But, aims to plant a trap of sorts for all subsequent transactions
-
- What to do?
 - sign and/or encrypt

Spooofing

Spooofing

- In TCP/IP, the devices themselves identify themselves in packets by setting the source address

Spoofing

- In TCP/IP, the devices themselves identify themselves in packets by setting the source address
- Therefore, nothing prevents a device from setting the source IP fraudulently
 - in general, this doesn't work as the host will not see the return traffic
 - in attacks, this may not matter or *may be the point!*

Preventing Spoofing

Preventing Spoofing

- What to do?


Preventing Spoofing

- What to do?
- Ingress / egress filtering
- Solution requires wide-scale buy-in

Preventing Spoofing

- What to do?
- Ingress / egress filtering
- Solution requires wide-scale buy-in
- Incentives are less-than-ideal
 - “I get nothing if I deploy”
 - “I get something if everyone else deploys”

Is Spoofing Possible?



CAIDA's Spoofer Project

Reflection

Reflection


- Coaxing a third-party to transmit traffic to a victim
 - to hide identity
 - to circumvent policy

Amplification


Amplification

- Reflection is often coupled with amplification
- I.e., with a small request we can coax a reflector to send a larger response to a victim


DNS Amplification



DNS Amplification



DNS Amplification



Denial-of-Service

Denial-of-Service

- Use a resource so someone else can't

DDoS

DDoS

- Distributed Denial-of-Service

DDoS

- Distributed Denial-of-Service
- Leverage a large number of hosts around the network to use resources
- can more effectively use more resources, so the more hosts an attacker controls the larger the attack can be

DDoS

- Distributed Denial-of-Service
- Leverage a large number of hosts around the network to use resources
 - can more effectively use more resources, so the more hosts an attacker controls the larger the attack can be
 - “botnets”

DDoS

- What to do?
 - (ugh)

DDoS

- Often about using capacity so legitimate transactions get squeezed out
 - i.e., just no room left

DDoS

DDoS

- But, we don't need a firehose to cause problems

DDoS

- But, we don't need a firehose to cause problems
- E.g., consider a TCP connections

DDoS

- But, we don't need a firehose to cause problems
- E.g., consider a TCP connections
 - originator starts a TCP connection by sending a SYN

DDoS

- But, we don't need a firehose to cause problems
- E.g., consider a TCP connections
 - originator starts a TCP connection by sending a SYN
 - recipient instantiates state upon receipt
 - track window size, sequence numbers, packet buffer, etc.
 - i.e., recipient *allocates resources*

DDoS

DDoS

- What if an attacker sent tons of SYNs, but then stopped transmitting?
 - i.e., no legit connection
 - can be combined with spoofing

DDoS

- What if an attacker sent tons of SYNs, but then stopped transmitting?
 - i.e., no legit connection
 - can be combined with spoofing
- The attacker would consume host resources that could not be used for legit traffic

DDoS

- What if an attacker sent tons of SYNs, but then stopped transmitting?
 - i.e., no legit connection
 - can be combined with spoofing
- The attacker would consume host resources that could not be used for legit traffic
- Called a “SYN flood”

DDoS

DDoS

- What to do about a SYN flood?

DDoS

- What to do about a SYN flood?
- Timeouts
 - “SYN caches”
- “SYN cookies”

DDoS

DDoS

- SYN cookies

DDoS

- SYN cookies
 - do not instantiate state upon SYN arrival

DDoS

- SYN cookies
 - do not instantiate state upon SYN arrival
 - carefully craft the recipient's initial seqno returned in the SYN+ACK
 - e.g., as the hash of the ISN in the SYN and a secret

DDoS

- SYN cookies
 - do not instantiate state upon SYN arrival
 - carefully craft the recipient's initial seqno returned in the SYN+ACK
 - e.g., as the hash of the ISN in the SYN and a secret
 - when the ACK of the SYN+ACK arrives, it can be validated as being legit ...
 - ... and now we instantiate state

DDoS

DDoS

- SYN cookie disadvantage:

DDoS

- SYN cookie disadvantage:
 - can't encode everything in the ISN
 - e.g., the window scale factor is given in the SYN and then never again
 - e.g., often can't deal with TCP options

Security Mitigations

Security Mitigations

- Good hygiene
 - keep software up-to-date
- Anti-virus scanners

Security Mitigations

- Good hygiene
 - keep software up-to-date
- Anti-virus scanners
- Firewalls / access control lists
 - limit who can access a particular service
 - host-based & network-based

Security Mitigations

Security Mitigations

- Intrusion Detection Systems (IDS)
 - monitor network for suspicious traffic
 - flag for analyst

Security Mitigations

- Intrusion Detection Systems (IDS)
 - monitor network for suspicious traffic
 - flag for analyst
- Intrusion Prevention System
 - hybrid of firewalls and IDS
 - i.e., monitor traffic and automatically initiate blocking of suspicious traffic

Security

- Just the tip of the iceberg ...
- These are some of the most thorny problems we face
- ...and oftentimes because they boil down to *policy issues*