

Transport Layer Part 4

Mark Allman mallman@case.edu

Fall 2018


"Got my 45 on ...
...so I ...
... can rock on"


These slides are more-or-less directly from the slide set developed by Jim Kurose and Keith Ross for their book "Computer Networking: A Top Down Approach, 5th edition".

The slides have been lightly adapted for Mark Allman's EECS 325/425 Computer Networks class at Case Western Reserve University.


All material copyright 1996-2010 J.F Kurose and K.W. Ross, All Rights Reserved







Reading Along ...




 3.5: Connectionoriented transport: TCP

- point-to-point:
 - one sender, one receiver


- point-to-point:
 - one sender, one receiver
- *reliable, in-order byte stream:
 - no "message boundaries"

- point-to-point:
 - one sender, one receiver
- *reliable, in-order byte stream:
 - no "message boundaries"
- * pipelined:
 - TCP congestion and flow control set window size

- point-to-point:
 - one sender, one receiver
- *reliable, in-order byte stream:
 - no "message boundaries"
- * pipelined:
 - TCP congestion and flow control set window size
- *send & receive buffers




- point-to-point:
 - one sender, one receiver
- *reliable, in-order byte stream:
 - no "message boundaries"
- * pipelined:
 - TCP congestion and flow control set window size
- * send & receive buffers



*full duplex data:

 bi-directional data flow in same connection

- point-to-point:
 - one sender, one receiver
- *reliable, in-order byte stream:
 - no "message boundaries"
- * pipelined:
 - TCP congestion and flow control set window size
- * send & receive buffers




*full duplex data:

 bi-directional data flow in same connection

* connection-oriented:

 handshaking inits sender, receiver state before data exchange

- point-to-point:
 - one sender, one receiver
- *reliable, in-order byte stream:
 - no "message boundaries"
- * pipelined:
 - TCP congestion and flow control set window size
- * send & receive buffers



*full duplex data:

 bi-directional data flow in same connection


* connection-oriented:

 handshaking inits sender, receiver state before data exchange

*congestion controlled:

- won't overwhelm network
- (tackle later in semester)

- point-to-point:
 - one sender, one receiver
- *reliable, in-order byte stream:
 - no "message boundaries"
- * pipelined:
 - TCP congestion and flow control set window size
- * send & receive buffers



*full duplex data:

 bi-directional data flow in same connection

* connection-oriented:

 handshaking inits sender, receiver state before data exchange

*congestion controlled:

- won't overwhelm network
- (tackle later in semester)

*flow controlled:

won't overwhelm receiver

- point-to-point:
 - one sender, one receiver
- *reliable, in-order byte stream:
 - no "message boundaries"
- * pipelined:
 - TCP congestion and flow control set window size
- *send & receive buffers



RFCs: 793, 1122, 1323, 2018, 2883, 3042, 3390, 5681, 6298, 6675, etc

*full duplex data:

 bi-directional data flow in same connection

* connection-oriented:

 handshaking inits sender, receiver state before data exchange


*congestion controlled:

- won't overwhelm network
- (tackle later in semester)

*flow controlled:


won't overwhelm receiver


Reading Along ...





- 3.5: Connectionoriented transport: TCP
 - segment structure


olt _	0	1	2	3	4	5	6	7	8	9	10	11	12	13	1	4	15	16	17	18	19	20	21	22	!	23	24	25	26	27	28	29	30	31
			Source Port Destination														ion	Por	t															
Sequence Number																																		
	Acknowledgement Number																																	
		HLEN Reserved U A P R S F V I Wind												dow	/																			
			Checksum														Urgent Pointer																	
8 8	Options (if any)														Padding																			
																	Da	ata																
																		<u>.</u>																






























olt _	0 1 2	3 4	5 6	7	8 9	10	11	12	13	3	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
	Source Port														Destination Port													
I	Sequence Number																											
	Acknowledgement Number																											
	HLEN	HLEN Reserved U A P R S F C S S Y I G K H T N N												VVindow														
		Checksum														Urgent Pointer												
5 60	Options (if any)														Padding													
												Da	ita															







olt _	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
		Source Port																			Des	stina	tion	Por	t							
		Sequence Number																														
		Acknowledgement Number																														
		HLEN Reserved U A P R S F R C S S Y I G K H T N N													Window																	
		Checksum															Urgent Pointer															
		Options (if any)																								Pa	dding	1				
																D	ata															
																100																



Seq. #'s:

byte stream "number" of first byte in segment's data

Seq. #'s:

byte stream "number" of first byte in segment's data

ACKs:

- seq # of next byte expected from other side
- cumulative ACK

<u>Seq. #'s:</u>

byte stream "number" of first byte in segment's data

ACKs:

- seq # of next byte expected from other side
- cumulative ACK
- Q: how receiver handles outof-order segments

Seq. #'s:

byte stream "number" of first byte in segment's data

ACKs:


- seq # of next byte expected from other side
- cumulative ACK
- Q: how receiver handles outof-order segments
 - A: TCP spec doesn't say, - up to implementor

Seq. #'s:

byte stream "number" of first byte in segment's data



Host A



ACKs:

- seq # of next byte expected from other side
- cumulative ACK
- Q: how receiver handles outof-order segments
 - A: TCP spec doesn't say, - up to implementor

simple telnet scenario

time

Seq. #'s:


byte stream "number" of first byte in segment's data



User

types

Host A



ACKs:

- seq # of next byte expected from other side
- cumulative ACK
- Q: how receiver handles outof-order segments
 - A: TCP spec doesn't say, - up to implementor

simple telnet scenario


time

Seq. #'s:

byte stream "number" of first byte in segment's data



Host A



User types 'C'

ACKs:

- seq # of next byte expected from other side
- cumulative ACK
- Q: how receiver handles outof-order segments
 - A: TCP spec doesn't say, up to implementor

simple telnet scenario


time

Seq. #'s:

byte stream "number" of first byte in segment's data



Host A



User types 'C' Seq=42, ACK=79, data = 'C'

ACKs:

- seq # of next byte expected from other side
- cumulative ACK
- Q: how receiver handles outof-order segments
 - A: TCP spec doesn't say, up to implementor


host ACKs receipt of 'C', echoes back 'C'

Seq. #'s:

byte stream "number" of first byte in segment's data



Host A



User types 'C' Seq=42, ACK=79, data = 'C'

Seq=79, ACK=43, data = 'C'

host ACKs receipt of 'C', echoes back 'C'

ACKs:

- seq # of next byte expected from other side
- cumulative ACK
- Q: how receiver handles outof-order segments
 - A: TCP spec doesn't say, - up to implementor

Seq. #'s:

byte stream "number" of first byte in segment's data



Host A

Host B

User types 'C' $S_{eq=42, ACK=79, data = 'C'}$

Seq=79, ACK=43, data = 'C'

ACKs:

- seq # of next byte expected from other side
- cumulative ACK
- Q: how receiver handles outof-order segments
 - A: TCP spec doesn't say, - up to implementor

host ACKs receipt of echoed host ACKs receipt of 'C', echoes back 'C'


<u>Seq. #'s:</u>

byte stream "number" of first byte in segment's data



of echoed

Host A



host ACKs

receipt of

'C', echoes

back 'C'

User types 'C'


 $S_{eq=42, ACK=79, data = 'C'}$

ACKs:

- seq # of next byte expected from other side
- cumulative ACK
- Q: how receiver handles outof-order segments
 - A: TCP spec doesn't say, - up to implementor

Seq=79, ACK=43, data = 'C' host ACKs Seq=43, ACK=80 receipt

Reading Along ...



- 3.5: Connectionoriented transport: TCP
 - connection management

Recall: TCP sender, receiver establish "connection" before exchanging data segments

- *initialize TCP variables:
 - seq. #s
 - buffers, flow control info (e.g. RcvWindow)
 - etc.

Recall: TCP sender, receiver establish "connection" before exchanging data segments

- *initialize TCP variables:
 - seq. #s
 - buffers, flow control info (e.g. RcvWindow)
 - etc.

Three way handshake:

Recall: TCP sender, receiver establish "connection" before exchanging data segments

- *initialize TCP variables:
 - seq. #s
 - buffers, flow control info (e.g. RcvWindow)
 - etc.

Three way handshake:

Step 1: client host sends TCP SYN segment to server

- specifies initial seq #
- no data

Recall: TCP sender, receiver establish "connection" before exchanging data segments

- *initialize TCP variables:
 - seq. #s
 - buffers, flow control info (e.g. RcvWindow)
 - etc.

Three way handshake:

Step 1: client host sends TCP
SYN segment to server

- specifies initial seq #
- no data

Step 2: server host receives SYN, replies with SYNACK segment

- server allocates buffers
- specifies server initial seq. #

Recall: TCP sender, receiver establish "connection" before exchanging data segments

- *initialize TCP variables:
 - seq. #s
 - buffers, flow control info (e.g. RcvWindow)
 - etc.

Three way handshake:

- Step 1: client host sends TCP SYN segment to server
 - specifies initial seq #
 - no data
- Step 2: server host receives SYN, replies with SYNACK segment
 - server allocates buffers
 - specifies server initial seq. #
- Step 3: client receives SYNACK, replies with ACK segment, which may contain data

Closing a connection:

Closing a connection:

```
client closes socket:
   close(sd);
```

Closing a connection:

```
client closes socket:
   close(sd);
```

Step 1: client end system sends TCP FIN control segment to server

Closing a connection:

```
client closes socket:
   close(sd);
```

Step 1: client end system sends TCP FIN control segment to server


Step 2: server receives FIN, replies with ACK. Closes connection, sends FIN.


Closing a connection:

client closes socket:
 close(sd);

Step 1: client end system sends TCP FIN control segment to server


Step 2: server receives FIN, replies with ACK. Closes connection, sends FIN.





Step 3: client receives FIN, replies with ACK.


Enters "timed wait" will respond with ACK to received FINs





Step 3: client receives FIN, replies with ACK.

Enters "timed wait" will respond with ACK to received FINs


Step 4: server, receives ACK. Connection closed.







Reading Along ...



- 3.5: Connectionoriented transport: TCP
 - timeouts

*Q: How to set TCP timeout value?

- *Q: How to set TCP timeout value?
 - longer than RTT ...

- *Q: How to set TCP timeout value?
 - longer than RTT ...
 - ... but RTT varies

Measured RTTs

*ping measurements from eecslab-5

Measured RTTs

*ping measurements from eecslab-5

Remote Host

RTT (msec)

Remote Host	RTT (msec)
eecslab-6.case.edu	0.5

Remote Host	RTT (msec)
eecslab-6.case.edu	0.5
www.ohiou.edu	7.9

Remote Host	RTT (msec)
eecslab-6.case.edu	0.5
www.ohiou.edu	7.9
www.icir.org	71

Remote Host	RTT (msec)
eecslab-6.case.edu	0.5
www.ohiou.edu	7.9
www.icir.org	71
www.iij.ad.jp	171

- *Q: How to set TCP timeout value?
 - longer than RTT ...
 - ... but RTT varies

- *Q: How to set TCP timeout value?
 - longer than RTT ...
 - but RTT varies
- *Q: What if we set the timeout too short?

- *Q: How to set TCP timeout value?
 - longer than RTT ...
 - but RTT varies
- *Q: What if we set the timeout too short?
 - premature timeout
 - unnecessary retransmissions

- *Q: How to set TCP timeout value?
 - longer than RTT ...
 - but RTT varies
- *Q: What if we set the timeout too short?
 - premature timeout
 - unnecessary retransmissions
- *Q: What if we set the timeout too long?

- *Q: How to set TCP timeout value?
 - longer than RTT ...
 - but RTT varies
- *Q: What if we set the timeout too short?
 - premature timeout
 - unnecessary retransmissions
- *Q: What if we set the timeout too long?
 - slow reaction to loss

*Q: How do we estimate the RTT?

- *Q: How do we estimate the RTT?
 - measure time between data transmission and ACK

- *Q: How do we estimate the RTT?
 - measure time between data transmission and ACK
 - do not time retransmissions
 - (Karn/Partridge algorithm)

- *Q: How do we estimate the RTT?
 - measure time between data transmission and ACK
 - do not time retransmissions
 - (Karn/Partridge algorithm)
- *RTT will vary across measurements

- *Q: How do we estimate the RTT?
 - measure time between data transmission and ACK
 - do not time retransmissions
 - (Karn/Partridge algorithm)
- *RTT will vary across measurements
 - want something smoother
 - instead of just the current RTT, use an average of the last few measurements
 - the "smoothed RTT" (SRTT)


* RFC 6298

$$SRTT = (1-\alpha)*SRTT + \alpha*R$$

- * Exponential weighted moving average
- influence of past sample decreases exponentially fast
- * standard value: $\alpha = 0.125$

Example SRTT Computation





Setting the timeout

- * SRTT plus "safety margin"
 - large variation in SRTT -> larger safety margin

Setting the timeout

- * SRTT plus "safety margin"
 - large variation in SRTT -> larger safety margin
- * first, estimate of how much SRTT deviates from the RTT sample:

Setting the timeout

- * SRTT plus "safety margin"
 - large variation in SRTT -> larger safety margin
- * first, estimate of how much SRTT deviates from the RTT sample:

```
RTTVAR = (1-\beta)*RTTVAR + \beta*|R-SRTT|
(\beta = 0.25, per standard)
```

Setting the timeout


- * SRTT plus "safety margin"
 - large variation in SRTT -> larger safety margin
- * first, estimate of how much SRTT deviates from the RTT sample:


RTTVAR =
$$(1-\beta)$$
*RTTVAR + β *|R-SRTT|
(β = 0.25, per standard)

Then set timeout interval:

$$RTO = SRTT + 4*RTTVAR$$

Example RTO Computation





*But, one issue remains ...

- *But, one issue remains ...
 - where do we start?!

- *But, one issue remains ...
 - where do we start?!

- *RFC 1122, RFC 2988 specify 3 seconds
 - why?

- *But, one issue remains ...
 - where do we start?!

- *RFC 1122, RFC 2988 specify 3 seconds
 - why?

*RFC 1122 published in 1989. RFC 2988 published in 2000.

- *But, one issue remains ...
 - where do we start?!

- *RFC 1122, RFC 2988 specify 3 seconds
 - why?

- *RFC 1122 published in 1989. RFC 2988 published in 2000.
 - does this constant still apply?



- Matt Sargent
- *Case PhD, 2015



- Matt Sargent
- *Case PhD, 2015

*Hypothesizes that an initial RTO developed in 1989 might not be appropriate anymore

*Conducts an empirical investigation

*How do we choose?

- *How do we choose?
 - look at some data!
 - investigated eight datasets (spanning 6 years)
 - datasets are packet traces!

- *How do we choose?
 - look at some data!
 - investigated eight datasets (spanning 6 years)
 - datasets are packet traces!
- *Lowering the InitRTO from 3 seconds to 1 second has cost:
 - less than 0.1% of the connections spuriously retransmit the SYN in most datasets
 - 1.1% of the connections in a wireless network spuriously retransmit the SYN

- *Connections experience performance boost when SYN is lost and requires retransmission
 - *i.e., connections only wait for 1sec when previously waited 3sec

- *Connections experience performance boost when SYN is lost and requires retransmission
 - *i.e., connections only wait for 1sec when previously waited 3sec

- *Connections realizing >= 10% boost:
 - 10-43% (across datasets)
- *Connections realizing >= 50% boost:
 - 17-73% (across datasets)

*The IETF decided that Matt's evidence was compelling

- *The initial RTO was lowered from 3sec to 1sec
 - specified in RFC 6298

*Details of Matt's investigation are given in appendix of RFC 6298

*One more thing ...

*What if we retransmit and the resent segment is dropped?

*One more thing ...

- *What if we retransmit and the resent segment is dropped?
 - backoff the RTO
 - RTO *= 2
 - (similar to collision backoff in Ethernet)

*Part of TCP's congestion control mechanism

Magic Numbers

Magic Numbers

- *Where do the constants in the RTO mechanism come from?
 - e.g., alpha = 0.125
 - e.g., initRTO = 1sec
 - e.g., we multiple RTTVAR by 4

Magic Numbers

- *Where do the constants in the RTO mechanism come from?
 - e.g., alpha = 0.125
 - e.g., initRTO = 1sec
 - e.g., we multiple RTTVAR by 4

- *Rough consensus ...
 - but, it still stinks
 - we strive for mechanisms that do not require magic constants