

Malware Analysis Tools and Techniques

Jan Arends

Hochschule Bonn-Rhein-Sieg

11. Jan 2018



Overview

① Introduction

Why

Goals

Save environment

Overview

① Introduction

- Why

- Goals

- Save environment

② Static Analysis

- File Identification

- Embedded Artifact Extraction

- Code Reversing

Overview

① Introduction

- Why

- Goals

- Save environment

② Static Analysis

- File Identification

- Embedded Artifact Extraction

- Code Reversing

③ Dynamic Analysis

- Monitoring

- Memory forensics

- Debugging

Overview

① Introduction

- Why

- Goals

- Save environment

② Static Analysis

- File Identification

- Embedded Artifact Extraction

- Code Reversing

③ Dynamic Analysis

- Monitoring

- Memory forensics

- Debugging

④ Conclusion

Why

Motivation

- Number of malware is still growing
- Malware is getting more complex
- Analysing is important because for
 - Recovery
 - Defeating
 - Eliminating
 - Detection

Goals

To answer questions like ...

- Nature and purpose of the program
- What type of malware is it?
- What is the intended purpose and how does it accomplish it?
- What is the functionality and capability?
- What affect does it have on the system?
- How does is spread?

Overview




Figure: Stages of Malware Analysis

Overview




Figure: Stages of Malware Analysis

Lab

Safety first

- Potentially damaging code
- Safe and secure lab environment
- Place the file on an isolated or sandboxed system
- Ensure that the code is contained
- Unable to connect to or otherwise affect any production system

① Introduction

Why

Goals

Save environment

② Static Analysis

File Identification

File Formats

Fingerprint

Obfuscation

Embedded Artifact Extraction

Code Reversing

③ Dynamic Analysis

Monitoring

Memory forensics

Debugging

④ Conclusion

Formats

- Have to be identified for proper analysis
- File signatures are used
- File identification tool or binary artifacts

Examples

- Portable Executable (PE)
- Executable and Linkable Format (ELF)
- Mach-O

Fingerprint

- Hash value for identification
- MD5 or SHA-1
- Malware might already be explored
- Antivirus scanning: Useful first Step

Tool

VirusTotal

Obfuscation

- Code is converted to a different version
- Semantic equivalence
- Different fingerprint
- Example techniques:
 - Junk code insertion
 - Pattern-based obfuscation
 - Stack-based obfuscation
 - ...

Wrapper




Figure: Typical packing and unpacking process [1]

① Introduction

Why

Goals

Save environment

② Static Analysis

File Identification

Embedded Artifact Extraction

Strings

Dependencies

Symbols

Metadata

Code Reversing

③ Dynamic Analysis

Monitoring

Memory forensics

Debugging

④ Conclusion

Vorbereitung I




Figure: Creation of an executable

Vorbereitung II

Linux	<ul style="list-style-type: none">- GNU C Library manual- The Open Group index of functions- Linux man-pages
Windows	<ul style="list-style-type: none">- Windows API reference- Microsoft DLL Help Database- TechNet Library

Table: Web references

Strings

Infos embedded in binary as ASCII or Unicode format

- Calls to functions, shared libraries and APIs
- Error messages and Comments
- Network information
- IRC Channels and C&C Server
- Directory and file names
- Compiler and versions

Tool

Strings

Dependencies I

- Identifying within the string search is a good starting point
- Additional research
- Good guess about behavior
- Actually called functions can be explored

Tool

- Windows: Dependency Walker
- Unix/Linux: ldd

Dependencies Tool Beispiel

Dependency Walker - [Stooges.exe]

File Edit View Options Profile Window Help

STOOGES.EXE

- LARRY.DLL
- KERNEL32.DLL
- NTDLL.DLL
- NTDLL.DLL
- CURLY.DLL
- SHEMP.DLL
- MOE.DLL
- KERNEL32.DLL
- NTDLL.DLL

Pi^	Ordinal	Hint	Function	Entry Point
	N/A	N/A	IsKnucklehead	Not Bound
	N/A	N/A	int SaySoitenly(char *,...)	Not Bound

E^	Ordinal	Hint	Function	Entry Point
4 (0x0004)	1 (0x0001)		int SaySoitenly(char *,...)	SHEMP.?SaySoitenly@@YAHP/
5 (0x0005)	2 (0x0002)		DoinkLarrysEye	0x00001010
3 (0x0003)	0 (0x0000)		void SayPoirectf(_int64)	0x00001020
1 (0x0001)	N/A		N/A	0x00001020
2 (0x0002)	3 (0x0003)		DoinkMoesEye	SHEMP.DoinkMoesEye

Module ^	File Time Stamp	Link Time Stamp	File Size	Attr.	Link Checksum	Real Checksum	CPU	Subsyste ^
CURLY.DLL	11/14/2006 5:17p	11/14/2006 5:13p	2,560	A	0x0000F739	0x0000F759	x86	GUI
KERNEL32.DLL	08/30/2006 1:22a	08/30/2006 1:20a	871,424	A	0x0000E388	0x0000E388	x86	Console
LARRY.DLL	11/14/2006 5:13p	11/14/2006 5:13p	2,560	A	0x000053DB	0x000053DB	x86	GUI
MOE.DLL	11/14/2006 5:15p	11/14/2006 5:15p	2,560	A	0x0000B191	0x0000B191	x86	GUI
NTDLL.DLL	08/30/2006 1:23a	08/30/2006 1:21a	1,147,664	A	0x00125FA5	0x00125FA5	x86	Console
SHEMP.DLL	11/14/2006 5:13p	11/14/2006 5:13p	2,560	A	0x00001CE7	0x00001CE7	x86	GUI

00:00:00.093: LoadLibraryA("Moe.dll") called from "STOOGES.EXE" at address 0x00401024 by thread 1.

00:00:00.093: Loaded "MOE.DLL" at address 0x00020000 by thread 1. Successfully hooked module.

00:00:00.093: DllMain(0x00020000, DLL_PROCESS_ATTACH, 0x00000000) in "MOE.DLL" called by thread 1.

00:00:00.093: DllMain(0x00020000, DLL_PROCESS_ATTACH, 0x00000000) in "MOE.DLL" returned 1 (0x1) by thread 1.

00:00:00.093: LoadLibraryA("Moe.dll") returned 0x00020000 by thread 1.

00:00:00.109: GetProcAddress(0x00020000 [MOE.DLL], "SmackCurly") called from "STOOGES.EXE" at address 0x0040102B and returne

For Help, press F1

Symbols

- Stored in a symbol table
- Identifiers for program variables and functions
- Variable names, addresses, data types and scopes
- Structure and class definitions

Requieres

Author didn't discarded the symbol information

Tool

- Windows: DUMPBIN
- Unix/Linux: `eu-nm`

Metadata

- Plant during the creation of an executable
- Can be generated from various parts of the file structure
- Information about the origin, ownership, and history
- Timestamps, location and previous file names

① Introduction

Why

Goals

Save environment

② Static Analysis

File Identification

Embedded Artifact Extraction

Code Reversing

Disassembly

Decompiled code

③ Dynamic Analysis

Monitoring

Memory forensics

Debugging

④ Conclusion




Figure: Creation of an executable




Figure: Creation of an executable




Figure: Creation of an executable

Disassembly

- Disassembler: Recovers a low-level language code
- Human-readable version of a computer architecture's instruction set
- Reliably and consistently
- Instructions: One-to-many relationship
- Analyzing instructions as groups

Tool

IDA (Interactive Disassembler) von Hey-Rays

Example

```
1  int i;  
2  for(i=0; i<100; i++) {  
3      printf("i equals %d\n", i);  
4  }
```

Listing 1: For-loop written in C

```
1  00401004      mov     [ebp+var_4], 0  
2  0040100B      jmp     short loc_401016  
3  0040100D loc_40100D:  
4  0040100D      mov     eax, [ebp+var_4]  
5  00401010      add     eax, 1  
6  00401013      mov     [ebp+var_4], eax  
7  00401016 loc_401016:  
8  00401016      cmp     [ebp+var_4], 64h  
9  0040101A      jge     short loc_40102F  
10 0040101C      mov     ecx, [ebp+var_4]  
11 0040101F      push    ecx  
12 00401020      push    offset a1D ; "i equals %d\n"  
13 00401025      call    printf  
14 0040102A      add     esp, 8  
15 0040102D      jmp     short loc_40100D
```

Listing 2: Assembly code for the for loop example above




Figure: Graph view for the for loop example above

Decompiled code

- Decompiler: Recovers high-level form of code
- Abstractions and structures inclusive
- Research topic

Major improvements in 2016 and 2017

- Goto-free DREAM and extended version DREAM⁺⁺
- Retargetable Decompiler RetDec by Avast

Beispiel

```

1  void __cdecl sub_10006390() {
2      __int32 v13; // eax@14
3      int v14; // esi@15
4      unsigned int v15; // ecx@15
5      int v16; // edx@16
6      char *v17; // edi@18
7      bool v18; // zf@18
8      unsigned int v19; // edx@18
9      char v20; // di@21
10     char v23; // [sp+0h] [bp-38h]@1
11     int v30; // [sp+30Ch] [bp-1Ch]@1
12     __int32 v36; // [sp+324h] [bp-3h]@14
13     int v37; // [sp+328h] [bp-1h]@1
14     int i; // [sp+330h] [bp-1h]@1
15     // [...]
16     v30 = *qwrtpsdfghjklzxcvbnm";
17     v37 = *"eyuloa";
18     // [...]
19     v14 = 0;
20     v15 = 3;
21     if ( v13 > 0 )
22     {
23         v16 = 1 - &v23;
24         for ( i = 1 - &v23; ; v16 = i )
25         {
26             v17 = &v23 + v14;
27             v19 = (&v23 + v14 + v16) & 0x80000001;
28             v18 = v19 == 0;
29             if ( (v19 & 0x80000000) != 0 )
30                 v18 = ((v19 - 1) | 0xFFFFFFFF) == -1;
31             v20 = v18 ? *(&v37 + dwSeed / v15 % 6)
32                     : *(&v30 + dwSeed / v15 % 0x14);
33             ++v14;
34             v15 += 2;
35             *v17 = v20;
36             if ( v14 >= v36 )
37                 break;
38         }
39     }
40     // [...]
41 }

```

Listing 3: Hey-Rays

Beispiel Fortsetzung

```

1  LPVOID sub_100063900{
2      int v1 = *qwrtpsdfghklzxcvbnm";
3      int v2 = *eyuioa";
4      // [...]
5      int v18 = 0;
6      int v19 = 3;
7      if(num > 0){
8          do{
9              char *v20 = v18 + (&v3);
10             int v21 = v18 + 1;
11             int v22 = v21;
12             int v23 = v21 & 0x800000001L;
13             bool v24 = !v23;
14             if(v23 < 0)
15                 v24 = !(((v23 - 1) | 0xffffffffL) + 1);
16             char v25;
17             if(!v24)
18                 v25 = *(((dwSeed / v19) % 20) + (&v1));
19             else
20                 v25 = *(((dwSeed / v19) % 6) + (&v2));
21             v18++;
22             v19 += 2;
23             *v20 = v25;
24         }while(v18 < num);
25     }
26     // [...]
27 }

```

Listing 4: Dream

```

1  LPVOID sub_100063900{
2      char *v1 = "qwrtpsdfghklzxcvbnm";
3      char *v2 = "eyuioa";
4      // [...]
5      int v13 = 3;
6      for(int i = 0; i < num; i++){
7          char v14 = i % 2 == 0 ? v1[(dwSeed / v13) % 20]
8              : v2[(dwSeed / v13) % 6];
9          v13 += 2;
10         v3[i] = v14;
11     }
12     // [...]
13 }

```

Listing 5: Dream++

Dynamic Analysis

Intro

- Running the malware
- Observing its behavior
- Overcomes anti static techniques
- Anti techniques exists:
 - Monitoring Detection
 - VM detection
 - Memory capturing detection

① Introduction

Why

Goals

Save environment

② Static Analysis

File Identification

Embedded Artifact Extraction

Code Reversing

③ Dynamic Analysis

Monitoring

Processes

System & API calls

File system & Registry

Network

Memory forensics

Debugging

④ Conclusion

Monitoring

Basic actions

- File Actions = $\{Create, Delete, Read, Write, Rename\}$
- Process Actions = $\{Create, Terminate\}$
- Network Actions = $\{TCP, UDP, IP\} \oplus$
 $\{Listen, Connect, Send, Recv\}$
- Registry Actions = $\{OpenKey, CloseKey, CreateKey\} \wedge$
 $\{SetValue, DeleteValue, QueryValue\}$

Processes

- Program in execution
- Explore all the processes related to the malware
- Which are running, created or terminated
- Loaded shared libraries

Tools

Windows: Process Monitor

Linux: htop

System & API calls

- Provided by the operating system
- Low level communications only via system calls, e.g.
 - File system interactions
 - Network functionality
- Tracking of parameters and return values
- great chance to get further knowledge
- Conformation of founded calls in string search

File system & Registry

- Used for persistence or configuration data
- Malware often uses the Windows registry
- Snapshot comparison

Tools

Regshot

Network

- Malware often requires internet access
- Additional components must be downloaded
- Capture packages in simulated network
- Analyzing packages, filter suspicious connections
- Reverse-engineering of the protocol
- Exploration of downloaded files

Tools

- Wireshark
- tcpdump
- Bro

① Introduction

Why

Goals

Save environment

② Static Analysis

File Identification

Embedded Artifact Extraction

Code Reversing

③ Dynamic Analysis

Monitoring

Memory forensics

Acquisition

Analysis

Debugging

④ Conclusion

Memory forensics

- Visibility into the runtime state of the system
- Full reconstruction of events
- Every action end up in specific modifications in RAM
- Actions performed can persist a long time after it was taken

Acquisition

- Process of copying the contents of volatile memory to non-volatile storage
- Happens in controlled environment (Lab)
- How: capturing, dumping or sampling
- When:
 - Terminating-Based
 - Interval-Based
 - Trigger-Based

Analysis

- Happens on another environment "offline"
- No API calls → unallocated or hidden data can be seen
- Visibility into the runtime state
 - Processes
 - Network connections
 - Executed commands
 - ...

Tool

Volatility Framework

Assembly-level debugging

- Information that would be difficult to get from a disassembler
- Ability to measure and control a program's execution
- Every memory location, register, and argument to every function
- Change and test variables
- Values of memory addresses as they change throughout the execution
- Conditional Breakpoints

Tools

OlllyDbg, IDA

Conclusion

Summary

- Multiple techniques to use to full capacity
- Basic analysis: simple tools, easy to use and understand
- Advanced analysis: working knowledge and practice necessary
- Still a lot to research for reverse engineering

Future

- Containing race between malware authors and analysts
- Anti techniques will get even smarter
- Detection methods of those as well
- Fully automated approach might be satisfying in near future
- Artificial intelligence, Deep Learning, Neural Networks helpful

Literatur I



G. Yuxin, L. Zexin, and L. Yuqing, "Survey on malware anti analysis," in *Fifth International Conference on Intelligent Control and Information Processing*, 2014.



M. Sikorski and A. Honig, *Practical Malware Analysis: A Hands-On Guide to Dissecting Malicious Software*. No Starch Press, 2012.



E. K. M. Egele, T. Scholte and C. Kruegel, *A Survey on Automated Dynamic Malware-Analysis Techniques and Tools*. ACM Computing Surveys, Vol. 44, ss, 2012.



C. Malin, E. Casey, and J. Aquilina, *Malware Forensics: Investigating and Analyzing Malicious Code*. Elsevier Science, 2008.

Literatur II



M. Kerrisk, *Linux Manual Page: ldd(1)*.

<https://www.kernel.org/doc/man-pages/>, September 2017.



Dependency Walker: Using Dependency Walker for General Information about Modules.

www.dependencywalker.com/help/html/overview_3.htm.






REMux.

www.remnux.org/.



I. You and K. Yim, "Malware obfuscation techniques: A brief survey," in *International Conference on Broadband, Wireless Computing, Communication and Applications*, 2010.

Literatur III

-  K. Yakdan, S. Eschweiler, E. Gerhards-Padilla, and M. Smith, “No more gotos: Decompilation using pattern-independent control-flow structuring and semantics-preserving transformations,” in ??, 2015.
-  K. Yakdan, S. Dechand, E. Gerhards-Padilla, and M. Smith, “Helping johnny to analyze malware: A usability-optimized decompiler and malware analysis user study,” in *2016 IEEE Symposium on Security and Privacy*, 2016.
-  J. T. Streib, *Guide to Assembly Language - A Concise Introduction*. Springer, 2011.

Literatur IV



M. Ligh, S. Adair, B. Hartstein, and M. Richard, *Malware Analyst's Cookbook and DVD: Tools and Techniques for Fighting Malicious Code*.

Books 24x7 IT PRO, Wiley, 2010.



D. Distler, *Malware Analysis: An Introduction*.

SANS Institute, 2007.



P. Ren, L. W., S. D., W. J., and L. K., "Analysis and forensics for behavior characteristics of malware in internet," in *14th Annual Conference on Privacy, Security and Trust (PST)*, 2016.



A. Software, *Retargetable Decompiler RetDec*.

<https://retdec.com/>, December 2017.

Literatur V



M. Hale Ligh, A. Case, J. Levy, and A. Walters, *The Art of Memory Forensics: Detecting Malware and Threats in Windows, Linux, and Mac Memory*.

John Wiley & Sons, Inc., 2014.



T. Haruyama and H. Suzuki, *One byte Modification for Breaking Memory Forensic Analysis*.

https://media.blackhat.com/bh-eu-12/Haruyama/bh-eu-12-Haruyama-Memory_Forensic-Slides.pdf, 2012.



T. Teller and A. Hayon, "Enhancing automated malware analysis machines with memory analysis," BlackHat, 2014.

Literatur VI



T. Shibahara, T. Yagi, M. Akiyama, D. Chiba, and T. Yada, “Efficient dynamic malware analysis based on network behavior using deep learning,” in *2016 IEEE Global Communications Conference (GLOBECOM)*, 2016.



J. Aycock, *Computer Viruses and Malware*. Advances in Information Security, Springer US, 2006.

The End

Fragen?