

SUPPLEMENTARY MATERIAL

RegNetAgents: A Multi-Agent AI Framework for Automated Gene Regulatory Network Analysis and Therapeutic Target Prioritization

Authors: Jose A. Bird, PhD

Affiliation: Bird AI Solutions

Table of Contents

- [Table S1: Domain Agent LLM Prompt Templates](#table-s1-domain-agent-llm-prompt-templates)
- [S1.1 Cancer Biology Agent](#s11-cancer-biology-agent)
- [S1.2 Drug Development Agent](#s12-drug-development-agent)
- [S1.3 Clinical Medicine Agent](#s13-clinical-medicine-agent)
- [S1.4 Systems Biology Agent](#s14-systems-biology-agent)
- [Notes on Prompt Engineering](#notes-on-prompt-engineering)
- [Table S2: Cervical Cancer Gene Validation](#table-s2-cervical-cancer-gene-validation)
- [Reproducibility Notes](#reproducibility-notes)

Table S1: Domain Agent LLM Prompt Templates

RegNetAgents employs four specialized domain agents that use structured LLM prompts to generate scientific insights. Each agent receives gene-specific context (network topology, functional annotations, pathway enrichment) and returns structured JSON responses with domain-specific interpretations and rationales.

LLM Configuration:

- Model: llama3.1:8b (via Ollama local inference)
- Temperature: 0.3 (for scientific accuracy)
- Timeout: 90 seconds (for parallel multi-gene analysis)
- Retry logic: 2 attempts with graceful fallback to rule-based heuristics

Context Variables (populated dynamically for each gene):

- {gene}: Gene symbol (e.g., "TP53", "MYC")
- {function_context}: NCBI/UniProt functional description
- {gene_info}: Network topology (regulatory role, degree centrality)
- {enriched_pathways}: Reactome pathway enrichment results (when available)
- {regulator_count}, {target_count}: Cascade analysis results
- {tissue_context}: Cross-cell-type activity
- {pagerank}: PageRank centrality score

S1.1 Cancer Biology Agent

System Prompt:

You are an expert cancer biologist analyzing gene regulatory networks. Provide scientifically accurate, evidence-based analysis in structured JSON format only.

User Prompt Template:

Analyze the gene {gene} from a cancer biology perspective. {function_context}

Gene Network Context:

- *Regulatory Role: {regulatory_role}*
- *Upstream Regulators: {num_regulators}*
- *Downstream Targets: {num_targets}*
- *Network Position: in-degree={num_regulators}, out-degree={num_targets}*

Enriched Pathways: {enriched_pathways}

Provide a cancer biology analysis in this EXACT JSON format:

```
{ "oncogenic_potential": "high/moderate/low", "oncogenic_rationale": "brief scientific
explanation based on network topology and cancer biology", "tumor_suppressor_likelihood":
"high/moderate/low", "tumor_suppressor_rationale": "brief scientific explanation",
"therapeutic_target_score": 0.0-1.0, "therapeutic_rationale": "explanation of druggability and
therapeutic potential", "cancer_pathways": ["pathway1", "pathway2"], "biomarker_potential":
"high/moderate/low", "biomarker_utility": "diagnostic/prognostic/predictive",
"biomarker_rationale": "explanation", "research_priority": "high/moderate/low", "summary":
"1-2 sentence synthesis of cancer relevance" }
```

Base your analysis on:

- Network centrality (hub regulators are critical for cancer)
- Regulatory control (highly regulated genes often tumor suppressors)
- Pathway involvement (cancer-related pathways)
- Known cancer biology principles

Provide only the JSON, no additional text.

Example Output Structure:

```
{ "oncogenic_potential": "high", "oncogenic_rationale": "TP53 acts as a hub regulator with 163 downstream targets, indicating strong regulatory influence characteristic of oncogenes when dysregulated.", "tumor_suppressor_likelihood": "high", "tumor_suppressor_rationale": "Heavily regulated by 7 upstream factors, consistent with checkpoint function.", "therapeutic_target_score": 0.8, "llm_powered": true }
```

S1.2 Drug Development Agent

System Prompt:

You are an expert in drug discovery and development analyzing gene regulatory networks. Provide scientifically accurate, evidence-based analysis in structured JSON format only.

User Prompt Template:

Analyze the gene {gene} from a drug development perspective. {function_context}

Gene Network Context:

- Regulatory Role: {regulatory_role}
- Upstream Regulators: {num_regulators}
- Downstream Targets: {num_targets}
- Total Regulators Found: {regulator_count}
- Total Targets Found: {target_count}

Provide drug development analysis in this EXACT JSON format:

```
{ "druggability_score": 0.0-1.0, "druggability_rationale": "explanation of druggability based on structure and network", "target_class": "kinase|GPCR|transcription_factor|nuclear_receptor|other", "intervention_strategy": "inhibition|activation|modulation|allosteric", "intervention_rationale": "why this strategy is appropriate", "development_complexity": "high|moderate|low", "cascade_effects": ["effect1", "effect2"], "clinical_trial_readiness": "ready|needs_preclinical|needs_research|not_suitable",
```

"development_timeline": "estimated years", "summary": "1-2 sentence synthesis of drug development potential" }

Base analysis on:

- *Network topology (hub genes may have broad effects)*
- *Regulatory control (heavily regulated may be indirect targets)*
- *Cascade effects (downstream impact)*
- *Known drug target classes*

Provide only the JSON, no additional text.

S1.3 Clinical Medicine Agent

System Prompt:

You are an expert clinician and translational researcher analyzing gene networks for precision medicine applications.

User Prompt Template:

Analyze the gene {gene} from a clinical medicine and personalized healthcare perspective. {function_context}

Gene Network Context:

- *Regulatory Role: {regulatory_role}*
- *Upstream Regulators: {num_regulators}*
- *Downstream Targets: {num_targets}*
- *Tissue Distribution: {tissue_context}*

Provide a clinical analysis in this EXACT JSON format:

```
{ "disease_association_likelihood": "high/moderate/low", "disease_rationale": "brief explanation of disease relevance", "biomarker_utility": "diagnostic/prognostic/predictive/therapeutic", "biomarker_rationale": "brief explanation of biomarker potential", "clinical_actionability": "high/moderate/low", "actionability_rationale": "brief explanation of clinical utility", "tissue_specificity": "tissue-specific/broadly_expressed/ubiquitous", "diagnostic_potential": "high/moderate/low", "summary": "1-2 sentence clinical significance summary" }
```

Focus on:

- *Disease association potential based on network position*

- Biomarker utility for diagnosis, prognosis, or therapeutic monitoring
- Clinical actionability and translational potential
- Tissue specificity implications for personalized medicine

Provide only the JSON, no additional text.

S1.4 Systems Biology Agent

System Prompt:

You are an expert systems biologist analyzing gene regulatory networks. Provide scientifically accurate, evidence-based analysis in structured JSON format only.

User Prompt Template:

*Analyze the gene {gene} from a systems biology and network theory perspective.
{function_context}*

Gene Network Context:

- Regulatory Role: {regulatory_role}
- Upstream Regulators: {num_regulators} (total in cascade: {reg_count})
- Downstream Targets: {num_targets} (total in cascade: {target_count})
- PageRank Centrality: {pagerank}
- Total Network Degree: {num_regulators + num_targets}

Provide a systems biology analysis in this EXACT JSON format:

```
{ "network_centrality": 0.0-1.0, "centrality_rationale": "brief explanation of network position",
  "regulatory_hierarchy": "master|hub|intermediate|peripheral", "hierarchy_rationale": "brief
  explanation of hierarchical position", "information_flow": "high|moderate|low",
  "flow_rationale": "brief explanation of information processing", "network_vulnerability":
  "critical|important|moderate|minimal", "vulnerability_rationale": "brief explanation of
  network impact", "perturbation_impact": "system-wide|modular|localized|minimal",
  "perturbation_rationale": "brief explanation of knockout/perturbation effects",
  "evolutionary_conservation": "high|moderate|low", "conservation_rationale": "brief inference
  about evolutionary importance", "summary": "1-2 sentence systems biology summary" }
```

Focus on:

- Network topology and centrality (degree, betweenness, PageRank implications)
- Hierarchical position and regulatory control

- *Information flow and signal transduction*
- *Network robustness and vulnerability to perturbation*
- *Evolutionary conservation inferred from network position*

Provide only the JSON, no additional text.

Notes on Prompt Engineering

Structured Output Constraints:

All prompts explicitly request JSON-only responses with predefined keys and value constraints (e.g., "high|moderate|low", "0.0-1.0"). This ensures:

1. Parseable structured output for downstream integration
2. Consistent classification schemes across genes
3. Minimal hallucination through constrained response space
4. Graceful error handling via JSON validation

Context Integration:

Each prompt incorporates multiple information sources:

- Gene functional annotations (UniProt/NCBI) provide biological grounding
- Network topology metrics constrain interpretations to data-supported claims
- Pathway enrichment results (when available) add mechanistic context
- Cross-cell-type analysis provides tissue specificity

Fallback Mechanism:

If LLM calls fail (timeout, parsing error, unavailable service), agents automatically fall back to rule-based heuristics using network topology thresholds:

- Oncogenic potential: >50 targets = high, 20-50 = moderate, <20 = low
- Tumor suppressor likelihood: >10 regulators = high (checkpoint function)
- Druggability: Hubs = complex (off-target risks), heavily regulated = lower priority

Each analysis result includes an `llm_powered: true/false` flag for transparency.

Temperature Selection:

Temperature = 0.3 balances determinism (reproducibility) with linguistic variety (natural rationale text). Lower temperatures (0.0-0.2) produced overly repetitive text; higher temperatures (0.5-1.0) increased inconsistency across runs.

Table S2: Cervical Cancer Gene Validation

To demonstrate framework generalizability beyond the colorectal cancer validation presented in the main manuscript, we analyzed 7 cervical cancer-associated genes with confirmed regulatory network coverage in epithelial cells (all genes with ≥5 regulators). This analysis serves as independent validation that the framework produces biologically meaningful results across different cancer contexts.

All 7 genes were successfully analyzed using the same comprehensive workflow (network modeling, therapeutic target prioritization, pathway enrichment) in 103 seconds. The analysis recapitulated expected regulatory architectures: TP53 and MYC emerged as hub regulators with extensive downstream connectivity (163 and 427 targets respectively), while BRCA1, BRCA2, EGFR, and CCND1 exhibited heavily regulated profiles consistent with their roles as downstream effectors in oncogenic signaling cascades. Therapeutic target prioritization identified high-confidence regulatory candidates for each gene, including WWTR1 (TAZ) as the top-ranked TP53 regulator - consistent with documented Hippo pathway regulation of p53 activity.

This cervical cancer validation demonstrates that RegNetAgents generates scientifically coherent results across cancer types, with regulatory network patterns aligning with established biological knowledge. The analysis required no modification to the framework or workflow, highlighting the system's generalizability for hypothesis generation across diverse disease contexts.

Gene	Regulatory Role	Regulators	Targets	Top Therapeutic Target	PageRank
-----	-----	-----	-----	-----	-----
TP53	Hub Regulator	7	163	WWTR1	0.473
MYC	Hub Regulator	25	427	ID4	0.622
BRCA1	Heavily Regulated	23	0	ZNF334	0.723
BRCA2	Heavily Regulated	20	0	HMGB2	0.510
EGFR	Heavily Regulated	37	0	HMGB2	0.510
CCND1	Heavily Regulated	42	0	ZBTB20	0.600
KRAS	Weakly Regulated	7	0	GPBP1	0.609

Table S2. Cervical cancer gene validation results. Seven cervical cancer-associated genes were analyzed in epithelial cells to demonstrate framework generalizability. Regulatory roles were automatically classified based on network topology. Top therapeutic target candidates were identified through PageRank-based ranking of upstream regulators. Analysis execution time: 103 seconds for all 7 genes.

Reproducibility Notes

To reproduce LLM analyses:

1. Install Ollama: <https://ollama.com/download>
2. Pull model: `ollama pull llama3.1:8b`
3. Configure environment variables:
 - `OLLAMA_HOST=http://localhost:11434`
 - `OLLAMA_MODEL=llama3.1:8b`
 - `OLLAMA_TEMPERATURE=0.3`
 - `OLLAMA_TIMEOUT=90`
 - `USE_LLM_AGENTS=true`
4. Run analysis via MCP server or Python API

LLM output variability:

Due to temperature-based sampling, exact wording of rationales will vary across runs. However, core classifications (high/moderate/low, diagnostic/prognostic) remain consistent. For deterministic analysis, use rule-based mode (`USE_LLM_AGENTS=false`).

Network metrics (PageRank, degree centrality) are deterministic and fully reproducible across all runs.

Code Availability:

Complete implementation available at: <https://github.com/jab57/RegNetAgents>