

## 2lexical-analysis-lab

---

CST 334 (Operating Systems)  
Dr. Glenn Bruns

### Lab: Lexical analysis

The purpose of this lab is to give you experience in using a lexical analyser. See hints at the end only if you get stuck.

Copy the file:

</home/CLASSES/brunsglenn/cst334/labs/lex-lab/lab.tar>

to a directory of your own, and extract the files.

1. Look at file main.c. The main program initializes the lexical analyzer, and then calls the function `parse()`, which is defined in `parser.c`
2. Look at the file `parser1.c`. The function `parse()` calls the lexical analyzer to get the lookahead symbol, then calls function `assign_stmt()`, which will parse a simple assignment statement.
3. Look at the function `assign_stmt()`. The comment at the top of the function shows the syntax of a very simple assignment statement:

`assign_stmt ::= ID "=" NUM`

The string "x = 3" can be derived from this grammar. Make sure you understand what `assign_stmt()` is doing.

4. Look at the Makefile. Make sure the value of `VERSION` is `parser1.c`. Look at what the target 'test1' does. Then, "make test1" at the command line. Does the test work?

(Note: if your machine complains about the <<< in the Makefile, create a file for the input text and use regular input redirection with < )

5. Next try the targets 'test2' and 'test3' of the Makefile.

6. Try running the parser from the command line. Enter `./parser`, hit return, enter your input, then enter ctrl-D to indicate end of file. Like this:

```
$ ./parser
x = 10
parsed
$ ./parser
x = 10
parsed
$ ./parser
x
= 10
parsed
$
```

7. Look at the function `match()` in `parser1.c`. It checks to make sure the token passed as a parameter is equal to the lookahead token. If so, it gets the next token. Otherwise, it reports a syntax error.
8. Copy `parser1.c` to `parser2.c`. Modify `assign_stmt()` so that it uses function `match()`. This will make the code of `assign_stmt()` much simpler.
9. Change the value `VERSION` in the Makefile to `parser2.c`. Try the three tests again.
10. Copy `parser2.c` to `parser3.c`. Modify `assign_stmt()` so that the variable name and number are saved during parsing, and then the assignment statement is printed at the end of the function. You will need

the function `lexer_id_val()` to get the value of the ID token, and the function `lexer_num_val()` to get the value of the NUM token.

Note: `lexer_num_val()`

When you print the statement at the end of the function, you can use a print statement like this:

```
printf("%s = %d\n", id, i);
```

11. Change the value `VERSION` in the Makefile to `parser3.c`. Try the three tests again. Please note carefully that the "pretty printed" output will have one space on either side of the equals sign, even if the input doesn't.

12. If you still have time, copy `parser3.c` to `parser4.c`, and change `assign_stmt()` so that an assignment symbol has the syntax

```
assign_stmt ::= ID "=" NUM + NUM
```

Also, modify your code to print the right thing at the end.

13. If you still have time, modify your code so that an assignment statement must have a semicolon at the end.

14. If you still have time, write the BNF for a simple function call of the form `f(x)`, where 'f' and 'x' are both ID tokens, and add a function `fun_call()` to `parser.c`. Test your function.

## Hints

1. Try hard to remember how to do this. Hint: 'x' stands for extract.

```
tar xf lab.tar
```

8. Here is the revised `assign_stmt()`:

```
void assign_stmt() {
    match(ID);
    match('=');
    match(NUM);
}
```

10. Here is the revised `assign_stmt()`:

```
void assign_stmt() {
    char *id;
    int i;
    if (lookahead == ID) {
        id = lexer_id_val();
    }
    match(ID);
    match('=');
    if (lookahead == NUM) {
        i = lexer_num_val();
    }
    match(NUM);
    printf("%s = %d\n", id, i);
}
```

---

Published by [Google Drive](#) – [Report Abuse](#) – Updated automatically every 5 minutes

---