
Manual station

수동조작함



SPRINKLER manual station





PV-SVP-B

Rated voltage DC24V ±20%


Display system Power/valve release/vale warning


Operation method Operation switch Frame material PC (Poly Carbonite) 160(W)*170(H)*26(D) Product size Recessed type BOX 160(W)*170(H)*57(D) Exposure type BOX 140(W) * 150(H) * 57(D) **BOX** material Poly Carbonate

Color Black/gray

DAMPER manual station







PV-DAMPER-B

Rated voltage DC24V ±20%


Display system Power/damper operation display


Operation method Operation switch Frame material PC (Poly Carbonite) Product size 160(W)*170(H)*26(D) Recessed type BOX 160(W)*170(H)*57(D) Exposure type BOX 140(W)*150(H)*57(D)

BOX material Poly Carbonate Color Black/gray

Extinguishing agent manual station







PV-CO2-B

Rated voltage DC24V ±20%

Display system Power/extinguishing agent release/

buzzer

Operation method Operation switch/delay switch

Frame material PC (Poly Carbonite) Product size 160(W)*170(H)*26(D) Recessed type BOX 160(W)*170(H)*57(D) Exposure type BOX 140(W)*150(H)*57(D)

BOX material Poly Carbonate Black/gray Color