
MODULE *GenericMulticast1*

LOCAL INSTANCE *Commons*
 LOCAL INSTANCE *Naturals*
 LOCAL INSTANCE *FiniteSets*
 LOCAL INSTANCE *TLC*

Number of groups in the algorithm.
 CONSTANT *NGROUPS*

Number of processes in the algorithm.
 CONSTANT *NPROCESSES*

Set with initial messages the algorithm starts with.
 CONSTANT *INITIAL_MESSAGES*

The conflict relation.
 CONSTANT *CONFLICTR*($_, _$)

ASSUME
 Verify that *NGROUPS* is a natural number greater than 0.
 $\wedge \textit{NGROUPS} \in (\textit{Nat} \setminus \{0\})$
 Verify that *NPROCESSES* is a natural number greater than 0.
 $\wedge \textit{NPROCESSES} \in (\textit{Nat} \setminus \{0\})$

LOCAL *Processes* $\triangleq \{p : p \in 1 \dots \textit{NPROCESSES}\}$
 LOCAL *Groups* $\triangleq \{g : g \in 1 \dots \textit{NGROUPS}\}$

The module containing the Atomic Broadcast primitive.
 VARIABLE *AtomicBroadcastBuffer*
AtomicBroadcast \triangleq INSTANCE *AtomicBroadcast*

The module containing the quasi reliable channel.
 VARIABLE *QuasiReliableChannel*
QuasiReliable \triangleq INSTANCE *QuasiReliable* WITH
INITIAL_MESSAGES $\leftarrow \{\}$

The algorithm's *Mem* structure. We use a separate module.
 VARIABLE *MemoryBuffer*
Memory \triangleq INSTANCE *Memory*

VARIABLES
 The process local clock.

K ,

The set contains previous messages. We use this with the *CONFLICTR* to verify conflicting messages.

PreviousMsgs,

The set of delivered messages. This set is not an algorithm requirement. We use this to help check the algorithm's properties.

Delivered,

A set contains the processes' votes for the message's timestamp. This structure is implicit in the algorithm.

Votes

$vars \triangleq \langle$
 K ,
 $MemoryBuffer$,
 $PreviousMsgs$,
 $Delivered$,
 $Votes$,
 $AtomicBroadcastBuffer$,
 $QuasiReliableChannel$
 \rangle

Check if the given message conflict with any other in the *PreviousMsgs*.

LOCAL $HasConflict(g, p, m1) \triangleq$
 $\exists m2 \in PreviousMsgs[g][p] : CONFLICTR(m1, m2)$

These are the handlers. The actual algorithm resides here, the lambdas only assert the guarding predicates before calling the handler.

LOCAL $ComputeGroupSeqNumberHandler(g, p, msg, ts) \triangleq$
 $\wedge \vee \wedge HasConflict(g, p, msg)$
 $\wedge K' = [K \text{ EXCEPT } ![g][p] = K[g][p] + 1]$
 $\wedge PreviousMsgs' = [PreviousMsgs \text{ EXCEPT } ![g][p] = \{msg\}]$
 $\vee \wedge \neg HasConflict(g, p, msg)$
 $\wedge PreviousMsgs' = [PreviousMsgs \text{ EXCEPT } ![g][p] =$
 $PreviousMsgs[g][p] \cup \{msg\}]$
 $\wedge \text{UNCHANGED } K$
 $\wedge \vee \wedge Cardinality(msg.d) > 1$
 $\wedge Memory!Insert(g, p, \langle msg, "S1", K'[g][p] \rangle)$
 $\wedge QuasiReliable!Send(\langle msg, g, K'[g][p] \rangle)$
 $\vee \wedge Cardinality(msg.d) = 1$
 $\wedge Memory!Insert(g, p, \langle msg, "S3", K'[g][p] \rangle)$
 $\wedge \text{UNCHANGED } QuasiReliableChannel$
 $\wedge \text{UNCHANGED } \langle Delivered, Votes \rangle$

LOCAL *SynchronizeGroupClockHandler*(g, p, m, tsf) \triangleq
 $\wedge \vee \wedge tsf > K[g][p]$
 $\wedge K' = [K \text{ EXCEPT } ![g][p] = tsf]$
 $\wedge PreviousMsgs' = [PreviousMsgs \text{ EXCEPT } ![g][p] = \{\}]$
 $\vee \wedge tsf \leq K[g][p]$
 $\wedge \text{UNCHANGED } \langle K, PreviousMsgs \rangle$
 $\wedge \vee \wedge \exists \langle n, s, ts \rangle \in MemoryBuffer[g][p] : s = \text{"S1"} \wedge m = n$
 $\wedge Memory!Insert(g, p, \langle m, \text{"S3"}, tsf \rangle)$
 $\vee \text{UNCHANGED } MemoryBuffer$
 $\wedge \text{UNCHANGED } \langle QuasiReliableChannel, Delivered, Votes \rangle$
 LOCAL *GatherGroupsTimestampHandler*(g, p, msg, ts, tsf) \triangleq
 $\wedge \vee \wedge ts < tsf$
 $\wedge AtomicBroadcast!ABroadcast(g, \langle msg, \text{"S2"}, tsf \rangle)$
 $\vee \text{UNCHANGED } AtomicBroadcastBuffer$
 $\wedge Memory!Insert(g, p, \langle msg, \text{"S3"}, tsf \rangle)$
 $\wedge \text{UNCHANGED } \langle K, PreviousMsgs, Delivered \rangle$

Executes when process P receives a message M from the Atomic Broadcast primitive and M is in P 's memory. This procedure is extensive, with multiple branches based on the message's state and destination. Let's split the explanation.

When M 's state is $S0$, we first verify if M conflicts with messages in the *PreviousMsgs* set. If a conflict exists, we increase P 's local clock by one and clear the *PreviousMsgs* set.

When message M has a single group as the destination, it is already in its desired destination and is synchronized because we received M from Atomic Broadcast primitive. P stores M in memory with state $S3$ and timestamp with the current clock value.

When M includes multiple groups in the destination, the participants must agree on the final timestamp. When M 's state is $S0$, P will send its timestamp proposition to all other participants, which is the current clock value, and update M 's state to $S1$ and timestamp. If M 's state is $S2$, we are synchronizing the local group, meaning we may need to leap the clock to the M 's received timestamp and then set M to state $S3$.

$ComputeGroupSeqNumber(g, p) \triangleq$
 $\wedge AtomicBroadcast!ABDeliver(g, p,$
 $\text{LAMBDA } t : t[2] = \text{"S0"} \wedge ComputeGroupSeqNumberHandler(g, p, t[1], t[3]))$

After exchanging the votes between groups, processes must select the final timestamp. When we have one proposal from each group in message M 's destination, the highest vote is the decided timestamp. If P 's local clock is smaller than the value, we broadcast the message to the local group with state $S2$ and save it in memory. Otherwise, we update the in-memory to state $S3$.

We only execute the procedure once we have proposals from all participating groups. Since we receive messages from the quasi-reliable channel, we keep the votes in the *Votes* structure. This structure is implicit in the algorithm.

LOCAL *HasNecessaryVotes*($g, p, msg, ballot$) \triangleq
 $\wedge Cardinality(ballot) = Cardinality(msg.d)$
 $\wedge Memory!Contains(g, p, \text{LAMBDA } n : msg = n[1] \wedge n[2] = \text{"S1"})$

$GatherGroupsTimestamp(g, p) \triangleq$
 $\wedge QuasiReliable!ReceiveAndConsume(g, p,$
 $\text{LAMBDA } t :$
 $\wedge \text{ LET}$
 $\quad msg \triangleq t[1]$
 $\quad origin \triangleq t[2]$
 $\quad vote \triangleq \langle msg.id, origin, t[3] \rangle$
 $\quad ballot \triangleq \{v \in (Votes[g][p] \cup \{vote\}) : v[1] = msg.id\}$
 $\quad elected \triangleq Max(\{x[3] : x \in ballot\})$
 IN
 $\quad \text{We only execute the procedure when we have proposals from all groups.}$
 $\wedge \vee \wedge HasNecessaryVotes(g, p, msg, ballot)$
 $\quad \wedge \exists \langle m, s, ts \rangle \in MemoryBuffer[g][p] : m = msg$
 $\quad \wedge GatherGroupsTimestampHandler(g, p, msg, ts, elected)$
 $\quad \wedge Votes' = [Votes \text{ EXCEPT } ![g][p] = \{$
 $\quad \quad x \in Votes[g][p] : x[1] \neq msg.id\}]$
 $\vee \wedge \neg HasNecessaryVotes(g, p, msg, ballot)$
 $\quad \wedge Votes' = [Votes \text{ EXCEPT } ![g][p] = Votes[g][p] \cup \{vote\}]$
 $\quad \wedge \text{ UNCHANGED } \langle MemoryBuffer, K,$
 $\quad \quad PreviousMsgs, AtomicBroadcastBuffer \rangle$
 $\wedge \text{ UNCHANGED } \langle Delivered \rangle)$

$SynchronizeGroupClock(g, p) \triangleq$
 $\wedge AtomicBroadcast!ABDeliver(g, p,$
 $\text{ LAMBDA } t : t[2] = \text{"S2"} \wedge SynchronizeGroupClockHandler(g, p, t[1], t[3]))$

When messages are to deliver, we select them and call the delivery primitive. Ready means they are in state S3, and the message either does not conflict with any other in the memory structure or is smaller than all others. Once a message is ready, we also collect the messages that do not conflict with any other for delivery in a single batch.

$DoDeliver(g, p) \triangleq$
 $\text{We are accessing the buffer directly, and not through the } Memory \text{ instance.}$
 $\text{We do this because is easier and because we are only reading the values here.}$
 $\text{Any changes we do through the instance.}$
 $\exists \langle m_1, state, ts_1 \rangle \in MemoryBuffer[g][p] :$
 $\quad \wedge state = \text{"S3"}$
 $\quad \wedge \forall \langle m_2, ignore, ts_2 \rangle \in (MemoryBuffer[g][p] \setminus \{\langle m_1, state, ts_1 \rangle\}) :$
 $\quad \quad \wedge \vee \neg CONFLICTR(m_1, m_2)$
 $\quad \quad \vee ts_1 < ts_2 \vee (m_1.id < m_2.id \wedge ts_1 = ts_2)$
 $\wedge \text{ LET}$
 $\quad G \triangleq Memory!ForAllFilter(g, p,$
 $\quad \quad \text{LAMBDA } t_i, t_j : t_i[2] = \text{"S3"} \wedge \neg CONFLICTR(t_i[1], t_j[1]))$
 $\quad D \triangleq G \cup \{\langle m_1, \text{"S3"}, ts_1 \rangle\}$
 $\quad F \triangleq \{t[1] : t \in D\}$
 IN
 $\quad \wedge Memory!Remove(g, p, D)$

$$\begin{aligned}
& \wedge \text{Delivered}' = [\text{Delivered} \text{ EXCEPT } ![g][p] = \\
& \quad \text{Delivered}[g][p] \cup \text{Enumerate}(\text{Cardinality}(\text{Delivered}[g][p]), F)] \\
& \wedge \text{UNCHANGED } \langle \text{QuasiReliableChannel}, \text{AtomicBroadcastBuffer}, \\
& \quad \text{Votes}, \text{PreviousMsgs}, K \rangle
\end{aligned}$$

$$\begin{aligned}
\text{LOCAL } \text{InitProtocol} & \triangleq \\
& \wedge K = [i \in \text{Groups} \mapsto [p \in \text{Processes} \mapsto i]] \\
& \wedge \text{Memory!Init} \\
& \wedge \text{PreviousMsgs} = [i \in \text{Groups} \mapsto [p \in \text{Processes} \mapsto \{\}]] \\
& \wedge \text{Delivered} = [i \in \text{Groups} \mapsto [p \in \text{Processes} \mapsto \{\}]] \\
& \wedge \text{Votes} = [i \in \text{Groups} \mapsto [p \in \text{Processes} \mapsto \{\}]]
\end{aligned}$$

$$\begin{aligned}
\text{LOCAL } \text{InitCommunication} & \triangleq \\
& \wedge \text{AtomicBroadcast!Init} \\
& \wedge \text{QuasiReliable!Init}
\end{aligned}$$

$$\text{Init} \triangleq \text{InitProtocol} \wedge \text{InitCommunication}$$

$$\begin{aligned}
\text{Step}(g, p) & \triangleq \\
& \vee \text{ComputeGroupSeqNumber}(g, p) \\
& \vee \text{GatherGroupsTimestamp}(g, p) \\
& \vee \text{SynchronizeGroupClock}(g, p) \\
& \vee \text{DoDeliver}(g, p)
\end{aligned}$$

$$\begin{aligned}
\text{GroupStep}(g) & \triangleq \\
& \exists p \in \text{Processes} : \text{Step}(g, p)
\end{aligned}$$

$$\begin{aligned}
\text{Next} & \triangleq \\
& \vee \exists g \in \text{Groups} : \text{GroupStep}(g) \\
& \vee \text{UNCHANGED } \text{vars}
\end{aligned}$$

$$\text{Spec} \triangleq \text{Init} \wedge \square[\text{Next}]_{\text{vars}}$$

$$\text{SpecFair} \triangleq \text{Spec} \wedge \text{WF}_{\text{vars}}(\exists g \in \text{Groups} : \text{GroupStep}(g))$$

Helper functions to aid when checking the algorithm properties.

$$\begin{aligned}
\text{WasDelivered}(g, p, m) & \triangleq \\
& \text{Verifies if the given process } p \text{ in group } g \text{ delivered message } m . \\
& \wedge \exists \langle idx, n \rangle \in \text{Delivered}[g][p] : n.id = m.id
\end{aligned}$$

$$\begin{aligned}
\text{FilterDeliveredMessages}(g, p, m) & \triangleq \\
& \text{Retrieve the set of messages with the same } id \text{ as message } m \text{ delivered by the given process } p \\
& \text{in group } g .
\end{aligned}$$

$$\{\langle idx, n \rangle \in Delivered[g][p] : n.id = m.id\}$$

$$DeliveredInstant(g, p, m) \triangleq$$

Retrieve the instant the process p in group g delivered message m .

$$(\text{CHOOSE } \langle t, n \rangle \in Delivered[g][p] : n.id = m.id)[1]$$