



EXERCISES — my itoa base

version #



IT IS MY JOB TO MAKE SURE YOU DO YOURS.

Copyright

This document is for internal use at EPITA ([website](#)) only.

Copyright © 2021-2022 Assistants [<assistants@tickets.assistants.epita.fr>](mailto:assistants@tickets.assistants.epita.fr)

The use of this document must abide by the following rules:

- ▷ You downloaded it from the assistants' intranet.*
- ▷ This document is strictly personal and must **not** be passed onto someone else.
- ▷ Non-compliance with these rules can lead to severe sanctions.

Contents

1	my itoa base	3
1.1	Goal	3
1.2	Examples	3

*<https://intra.assistants.epita.fr>

1 my itoa base

Files to submit:

- my_itoa_base/my_itoa_base.c
- my_itoa_base/my_itoa_base.h

Authorized headers: You are only allowed to use the functions defined in the following headers:

- assert.h
- err.h
- errno.h
- stddef.h

1.1 Goal

You have to implement the following function:

```
char *my_itoa_base(int n, char *s, const char *base);
```

This function should convert the integer `n` in its representation in base `base` and store this representation in `s` (without forgetting to end it by `'\0'`). The function returns the resulting string (the same as the one given by the argument `s`). Consider that the caller already allocated the space needed in `s`.

You need to handle negative numbers only in base 10.

The argument `base` is interpreted as follows: the `i`-th character of the string is the representation of the value `i` in the target base.

Base 1 is the only base you can leave behind. All other bases must be handled.

1.2 Examples

```
my_itoa_base(42, s, "0123456789ABCDEF");
```

`s` will be equal to "2A".

```
my_itoa_base(32, s, "0123456789abcdef");
```

`s` will be equal "20".

```
my_itoa_base(12, s, "01");
```

`s` will be equal "1100".

```
my_itoa_base(80, s, "0123456");
```

`s` will be equal "143".

It is my job to make sure you do yours.