

# **Exercises** — Array binary search

version #



ASSISTANTS C/UNIX 2022 <assistants@tickets.assistants.epita.fr>

## Copyright

This document is for internal use at EPITA (website) only.

Copyright © 2021-2022 Assistants <assistants@tickets.assistants.epita.fr>

## The use of this document must abide by the following rules:

- ▶ You downloaded it from the assistants' intranet.\*
- ▶ This document is strictly personal and must **not** be passed onto someone else.
- ▶ Non-compliance with these rules can lead to severe sanctions.

### **Contents**

1 Array binary search		3	
	1.1	Goal	3
		Fxample	3

<sup>\*</sup>https://intra.assistants.epita.fr

## 1 Array binary search

#### Files to submit:

binary\_search/binary\_search.c

Main function: None

Authorized headers: You are only allowed to use the functions defined in the following headers:

- · assert.h
- · stddef.h
- errno.h
- err.h

#### 1.1 Goal

```
int binary_search(const int vec[], size_t size, int elt)
```

When looking for an element in a sorted array, it is possible to get the result with a logarithmic complexity using *dichotomy*. Let us remind how dichotomy works:

- If the minimum and maximum indices of the sub-vector are equal or reversed (max < min), the search is negative (we did not find the element).
- Otherwise, the middle element of the array is chosen as the pivot:
  - If the searched item is equal to the pivot, we return its position.
  - If the searched item is greater than the pivot, we restart the search on the sub-vector starting at the pivot + 1 position.
  - If the searched item is less than the pivot, we restart the search on the sub-vector ending at the pivot - 1 position.

#### 1.2 Example

Write the function that returns the index of the searched element in a sorted vector of integers, or -1 if it is not present. The size of the array will always be correct.

It is my job to make sure you do yours.