



EXERCISES — Functional programming

version #



IT IS MY JOB TO MAKE SURE YOU DO YOURS.

Copyright

This document is for internal use at EPITA ([website](#)) only.

Copyright © 2021-2022 Assistants [<assistants@tickets.assistants.epita.fr>](mailto:assistants@tickets.assistants.epita.fr)

The use of this document must abide by the following rules:

- ▷ You downloaded it from the assistants' intranet.*
- ▷ This document is strictly personal and must **not** be passed onto someone else.
- ▷ Non-compliance with these rules can lead to severe sanctions.

Contents

1	Functional programming advanced	3
1.1	Goal	3
1.1.1	all	4
1.1.2	any	4
1.1.3	filter	4
1.1.4	print_even	4
1.1.5	max	5

*<https://intra.assistants.epita.fr>

1 Functional programming advanced

Files to submit:

- `functional_programming_advanced/all.c`
- `functional_programming_advanced/any.c`
- `functional_programming_advanced/filter.c`
- `functional_programming_advanced/max.c`
- `functional_programming_advanced/print_even.c`

Provided files:

- `functional_programming_advanced/functional_programming_advanced.h`

Authorized functions: You are only allowed to use the following functions:

- `malloc(3)`
- `calloc(3)`
- `free(3)`
- `realloc(3)`
- `printf(3)`

Authorized headers: You are only allowed to use the functions defined in the following headers:

- `stddef.h`
- `assert.h`
- `errno.h`
- `err.h`

1.1 Goal

Be careful!

This exercise is the next step after having completed the *functional_programming* exercise. Make sure you have already completed it, because you will need some of the functions you wrote in the first part.

In this exercise you will continue to implement functional functions.

1.1.1 all

Write the `all` function, that iterates over the list, and checks whether the predicate (function returning true or false) is true for every element.

For example, if you have the predicate `is_even` (which returns whether or not a number is even), `all(is_even, {1, 2, 3})` returns false while `all(is_even, {2, 4, 6})` returns true.

```
bool all(int *array, size_t len, bool (*func)(int));
```

1.1.2 any

Write the `any` function that traverses the list, and returns true if the predicate returns true for at least one element of the array.

For example, `any(is_even, {1, 2, 3})` is true, while `any(is_even, {1, 5, 7})` is false.

```
bool any(int *array, size_t len, bool (*func)(int));
```

1.1.3 filter

Write the `filter` function. It takes an `int` array `array` as parameter, the number of elements `len`, a pointer to the `int` array `out_array` that will contain the results, and the predicate `func`. The array `out_array` must contain every element of `array` for which `func` returns true. `filter` returns the size of the new array.

As `out_array` is a pointer to an array, it is your responsibility to allocate `out_array` in the `filter` function. Do not forget to free the result!

```
size_t filter(int *array, size_t len, int **out_array, bool (*func)(int));
```

1.1.4 print_even

This function is a good example use of the previous functions.

Write `print_even`, that will display every even element of the array, one per line. For this, you will need to use `map` and `filter`.

```
void print_even(int *array, size_t len);
```

1.1.5 max

Write a function that will find the maximum value of an `int` array. For this, you will need to use either `foldl` or `foldr`.

```
int max(int *array, size_t len);
```

It is my job to make sure you do yours.