



# EXERCISES — my strstr

---

version #



# Copyright

This document is for internal use at EPITA ([website](#)) only.

Copyright © 2021-2022 Assistants <[assistants@tickets.assistants.epita.fr](mailto:assistants@tickets.assistants.epita.fr)>

**The use of this document must abide by the following rules:**

- ▷ You downloaded it from the assistants' intranet.\*
- ▷ This document is strictly personal and must **not** be passed onto someone else.
- ▷ Non-compliance with these rules can lead to severe sanctions.

## Contents

1	my strstr	3
1.1	Goal . . . . .	3

---

\*<https://intra.assistants.epita.fr>

# 1 my strstr

## Files to submit:

- my\_strstr/my\_strstr.c
- my\_strstr/my\_strstr.h

**Authorized headers:** You are only allowed to use the functions defined in the following headers:

- stddef.h
- errno.h
- err.h
- assert.h

## 1.1 Goal

Write a function that behave like `strstr(3)`. Your function must look for the first occurrence of the `needle` string within the `haystack` string, and return the index to the beginning of `needle`. If `needle` was not found, `my_strstr` must return `-1`.

```
int my_strstr(const char *haystack, const char *needle);
```

If `needle` is empty, you must return 0. The case where only `haystack` is empty will not be tested.

*It is my job to make sure you do yours.*