MCU



U2 must be programmed before being soldered down due to restrictive in-circuit programming requirements. JD_STATUS is PWM-capable GPIO.

Button



MCU must have internal pull-up on BUTTON GPIO.

Status LED



D6
Alternative part
SML-D12D
E6C0603SEAC1UDA
NCD0603O1

Jacdac modules require a status LED.

The LED can be monochrome or multicolor depending on GPIO availability

If using alternative part recalculate the resistor values R2

3V3 Regulator



U1 alternative parts:
ME6212C33M5G 6V 260mV @ 200mA Iout 350mA
NCP114BSN330T1G 5.5V 225mV @ 300mA Iout 300mA

Mounting holes



JACDAC mounting holes are plated through hole, finished diameter of 2.1mm, annular ring of 3.0mm diameter and copper/component keepout of 5.0mm. The mounting holes should be on 2.5mm pitch.

MH1 & MH2 : GND
MH3 : JD_DATA
MH4 : JD_PWR

Mounting holes should have appropriate silkscreen marker, and MH1 should have a pin 1 marker on the top side.

Jacdac modules require mounting holes. Modules mounting holes are electrically connected so that modules can be mounted on top of other PCBs without using cables.

Jacdac connector



D1 clamps JD_DATA to protect MCU.

FB1 reduces EMI.

Jacdac modules with <50mA max current consumption may have more than one edge connector for easy daisy-chaining. Connectors should have separate ESD protection unless they are adjacent.

Use ultra-low capacitance ESD diodes.

R1/C1 form low-pass EMC filter.

ESD diode pair required for each Jacdac connector.

Silkscreen & layout notes

Block name

Design notes

When this PDF is viewed with Adobe Reader, clicking on components shows part numbers and other details.

PROJECT FILENAME JacdackeyboardKey 46.PrjPCB	PROJECT CODENAME JacdackeyboardKey	Microsoft	PROJECT DESCRIPTION Jacdac Keyboard Key using low-cost OTP PADAUK MCU
SHEET FILENAME JacdackeyboardKey 46.SchDoc	LICENCE Attribution 4.0 International (CC BY 4.0)	LAST MODIFIED 10/11/2021 PAGE 1 OF 1 DRAWN BY DG, JD & SH	SHEET DESCRIPTION Complete design REVISION 1.3 PCB ID 46-1.3

Board Outline
Top Assy



Board Outline

Bottom Assy




Keyboard
Key
46-1.3

Fabrication Notes

Board Outline



Top Layer

Board Outline



Bottom Layer

Board Outline



Board Outline

Top Overlay



Board Outline

Bottom Overlay



Board Outline

Top Paste



Board Outline

Bottom Paste



Board Outline

Top Solder (resist)



Board Outline

Bottom Solder (resist)



Board Outline