SITE AUTOMATION

Operations Runbooks

Health checks, troubleshooting, ServiceNow, POA&M and patching - with AAP and, later, ACT

Setup guide for new AAP admins | site-automation 1.50.0 | October 2026

What this is. A step-by-step guide to setting up the site's operations runbooks in Ansible Automation Platform: health checks (system, compliance, MariaDB / MySQL, certificates, patching), troubleshooting, ServiceNow tickets, POA&M status and patching, and later ACT (GenAI). It starts with what each AAP object *is* and walks through every click, saying what each step does, why, and what you should see.

How to read it

New to Ansible or AAP: read chapter 1 first, then do chapter 2 in order. Inventory already in AAP? Chapter 3 replaces the inventory parts of chapter 2. The later chapters are reference: open them when you build a workflow, read a finding, add ACT, change a setting, approve commands or set up the MariaDB / MySQL check.

Every setting, with its default and what it does - and where to put it - is in its own PDF, the *Settings Reference*: keep it open next to this one.

Rendered from `docs/` in the site-automation repository (version 1.50.0). The repository is the source of truth.

Host names and addresses in this guide are placeholders. Copy YAML from the repository files, not from the PDF.

Contents

1. Start here: the pieces and how they fit 15

What the runbooks do . . . 16
The ideas behind Ansible, in plain words . . . 18
The AAP objects, and what each one is for . . . 18
How a health check works, start to finish . . . 19
The findings: the one idea that makes everything modular . . . 20
Where things are . . . 20
The order to do things in . . . 21

2. Setting up AAP, step by step 22

Before you start . . . 22
Step 1. Put the repository in your work Git, with your inventory . . . 22
Step 2. Credential types . . . 23
Step 3. Credentials . . . 24
Step 4. Project . . . 24
Step 5. Inventory (filled from the repository) . . . 25
Step 6. The first job template: Health check . . . 25
Step 7. Run it on one host and read the output . . . 26
Step 8. Tune the thresholds . . . 27
Step 9. The other job templates . . . 27
Step 10. ServiceNow . . . 38
Step 11. Workflows and schedules . . . 39
Step 12. Who can do what . . . 39
If something goes wrong . . . 40

3. Using the inventory you already have in AAP 41

The easy way: your settings files, already named after your groups . . . 41
How variables work in AAP (two minutes) . . . 43
Step 1. Look at what you have . . . 44
Step 2. Create the groups the runbooks use . . . 44
Step 3. Settings for every host (inventory variables) . . . 45
Step 4. Settings for particular groups . . . 46
Step 5. Settings for one host (only when one host is different) . . . 46

Step 6. Use your inventory in the job templates . . . 47
Step 7. Check that it worked . . . 47
Which YAML files in the repository do I change? . . . 47
4. The Linux inventory from IdM 48
Step 1. An IdM user to read with . . . 48
Step 2. Your host groups to the runbooks' groups . . . 49
Step 3. Try it before AAP . . . 50
Step 4. In AAP: the credential type and the credential . . . 50
Step 5. In AAP: the inventory and its source . . . 50
Step 6. Keep it in sync . . . 52
Step 7. Use it . . . 52
Every setting . . . 52
When the sync fails . . . 53
Tested . . . 54
5. Disk space: the report and the tmp cleanup 55
What the report shows . . . 55
What the cleanup deletes . . . 56
Set it up . . . 56
Hand-over . . . 57
6. STIG Manager: health and availability 58
What the health check reads . . . 58
Set it up . . . 59
Settings . . . 60
7. Availability checks 61
How a run decides . . . 61
Availability over time . . . 62
Set it up . . . 62
Settings . . . 62
8. AAP - template variables audit: what belongs somewhere else 63
What it flags . . . 64
The report . . . 66
Set it up in AAP . . . 66
Settings . . . 66

When something goes wrong . . . 67

9. Enclaves: setting up another enclave's AAP - the banner, ACT off, what to change 68

1. Which enclave this AAP serves, and the banner . . . 68
2. ACT (GenAI) . . . 69
3. The credentials . . . 70
4. Paths, addresses and hosts in all.yml (and the group files) . . . 70
5. Images for an air-gapped enclave . . . 72
6. Check it . . . 72

10. ServiceNow: set up, test and verify 73

What you need . . . 73
Step 1. Ask the ServiceNow admins for an API account . . . 73
Step 2. The addresses . . . 74
Step 3. The network path from AAP . . . 76
Step 4. Check from a shell first (optional, fastest) . . . 76
Step 5. The credential in AAP . . . 77
Step 6. Your settings . . . 77
Step 7. The ServiceNow - test ticket template . . . 78
Step 8. Run it: first a dry run, then for real . . . 78
Step 9. Check the ticket in ServiceNow . . . 79
When a step fails . . . 80
MID Servers . . . 80
Self-hosted instance . . . 82
Next . . . 89

11. ServiceNow - ticket insights: months of tickets for management 90

What the page has . . . 91
Sites, directorates and teams (0.97.0) . . . 95
The org map and Custom view (1.8.0) . . . 96
Periods on every page (1.39.0) . . . 100
VIP tickets (1.43.0) . . . 101
ACT (GenAI), and what never reaches it . . . 102
The hand-off paths (0.97.0) . . . 103
Step 1. The account . . . 104
Step 2. The job template . . . 105

Team leads (1.15.0) . . . 106
Your SLAs, priorities and categories . . . 106
Satisfaction (1.16.0) . . . 108
What to act on first . . . 109
The life cycle and the flow (1.9.0) . . . 109
Trends and the report database (1.13.0) . . . 110
The window . . . 111
Every setting . . . 112
The job's output . . . 112

12. The report database: ticket insights' trends, month by month 113

What it keeps . . . 113
Set it up . . . 113
The backfill . . . 116
Is it writing? . . . 116
On the pages . . . 117
The tables and views . . . 118
The ticket store and the ACT cache (1.17.0) . . . 119
Making the tables by hand . . . 121
TLS (optional) . . . 127
The EE and FIPS . . . 127
Watching it . . . 127
Backups and retention . . . 127
When something goes wrong . . . 128
Settings . . . 129
Later . . . 129

13. Workflows and schedules 130

How to build any workflow, click by click . . . 130
Adding ACT to a workflow: what "on fail" means, and where site_act goes . . . 131
Linux workflows . . . 133
Windows workflows . . . 146
Linux and Windows together . . . 149
VMware workflows . . . 150
Horizon workflows . . . 153
Schedules . . . 154

Things that trip people up . . . 157

14. Every job template: what it is, and where its how-to is 158

Linux servers . . . 159
Windows servers . . . 161
Certificates and trust stores . . . 162
VMware (vCenter) . . . 163
Horizon 8 (VDI) . . . 165
Network devices, mail relays and storage . . . 167
Tenable.sc (ACAS) . . . 167
ServiceNow, AAP and the reports . . . 168
Outage documents (AAR and SOP) . . . 169
What one job hands to the next . . . 169

15. Dry runs: try anything, change nothing 171

Where to set it . . . 171
What each template does in a dry run . . . 172
Examples . . . 173
What a dry run cannot tell you . . . 174

16. The runbooks: every check and what to do 175

Health check (playbooks/health_check.yml) . . . 175
Troubleshoot (playbooks/troubleshoot.yml) . . . 192
fapolicyd denials (playbooks/fapolicyd_denials.yml) . . . 193
fapolicyd (playbooks/fapolicyd.yml) . . . 193
Certificate report (playbooks/cert_report.yml) . . . 196
Trust store report (playbooks/trust_report.yml) . . . 197
Windows trust store report (playbooks/win_trust_report.yml) . . . 198
VMware trust store report (playbooks/vmware_trust_report.yml) . . . 198
Certificate renewal: the CSRs (playbooks/cert_renew_csr.yml) . . . 198
POA&M status (playbooks/poam_status.yml) . . . 201
ServiceNow tickets (playbooks/servicenow_tickets.yml) . . . 202
ServiceNow - test ticket (playbooks/servicenow_test_ticket.yml) . . . 202
ServiceNow health (playbooks/servicenow_health.yml) . . . 203
Patch hosts (playbooks/patch_hosts.yml) . . . 203
Apply approved ACT fix (playbooks/act_fix_approved.yml) . . . 206

VMware jobs and reports (playbooks/vm_*.yml) . . . 206
Account lockout (playbooks/ad_lockout.yml) . . . 206
Horizon 8 (VDI) (playbooks/horizon_*.yml) . . . 207
VMware pick lists (playbooks/vm_pick_refresh.yml, vm_snapshot_delete_picked.yml, vm_reboot_picked.yml) 207
Windows hosts . . . 207
Not built yet (and why) . . . 207

17. Adding ACT (GenAI) later 208

How they fit: checks find WHAT, ACT finds WHY . . . 208
The three levels . . . 208
Turn it on . . . 209
Both endpoint formats and :probe (ACT 0.6.19 and newer) . . . 212
ACT for vCenter alarms (it runs on the AAP side) . . . 216
Write your own check (it works with the report, tickets and ACT automatically) . . . 216
Use ACT in a playbook of your own . . . 217
What ACT is told, and what it cannot do . . . 218

18. Windows servers 219

Step 1. WinRM on the servers . . . 221
Step 2. The execution environment . . . 221
Step 3. The credential . . . 221
Step 4. The Windows inventory . . . 222
Step 5. Test the connection . . . 222
Step 6. The job templates . . . 223
Step 7. Workflows and schedules . . . 226
Start small: the pilot order . . . 227
Patching through Software Center . . . 227
ACT on the servers (C:\ProgramData\act) . . . 228
Settings: what each check looks at, and how to change it . . . 229
If something goes wrong . . . 231
Not in this release (next) . . . 231

19. VMware jobs (vCenter): restart, snapshots, VLAN, reports, alarms and ACT 232

Before you start . . . 237
Which VMs a job acts on . . . 240
The templates . . . 240

Snapshots: the report, the cleanup, and the approval workflow . . . 249
Pick lists: choose what to restart, which snapshots to delete . . . 253
Health: every datacenter, cluster and host . . . 256
VMs created: the weekly report . . . 262
Alarms: the report, and ACT's analysis . . . 263
Outage watch: what is down or hung right now . . . 266
Ask a question: plain words, read-only . . . 267
Capacity planning: overall and per cluster . . . 267
Deploy a VM from a ServiceNow ticket . . . 269
Trust stores: vCenter's trusted roots and the ESXi hosts' trusted CAs . . . 270
ESXi security settings (every night): SSH off, timeouts, lockdown - and the vCenter appliance's access . . . 270
The ESXi network check: vmkping, vMotion, MTU, storage latency . . . 273
Certificates of vCenter and the ESXi hosts: incidents and CSRs (weekly) . . . 275
Installing the issued certificates of vCenter and the ESXi hosts (with an approval) . . . 279
Email the report . . . 283
What you see . . . 285
Troubleshooting . . . 285
Limits . . . 297

20. VM outage watch: what is down or hung right now 298

What it looks at . . . 298
What you see . . . 300
Set it up . . . 300
Settings . . . 301
Phase 2 - the response (not built yet) . . . 302
Event-driven, later . . . 302
Troubleshooting . . . 303

21. VM - ask a question: vCenter in plain words, read-only 304

It only reads . . . 304
Set it up in AAP . . . 305
What you can ask about . . . 306
The settings . . . 307
The query . . . 309
What you get . . . 310
When something goes wrong . . . 311

22. VMware ask: the web page at STIG Manager's /ask/, the card's certificate, read-only 312

It only reads . . . 312
How it works . . . 313
Set it up . . . 313
Who asked what . . . 316
Settings . . . 316
When something is wrong . . . 318
Not yet . . . 318

23. Log analysis: the patterns in a group of servers' logs, explained by ACT 320

What it does . . . 320
What it reads, per kind of host . . . 321
The settings . . . 321
Profiles . . . 323
Set it up in AAP . . . 324
Sizes and the GenAI quota . . . 325

24. NetApp ONTAP health report 326

What the report shows . . . 326
Before you start . . . 328
Set it up . . . 329
The hardware inventory . . . 330
Settings . . . 331
Troubleshooting . . . 333
Limits . . . 334

25. Network device certificates: report and renewal 336

Which devices . . . 336
What is due . . . 337
The renewal . . . 337
Templates . . . 338
Troubleshooting . . . 338

26. Trust stores: who still trusts a compromised or dropped CA 339

The list . . . 339
What it reads, on a Linux host . . . 341
The findings . . . 342

Windows . . . 343
VMware . . . 344
Removing them . . . 344
Set it up . . . 346
When the fixes land . . . 346

27. STIG drift: has a server moved away from its checklist? 347

What it reports . . . 348
When OpenSCAP and DISA's checks do not line up . . . 349
On the host . . . 353
STIG Manager: the login and finding each host's asset . . . 353
Setting it up . . . 354
Windows servers . . . 354
The STIG recheck . . . 356
Updating STIG Manager, with an approval . . . 358
Settings . . . 361
Updating Evaluate-STIG . . . 362
Not in this version . . . 362

28. Network performance: is the network slow, and where? 363

What it reports . . . 363
Set it up . . . 364
On the host . . . 365
The hosts' and VMs' drops seen by vCenter . . . 365
Not in this version . . . 365

29. Network device configurations: backup and load 366

Which devices . . . 366
The backup . . . 367
The load . . . 368
Templates . . . 369
Troubleshooting . . . 371

30. Mail relay whitelist: one address per line; add or remove with an approval 372

Format the list: one address per line . . . 373
Remove the addresses that sent no mail . . . 374
What it refuses . . . 376

Set it up (once) . . . 377
Starting it from Orchestrator (or any other tool) . . . 378
Try it without changing anything . . . 379
When something goes wrong . . . 379

31. The certificate inventory: CSV, JSON and SQL Server, for a dashboard 381

What each certificate has . . . 382
Files: CSV and JSON . . . 383
SQL Server . . . 383
Schedule . . . 384
Troubleshooting . . . 384

32. Certificate renewal through the PKI's ServiceNow catalog item 385

What a run does . . . 385
Before you start . . . 386
Step 1 - the item's questions (their internal names) . . . 386
Step 2 - the settings . . . 387
Step 3 - the catalog test . . . 388
Step 4 - the renewals . . . 388
After the PKI issues the certificate . . . 389
When it goes wrong . . . 390
Limits . . . 390

33. Installing the issued certificate: from the request, with an approval 391

What it does . . . 391
A request you name (opened by hand, or after an incident) . . . 393
Never automatic - a person installs it (BY HAND) . . . 393
Held for a person (HELD) . . . 394
When the PKI sends only the .cer: a CA bundle . . . 394
Which service, which key (Linux) . . . 396
Setting it up . . . 397
Put the old certificate back . . . 398
When it goes wrong . . . 399
Limits . . . 400

34. Emailed reports: the formatted email and its look 402

Which jobs email . . . 403

Turning it on . . . 405
Also email the report to (asked at launch) . . . 406
Green or red: when a report finds problems . . . 407
What a report looks like . . . 408
The look: standard, command, portal or glass, your logo, the last runs . . . 408
A workbook attached . . . 410
The classification banner . . . 410
Also on a web page . . . 410
Changing the look . . . 410
Emailing a report from another playbook . . . 410
Troubleshooting . . . 411

35. The report website: every report as a web page 414

The look . . . 414
The classification banner . . . 419
What it writes . . . 419
Where the files go . . . 423
Turning it on . . . 426
The copy job: report templates in any execution environment . . . 427
Using the address in a workflow or another job . . . 429
Troubleshooting . . . 430

36. Secrets: where they live 432

Recommendation . . . 432
Where each secret lives . . . 433
Rules for every playbook in this repository . . . 435
The real trust boundary . . . 436
Keeping secrets out of Git . . . 436
Rotation checklist . . . 437

37. Approved commands: what ACT may run by itself 438

Read this first: two safety rules that you cannot switch off . . . 438
How a command becomes "approved": the three ways . . . 438
Add an approved command, step by step . . . 439
How to verify it worked . . . 441
Reference: what the guard rails are . . . 443

38. The MariaDB and MySQL check, step by step 444

The short version . . . 444
1. Which hosts the check runs on . . . 444
2. Tell it where MariaDB is . . . 445
3. Where to put the settings . . . 446
4. The login: the "MariaDB monitor" credential . . . 446
5. What it checks, and the limits you can change . . . 447
How to verify . . . 449
What was tested, and what was not . . . 449
If it does not work . . . 450

39. Active Directory health report and account lockout 451

What the report shows . . . 451
Before you start . . . 454
Set it up . . . 454
Settings . . . 455
Troubleshooting . . . 457
Limits . . . 457
Without a domain admin . . . 458
Account lockout . . . 462

40. Horizon 8 (VDI): reports, broken desktops, user help, image push 467

Your Horizon version . . . 469
Step 1. The service account and its Horizon role . . . 470
Step 2. The credential type and the credentials . . . 471
Step 3. The job templates . . . 471
Workflow: fix broken desktops, with an approval . . . 473
Golden image check . . . 474
Workflow: push a new golden image, with an approval . . . 475
User help (the service desk) . . . 476
Session cleanup . . . 477
Events report . . . 477
Settings report . . . 477
Sessions report . . . 478
Logon times report . . . 478

Internal VMs report . . . 478
FSLogix profiles report . . . 479
Message users . . . 479
Workflow: ESXi host maintenance . . . 480
Reports and schedules . . . 481
Messages and what to do . . . 482

Appendix: credential types to paste into AAP **483**

ServiceNow API (servicenow_api.yml) . . . 483
ServiceNow node stats login (servicenow_node_stats_login.yml) . . . 483
MariaDB monitor (mariadb_monitor.yml) . . . 484
Keystore password (keystore_password.yml) . . . 484
STIG Manager API (stigman_api.yml) . . . 485
ACT model key (act_model_key.yml) . . . 485
ACT GenAI beta key (act_genai_beta_key.yml) . . . 485
STIG Manager database (stigman_database.yml) . . . 486
TLS certificate (tls_certificate.yml) . . . 486
Container registry login (hosts) (registry_login.yml) . . . 487
Teams webhook (teams_webhook.yml) . . . 487
SMTP relay (smtp_relay.yml) . . . 488
Report website (report_web.yml) . . . 488
Horizon API (horizon_api.yml) . . . 489
Report database (report_database.yml) . . . 490

1. Start here: the pieces and how they fit

Confused by all the moving pieces?
Read HOW_IT_FITS_TOGETHER.md (or its PDF in `docs/pdf/`). It shows what the code, the inventory, the credentials and the survey each do, how a setting travels from a YAML file to a host, and how to update the repository safely.

This repository holds **runbooks**: jobs that check Linux servers and help troubleshoot them. You run them from **Ansible Automation Platform (AAP)**, by hand or on a schedule. This page explains the few ideas you need. SETUP_AAP.md then walks you through the setup, one click at a time.

What the runbooks do

Runbook	What it answers	When it runs
Health check	Is anything wrong on these servers right now? Disk, mounts, services, load/memory, time, network, logging, SELinux, fapolicyd, auditd, accounts, certificates, patching, MariaDB / MySQL	Daily (the "daily" set) and weekly (the "weekly" set)
Database health	Are the MariaDB / MySQL databases (on the host or in podman containers) running, with connection room, no stuck replication, and disk space?	Hourly or daily, on its own
Troubleshoot	Someone reports a problem on a host. What does it look like?	On demand
Certificate report	Which certificates expire soon, on every server, in one list?	Weekly
Trust store report	Which servers (Linux, and Windows with its own template), Java, Python, Node, containers and Go programs - and, with its own VMware template, vCenter and ESXi - still trust a compromised or dropped certificate authority? (TRUST_STORES.md)	Weekly (the check `trust` is in the weekly set), and when a CA incident is announced
STIG drift report	Has a server moved away from its STIG checklist? An OpenSCAP STIG scan of each Linux host against what STIG Manager has as Not a Finding (read-only) and against the host's earlier scans; the scans stay on the hosts (STIG_DRIFT.md)	Weekly, and after patching or a change window
Network performance report	Is the network slow, and where? Latency, loss and jitter from each server to what it depends on, its OCSP responders, its interfaces' drops - against its own usual (NETWORK_PERF.md)	Hourly or daily, and when users say "the network is slow"
POA&M status	Which POA&M items are overdue or due soon? Which open CAT I/II findings have no POA&M item?	Weekly
ServiceNow tickets	Opens or updates a ticket for each problem a check found. Notes the ones that cleared	After every check (as a workflow step)
ServiceNow health	Is ServiceNow answering? Are the MID Servers up, reporting and working - and on their Windows hosts, the MID service, its logs and drive?	Hourly
Patch hosts	Installs updates, and proves every service came back. Reboots only with `automatic_restarts: yes`	Monthly, after an approval

Runbook	What it answers	When it runs
Apply approved ACT fix	Applies exactly the fix a person approved	Only inside a workflow, after an approval
NetApp ONTAP health report	Is any node, disk, port, volume, aggregate, SnapMirror or certificate in trouble on the storage clusters? (NETAPP.md)	Daily
Cisco UCS inventory	Which fabric interconnects, chassis and servers do we have - serial numbers, service profiles, BIOS, CIMC and adapter firmware - and is any of it not operable? (UCS.md)	Monthly
Outage AAR and SOP	Write the after action report of an outage - and an SOP to troubleshoot and fix it, made from the AAR - from a survey, as Word documents with your logo, emailed; ACT can tidy the wording and suggest what is missing (INCIDENT_DOCS.md)	After an outage
VMware jobs	Restart, shut down, snapshot, notes or change the VLAN of VMs through vCenter. Reports: secure boot, datastores, snapshots (with an approved cleanup), alarms and events, and ACT's analysis of the alarms: likely cause, fix and confidence (VMWARE.md)	On demand; the reports daily or weekly
VM outage watch	Is something down or hung right now: hosts, HA, datastores, VMs on a question, hung VMs (no heartbeat AND no answer on the network). Quiet when clean; a report and a ServiceNow incident per problem when not. Watch only for now: it restarts nothing (VM_OUTAGE_WATCH.md)	Every 5 to 15 minutes
VM - ask a question	Ask vCenter in plain words: *all VMs with dbv in the name*, *VMs on datastores under 10% free*, *hosts in maintenance mode*. GenAI turns the question into a query the job checks; the job only reads, and refuses a question that asks for a change (VM_ASK.md)	On demand
VMware ask (a web page)	The same as a page at STIG Manager's /ask/: open it with your card, ask, the answer in seconds - for people without AAP. Read-only; who asked what is kept (VMWARE_ASK.md)	Set up once
Log analysis	Point it at a group of servers (Linux, Windows, a vCenter appliance) or at vCenter and its ESXi hosts: their log lines grouped into patterns, and ACT's likely cause, fix and confidence for each (LOG_ANALYSIS.md)	On demand, or daily


Every check is **read-only**. It looks and reports, and changes nothing. Patching changes servers, and waits for an approval first; the VMware jobs change only what an operator asked for, and never the AAP server's VM.

The ideas behind Ansible, in plain words

- **Host**: a server Ansible connects to, over SSH, the way you would.
- **Inventory**: the list of hosts, sorted into **groups** such as `stigman` (the STIG Manager servers) or `mariadb`. The built-in group `all` holds every host. A group can also carry **settings (variables)**, for example "on the database hosts, the MariaDB container is called servicenow-mariadb".
- **Task**: one step, such as "run `df` and read the result". A **module** is the tool a task uses (`command`, `shell`, `uri`, `set_fact`...).
- **Role**: a folder of tasks that does one job, plus its settings. `roles/check_disk/` is "check the disks". Its settings, with their defaults, are in `roles/check_disk/defaults/main.yml`.
- **Playbook**: the file you run. It says which hosts, and which roles or tasks to run on them. `playbooks/health_check.yml` says "on every host, run the checks I was given".
- **become**: run as root through sudo. The checks need it to read root-only information (the audit log, /etc/shadow).
- **Check mode**: a dry run. Ansible shows what it would change and changes nothing. Every runbook here works in check mode, and the checks give the same answers in both modes.
- **Idempotent**: running it twice does no harm. The second run changes nothing.

The AAP objects, and what each one is for

AAP is a web front end that runs playbooks for you. It keeps the passwords, records every run, and runs things on a schedule. You set up a handful of objects once. Each one points at the next:



The AAP objects you create once. The job template is what you launch; a workflow chains templates; a schedule launches either.

AAP object	What it is	Here
Project	A copy of a Git repository that AAP keeps in sync	`site-automation` (this repository)

AAP object	What it is	Here
Inventory	The hosts and groups, and their settings	`Linux servers`, filled from `inventories/site/` in this repository, or the inventory you already have in AAP (USING_YOUR_AAP_INVENTORY.md), or filled from IdM (IDM_INVENTORY.md)
Credential type	A form for a kind of secret, and how to hand it to the job	`ServiceNow API`, `MariaDB monitor`, `ACT model key`... (`aap/credential_types/`)
Credential	One filled-in form: the actual secret. Nobody can read it back	`Linux ssh (sudo)`, `ServiceNow API`...
Execution environment	The container a job runs in (Ansible, Python, tools)	The **Minimal** execution environment is enough. This repository needs no extra collections
Job template	"Run this playbook, on this inventory, with these credentials" plus the questions to ask (**survey**). This is what you launch	`Health check`, `Troubleshoot`, `Patch hosts`...
Workflow	Job templates chained together. The next step can depend on the last one's result (success, failure, always). It can stop for an **approval**	`Daily health` = Health check, then ServiceNow tickets
Schedule	"Launch this template or workflow at these times"	Daily health every day at 06:00

Three more words you will see:

- **Survey**: the questions a template asks when you launch it, such as "which checks?". Each answer becomes a variable for the playbook.
- **Limit**: run on only some hosts or groups, for example `snowdb01.example.mil` or `mariadb_hosts`.
- **Artifacts**: what a job hands to the next step of a workflow. The health check hands its findings to the ServiceNow step this way (`set_stats` in the playbook).

How a health check works, start to finish

1. You click **Launch** on the *Health check* template (or its schedule fires).
2. AAP syncs the project, starts the execution environment, and connects to each host over SSH with the Machine credential.
3. On each host, each chosen check runs read-only commands and turns what it sees into **findings**. One finding is one thing that is wrong, in plain words. It includes a command you can paste to look further:

```
[CRITICAL] disk: /var is 96% full (critical at 95%), 1.2 GiB free of 40.0 GiB
      look: timeout 60 du -xh --max-depth=2 /var 2>/dev/null | sort -h | tail -15
```

4. The job prints a summary per host and for the whole fleet. It then **fails the hosts that have findings**. The red status is on purpose: it is how a workflow knows it should open tickets (or ask ACT, or ask for approval).
5. In the *Daily health* workflow, the *ServiceNow tickets* step runs next. It opens a ticket for each finding, or updates the ticket that is already open.

The findings: the one idea that makes everything modular

Every check produces the same kind of finding:

Field	Example	Used by
`check`	`disk`	reports, tickets
`id`	`disk:/var`	ServiceNow updates the same ticket every run, instead of opening a new one
`severity`	`critical` or `warning`	pass/fail, ticket urgency
`summary`	`/var is 96% full (critical at 95%)`	people
`hint`	`du -xh --max-depth=2 /var ...`	people, and ACT, which runs it to collect evidence

The report, the ServiceNow tickets and ACT only ever read findings. That is why:

- a new check you write shows up in reports and tickets with no other change;
- ACT works on top of **any** check. Add `use_act=true` and ACT reads the findings and the hint commands' output, then explains the root cause (ADDING_ACT.md).

Where things are

Path	What
`playbooks/`	the files AAP runs (one per job template)
`playbooks/group_vars/`	**your settings**, one file per AAP group: edit these (VARIABLES.md, USING_YOUR_AAP_INVENTORY.md)
`roles/check_*/`	one folder per check. Its settings are in `defaults/main.yml`
`roles/site_findings/`	starts, reports and publishes findings, and decides pass/fail
`roles/servicenow/`, `roles/troubleshoot/`, `roles/patch/`, `roles/poam/`	the other runbooks
`roles/site_act/`	the bridge to ACT (GenAI)
`inventories/example/`	a sample inventory and settings. Copy it to `inventories/site/`
`aap/credential_types/`	the credential types to create in AAP
`poam/poam.csv`	your POA&M list (for the POA&M runbook)
`docs/`	this guide, SETUP_AAP.md, USING_YOUR_AAP_INVENTORY.md, VARIABLES.md, RUNBOOKS.md, MARIADB.md, WORKFLOWS_AND_SCHEDULES.md, JOB_TEMPLATES.md, ADDING_ACT.md, APPROVED_COMMANDS.md; PDFs in `docs/pdf/`

The order to do things in

1. **Set up and run one health check by hand** (SETUP_AAP.md, steps 1 to 8). Your inventory is already in AAP? Use USING_YOUR_AAP_INVENTORY.md for the inventory part. Read its output. Adjust thresholds in your settings files (VARIABLES.md) until the findings are the ones you care about.
2. **Add the other job templates** (step 9) and try each once. Every template, with the link to its how-to: JOB_TEMPLATES.md.
3. **Add ServiceNow** (step 10), and build the *Daily health* workflow (WORKFLOWS_AND_SCHEDULES.md).
4. **Schedule** the workflows.
5. **Later: add ACT** to the runbooks you trust (ADDING_ACT.md).

2. Setting up AAP, step by step

Every step says **what** you are doing, **why**, the **clicks**, and what you should **see** when it worked. Menu names are from AAP 2.7. Older versions (2.5, 2.6) may word a label or a menu differently: follow the meaning, not the exact word. If you have not yet, read START_HERE.md first. It explains the words used here.

Before you start

You need:

- An AAP account that can create projects, inventories, credentials and templates in your organization (an **Organization admin** does it all).
- A **Linux account on the servers** that AAP logs in as, for example `svc_aap`. It needs an SSH key and sudo. With `NOPASSWD` sudo, add it to `check_accounts_nopasswd_allowed`, or the accounts check will report it.
- A **Git repository at work** that AAP can reach (GitLab, Bitbucket, GitHub Enterprise).
- For ServiceNow: an **API account** (step 10).

Step 1. Put the repository in your work Git, with your inventory

> **Already have your inventory in AAP?**
> Then you do not need `inventories/site/`. Push the repository without it (skip items 1-3 below), skip step 5, and follow USING_YOUR_AAP_INVENTORY.md for the groups and settings to add.

What. Copy this repository into your work Git, and create your real inventory in it. (Already pushed an earlier release at work? Update it with `scripts/update-from-release.ps1` in VS Code, as in HOW_IT_FITS_TOGETHER.md, "Updating the repository at work". Then skip to step 2.)

Why. AAP reads playbooks from Git, never from your laptop. The inventory lives in the same repository, so host lists and thresholds are versioned and reviewed like code. Every change has a who, a when and a why.

1. Extract the release zip (right-click › **Extract All**). In the extracted folder, copy the folder `inventories\example` and name the copy `inventories\site`.
2. Edit `inventories/site/hosts.yml`. Replace the example host names with yours and keep the group names: the playbooks use them. A host can be in several groups.
3. Edit `inventories/site/group_vars/all.yml`. These settings apply to every host: the LDAP and SIEM servers each host must reach, the account AAP logs in as (`svc_aap`), and the thresholds. Every setting and its default is listed in VARIABLES_REFERENCE.md. **Two places can hold a setting:** this inventory file (it becomes AAP's *inventory* Variables box) and the project's own settings files `playbooks/group_vars/*.yml` (`all.yml` is only switched-off placeholders; a few group files, such as `stigman.yml` and `aap.yml`, ship real values). If a setting is in both, the project file wins. Use one place per setting: VARIABLES.md explains the order.
4. Put it in your work Git, with VS Code:
   - Create an empty repository on your Git server (for example `site-automation`) and copy its clone URL.
   - In VS Code: **Source Control › Clone Repository** › paste the URL › pick a folder, such as `C:\git\site-automation`.

- Copy everything from the extracted release folder into that folder.
- In **Source Control**: type a message, click **Commit** (answer *Yes* to "stage all changes"), then **Sync Changes** / **Publish Branch**.

The same from a command line: `git add -A`, `git commit -m "site-automation <version>"`, then `git push`.

5. Note the two values AAP needs in step 4: the **clone URL** (the one you pasted above) and the **branch** (shown at the bottom left of VS Code, usually `main`). AAP does not read them from your copy; you type them in once.

You should see the files in your Git server's web page, including `inventories/site/`.

Step 2. Credential types

What. Teach AAP the kinds of secrets these runbooks use, one form per kind.

Why. AAP ships with types for SSH (Machine) and Git (Source Control). The ServiceNow login and the others are custom. A credential type says which fields the form has and how the secret reaches the job. Every type here passes it as an **environment variable** in the execution environment. The playbook must ask for it on purpose, and it never shows in job output or Git.

For each file in `aap/credential_types/` that you need now:

1. **Automation Execution › Infrastructure › Credential Types › Create credential type**.
2. **Name**: the name at the top of the file (for example `ServiceNow API`).
3. **Input configuration**: paste the `inputs:` part of the file, *without* the `inputs:` line.
4. **Injector configuration**: paste the `injectors:` part, *without* the `injectors:` line.
5. Click **Create credential type**.

File	Name	Needed for
`report_database.yml`	Report database	the ticket insights' trends, with `servicenow_insights_db: true` - optional (REPORT_DATABASE.md)
`servicenow_api.yml`	ServiceNow API	tickets, ServiceNow health (step 10), the weekly activity report (SERVICENOW_WAR.md), the ticket insights (SERVICENOW_INSIGHTS.md)
`servicenow_node_stats_login.yml`	ServiceNow node stats login	optional: ServiceNow health on a self-hosted instance whose nodes show their stats page only after a login (`servicenow_node_stats_auth: form`; SERVICENOW_SETUP.md, "The node stats login")
`mariadb_monitor.yml`	MariaDB monitor	the MariaDB check on a containerized database (root login refused there); optional on host installs
`keystore_password.yml`	Keystore password	optional: certs check on a PKCS12 keystore

File	Name	Needed for
`stigman_api.yml`	STIG Manager API	optional: POA&M cross-check with STIG Manager; the STIG drift report's checklist comparison
`act_model_key.yml`	ACT model key	later, for ACT (ADDING_ACT.md): GenAI.mil and Ask Sage keys
`act_genai_beta_key.yml`	ACT GenAI beta key	only for ACT with the GenAI.mil beta provider
`idm_inventory.yml`	IdM inventory	optional: the Linux inventory filled from IdM (IDM_INVENTORY.md)

You should see each new type in the Credential Types list.

Step 3. Credentials

What. Store the actual secrets, once.

Why. This is the only place a password or key is kept. Templates point at the credential by name. Nobody, including you, can read the secret back, and it is never in Git or job output.

Automation Execution › Infrastructure › Credentials › Create credential:

Name	Credential type	Fill in
Linux ssh (sudo)	Machine	**Username** `svc_aap`, **SSH Private Key**, **Privilege Escalation Method** `sudo` (plus the sudo password if sudo asks for one)
site-automation git	Source Control	only if the repository is private: user name and token, or an SSH key
ServiceNow API	ServiceNow API	instance URL, API user, password (step 10)
MariaDB monitor	MariaDB monitor	the read-only database account, for MariaDB **and MySQL**; needed when the database runs in a container (the ServiceNow database), usually needed for MySQL on a host, optional for MariaDB on a host. See MARIADB.md for the setup and the account to ask the DBA for

You should see the credentials listed, with secret fields shown as `ENCRYPTED`.

Step 4. Project

What. Tell AAP where the repository is.

Why. A project is AAP's copy of the repository. Templates pick their playbook from it.

1. **Automation Execution › Projects › Create project**.
2. **Name** `site-automation`. **Organization**: yours.
3. **Execution environment**: **Minimal execution environment** (`ee-minimal`). These runbooks use only modules that come with Ansible itself, so no extra collections or custom execution environment are needed (useful on a disconnected network).

4. **Source control type** `Git`. **Source control URL**: from step 1. **Source control branch/tag/commit**: `main`. Later, pin a release tag such as `v<version>` (the tags are listed on the repository's Releases page). **Source control credential**: `site-automation git` if the repository is private.
5. Tick **Update revision on launch**. Every job then syncs first, so a change you push is used right away.
6. Click **Create project**.

You should see the project's **Last job status** turn **Successful** after a few seconds. If it fails, open the sync job: it is almost always the URL, the branch name, or the credential.

Step 5. Inventory (filled from the repository)

(Skip this step if your inventory is already in AAP: see USING_YOUR_AAP_INVENTORY.md.)

What. Create the `Linux servers` inventory and fill it from `inventories/site/hosts.yml`.

Why. Sourcing the inventory from the project brings in hosts, groups and the settings in `group_vars/`, all at once, and keeps them in step with Git. You do not type hosts into AAP by hand.

1. **Automation Execution › Infrastructure › Inventories › Create inventory › Create inventory**. **Name** `Linux servers`. Click **Create inventory**.
2. Open it › **Sources** tab › **Create source**:
   - **Name** `site inventory from Git`
   - **Source** `Sourced from a Project`
   - **Project** `site-automation`
   - **Inventory file** `inventories/site/hosts.yml`
   - Tick **Overwrite**, **Overwrite variables** and **Update on launch**.
3. Click **Create source**, then **Launch inventory update**. The rocket icon also starts it.

You should see, under **Groups**, `stigman`, `mariadb_hosts`, `patch_hosts`... Under **Hosts** you should see your servers. Open a group: its **Variables** are the ones from `group_vars/<group>.yml`.

Step 6. The first job template: Health check

What. A template that runs `playbooks/health_check.yml`.

Why. A job template is the thing you launch. It fixes which playbook, which inventory and which credentials. Its survey asks which checks to run.

1. **Automation Execution › Templates › Create template › Create job template**.
2. Fill in:

Field	Value	Why
Name	`Health check`	
Job type	Run	(Check also works: the checks read the same way)
Inventory	`Linux servers`	
Project	`site-automation`	
Playbook	`playbooks/health_check.yml`	

Field	Value	Why
Execution environment	Minimal execution environment	
Credentials	`Linux ssh (sudo)` (+ `MariaDB monitor` if you made it)	how AAP logs in
Limit	leave empty, tick **Prompt on launch**	so you can run it on one host
Privilege escalation	ticked	the checks read root-only files

3. Click **Create job template**.
4. **Survey** tab › **Create survey question**:
   - **Question** `Which checks?`
   - **Answer variable name** `health_checks`
   - **Answer type** *Multiple Choice (multiple select)*
   - **Choices**, one per line: `daily`, `weekly`, `all`, `disk`, `mounts`, `services`, `performance`, `time`, `network`, `logging`, `selinux`, `fapolicyd`, `auditd`, `accounts`, `certs`, `patching`, `mariadb`, `mysql`, `database`, `containers`, `stig`, `sso`
   - **Default answer** `daily`. Tick **Required**. Click **Create question**.

Made this survey with an earlier release? AAP never updates a survey for you: open the **Health check** template › **Survey** tab › click the `health_checks` question › **Edit** › add `containers` and `sso` on new lines under **Choices** › **Save**. (`daily` and `all` already include the containers and sso checks without that; the choice is for running one on its own. `stig`, the STIG drift scan, is in no shortcut: add it the same way to run it by name.)

5. Turn the survey **on** (the switch at the top of the Survey tab).

You should see the template in the Templates list with a rocket icon.

Step 7. Run it on one host and read the output

What. Launch the health check on a single server.

Why. Start small. You will see what the checks find on a real host, and whether the thresholds suit you.

1. Click the rocket on **Health check**. **Limit**: one host name. Survey: `daily`. Click **Next**, then **Launch**.
2. The job output scrolls by. The parts to read:
   - `Check disk | run`, `Check services | run`...: each check running (green `ok` lines are normal).
   - `Report | result for this host`: the verdict in plain words. Either `HEALTHY. Checks run: ...` or a list of `[CRITICAL]` / `[WARNING]` findings. Each finding has a `look:` line: a command you can paste on the host to see more.
   - `Report | fleet summary`: one line for all hosts, for example `3 healthy, 1 with findings`.
   - A red `FAIL this host because it has findings` at the end. This is **on purpose**: a job with findings fails, so a workflow can react (open tickets). It does not mean the playbook broke.
3. The **Details** tab shows who launched it, when, and the exact revision of the repository.

You should see a finished job, green if the host is healthy, red with findings otherwise.

Step 8. Tune the thresholds

What. Make the findings match what you care about.

Why. Defaults are a starting point. If a warning is expected on some host, change the setting for that host or group, not the code.

1. Change the setting in the project's settings file `playbooks/group_vars/<group>.yml` (every host: `all.yml`; one host: `playbooks/host_vars/<host>.yml`, create it). This is the place VARIABLES.md recommends, and it wins over the same setting in `inventories/site/group_vars/` or in an AAP group or inventory Variables box. The file name must be the exact group or host name. Examples:

```yaml
check_disk_overrides:
  /var/log/audit: {warn: 70, crit: 85}      # this filesystem: warn earlier
check_services_ignore_failed: ['^dnf-makecache']
site_fail_on: [critical]                    # warnings are reported but do not fail the job
```

(With `[critical]`, a check that could not run, `<check>:check-error`, still fails the host: a check that did not run is not a healthy result.)

2. Commit and push. `playbooks/group_vars/` is read straight from the project, which syncs on launch: nothing else to do. Only if you changed `inventories/site/group_vars/` instead, run the inventory source again in AAP (**Inventories › Linux servers › Sources › Launch inventory update**): those files reach AAP only through the inventory source.
3. Launch the health check again.

You should see the finding gone, or at its new threshold.

Step 9. The other job templates

Create each the same way as step 6: **Inventory** `Linux servers`, **Project** `site-automation`, **Execution environment** Minimal. For the ones that log in to hosts, tick **Privilege escalation** and leave **Limit** empty with **Prompt on launch** ticked. Only the differences are listed. A survey question is *Multiple Choice (single select)* unless it says otherwise.

> **Two templates run on the controller, not on hosts:**
> POA&M status and ServiceNow tickets. For these, do **not** tick Prompt on launch for Limit. A workflow's Limit (for example `patch_hosts`) is passed to every step that prompts for one. These playbooks run on `localhost`, so the Limit would match nothing and the step would silently do nothing, and still show green. **ServiceNow health** needs no `localhost` in a Limit (1.0.0: a host of the Limit stands in for it), but leave its Limit unprompted too: a workflow's Limit would leave its MID Server hosts and nodes unread.

Troubleshoot

On demand, when someone reports a problem. Always launch it with a **Limit**: the host with the problem. Findings do not fail this job.

Field	Value
Playbook	`playbooks/troubleshoot.yml`
Credentials	`Linux ssh (sudo)`

Field	Value
Survey: `ts_area`	"What kind of problem?" Choices: `overview`, `disk`, `performance`, `service`, `network`, `selinux`, `fapolicyd`, `login`, `time`, `logs`, `mariadb`, `mysql`. Default `overview`
Survey: `ts_service`	*Text*, not required. "Service name (for area = service), e.g. nginx"
Survey: `ts_target`	*Text*, not required. "host:port it cannot reach (for area = network)"
Survey: `ts_since`	*Text*. "How far back to read logs". Default `-2h`

Database health - MariaDB / MySQL

The database check on its own, for **MariaDB and MySQL**, installed on the host or in **podman containers** (one, several, found automatically, rootless). Give it to the database team. It only reads: no data is read, nothing is changed. Set the databases up first (MARIADB.md): the container name in a settings file, and the account for the credential.

Field	Value
Name	`Database health - MariaDB / MySQL`
Playbook	`playbooks/database_health.yml`
Credentials	`Linux ssh (sudo)` and `MariaDB monitor` (the read-only database account)
Privilege escalation	ticked
Job type	Run, with **Prompt on launch** ticked, so you can pick *Check* first
Limit	empty, **Prompt on launch** ticked. The job runs on the groups `mariadb_hosts`, `mysql_hosts`, `database_hosts`, `mariadb` and `mysql`; a Limit narrows that to one host or group. A Limit cannot add a server outside those groups: for that, put `target: <group or host>` in the template's **Variables**
Survey	none. (Optional: a *Multiple Choice* `use_act`, choices `no` and `yes`, to add ACT's explanation; then also attach the *ACT model key* credential, ADDING_ACT.md)

Steps: create the template as in step 6, then launch it twice.

1. Launch with **Job type** `Check`. You should see, for every database host, a `MariaDB | status` line such as `MySQL 8.4.11 - container snow-mysql (podman, image ...): up 312.4 h, 23/151 connections ...`, then `HEALTHY` (or a list of findings, each with a command to look further), and at the end `N healthy, M with findings`. *Check* is safe here: the job only reads either way.
2. Launch with **Job type** `Run`. The result is the same. A host with findings shows as failed, so a workflow can open a ticket (workflow 8).

If a host prints `mariadb:connect` with `Access denied`, the credential is missing, its password is not the one this container has (each container has its own root password: the finding names every container that refused it), or the account lacks a privilege: MARIADB.md.

Service watch

Two templates and a workflow: the steps are in SERVICE_WATCH_DEMO.md (Parts 5 and 6). The one field to decide here is which hosts it watches.

Field	Value
Playbooks	`playbooks/service_watch.yml` (*Service watch - check*) and `playbooks/service_fix_approved.yml` (*Service watch - apply approved fix*)
Credentials	`Linux ssh (sudo)`, plus `ACT model key` on the check template
Variables	optional: `target: <group or host>`. Without it the jobs run on the group `stigman` - a **group inside the template's inventory**, not an inventory called stigman (if there is no such group, the job stops and lists the groups the inventory has). To watch the containers of other servers, put that group (or `all`) here, on **both** templates. Which containers are watched on each host is found by itself: every container that should be running, root's and each user's (SERVICE_WATCH_DEMO.md, "Which containers are watched")
Survey	on the workflow: `watch_mode` (`approval` / `self-heal`)

Certificate report

Weekly: one table of every certificate on every host, soonest expiry first.

Field	Value
Playbook	`playbooks/cert_report.yml`
Credentials	`Linux ssh (sudo)` (+ `Keystore password` if you use it)
Survey: `check_certs_warn_days`	*Integer*. "Warn this many days before expiry". Default `30`

Trust store report

Weekly, and when a CA incident is announced: which trust stores still hold a compromised or dropped certificate authority (TRUST_STORES.md).

Field	Value
Playbook	`playbooks/trust_report.yml`
Credentials	`Linux ssh (sudo)`
Variables	`check_trust_extra` for certificates of your own; `check_trust_severity` to change a severity; `check_trust_remove: true` to take the certificates out (run as Check first)

STIG drift report

Weekly, and after patching: each Linux host's OpenSCAP STIG scan against its checklist in STIG Manager (read-only) and against its earlier scans; the scans stay on the hosts (STIG_DRIFT.md).

Field	Value
Playbook	`playbooks/stig_drift_report.yml`
Credentials	`Linux ssh (sudo)`, `STIG Manager API` (the client: your autostig one, or another with `stig-manager:collection:read` and a grant in the collections); `Windows file share` when Evaluate-STIG's answer files are on a share (`check_stig_evaluate_answers`)

Field	Value
Variables	`aap/extra_vars/stig_drift_report.yml`: `check_stig_stigman_api`; each host's `check_stig_stigman_collection` in the inventory (per group or host)

Windows STIG drift report

Weekly, and after patching: Evaluate-STIG on each Windows server - every STIG that applies - each checklist against the server's asset in STIG Manager (read-only) and against its earlier scans; the scans stay on the servers (STIG_DRIFT.md).

Field	Value
Playbook	`playbooks/win_stig_drift_report.yml`
Credentials	`Machine (Windows)` (an administrator: Evaluate-STIG runs as SYSTEM in a one-time scheduled task), `STIG Manager API` (the same as the Linux report)
Variables	`aap/extra_vars/win_stig_drift_report.yml`: `check_stig_stigman_api`; `win_check_stig_evaluate` if Evaluate-STIG is not found; each server's `check_stig_stigman_collection` in the inventory

STIG recheck

After fixing hosts, or before updating STIG Manager: the rules STIG Manager has Open or Not Reviewed for each host checked again on it - only those - and what to update in STIG Manager (read-only); report only (STIG_DRIFT.md). Two templates, as for the drift report.

Field	Value
Playbook	`playbooks/stig_recheck.yml` (Linux), `playbooks/win_stig_recheck.yml` (Windows)
Credentials	as the STIG drift report and the Windows STIG drift report: the machine credential and `STIG Manager API` (Linux: and `Windows file share` with `check_stig_evaluate_answers` on a share)
Variables	`aap/extra_vars/stig_recheck.yml`, `win_stig_recheck.yml`: `check_stig_stigman_api` (required: what to recheck is read from it); the scanner settings of the drift report

For workflow 37, make a copy of each, *STIG recheck - check* (and *Windows STIG recheck - check*), with `check_stig_update_workflow: true` in its Variables.

STIG Manager - update

Workflow 37's (and 40's) step after the approval: it writes the reviews the STIG recheck's (or the checklist import's) check listed to STIG Manager, each only if it is unchanged since the check - and, with `check_stig_update_create_assets`, creates the new assets it listed (its client then needs Manage) - and nothing else (STIG_DRIFT.md).

Field	Value
Playbook	`playbooks/stigman_update.yml`
Inventory	any (it runs on the controller)

Field	Value
Credentials	a second `STIG Manager API` credential: the client that may write reviews (scope `stig-manager:collection`, a grant in the collections). The reports keep their read-only one
Variables	`aap/extra_vars/stigman_update.yml`: none needed when `check_stig_stigman_api` is in `all.yml`. Tick **Prompt on launch** for Job type, for a dry run

STIG Manager - import checklists

Workflow 40's check: the checklists (CKL, CKLB) on your share - VMware's InSpec ones too - matched to STIG Manager's assets (by the host name) and installed STIGs (by their rules); the reviews to write and the new assets, for the approval. Reads only (CKL_IMPORT.md).

Field	Value
Playbook	`playbooks/stigman_ckl_import.yml`
Inventory	any (it runs on the controller)
Credentials	`STIG Manager API` (the read-only one; Full in the collection) and `Windows file share` (Read on the folder)
Variables	`aap/extra_vars/stigman_ckl_import.yml`: `stigman_ckl_import_src`, `stigman_ckl_import_collection`

For workflow 40, make a copy, *STIG Manager - import checklists - check*, with `stigman_ckl_import_workflow: true` in its Variables.

As STIG Manager Watcher (0.76.0: on a schedule, written at once, several collections, the files moved - `stigman_ckl_import_auto`, `stigman_ckl_import_collections`, `stigman_ckl_import_move`): the *STIG Manager API* credential is the client that writes (Full in every collection searched, Manage in the staging one), the *Windows file share* account needs **Modify** on the folder. CKL_IMPORT.md.

Network performance report

Hourly or daily, and when users say "the network is slow": latency, loss and jitter from each Linux host to its targets, its OCSP responders, its interfaces' drops, against its own usual (NETWORK_PERF.md).

Field	Value
Playbook	`playbooks/net_perf_report.yml`
Credentials	`Linux ssh (sudo)`
Variables	`aap/extra_vars/net_perf_report.yml`: `net_perf_targets` (and `net_perf_ocsp`, `net_perf_iperf_pairs`); `target:` the group to measure from

VMware - trust store report

vCenter's trusted root store and each ESXi host's trusted CAs, against the same list, on its own.

Field	Value
Playbook	`playbooks/vmware_trust_report.yml`

Field	Value
Credentials	`VMware vCenter`
Variables	`aap/extra_vars/vmware_trust_report.yml`: `vmware_trust_esxi: false` for vCenter only; `check_trust_remove: true` to delete (run as Check first)

Windows - trust store report

The Windows servers' certificate stores, Java and Python, against the same list (the Windows health check's weekly set runs the check `trust` too).

Field	Value
Playbook	`playbooks/win_trust_report.yml`
Credentials	`Machine (Windows)`
Variables	`aap/extra_vars/win_trust_report.yml`; `check_trust_remove: true` to put the certificates in Disallowed and delete them (run as Check first)

Certificate renewal - CSRs

A new key and a CSR on the host for each certificate that expires (in a file, on a port, in a keystore), with the CSR attached to the certificate's ServiceNow incident (step 3 of workflow 7; RUNBOOKS.md, "Certificate renewal"). It sends no email.

Field	Value
Playbook	`playbooks/cert_renew_csr.yml`
Credentials	`Linux ssh (sudo)`, `ServiceNow API` (+ `Keystore password` if the certificate report uses it)
Variables	`servicenow_assignment_group: <your PKI or Linux team>`: who gets a ticket this job opens (a certificate with no ticket yet). `cert_skip_hosts: [<your Satellite and Capsules>]` if they are not in a group `sat` (left out of the report too). `cert_renew_skip_hosts: [<IdM, AAP ...>]` for servers renewed by hand: reported, never a CSR. `cert_renew_self_signed: true` for CSRs for self-signed certificates too (never postfix's placeholder). `cert_renew_attach_ext: txt` when your instance refuses `.csr` attachments (a refused one is tried as `.txt` anyway). Better in `all.yml`, so the certificate report gets the same
Job type	try it as **Check** first: it makes and sends nothing

Windows: *Windows certificate renewal - CSRs* (`playbooks/win_cert_renew_csr.yml`) does the same on Windows servers with `certreq`, with the Windows machine credential: WINDOWS.md.

Certificate install - check / approved, and the restore

With the CSRs ordered from the PKI's catalog item, the issued certificate is installed from that request after an approval: *Certificate install - check* (`playbooks/cert_install_check.yml`: `Linux ssh (sudo)`, `ServiceNow API`) in a workflow with an **Approval** (Run on fail) and *Certificate install - approved* (`playbooks/cert_install_approved.yml`: the same credentials, the same inventory, **no** Limit and **no** Prompt on launch for Variables). *Certificate restore* (`playbooks/cert_restore.yml`) puts an old certificate back. The Windows three: `win_cert_install_check.yml`, `win_cert_install_approved.yml`, `win_cert_restore.yml`, with the Windows machine credential. The templates, the workflow and the settings: CERT_INSTALL.md. vCenter and the ESXi hosts: *VMware - certificate request* (`playbooks/vmware_cert_request.yml`, on demand) and *VMware - certificate install - check / approved* (`playbooks/vmware_cert_install_check.yml`, `vmware_cert_install_approved.yml`: `VMware vCenter`, `ServiceNow API`), workflow 39: VMWARE.md.

The PKI sends only the .cer? Keep the DoD PKI's CA bundle in your repository (`playbooks/files/dod_pki_bundle.p7b`) and set `cert_install_ca_bundle: files/dod_pki_bundle.p7b` in `all.yml`: the three checks (Linux, Windows, VMware) complete the chain from it. *PKI - DoD bundle check* (`playbooks/pki_bundle_check.yml`, no credential, weekly) emails you a newer bundle when DISA publishes one: CERT_INSTALL.md.

Network device certificate report / renewal

The certificates of switches, firewalls, printers, iLO / iDRAC ... read from the controller: no login to the devices. Both run on the controller (Limit empty, **no** Prompt on launch). Report: `playbooks/net_cert_report.yml`, no credential. Renewal: `playbooks/net_cert_renew.yml`, `ServiceNow API` (and a Machine credential for the Cisco devices with `net_cert_cisco_csr`). The devices, the templates and the settings: NETWORK_CERTS.md.

Network config backup / load

Cisco IOS / IOS-XE (its CLI: a Machine credential that logs in to the devices) and Palo Alto PAN-OS (its XML API from the controller: the `Palo Alto PAN-OS API` credential). Backup: `playbooks/net_config_backup.yml`, with the `Network config git repository` credential and `net_config_git_repo` - a **private, internal** repository: the configurations hold the devices' secrets (or `net_config_store: share`). Load: `playbooks/net_config_load.yml`, with `ServiceNow API` - it needs a change request in Implement (`net_config_change`); run it in Check first. The devices, the templates and the settings: NETWORK_CONFIG.md.

Certificate inventory (CSV / SQL Server)

Not a template: a setting of every certificate report (`cert_inventory_files`, `cert_inventory_sql`). For the SQL Server table, add the *SQL Server (certificate inventory)* credential to each report template: CERT_INVENTORY.md.

POA&M status

Weekly. Runs on the controller and reads `poam/poam.csv` from the project.

Field	Value
Playbook	`playbooks/poam_status.yml`
Credentials	none (+ `STIG Manager API` for the cross-check)
Privilege escalation	not needed

Field	Value
Limit	empty, and **no** Prompt on launch (it runs on the controller)
Survey: `poam_stigman_api`	*Text*, not required. "STIG Manager API URL (blank = skip the cross-check)"

ServiceNow - test ticket

Run once before the tickets step, and again after a password or certificate change. It opens a test incident, reads it back, adds a work note and resolves it, with PASS / WARN / FAIL for each step (SERVICENOW_SETUP.md). Runs on the controller.

Field	Value
Playbook	`playbooks/servicenow_test_ticket.yml`
Credentials	`ServiceNow API`
Job type	Run, with **Prompt on launch** ticked, so you can pick *Check* (a dry run: it only logs in and reads)
Privilege escalation	not needed
Limit	empty, and **no** Prompt on launch (it runs on the controller)
Survey	none

ServiceNow - catalog test

Only with `cert_renew_servicenow: catalog` (the certificate renewals order the PKI's catalog item instead of opening incidents). It finds `cert_renew_catalog_item`, lists its questions by their internal names and checks `cert_renew_catalog_variables` against them, PASS / FAIL per step; `servicenow_catalog_test_order: true` also orders it once with a test CSR (CERT_RENEWAL_CATALOG.md). Runs on the controller.

Field	Value
Playbook	`playbooks/servicenow_catalog_test.yml`
Credentials	`ServiceNow API` (the account that will order)
Variables	`cert_renew_catalog_item: <the item's name or sys_id>` - the rest: aap/extra_vars/servicenow_catalog_test.yml
Limit	empty, and **no** Prompt on launch (it runs on the controller)
Survey	none

ServiceNow tickets

Only useful as a workflow step after a check. Runs on the controller.

Field	Value
Playbook	`playbooks/servicenow_tickets.yml`
Credentials	`ServiceNow API`

Field	Value
Privilege escalation	not needed
Limit	empty, and **no** Prompt on launch (it runs on the controller)
Survey	none

ServiceNow health

Hourly. The instance's view runs on the controller; the MID Server hosts are read over WinRM (SERVICENOW_SETUP.md).

Field	Value
Playbook	`playbooks/servicenow_health.yml`
Inventory	your **Windows** inventory, with the MID Server hosts in a group `servicenow_mid_hosts` (without that group: any inventory, the instance's view only)
Credentials	`ServiceNow API`, and the Windows inventory's `Machine (Windows)` credential
Privilege escalation	not needed
Limit	empty, and **no** Prompt on launch (it runs on the controller)
Survey	none
Variables	`servicenow_health_part: mids` when a second template reads a self-hosted instance's nodes (below)

ServiceNow health - nodes

Only for a self-hosted instance: its front-end nodes, its database host and the cluster, hourly, in the same report as the MID Servers' template's (SERVICENOW_SETUP.md).

Field	Value
Playbook	`playbooks/servicenow_health.yml`
Inventory	your **Linux** inventory, with the groups `servicenow_nodes` and `servicenow_db_hosts` (no `servicenow_nodes` group: the nodes in the Limit)
Credentials	`ServiceNow API`, `Linux ssh (sudo)`, `MariaDB monitor`
Privilege escalation	ticked
Limit	empty (one node: its name - nothing else is contacted; with no `servicenow_nodes` group: the nodes, `node01,node03`)
Variables	`servicenow_health_part: nodes`
Survey	none

Patch hosts

Monthly, inside the *Patch with checks* workflow. Run it as *Check* first: it lists what would be updated and changes nothing.

Field	Value
Playbook	`playbooks/patch_hosts.yml`
Credentials	`Linux ssh (sudo)`; and a **VMware vCenter** credential with `patch_snapshot: true` (a snapshot of each VM before it is patched: RUNBOOKS.md)
Job type	Run, with **Prompt on launch** ticked, so you can pick *Check* (a dry run)
Variables	**required**: `target: <group>`, the name of a **group (or host) inside the inventory** - not the inventory's own name. For example `target: stigman`, or `target: all` when the template's inventory holds only the servers to patch. Without it the job looks for a group called `patch_hosts`, and stops with a message that lists the groups your inventory does have
Survey: `patch_security_only`	"Security updates only?" Choices `false`, `true`. Default `false`
Survey: `automatic_restarts`	"Reboot hosts automatically when the updates need it?" Choices `no`, `yes`. Default `no` (no automatic restarts: the job lists the hosts that need a reboot)
Survey: `patch_serial` (optional)	"How many hosts at a time?" *Integer*, minimum 1. Default `1`. Only here or in Variables: in `all.yml` it does nothing
Survey: `patch_snapshot` (optional)	"VMware snapshot of each VM before it is patched?" Choices `false`, `true`. Needs the VMware vCenter credential

Apply approved ACT fix

Only inside the approval workflow (ADDING_ACT.md). Create it when you add ACT.

Field	Value
Playbook	`playbooks/act_fix_approved.yml`
Credentials	`Linux ssh (sudo)` (no ACT key: it runs the approved commands itself)
Job type	Run, with **Prompt on launch** ticked, so a workflow can run it as *Check* (a dry run that only shows what it would run)
Variables	leave **Prompt on launch** unticked
Survey	none

VMware jobs and reports

They run against vCenter, not your hosts, and have their own setup: the VMware execution environment, a vCenter credential, one template per job. Follow VMWARE.md; the emails are in EMAIL_REPORTS.md. The VM deploy from a ServiceNow ticket has a guide of its own, setup included: VM_DEPLOY_GUIDE.md.

VMware pick lists (choose what to restart, which snapshots to delete)

Three templates - `VM - refresh the pick lists` (`playbooks/vm_pick_refresh.yml`, scheduled every 30 minutes, with the **VMware vCenter** and the **Red Hat Ansible Automation Platform** credentials), `VM - delete picked snapshots` and `VM - restart picked VMs` - and two workflows (plan, approval, the same template again) whose survey has the multiple-select question the refresh fills. The AAP credential's user needs the **Admin** role on those workflows. Click by click: VMWARE.md, "Pick lists"; the workflows: WORKFLOWS_AND_SCHEDULES.md, 26 and 27.

AAP - report email question ("Also email the report to")

One template - `AAP - report email question` (`playbooks/aap_email_question.yml`), with only the **Red Hat Ansible Automation Platform** credential (its user: **Admin** on the report templates and their workflows), any inventory, no Limit. Run it with **Check** first, then for real, once all your report templates exist (and again when you add one): it adds the optional box **Also email the report to** to every report template's survey and to the workflows that run them. What it does and what people can type: EMAIL_REPORTS.md, "Also email the report to".

AAP - set execution environment

One template - `AAP - set execution environment` (`playbooks/aap_ee.yml`), with only the **Red Hat Ansible Automation Platform** credential (its user: **Admin** on the job templates, and **Use** on the execution environment), any inventory, no Limit. It puts one execution environment on many job templates at once, after you add a new one to AAP - instead of editing each template. In its Variables (`aap/extra_vars/aap_ee.yml`):

- `aap_ee_name`: the execution environment, as AAP names it (*Automation Execution* > *Infrastructure* > *Execution Environments*), or its ID when two have that name;
- which templates, at least one of: `aap_ee_project` (your site-automation project's name: its templates), `aap_ee_from` (only those on these EEs now, e.g. `[Minimal execution environment]`), `aap_ee_templates` (by name or ID); `aap_ee_exclude` leaves some out - jobs that need another EE, such as the network config jobs for Palo Alto when your all-in-one EE has no Palo Alto.

Launch it with Job type **Check** first: it lists every template it would change, from which EE to which, and the EE's image - nothing is changed. Then for real. A template with no EE set uses the project's or organization's default: it is listed and left as it is, unless `aap_ee_from` has `none`. A name that matches nothing - a misspelled exclude, say - or two templates changes nothing at all: the job lists what it would change, and fails.

A rebuild: build and push the EE with the next tag (`PUSH=hub.example.mil bash build-ee.sh all-in-one 3`), then run this job with `aap_ee_name` and `aap_ee_image` (the new image, `hub.example.mil/site-ee-all:3`) - Check first: it changes that EE's **Image**, and every template already on it runs the new image; no template need be picked (add `aap_ee_project` to move the others onto it in the same run). The image it has now is refused: an execution node that has pulled a tag keeps it, so a rebuild pushed under the same tag would never reach the jobs. Its user needs **Admin** on the execution environment for this. (By hand: change the EE's **Image** in AAP.)

Report website - copy

Only when report templates run in an execution environment that cannot reach the report website's server (no WinRM or Kerberos in it) and `report_web_copy: true` is in `all.yml`. One template - `Report website - copy` (`playbooks/report_web_copy.yml`) - in the execution environment your Windows jobs use, with the inventory that has the web server (no Limit), its Machine credential (an account with Modify on the folder) and a **Red Hat Ansible Automation Platform** credential (its user: **Organization Auditor** on the report templates' organizations). *Concurrent jobs* off. Run it with **Check** first (it lists what it would copy), then for real, then give it a schedule (every 15 minutes). WEB_REPORTS.md, "The copy job".

NetApp ONTAP health report

It reads the storage clusters' REST API, not your hosts: a read-only ONTAP account, a NetApp ONTAP credential, one template. Follow NETAPP.md.

Cisco UCS inventory

It reads UCS Manager's XML API, not your hosts: a read-only UCS Manager account, a Cisco UCS Manager credential, one template. Follow UCS.md.

Active Directory - account lockout

For the service desk: is an account locked out, and which computer is locking it out (the DCs' Security logs), with an optional unlock. The Windows inventory and execution environment, an account that may read the DCs' Security logs, a survey that asks for the account, **Execute** for the service desk team. Follow ACTIVE_DIRECTORY.md.

Horizon 8 (VDI) jobs

They read a Connection Server's REST API, not your hosts: an AD account with a Horizon role, a "Horizon API" credential, one template per job, two workflows with an approval. Follow HORIZON.md; run *Horizon - API test* first.

Try each one

With a Limit of one host:

- **Troubleshoot**: `ts_area` = `disk`. Each command's output appears under a `### what it shows` line.
- **Patch hosts**: Job type **Check**. It lists what would be updated and changes nothing.
- **Certificate report**: read the table under `All certificates on all hosts, soonest expiry first`.

Step 10. ServiceNow

What. An API account, its credential, and a test ticket that proves it works.

Why. The tickets step and the ServiceNow health check use ServiceNow's REST Table API with a user name and password. No plugin or collection is installed.

The whole setup, step by step, is in SERVICENOW_SETUP.md: the account to ask for (with a request you can copy), the instance URL and every API call, the network path (firewall, proxy, the DoD CA), the credential, the settings, the test ticket, and how to check the ticket in ServiceNow. In short:

1. Ask the ServiceNow admins for an **integration account** (web service access only) with:
   - `itil` (or a role that can create and update incidents);
   - `mid_server` (or read on `ecc_agent`, `ecc_queue` and `ecc_agent_issue`), if you want the MID Server check.

2. Create the **ServiceNow API** credential (step 3) with the instance URL, for example `https://servicenow.example.mil`, and the account.
3. In your settings file (`playbooks/group_vars/all.yml`; the example inventory's `inventories/site/group_vars/all.yml` already has these two lines, so change the value in one place only), set who gets the tickets:

```yaml
servicenow_assignment_group: Linux Operations   # a group that exists in ServiceNow
servicenow_min_severity: warning                # or critical: tickets for critical findings only
```

4. Create **ServiceNow - test ticket** (step 9) and launch it, first as *Check*, then as *Run*. **You should see** six steps that say PASS, and a link to the test incident. It is resolved by the same job.
5. Launch **ServiceNow health** once: `API answers in N s`, then the MID Servers and their status. With the Windows inventory (a group `servicenow_mid_hosts`) and its Machine (Windows) credential, it checks the MID Server hosts too (SERVICENOW_SETUP.md).
6. Build the *Daily health* workflow (WORKFLOWS_AND_SCHEDULES.md). Its tickets step then runs after every check.

Try it safely first: launch the workflow **without** the ServiceNow API credential on the tickets template. The step then only prints `NOT CONNECTED - what would be opened` and sends nothing.

Step 11. Workflows and schedules

See WORKFLOWS_AND_SCHEDULES.md: *Daily health*, *Weekly compliance*, *Patch with checks*, *Fix with approval (ACT)*, and when to schedule each.

Going further, once the basics work:

- ACT (the model): ADDING_ACT.md. If a model answers `HTTP 400`, see its section Both endpoint formats and `:probe`.
- Letting ACT run fixes you trust without asking: APPROVED_COMMANDS.md.
- Every setting you can change, and where to put it: VARIABLES.md and VARIABLES_REFERENCE.md (in print: the *Settings Reference* PDF).
- MariaDB and MySQL checks (also in podman containers): MARIADB.md.

Step 12. Who can do what

Open a template or workflow › **User Access** (or **Team Access**) › **Add roles**:

Role	Can
Execute	launch it (and answer its survey)
Approve	approve or deny its approval steps (workflows)
Read	see it and its job output
Admin	change it

For example, give the help desk **Execute** on *Troubleshoot*, and only the server team **Execute** on *Patch hosts* and **Approve** on the patch workflow.

If something goes wrong

You see	It means	Do
Project sync fails	wrong URL, branch or Git credential	open the sync job and read the last lines
`UNREACHABLE! ... Permission denied (publickey)`	SSH key or user wrong for that host	check the Machine credential; test `ssh svc_aap@host` from a workstation
`Missing sudo password` / `a password is required`	sudo wants a password	put it in the Machine credential (Privilege Escalation Password)
`Unknown check(s): ...`	a survey choice that is not a check name	fix the survey choices (step 6)
`the <name> check could not run: ...`	that check hit an error. The others still ran	the message says why, often a missing command such as `semanage`
`skipped: the MariaDB/MySQL check is off for <host>`	the database check only runs on database hosts	add the host to `mariadb_hosts`, `mysql_hosts` or `database_hosts` in the inventory, or name its container (MARIADB.md)
Findings you do not care about	defaults do not fit that host	step 8: change the setting for its group or host
`NOT CONNECTED - what would be opened`	the tickets template has no ServiceNow API credential	attach it (step 10)
Tickets step fails: `No check results reached this job`	the check step before it failed before checking any host, or it was launched on its own	read the first red job in the workflow; run the tickets step only inside a workflow
`The job's Limit (...) leaves out localhost`	the job does its work on the AAP side (`localhost`) - the network config and network certificate jobs and the mail relay jobs: a Limit without `localhost` would skip it and end green. The other jobs need no `localhost` in a Limit (*ServiceNow health* since 1.0.0)	add `,localhost` to the Limit (`sw01,localhost`), or clear the Limit (the network jobs: `net_config_only`, `net_cert_only`)
A controller step (tickets, POA&M) shows `skipping: no hosts matched`	its template prompts for a Limit and the workflow passed one	untick Prompt on launch for Limit on that template (step 9)
A VMware job or report fails	see the troubleshooting tables	VMWARE.md, "Troubleshooting"
No email, or an email error	see the troubleshooting table	EMAIL_REPORTS.md, "Troubleshooting"

3. Using the inventory you already have in AAP

Your RHEL hosts are enrolled in IdM?
AAP can fill the Linux inventory from IdM and keep it in sync, its groups from your IdM host groups: IDM_INVENTORY.md. The groups and settings below apply to it the same.

You imported your inventory into AAP. You do not need `inventories/site/` in Git, and you can skip the Git inventory parts of SETUP_AAP.md (the `cp inventories/example ...` in step 1, and all of step 5). Your hosts and groups stay in AAP. Your **settings** can go in either of two places, and you can use both as long as **one setting lives in one place**:

- **this project's settings files** in `playbooks/group_vars/` (edited in VS Code, reviewed in Git, never overwritten by an update): the next section; or
- **AAP's Variables boxes** (inventory, group, host): the steps after it. What you paste there is YAML, and the blocks to paste are below.

Which place wins when a setting is in both, and the full list of places, is in VARIABLES.md. Every setting and its default: VARIABLES_REFERENCE.md.

The runbooks need two things from your inventory:

1. **Groups**: which hosts are which (steps 1-2). The safety lists are built in and already cover the usual group names (`aap`, `aap_hosts`, `sat`, `idm`, `netapp`, `netapp_console_hosts`...).
2. **Settings (variables)**: your LDAP server, your SIEM, the account AAP logs in as, the ServiceNow assignment group... (steps 3-5).

The easy way: your settings files, already named after your groups

The repository has one settings file per AAP group, in `playbooks/group_vars/`. **The file name is the group name**: `mariadb.yml` applies to the hosts in AAP group `mariadb`, and `all.yml` to every host. Ansible reads these files by itself on every run, and the hosts and groups stay in AAP. **If your group has another name, copy the file to your group's name** (for example `mariadb.yml` to `mariadb_hosts.yml`, `aap.yml` to `aap_hosts.yml`, `netapp.yml` to `netapp_console_hosts.yml`, which are the names the example inventory uses). A file for a group your inventory does not have is never used, without any error. The files are:

File	For AAP group	What is in it
`all.yml`	every host (and the ServiceNow / POA&M jobs)	placeholders, all switched off: the safety lists (already built in), ACT provider and models, LDAP/log server, service account, ServiceNow assignment group
`stigman.yml`	`stigman`	the containers service watch watches (`stigman`, `nginx`); the web certificate
`mariadb.yml`, `mysql.yml`	`mariadb`, `mysql`	placeholders: turn the database check on, and the container's name (MariaDB or MySQL; MARIADB.md)
`aap.yml`, `sat.yml`, `idm.yml`, `logstash.yml`	the same names	disk limits, certificates, services that must run

File	For AAP group	What is in it
`netapp.yml`	`netapp`	nothing yet (the group is protected by the built-in lists)
`rhel8_all.yml`	`rhel8_all`	a placeholder for Python 3.9 (only with a newer AAP)

To change a setting:

1. Open the file in VS Code (for example `playbooks\group_vars\mariadb.yml`).
2. A line that starts with `#` is **off**. To turn a placeholder on, delete the `#` in front of it (and in front of the lines that belong to it), and replace `CHANGE-ME` with your value. Keep the indentation exactly as shown: spaces, never tabs.
3. **Commit** and **Sync Changes**. AAP uses it on the next run: the project syncs itself when **Update revision on launch** is ticked.

Example (the full guide, with several containers and rootless ones, is MARIADB.md): MariaDB runs in a container called `snow-mariadb`. In `mariadb.yml`, change

```
check_mariadb_enabled: true
# check_mariadb_container: CHANGE-ME
```

into

```yaml
check_mariadb_enabled: true
check_mariadb_container: snow-mariadb
```

A group that has no file yet (`sn_prod` here is only an example name; use one of yours): create `playbooks/group_vars/sn_prod.yml` with the settings for it. The same name as the AAP group, `.yml` at the end. For one host only: `playbooks/host_vars/<host name>.yml` (create the folder).

One thing the files cannot do: choose which hosts a template runs on. That is decided before any setting is read. Each playbook therefore has a built-in choice, and the job template's own **Variables** box (the *Extra variables* on its Details page, not the inventory's) can change it with one `target:` line:

Job templates	Variables box empty: runs on	To run on something else
Health check, Troubleshoot, Certificate report, Apply approved ACT fix	**every host** in the template's inventory (the built-in group `all`)	one run: the **Limit** at launch (tick **Prompt on launch** next to Limit). Always: `target: "rhel8_all:rhel9_all"`
Database health - MariaDB / MySQL	the groups `mariadb_hosts`, `mysql_hosts`, `database_hosts`, `mariadb`, `mysql`	`target: <group or host>` (a Limit only narrows those groups; it cannot add a server outside them)
Service watch, Service watch - apply approved fix, STIG Manager - deploy	the group `stigman`	`target: <group>`
VMware ask - deploy	the group `vmware_ask`	`target: <group or host>`

Job templates	Variables box empty: runs on	To run on something else
Patch hosts	the group `patch_hosts` only (no such group: the job stops and lists your groups)	**always set it**, for example `target: "rhel8_all:rhel9_all"`, and pick the hosts with the Limit at launch. `target` is a group or host **inside** the inventory, never the inventory's own name

`target` and the Limit take group names, host names, or several joined with `:`. `stigman:mariadb` means either group, `rhel9_all:&sn_prod` only hosts in both, and `rhel9_all:!sn_dev` all of `rhel9_all` except `sn_dev`. Put a space after `target:`, quote a value that has a `:` in it, and use the group name exactly as the inventory's **Groups** tab shows it (`rhel9_all`, not `rhel9`).

Is every host in this inventory a Linux server? If some are not (firewalls, switches, appliances), an empty Variables box tries them too: they show as failed, and in a workflow that opens ServiceNow tickets each of them gets a ticket (a host that never reports is ticketed), on every run. Then put `target: "rhel8_all:rhel9_all"` on those templates **before** you schedule anything.

These files are yours. The update script adds a settings file you do not have yet, and never changes one you already have. A new release can therefore never overwrite your settings.

Or put the same lines in AAP instead. Everything below explains the AAP Variables boxes, which take exactly the same lines. **Keep each setting in one place.** If the same setting is in both a file here and an AAP *group* or *inventory* box, **the file here wins** (every job prints a note when that happens). The exception is one host: a *host's* Variables box in AAP beats a group file, and only a `playbooks/host_vars/` file beats the host box. Full order: VARIABLES.md.

How variables work in AAP (two minutes)

A variable is a setting with a name, such as `check_disk_warn_pct: 85`. Where you type it decides which hosts get it:

Where in AAP	Applies to	The Git-file equivalent
Inventories › your inventory › Edit inventory › Variables	every host in the inventory	`group_vars/all.yml`
… › Groups › a group › Edit group › Variables	the hosts in that group (and in its child groups)	`group_vars/<group>.yml`
… › Hosts › a host › Edit host › Variables	that one host	`host_vars/<host>.yml`

- **Inside AAP the more specific one wins**: host beats group, a child group beats its parent group, and a group beats the inventory. A survey answer, or the template's own **Variables**, beats all of them. **Files in this project's `playbooks/group_vars/` beat the AAP group and inventory boxes** (see the previous section).
- **Anything you do not set uses the default** in `roles/<role>/defaults/main.yml`. Every setting is explained in VARIABLES_REFERENCE.md. Do not edit the role files: set the value in a settings file or in AAP instead. A new release would overwrite edits in the roles, but never your settings files or AAP variables.

- The boxes take YAML. Keep the indentation exactly as shown (spaces, not tabs). AAP refuses to save YAML it cannot read.

Step 1. Look at what you have

Inventories › your inventory: open the **Groups** tab, then the **Hosts** tab. Write down which of your groups (or hosts) are:

- all your Linux servers;
- the AAP server(s);
- the NetApp Console host;
- the STIG Manager host(s);
- the ServiceNow database host(s);
- the ServiceNow MID Server host(s), in the Windows inventory (the ServiceNow health job reads them);
- the servers monthly patching may touch.

On the old ansible-core machine, `ansible-inventory -i <your inventory> --graph` prints the same tree.

Step 2. Create the groups the runbooks use

A host can be in many groups. Creating these groups leaves your existing groups as they are.

Create group	Put in it	Why	Needed?
`aap_hosts`	the AAP server(s)	**safety**: ACT never fixes anything here by itself, and patching never reboots it	**yes**
`netapp_console_hosts`	the NetApp Console host	**safety**: ACT only diagnoses here (vendor-managed)	**yes**, if you have one
`no_patch`	the groups `aap_hosts` and `netapp_console_hosts` (as children)	**safety**: *Patch hosts* skips these even when a job targets them	**yes**
`patch_hosts`	the servers monthly patching may touch	*Patch hosts* only patches these	only for patching
`mariadb_hosts`, `mysql_hosts`, `database_hosts`	the database host(s), MariaDB or MySQL (any of the three, or the groups `mariadb` / `mysql`; the check treats them alike)	the database check runs here, and the **Database health** template targets these by default	only for the database check
`stigman`	the STIG Manager host(s)	service watch and STIG Manager deploy run here	only for those
`vmware_ask`	the VMware ask page's server	VMware ask - deploy runs here	only for it

The clicks:

1. **Inventories › your inventory › Groups › Create group**. Type the **Name** (exactly as in the table), then **Create group**.
2. Add hosts: open the new group › **Hosts** tab › **Add existing host** › tick the hosts › **Add**.

3. Or add one of your groups inside it: open the new group › **Related Groups** tab › **Add existing group** › tick your group › **Add**. Its hosts are now in the new group too.

Keep your own names instead? If you already have, say, an `aap` group and do not want a second group, tell the runbooks your names. Put these in the inventory **Variables** (step 3). A list you write **replaces** the shipped one, so repeat every name you want kept; `aap` and `aap_hosts` are always protected, whatever you write:

```yaml
site_act_diagnose_only_groups: [aap, netapp]   # ACT never fixes these
patch_never_reboot_groups: [aap]               # patching never reboots these
patch_never_patch_groups: [aap, netapp]        # patching skips these
```

Updated from 0.4.1 or older? Your `playbooks/group_vars/all.yml` then still sets these three lists (and `site_act_provider`, `site_act_models`) as real lines, and that file silently wins over the inventory Variables box. Open it and put `#` in front of those lines (or delete them), or make your change there instead. The job's `NOTE - settings in this project's files win ...` line lists what the file still sets.

The checks run on every host of the inventory. To keep them to your Linux servers, put `target: linux_servers` (your all-Linux group) in the **Variables** of the Health check, Troubleshoot, Certificate report and Apply approved ACT fix templates.

Step 3. Settings for every host (inventory variables)

Inventories › your inventory › Edit inventory › Variables. If something is already there, add below it; do not delete what is there. Paste, then change every line marked `CHANGE`:

```
---- what every host must be able to reach, from itself ----
check_network_dns_names: [ldap.yoursite.mil]              # CHANGE: names that must resolve
check_network_tcp:                                        # CHANGE: services every host needs
  - {name: LDAP, host: ldap.yoursite.mil, port: 636}
check_logging_remote:                                     # CHANGE: your SIEM / log collector
  - {name: SIEM, host: siem.yoursite.mil, port: 6514}

# ---- the account AAP logs in as ----
check_accounts_nopasswd_allowed: [svc_aap]                # CHANGE: your AAP service account
check_accounts_expiry_watch: [svc_aap]                    # CHANGE: the same account

# ---- STIG ----
check_fapolicyd_required: true                            # false if some hosts do not run
                                                          # fapolicyd

# ---- where tickets go ----
servicenow_assignment_group: Linux Operations             # CHANGE: a group that exists in
                                                          # ServiceNow
servicenow_min_severity: warning                          # or critical: tickets for critical
                                                          # only
```

The ACT provider and models are **not** set here: they are chosen in `playbooks/group_vars/all.yml` (lines ready as comments) or per template (ADDING_ACT.md, step 2). Do not also set them here: if the file ever sets them, the file wins and the value here is ignored.

Not sure about a value yet? Leave the line out. The check then uses its default, or checks nothing for it (no `check_network_tcp` means no TCP checks).

Step 4. Settings for particular groups

Open the group › **Edit group** › **Variables**, paste, change the `CHANGE` lines, **Save**. Put these on your own groups or on the groups from step 2. Both work.

The AAP server(s), for example on `aap_hosts`:

```yaml
check_disk_overrides:
  /var: {warn: 80, crit: 90}          # AAP keeps job output and container images under /var
```

The STIG Manager host(s), on `stigman`:

```yaml
check_certs_endpoints:                  # the certificate browsers actually see
  - {name: STIG Manager, host: 127.0.0.1, port: 443, servername: stigman.yoursite.mil}   # CHANGE
check_certs_files: [/etc/stigman/*.crt, /etc/stigman/*.pem]                          # CHANGE:
  where your cert files are
watch_containers:                       # optional since 0.6.0: service watch finds the containers
  - name: stigman                       # that should run by itself; this list is watched first,
  - name: nginx                         # in this order (dependencies first), and a missing one is
                                        # reported
```

If STIG Manager runs as systemd units (`systemctl list-units | grep -i stig` shows them), also add them, so the services check watches them: `check_services_required_extra: [<unit>, <unit>]`.

The ServiceNow database host(s) (MariaDB or MySQL): also add this group to `mariadb_hosts` or `mysql_hosts` (step 2).

```yaml
check_mariadb_container: servicenow-mariadb     # CHANGE: the container name from `sudo podman ps
                                                # -a`
```

Then attach the **MariaDB monitor** credential to the **Database health**, Health check and Troubleshoot templates (it serves MySQL too). Container images give root a password, so the check logs in with a monitoring account instead. The whole setup (several containers, discovery, rootless containers, the account to ask the DBA for, and how to verify) is in MARIADB.md.

The ServiceNow MID Server host(s): nothing here. They are Windows servers, checked by the **ServiceNow health** job: a group `servicenow_mid_hosts` in the **Windows** inventory (SERVICENOW_SETUP.md).

The NetApp Console host: nothing is needed. It is checked like every host; being in `netapp_console_hosts` and `no_patch` keeps automation from changing it.

Step 5. Settings for one host (only when one host is different)

Hosts › the host › Edit host › Variables. For example, a host whose `/data` is always nearly full on purpose:

```yaml
check_disk_overrides:
  /data: {warn: 95, crit: 98}
```

Or a host with a known-broken vendor unit you want ignored:

```yaml
check_services_ignore_failed: ['^vendor-agent']
```

Step 6. Use your inventory in the job templates

On every job template (and workflow), set **Inventory** to your inventory. That is the only link between them. Everything else (project, playbook, credentials, survey) is as in SETUP_AAP.md, steps 6 and 9.

Step 7. Check that it worked

1. Launch **Health check** with **Limit** = one server and the survey set to `daily`.
2. In `Report | result for this host`, look for your own values. A network finding names *your* LDAP server; an accounts finding names *your* service account. If a value is not there, the variable did not reach the host: check its spelling, and which group or host it is on.
3. `skipping: no hosts matched` (a green job that did nothing) means the Limit or `target` names a group or host this inventory does not have. Check the spelling against the inventory's **Groups** tab, and that the template uses the right **Inventory**.
4. `skipped: the MariaDB/MySQL check is off for <host>` means the host is in none of `mariadb_hosts`, `mysql_hosts`, `database_hosts`, `mariadb` or `mysql` and has no container name set (MARIADB.md).
5. Findings you do not care about: change the setting for that group or host (steps 4-5), not the code.

Which YAML files in the repository do I change?

File	Change it?
`playbooks/group_vars/*.yml`, `playbooks/host_vars/*.yml`	**Yes, these are your settings** (the update script never overwrites them)
`inventories/example/...`	**No.** Only a reference to copy blocks from; AAP does not read it
`roles/*/defaults/main.yml`	**No.** Read VARIABLES_REFERENCE.md to see every setting; set values in a settings file or in AAP instead
`playbooks/*.yml`	**No**
`aap/credential_types/*.yml`	**No.** Paste their contents into AAP (credential types)
`ansible.cfg`	**No.** AAP ignores its `inventory =` line and uses the template's inventory
`poam/poam.csv`	**Yes.** Your POA&M export (see `poam/README.md`)

4. The Linux inventory from IdM

Your RHEL hosts are enrolled in Red Hat IdM, so IdM already knows them, and its **host groups** already sort them. An AAP inventory can be filled from IdM and kept up to date by AAP itself, by a schedule or at a job's launch. Nobody adds a host twice.

- **Hosts**: each host enrolled in IdM (`ipa-client-install` ran on it, so it has a keytab), named by its FQDN. A host entry made only for a name (a load balancer's, a service's) has no keytab and is left out.
- **Groups**: each IdM host group becomes an AAP group of the same name, nested as in IdM. Characters other than letters, digits and _ become _: `rhel9-servers` is `rhel9_servers`, and `2fa-pilot` is `idm_2fa_pilot`.
- **Your names to the runbooks' names**: your host groups will rarely be called `aap_hosts` or `rhel9_all`. `IDM_GROUP_MAP` puts the hosts of an IdM host group in the runbooks' groups too. Nothing in IdM changes.
- **Each host's IdM details** as variables: `idm_description`, `idm_locality`, `idm_location`, `idm_os`, `idm_platform`, `idm_hostgroups` (every host group it is in, nested ones too), `idm_fqdn`, `idm_enrolled`.
- **It only reads IdM**, as a plain IdM user. Every IdM user may read hosts and host groups, so no admin role is needed.
- **A sync that would be wrong stops instead**, and AAP then keeps the inventory as it was. That happens when IdM is not reached, the login is refused, IdM cuts the list short, fewer hosts come back than `IDM_MIN_HOSTS`, or a group you named in `IDM_REQUIRE_GROUPS` is empty. An empty answer never empties your inventory.

It is an inventory plugin in this repository (`inventories/idm/inventory_plugins/site_idm.py`) with its file `inventories/idm/idm.yml`. AAP runs it as an inventory source **Sourced from a Project**. It needs nothing beyond ansible-core, so any of this project's execution environments will do. Windows hosts are not in IdM; keep your Windows inventory as it is.

Step 1. An IdM user to read with

Any IdM user can read the hosts and host groups. Use one for this only, for example `svc_aap_inventory`. Ask your IdM admin, or as an IdM admin:

```
ipa user-add svc_aap_inventory --first=AAP --last=Inventory --password
```

A new IdM user's first password is already expired. IdM makes you choose a new one at the first login. Do that once from any IdM client, then put the **new** password in the credential (step 4):

```
kinit svc_aap_inventory          # asks for the first password, then a new one
ipa host-find --sizelimit=0 | grep -c "Host name"      # the hosts it sees
```

The password also expires under your IdM password policy (90 days by default). When it does, the sync stops with `the password has expired` and the inventory stays as it was until you set a new one. Your IdM admin can give this user a policy with a longer life, or set its expiry date.

IdM's CA certificate: `/etc/ipa/ca.crt` on any IdM client. You paste it into the credential.

Step 2. Your host groups to the runbooks' groups

List your host groups (from any IdM client, after `kinit`):

```
ipa hostgroup-find --sizelimit=0 --pkey-only
```

Then fill in the right-hand column of this table. The runbooks look for the groups on the left (USING_YOUR_AAP_INVENTORY.md step 2 says what each one is for). Leave a row empty if you have no such hosts.

Runbook group	Hosts	Your IdM host group(s)
`aap_hosts`	the AAP servers. **Safety**: ACT never fixes them, patching never reboots them	
`netapp_console_hosts`	the NetApp Console host. **Safety**: diagnose only	
`no_patch`	hosts *Patch hosts* must skip (put `aap_hosts`' and `netapp_console_hosts`' groups here too)	
`patch_hosts`	the hosts monthly patching may touch	
`rhel8_all`, `rhel9_all`	all RHEL 8 / RHEL 9 hosts (or derive them from the OS, below)	
`idm`	the IdM servers (IdM's own host group `ipaservers` has them)	`ipaservers`
`stigman`	the STIG Manager host(s)	
`mariadb_hosts`, `mysql_hosts`	the database host(s)	
`sat`, `logstash`, `vmware_ask` ...	the others in `playbooks/group_vars/`	

That table becomes `IDM_GROUP_MAP` (step 5): the IdM host group on the left, the runbook group(s) on the right.

YAML

```yaml
IDM_GROUP_MAP:
  ansible-controllers: [aap_hosts, no_patch]   # one IdM host group into two groups
  ipaservers: idm
  rhel9-servers: rhel9_all
  rhel8-servers: rhel8_all
  "db-*": mariadb_hosts                         # a pattern: every host group whose name starts
                                                # with db-
  monthly-patching: patch_hosts
```

- A host in a **nested** host group counts too. If `all-linux` holds `rhel9-servers`, a map from `all-linux` takes the hosts of `rhel9-servers`.
- The settings files in `playbooks/group_vars/` are named after groups (`idm.yml`, `stigman.yml`, `aap.yml`...). With the map, the files you already have apply to the right hosts without being renamed. A file named after one of your IdM groups (`rhel9_servers.yml`) works too.
- **A new host lands in the right groups by itself** when IdM puts it in a host group as it enrolls. That is IdM's *automember* rule (`ipa automember-add --type=hostgroup rhel9-servers`, then `ipa automember-add-condition ... --key=fqdn --inclusive-regex=...`).

RHEL 8 or 9 from the OS, not a host group. `ipa-client-install` records the host's kernel version in IdM (`idm_os`, for example `5.14.0-427.13.1.el9_4.x86_64`), so a group can be made from it. This needs your own copy of `idm.yml` (the end of step 5):

```yaml
plugin: site_idm
groups:
  rhel9_all: "'.el9' in idm_os"
  rhel8_all: "'.el8' in idm_os"
```

`idm_os` is what the host reported when it enrolled. A host upgraded in place since keeps its old value, so a host group is the surer way.

Step 3. Try it before AAP

On any machine with ansible-core and this repository (the old ansible-core machine, or your VS Code machine with WSL), from the repository's folder:

```
export IDM_SERVER=idm1.yoursite.mil IDM_USER=svc_aap_inventory IDM_CA_PATH=/etc/ipa/ca.crt
read -rsp "IdM password: " IDM_PASSWORD; export IDM_PASSWORD; echo
export IDM_GROUP_MAP='{ansible-controllers: [aap_hosts, no_patch], ipaservers: idm, rhel9-servers:
  rhel9_all}'
ansible-inventory -i inventories/idm/idm.yml --graph
ansible-inventory -i inventories/idm/idm.yml --host <one host's FQDN>
```

You should see your hosts under their host groups, and under `aap_hosts`, `idm`, `rhel9_all`... as mapped. A `[WARNING]: site_idm: group_map 'xyz' matches no IdM host group with a host here` means a typo in a name, or a host group with no enrolled host.

Step 4. In AAP: the credential type and the credential

1. **Automation Execution › Infrastructure › Credential Types › Create credential type**: name `IdM inventory`, the `inputs` and `injectors` of `aap/credential_types/idm_inventory.yml` (as in SETUP_AAP.md step 2).
2. **Credentials › Create credential**: name `IdM inventory`, type **IdM inventory**. Fill in the **IdM server** (its own FQDN), **IdM user**, **Password**, and paste `/etc/ipa/ca.crt` into **IdM CA certificate**.

Step 5. In AAP: the inventory and its source

1. **Automation Execution › Infrastructure › Inventories › Create inventory › Create inventory**. Name it, for example, `Linux servers (IdM)`, and pick the organization.
2. Open it, then **Sources › Create source**:

Field	Value
Name	`IdM`
Execution environment	the one your jobs use (Minimal is enough)
Source	**Sourced from a Project**
Credential	`IdM inventory`
Project	`site-automation`

Field	Value
Inventory file	`inventories/idm/idm.yml`
Source variables	the block below
Overwrite	ticked: a host removed from IdM (or no longer enrolled) leaves this inventory, and so does a host group
Overwrite variables	ticked: the `idm_*` variables follow IdM

Source variables (the names are fixed; leave out what you do not need):

YAML

```
IDM_GROUP_MAP:                          # step 2
  ansible-controllers: [aap_hosts, no_patch]
  ipaservers: idm
  rhel9-servers: rhel9_all
  rhel8-servers: rhel8_all
IDM_REQUIRE_GROUPS: [aap_hosts]         # the sync stops if no host is left in these
IDM_MIN_HOSTS: 20                       # the sync stops below this many hosts (about your
                                        # fleet's size, minus a margin)
# IDM_EXCLUDE_HOSTGROUPS: [lab-*]       # leave out the hosts of these host groups (nested ones
# too)
# IDM_INCLUDE_HOSTGROUPS: [all-linux]   # only the hosts of these host groups
# IDM_EXCLUDE_HOSTS: ["*.lab.yoursite.mil"]
# IDM_HOSTNAME: short                   # web01, not web01.yoursite.mil (ansible_host stays the
# FQDN)
# IDM_GROUPS: false                     # only the mapped groups, not one per IdM host group
# IDM_GROUP_PREFIX: idm_                # idm_rhel9_servers - keeps IdM's groups apart from the
# runbooks'
```

AAP passes each Source variable to the sync as an environment variable. The plugin reads lists and dictionaries back from them.

3. **Save**, then **Launch inventory update** (the rocket on the source). **You should see** the update succeed, and your hosts and groups in the inventory's **Hosts** and **Groups** tabs.

`IDM_REQUIRE_GROUPS: [aap_hosts]` **matters.** If someone renames the IdM host group `aap_hosts` is mapped from, the next sync would otherwise leave `aap_hosts` empty. The AAP servers would then lose the protection the safety lists give them. With it, that sync stops and the inventory stays as it was until the map is fixed.

Do not add groups or hosts by hand in this inventory. With **Overwrite**, the sync owns it: a group made in AAP may be removed by the next sync. Make the group in IdM, or map it. Settings go in `playbooks/group_vars/<group>.yml` (where VARIABLES.md recommends them anyway), not in this inventory's Variables boxes.

Your own `idm.yml` (only for `groups:` / `keyed_groups:` / `compose:` as in step 2): copy `inventories/idm/idm.yml` to `inventories/idm/site-idm.yml` (the name must end in `idm.yml`), add your lines, commit, and pick that file as the **Inventory file**. A setting written in the file wins over the same one in Source variables. Add the line `inventories/idm/site-idm.yml` to `.site-local` (and commit it), or `scripts/update-from-release` deletes the file as not part of the release. A changed-since zip pasted over your copy never deletes anything.

Step 6. Keep it in sync

Pick one or more:

How	When	Set it
A schedule on the source	every hour, or every night	the source › **Schedules › Create schedule**
Update on launch	before any job on this inventory, if the last sync is older than the **Cache timeout** (seconds; 3600 = once an hour at most)	the source › **Edit** › tick **Update on launch**, set **Cache timeout**
A workflow node	at the start of a workflow (patching, workflow 40...)	in the workflow visualizer: **Add step** › node type **Inventory source sync** › this source, then the jobs after it on success
By hand	now	the source › **Launch inventory update**

With **Update on launch**, a sync that fails also fails the job it ran for: AAP does not run a job whose inventory update failed. That is the safe side. A schedule plus a cache timeout keeps jobs running on the last good inventory while IdM is down.

Step 7. Use it

Point the Linux job templates at `Linux servers (IdM)` (each template › **Edit** › **Inventory**). Everything in USING_YOUR_AAP_INVENTORY.md still applies (`target:`, the Limit, the safety groups). The groups simply come from IdM now.

Host names change to FQDNs if your old inventory used short names. ServiceNow tickets, reports and the report website then show `web01.yoursite.mil`, and history kept under `web01` starts again under the new name. Want the old names? Set `IDM_HOSTNAME: short`.

Every setting

Each one is an environment variable: the credential sets the first four, the Source variables box the rest. In your own `idm.yml` the same setting is the name in lower case without `IDM_` (`group_map:`, `min_hosts:`, `ca_path:`...), except `IDM_GROUPS`, which is `idm_groups:` there.

Variable	Default	What
`IDM_SERVER`		the IdM server's own FQDN (`idm1.yoursite.mil`), `host:port` or `https://host[:port]`. IdM answers only to its own name
`IDM_USER`, `IDM_PASSWORD`		the IdM user that reads (step 1)
`IDM_CA_PATH`	the system's trust	IdM's CA certificate (PEM). The credential writes it to a file
`IDM_VALIDATE_CERTS`	`true`	check IdM's certificate
`IDM_TIMEOUT`	`60`	seconds per request
`IDM_GROUP_MAP`	`{}`	IdM host group (a name or a pattern with `*` `?`) to one group or a list of groups

Variable	Default	What
IDM_GROUPS	true	also one group per IdM host group, by its own name
IDM_GROUP_PREFIX	''	put before each group made from an IdM host group
IDM_INCLUDE_HOSTGROUPS, IDM_EXCLUDE_HOSTGROUPS	[]	only / not the hosts of these IdM host groups (names or patterns; nested ones count)
IDM_INCLUDE_HOSTS, IDM_EXCLUDE_HOSTS	[]	only / not these hosts (FQDN, patterns)
IDM_ENROLLED_ONLY	true	leave out a host entry with no keytab (never enrolled)
IDM_HOSTNAME	fqdn	short: the first label as the name, ansible_host the FQDN
IDM_MIN_HOSTS	1	fewer hosts than this: the sync stops
IDM_REQUIRE_GROUPS	[]	these groups must have a host, or the sync stops

Your own idm.yml may also use Ansible's groups, keyed_groups, compose and strict (as in any inventory plugin; ansible-doc -t inventory constructed) with the idm_* variables.

When the sync fails

The inventory update's output in AAP (the source › **Jobs**, or **Jobs** › the update) says why:

It says	Why	Do
IdM refused the login of ... (HTTP 401, password-expired)	the password expired, or is the first one, never changed	kinit <user> once, set a new one, put it in the credential
... (HTTP 401, invalid-password)	the user name or password is wrong	fix the credential
IdM at ... not reached: [SSL: CERTIFICATE_VERIFY_FAILED]	IdM's CA not given, or the wrong one	paste /etc/ipa/ca.crt into the credential
IdM at ... not reached: ... (any other)	the name does not resolve, a firewall	the execution node must reach the IdM server on 443
answered with a redirect to ... - set server to the IdM server's own FQDN	an alias, an address or a load balancer name	the server's own name, as hostname -f prints it on the IdM server
IdM's host_find returned only N - a limit of IdM's directory cut the list short	a size or time limit set on this user (or the directory's)	the IdM admin raises it for this user
only N host(s) from IdM ..., min_hosts is M	a filter leaves out too much, or the user sees nothing	the counts in the message say what was left out and why
no host in aap_hosts (require_groups)	the IdM host group mapped to it was renamed or emptied, or the map changed	fix IDM_GROUP_MAP

It says	Why	Do
`group_map: aap-hosts - a group name is letters, digits and _`	a target group name with `-` or `.`	`aap_hosts`
`Failed to parse ... with auto plugin: ... site_idm` with no reason above	the project is older than 0.78.0	sync the project
`inventories/idm/idm.yml` is not in the **Inventory file** list	the project in AAP is older than 0.78.0	sync the project, then open the source again

Tested

`tests/idm/run_idm_real_test.sh` runs against a real IdM (FreeIPA on AlmaLinux 9, in a container), on ansible-core 2.16 and the latest. It checks nested host groups, a host group named `all`, five enrolled hosts and one name-only entry, all read as a plain IdM user with no role. It also checks the map as the Source variables box passes it, the filters, short names, a constructed group from `idm_os`, and the sync started as AAP starts it (from `/` with `--playbook-dir`). On the failure side: a first password never changed, a wrong password, a list cut short by a size limit, no CA, an address instead of the name, too few hosts, and a required group left empty. In CI, `tests/test_idm_inventory.py` runs against a stand-in IdM. Not tested here: AAP itself running the source.

5. Disk space: the report and the tmp cleanup

Two Linux jobs and a workflow to tie them together:

- **Linux - disk space report** (`playbooks/disk_report.yml`) - every mounted local filesystem on every host (logical volumes included, by their mount point), and every LVM thin pool and snapshot: **warning at 85%, critical at 90%** (space or inodes). Read-only; the job stays green whatever it finds - it is a report, in an email and on the report website like the others. A host it cannot reach is listed, not failed.
- **Linux - tmp cleanup** (`playbooks/tmp_cleanup.yml`) - deletes the old files of `/tmp` and `/var/tmp` on the hosts the report found full. Never on its own by accident: in the workflow only after the approval, and only what the report planned.
- **Workflow 42** - the report, an approval, the cleanup, the report again.

The health check's `disk` check is the same check with its own limits (85% and 95%); it fails a host for what it finds, so a workflow can open a ticket. This report never fails, and adds the old tmp files and the volume groups.

What the report shows

Table	What is in it
Filesystems at or above 85%	host, mount point, device (`/dev/mapper/rhel-var`...), type, % used, used, free, size, inodes used, the old tmp files on it; red at 90%, amber at 85%, fullest first
LVM thin pools and snapshots	a thin pool's data and metadata %, an old-style snapshot's %; a snapshot that filled up and is no longer valid is red
Volume groups of those hosts	the free space that could grow a full logical volume: `lvextend -r -L +10G /dev/VG/LV` grows it and its filesystem in one step
Old files in the tmp folders of a full filesystem	how much of `/tmp` (older than 10 days) and `/var/tmp` (older than 30 days) could go, the biggest of them - only where the folder is on a full filesystem

The same tables are printed at the end of the job (*Full filesystems and thin pools, fullest first*). Network filesystems (NFS, CIFS) are never read - a hung server would hang the job; the mounts check covers them. `tmpfs`, `overlay` and the other types in `check_disk_exclude_types` are left out too.

Settings (the template's Variables, `aap/extra_vars/disk_report.yml`):

Setting	Default	
`disk_report_warn_pct`	`85`	warning at this % used (space, inodes, thin pools, snapshots)
`disk_report_crit_pct`	`90`	critical
`disk_report_all`	`false`	`true` = every filesystem and thin pool in the tables, not only the full ones
`check_disk_overrides`	`{}`	other limits for one mount point: `{/var/log/audit: {warn: 70, crit: 85}}`

Setting	Default	
`check_disk_lvm`	`true`	read LVM (thin pools, snapshots, volume groups)
`report_email_to`		who gets the email

What the cleanup deletes

Only **regular files** in a tmp folder whose **access, change and modification** times are all older than the folder's limit - the way `systemd-tmpfiles` ages them, so a file still read or written is never old. Then the folders left empty that are as old (a folder emptied by this run goes next time).

Never deleted:

- sockets, pipes and devices;
- anything under a name in `tmp_cleanup_keep`: `systemd-private-*` (each service's private tmp), `.X11-unix` and the other X folders, `krb5cc*` (Kerberos tickets), `ssh-*` (agents), `tmux-*`, PostgreSQL's and MySQL's sockets;
- anything on another filesystem mounted inside the tmp folder (`find -xdev`);
- any folder that is not a tmp folder: the last part of each path in `tmp_cleanup_dirs` must be *tmp* or end in `.tmp`, `-tmp` or `_tmp` (`/tmp`, `/var/tmp`, `/opt/app/tmp`; not `/usr/lib/tmpfiles.d`), with no `.` or `..` part, and never be `/`, `/var`, `/usr`, `/etc`, `/home`... - a setting that names one stops the job before anything is read;
- anything through a folder replaced by a link while the cleanup runs (`rm` and `rmdir` run in each file's own folder, `find -execdir`).


Setting	Default	
`tmp_cleanup_dirs`	`/tmp` 10 days, `/var/tmp` 30 days	the folders and their ages (`[{path: /tmp, days: 10}, ...]`)
`tmp_cleanup_keep`	the list above	names never touched (`*` and `?`)
`tmp_cleanup_confirm`	`false`	on its own (not in workflow 42): `true` deletes; without it the job lists what it would delete

Run it as **Check** (a dry run) and it deletes nothing, in the workflow or not. The email lists, per host and folder, what was deleted and the free space before and after.

Nothing else is cleaned up - not logs, not the journal, not caches. A full `/var/log` or `/home` is for a person to look at: the report's table names the filesystem, and the health check's runbook says how to find what grew (RUNBOOKS.md).

Set it up

1. **Linux - disk space report**: playbook `playbooks/disk_report.yml`, your Linux inventory, the Machine credential (with *Privilege Escalation Method* `sudo`: LVM is read as root), paste `aap/extra_vars/disk_report.yml` into Variables and set `report_email_to`. Schedule it every day (06:30), or only as workflow 42's first step.
2. **Linux - tmp cleanup**: playbook `playbooks/tmp_cleanup.yml`, the same inventory and credential. Leave *Prompt on launch* for Variables unticked: the plan must come from the workflow's own report.
3. **Workflow 42** (WORKFLOWS_AND_SCHEDULES.md):



The approver reads the first report's email - its last table, *Old files in the tmp folders of a full filesystem*, is exactly what the cleanup deletes. No host in it: approve or deny, the cleanup leaves every host alone. Schedule the workflow instead of the report (every day 06:30) if the cleanup should be offered every day.

On its own, the cleanup is for one host now and then: Limit it to the host, run it as **Check**, then again with `tmp_cleanup_confirm: true` in the Variables of the launch.

Hand-over

The report hands `disk_cleanup_plan` (`{host: [folders]}`: only folders on a full filesystem that hold old files) and `disk_cleanup_plan_workflow` (its workflow job's ID) to the cleanup. The cleanup takes a plan only from its own workflow; a plan from anywhere else - typed into Variables, another workflow - stops it before anything is deleted.

6. STIG Manager: health and availability

Two jobs watch a STIG Manager deployment - for example **two front-end nodes** (each runs STIG Manager's API and web client, behind one address) and **MariaDB in a container on another host**:

- **STIG Manager - health** (`playbooks/stigman_health.yml`) - once a day, or after a change: everything, through the API and on the hosts. Read-only. Fails when it finds something, for a workflow's ticket step.
- **STIG Manager - availability** (`playbooks/stigman_availability.yml`) - every 5 to 15 minutes: does it answer. Quiet when it does, red when it does not; the availability over a day, a week and a month. AVAILABILITY.md says how every availability check works.

What the health check reads

Through the API, from the AAP side (`site_stigman_health`) - the address people use (`stigman_health_api`) and **each node on its own** (a node that went bad behind a load balancer is found too):

Asked	What it tells	A finding when
`/op/state` (no login)	the API's own state - `available`, `unavailable`, `starting` - and whether its **database** and **Keycloak** connections are up	not `available` (with which connection is down), or no answer
`/op/configuration` (no login)	the version and the database schema (`lastMigration`)	the nodes differ (one not updated, or not on the same database); not at `stigman_health_version`
Keycloak: the realm, then a token for the client	that people can log in	the realm does not answer; no token for the client
`/user` with that token	a login that reads the database, and how long it takes	a node refuses the token (its OIDC settings differ), the call fails, or it is slow
`/collections`	the collections the client sees	they cannot be listed
`/op/appinfo?elevate=true` (an admin client)	the database's version, uptime and connections; each node's uptime and memory	connections at 80% / 95% of `max_connections`; the database or a node restarted in the last hour; the nodes see **different databases** (version or uptime)

On the hosts, over SSH - the hosts of the inventory group `stigman` (the nodes) and `stigman_db` (the database): their **containers** (each one that should run, runs; no restart loop - `check_containers`) and **disk** (`check_disk`), and on the database host the **database itself** (`check_mariadb`: up, connections, slow queries, the error log, its disk, ...; MARIADB.md). A host that cannot be reached is a finding of its own.

One report (named `stigman`): the findings, then *STIG Manager's address and nodes* (each one's state, database and Keycloak connections, version, schema, answer times, login, memory), *The database, as STIG Manager sees it* and *Keycloak*. The hosts' findings carry the host's name.

Set it up

1. **The inventory.** Your STIG Manager hosts in two groups (or name yours with `stigman_health_nodes_group` and `stigman_health_db_group`):

```yaml
stigman:            # the nodes
  hosts:
    stig01.yoursite.mil:
    stig02.yoursite.mil:
stigman_db:         # the database host
  hosts:
    stigdb01.yoursite.mil:
```

One node that runs everything (the API, the web, Keycloak and MariaDB in containers on one host): put that host in **both** groups. It is read once - its containers, its disk and the database:

```yaml
stigman:
  hosts:
    stig01.yoursite.mil:
stigman_db:
  hosts:
    stig01.yoursite.mil:
```

With no `stigman` or `stigman_db` group in the inventory at all, the job's **Limit** names the host(s): a Limit of `stig01.yoursite.mil` reads that host as the node and its database. No groups and no Limit: the API only. With `stigman_health_api` set and no nodes (an empty `stigman` group, no `stigman_health_nodes`), the address people use is checked alone. `stigman_health_hosts: false`: no SSH at all, whatever the Limit.

2. **The addresses** (in `all.yml`: both jobs read them):

```yaml
stigman_health_api: https://stigman.yoursite.mil/api        # the address people use
stigman_health_node_url: "https://{host}/api"               # each node's own API ({host} = its
                                                            # inventory name)
```

A node whose API is on another port or name: `stigman_health_node_url` in its host_vars, or list them all with `stigman_health_nodes: [{name: stig01, url: "https://stig01.yoursite.mil:8443/api"}, ...]`. Only one address and no load balancer? Leave `stigman_health_api` empty: the nodes are then the service.

3. **A Keycloak client** for the health check (or your `autostig` client): client credentials, a service account, the scopes `stig-manager:user:read stig-manager:collection:read`, and for the database numbers `stig-manager:op:read` with **admin** in STIG Manager (else that part says *Not read* - the rest works; `stigman_health_appinfo: false` stops asking). Put it in a **STIG Manager API** credential (`STIGMAN_TOKEN_URL`, `STIGMAN_CLIENT_ID`, `STIGMAN_CLIENT_SECRET` - SECRETS.md).
4. **STIG Manager - health**: playbook `playbooks/stigman_health.yml`, the inventory with those groups, the credentials **Machine** (sudo), **STIG Manager API** and **MariaDB monitor** (the database in its container gives root a password: MARIADB.md); paste `aap/extra_vars/stigman_health.yml` into Variables and set `report_email_to`. A Limit is not needed; a Limit of hosts needs no `localhost` - the API part runs once on the AAP side (on `localhost`, or on the Limit's first host standing in for it, connection local: nothing of it runs on that host). Schedule it every day (06:15).

5. **STIG Manager - availability**: playbook `playbooks/stigman_availability.yml`, any inventory (it runs on the AAP side only - a Limit, if any, needs no `localhost`), the credentials **Red Hat Ansible Automation Platform** (for the percentages; Organization Auditor) and **STIG Manager API** (only to know Keycloak's address - it never logs in). Paste `aap/extra_vars/stigman_availability.yml`; schedule it every 5 to 15 minutes, **Concurrent jobs** off - or as workflow 43 with the ServiceNow tickets step (WORKFLOWS_AND_SCHEDULES.md).

Run the health check once by hand and read its tables: every node `available`, the same version and schema, the login in well under a second.

Settings

Setting	Default	
`stigman_health_api`	(empty)	the address people use; empty = the nodes only
`stigman_health_nodes`	`[]`	each node `{name, url}`; `[]` = the hosts of `stigman_health_nodes_group` at `stigman_health_node_url`
`stigman_health_nodes_group` / `stigman_health_db_group`	`stigman` / `stigman_db`	the inventory groups
`stigman_health_hosts`	`true`	`false` = the API only (no SSH, whatever the Limit)
`stigman_health_appinfo`	`true`	ask `/op/appinfo` (an admin client)
`stigman_health_slow_ms`	`2000`	slower answers: warning
`stigman_health_node_down`	`critical`	a node down or not `available`; `warning` = only the address counts
`stigman_health_conn_warn_pct` / `_crit_pct`	`80` / `95`	the database's connections in use
`stigman_health_restart_minutes`	`60`	restarted more recently: warning
`stigman_health_version`	(empty)	the version every node must run
`stigman_availability_nodes`	`true`	the availability check asks each node too, not only the address

Older STIG Manager (before `/op/state`): the state is read from `/op/configuration` answering, the rest as above.

7. Availability checks

A short job, every 5 to 15 minutes, that asks a service's addresses whether it is there - and its own past runs say how available it was over a day, a week and a month. Read-only, from the AAP side (`roles/api_availability`).

Job template	Playbook	Asks
STIG Manager - availability	`playbooks/stigman_availability.yml`	`/op/state` of the address people use and of each node (the API, its database and Keycloak connections all up: `available`), and Keycloak's realm - no login (STIGMAN_HEALTH.md)
ServiceNow - availability	`playbooks/servicenow_availability.yml`	the REST API (one record of `servicenow_table`, with the ServiceNow API credential) and the login page `/login.do`

Both run on the AAP side only. A Limit is not needed, and a Limit of hosts needs no `localhost`: the job then runs once on the Limit's first host standing in for it (connection local - nothing runs on that host).

The full checks are other jobs: *STIG Manager - health*, *ServiceNow health* (the MID Servers).

How a run decides

Each address is asked `availability_attempts` (3) times, `availability_pause_seconds` (2) apart; each answer timed. A redirect (3xx) is not followed and is a bad try that says where it pointed, so a login is never sent on to another address. Only an address asked without a login may follow one: the ServiceNow login page, which may send people on to the single sign-on page.

	Severity	The run
The service's address (or what it needs: Keycloak) never answered well	critical	**DOWN** - the job fails
No address set, and every node down	critical	**DOWN**
One node down while the address answers	`availability_node_down` (warning)	DEGRADED - green
Some tries bad (flaky), or the median slower than `availability_slow_ms` (3000)	warning	DEGRADED - green
All good		UP - one line, green

The job's line says it all: `STIG Manager UP: API 3/3 85 ms; stig01 3/3 40 ms; stig02 3/3 42 ms; Keycloak 3/3 30 ms; last 24 h 99.65%`. A report (email, web page) goes out only for `availability_report_on` (`[critical]`: when down) and once when it is **UP AGAIN** after a failed run (`availability_report_recovery`); add `warning` to hear about slow, flaky or one node down. The job fails for `availability_fail_on` (`[critical]`).

Availability over time

With a **Red Hat Ansible Automation Platform** credential on the template (a user with Organization Auditor), each run counts this template's own runs in AAP: those that ended well are *up*, those that failed *down* (canceled runs are not counted) - over the last 24 hours, 7 days and 30 days (`availability_history_hours`). The report's *Availability* table shows them, and since when it is down. It is as fine-grained as the schedule (every 5 minutes: 288 runs a day), and AAP keeps jobs only as long as its cleanup job lets it (*Cleanup Job Details*, 120 days by default). Without the credential the check still runs; the table says why there are no percentages.

Set it up

1. A template per service (above), the credentials it names, Variables from `aap/extra_vars/<playbook>.yml`, `report_email_to`.
2. A schedule every 5 to 15 minutes; on the template, **Concurrent jobs** off.
3. **When it goes down**: STIG Manager - workflow 43, the ServiceNow tickets step after it on *Run always* (WORKFLOWS_AND_SCHEDULES.md): an incident while it is down, resolved when it is back. ServiceNow - an email **notification on failure** on the template (a ticket cannot be opened in the ServiceNow that is down).

Settings

Setting	Default	
`availability_attempts`	`3`	tries per address per run
`availability_pause_seconds`	`2`	between two tries
`availability_timeout`	`10`	seconds a try may take
`availability_slow_ms`	`3000`	median slower than this: warning
`availability_node_down`	`warning`	one node down while the address answers; `critical` fails the job
`availability_fail_on`	`[critical]`	the job fails for these
`availability_report_on`	`[critical]`	an email and the web page for these
`availability_report_recovery`	`true`	a report when it is back after a failed run
`availability_history` / `_hours`	`true` / `[24, 168, 720]`	the percentages from AAP
`servicenow_availability_ui`	`true`	ServiceNow: also the login page

8. AAP - template variables audit: what belongs somewhere else

AAP - template variables audit (`playbooks/aap_template_audit.yml`, role `roles/aap_template_audit`) reads every job template and workflow template in AAP, and the **Variables** box of each, and says which settings there belong somewhere else - and where. A template's Variables beat every other place a setting can be (`all.yml`, the group files, the inventory), so a setting left there by mistake quietly wins: a mail relay changed in `all.yml` that one template still sends through, a vCenter address that is right in one enclave and wrong in the other.

It is **read-only**: it reads through AAP's API (GET) and changes nothing in AAP. A secret it finds is named, **never shown**: not its value, not part of it, not in the email, the website, the job's output or its artifacts.

What it flags

Why	What	Move it to
connection	any `ansible_*` setting: `ansible_winrm_*`, `ansible_port`, `ansible_user`, `ansible_connection`, `ansible_become*`	the Windows ones: the windows group (`playbooks/group_vars/windows.yml`); the login (`ansible_user`, `ansible_password`, `ansible_become_password`): the template's **Machine** credential; the rest: the inventory's group or host variables
an address	a value that is a host name, a URL or an IP address (`vcsa01.yoursite.mil`, `https://stigman.yoursite.mil/api`, `192.0.2.10`)	`all.yml` of the enclave's own AAP - one AAP per enclave (below)
site-wide	a setting the job templates' variable files mark *usually in all.yml* (`aap/extra_vars`: the settings of the email, ACT and findings roles - the mail relay, the report website, the logo)	`playbooks/group_vars/all.yml`
repeated	the same setting with the same value in 3 templates or more (`aap_template_audit_repeat_min`): one change would have to be made in each. The note names the other templates	`all.yml` - one place to change it
a secret	a setting named like one - a whole word of its name, in any case, split at `_ - .`, camelCase and digits: password, passwd, pwd, pass, pw, secret, token, api key, passphrase, pin, community, private / secret / access key, key material, or a word ending in a long one, in pw or in pass (`db_password`, `adminPwd`, `client-secret`, `API-KEY`, `secret1`, `PGPASSWORD`, `dbpassword`, `adminpass`, `rootpw`, `bindpw`, `snmp_community`; not `bypass_mode`, `keyboard_layout`, `pin_version` or `pass_count`) - with a value (text or a number); a setting named for a credential (`ldap_credential`) whose value is not a credential's name or id; a list or dict with a key named like one anywhere inside (`stigman_db: {password: ...}`, also in a text holding JSON or YAML); whatever its name, a text with a password in a URL (`mysql://svc:...@db01`), after a secret's name (`Uid=svc;Pwd=...`, `PGPASSWORD=...`) or option (`--password X`, `-p X`, `-pS3cret!`; a tool's own password option after that tool: mysql's `-pXXXX`, `curl -u user:password`, `sqlcmd -P`, `ldapsearch -w`, `smbclient -U user%password`, `ipmitool -P`, `redis-cli -a`, `winrs -p:`, `sshpass -p`), an Authorization header's `Basic ...` or `Bearer ...`, a PEM private key, or any value that is a long random string or vault-encrypted	a credential (a custom credential type, SECRETS.md) - never plain in Variables

Why	What	Move it to
set at launch	a template with **Prompt on launch** on for its Variables (a launch can set any of the flagged settings again), or whose survey asks for a flagged setting - or for a password in a *Text* question instead of a *Password* one	ask on launch only for what a launch must choose

One AAP per enclave. Each enclave has its own AAP, with its own copy of the settings: what differs between enclaves - the addresses, the credentials, the paths - goes in that AAP's `all.yml`, never in a template. ENCLAVES.md lists what to change when you set up the next enclave's AAP. `aap_template_audit_per_enclave` names more settings that differ by enclave (none by default: the addresses are what point to it).

Not flagged:

- settings that belong to one template - who gets its report (`report_email_to`, `report_email_cc`, `report_email_also`), when it fails (`site_fail_on`), what it runs on (`target`); see `aap_template_audit_per_template`. Still flagged when they are a secret, or the same in many templates;
- a rule or a place for a password (`check_accounts_pw_max_days: 60`, `vcenter_password_file`), and true / false under a password's name (its value is not shown either);
- a credential's name or id under a credential's setting (`incident_docs_draft_credential: AAP - SOP draft`, `tenable_scan_credentials: [12, 15]` or `["ssh-linux"]`; a single word on its own may be a password: it is);
- a limit (`max_tokens: 4096`) and a sentence of plain words (`Change the password: see the runbook`);
- a file name as an address (`report.html.j2`, `logo.png`).

On a command line, a tool's own password option counts wherever a shell starts the tool - after `$(`, a backquote, `(`, `;`, `|`, `&&`, inside a quoted string (`ssh db01 'mysql ...'`) - up to the end of that command or line (a line ending in `\` goes on). A quoted string is one word of the command around it (`mysql -e "select count(*)" -p...`); a backslash works as in a shell (`ssh h "mysql -e \"select 1\" -p..."`). A Windows tool's switch counts with `/` or `-`, in any case.

The audit hides on suspicion: a value it cannot tell from a secret is not shown, and it may call a setting a secret that is none. A false "not shown" costs a look in AAP; a shown secret cannot be taken back.

Known limits - the audit finds secrets by their name and their shape, not every one; a reviewer still reads the template. Shown, though they may be a secret:

- a name ending in pass of 5 letters or fewer (`xpass`);
- a password-like value under a plain name (`Passw0rd`), an AWS access key ID (`AKIA...`), a Bearer token under 8 characters;
- a secret inside free text under a plain name (a kickstart's `rootpw --plaintext ...`, snmpd's `rocommunity ...`);
- a password option of a tool not in the audit's list, a password given as a plain argument (`net use \\fs01\share PASSWORD /user:svc`), a host named like one of the tools (`mysql -h curl ...`);
- a glued `-p` of letters only outside mysql (`-pabcdef` reads as flags, like `rsync -prltDvz`), and `sqlcmd -P 1` (`-p1` is sqlcmd's statistics switch);
- a command inside quotes inside quotes more than 3 levels deep (`ssh a "ssh b 'bash -c \"...\"'"` is 3).

The report

One report, on the report website and by email like the others (`report_email_to`, `report_web_dest`; EMAIL_REPORTS.md, WEB_REPORTS.md):

- **the counts**: job templates and workflows read, how many have something to move, and each kind of flag;
- **By setting**: each flagged setting once - why, how many templates have it, in how many it is the same, the value (cut; *not shown* for a secret, a setting named like one, or a list or dict, a text holding one as JSON or YAML too - only *(same; not shown)*) and where to move it;
- **a table per template** (the ones with a secret first, then the most flags): setting, why, where to move it, a note (the other templates with the same value; what its survey asks);
- **Nothing to move**: the templates with nothing flagged, by name.

The colour: red when a secret is in a template's Variables, amber for anything else, green when nothing is flagged. When a part could not be read (a page of templates, a survey), the title says *incomplete: N parts not read* and the report is never green: *nothing to move in what was read* at best (1.47.0). The job's artifact `aap_template_audit` has the counts and the flagged settings' names (no values). The job does not fail on what it finds unless `aap_template_audit_fail: true` (for a workflow's ticket step): then it fails on a flagged setting or a part not read, after the report. It fails when AAP cannot be read at all.

Set it up in AAP

1. **The job template** *AAP - template variables audit*:
   - playbook `playbooks/aap_template_audit.yml`; any inventory (it runs on localhost, the execution environment); no Limit;
   - a **Red Hat Ansible Automation Platform** credential. Its user only reads: **Organization Auditor** is enough (System Auditor sees every organization);
   - Variables, if you like, from `aap/extra_vars/aap_template_audit.yml`.
2. **Launch it.** The output prints the report; the website and the email have the same.
3. **Schedule it**, if you like - weekly, say - and move what it finds as you go.

A template the AAP user cannot see is not read: give it Auditor on the organization (or each template's Read role).

Settings

The main ones; every setting with its default: VARIABLES_REFERENCE.md.

Setting	Default	What it does
`aap_template_audit_project`	`""`	only the job templates of this project (its name in AAP); workflows are all read
`aap_template_audit_workflows`	`true`	read the workflow templates too
`aap_template_audit_exclude`	`[]`	templates left out, by name or ID

Setting	Default	What it does
`aap_template_audit_repeat_min`	`3`	a setting with the same value in this many templates is flagged; `0` = never
`aap_template_audit_site_wide_roles`	`[site_email, site_act, site_findings]`	the roles whose settings are site-wide (read from their defaults when the job runs)
`aap_template_audit_site_wide`	`[]`	more site-wide settings
`aap_template_audit_per_enclave`	`[]`	settings that differ by enclave: `all.yml` of each enclave's AAP (ENCLAVES.md)
`aap_template_audit_per_template`	`report_email_to`, `report_email_cc`, `report_email_also`, `site_fail_on`, `target`	settings that belong in a template: never site-wide or an address
`aap_template_audit_ignore`	`[]`	settings never flagged
`aap_template_audit_ca_path`	`""`	a CA file for AAP's HTTPS certificate
`aap_template_audit_fail`	`false`	`true` = the job fails when something is flagged or a part was not read

When something goes wrong

What you see	Why, and what to do
`No AAP connection: attach a credential of type "Red Hat Ansible Automation Platform"`	the template has no AAP credential: add one (an auditor is enough)
`AAP refused the login (HTTP 401)`	the credential's user name and password, or its token, are wrong or expired
`the survey of job template X (ID n) could not be read (HTTP 403)`	the AAP user may not read that template's survey: give it Auditor on the organization
the title says *incomplete: 1 part not read*	a page of templates or a survey could not be read (*Not read* says which): what was read is reported, the rest was not checked. Run it again; if it stays, check AAP's API
a template's section says *Its Variables could not be read: X could not be checked*	one setting's value could not be weighed (1.47.0): the other settings and templates were audited; look at that setting in AAP
a template's section says *Its Variables could not be read: not YAML or JSON*	the template's Variables box does not parse: open it in AAP and fix it (AAP keeps a box it cannot use as it is)
a setting flagged that belongs where it is	add it to `aap_template_audit_per_template` (still checked for secrets) or `aap_template_audit_ignore`

9. Enclaves: setting up another enclave's AAP - the banner, ACT off, what to change

The same repository runs in each enclave. **Each enclave has its own AAP**, built on its own: you import the settings there (the project, `playbooks/group_vars/all.yml` and the group files, the job templates from `aap/extra_vars`) and then change, by hand, what is different in that enclave. Nothing in a job template has to change: what differs between enclaves lives in that AAP's credentials and in its `all.yml`.

This chapter is the list of what to change. Go through it top to bottom on the new AAP, then run *AAP - template variables audit* (TEMPLATE_AUDIT.md): it names any address, path or secret still sitting in a template's Variables, where it would quietly win over `all.yml`.

The examples use placeholders only: `ENCLAVE-A` / `ENCLAVE-B`, `yoursite.mil`, `classified.example.mil`. Never put an enclave's real network name or domain in the repository.

1. Which enclave this AAP serves, and the banner

In `all.yml`:

YAML

```
site_enclave: classified            # or unclassified; empty = found from the job's hosts (below)
report_banner_text: SECRET          # the marking, e.g. SECRET, SECRET//NOFORN, TOP SECRET, CUI,
                                    # UNCLASSIFIED
```

Setting	Default	What it does
`site_enclave`	`""`	`classified` or `unclassified`. Empty: classified when a target host's name or address (`inventory_hostname`, `ansible_host`) ends in one of `site_enclave_classified_domains`, else unclassified. When set, it always wins
`site_enclave_classified_domains`	`[]`	the classified enclave's DNS suffixes, e.g. `[classified.example.mil]` - a suffix, any case (`web01.CLASSIFIED.example.mil` matches; `notclassified.example.mil` does not). One classified host makes the report classified
`report_banner`	`auto`	the classification banner on every report: `auto` = on in the classified enclave, off in the unclassified; `true` / `false` = always / never
`report_banner_text`	`SECRET`	the banner's text
`report_banner_color`	`""`	the banner's colour as `#rrggbb`; empty = the standard colour of the text's classification (below)
`report_banner_subject`	`true`	with the banner on: `(SECRET)` before the email subject (before `report_email_subject_prefix`)

The banner's colour follows the classification the text starts with - **UNCLASSIFIED** green (`#007a33`), **CUI** purple (`#502b85`), **CONFIDENTIAL** blue (`#0033a0`), **SECRET** red (`#c8102e`), **TOP SECRET** orange (`#ff8c00`) - with the text in white or near-black, whichever reads 4.5:1 or better. A text of no known classification is dark

grey unless `report_banner_color` says otherwise.

Where the banner goes, top and bottom:

- every email look (standard, command, portal, glass), and the plain text (its first and last line);
- every report website page and the index, the ticket insights pages (the site's and each team's), and the pages the job *Report website - copy* writes (the banner is kept with the report);
- in print: at the top and bottom of every sheet;
- the first row of each sheet of the workbooks (`report_email_xlsx`, and the reports' own), across the table, the column names under it.

Each job says which it used, in one line: `Banner SECRET (site_enclave: classified)` or `No banner (unclassified: no target host under site_enclave_classified_domains)`.

The outage AAR and SOP (Word, INCIDENT_DOCS.md) follow the banner: `incident_docs_banner: auto` (the default) is the report banner's text and colour when it is on - SECRET on the classified side without setting it twice - else the CUI marking; your own `incident_docs_banner` still wins. STIG Manager's (`stigman_classification`) and VMware ask's page (`vmware_ask_classification`) keep their own markings - set them too (section 4).

2. ACT (GenAI)

An enclave without a model endpoint - or one that loses it - turns ACT off with `site_act_enabled` (default `true`):

```yaml
site_act_enabled: false
```

Then **no job asks ACT**: no request, no model address or key needed, no error. Each report that would have had ACT's part says so in one line - *ACT is off (site_act_enabled false).* - and the job stays green:

- the runbooks with `use_act=true` (Health check, Database health, Troubleshoot): the findings, without ACT;
- the analyses (VMware alarms, capacity, right-sizing, log analysis, ticket insights, the ticket review, incident documents, fapolicyd): the report without ACT's part, the job not failed for it;
- *VM - ask a question*: the job's own reader takes the simple questions; one it cannot take ends green with one line ("Not answered: ACT is off ...");
- *VMware ask* (the page): the job's own reader only;
- *Service watch*: the standard fix, as when ACT cannot run;
- the VM deploy with `vm_deploy_genai`: the ticket's own `key: value` lines, as with `vm_deploy_genai: false`;
- *fapolicyd denials* (ACT's own playbook): nothing read, nothing asked - *fapolicyd* reads the denials without ACT.

`tests/test_act_switch.py` walks every place that calls ACT, so a job added later cannot miss the setting.

An enclave **with** a model: its own provider, models and addresses -

Setting	What to change
`site_act_provider`	the provider there (`genai`, `genai-beta`)

Setting	What to change
site_act_models	the model for each provider there
site_act_urls	the API address for each provider there (ACT's defaults are the unclassified enclave's)
site_act_ca	the CA file that signed the model's certificate
site_act_env	a proxy there (HTTPS_PROXY), if one is needed
the **ACT model key** credential	that enclave's key

3. The credentials

Every login is an AAP credential (SECRETS.md lists each type and what it carries), so each enclave's AAP has its own: create each one again there with that enclave's account - never copy one from the other AAP. Most addresses come with them, so they need no setting:

Credential	Carries the address of
Machine (SSH), Machine (WinRM)	- (the hosts are in the inventory)
VMware vCenter	the vCenter (VMWARE_HOST)
ServiceNow API	the instance (SN_HOST)
STIG Manager API	Keycloak's token address (STIGMAN_TOKEN_URL)
Registry	the registry (REGISTRY_HOST)
PAN-OS, IdM, Red Hat Ansible Automation Platform	the firewall, the IdM server (IDM_SERVER), AAP itself
Report website, mail relay login, MariaDB monitor, ACT model key, Teams webhook	-

4. Paths, addresses and hosts in all.yml (and the group files)

What a job reaches by its address, its files and what it trusts. Each is empty or a placeholder by default unless the table says otherwise; change each that the enclave uses.

Mail and the report website (EMAIL_REPORTS.md, WEB_REPORTS.md, REPORT_SHARE.md):

Setting	What to change
report_email_smtp_host, report_email_smtp_port, report_email_ca_path	that enclave's mail relay and its CA
report_email_from	an address that relay takes
report_web_dest, report_web_url, report_web_host, report_web_ca_path	that enclave's report website: the folder or share, its address, the Windows server
report_logo_file, report_email_header_text	the logo and the line with it

Trust and certificates:

Setting	What to change
`pki_bundle_url`, `pki_bundle_proxy`, `pki_bundle_ca_path`	the CA bundle's address there (the default is the unclassified bundle on the internet)
`aap_health_trust_cas`	the root CAs the AAP host must trust there
every `*_ca_path` (`servicenow_ca_path`, `stigman_health_ca_path`, `ucs_ca_path`, `ontap_ca_path`, `horizon_ca_path`, `tenable_ca_path`, `aap_ee_ca_path`, `net_config_panos_ca_path`)	the CA files there - same names, that enclave's files
`vmware_validate_certs`	`true` once the execution environment trusts that vCenter's CA

What the jobs reach:

Setting	What to change
`check_network_dns_names`, `check_network_tcp`	the names and ports every host must reach there (directory, ServiceNow, the log server)
`vmware_vcenters`, `vm_hostnet_targets`	the vCenters, and what the hosts' networks must reach
`vm_deploy_templates`, `vm_deploy_clusters`, `vm_deploy_datastores`, `vm_deploy_folders`, `vm_deploy_domain`	that vCenter's objects and the domain of new VMs (VM_DEPLOY_GUIDE.md)
`ontap_clusters`, `ucs_domains`	the storage clusters and UCS domains
`check_stig_stigman_api`, `check_stig_stigman_token_url`, `poam_stigman_api`, `stigman_health_api`, `stigman_health_token_url`, `stigman_oidc_provider`	STIG Manager and its Keycloak there
`check_stig_evaluate_answers`	the share with Evaluate-STIG's answer files
`stigman_images`, `vmware_ask_image`	the images from that enclave's registry or hub
`net_perf_targets`, `net_perf_ocsp`, `net_perf_iperf_pairs`, `tenable_scan_targets`, `net_cert_subnets`	the addresses to measure and scan there
`net_config_git_repo`, `net_config_share_host`, `cert_inventory_sql_server`	the repository, share and SQL Server there

Markings of their own (section 1): `stigman_classification`, `vmware_ask_classification` (`incident_docs_banner` follows the banner).

Outside `all.yml`:

- the inventories: the hosts, and an AD inventory source's `search_base` and `server` (the domain's own);
- each execution environment's `ansible.cfg` (copied from `ansible.cfg.example`): that enclave's hub (EXECUTION_ENVIRONMENT.md);
- the project's source control address in AAP.

5. Images for an air-gapped enclave

The report database's MySQL (`tools/report-db-setup.sh`) is started from an image already on the host. Since 1.50.0 the script never pulls it from Docker Hub. You bring the image in once, the same way in every enclave.

Local name (the default)	Used by	Upstream image
`localhost/mysql:8.4`	the report database	`docker.io/library/mysql:8.4`

STIG Manager's stack and VMware ask are not changed by this.

a. On a connected machine, pull and save the image:

```shell
podman pull docker.io/library/mysql:8.4
podman save -o mysql-8.4.tar docker.io/library/mysql:8.4
```

b. Carry the file in the way your enclave allows.

c. On the report database host, as root, load and tag it:

```shell
podman load -i mysql-8.4.tar
podman tag docker.io/library/mysql:8.4 localhost/mysql:8.4
podman images localhost/mysql
```

When the image is missing, the script stops at its step 2, before it changes anything. It prints these steps.

One setting per enclave. An enclave whose hosts reach its own registry can name it and allow the pull:

```shell
IMAGE=registry.enclave-b.example.mil/library/mysql:8.4 PULL=1 AAP_SOURCES="192.0.2.21" bash
  report-db-setup.sh
```

ENCLAVE-A loads the image by hand and sets nothing. Without `PULL=1` the script never pulls.

A database set up before 1.50.0 keeps running as it is. Its container and unit still name `docker.io/library/mysql:8.4`, and that image is on the host.

- The script keeps the container's image and restarts nothing.
- When its unit names another image than `IMAGE`, it says so and prints the commands to switch by hand.

6. Check it

1. *AAP - template variables audit* (TEMPLATE_AUDIT.md): nothing in a template's Variables that belongs in `all.yml` or a credential.
2. A report job with an email - say *Health check* on one host: the banner (or none) as section 1 says, the mail through that relay, the page on that website.
3. With ACT on: a job with ACT (*VM - ask a question*); with it off: the same job ends green with *ACT is off (site_act_enabled false)*.

10. ServiceNow: set up, test and verify

The runbooks open ServiceNow incidents for the problems the checks find (the **ServiceNow tickets** step), and check that ServiceNow itself is healthy (**ServiceNow health**). This page takes you from nothing to a **verified test ticket**, one step at a time:

1. an API account from the ServiceNow admins;
2. the addresses: the instance URL and the API calls;
3. the network path from AAP to ServiceNow;
4. a quick check from a shell (optional);
5. the credential in AAP;
6. your settings: which assignment group gets the tickets;
7. the **ServiceNow - test ticket** template;
8. a dry run, then a real run;
9. checking the ticket in ServiceNow.

Sign-in method. This integration uses **basic authentication only** (an account name and password over HTTPS). OAuth, CAC/PKI login and SSO are **not supported**. If your instance requires one of them for the API, ask the ServiceNow admins for an integration account that is allowed to use basic authentication for the Table API, and exempt from SSO.

Plan about 30 minutes, plus the time the ServiceNow admins need for step 1.

What you need

Item	Example	Who gives it to you
The instance URL	`https://yourinstance.servicenowservices.com` or `https://servicenow.example.mil`	the ServiceNow admins (or your browser's address bar)
An API account and its password	`svc_aap_sn`	the ServiceNow admins
Roles on that account	`itil` (and read on `ecc_agent`, `ecc_queue`, `ecc_agent_issue` for the MID Server check, e.g. `mid_server`)	the ServiceNow admins
The assignment group for the tickets	`Linux Operations`	the ServiceNow admins or your team lead
A network path from AAP to the instance	TCP 443 from the AAP execution nodes	the network or firewall team
Trust for the instance's certificate	the DoD root CA, if the instance uses a DoD certificate	you (step 3)

Step 1. Ask the ServiceNow admins for an API account

What. An account that only the automation uses, allowed to read, open and update incidents.

Why. The playbooks log in to ServiceNow's REST API with a user name and password (basic authentication). A dedicated account keeps the tickets traceable ("opened by svc_aap_sn"), and its access can be limited to what the automation needs.

Send them this (change the names in brackets):

```
Request: a ServiceNow integration account for Ansible Automation Platform (AAP)

- User ID: svc_aap_sn (or your naming standard)
- "Web service access only": ticked (API use only, no interactive login)
- "Internal Integration User": ticked, if our release has it
- Roles: itil (read, create and update incidents; read groups and users)
         mid_server, or read access to ecc_agent, ecc_queue and ecc_agent_issue (the MID Server
           list, their queue and their issues; only if we want the MID Server check)
  No admin role.
- Authentication: basic authentication over HTTPS for the Table API. If MFA or single
  sign-on is enforced, this account must be exempt, as web-service accounts usually are.
- If IP address access control is on: allow the AAP execution nodes' addresses: [addresses]
- Password: set, with "Password needs reset" unticked. Tell me the expiry or rotation
  rule, so the AAP credential can be updated in time.
- Tickets go to the assignment group: [Linux Operations]. Please confirm its exact name.
- If our instance has custom incident states or close codes: the value for "Resolved"
  and a valid close code.
```

You should get back the user ID, the password (through your normal secure channel), the exact assignment group name, and, if they are custom, the resolved state and close code.

Step 2. The addresses

The instance URL is the start of the address you see in your browser on ServiceNow: the `https://` and the host name, **nothing after it**.

In the browser	Instance URL for AAP
`https://yourinstance.servicenowservices.com/now/nav/ui/home`	`https://yourinstance.servicenowservices.com`
`https://servicenow.example.mil/nav_to.do?uri=incident_list.do`	`https://servicenow.example.mil`

The API calls. Everything goes to that host over HTTPS (TCP 443), with basic authentication and JSON. These are the only calls the playbooks make:

Method and path	What for	Used by
`GET /api/now/table/incident?sysparm_limit=1`	log in and read (the connection test)	test ticket, health
`GET /api/now/table/sys_user_group?sysparm_query=name=<group>`	does the assignment group exist?	test ticket
`GET /api/now/table/sys_user?sysparm_query=user_name=<caller>`	does the caller exist?	test ticket
`GET /api/now/table/incident?sysparm_query=correlation_id=...`	is a ticket for this problem already open?	tickets

Method and path	What for	Used by
`POST /api/now/table/incident`	open an incident	test ticket, tickets
`GET /api/now/table/incident/<sys_id>`	read an incident back	test ticket
`PATCH /api/now/table/incident/<sys_id>`	add a work note; resolve	test ticket, tickets
`GET /api/now/table/ecc_agent`	MID Servers: up, validated, heartbeat, version?	health
`GET /api/now/stats/ecc_queue?sysparm_count=true&sysparm_group_by=agent`	MID Servers' output waiting too long (stuck)?	health
`GET /api/now/table/ecc_agent_issue`	open MID Server Issues?	health
`GET /api/now/table/sys_user_group?sysparm_query=nameIN...`, `/sys_user?sysparm_query=user_nameIN...`	the assignment group's and the people's sys_ids	weekly activity report
`GET /api/now/table/<incident, sc_task, change_request, change_task, problem_task ...>?sysparm_query=assignment_groupIN...^opened_at<=...`	the group's tasks of the week (SERVICENOW_WAR.md)	weekly activity report
`GET /api/now/table/task_sla?sysparm_query=taskIN...^stage!=cancelled`	those tasks' SLAs: breached, or close to breaching	weekly activity report
`GET /api/now/table/<incident, sc_req_item, sc_task, change_request, change_task, problem>?sysparm_query=opened_at>=...^ORclosed_at>=...^ORactive=true...`	months of tickets, page by page (SERVICENOW_INSIGHTS.md)	ticket insights
`GET /api/now/table/sys_audit?sysparm_query=tablename=incident^fieldname=assignment_group^documentkeyIN...`	the groups an incident passed through	ticket insights

With `cert_renew_servicenow: catalog` the certificate renewals order the PKI's catalog item instead of opening incidents (CERT_RENEWAL_CATALOG.md). Those jobs, and the catalog test, make these calls:

Method and path	What for
`GET /api/sn_sc/servicecatalog/items?sysparm_text=<name>`, `GET /api/sn_sc/servicecatalog/items/<sys_id>`	find the item; its questions
`GET /api/now/table/sys_user`, `/cmn_location` (or another reference's table) `?sysparm_query=name=...`	a reference answered by name: its sys_id
`GET /api/now/attachment?sysparm_query=file_nameSTARTSWITH...`	has this certificate's CSR been ordered already?
`GET /api/now/table/sc_req_item/<sys_id>`, `?sysparm_query=request=<sys_id>`	that request's state; the requested item of a new order
`POST /api/now/attachment/file`	the CSR, for the item's attachment question (or on the requested item)

Method and path	What for
`POST /api/sn_sc/servicecatalog/items/<sys_id>/order_now`	the order
`GET /api/now/attachment/<sys_id>`	is the CSR on the requested item?

Step 3. The network path from AAP

Which machine talks to ServiceNow. The ServiceNow jobs run on the **AAP execution node**, inside the execution environment container, not on your managed hosts. To see the nodes, open **Automation Execution › Infrastructure › Instances** (or **Instance Groups**). Those are the addresses the firewall (and ServiceNow's IP access control, if any) must allow.

Firewall. Allow the execution nodes › the instance, TCP 443.

A proxy. If the execution nodes reach the outside only through a proxy, give the jobs the proxy settings. Go to **Settings › Automation Execution › Job › Edit › Extra Environment Variables**, and set (add to what is already there):

```
{"https_proxy": "http://proxy.example.mil:8080", "no_proxy": "localhost,127.0.0.1,.example.mil"}
```

This applies to every job. Leave hosts that must not go through the proxy in `no_proxy`.

The certificate. A ServiceNow instance with a DoD certificate is only trusted if the execution environment trusts the DoD root CA. Choose one:

Option	How	When
A. The CA in the execution environment	have the AAP admins build the execution environment with the DoD root CAs in its trust store	best: every job trusts it
B. A CA file in the repository	put the CA certificate (PEM) in the project, for example (an example path: the folder does not exist until you create it) `playbooks/files/ca/servicenow-ca.pem`, and set `servicenow_ca_path: "{{ playbook_dir }}/files/ca/servicenow-ca.pem"` (step 6)	when you cannot change the execution environment. CA certificates are public, so this is fine
C. Switch the check off	`servicenow_validate_certs: false`	only for one test, never for real use

Step 4. Check from a shell first (optional, fastest)

On the AAP execution node, or any Linux machine on the same network:

shell

```
curl -sS -u svc_aap_sn -H 'Accept: application/json' \
  'https://yourinstance.servicenowservices.com/api/now/table/incident?sysparm_limit=1&sysparm_fiel
    ds=number'
```

`curl` asks for the password, so it is not left in your shell history.

You should see `{"result":[{"number":"INC0012345"}]}` (any number). Anything else:

What you get	What it means
`SSL certificate problem: unable to get local issuer certificate`	the CA is not trusted (step 3, the certificate)
`Could not resolve host`	DNS: check the host name
nothing, then `Connection timed out`, or `Connection refused`	firewall or proxy (step 3)
`{"error":{"message":"User Not Authenticated"...}}` (HTTP 401)	wrong user or password, the account is locked, or it is not allowed to use basic authentication
`{"error":{"message":"Operation Failed","detail":"ACL Exception..."}}` (HTTP 403)	the account lacks the `itil` role
an HTML page	the URL has something after the host name, or a login page (SSO) answered: the account must be exempt from SSO

Step 5. The credential in AAP

1. If you have not yet, create the **ServiceNow API** credential type (SETUP_AAP.md, step 2). It uses the file `aap/credential_types/servicenow_api.yml`.
2. **Automation Execution › Infrastructure › Credentials › Create credential**:
   - **Name** `ServiceNow API`;
   - **Credential type** `ServiceNow API`;
   - **Instance URL**: from step 2 (only `https://` and the host name);
   - **API user name** and **API password**: from step 1.
3. **Create credential**.

You should see the credential listed, with the password shown as `ENCRYPTED`. The job gets the three values as `SN_HOST`, `SN_USERNAME` and `SN_PASSWORD`. They never appear in job output, and never reach your managed hosts.

Step 6. Your settings

In VS Code, open `playbooks/group_vars/all.yml`. (If your inventory comes from Git, the same lines in `inventories/site/group_vars/all.yml` end up in AAP's inventory Variables box, and the project's file wins over them: keep each setting in **one** place. See VARIABLES.md.) In the ServiceNow block, delete the `#` in front of the lines and fill in your values:

```
---- ServiceNow tickets ------------------------------------------------------------
servicenow_assignment_group: Linux Operations   # the exact name from step 1
servicenow_min_severity: warning                # or critical: tickets for critical findings only
# servicenow_caller: svc_aap_sn                  # optional; empty = the API account is the caller
# servicenow_ca_path: "{{ playbook_dir }}/files/ca/servicenow-ca.pem"   # step 3, option B
```

Fields your instance makes mandatory. If your incident form requires more fields (a red asterisk: Location, Subcategory, Channel ...), set them for every new ticket, and the fields a resolved ticket needs for the resolve step. Use each field's **column name**: right-click its label on the form and choose **Show - '<column name>'** (Channel is `contact_type`). Names and choice labels work as values, as they appear on

the form:

```yaml
servicenow_category: Software
servicenow_fields:
  location: "Building 100"
  subcategory: "Operating System"
  contact_type: "Self-service"         # Channel
servicenow_close_code: "Solution provided"     # Resolution code, as your instance has it
servicenow_resolve_fields:
  resolved_by: svc_aap_sn
```

Mandatory fields enforced only by the form (UI policies) do not stop the API, but the ticket then cannot be closed by hand until someone fills them in, so set them here anyway. A data policy does stop the API: step 3 or 6 of the test then fails with `Data Policy Exception` and names the field.

Commit and **Sync Changes**. Every other ServiceNow setting (urgency, impact, resolve, close code) is described in `roles/servicenow/defaults/main.yml`.

All settings, with their defaults: servicenow.

Step 7. The ServiceNow - test ticket template

Automation Execution › Templates › Create template › Create job template:

Field	Value
Name	`ServiceNow - test ticket`
Inventory	any (for example `rhel-inventory`); it runs on AAP itself, not on these hosts
Project	`site-automation`
Playbook	`playbooks/servicenow_test_ticket.yml`
Credentials	`ServiceNow API`
Job type	Run, with **Prompt on launch** ticked (so you can pick *Check*, a dry run)
Limit	empty, and **no** Prompt on launch
Privilege escalation	not needed

Create job template.

Step 8. Run it: first a dry run, then for real

The dry run. Launch › **Job type** `Check` › **Launch**. Steps 1 and 2 run for real, because they only read. Steps 3 to 6 are only printed:

```
PASS 1 connection: the instance answers and svc_aap_sn logged in and read the incident table (0 s)
PASS 2 settings: assignment group "Linux Operations" exists; caller not set: the tickets show the
  API account as the caller
DRY RUN (Check mode): steps 1-2 ran (they only read). Steps 3-6 would:
3 open: POST https://yourinstance.servicenowservices.com/api/now/table/incident {...}
```

Nothing was created in ServiceNow.

The real run. Low priority does not mean silent: ServiceNow may still send its usual emails, to the assignment group for the new incident and to the caller when it is resolved. Warn the group first, or point the test at a test group (`servicenow_assignment_group: <test group>` in the template's **Variables**), or at a test instance if you have one.

Launch › **Job type** Run. At the end it prints a summary like this:

```
ServiceNow test at https://yourinstance.servicenowservices.com as svc_aap_sn:
PASS | 1 connection | the instance answers and svc_aap_sn logged in and read the incident table (0
  s)
PASS | 2 settings | assignment group "Linux Operations" exists; caller not set: ...
PASS | 3 open | opened INC0012346 (sys_id 5f1c...)
PASS | 4 read back | INC0012346: state New, priority 5 - Planning, assignment group Linux
  Operations, ...
PASS | 5 work note | added a work note to INC0012346 (see its Activity stream)
PASS | 6 resolve | resolved INC0012346 (state 6)
```

Step 4 also prints a link: `Open it in ServiceNow: https://.../nav_to.do?uri=incident.do?sys_id=...`.

Result	Meaning
PASS	that step works
WARN	it works, but look at it (for example, no assignment group is set, or the instance would not resolve the ticket). The job stays green
FAIL	that step does not work. The job is red, and the line says why and what usually causes it

To leave the test ticket open and look at it first, add `servicenow_test_resolve: false` to the template's **Variables**.

Step 9. Check the ticket in ServiceNow

1. Click the link from step 4 of the job output, or go to **Incident › All** and search for the number (`INC0012346`).
2. Check:
   - **Short description**: `[site-automation test] test ticket from AAP job <number> - safe to close`;
   - **Assignment group**: yours (step 6);
   - **Caller**: your `servicenow_caller`, or the API account;
   - **Urgency** 3 and **Impact** 3, so normally **Priority** 5 - Planning, the lowest (your instance's priority table decides). The real tickets use `servicenow_urgency` and `servicenow_impact`;
   - **Activity**: the work note `Test work note from AAP job ...`;
   - **State**: Resolved, with the close notes `Test ticket from AAP job ...: resolved automatically by the same job` (unless you set `servicenow_test_resolve: false`).
3. To find every test ticket: filter **Incident › All** on **Correlation display** = `site-health-test`.

The test passes when all six steps say PASS (or WARN for step 6, if you do not resolve tickets automatically), and the ticket in ServiceNow looks like the list above.

When a step fails

Step and message	Cause	Fix
1: `Attach the "ServiceNow API" credential`	the template has no ServiceNow credential	step 7: add it under Credentials
1: `HTTP -1 ... certificate verify failed`	the execution environment does not trust the instance's CA	step 3, the certificate
1: `HTTP -1 ... Name or service not known`	DNS	the Instance URL's host name; DNS from the execution node
1: `HTTP -1 ... timed out` or `Connection refused`	firewall or proxy	step 3
1: `HTTP 401`	wrong user or password; account locked or inactive; "Password needs reset"; basic authentication not allowed	step 1 with the admins, then update the credential
1: `HTTP 403`	the account may not read incidents	the `itil` role
1: `HTTP 404`	the Instance URL has a path after the host name	only `https://` and the host name
2: `assignment group "..." does not exist`	the name differs from ServiceNow's, even in capitals or spaces	copy the exact name from ServiceNow into `servicenow_assignment_group`
2: `could not look up ...` (WARN)	the account may not read groups or users	fine if step 4 shows the group; otherwise ask for read access to `sys_user_group`
3: `HTTP 403 ... ACL Exception Insert Failed`	the account may read but not create incidents	the `itil` role
3: `HTTP 400`	ServiceNow refused a value, and says which	usually `servicenow_category` or a custom field
4: `did not stick` (WARN)	the ticket was opened without the group	the group name (step 6)
5: `HTTP 403`	the account may create but not update	the `itil` role, or an ACL on work notes
6: `could not resolve ... Data Policy Exception` (WARN)	the instance needs other values to resolve	ask the admins for the resolved state and close code; set `servicenow_resolved_state` and `servicenow_close_code`. Only needed if you use `servicenow_resolve_cleared: true`

MID Servers

The **ServiceNow health** job (`playbooks/servicenow_health.yml`) checks the MID Servers - all of it, in one job and one report, with a MID Server table. No other job needs a MID Server setting.

What the instance says (the API account, from the AAP side):

Finding	Severity	Setting
a MID Server Down (or any state but Up), or not validated	critical	
Upgrading or Paused	warning	
Up, but its heartbeat (`last_refreshed`) older than 15 minutes	critical	`servicenow_mid_stale_minutes`
one you expect is not in the list (renamed, deleted)	critical	`servicenow_mid_expected: [mid01, mid02]`
the MID Servers on different versions (one stuck in its upgrade)	warning	`servicenow_mid_version_check`
output waiting more than 10 minutes for a MID Server (it is not picking up its work)	warning; 50 or more critical	`servicenow_mid_queue_minutes`, `_queue_warn`, `_queue_critical`
open MID Server Issues	warning	`servicenow_mid_issues_check`

Only some MID Servers: `servicenow_mid_names: [PROD-*]`. A table the account cannot read (ecc_queue, or ecc_agent_issue on an older release) is said in the job's output, not counted as a problem.

What the MID Server hosts say (Windows, over WinRM, in the same run): put the MID Server hosts in a group `servicenow_mid_hosts` of your **Windows** inventory (`inventories/example-windows/hosts.yml`), run the ServiceNow health template with that inventory, and attach its **Machine (Windows)** credential next to the ServiceNow API one. The check reads, and changes nothing:

Finding	Severity	Setting
a MID Server service (`snc_mid*`, or display name "ServiceNow MID Server*") not running	critical	`servicenow_mid_service_match`
its service not set to start by itself	warning	
it runs, but its agent log (`agent\logs\agent0.log.0`) not written for 30 minutes - hung	critical	`servicenow_mid_log_stale_minutes`
20 or more SEVERE lines in the agent log in the last 24 hours (the latest one shown)	warning	`servicenow_mid_severe_warn`, `servicenow_mid_hours`
the JVM crashed, hung or ran out of memory (`wrapper.log`)	warning	`servicenow_mid_jvm_restarts_warn`
the agent's drive under 10 % free (5 %: critical)	warning	`servicenow_mid_disk_warn_pct`, `_critical_pct`
`config.xml` pointing at another instance (after a clone, a moved MID Server)	critical	`servicenow_mid_url_check`
a host of the group not reached, or no MID Server service on it	critical / warning	

The two views meet in the report: a MID Server the instance says is Down names its stopped service, and the host it runs on. The agent folder is read from each service's command line, so any install folder works. A group named otherwise: `servicenow_mid_hosts_group`; the instance's view only: `servicenow_check_mid_hosts: false`. The MID Servers' logs explained by ACT: the log analysis with `log_analysis_profiles: [mid_server]` (LOG_ANALYSIS.md).

In a workflow: `[ServiceNow health] --Always--> [ServiceNow tickets]` opens one incident per MID Server problem (on the host "servicenow"). Hourly is a good schedule. When the API itself is down, an AAP notification on the template's failure is the alert: a broken ServiceNow cannot take tickets.

Self-hosted instance

An instance you run yourself - front-end (application) nodes on RHEL, MariaDB on its own RHEL host, the MID Servers on Windows (above) - gets the rest of its health in the same **ServiceNow health** report: the nodes, the database host and the instance's cluster view. Nothing is started, stopped or changed. The one thing the job writes is the database's size, kept for its growth: a small JSON file on the database host (`servicenow_db_history_file`, `/var/lib/site-health/servicenow-db-history.json`), never in Check mode; `servicenow_db_history: false` turns it off (and the growth with it). Without these groups in the inventory the job is as before.

The groups (your Linux inventory, `inventories/example/hosts.yml` shows them):

YAML

```
servicenow_nodes:            # the front-end nodes (servicenow_nodes_group)
  hosts:
    node01.yoursite.mil:
    node03.yoursite.mil:
servicenow_db_hosts:         # the database host (servicenow_db_group) - already a child of
                             # mariadb_hosts
  hosts:
    snowdb01.yoursite.mil:
```

The nodes, over SSH with sudo (the Linux **Machine** credential; root reads the node's logs):

- **The units.** Each node runs as a systemd unit `snc_<env>.service`; a box normally runs one of them. `servicenow_node_units: [snc_prod, snc_test, snc_dev]` (the default) is what is looked for: the units installed on the host are judged, those not installed are no finding, and a host of the group with none of them is critical ("no ServiceNow node unit found"). `servicenow_node_units: []` finds every `snc_*.service`.
- **The install folder**, `servicenow_node_home: /glide`. A node's own folder is the one its unit starts from (`/glide/nodes/prod_16000`), else `/glide/nodes/<env>*`; its logs are the `localhost_log*` files in its `logs` folder, its port `glide.servlet.port` in its `conf/glide.properties`.
- **The stats page**, read from the node itself. The port: `servicenow_node_port` (a number, or per unit `{snc_prod: 16000, snc_test: 16001}`), else `glide.servlet.port` in the node's `conf/glide.properties` (that key only), else the unit's command line (`-Dglide.servlet.port`), else the port the unit's java listens on.
- **Where it is asked**, in turn, until one answers with the numbers: `https://<the node's own name>:<port>`, `http://` on it (its inventory name, then its FQDN), `http://127.0.0.1`, `https://127.0.0.1` (a TLS connector answers plain HTTP with 400), then 127.0.0.1 with a name as the Host header (the node's, then the instance's); each `/xmlstats.do`, then `/stats.do`.

- **The instance's address is never asked** (`glide.servlet.uri`): a load balancer hands it to any node, so its numbers are not this node's. The report's *Stats page answered at* column says which address answered, per node.
- **Or force one address:** `servicenow_node_stats_url: "https://{fqdn}:{port}/stats.do"`.
- **A page that asks for a login** (401, 403, a login page - or, with `auto`, the instance's normal web page in place of the numbers) is asked again with the ServiceNow API credential's login (basic auth; `servicenow_node_stats_auth: auto`, or `basic` from the start, `none` never). The login is sent only over HTTPS to the node's own name (its inventory name or FQDN) or to 127.0.0.1, and never shown.
- **The login refused too** (the web page again, 401 or 403): the finding says *the stats page wants a login this account cannot give (the API account needs a role that may read stats.do)*. The page wants single sign-on, or the account has no access to the UI or to `stats.do`. Give the account that role, or try the XML page: `servicenow_node_stats_url: "https://{fqdn}:{port}/xmlstats.do"`.
- **A redirect** (to login.do, an SSO page) is not followed, so the login never goes on to another address: that try fails and says where it pointed.
- **Single sign-on in front, and no basic auth** (every try ends in a redirect to `logout_redirect.do`): `servicenow_node_stats_auth: form` logs in through the instance's local login page. It needs its own credential - see *The node stats login* below.
- **HTTPS is checked** - the certificate and the name, with the node's own trust store (`servicenow_node_validate_certs: true`): a self-signed certificate, or one from a CA the node does not trust, needs that CA in the node's trust store, or the setting false. Plain HTTP on 127.0.0.1 is read as before.
- **Not read:** the finding says the port and the last answer, and lists what was tried and how the answer began.
- **The numbers** are found by their names on the page (memory max and in use, the semaphore sets' in use and queue depth, the scheduler's workers and queue, active transactions, uptime, the node's ID). A page that answers but holds none of them is said, and a field it cannot find is shown as `-`. The page is read 3 times, 5 seconds apart (`servicenow_node_stats_samples`, `_interval`): a semaphore queue counts only when it is there in every read.

The node stats login (optional; `servicenow_node_stats_auth: form`). For nodes that show `stats.do` only in a logged-in session: single sign-on is in front, and the API login (basic auth) is answered with a redirect. The check then does what a browser does, on the node's own address:

1. it reads `side_door.do` (the instance's local login page) for the form's hidden `sysparm_ck`; when that page shows no form (some instances answer it with a redirect to `navpage.do`), it reads `login.do` once for the form;
2. it sends the user name and password to `login.do`, once;
3. it reads the stats page in that session (3 reads, as always);
4. it logs out (`logout.do`), also when a read failed.

Set it up:

1. **In ServiceNow**, ask for a dedicated **local** account (not a single sign-on one), for example `svc_aap_stats`, with only a role that may read `stats.do`. Not a person's account, not an admin, and not the API account.
2. **Try it in a browser:** `https://node01.yoursite.mil:16000/side_door.do`, log in, then open `https://node01.yoursite.mil:16000/stats.do`. **You should see** the stats page.

3. **In AAP**, create the credential type **ServiceNow node stats login** from `aap/credential_types/servicenow_node_stats_login.yml` (SETUP_AAP.md, step 2), then a credential of that type with the account's user name and password.
4. **On the template** *ServiceNow health - nodes*: add that credential, and in Variables:

```yaml
servicenow_node_stats_auth: form
```

5. Run it. **You should see** the nodes' numbers in the *Front-end nodes* table, and no finding about the stats page.

What to know:

- **One login per node address per run.** A node address is the node and its port. Each run shows as one UI login per address in the instance's login history (hourly: 24 a day).
- A node with one instance: one login.
- A node whose units answer on one port: one login, and the units share the session.
- A node with two instances on two ports: one login each.
- **No login form on `side_door.do` and on `login.do`:** the instance's local login is switched off or redirected. Nothing is sent. Ask the ServiceNow admins, or read this instance's nodes with `servicenow_node_stats_auth: basic`.
- **Never a second try.** The first node is asked alone. When its login is refused, the other nodes and the listed stats pages send none in that run, so a wrong password costs one failed login, not one per node.
- **The login is refused** when `login.do` answers anything but the redirect to `login_redirect.do`: a wrong password, a locked account, a page that asks one more step (a code, a new password). The finding says the status and where the answer pointed - never the page.
- **Where the login goes:**
- over HTTPS to the node's own name;
- or to 127.0.0.1 on the node, also over plain HTTP - it never leaves the node;
- for a listed stats page: only over HTTPS to the host the entry names.

Over HTTPS the certificate is checked. No redirect is followed, and a line about one shows only its page, never what follows the `?`.

- **What is kept:** nothing. The session's cookies and the `sysparm_ck` live in memory until the node is read; they, and the password, are in no result, log or report.
- `auto` **never picks** `form`, and `form` never uses the API account.
- **The logout failed:** a warning. The session stays open until the instance's session timeout.

A friendly name per node (optional). The report shows it beside the host - *Node 1 (node01.yoursite.mil)* - in the *Front-end nodes* table, the findings and the *Start here* cards. Either way:

- on the node, in the inventory: the host variable `servicenow_node_label: Node 1`;
- or by host, in the template's Variables:

```yaml
servicenow_node_labels:
  node01.yoursite.mil: Node 1
  node03: Node 3            # the inventory name, or its short name
```

The host variable wins. The host stays in every line, and the tickets' keys do not change.

Nodes AAP does not log in to (optional, off by default): list each node's own stats page, and the job reads it from the AAP side - no SSH to that node.

```yaml
servicenow_node_stats_pages:
  - {name: "Node 1", url: "https://node01.yoursite.mil:16000/stats.do"}
  - {name: "Node 3", url: "https://node03.yoursite.mil:16000/stats.do"}
```

- The same numbers, the same 3 reads and the same thresholds as a node read over SSH.
- A redirect is never followed. The login goes only over HTTPS, and only to the host the entry names.
- The `url` is plain: `https://host:port/page`. One that carries a login (`user@`), a `#`, a backslash or a blank is refused before anything is read, and the message names the entry.
- With `servicenow_node_stats_auth: form`, two entries on one address (the same host and port, two pages) share one login.
- The unit, the log, the disk and fapolicyd of such a node are not read: its rows say *stats page only*.
- A host that is also a node of `servicenow_nodes` is read once, over SSH; the entry's name becomes its friendly name.
- An entry that does not answer is a finding that names the entry and what was tried (critical: not reached; warning: answered, but not read). The job never ends green having read nothing.
- The execution environment must reach each address: the node's port open from AAP, and the node's CA trusted there (or `servicenow_node_validate_certs: false`).
- With no node in the inventory at all, the listed pages are the nodes (`servicenow_health_part: nodes`).

Finding	Severity	Setting
a node host not reached; none of `servicenow_node_units` installed on it	critical	`servicenow_node_units`
a node unit not running	critical	
a node unit that does not start at boot	warning	
its stats page not answering while the unit runs	critical	
the stats page refused (HTTP 401/403), no port found, nothing on it recognised	warning	`servicenow_node_port`
the stats page wants a login the API account cannot give	warning	`servicenow_node_stats_auth`, `servicenow_node_stats_url`
`form`: the node stats login refused (the other nodes: not read, the login is not tried again)	warning	the *ServiceNow node stats login* credential
`form`: no login form on `side_door.do` or `login.do`; logged in and still no numbers; no credential on the template	warning	`servicenow_node_stats_auth`

Finding	Severity	Setting
`form`: the session was not closed (`logout.do` failed)	warning	
a listed stats page (`servicenow_node_stats_pages`) not reached	critical	`servicenow_node_stats_pages`
JVM memory in use 85 % of its max (95 %: critical)	warning	`servicenow_node_mem_warn_pct`, `_critical_pct`
transactions queued for a semaphore in every read (10 or more: critical)	warning	`servicenow_node_semaphore_queue_critical`
more than 50 scheduled jobs waiting for a worker	warning	`servicenow_node_scheduler_queue_warn`
OutOfMemory in the node's log in the last 24 hours	critical	`servicenow_node_log_hours`
semaphore problems: a semaphore queue, a limit exceeded or a wait timed out, or a slow transaction that waited 1000 ms or more for its semaphore	warning	`servicenow_node_semaphore_wait_ms`
200 or more slow transactions ("waited excessive time to run")	warning	`servicenow_node_slow_tx_warn`
100 or more SEVERE lines (the most frequent message shown)	warning	`servicenow_node_severe_warn`
the install folder's or `/`'s filesystem 85 % used (95 %: critical)	warning	`servicenow_node_disk_warn_pct`, `_critical_pct`
swap 50 % used	warning	`servicenow_node_swap_warn_pct`
fapolicyd denials today (by program and path)	warning	`servicenow_fapolicyd_since`
a fapolicyd denial of the node's java or its install folder	critical	`servicenow_node_fapolicyd_critical`

The log lines are grouped by their message, as the AAP health check groups its containers' errors (times, thread numbers, transaction and session IDs, IDs in paths, numbers taken out): the report's **Node log errors** table lists the most frequent (`servicenow_node_log_groups`, 10). A slow transaction is one of three kinds: *semaphore wait* (it waited for one of the node's semaphores - the only kind that is a semaphore problem), *session wait* (its session wait about its whole run: one user's own requests queued behind each other) or *slow transaction*; the table gives each group's longest run and session wait. Who did it is never shown: a user name in a log line becomes `user: …` in the report and the email.

The cluster, from the API (GET `sys_cluster_state`: `system_id`, `node_id`, `status`, `most_recent_message`, `schedulers`; the API account needs read on that table - admin, or an ACL). Read when the inventory has front-end nodes (`servicenow_cluster_check: auto`; `true` / `false`):

Finding	Severity	Setting
a node of the inventory offline in the cluster	critical	
a node online, but its last heartbeat older than 10 minutes (hung)	critical	`servicenow_cluster_stale_minutes`
an online node whose host is not in `servicenow_nodes` (not checked)	warning	
an offline node not in the inventory (a retired node's record, which can be deleted)	warning	
a host of `servicenow_nodes` not in the cluster (the finding names the units it runs)	warning	`servicenow_cluster_check`

A table the account cannot read is said in the job's output, not counted as a problem.

Two instances (say production and development): a node that runs `snc_dev` is not in the cluster of the production instance, and the finding says so - *node05 (runs snc_dev) is in the inventory group ..., but not in the instance's cluster*. Use one job template per instance: its own group (`servicenow_nodes_group`) and its own ServiceNow credential. Or `servicenow_cluster_check: false`.

fapolicyd, on every node and the database host (as root, read-only): is it active, and what did it deny today (`ausearch -m FANOTIFY -ts today`), grouped by the program and the path denied - a table in the report. fapolicyd inactive is said, as info, and is no finding; denials while it runs are a warning, and a denial of what the host runs is critical: the node's `java` or its install folder (`servicenow_node_fapolicyd_critical`), the database server (`mariadbd`, `mysqld`), `/database` or its data dir (`servicenow_db_fapolicyd_critical`). `servicenow_fapolicyd: false`: not read.

The database host, over SSH with sudo:

- **The database** - the MariaDB check (MARIADB.md: up, connections, slow queries, the error log, replication if any). Attach the **MariaDB monitor** credential - the same one as STIG Manager's (`aap/credential_types/mariadb_monitor.yml`; MARIADB.md section 4 has the GRANT). What it runs: `servicenow_db_checks: [mariadb]`.
- **Its disk**: the filesystems of `servicenow_db_paths` (`[/database]`), of the data dir and of `/`. The data dir is what the server says (`@@datadir`); one that is not under `servicenow_db_paths` is a warning (the disk watched is not the one it fills). A database in a container: `servicenow_db_datadir` is its data dir's path on the host.
- **Its size against that disk** (the report's *Database size*, *Largest schemas* and *Largest tables*): data and indexes per schema from `information_schema` (names and numbers only), plus InnoDB's system, undo and redo files; the filesystem holding the data dir, used and free; the database's share of it; the 5 largest schemas and the 10 largest tables (`servicenow_db_top_schemas`, `_tables`). The monitor account sees in `information_schema` only the schemas it may read; when it sees none, the sizes are read from the data dir's own files instead - one level down, the size of each file, never a recursive `du` of the database.
- **Its growth**: each run's size is kept in `servicenow_db_history_file` (60 days); from the second run the change since the last one, from a day on the growth per day, and when the data dir's filesystem is full at that growth.

Finding	Severity	Setting
the database host not read	critical	
`/database`, the data dir's or `/`'s filesystem 85 % used (95 %: critical)	warning	`servicenow_node_disk_warn_pct`, `_critical_pct`
at the database's growth, its filesystem full in under 30 days (7: critical)	warning	`servicenow_db_fill_warn_days`, `_critical_days`
the data dir not under `servicenow_db_paths`	warning	`servicenow_db_paths`, `servicenow_db_datadir`
fapolicyd denials (the database server or its data: critical)	warning	`servicenow_db_fapolicyd_critical`
what the MariaDB check finds	its own	MARIADB.md

Another group name: `servicenow_db_group`. Read only when the inventory has front-end nodes (`servicenow_check_db: auto`), so an inventory that has `servicenow_db_hosts` for its Health check is not read by this job before then; `true` / `false` to force it.

Two templates, or one. AAP gives a job template one inventory and one Machine credential, and the MID Server hosts (Windows, WinRM) and the nodes (Linux, SSH) need one each:

- **Two templates** (recommended): *ServiceNow health* as before - the Windows inventory, `servicenow_health_part: mids` - and **ServiceNow health - nodes**: the same playbook, the Linux inventory, its Machine credential, ServiceNow API, MariaDB monitor (and, with `servicenow_node_stats_auth: form`, ServiceNow node stats login), and `servicenow_health_part: nodes`. The nodes part reads the API it needs (the answer, the cluster) and no MID Server. Its findings carry the check `servicenow_node`, never `servicenow`, so the two templates never resolve each other's tickets.
- **One template** (`servicenow_health_part: all`, the default): its inventory holds both - an AAP constructed inventory of the Windows and Linux ones - with the Linux Machine credential and the MID Server hosts' WinRM login in their group's variables (`ansible_user`, `ansible_password` from a vaulted value).

A **Limit** works: `-l node01.yoursite.mil` reads that node alone (with the API, on the AAP side - the node stands in for localhost with a local connection); the hosts of the groups outside the Limit are not contacted and not judged, and the job's line names them. **No group** `servicenow_nodes` in the inventory: the Limit's hosts are the front-end nodes (`-l node01.yoursite.mil,node03.yoursite.mil`; not localhost, not a MID Server or database host), and the job says so. `servicenow_check_nodes: false`: no node and no database host is read.

The job **never ends green having read nothing**: before it reads any host it fails, saying why and listing the groups the inventory has, when `servicenow_health_part: nodes` finds no front-end node (no group `servicenow_nodes_group` - or one with no hosts - and no Limit naming them), when `servicenow_check_db: true` names a database group that is not there, or when `servicenow_health_part: mids` finds no MID Server hosts' group (`servicenow_check_mid_hosts: false` for the instance's view only). With `all` (the default) a missing group means that part is not read, as before.

In a workflow: `[ServiceNow health - nodes] --Always--> [ServiceNow tickets]`, hourly, like the MID Servers' template. A problem opens one incident on the host "servicenow" (check `servicenow_node`).

Next

- **ServiceNow health** (hourly): the instance's API and the MID Servers (above); a self-hosted instance's nodes, database host and cluster with **ServiceNow health - nodes** (above).
- **The tickets step** in the *Daily health* workflow (WORKFLOWS_AND_SCHEDULES.md): one incident per problem, updated on later runs, noted or resolved when it clears.
- Keep **ServiceNow - test ticket**. Run it again after a password change, a new certificate, or a ServiceNow upgrade.

11. ServiceNow - ticket insights: months of tickets for management

ServiceNow - ticket insights (`playbooks/servicenow_insights.yml`) reads months of tickets from ServiceNow and turns them into one report for management: what the site's incidents are really about and how they get fixed, what people ask for most, whether the teams keep up, where tickets bounce between groups, which changes went wrong and what followed, which close notes say nothing, and who the All-stars of each team are. ACT (GenAI) groups the incidents into issues, writes each top issue's fix from its close notes (or suggests one, marked, where the notes say too little) and drafts knowledge articles. It runs on the AAP side with the **ServiceNow API** credential and only reads (in Check too).

The report is a **web page** (the report website, `report_web_dest`) with collapsible sections, search, sortable tables, copy buttons and charts - one for the whole site and one for each team, linked to each other. The **email** is optional and simpler: the tiles and the main tables, a link to the page, and an Excel workbook with every incident.

What the page has

Section	What it shows
At a glance	the tickets read, open now (and at the start), the median time to resolve an incident, SLAs met, reopened (or *came back*, below), bare close notes, changes successful, incidents reassigned 3+ times - each against the window before; then **What the period says**: three or four sentences, written by ACT from the tables (or made from the numbers without it)
Teams side by side (the site's page)	one row per team: its backlog over the period (Keeping up / Falling behind), open now with what it was, open over 30 days, median fix, SLA met, its close notes, its change tasks closed / open (1.2.0), its top issue - the team's name opens its own page
Act on first (1.7.0)	what the process says to look at, as tiles and lists (the first 10 rows, the rest folded): **SLA at risk now** (open incidents past 75% of their SLA, or breached and still open - worst first), **open over 3 hops**, **Awaiting Caller over 6 business days**, **No Resolution Provided** in the period (each for leadership's review, the close note's start with names and numbers replaced), **resolved, not closed after 7 days** - below
Hops, on hold and resolution codes (1.7.0)	per group: over the hop limit and the hops each group took, on hold now (no reason, Awaiting Caller too long), on hold by reason and business days, the resolution codes to look at and reopened
How incidents ended (1.7.0)	the outcome mix (Fixed, Workaround, Duplicate, Known Error, No Resolution Provided) per group against the window before, **unable to resolve**, first-contact resolution (and the service desk's), reopened within 7 days
Time in each state (1.9.0)	stacked bars per group: the average hours waiting to start, in progress and on hold, for the incidents resolved in the period. A table view adds resolved to closed. On hold: its share of the time, repeat holds, the reasons
Backlog age and flow (1.9.0)	what is open now per group, by business days since opened (0-1, 2-5, 6-10, over 10). Each week's net: opened minus resolved
Ticket quality and hot spots (1.9.0)	per group: no real category, no CI, a short description. The CIs with the most incidents and repeats. Problem links and ping-pong
After hours (1.9.0)	incidents opened outside the core hours, per group, for staffing
Workload (1.9.0)	per person: open now and resolved in the period. Each person's time to resolve only with `servicenow_insights_person_metrics: true`
Keeping up	opened and resolved per week, the backlog at the end of each week, the age of what is open now (0-5, 6-15, 16-30, over 30 days), a heatmap of when incidents are opened (weekday by hour), the weeks as a table
Severity	incidents per priority - its name (1 - Critical ... 5 - Exempt), count, median to resolve, Response met and Resolution met (1.7.0), No SLA -, the **priority set by hand** (impact x urgency, the 3 x 3 matrix) per group, then every P1 and P2: when, what, the group, the change that caused it, its problem record
VIP tickets (1.43.0)	a row per VIP tier and Not VIP, the incidents by priority, each tier's SLA definitions, and by unit on the All, site and directorate pages. See *VIP tickets* below

Section	What it shows
Categories (1.7.0)	incidents per category (against the window before), their median time to resolve and SLAs met, the group they are mostly in; a data-quality line - no category, Other, off your official list (named)
Satisfaction (1.7.0)	the incident surveys, each on its own scale, by survey: the average graded Good, Fair or Low, by month and by group (1.16.0, see *Satisfaction*)
Top incident issues	the issues ranked, with their rank against the window before (▲▼ New), their share and the cumulative share, a weekly trend, the median time to fix; open one for its **fix action** (with a Copy button), where the fix comes from - **From the tickets**, **Partly from tickets** or **Suggested by ACT** (not verified) -, the CIs it was seen on, example tickets (links into ServiceNow), its close-note quality, and the flags *KB candidate*, *Self-service candidate*, *Problem candidate*; a fix the close notes disagree on is said
Problem candidates	3 or more incidents of one issue on one CI within 30 days: the counts, the group, the problem record - or *No problem record*, or *Resolved, incidents continue*
Passed between groups	incidents reassigned 3 or more times, the paths they took (a group the ticket came back to in amber), the most common issue on each path and the time it added. The groups are shown by their short names - the name without the parts every group shares, such as a site prefix or a contract suffix; rest on one for the full name
Most requested services	the catalog items ranked (▲▼ against the window before), the median time to fulfil, SLA met, the trend; and **requests opened as incidents** (an install, an account, access - things the catalog offers), when ACT ran
Changes	success rate, failed or backed out, followed by an incident, emergency share; each failed or backed-out change with the incidents that followed it - **Caused by** (linked in ServiceNow) or **Same CI** (on its CI within 72 hours, not linked) - and the emergency changes by group; then **Change tasks** (1.2.0, below)
All-stars	each team: the awards (Most resolved - *Most closed* when the change tasks are read -, Best close notes, Fastest to resolve, Fixed for good), the leaderboard - the team's members (ServiceNow's group membership), each with closed (incidents resolved, catalog tasks and change tasks closed), change tasks (how many of them were change tasks, 1.2.0), median to resolve (without the change tasks), close notes, reopened or came back; a member with nothing closed is listed too -, the team's total, and **who sends this team its tickets**: Opened by on the tickets assigned to it, with the group each opener works tickets in (or *end user*), the first 8 and of how many (1.18.0: *312 of 540 tickets, from 8 of 61 people*)
Close notes (after the All-stars)	one line: how many close notes say what was done, are vague, or are a stock phrase or empty; open it for Good / Thin / Bare per group and the most common bare notes word for word
Knowledge article drafts	for the issues with enough incidents and a fix the close notes agree on: symptoms, cause, resolution, with a Copy button - drafts to review, never written to ServiceNow
How this was made	what was read, the window, what was replaced before GenAI, how ACT did

Change tasks (1.2.0)

The changes' tasks (`change_task`, read with GET like the rest) have figures of their own - they are not in the backlog, *Open now*, the weeks or the SLAs, which stay the incidents' and requested items':

- **each team's** (and each directorate's, site's and All - a task counts once at every level, in the group it is assigned to): change tasks opened and closed in the window, the **median time to close** (opened to closed), closed **by the planned end** or **after it** (*planned end date*), and closed with **no planned end** apart; **open now**, how many are **past their planned end**, and how old they are (0-5, 6-15, 16-30, over 30 days);
- **tasks per change**: of the changes closed in the window, how many had tasks, the average, and the change with the most;
- **held up by**: for each change closed in the window with its tasks closed, the team whose task was closed last and the **wait** - from when the change's other tasks were all closed (a change with one task: from the change's *actual start*, else its *planned start*) to that last task's close. The 5 teams that held up the most changes, how often, and their median wait;
- the **Teams side by side** table has one column *Change tasks closed / open*, on the page and in the email (1.30.0, so it fits 1280 px); the **All-stars** count them in *Closed*, with a *Change tasks* column (their time is the change's plan, so *Median to resolve* leaves them out);
- the workbook has a **Change tasks** sheet: every change task opened, closed or open in the window, its change, group, planned start and end, when it was closed, and whether by the planned end; the *People*, *Teams* and *Sites and directorates* sheets have the counts.

The split (`servicenow_insights_split_label`) splits the change tasks by their own group, like every other ticket. The account needs read on `change_task` (`itil`); refused (403), the report says so under *Not read* and leaves the change tasks out, the rest whole. Take `change_task` out of `servicenow_insights_tables` to leave them out on purpose.

Each team's page has every section for that team alone (its incidents, requests, changes, problem candidates, the paths that went through it, its All-stars, its drafts). A team is a group named in `servicenow_insights_groups`, else each group with at least `servicenow_insights_team_min` (10) tickets in the window (the busiest first, at most `servicenow_insights_teams_max`, 60). A group you expect and do not see: it had fewer tickets than that in the window, or was past the busiest 60 - lower the one or raise the other, or name your groups (the report is then about them only). Each team's page is one file, written over each run (`<template>/<team>/latest.html`): the menu at the top and the *Teams side by side* table open it. The website's index has one line for the report, the site's page - not one per team (since 0.88.0; the team lines an older run put there are taken off it).

Someone in several groups is counted in each group for the tickets they resolved there - each team's numbers are that team's tickets, as they were assigned and resolved.

The leaderboard is fair on purpose. People are compared only within their team, and the team is its members in ServiceNow (`sys_user_grmember`, read with the tickets; `servicenow_insights_members`). A ticket counts for the member who resolved it, not for everyone it passed through; one resolved by someone outside the team (the service desk closing it on the user's word) counts for the member it was assigned to, and when it was assigned to nobody of the team it is in the team total, not ranked, and the page says who resolved those. A member with nothing resolved in the period is on the list with 0. A ticket with a bare close note counts half (`servicenow_insights_bare_weight`), so closing with "fixed" does not win. Awards need at least `servicenow_insights_star_min` tickets resolved. There is no "worst" list. When the account cannot read `sys_user_grmember`, each leaderboard lists everyone the team's tickets were assigned to or resolved

by, and the report says so under *Not read*.

Ticket links (1.18.0). Each ticket number opens the ticket in ServiceNow, in a new tab. The link goes through `nav_to.do`, so the ticket shows inside ServiceNow's own frame.

```yaml
servicenow_insights_ticket_links: true          # false = the numbers alone
servicenow_insights_ticket_base: ""             # the address people open ServiceNow at; "" = the
                                                # API credential's
servicenow_insights_ticket_prefixes: {}         # PREFIX: table, for a prefix no record read
                                                # carries (1.30.0)
```

Set `servicenow_insights_ticket_base` when people reach ServiceNow at another address than the API's. An address that is not a web address is ignored: the numbers then show without links.

Since 1.30.0 a number's table comes from the records read, so your instance's own prefixes link too. A number seen only in another ticket's field (a change or a problem) uses the same prefixes. For a prefix no record read carries, name it in `servicenow_insights_ticket_prefixes`:

```yaml
servicenow_insights_ticket_prefixes:
  XINC: incident
```

Sorting (1.18.0). A table sorts as the report website does (WEB_REPORTS.md). A number sorts as a number, an IP address by its four parts, *host2* before *host10*. An empty cell or a lone dash goes last both ways. The first click sorts ascending. On a column already in that order it sorts descending, so the click always shows.

Without the page's script. The page carries a little script (search, sorting, Copy, the tooltips on the charts, the team menu). A report web server whose Content-Security-Policy blocks inline scripts does not run it; since 0.88.0 the job writes the script beside the website's index as `site-insights.js` too, and every page loads it from there (as the other reports do with `site-report.js`: WEB_REPORTS.md). Where no script runs at all, the page still works: the teams are links in the side bar and in the Team menu, resting on a chart shows its values, and the issues open and close.

Moving between pages (0.96.0, a tree since 0.97.0). The bar at the top has a **View** menu on every page, a phone's too (full width): *All assignment groups* first, then every site, under it its directorates, under each its teams - A to Z at each level (case and spaces ignored, numbers as numbers), Other and Unknown last - the current page checked. Type to narrow it (a match at any level shows its branch: a team's site and directorate, a site's directorates and teams), ↑ ↓ and Enter to go, Esc to close; **t** opens it from anywhere on the page and **/** goes to the search. The side bar has the same tree (wide screens), each site and directorate folding, with a filter box above it. Every page has breadcrumbs (*All › SITEA › J6 › Service Desk*). On a page of more than one group a group's name in a chart or a table (*Emergency changes by group*, the hand-off paths, an issue's *mostly* group, the close notes by group) opens that team's page. The menu and the lists are plain links: without the script they still work, the filters and the keys are what the script adds.

In the website's brief look (`report_web_theme: brief`, 0.92.0 - WEB_REPORTS.md, "The brief look"): the same page in the brief colours and type (translucent sections, soft greys in dark since 0.94.0), its figures as one strip, and *Keeping up* or *Falling behind* as a chip at the top, with what was resolved of what was opened, the backlog and the SLAs met. The page also takes the light or dark choice the reader made on the website's other pages (all looks).

Reopened, or came back. When almost no incident in the window was ever reopened (fewer than `servicenow_insights_reopen_min_percent` %), the site does not reopen tickets - people open a new one. The report then counts **came back**: a new incident from the same person on the same issue within 14 days of this one being resolved, and says so on the tile ("Reopen not used here"), on the leaderboard and under *How this was made*. Where reopening is used, the tile shows both.

Close notes are graded by rules: **bare** = shorter than 20 characters, or only a stock phrase (`servicenow_insights_bare_phrases`: fixed, done, resolved per user, see work notes ...); **thin** = longer, but no action word; **good** = says what was done (restarted, replaced, unlocked, added ...).

What is not a hand-off. *Passed between groups* reads incidents only. A change whose tasks go to different teams, or a requested item whose catalog tasks do, is work split up by design: those are separate records, each assigned to its team from the start, and nothing is counted.

Sites, directorates and teams (0.97.0)

The report has a page for **All**, for **each site**, for **each directorate** of a site and for **each team** (the teams as before: `servicenow_insights_team_min`, `_teams_max`, or the groups named). Every page has every section, worked out from the tickets of its groups: a ticket is one record, counted in the group it is assigned to now (where it ended), so it counts once at each level however often it moved. The All page shows *Sites side by side*, a site's page *Directorates side by side*, a directorate's *Teams side by side*. On the website the pages are `{template}/latest.html`, `{template}/<site>/latest.html`, `{template}/<site>/<directorate>/latest.html` and `{template}/<site>/<directorate>/<team>/latest.html`; the website's index keeps one line, the All page. (The team pages of 0.88.0 to 0.96.0, `{template}/<team>/latest.html`, are no longer written or linked: delete those folders by hand.)

Where each assignment group belongs comes from `servicenow_insights_hierarchy_source`:

parents (the default): ServiceNow's own group tree - the job reads `sys_user_group` (GET only: `sys_id`, `name`, `parent`, `active`, `type` of the groups the tickets name and their parents; a person's field only for the team leads, below). The **site** is the root group at the top (shown by its name's first `-` part: a root *SITEA - J6* shows as SITEA); the **directorate** is the group one below the root (a group right under the root has the root as its directorate - *J6*, or *(site direct)* when the root is just the site's name); the **team** is the group (a team under a team is still a team of that directorate, shown *under* its parent team). The roots are the parentless groups that have groups under them, or those you name:

```yaml
servicenow_insights_site_roots: ["SITEA - J6", "SITEB", "SITE-C"]
```

A group with tickets but no way up to a root (no parent, a loop) goes in **Unknown** (under its site when its name starts with a root's site name). An account that may not read `sys_user_group`: the sites come from the names' first `-` part, every directorate is *(unknown)*, and the page says so.

names: from the group's name, split at `-` (a space each side: *SITE-C* is one site). The site is the first part. The directorate, the first that applies: a **suffix** - the name, or a parent group below the root, ends in `- WORD` (any case) for a word of `servicenow_insights_suffix_directorates`: that directorate; a whole word of the name in `servicenow_insights_directorate_tags`; a **staff code** in the name after the site (one or two letters then digits: J633, A6, G6 - not IPv6 or Win10), else a second part named in `servicenow_insights_directorates`, else the nearest parent's staff code; the parent group below the root; else **Other**. `servicenow_insights_directorate_alias` renames or merges directorates last.

```yaml
servicenow_insights_hierarchy_source: names
servicenow_insights_suffix_directorates: [NOVA]     # "SITEB - Ops - VDI - NOVA" is in NOVA
servicenow_insights_directorates: [CODEX]           # a second part that names a directorate
servicenow_insights_directorate_tags: {COMPONENTX: N6}
servicenow_insights_directorate_alias: {J602: J60}
```

Both: `servicenow_insights_hierarchy_map` places a group by its exact name and wins over either - `{"SITEB - Odd One": {site: SITEA, directorate: J6, team: Odd}}`. With `servicenow_insights_known_groups_only: true` every group not in the map goes in **Unknown** (its site's when its name starts with a known site) - to find the new ones and map them.

Groups with no team page; their tickets still count in All, their site and their directorate: `servicenow_insights_exclude_groups` (exact names or patterns: `["* - Legacy*", "Old Approvals"]` - for groups being retired whose old tickets still name them); groups inactive in ServiceNow (`servicenow_insights_inactive_teams: true` gives them a page again); groups whose type is one of `servicenow_insights_skip_group_types` (approver, permission, survey, system, idea, legacy).

Checking the result. *How this was made* has *Sites, directorates and teams*: how many groups each source placed (map, ServiceNow parent, name rule, Other, Unknown), the groups in **Other** (no rule placed them: map them), the **Unknown** groups with their ticket counts, and each group without a page and why. The workbook's Incidents sheet has Site, Directorate and Placed by columns and a *Sites and directorates* sheet.

The split. With `servicenow_insights_split_label` and `servicenow_insights_split_pattern` set, every page has a switch - *All* | *LABEL* | *non-LABEL* - that shows the same page for the tickets of the groups that match (the group's name, or a parent team's below the root; `*` and `?`, any case) and for the rest:

```yaml
servicenow_insights_split_label: NOVA
servicenow_insights_split_pattern: "*- NOVA"
```

Each is its own file beside the page (`latest-nova.html`, `latest-non-nova.html`), worked out when the job runs: the switch is a link, every link on a LABEL page goes to LABEL pages, and nothing is counted in the browser. A site of 130 teams has some 450 pages with the split; `servicenow_insights_split_teams: false` keeps the switch on All, the sites and the directorates only. A page the same as the one already there is not written again, and the pages an older run wrote that this one did not (a team gone, the split switched off) are deleted (`report_web_delete_old`; the job writes its own pages - not with the copy job).

The org map and Custom view (1.8.0)

Use the org map when your management keeps its own tree of the organization. It need not follow ServiceNow's group parents, and it can be deeper in some places than in others. Set it in your `playbooks/group_vars/all.yml`:

```yaml
servicenow_insights_hierarchy_source: map
servicenow_insights_hierarchy_map:
  "SITEA - Ops - Desk - SPLIT": [SITEA, SPLIT, Operations, EUCS]        # a list: the levels, the
                                                                        # site first
  "SITEA - Ops - Windows - SPLIT": "SITEA > SPLIT > Operations > Systems"  # or a string with " >
                                                                           # "
  "SITEB - Ops - VDI": [SITEB]                                          # a team straight under a
                                                                        # site
  "SITEB - Network": ["SITEB", "Networks & Comms / East"]               # names may hold "/" and
                                                                        # "&"
```

Each key is an assignment group's exact name (any case), and the group is the team under its levels. The map names your organization, so keep it in your own `all.yml`, never in the repository.

How groups are placed

- **Only the map places a group.** ServiceNow's parents and the name rules are not used. The `parents` and `names` sources work as before.
- **Unknown**: groups with tickets that the map does not name (`servicenow_insights_unmapped_bucket`).
- **Unassigned**: tickets with no assignment group. Unknown and Unassigned are always listed last.
- *How this was made* lists the groups not in the map, each with its tickets, so you can add them. It also lists any map entry with no level.

The pages

- Every level has a page and a rollup: All, each unit of the tree at every depth, and each group of the map with tickets. A ticket counts once at every level.
- A group that is excluded, inactive or of a skipped type gets no page.
- The folders nest like the tree: `{template}/sitea/split/operations/eucs/latest.html`, the team one folder deeper.
- Breadcrumbs lead up every level. *Side by side* shows a unit's children (*Units*, *Teams*, or both).
- The **View** menu and the side bar show the whole tree, A to Z, with Unknown and Unassigned last. Each unit folds, and the filter opens a match's branch.

The Custom view

The All page's Custom view (`servicenow_insights_custom_view: true`) works out the figures for any mix of units and groups. Tick them, then **Apply**.

- Ticking a unit ticks every group under it. A unit with some groups ticked shows half-ticked.
- Every level says how many of its groups are ticked (*3 / 12*), and every group how many tickets it opened.
- The figures: tickets opened, incidents resolved, open now (and at the start), the median time to resolve an incident and the SLAs met. Where the tickets carry them (1.7.0): Response met, Resolution met, open over the hop limit, on hold now, unable to resolve and first-contact resolution.
- A table lists the groups ticked. Every figure follows the same rules as the rest of the page.
- The address keeps the choice (`#cv=0-3,7`), so you can copy it to share the view. Each unit's page links to the Custom view with its own groups ticked.

Quick choices are buttons above the tree. One click ticks exactly those groups and applies.

- One button for each half of the split (*SPLIT*, *non-SPLIT*), when the split is set.

- One for each of `servicenow_insights_custom_view_presets`:
- `{name: {levels: [...]}}`: the groups whose map path has every level listed, in any position.
- `{name: {pattern: "..."}}`: the groups whose name matches.
- The address keeps a quick choice too: `#cv=preset:SPLIT`.

Periods (1.10.0) are buttons under the result. Each works the figures out for that period and compares them with the period before it. They follow the calendar, not a count of days back from today.

Period	What it is	Compared with
The window (`all`)	the report's whole window	the window before
This month (`this_month`)	the report end's month so far	the same days of the month before
Months `1m` to `12m`	the last N whole calendar months	the N months before them
Weeks `1w` to `8w`	the last N whole weeks, Monday to Sunday	the N weeks before them
From / to	any days you pick	the same number of days just before

The default is `[all, this_month, 1m, 2m, 3m, 6m, 9m, 12m, 1w, 2w, 4w]` (1.16.0).

- The buttons sit in two short rows, *Months* and *Weeks*, each showing its number (1, 2, 3 ...). The window and This month come first, the from / to after. On a phone the buttons become one list to pick from.
- Each button's tooltip, and the heading of the result, give the real dates: "October 2026, compared with September 2026".
- When the report ends on a month's last day, This month is Last month, so only Last month shows.
- A month or week period needs its own length and the length before it in the page's tickets. One that does not fit is left out, never shown with partial figures. One muted line under the buttons says what and why:
- *9 and 12 months need a longer window: servicenow_insights_months.*
- *... need the period before as well: ...* when the window before is not carried (the row cap below, or `servicenow_insights_compare: false`).
- A name that is not a period stops the job: `servicenow_insights_periods: 13m is not a period - all, this_month, 1m to 12m (calendar months) or 1w to 8w (weeks)`.
- The address keeps the period too: `#cv=0-3,7&p=1m`, or `&p=2026-10-05_2026-10-18` for a from / to.

What each figure means for a period:

- **Opened, resolved, the SLAs, the median time to resolve**: the tickets opened, or done, in the period.
- **Open at the period's end**: the backlog on its last day, with the start's number beside it. For a period that ends now, the tile says *Open now*.
- **On hold now** and **Open over N hops**: ServiceNow only says how a ticket is now. For a period that ends earlier, these tiles say *known now only*.
- **Time in each state** (1.9.0): the average hours new, in progress and on hold, of the incidents resolved in the period. It needs the state metric (see "The life cycle and the flow").
- **Open over 10 business days** (1.9.0): the backlog's age at the period's end, in your business days, with the 0–1, 2–5 and 6–10 day counts.

- **The chart**: opened and incidents resolved per day (up to a month), per week (up to 4 months), else per month.

`servicenow_insights_periods` picks the buttons, in order. `servicenow_insights_week_start` sets the day a week starts on (`mon` by default).

The Custom view needs no server. The All page carries the tickets as compact rows, about 55 bytes a ticket, in a data block the browser never runs. So a strict Content-Security-Policy, a share or an offline copy all work.

The rows include the window before, so every period can be compared. At most `servicenow_insights_custom_view_max_rows` tickets (30,000) are carried:

- Over that with the window before, only the window's own tickets are carried. The window then has no compare, and the month and week periods that need the window before are left out, said under the buttons.
- Over that with the window alone, the page says so and has no Custom view.

The split with the map

`servicenow_insights_split_label` works with the map too. `servicenow_insights_split_by` says how a group is picked:

- `pattern`: its name matches `servicenow_insights_split_pattern`.
- `level`: the label is one of its levels in the map.
- `both` (the default): either. So `split_label: SPLIT` alone picks every group under any *SPLIT*.

All and every unit get the *All* | *SPLIT* | *non-SPLIT* switch and a page for each half (`latest-split.html`, `latest-non-split.html`). The teams follow `servicenow_insights_split_teams`. The split's pages have no Custom view: they link to the All page.

Setting	Default	What it does
`servicenow_insights_hierarchy_source`	`parents`	`map`: the groups placed only by the map
`servicenow_insights_hierarchy_map`	`{}`	`{"<group>": [Site, Level1, ...]}` or `"Site > Level1 > ..."`
`servicenow_insights_unmapped_bucket`	`Unknown`	where the groups with tickets that are not in the map go
`servicenow_insights_custom_view`	`true`	the All page's Custom view
`servicenow_insights_custom_view_max_rows`	`30000`	its tickets carried in the page at most
`servicenow_insights_custom_view_presets`	`{}`	more quick choices: `{name: {levels: [...]}}` or `{name: {pattern: "..."}}`
`servicenow_insights_split_by`	`both`	with the map, the split by `pattern`, by `level` (the label one of the group's levels), or `both`

Setting	Default	What it does
`servicenow_insights_periods`	`[all, this_month, 1m, 2m, 3m, 6m, 9m, 12m, 1w, 2w, 4w]`	the periods of the Custom view and of every page (1.10.0): `all`, `this_month`, `1m` to `12m`, `1w` to `8w` (1.16.0)
`servicenow_insights_week_start`	`mon`	the day a week starts on, for the weeks

Periods on every page (1.39.0)

The All page and every site's, unit's and team's page have a period bar at the top. It has the Custom view's buttons, from / to and phone select. No groups to tick: each page takes its own tickets. A split's page takes its half's.

The page opens on *The window*, exactly as written. A period chosen changes:

- **At a glance**: tickets, open now (or at the period's end), the median time to resolve, response and resolution met, first-contact resolution and unable to resolve. Each is compared with the period before, as in the Custom view.
- **Keeping up**: its first chart, as opened and incidents resolved per day, week or month.

Everything else stays on the window and says *whole window* in its heading while a period is chosen. These tiles do too: reopened, changes successful, reassigned 3+ times and the close notes. The rows do not carry what they need. *What the period says* under At a glance is marked too (1.43.0). Its sentences are the window's.

Section	With a period
At a glance	follows, except the four tiles above and *What the period says*
Keeping up	the first chart follows, the rest is the window
Every other section	the window: *whole window*

The address keeps the period: `#p=3m`, or `#p=2026-10-05_2026-10-18` for a from / to. *Copy link* copies it, and Back goes to the period before.

The bar works with or without the map. Each page carries its own tickets as rows, about 52 bytes a ticket. On the made-up site of the tests (1,952 tickets with the window before):

Page	Before	With the bar
All, no map	340 KB	458 KB
A team of 1,018 tickets	250 KB	319 KB
All, with the map	466 KB	475 KB

With the map, the All page's bar uses the Custom view's rows, so they are carried once. A page's rows follow `servicenow_insights_custom_view_max_rows`, each page on its own. Over it with the window before, the page carries the window's rows and says which periods are left out. Over it with the window alone, the page says so and has no bar.

```yaml
servicenow_insights_page_periods: true          # false = no bar, the pages as before
```

The email and the workbook do not change.

VIP tickets (1.43.0)

Every page has a **VIP tickets** section: the All page, each site's, unit's and team's page, and the split's pages. Each counts its own tickets. A ticket's tier comes from the person it was raised for: an incident's caller, a request's requested for.

Table	What it shows
VIP tickets	a row per tier and Not VIP: incidents, requests, open now, median to respond and resolve, response and resolution met, no SLA
Incidents by priority	each priority's incidents, per tier
SLA definitions: a tier	each SLA on the tier's tickets done in the window: tickets, met, missed, met %, median elapsed
VIP tickets by unit	All, site and directorate pages: a row per unit below, sortable

A row with fewer than `servicenow_insights_vip_min` tickets shows counts only, and a dash for the rest. Median to respond is the response SLAs' elapsed time, from task_sla.

The **Custom view** has a *VIP only* choice: every ticket, every VIP tier, or one tier. The tiles, the chart and the groups' table follow it, and the address keeps it (`&v=1`). The **email** has the scope's VIP table. On the All, site and directorate emails, the by-unit table follows while it fits 800 px. Otherwise each unit gets one line. The **workbook** has a VIP sheet with counts only. No sheet shows a ticket's tier.

The tiers

Each tier is a true / false column on sys_user. The default is ServiceNow's own VIP flag:

```yaml
servicenow_insights_vip_fields: [{label: VIP, column: vip}]
```

A second tier is one more line. The first tier listed that is true for a person wins:

```yaml
servicenow_insights_vip_fields:
  - {label: "Tier 1", column: u_tier1_vip}
  - {label: VIP, column: vip}
```

To find a column's name, open a user in ServiceNow, right-click the field's label and choose **Show**. The name is after `sys_user.`. Column names are checked: a-z, 0-9 and _ only.

What is read

The job reads sys_user in batches of 100 (`sys_id IN`), and only `sys_id` and the tiers' columns. It never reads a name. The page, email and workbook keep counts only.

- A column the account cannot read is said in the section, and that tier counts no one. The other tiers still count.

- When sys_user is refused, the section says so and every ticket counts as Not VIP. The job goes on.
- `[]` turns the section off.

```yaml
servicenow_insights_vip_people: caller     # caller_and_opened_by: who opened it counts too
servicenow_insights_vip_min: 5             # under this many tickets: counts only
```

The account needs read on sys_user and its tier columns. The itil role reads sys_user. A custom column may need its own read ACL.

ACT (GenAI), and what never reaches it

ACT is off by default (1.13.0). It runs only when asked: `servicenow_insights_act: true` in the template's Variables for a monthly run, or on a launch. The work notes stay on, so ACT reads them when it runs. With ACT off, the page says so once, in *Top incident issues*.

With an **ACT model key** credential on the template and `servicenow_insights_act: true`, ACT is asked in batches - nothing large goes in one question:

1. **The issues.** The incidents' short descriptions, one per distinct description with its count (the most frequent first, at most `servicenow_insights_act_max_descriptions`), `servicenow_insights_act_batch` per question. Each question carries the issues defined so far, so the same issue keeps its name from batch to batch (at most `servicenow_insights_act_max_issues`). With the report database on, a description asked before is placed from the ACT cache and not asked again (1.17.0).
2. **The fixes.** The top `servicenow_insights_act_fix_issues` issues, `servicenow_insights_act_fix_batch` per question, each with its close notes that say something (`servicenow_insights_act_notes`) and, since 0.96.0, its **work notes** - what was tried while the tickets were open (below): the steps (those that resolved tickets first, not what was tried and did not help), how many notes show each step, where they come from, whether the notes disagree, how many tickets the steps worked on, a **repeated workaround** where the notes show one (a restart again and again: the issue becomes a *KB candidate*), and a knowledge article draft where the notes agree and the issue has `servicenow_insights_kb_min` incidents or more, or a repeated workaround on 5 tickets or more - the draft says how many tickets its steps worked on. Under each top issue's fix the page says what it was read from: *From 40 close notes and 18 work notes of 9 tickets*.
3. **The summaries.** One question with each scope's numbers (the site and each team).

Before anything goes to the model, the job replaces with placeholders (PERSON-1, PHONE-2, EMAIL-3, HOST-4, IP-5, ID-6): the names of every person the records name (assigned to, opened by, caller, resolved by - the full name, "Last, First" and the last name), configuration items that look like host names, and in the text: email addresses, IP addresses, phone numbers, 10-digit numbers (EDIPIs), and host names. The answers come back with the placeholders, and the job puts the real values back before the page is written. ACT also masks host names, addresses and accounts itself. The count of each kind is under *How this was made*. Add your own words to replace with `servicenow_insights_mask_names` (a project, a building); a word that looks like a host name but is not (a product, `rhel9`) goes in `servicenow_insights_mask_keep`.

The work notes (0.96.0). Only for the top issues ACT writes a fix for, only their incidents resolved in the window or the one before (200 per issue at most), read-only: GET `sys_journal_field` with `element=work_notes`, `name=incident`, `element_id` one of those incidents, newest first - the note's text and time, never who wrote it, and nothing is written anywhere. Per issue the newest `servicenow_insights_act_work_notes_max` (20), one of each text, each cut to

servicenow_insights_act_work_note_chars (1500) characters. They are masked like everything else before ACT reads them (the people the records name, servicenow_insights_mask_names, and the email and IP addresses, phone numbers, IDs and host names in them - those only the work notes hold too) and the real values are put back in the answer. servicenow_insights_act_work_notes: false leaves them out. An account that may not read sys_journal_field (403): the page says so above the top issues and under *Not read*, the fixes come from the close notes, and the job is green.

Without ACT (off, no key, or a dry run) the report is still whole: the issues are the incidents' category / subcategory, each issue's fix is its most common close notes that say what was done, the summary is made from the numbers, and there are no knowledge drafts. The report says why ACT did not run.

How long it takes. The reads take a minute or two for a few thousand records per table. ACT adds one question per batch: 2,000 descriptions in batches of 100 are 20 questions, plus 5 for the fixes and one for the summaries - each the model's time (servicenow_insights_act_model_timeout). Schedule it monthly, overnight.

Where this run's time went (1.14.0). The job's last lines say it by phase, for example:

```
Time: ServiceNow reads 78 s, ACT 1 s, The report worked out 8 s, The report database (read and
  written) 0 s,
Pages and email 3 s - 89 s in all
Report database db.yoursite.mil:3309/site_reports: written - run 41, 2 months (2026-10, 2026-11
  (so far)), 4,210 figures;
the database now holds 38 runs, first month 2025-11, last month 2026-11
```

The last line says whether this run's figures reached the report database (1.15.0): see REPORT_DATABASE.md, *Is it writing?*.

How this was made on the page has the same split, up to the pages (they are written after it is made).

The pages in one go (1.14.0). Each site's, unit's and team's page is written servicenow_insights_pages_per_call (40) at a time, in one task after the All page. Before, the email role ran once per page, about a second each. The pages are the same, file for file (a test checks it). Copy mode (report_web_copy) and report_web_host still write them one by one; so does servicenow_insights_pages_per_call: 0.

The hand-off paths (0.97.0)

Passed between groups counts the incidents reassigned servicenow_insights_handoff_min times or more from the incidents themselves; the **paths** (Service Desk › Windows › Service Desk ...) need each incident's history of assignment groups, which the incident does not hold. The job reads it, GET only, for those incidents alone:

- sys_audit - every change of the field assignment_group (the default first);
- metric_instance - the out-of-box incident metric *Assignment Group* (definition.name=Assignment Group, table=incident, the incidents' sys_ids; id, value, start, end in order of start): one row per group the incident was with.

servicenow_insights_handoff_source: auto (sys_audit, else the metric), audit, metric (sys_audit is never asked - for an account that may not read it), none. *Not read* says where the paths came from when sys_audit was refused, or which table the account needs when neither was read.

```yaml
servicenow_insights_handoff_source: metric
```

Step 1. The account

The **ServiceNow API** credential you already have works (SERVICENOW_SETUP.md). Its account needs **read** on:

Table	What	The role that reads it
`incident`, `sc_req_item`, `sc_task`, `change_request`, `change_task` (1.2.0), `problem`	the tickets	`itil`; `change_task` refused (403): said under *Not read*, the change tasks left out
`sys_user_group`	the groups named in `servicenow_insights_groups`; since 0.97.0 the tickets' groups and their parents (sites and directorates); since 1.15.0 each group's `manager` with its name and active flag (the team leads), and its email only when `servicenow_insights_email_leads` names a team (1.18.0)	`itil`; refused, the sites come from the names (or `servicenow_insights_use_group_parents: false`); the manager refused, said under *Not read*, no Group manager line
`sys_audit`	the assignment history of incidents passed between groups (the paths)	`itil` on most instances; refused, the paths come from `metric_instance` (below)
`metric_instance`	the same history from the out-of-box incident metric *Assignment Group* (0.97.0), when `sys_audit` is refused or `servicenow_insights_handoff_source: metric`	read on `metric_instance` (`itil` on most instances); both refused, the report shows the counts without the paths and says which table it could not read
`sys_user_grmember`	the members of the groups the tickets name (the teams' leaderboards)	`itil` on most instances; else the report says so and each leaderboard lists everyone the team's tickets were assigned to or resolved by (or `servicenow_insights_members: false`)
`task_sla` (1.7.0)	the SLAs of the incidents and requested items done in the window (and the one before), and of the incidents open now: met or missed, at risk now, on hold since (the SLA's pause)	`itil`; refused (403), the report says so under *Not read* and counts met or missed from your targets
`metric_instance` (1.7.0)	the metric *Incident State Duration* (`servicenow_insights_state_metric`: the time on hold, reopened within 7 days) and the metric *Assigned to* (the response, with your targets)	as above; not there, the page says what it could not measure

Table	What	The role that reads it
`asmt_metric_result` (1.7.0)	the incident surveys' answers, with each question's survey, state and scale dot-walked (1.16.0; best-effort; `servicenow_insights_survey: false` = not read)	read on the assessment tables (`asmt_metric_result`, through `asmt_assessment_instance`); refused, said under *Not read*, no satisfaction figures
`sys_user` (1.43.0)	the VIP tiers: `sys_id` and the tiers' columns (`servicenow_insights_vip_fields`) of the people the tickets were raised for, never a name	`itil`; a custom column may need its own read ACL; refused, the VIP section says so and every ticket counts as Not VIP
`sys_journal_field`	the work notes of the top issues' incidents, for ACT's fixes (0.96.0; only with ACT)	read on `sys_journal_field` - `itil` reads the work notes of the incidents it can read on most instances; where an ACL on `sys_journal_field` refuses it (403), ask the ServiceNow admin for a read ACL on `sys_journal_field` for the account's role (the work notes of incidents only is enough), or set `servicenow_insights_act_work_notes: false`; refused, the report says so and the fixes come from the close notes

A table the account cannot read is listed under *Not read* and the rest is reported; take a table out of `servicenow_insights_tables` to leave its sections out.

Step 2. The job template

1. **Templates › Create job template**: name `ServiceNow - ticket insights`, **Inventory** any (the job runs on localhost), **Project** site-automation, **Playbook** `playbooks/servicenow_insights.yml`, **Credentials** `ServiceNow API`, *ACT model key* for the runs that ask ACT, *Report database* for the trends, and *SMTP relay* if your mail relay needs a login. **Execution environment** the all-in-one EE (the report database needs PyMySQL). No Limit. Tick **Prompt on launch** for Variables.
2. **Variables** (paste `aap/extra_vars/servicenow_insights.yml` and switch on what you change):

```yaml
servicenow_insights_months: 6                  # the window: 1, 2, 3, 6, 12 ... months (or
                                               # servicenow_insights_days: 60)
# servicenow_insights_groups: [Ops - Service Desk, Ops - Windows]   # empty = every group
# report_email_to: [it-leadership@yoursite.mil] # the email is optional: the page is the report
```

`report_web_dest` (the report website), `report_time_zone`, the look of the email and the logo come from `all.yml` as for every report.

3. **Run it** once by hand. The job prints the report and the page's address; the site's page is `<template>/latest.html`, each team's `<template>/<team>/latest.html` (e.g. `servicenow-ticket-insights/ops-windows/latest.html`).
4. **Schedule** it monthly - the first of the month, early morning, with `servicenow_insights_until` empty (up to now) - or quarterly with `servicenow_insights_months: 3`. For ACT on the monthly run, add `servicenow_insights_act: true` to that schedule's Variables.

To email a team lead their team's page as well, see Team leads below.

Team leads (1.15.0)

The team lead is the group's **Manager** in ServiceNow (`sys_user_group.manager`). The job reads it with the groups it already reads: no extra call per group. A team's page shows **Group manager: NAME** under the title. Its email shows it after the window.

- No manager in ServiceNow: no line.
- An inactive manager: the name, then *(inactive in ServiceNow)*.
- Site, directorate and unit pages: no line, in every hierarchy source. Their list of teams has no Manager column: it would not fit at 1280 px (1.18.0).
- The workbook's **Teams** sheet has a **Manager** column (1.18.0), empty for a team without one.
- The manager's email address is read only when `servicenow_insights_email_leads` names a team (1.18.0).
- The account may not read the manager (403), or the person's name comes back empty: said once under *Not read*. The rest of the report is whole.

To email a team's page to its lead, name the teams:

```yaml
servicenow_insights_email_leads: ["Ops - Windows", "ops - net*"]   # names or patterns, any case;
                                                                   # or "all"
servicenow_insights_show_lead: true                                # the Group manager line; false
                                                                   # = off (the emails still go)
```

- `[]` (the default) emails nobody.
- A pattern works as in `servicenow_insights_split_pattern` (`*` any text, `?` one character).
- A manager who is inactive, or has no email address, gets nothing. The job output says so, one line per team.
- `servicenow_insights_team_email_to: {"Ops - Windows": [lead@yoursite.mil]}` still works. For a team named in both, it wins: the email goes to its addresses, not to the manager.

Each lead's email goes **To** the lead alone. `report_email_to` does not get it, even as an extra variable. The email links the team's page on the report website. The report database keeps no name: the lead is never written there.

Your SLAs, priorities and categories

The page and the email count **met or missed** from your SLAs. `servicenow_insights_sla_source` says where from:

Source	Where met or missed comes from
`auto` (the default)	ServiceNow's own SLAs (`task_sla`) when the account reads them, else your targets (below). *Not read* says which.
`task_sla`	ServiceNow's SLAs, as configured there (business hours, on hold paused)
`targets`	your targets below, in your business hours when set
`made_sla`	ServiceNow's *Made SLA* flag (the way before 1.7.0, without targets)

With `task_sla`, each SLA definition is a Response or a Resolution by its name:

- **Response**: the name has one of `servicenow_insights_sla_response_match` (`[response]`, any case).
- **Resolution**: the name has one of `servicenow_insights_sla_resolution_match` (`[resolution, resolve]`).
- **Other**: any other definition. It is shown by name under *How this was made* and not counted.
- **No SLA**: a ticket with no SLA attached (your P5s, say). It is counted, but left out of the percentages.

Met or missed counts the incidents and requested items **done in the window**. The tiles show **Response met** and **Resolution met** (with `task_sla`, or a response target), else one *SLAs met*. Severity has them per priority, the side by side per team, and Categories per category.

Your targets

Your targets are the fallback, or the source with `servicenow_insights_sla_source: targets`. They are hours from opened to resolved (incidents) or closed (requested items), by table and priority.

- A number is the resolution target.
- A mapping adds a response target: opened to first assigned to a person (the metric *Assigned to*).
- `none` is no SLA for that priority, and `"*"` is every priority not listed.

YAML

```
servicenow_insights_sla_targets:
  incident:
    "1": {response: 0.25, resolution: 4}
    "2": {response: 0.5, resolution: 9}
    "3": {response: 4, resolution: 27}
    "4": {response: 9, resolution: 45}
    "5": none                                  # no SLA for P5
  sc_req_item: {"*": 45}
servicenow_insights_sla_items: {"New account / onboarding": 18}     # a catalog item's own target,
                                                                    # beating its priority's
servicenow_insights_business_hours: {days: [mon, tue, wed, thu, fri], start: "07:30", end:
  "16:30", holidays: ["2026-12-25"]}
```

- The business hours are in `report_time_zone`. An end before the start is a shift past midnight, and `{}` is calendar hours.
- Put both tables in `all.yml`: the setting is replaced whole, and a table left out uses ServiceNow's *Made SLA*.

Priorities

- `servicenow_insights_priority_names` names them on the report: `{"1": Critical, "2": High, "3": Moderate, "4": Low, "5": Exempt}`.
- `servicenow_insights_priority_matrix` is the standard 3 x 3 (impact, then urgency, gives the priority).
- An incident whose priority is not the one its impact and urgency give was **set by hand**. Severity counts these per group, set higher or lower.
- `servicenow_insights_priority_matrix: []` turns the check off.

Categories

`servicenow_insights_categories` is your official list, e.g. `[Email, Network Connectivity, Workstations, Other]`.

- With a list, Categories counts and names the categories not on it. It also counts those with no category and those in Other.
- Without a list, every category is shown as it is.
- Without ACT, the issues stay the incidents' category / subcategory.

Satisfaction (1.16.0)

The page never averages questions on different scales together. Each survey has its own block, each question its own scale.

- **The scale** comes from ServiceNow: the question's min and max, or its template's values. When those can not be read, the answers' lowest and highest are used and the page says *as observed*.
- **A rating** is a question ServiceNow calls a scale (scale, numericscale, template) up to 10. When that can not be read, every answer must be a whole number from 0 to 10, with 3 or more different answers.
- **Not a rating**: a yes / no, a 0 to 100 score, a count. Read, but not shown as a rating. *How this was made* lists it, under *The surveys read*. To show one anyway, name it in `servicenow_insights_survey_metrics`.
- **A retired survey** keeps its own block, marked *retired*. Months before a switch of surveys show the old survey's figures on its own scale.
- **The headline** (the tile, the email, the report database): the active survey with the most answers. Its overall average when all its rating questions share one scale, else its most-answered question.

Every average reads *3.46 of 4* with a grade: **Good**, **Fair** or **Low**, by its share of the scale: (average - lowest) / (highest - lowest).

Scale	Good from	Fair from
1 to 4	3.4	2.8
1 to 5	4.2	3.4
0 to 10	8	6

Under 5 answers, the average shows with no grade, so one answer does not paint a team.

Setting	Default	What it does
`servicenow_insights_survey_metrics`	`[]`	the questions read, by name; a named question is always a rating
`servicenow_insights_survey_types`	`[]`	the surveys read, by name: questions named Q1 in two surveys stay apart
`servicenow_insights_survey_headline`	`""`	a survey or a question for the headline
`servicenow_insights_survey_grades`	`{good: 0.8, fair: 0.6}`	the shares of the scale for Good and Fair
`servicenow_insights_survey_min_answers`	`5`	fewer answers: no grade

What to act on first

The *Act on first* section (in the email: **Act on**) lists what the process says to look at.

What	Setting	What is listed
SLA at risk now	`servicenow_insights_sla_risk_pct: 75`	open incidents past 75% of their running SLA, or breached and open. Worst first, with the time left.
Over 3 hops	`servicenow_insights_hop_limit: 3`	open incidents transferred more than 3 times after the first assignment. Oldest first.
Awaiting Caller over 6 business days	`servicenow_insights_awaiting_caller_days: 6`	incidents on hold with the reason Awaiting Caller for longer
No Resolution Provided	`servicenow_insights_review_code`	each incident of the period resolved with that code, for review
Resolved, not closed after 7 days	`servicenow_insights_close_after_days: 7`	resolved and never closed: the auto-close is not working

How each is read:

- **SLA at risk**: the running SLAs (`task_sla`), in business time where ServiceNow keeps it.
- **Hops**: `reassignment_count` over 4 (the first assignment is not a hop). Per group, the page shows the share over the limit, and the hops each group took when the assignment paths are read.
- **On hold**: the state's name has *hold*, and the reason is `hold_reason` as shown. On hold with no reason is counted.
- *On hold since* comes from the metric *Incident State Duration* (`servicenow_insights_state_metric`), else from when the SLA was paused (`task_sla`).
- Business days are the business hours' days, else Mon-Fri.
- **Resolution codes**: `close_code` as shown, counted per group for each of `servicenow_insights_scrutiny_codes`. The listed incidents show the close note's start, with names, phone numbers, addresses and hosts replaced.

How incidents ended groups the close codes by `servicenow_insights_outcome_map` (any other code is Fixed):

- **Unable to resolve**: `servicenow_insights_unable_outcomes` (Known Error + No Resolution Provided), of those resolved.
- **First-contact resolution**: resolved without being reassigned. For the service desk's own, name its groups in `servicenow_insights_service_desk_groups`.
- **Reopened within 7 days** needs the state metric.

The life cycle and the flow (1.9.0)

These sections read the metric *Incident State Duration* and the tickets already read. Without the metric, *Time in each state* says it is not measured.

Section	What it counts	Setting
Time in each state	the incidents resolved in the period: average hours waiting to start (New), in progress (In Progress, Assigned, Work in Progress) and on hold (On Hold, Awaiting, Pending); resolved to closed in the table	`servicenow_insights_state_metric`
On hold	the share of the time to resolve; incidents on hold more than twice; hours by reason; Awaiting Vendor's share	`servicenow_insights_hold_many: 2`
Backlog age	what is open now, by business days since opened	`servicenow_insights_business_hours` (its days, else Mon-Fri)
Ticket quality	category Other or none, no CI, a short description	`servicenow_insights_short_desc_chars: 15`
Hot spots	the CIs with the most incidents, and repeats on the same CI	`servicenow_insights_repeat_ci_days: 7`
Ping-pong	incidents sent from A to B and back to A, from the assignment paths	-
After hours	incidents opened outside the core hours	`servicenow_insights_core_hours` (`{}`: the business hours, else Mon-Fri 07:30-16:30)
Workload	open now and resolved, per person (the one each is assigned to)	`servicenow_insights_person_metrics: false`

The on-hold reason is the one the incident had when resolved. Where ServiceNow cleared it, the table says *reason not kept*. Each person's time to resolve is shown only when `servicenow_insights_person_metrics` is true.

Trends and the report database (1.13.0)

With `servicenow_insights_db: true` and the **Report database** credential, each run writes its figures to the report database. Every page then has a **Trends** section after *At a glance*: the figures month by month, for that site, unit or team.

- Each point is a calendar month. The month so far is drawn dashed.
- The section says "N months so far" until there are 12.
- The database not reached: one warning, the report whole, the job green.

Fill the past year once with `servicenow_insights_backfill_months: 12`, as a separate launch. Setup, the backfill, the tables and what is never stored: REPORT_DATABASE.md.

Only what changed is read (1.17.0)

With the report database on, it also keeps each ticket's fields (never its text, people or CI). The names ServiceNow shows, such as a group's, are read every run, so a renamed group shows its new name. Each run then reads in full only the tickets that changed, and makes the follow-up reads only for those and the open ones. The pages, the email and the workbook are the same as a full read's. The first run reads everything and fills the store.

- The job's last lines say how: *Tickets: 2,253 - 4 read from ServiceNow (new or changed), 2,249 from the report database*.
- `servicenow_insights_full_refresh: true` on a launch reads everything again.
- With ACT on, each description's issue is kept too: only new descriptions go to ACT. The fixes are asked every run.

What is kept, and how to remove it: REPORT_DATABASE.md, *The ticket store and the ACT cache*.

The window

Setting	Default	What
`servicenow_insights_months`	6	the last N calendar months, up to now (a run on 1 November with until 31 October: 1 May - 31 October)
`servicenow_insights_days`	0	> 0: the last N days instead
`servicenow_insights_until`	""	the last day (through its end), e.g. `2026-10-31`; "" = now
`servicenow_insights_compare`	true	the window before (the same months, or days) is read too, for the up and down arrows and the tiles' changes
`servicenow_insights_max_records`	20000	at most this many records per table, the newest kept (see below). 20000 needs about 0.4 GB in the EE; 100000 about 1.5 GB and 4 minutes more

Weekly charts use whole weeks (Monday to Sunday, in `report_time_zone`).

More records than the cap (1.16.0)

A table over `servicenow_insights_max_records` keeps its newest records. Then the job reads the older ones that still count in the window: open now, or closed or resolved in it. So the window is whole first.

- **Only the window before is cut.** The figures are whole. There is no compare this run: no up or down arrows, and every page says *No compare this run* at the top.
- **The window itself is cut** (that second read hit the cap too). Every page and the email start with *Records cut: some figures are incomplete*, for example *incident: only the newest 40,000 of 52,310 read, back to 2026-06-03. Figures in this report are incomplete: raise servicenow_insights_max_records.* The job ends with a WARNING line, and there is no compare.
- The date is where the read stopped. A ticket opened before it is missing from every month it counts in, a later one too (resolved in August, open at the end).
- So a cut window writes nothing to the report database: no run, no month. The rows already there stay as they were. The job's *Report database* line says so.
- The cap counts exactly: a table of exactly `servicenow_insights_max_records` records is not cut.

What to raise: the job's line names the table and how many there were. Set `servicenow_insights_max_records` above that number, in the template's Variables. Measured on the test site (6 tables, 100,000 incidents in 13 months):

servicenow_insights_max_records	Memory in the EE	Time added
20000	about 0.4 GB	-
100000	about 1.5 GB while it reads, 0.7 GB for the report	about 4 minutes

Before 1.16.0 a capped table kept its oldest records, so the newest months looked empty.

Every setting

The thresholds of every section (`servicenow_insights_old_days`, `_handoff_min`, `_problem_min`, `_problem_days`, `_repeat_days`, `_change_follow_hours`, `_change_failed_codes`, `_change_backout_words`, `_bare_chars`, `_bare_phrases`, `_top_issues`, `_top_requests` ...) are in `roles/servicenow_insights/defaults/main.yml`, each with what it does, and in VARIABLES_REFERENCE.md.

The job's output

- the report as text in the job output, and the page's address (`Report: https://...`, the artifact `site_report_url`);
- the job artifact `servicenow_insights`: the window, ACT's questions and answers, what was replaced (counts), and each scope's main numbers (counts, backlog, median fix, SLA, close notes, top issues and requests, the summary) - for a dashboard of your own;
- the workbook on the email: every incident of the window with its issue and close-note grade, then Issues, Requests, Changes failed, Problem candidates, People (every team), Teams, Hand-off paths;
- the page's data as JSON beside it on the report website.

With `report_web_copy` (the copy job writes the pages), the copy job writes the report in the website's standard look, not this page: run this job where it can write `report_web_dest` itself.

12. The report database: ticket insights' trends, month by month

The report database keeps the ticket insights' figures from run to run. Each site's, unit's and team's page then shows how they moved, month by month, in a **Trends** section. ServiceNow stays the record: the database holds numbers only.

It is MySQL 8.4 LTS in its own podman container, `report-db`, on the STIG Manager host, apart from STIG Manager's own database. Ticket insights is its first user (1.13.0). Since 1.17.0 it also keeps each ticket's fields, so a run reads only what changed (*The ticket store and the ACT cache*).

What it keeps

The figures, per run and per org node (All, each site, each unit at any depth, each team, and the split's two halves). Since 1.17.0 also each ticket's fields and ACT's grouping (*The ticket store and the ACT cache*).

Kept	Never kept
Counts: incidents, requested items, changes, problems, resolved, open, open over 30 days	A caller, an assignee, anyone's name
Percentages: SLA met, response met, first contact, reopened, hops, hand-offs, ping-pong, ticket quality, after hours	A short description, a close note, a work note
Hours: median time to resolve, the average time in each state	ACT's fixes, knowledge drafts and summaries
Outcomes, categories and backlog age, with their names	The workload table (it names people)
The hot CIs, with their names	A ticket's CI
Per ticket (1.17.0): its numbers, times, codes, flags and group	
ACT's short name for each issue, masked (1.17.0): the only text	

Each run writes two kinds of rows:

- **The window**: the figures of the run's own window (for example the last 6 months).
- **Calendar months**: each whole calendar month inside the window, worked out by the same report. The month the window ends in is kept too, marked *so far*.

A month is keyed by the instance, the month and the org node. The newest run that holds a month replaces it, so a weekly run, a monthly run and a 3-month window all fill the same points. Nothing is counted twice. A month *so far* never replaces a complete month.

Set it up

The setup script `tools/report-db-setup.sh` does the host's part (steps 1 to 3). Copy it to the host and run it as root, with the AAP execution nodes' addresses:

```shell
AAP_SOURCES="192.0.2.21 192.0.2.22" bash report-db-setup.sh
```

The image `localhost/mysql:8.4` must be on the host first. It is never pulled from Docker Hub (1.50.0):

- Load and tag it once, as ENCLAVES.md shows.
- Without it the script stops at step 2. Nothing is changed, and it prints the steps.
- `IMAGE=` names another image, such as your enclave's registry. `PULL=1` lets the script pull it from there.

It is safe to run again: each step checks first. What was tested:

- The 1.16.0 tester ran it on a test host, as root and rootless, twice.
- CI runs `bash -n`, ShellCheck, and the script against a podman that runs nothing (`tests/test_report_db_setup.py`).
- 1.50.0's image step ran with rootless podman 5.8: a missing image, a loaded one, and `PULL=1` from a registry.

Every name below is the one it uses:

What	Name
The container	`report-db` (MySQL 8.4), run by the Quadlet / systemd unit `report-db`
Its data	the host folder `/var/lib/report-db`
The root password	`/root/report-db.container.env` (read by the container, `--env-file`)
The accounts' passwords	`/root/report-db.env` (root only)
The port	**3309** on the host (3306 and 3307 may be the other databases there)
The database	`site_reports`
The accounts	`report_writer` and `report_reader`

The commands under each step are what the script does, for doing it by hand.

1. **The container.** On the STIG Manager host, as root. `/root/report-db.container.env` holds one line, `MYSQL_ROOT_PASSWORD=...`, and is readable by root only.

```shell
mkdir -p /var/lib/report-db
podman run -d --name report-db --pull=never -p 3309:3306 \
  -v /var/lib/report-db:/var/lib/mysql:Z \
  --env-file /root/report-db.container.env \
  -e MYSQL_DATABASE=site_reports \
  localhost/mysql:8.4
```

The image comes from the host itself, never from Docker Hub (1.50.0). Load and tag it once: ENCLAVES.md. Without it the script stops before it changes anything, and prints the steps.

The script runs the same container as the systemd unit `report-db`, so it starts with the host. Check it:

```shell
systemctl status report-db
podman ps --filter name=report-db
```

2. **The firewall.** Open 3309 to the AAP execution nodes only, one rule per node:

```shell
firewall-cmd --permanent --add-rich-rule='rule family=ipv4 source address=192.0.2.21 port
  port=3309 protocol=tcp accept'
firewall-cmd --reload
podman network reload --all
```

- A firewalld reload can drop the rules podman made for every container's network on the host, not only this one. `podman network reload --all` puts them back. Nothing is stopped or restarted.
- The source takes addresses, not names: firewalld says `INVALID_ADDR` for a name. The script's `AAP_SOURCES` looks a name up for you.

3. **The two accounts.** In the container (`podman exec -it report-db mysql -uroot -p`):

```SQL
CREATE USER 'report_writer'@'%' IDENTIFIED BY 'A-WRITER-PASSWORD';
GRANT SELECT, INSERT, UPDATE, DELETE, CREATE, ALTER, INDEX, CREATE VIEW, SHOW VIEW
  ON site_reports.* TO 'report_writer'@'%';
CREATE USER 'report_reader'@'%' IDENTIFIED BY 'A-READER-PASSWORD';
GRANT SELECT, SHOW VIEW ON site_reports.* TO 'report_reader'@'%';
```

- **report_writer**: the job's account. It makes the tables and views on the first run, then adds and replaces rows. DELETE is needed because a newer run replaces a month's rows.
- **report_reader**: for people and, later, dashboards. It only reads.

Both use MySQL 8.4's default login, `caching_sha2_password`. The script keeps their passwords in `/root/report-db.env`.

4. **The credential.** In AAP, create the credential type **Report database** from `aap/credential_types/report_database.yml`. Then create a credential of that type:

Field	Value
Database host	the STIG Manager host's name
Port	3309
Database	site_reports
User	report_writer
Password	the writer's password
Use TLS	off (see *TLS* below)

Attach it to the ticket insights job template.

5. **Turn it on.** Add to the template's Variables (or `all.yml`):

```YAML
servicenow_insights_db: true
```

The first run makes the tables and views. From the second month on, the pages draw lines.

6. **Fill the past months, once.** Launch the template once more, as a separate launch:

```yaml
servicenow_insights_backfill_months: 12
```

Leave the Limit empty. See *The backfill* below.

The backfill

`servicenow_insights_backfill_months: 12` reads the last 12 whole calendar months from ServiceNow, once. It works out each month with the report's own rules and writes it. Then the job stops:

- no ACT, no email, no pages;
- the job output shows each month as it is written, then a summary: months written and tickets per month.

It is safe to run twice: each month replaces what was there. A month the normal runs already wrote is replaced by the backfill's figures, which are the same.

How long it takes. Almost all of it is the read from ServiceNow: as long as a normal run's read of the same months, without the window before. Working out the months is quick. Measured on the test site, scaled up:

Records read	Working out the months
2,250	under 1 second
22,500	about 5 seconds
100,000	about 25 seconds (estimated, it grows in step)

The job prints each month as it is written, so you can follow it.

A table cut inside the window at `servicenow_insights_max_records` (1.16.0): every month can be short, so the backfill writes nothing, and says so. Raise the cap for the backfill launch and run it again.

Is it writing?

Three ways to know (1.15.0).

1. The job's last line. Every ticket insights run ends with it. After a write, the job reads the database back with a SELECT, so the counts are what the database holds, not what was sent:

```
Report database db.yoursite.mil:3309/site_reports: written - run 41, 2 months (2026-10, 2026-11
  (so far)), 4,210 figures;
the database now holds 38 runs, first month 2025-11, last month 2026-11
```

When nothing was written, the same line says why:

- `NOT written - servicenow_insights_db is false`;
- `NOT written - no Report database credential on the job template`;
- `NOT written - not reached or refused: ...` (down, the firewall, a wrong password);
- `NOT written - refused: ...` (the write itself failed, e.g. a grant missing);
- `NOT written - Check mode`;
- `NOT written - the records were cut (servicenow_insights_max_records): an incomplete run is never written` (1.16.0: the window itself was cut, so every month can be short; the rows already there

stay as they were).

A backfill ends with the same line. The pages say it too, under *How this was made*, without the host.

2. The check launch. It needs no ServiceNow read and writes nothing. Launch the ticket insights template with this extra variable:

```yaml
servicenow_insights_db_check: true
```

It connects with the template's Report database credential, then stops. The `report_reader` account works too. It prints:

```
Report database db.yoursite.mil:3309/site_reports: reached - MySQL 8.4.3, TLS none, as
  report_writer@% (may write)
Tables and views: all 15 there, schema version 1
Held: sn.yoursite.mil, period month - 13 runs, 13 months (12 complete), 2025-11 to 2026-11, newest
  written 2026-11-01 06:04:12 UTC
Held: sn.yoursite.mil, period 6m - 25 runs, 13 months (12 complete), 2025-11 to 2026-11, newest
  written 2026-11-01 06:04:12 UTC
```

Not reached, the job fails with the reason.

3. By hand, on the STIG Manager host:

```shell
podman exec -it report-db mysql -ureport_reader -p site_reports \
  -e "SELECT source, period, month, period_end, partial FROM insights_v_latest_run"
```

It shows the newest run per instance and period. The newest write's time is in `insights_run`: `SELECT MAX(written_at) FROM insights_run`.

On the pages

Each page has a **Trends** section after *At a glance*:

- **Service levels**: SLA met, response met, first contact, in %.
- **Volume**: incidents opened each month, and open at its end.
- **The months as a table**, with the median time to resolve and reopened.

What it shows depends on the months kept:

- **No month yet**: no section.
- **1 month**: its figures, and "1 month so far: the line starts next month".
- **2 to 11 months**: the lines, titled "N months so far".
- **12 months**: "the last 12 months".

A month with no run is a gap in the line. The month so far is drawn dashed. The pages are static. They never ask the database anything: the job reads it and draws the lines into each page.

The tables and views

Name	What it holds
`insights_run`	One row per run: the instance, the period (`6m`, `30d`, or `month`), the window, the month, `partial` (the month so far)
`insights_node`	One row per run and org node: its label, level, depth (0 = All), parent, and six main figures as columns
`insights_figure`	Every figure: run, node, metric, item (an outcome, category, backlog-age bucket or CI; empty for a plain figure), value
`insights_ticket`	1.17.0: one row per ticket - its fields less its text, people and CI, and its follow-up reads (*The ticket store*)
`insights_act_class`	1.17.0: each description's issue, the description as a hash (*The ACT cache*)
`insights_act_issue`	1.17.0: each issue's number, name (masked), kind and self-service (*The ACT cache*)
`schema_version`	The schema's version, per component (`servicenow_insights`: 1)
`insights_v_service`, `_volume`, `_process`, `_lifecycle`, `_quality`	A row per run and node, a column per figure of that set
`insights_v_labelled`	The figures with an item: outcomes, categories, backlog age, hot CIs
`insights_v_month_run`	The newest run of each month, per instance and period
`insights_v_latest_run`	The newest run, per instance and period

New figures in later releases are new metric names in `insights_figure`. They need no change to the tables.

The survey figures (1.16.0)

`survey_avg` is the headline survey's average on its scale (docs/SERVICENOW_INSIGHTS.md, *Satisfaction*). Two figures come with it, in `insights_figure` only (in no view):

Figure	What it holds
`survey_scale_max`	the top of that average's scale (4 for 1 to 4)
`survey_questions`	how many rating questions were read

Rows written before 1.16.0 have no `survey_scale_max`. Their `survey_avg` may mix questions on different scales, so nothing draws them. They are not rewritten. To see those months:

SQL

```
SELECT r.month, f.node, f.value FROM insights_figure f JOIN insights_run r ON r.run_id = f.run_id
WHERE f.metric = 'survey_avg' AND NOT EXISTS (SELECT 1 FROM insights_figure g WHERE g.run_id =
  f.run_id
  AND g.node = f.node AND g.variant = f.variant AND g.metric = 'survey_scale_max');
```

To replace them, run the backfill again (*The backfill*): it writes each month with the fix.

The ticket store and the ACT cache (1.17.0)

With `servicenow_insights_db: true`, the database also keeps each ticket's fields and ACT's grouping. A run then reads in full only the tickets that changed. The pages, the email and the workbook are the same as a full read's.

How a run reads

1. **The light read.** The report's own query, with only these fields: `sys_id`, `sys_updated_on`, `opened_at`, the short description, the close notes, the people and the CI. Also the names ServiceNow shows, which can change without `sys_updated_on` moving: the group, state, priority, category, subcategory, close code, hold reason, impact, urgency, catalog item and change type. The same cap as before (*More records than the cap*).
2. **Unchanged tickets** (the same `sys_updated_on` as the database holds) come from the database, with this run's text, people and CI from step 1.
3. **New or changed tickets** are read in full, by `sys_id`.
4. **The follow-up reads** (task_sla, the state metric, the hand-off paths, first assigned) are made for the changed tickets and every open one. A closed, unchanged ticket's come from the database.

A deleted ticket, or one moved to a group the report does not read, is not in step 1, so it drops out by itself. A renamed group shows its new name on the next run: step 1 reads it.

A run whose window was cut by the cap keeps no ticket. A cut in the window before only keeps the tickets read: they are full reads.

The job's last lines and *How this was made* say how the tickets were read:

```
Tickets: 2,253 - 4 read from ServiceNow (new or changed), 2,249 from the report database; 4
  written to the report database in 0 s.
```

The first run

The first run after the upgrade reads everything, as before, and fills the store. It takes as long as a run of 1.16.0, plus the write: 1 s or less for 2,253 tickets in the tests. The second run shows the gain.

What is stored per ticket

`insights_ticket`, one row per ticket:

Kept	Never kept
Number, table	The short description, the close notes, the work notes
Opened, resolved, closed and done times; `sys_updated_on`	The caller, the assignee, the resolver, anyone's name or sys_id
The assignment group's sys_id (new in 1.17.0: per ticket)	The CI
Reassignment and reopen counts, Made SLA, active	The names ServiceNow shows: the group's, the state's, the priority's, the category's ...
The parent, problem and caused-by numbers	

Kept	Never kept
Its SLAs (name, stage, breached, percent), state times, hand-off path, first assigned	

The hand-off path is kept as sys_audit gives it: the groups' sys_ids and times. The metric `Assignment Group` gives the names it recorded.

A row is deleted 800 days after its ticket was done. A ticket deleted in ServiceNow, or moved out of the report while open, has no done time: its row is deleted 800 days after its last update. Both deletes happen on a run that writes tickets. A cut run deletes nothing.

The ACT cache

Table	What it holds
`insights_act_class`	Each description's issue: the description as a SHA-256 hash (never its words) and the issue's number

The hash is a plain SHA-256. It cannot be turned back into the words. A reader holding a list of likely descriptions could still confirm one by hashing it.

insights_act_issue	Each issue: its number, its name, kind (incident or request), self-service

The issue's name is the only text the database holds. It is ACT's short name for an issue ("Printer offline / print queue stuck"), never a ticket's own text. Before it is stored, the same mask as the page's replaces any name, host, address or phone number in it with `[person]`, `[host]` and so on. It is at most 80 characters. A name that ACT invents and that is not in the ServiceNow data cannot be masked: it is stored as ACT gave it.

Only new descriptions go to ACT. The fixes and knowledge drafts are asked every run: ACT's text is not kept. Another provider, model or grouping prompt starts the cache again. The model is the one the run uses, also when it comes from site_act's default.

`servicenow_insights_act_cache_clear: true` replaces the cache only when ACT answered every grouping question. The old rows are deleted and the new ones written in one transaction. When ACT fails during the run, the cache is kept as it was, and the job says so:

```
ACT cache: not cleared - ACT answered 2 of 5 grouping questions, so the cache is kept as it was.
  Launch with servicenow_insights_act_cache_clear: true again.
```

Turning it off, and removing it

To	Do
Read everything once (e.g. after a ServiceNow restore)	Launch with `servicenow_insights_full_refresh: true`
Ask ACT everything again and replace the cache	Launch with `servicenow_insights_act_cache_clear: true`
Stop keeping tickets	`servicenow_insights_incremental: false`
Stop keeping ACT's grouping	`servicenow_insights_act_cache: false`
Remove what is kept	As root: `DELETE FROM insights_ticket; DELETE FROM insights_act_class; DELETE FROM insights_act_issue;`

What it does not see

- A closed ticket's SLA or metric row changed without its `sys_updated_on` moving (an SLA recalculated after closing). The store keeps the old one. `servicenow_insights_full_refresh: true` reads it again.

When the writer cannot make the tables

A database from 1.16.0 needs the three tables `insights_ticket`, `insights_act_issue` and `insights_act_class`. The first run makes them when the writer has the CREATE grant. Without it, or with `servicenow_insights_db_create: false`:

- the figures are read and written as before;
- the ticket store and the ACT cache are off for that run;
- the job warns once, naming the three tables and the CREATE grant.

Make them once by hand, or grant the writer CREATE on the database. By hand: run only the three statements `CREATE TABLE IF NOT EXISTS insights_ticket`, `insights_act_issue` and `insights_act_class` of *Making the tables by hand*. The rest are there already. A view's statement would stop with *ERROR 1050: Table … already exists*.

A row whose `sys_updated_on` differs from ServiceNow's in either direction (a database restored from an older backup) is read again.

Making the tables by hand

The first run makes the tables and views itself. If your writer account may not create them (`servicenow_insights_db_create: false`), make them once as root with these statements, in `site_reports`. Then the writer needs only SELECT, INSERT, UPDATE and DELETE.

On a database that already has some of them (an upgrade), run only the statements of what is missing. The tables' statements may run again, the views' may not (*ERROR 1050*).

SQL

```
CREATE TABLE IF NOT EXISTS schema_version (
  component VARCHAR(64) NOT NULL PRIMARY KEY,
  version INT NOT NULL,
  applied_at DATETIME NOT NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin;
```

SQL

```
CREATE TABLE IF NOT EXISTS insights_run (
  run_id BIGINT UNSIGNED NOT NULL AUTO_INCREMENT PRIMARY KEY,
  source VARCHAR(190) NOT NULL,
  period VARCHAR(16) NOT NULL,
  window_start DATETIME NOT NULL,
  window_end DATETIME NOT NULL,
  month CHAR(7) NOT NULL,
  partial TINYINT NOT NULL DEFAULT 0,
  data_end DATETIME NULL,
  written_at DATETIME NOT NULL,
  job VARCHAR(64) NOT NULL DEFAULT '',
  UNIQUE KEY run_key (source, period, window_end)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin;
```

SQL

```
CREATE TABLE IF NOT EXISTS insights_node (
  run_id BIGINT UNSIGNED NOT NULL,
  variant VARCHAR(8) NOT NULL DEFAULT '',
  node VARCHAR(255) NOT NULL,
  label VARCHAR(190) NOT NULL DEFAULT '',
  level VARCHAR(16) NOT NULL DEFAULT '',
  parent VARCHAR(255) NOT NULL DEFAULT '',
  depth INT NOT NULL DEFAULT 0,
  incidents INT NULL,
  requests INT NULL,
  resolved INT NULL,
  backlog INT NULL,
  sla_met_pct DECIMAL(6,2) NULL,
  median_resolve_h DECIMAL(12,2) NULL,
  PRIMARY KEY (run_id, variant, node)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin;
```

SQL

```
CREATE TABLE IF NOT EXISTS insights_figure (
  run_id BIGINT UNSIGNED NOT NULL,
  variant VARCHAR(8) NOT NULL DEFAULT '',
  node VARCHAR(255) NOT NULL,
  metric VARCHAR(64) NOT NULL,
  label VARCHAR(190) NOT NULL DEFAULT '',
  value DOUBLE NOT NULL,
  PRIMARY KEY (run_id, variant, node, metric, label),
  KEY by_metric (metric, node)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin;
```

SQL

```
CREATE TABLE IF NOT EXISTS insights_ticket (
  source VARCHAR(190) NOT NULL,
  sys_id VARCHAR(64) NOT NULL,
  tbl VARCHAR(40) NOT NULL,
  number VARCHAR(40) NOT NULL DEFAULT '',
  updated_on DATETIME NULL,
  active TINYINT NOT NULL DEFAULT 1,
  opened_at DATETIME NULL,
  done_at DATETIME NULL,
  grp VARCHAR(255) NOT NULL DEFAULT '',
  code VARCHAR(8) NOT NULL,
  fields JSON NOT NULL,
  follow JSON NOT NULL,
  written_at DATETIME NOT NULL,
  PRIMARY KEY (source, sys_id),
  KEY by_done (source, done_at)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin;
```

SQL

```
CREATE TABLE IF NOT EXISTS insights_act_issue (
  source VARCHAR(190) NOT NULL,
  cache_key VARCHAR(190) NOT NULL,
  issue_no INT NOT NULL,
  label VARCHAR(80) NOT NULL,
  kind VARCHAR(16) NOT NULL DEFAULT 'incident',
  self_service TINYINT NOT NULL DEFAULT 0,
  written_at DATETIME NOT NULL,
  PRIMARY KEY (source, cache_key, issue_no)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin;
```

SQL

```
CREATE TABLE IF NOT EXISTS insights_act_class (
  source VARCHAR(190) NOT NULL,
  cache_key VARCHAR(190) NOT NULL,
  key_hash CHAR(64) NOT NULL,
  issue_no INT NOT NULL,
  written_at DATETIME NOT NULL,
  PRIMARY KEY (source, cache_key, key_hash)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin;
```

SQL

```
CREATE VIEW insights_v_month_run AS SELECT *
FROM (SELECT r.run_id, r.source, r.period, r.window_start AS period_start, r.window_end AS
  period_end, r.month, r.partial,
  ROW_NUMBER() OVER (PARTITION BY r.source, r.period, r.month ORDER BY r.window_end DESC) AS
    newest
  FROM insights_run r) x
WHERE newest = 1;
```

SQL

```
CREATE VIEW insights_v_latest_run AS SELECT *
FROM (SELECT r.run_id, r.source, r.period, r.window_start AS period_start, r.window_end AS
  period_end, r.month, r.partial,
  ROW_NUMBER() OVER (PARTITION BY r.source, r.period ORDER BY r.window_end DESC) AS newest
  FROM insights_run r) x
WHERE newest = 1;
```

SQL

```
CREATE VIEW insights_v_labelled AS SELECT r.run_id,
  r.source,
  r.period,
  r.window_start AS period_start,
  r.window_end AS period_end,
  r.month,
  r.partial,
  n.node,
  n.variant,
  n.label,
  n.level,
  n.depth,
  n.parent,
  f.metric,
  f.label AS item,
  f.value
FROM insights_run r
JOIN insights_node n ON n.run_id = r.run_id
JOIN insights_figure f ON f.run_id = n.run_id AND f.variant = n.variant AND f.node = n.node AND
  f.label <> '';
```

SQL

```
CREATE VIEW insights_v_service AS SELECT r.run_id,
  r.source,
  r.period,
  r.window_start AS period_start,
  r.window_end AS period_end,
  r.month,
  r.partial,
  n.node,
  n.variant,
  n.label,
  n.level,
  n.depth,
  n.parent,
  MAX(CASE WHEN f.metric = 'sla_met_pct' THEN f.value END) AS sla_met_pct,
  MAX(CASE WHEN f.metric = 'response_met_pct' THEN f.value END) AS response_met_pct,
  MAX(CASE WHEN f.metric = 'fcr_pct' THEN f.value END) AS fcr_pct,
  MAX(CASE WHEN f.metric = 'fcr_desk_pct' THEN f.value END) AS fcr_desk_pct,
  MAX(CASE WHEN f.metric = 'reopen_pct' THEN f.value END) AS reopen_pct,
  MAX(CASE WHEN f.metric = 'reopen7_pct' THEN f.value END) AS reopen7_pct,
  MAX(CASE WHEN f.metric = 'median_resolve_h' THEN f.value END) AS median_resolve_h
FROM insights_run r
JOIN insights_node n ON n.run_id = r.run_id
LEFT JOIN insights_figure f ON f.run_id = n.run_id AND f.variant = n.variant AND f.node = n.node
  AND f.label = ''
GROUP BY r.run_id, n.run_id, n.variant, n.node;
```

SQL

```
CREATE VIEW insights_v_volume AS SELECT r.run_id,
  r.source,
  r.period,
  r.window_start AS period_start,
  r.window_end AS period_end,
  r.month,
  r.partial,
  n.node,
  n.variant,
  n.label,
  n.level,
  n.depth,
  n.parent,
  MAX(CASE WHEN f.metric = 'incidents' THEN f.value END) AS incidents,
  MAX(CASE WHEN f.metric = 'requests' THEN f.value END) AS requests,
  MAX(CASE WHEN f.metric = 'changes' THEN f.value END) AS changes,
  MAX(CASE WHEN f.metric = 'problems' THEN f.value END) AS problems,
  MAX(CASE WHEN f.metric = 'resolved' THEN f.value END) AS resolved,
  MAX(CASE WHEN f.metric = 'backlog' THEN f.value END) AS backlog,
  MAX(CASE WHEN f.metric = 'open_old' THEN f.value END) AS open_old
FROM insights_run r
JOIN insights_node n ON n.run_id = r.run_id
LEFT JOIN insights_figure f ON f.run_id = n.run_id AND f.variant = n.variant AND f.node = n.node
  AND f.label = ''
GROUP BY r.run_id, n.run_id, n.variant, n.node;
```

SQL

```
CREATE VIEW insights_v_process AS SELECT r.run_id,
  r.source,
  r.period,
  r.window_start AS period_start,
  r.window_end AS period_end,
  r.month,
  r.partial,
  n.node,
  n.variant,
  n.label,
  n.level,
  n.depth,
  n.parent,
  MAX(CASE WHEN f.metric = 'hops_over_pct' THEN f.value END) AS hops_over_pct,
  MAX(CASE WHEN f.metric = 'hops_open' THEN f.value END) AS hops_open,
  MAX(CASE WHEN f.metric = 'hold_open' THEN f.value END) AS hold_open,
  MAX(CASE WHEN f.metric = 'hold_no_reason' THEN f.value END) AS hold_no_reason,
  MAX(CASE WHEN f.metric = 'at_risk' THEN f.value END) AS at_risk,
  MAX(CASE WHEN f.metric = 'breached' THEN f.value END) AS breached,
  MAX(CASE WHEN f.metric = 'handoff_pct' THEN f.value END) AS handoff_pct,
  MAX(CASE WHEN f.metric = 'pingpong_pct' THEN f.value END) AS pingpong_pct,
  MAX(CASE WHEN f.metric = 'matrix_off_pct' THEN f.value END) AS matrix_off_pct,
  MAX(CASE WHEN f.metric = 'closure_late' THEN f.value END) AS closure_late,
  MAX(CASE WHEN f.metric = 'changes_failed' THEN f.value END) AS changes_failed,
  MAX(CASE WHEN f.metric = 'changes_backed_out' THEN f.value END) AS changes_backed_out,
  MAX(CASE WHEN f.metric = 'ctasks_overdue' THEN f.value END) AS ctasks_overdue
FROM insights_run r
JOIN insights_node n ON n.run_id = r.run_id
LEFT JOIN insights_figure f ON f.run_id = n.run_id AND f.variant = n.variant AND f.node = n.node
  AND f.label = ''
GROUP BY r.run_id, n.run_id, n.variant, n.node;
```

SQL

```
CREATE VIEW insights_v_lifecycle AS SELECT r.run_id,
  r.source,
  r.period,
  r.window_start AS period_start,
  r.window_end AS period_end,
  r.month,
  r.partial,
  n.node,
  n.variant,
  n.label,
  n.level,
  n.depth,
  n.parent,
  MAX(CASE WHEN f.metric = 'state_new_h' THEN f.value END) AS state_new_h,
  MAX(CASE WHEN f.metric = 'state_progress_h' THEN f.value END) AS state_progress_h,
  MAX(CASE WHEN f.metric = 'state_hold_h' THEN f.value END) AS state_hold_h,
  MAX(CASE WHEN f.metric = 'state_resolved_h' THEN f.value END) AS state_resolved_h,
  MAX(CASE WHEN f.metric = 'hold_share_pct' THEN f.value END) AS hold_share_pct
FROM insights_run r
JOIN insights_node n ON n.run_id = r.run_id
LEFT JOIN insights_figure f ON f.run_id = n.run_id AND f.variant = n.variant AND f.node = n.node
  AND f.label = ''
GROUP BY r.run_id, n.run_id, n.variant, n.node;
```

SQL

```
CREATE VIEW insights_v_quality AS SELECT r.run_id,
  r.source,
  r.period,
  r.window_start AS period_start,
  r.window_end AS period_end,
  r.month,
  r.partial,
  n.node,
  n.variant,
  n.label,
  n.level,
  n.depth,
  n.parent,
  MAX(CASE WHEN f.metric = 'notes_good_pct' THEN f.value END) AS notes_good_pct,
  MAX(CASE WHEN f.metric = 'notes_thin_pct' THEN f.value END) AS notes_thin_pct,
  MAX(CASE WHEN f.metric = 'notes_bare_pct' THEN f.value END) AS notes_bare_pct,
  MAX(CASE WHEN f.metric = 'filed_other_pct' THEN f.value END) AS filed_other_pct,
  MAX(CASE WHEN f.metric = 'filed_no_ci_pct' THEN f.value END) AS filed_no_ci_pct,
  MAX(CASE WHEN f.metric = 'filed_short_pct' THEN f.value END) AS filed_short_pct,
  MAX(CASE WHEN f.metric = 'after_hours_pct' THEN f.value END) AS after_hours_pct,
  MAX(CASE WHEN f.metric = 'survey_avg' THEN f.value END) AS survey_avg,
  MAX(CASE WHEN f.metric = 'survey_n' THEN f.value END) AS survey_n
FROM insights_run r
JOIN insights_node n ON n.run_id = r.run_id
LEFT JOIN insights_figure f ON f.run_id = n.run_id AND f.variant = n.variant AND f.node = n.node
  AND f.label = ''
GROUP BY r.run_id, n.run_id, n.variant, n.node;
```

SQL

```
INSERT INTO schema_version (component, version, applied_at) VALUES ('servicenow_insights', 1,
  UTC_TIMESTAMP());
```

TLS (optional)

The connection is plain TCP by default. MySQL 8.4's `caching_sha2_password` then sends the password encrypted with the server's RSA key. That needs the Python library `cryptography`, which the all-in-one EE has.

To use TLS, give the server a certificate and tick **Use TLS** on the credential. Paste the CA that signed the certificate into the credential's CA field, or leave it empty to use the EE's trust store. The certificate must name the host the credential names.

TLS is not tested end to end in this release: the tests run against a database without TLS, as the setup uses. Check it on your own server before you rely on it.

The EE and FIPS

The job needs **PyMySQL** (pure Python) and **cryptography**. Both are in the all-in-one EE (`ee-check` lists them).

On a FIPS host, check the EE before the first run. `ee-check` tries the login's RSA step:

```shell
podman run --rm site-ee-all:3 ee-check | grep -i 'MySQL login'
#   YES  MySQL login without TLS (caching_sha2_password: PyMySQL's RSA step)
```

A `no` means the EE's OpenSSL refuses that step. Then turn on TLS (above): over TLS no RSA step is needed.

`ee-check` also says no for PyMySQL 1.2.1 to 1.2.3 (1.16.0). Their first login after the database restarts fails. Build the EE again from the current `ee/` files: they ask for PyMySQL 1.2.4 or later.

Watching it

Use the existing **Database health** job (`docs/MARIADB.md`). Add the container to the STIG Manager host's settings:

```YAML
check_mariadb_containers: [STIG-MANAGER-DB-CONTAINER, report-db]
```

Create the monitoring account in this container too, with the same password (`docs/MARIADB.md`, section 4).

Backups and retention

Backups are the host's existing process: include the folder `/var/lib/report-db`. The figures are kept for ever. A site with a few hundred groups adds a few MB a month. The ticket store holds about 2 KB per ticket on disk, for the tickets of the last 800 days.

When something goes wrong

The job says	What it means	What to do
`servicenow_insights_db is true, but the job template has no "Report database" credential`	No credential on the template	Attach it (step 4)
`[WARNING]: The report database HOST:3309/site_reports: Can't connect ...`	The database is down, or the firewall blocks this execution node	The report is whole and the job green. Check the container and step 2
`... Access denied for user 'report_writer'`	A wrong password	Fix the credential
`... the login needs the cryptography library`	The EE lacks `cryptography`	Use the all-in-one EE, or turn on TLS
`... the server wants TLS`	The server requires TLS	Tick **Use TLS** on the credential
`... 'NoneType' object has no attribute 'is_auth_switch_request'`	A bug in PyMySQL 1.2.1 to 1.2.3: the first login after the database restarts fails. Since 1.16.0 the job tries once more by itself	Launch again: it works. The lasting fix: build the EE again from the current `ee/` files (PyMySQL 1.2.4 or later)
Another application on the host lost its database after the firewall step	The firewall reload dropped podman's network rules	`podman network reload --all` on the host. Nothing needs a restart
`STOPPED: the image localhost/mysql:8.4 is not on this host`	The setup script found no image. Nothing was changed	Load and tag it (the steps it printed), then run the script again
`kept complete: 2026-10`	A run ending inside a month met that month already complete	Nothing: the complete month is kept

`servicenow_insights_db_required: true` turns the warnings into a failed job.

Settings

Setting	Default	What it does
`servicenow_insights_db`	`false`	Write the figures and draw the trends
`servicenow_insights_db_required`	`false`	`true`: no credential, or the database not reached, fails the job
`servicenow_insights_db_create`	`true`	Make the tables and views on the first run. `false`: made by hand (*Making the tables by hand*)
`servicenow_insights_db_months`	`12`	The months the trends show
`servicenow_insights_db_timeout`	`10`	Seconds to connect
`servicenow_insights_backfill_months`	`0`	`> 0`: read and write that many past months, then stop
`servicenow_insights_db_check`	`false`	`true`: only check the database, read only, then stop (*Is it writing?*)
`servicenow_insights_incremental`	`true`	Keep each ticket and read only what changed (*The ticket store*)
`servicenow_insights_full_refresh`	`false`	`true`: this launch reads every ticket again
`servicenow_insights_act_cache`	`true`	Keep each description's issue: only new descriptions go to ACT
`servicenow_insights_act_cache_clear`	`false`	`true`: this launch asks ACT everything again and replaces the cache

Later

A management dashboard (Grafana or another) can read the views as `report_reader`. It is not part of 1.13.0.

13. Workflows and schedules

A **workflow** chains job templates. Each arrow says when the next step runs:

- **Run on success**: only if the step before it succeeded.
- **Run on fail**: only if it failed.
- **Run always**: either way.

The checks *fail on purpose* when they find something. So "Run on fail" means "a problem was found", and "Run always" means "whatever happened". A step also receives what the steps before it published (**artifacts**). That is how the tickets step learns what the health check found.

This chapter first shows how to build any workflow, then a catalog of ready-made workflows for Linux, for Windows, and for both, and how to schedule them.

How to build any workflow, click by click

1. **Automation Execution › Templates › Create template › Create workflow job template**.
2. **Name** (e.g. `Daily health`), **Organization**.
   - **Inventory: leave it empty.** Each step then uses its own template's inventory, so one workflow can hold Linux and Windows steps. A workflow inventory only reaches steps whose template prompts for the inventory.
   - Tick **Prompt on launch** next to **Limit** if you want to pick hosts at launch.
   - Leave **Variables** empty: workflow variables override every step's own answers.
3. **Create workflow job template**. The **workflow visualizer** opens.
4. **The first step: Add step** › **Node type**:
   - *Job Template*: one of the templates (the usual case);
   - *Approval*: a person must click Approve (give it a **Timeout**);
   - *Workflow Job Template*: another workflow, as one step;
   - *Project Sync* / *Inventory Source Sync*: refresh the code or the inventory first.

Pick the template, then fill in **this step's** answers:

- **Survey answers**, e.g. `health_checks` = `daily`;
- **Job type** `Check` for a dry run (DRY_RUNS.md);
- a **Limit**.

The wizard only offers what the template asks in its survey or has **Prompt on launch** ticked for. › **Finish**.

5. **Next steps:** hover over a box › **Add step and link** (the plus sign) › the node, and the **link type** (success / fail / always).
   - **Two things at once:** add a second first step with **Add step**. Both start together.
   - **Two arrows into one step:** open the step › **Convergence**: *Any* runs it when one parent finishes as linked, *All* waits for all of them.
6. **Save** (top right). Closing without saving throws the graph away.
7. **Try it:** launch it once with the risky steps set to `Check` (step 4), then set them back.

Who may approve: open the workflow › **User Access** (or **Team Access**) › **Add roles** › **Approve**. Pending approvals are in **Automation Execution › Administration › Workflow Approvals**, and in the workflow job's view.

Which templates fit where:

Template	Fails when	Publishes (for the next step)	Typical next step
Health check / Windows health check	a finding (`site_fail_on`), or ACT proposes a fix	the findings (`site_health`)	ServiceNow tickets (**always**); an approval (**on fail**)
Certificate report / Windows certificate report	a certificate expires soon	the findings	ServiceNow tickets (**always**)
POA&M status	an item is overdue / due soon	the findings	ServiceNow tickets (**always**)
STIG drift report	a host drifted from its checklist, or fails a rule it passed last time	the findings	ServiceNow tickets (**always**)
STIG recheck - check (`check_stig_update_workflow: true`)	reviews to write to STIG Manager (NEEDS APPROVAL)	the reviews (`stigman_update_plan`)	an approval (**on fail**), then STIG Manager - update
Network performance report	loss, latency, a refused port, drops or an OCSP responder over its limits	the findings	ServiceNow tickets (**always**)
Troubleshoot / Windows troubleshoot	never for findings (a look, not a verdict)	the findings	a health check, tickets if you want them
Patch hosts / Windows patch	a host fails, or its services do not come back	-	a health check (**always**)
Apply approved ACT fix	the problem is still there	the findings of the re-check	ServiceNow tickets (**always**)
Service watch - check	a container is down (NEEDS APPROVAL)	the fix to approve	an approval (**on fail**)
ServiceNow tickets	problems exist (it opened or updated tickets)	-	- (the end)

Adding ACT to a workflow: what "on fail" means, and where site_act goes

You do not add `site_act` to the workflow. There is no ACT template and no ACT box. ACT runs **inside the check job**. The check playbooks (Health check, Troubleshoot, Database health, Service watch) already include `roles/site_act` - the Windows ones not yet (WINDOWS.md, "Not in this release") - and it runs when that job's answers say `use_act` = `yes`, at the level in `site_act_level`. In the workflow you only give the check box those two answers.

"On fail" is the check job's own result. Nothing extra is checked. The check playbook decides by itself, against its thresholds (the role defaults and your `group_vars`: disk full %, certificate days, ...). The check box ends **red** when:

- it found a problem at or above `site_fail_on` (default: `critical` and `warning`), or
- ACT (`diagnose`) proposed a fix that waits for a person: `NEEDS APPROVAL ... ACT proposes: <commands>`, or
- a host could not be checked (sudo failed, the job stopped on it), or no host at all could be reached. One host that cannot be reached does not make it red: it is listed as NOT REACHED and gets its "no result" ticket (`site_unreachable_fails: true` = red, as before).

A **Run on fail** link from the check box therefore leads to the approval. **Run on success** means the check box ended green; **Run always**, either way.

Box	Link into it	Runs when
1. Health check (`use_act` = `yes`, `site_act_level` = `diagnose`)	(start)	always
2. Approval	**Run on fail**, from 1	the check job ended red
3. Apply approved ACT fix	**Run on success**, from 2	a person clicked Approve
4. ServiceNow tickets	**Run always**, from 1 and from 3	after the check, and after the fix

The steps in words:

1. **Health check** box: answers `use_act` = `yes`, `site_act_level` = `diagnose`. This needs those two survey questions on the template (ADDING_ACT.md, step 3).
2. **Approval** box, **Run on fail** from 1.
3. **Apply approved ACT fix** box (`playbooks/act_fix_approved.yml`), **Run on success** from 2. It needs no answers: AAP hands it ACT's proposed commands from the health check job, and it runs exactly those.
4. **ServiceNow tickets** boxes, **Run always**, from 1 and from 3.

The approver opens the health check job and reads `ACT | what ACT says` and the red `NEEDS APPROVAL` line. If there is no such line (the job is red because of findings ACT had no fix for), there is nothing to approve: **Deny**. Approving does no harm either: the apply step skips every host with nothing approved.

Without approvals: `site_act_level` = `self-heal` with the fixes you allow in `site_act_allow`. ACT applies those itself, inside the check job, and the checks run again. Then the workflow is simply `[Health check] --Run always--> [ServiceNow tickets]`.

A playbook of your own gets ACT in the **playbook**, not in the workflow: it includes `site_findings` (start, your check), then `site_act`, then `site_findings` report. See ADDING_ACT.md, "Use ACT in a playbook of your own". Its job template then gets the same two survey questions, and it fits the same workflow.

Linux workflows

1. Daily health



Daily health: every run hands its findings to the tickets step, healthy or not.


Step	Template	Answers	Link
1	Health check	`health_checks` = `daily`	(start)
2	ServiceNow tickets	none	**Run always**, from step 1

Why "always". The tickets step opens tickets for what failed, and also notes the tickets of problems that cleared. That needs the healthy runs too. It fails when problems exist, so the workflow shows red until they are fixed.

Schedule: every day at 06:00.

2. Weekly compliance

Three independent chains in one workflow. Add each first box with **Add step** (not "Add step and link"), so they all start together:




Weekly compliance: three independent chains, each with its own tickets step (a step with two parents would get only one parent's findings).

Give each chain **its own** tickets box. A box with two parents gets only one parent's findings: the artifacts overwrite each other.

The `weekly` set includes the trust check (a compromised or dropped CA still trusted somewhere on the host). For the one table of every store on every Linux host, add a fourth chain, *Trust store report -> ServiceNow tickets*, or run that template on demand. vCenter and the ESXi hosts have their own report, *VMware - trust store report*, which does not feed tickets (TRUST_STORES.md).

Schedule: Mondays at 07:00.

3. Patch with checks



Patch with checks: every host healthy first (one failing host stops the whole run), a person approves, patch one host at a time, then check again.

Step	Template	Answers	Link
1	Health check	`health_checks` = `disk`, `mounts`, `services`	(start)
2	*Approval*	Name `Patch these hosts now?`, **Timeout** 8 hours	**Run on success**, from 1
3	Patch hosts	`patch_security_only` as you like; `automatic_restarts` (see below); `patch_serial` (hosts at a time) and `patch_snapshot` (a VMware snapshot before each host: RUNBOOKS.md) as you like	**Run on success**, from 2
4	Health check	`health_checks` = `daily`	**Run always**, from 3
5	ServiceNow tickets		**Run always**, from 4
6	ServiceNow tickets		**Run on fail**, from 1 (tickets for what the pre-check found)

Why these links:

- **Healthy first.** Patching a host that is already failing makes the next problem impossible to diagnose. The pre-check must pass before anyone is asked. **If any one host fails it, the whole run stops before the approval and no host is patched.** Fix that host (the ticket says what is wrong), or launch again with a Limit that leaves it out. Warnings count too while `site_fail_on` includes `warning`. A disk at 86% blocks patching, so clear it before the maintenance window.
- **A person approves.** The approval step waits (up to its **Timeout**). Deny, or no answer, stops the workflow and nothing is changed.

- **Always check after.** The post-check runs whatever happened in patching, so a half-patched host is still reported.


No automatic restarts unless you ask for them. Patching installs the updates; a host that then needs a reboot is **not** rebooted, and the job says so. The post-check's `patching` finding ("reboot needed") keeps it visible until someone reboots it. To let the job reboot hosts that need it, give step 3 `automatic_restarts` = `yes`. Add a survey question for it on the Patch hosts template (*Multiple Choice*, `no` / `yes`, default `no`), or put `automatic_restarts: true` in the step's variables. Hosts in `patch_never_reboot_groups` are never rebooted either way.

Snapshots before patching: with `patch_snapshot: true` on step 3, each VM gets a snapshot named `patching` right before it is patched. Delete them a few days later, once the patching is proven: workflow 19 (snapshot cleanup) with `vm_snapshot_cleanup_name_words: [patching]`.

Launch with **Limit** `patch_hosts`, or one group at a time (`stigman` this week, another group next week). **Schedule:** monthly, in your maintenance window, for example the second Wednesday at 20:00. The approval then waits for the on-call person.

4. Patch with a dry run first

The same as 3, but the approver sees exactly what will be installed before approving:




Step	Template	Answers	Link
1	Health check	`health_checks` = `disk`, `mounts`, `services`	(start)
2	Patch hosts	**Job type** `Check`	**Run on success**, from 1
3	*Approval*	Name `Install what the dry run listed?`. Description: `Open the "Patch hosts" dry-run job: it lists every package per host.`	**Run on success**, from 2
4	Patch hosts	**Job type** `Run`; `automatic_restarts` as you decide	**Run on success**, from 3
5	Health check	`health_checks` = `daily`	**Run always**, from 4
6	ServiceNow tickets		**Run always**, from 5

Needs **Prompt on launch** for **Job type** on the Patch hosts template (steps 2 and 4 set it).

5. Fix with approval (ACT)

For when you use ACT. See ADDING_ACT.md for the three levels.



Fix with approval (ACT): the check job fails with NEEDS APPROVAL only when ACT proposed a fix; deny or timeout changes nothing.

Step	Template	Answers	Link
1	Health check (with the ACT survey questions)	`use_act` = `yes`, `site_act_level` = `diagnose`	(start)
2	ServiceNow tickets		**Run always**, from 1
3	*Approval*	Name `Apply the fix ACT proposed?`, **Timeout** 30 minutes. Description: `Read ACT's report and the NEEDS APPROVAL line in the health check job first.`	**Run on fail**, from 1
4	Apply approved ACT fix		**Run on success**, from 3

Step	Template	Answers	Link
5	ServiceNow tickets		**Run always**, from 4 (notes the tickets whose problem the fix cleared)

Caveat: not yet proven in a live AAP. The whole approve-and-fix path depends on the check job's result (the proposed commands) reaching the apply job through the Approval node. The playbooks were tested on their own, but that hand-over inside AAP itself has not been run end to end. Rehearse it first with the dry run below, and read SERVICE_WATCH_DEMO.md (Part 9) if the apply job says `Nothing to apply`.


The approver reads, in the health check job, `ACT | what ACT says` (root cause, evidence, the fix) and the red `NEEDS APPROVAL ... ACT proposes: <command>` line. **That exact command** is all the apply step can run: it runs it itself (no model, no key), stops at the first command that fails, and runs the same checks again. The tickets carry ACT's analysis too.

Rehearse it: see ACT's fixes, change nothing.

- **One job, no workflow.** Launch **Health check** (or **Troubleshoot**) with `use_act` = `yes` and `site_act_level` = `diagnose`. ACT investigates with read-only commands and proposes fixes; every change is refused. The job ends red with `NEEDS APPROVAL ... ACT proposes: <commands>`: that list is what would run. Nothing on the host changed.
- **The whole workflow, as a dry run.** On the **Apply approved ACT fix** template (and *Service watch - apply approved fix*) tick **Prompt on launch** next to **Job type**. In the workflow visualizer click the apply box › **Edit** (pencil) › **Job type** `Check` › **Save**. Now run the workflow and approve: the apply job prints `DRY RUN on <host>: approved, and would run: <commands>. Nothing was changed (Check mode).` and ends green. When you trust it, set that node's **Job type** back to `Run`.

6. Security posture (weekly)

The STIG-related checks, and the POA&M list, with tickets:




Step	Template	Answers	Link
1	Health check	`health_checks` = `selinux`, `fapolicyd`, `auditd`, `accounts`	(start)
2	ServiceNow tickets		**Run always**, from 1
3	POA&M status		(start, with **Add step**)
4	ServiceNow tickets		**Run always**, from 3

Schedule: Wednesdays 07:00. Use it instead of the `weekly` set in *Weekly compliance* if your security team wants these on their own day.

7. Certificate watch (daily)

Certificates expire on a day, not in a week:



Step	Template	Answers	Link
1	Certificate report		(start)
2	ServiceNow tickets		**Run always**, from 1
3	Certificate renewal - CSRs (optional)		**Run always**, from 2

Schedule: every day 06:30. Put `check_certs_warn_days` (survey, 30) on the **workflow**, so every step uses the same number. Tickets then start a month ahead. The de-duplication keeps it to one ticket per certificate.

Step 3 makes a new key and a CSR on the host for each certificate that expires (in a file, on a port, in a keystore - never the trust store's), and attaches the CSR to that certificate's ticket from step 2 (RUNBOOKS.md, "Certificate renewal"). It must be **Run always**: steps 1 and 2 are red on purpose while certificates expire. Hosts in `cert_skip_hosts` or `cert_skip_groups` (Satellite) are left out of every step: set them in `all.yml`, or on the workflow, so every step gets them.


No incidents (`cert_renew_servicenow: catalog` - the CSRs ordered from the PKI's catalog item): leave step 2 out and link step 3 to step 1, **Run always** (CERT_RENEWAL_CATALOG.md).

Install the issued certificates (with the catalog item): workflow 29, after this one.

Network devices: *Network device certificate renewal* on its own, daily - it reads the devices, opens the incidents and emails the report (NETWORK_CERTS.md). **A dashboard:** with `cert_inventory_files` or `cert_inventory_sql` in `all.yml`, each certificate report also writes every certificate it read (CERT_INVENTORY.md).

Network configurations: *Network config backup* on a daily schedule - a commit in the backups' repository when a device changed, optionally an incident for it. A **load** as a workflow: *[Network config load]* as **Check** › **Approval** › *[Network config load]* as **Run**, the change and its lines in the workflow's Variables: the approver sees the dry run's report - exactly what will be sent - before anything is. Click by click: NETWORK_CONFIG.md, "A load, with an approval".

29. Certificate install, with an approval (daily)




Step	Template	Link
1	Certificate install - check	(start)
2	*Approval*: `Install the certificates the check listed?`, **Timeout** 8 hours. Description: `Open the check job: its READY lines say what each one changes.`	**Run on fail**, from 1
3	Certificate install - approved (the check's inventory, no Limit)	**Run on success**, from 2

Schedule: every day 07:00, after workflow 7. The check reads each renewal's request in ServiceNow for the certificate the PKI put there and fails on purpose when one is ready (`NEEDS APPROVAL`); nothing ready, it stays green and the approval never comes. The install plans each one again, copies the old files aside, reloads the service, checks the port, and puts the old files back if anything is wrong. Windows: the same with *Windows certificate install - check / approved*. **A request opened by hand:** a workflow survey question `cert_install_ritm` (not required) - launched with a RITM number, the check reads that request instead of each renewal's own; the schedule leaves it empty. Everything else - what stays for a person, the restore: CERT_INSTALL.md.

(There is no workflow 35: the number was skipped, and the ones after it keep their numbers.)

36. fapolicyd, with an approval (daily)



Step	Template	Link
1	fapolicyd - check: Variables `fapolicyd_workflow: true`, `fapolicyd_since: yesterday`, and `fapolicyd_act: true` for ACT's explanation (the *ACT model key* credential)	(start)
2	*Approval*: `Make the fapolicyd changes the check listed?`, **Timeout** 8 hours. Description: `Open the check job or its report: Changes to approve, and why.`	**Run on fail**, from 1
3	fapolicyd - approved (the same playbook, the check's inventory, `fapolicyd_workflow` not set)	**Run on success**, from 2

Both templates are `playbooks/fapolicyd.yml` with the *Machine* credential (sudo); tick **Prompt on launch** for **Limit** on both, and on the workflow, to run it on some hosts only. **Schedule:** every day 07:00. The check reads each host - what keeps fapolicyd down, what it blocked or would have blocked since yesterday, its rules - and when there is something to change it hands **each host's own lines** to step 3 (`fapolicyd_workflow_plan`) and fails on purpose, `NEEDS APPROVAL`; nothing to change, it stays green and the approval never comes. Approve, and step 3 makes each host's lines - getting fapolicyd running first, then the rest; deny, and nothing changes.


The check's report says what Approve makes on each host (*Approve makes these*) and what it holds back (*Held back for a person*). **Limit the workflow to the hosts that must run fapolicyd** (an inventory group, as its Limit or the schedule's): it starts fapolicyd - permissive - on every host where it is installed and stopped.

A host where fapolicyd is down comes back by itself, one morning at a time: its trust files, `db_max_size`, enabled at boot, started **permissive** (blocking nothing); then the trust entries and rules for what it would block, the rules cleaned up; then, on the first quiet day, `permissive: 1 -> 0`. Held back for a person (the check's output and report say which, and why): `permissive: 0 -> 1` on a running, enforcing host; a clean-up that blocks more on an enforcing host; and `permissive: 1 -> 0` while fapolicyd is not running, still has would-be blocks, or such a clean-up to make first.

A dry run: deny at step 2 - or a copy of the workflow whose step 3 has **Job type Check** (tick Prompt on launch for Job type on *fapolicyd - approved*). The audit log must still hold yesterday at 07:00 (`ls -l /var/log/audit/`); approve within the day: step 3 reads the same window again. docs/RUNBOOKS.md, "fapolicyd".

37. STIG Manager updated, with an approval

The STIG recheck's "update the review", written to STIG Manager after a person approves it.




Step	Template	Link
1	STIG recheck - check: the *STIG recheck* playbook (`playbooks/stig_recheck.yml`) with Variables `check_stig_update_workflow: true`	(start)
2	*Approval*: `Write the reviews the check listed to STIG Manager?`, **Timeout** 8 hours. Description: `Open the check's report: Approve writes these reviews to STIG Manager.`	**Run on fail**, from 1
3	STIG Manager - update (`playbooks/stigman_update.yml`, its own *STIG Manager API* credential: the client that may write reviews)	**Run on success**, from 2

- **The check template:** a copy of *STIG recheck*, with the same inventory and credentials (the machine credential and the read-only *STIG Manager API*). Tick **Prompt on launch** for **Limit**.
- **Windows:** a second workflow of the same shape, with *Windows STIG recheck - check* (`playbooks/win_stig_recheck.yml`, the same Variable). It uses the same *STIG Manager - update* template.
- **The update template:** inventory any (it runs on the controller). Its only credential is the writing client's *STIG Manager API*.
- **What happens:** the check fails on purpose (`NEEDS APPROVAL`) when there is something to write, and hands the list on. With nothing to write it stays green, and the approval never comes. Approve, and step 3 writes exactly those reviews, each only if STIG Manager still has it as the check read it. Deny, and nothing is written.
- **A host with no asset** (0.72.0, Linux): add `check_stig_update_create_assets: true` to the check's Variables (and have `check_stig_stigman_collection` set): the check scans it in full and lists *NEW ASSET …*; Approve creates it, with its STIG and the scan's answers. The update's client then needs **Manage** in that collection.
- **Schedule:** on demand after fixing hosts, or after patch night. Approve the same day, so few reviews change in between.
- **A dry run:** deny at step 2, or give a copy of the workflow a step 3 with **Job type Check** (tick **Prompt on launch** for Job type on *STIG Manager - update*).

Everything else, including what is written, the client and its grant: STIG_DRIFT.md.

40. Checklists imported into STIG Manager, with an approval

Checklists (CKL, CKLB) you keep on a share - VMware's InSpec checklists too, which STIG Manager's own import rejects - written into STIG Manager after a person approves them.



Step	Template	Link
1	STIG Manager - import checklists - check: the *STIG Manager - import checklists* playbook (`playbooks/stigman_ckl_import.yml`) with Variables `stigman_ckl_import_workflow: true`	(start)
2	*Approval*: `Write the checklists' reviews (and the new assets) to STIG Manager?`, **Timeout** 8 hours. Description: `Open the check's report: Approve writes these reviews to STIG Manager.`	**Run on fail**, from 1
3	STIG Manager - update (`playbooks/stigman_update.yml`, workflow 37's template: the client that may write reviews, **Manage** to create assets)	**Run on success**, from 2

- **The check template:** a copy of *STIG Manager - import checklists*, with the same credentials (the read-only *STIG Manager API* and *Windows file share*) and Variables (`stigman_ckl_import_src`, `stigman_ckl_import_collection`).
- **What happens:** the check fails on purpose (`NEEDS APPROVAL`) when there is something to write, and hands the list on; with nothing to write it stays green. Approve, and step 3 creates the new assets listed and writes exactly those reviews. Deny, and nothing is written.
- **Schedule:** on demand, after new checklists are on the share.

As STIG Manager Watcher (0.76.0) - the same workflow on a schedule, every 15 to 60 minutes, **Concurrent jobs** off. On the check template's Variables, besides `stigman_ckl_import_workflow: true`:

YAML

```
stigman_ckl_import_collection: Watcher      # the staging collection: a host found nowhere is
                                            # created here
stigman_ckl_import_collections: ['*']       # a host's asset looked for in every collection -
                                            # written to each that has the STIG
stigman_ckl_import_auto: existing           # reviews of assets that are there written by the
                                            # check at once
stigman_ckl_import_move: true               # files done with moved to imported/<date>/ (the
                                            # share's account: Modify)
```

The check then writes what is for assets that are there itself, and fails on purpose (`NEEDS APPROVAL`) only when a new host waits to be created - the approval and step 3 as above. Its *STIG Manager API* credential is then the client that writes (Full in the collections, as step 3's). With `stigman_ckl_import_auto: all` no approval is ever asked: run the plain template on the schedule, no workflow. CKL_IMPORT.md.

Everything else - how a checklist's asset and STIG are found, what is written: CKL_IMPORT.md.

33. STIG drift (weekly)


Has a server moved away from its STIG checklist since it was reviewed?



Step	Template	Answers	Link
1	STIG drift report	`target`: the group to scan	(start)
2	ServiceNow tickets		**Run always**, from 1

Schedule: weekly, e.g. Sunday 02:00 (a STIG scan takes a few minutes per host and some CPU), and once after patch night. One incident per host with drift (a rule STIG Manager has as Not a Finding passed before and fails now) or a new fail since an earlier scan; *Run always*, so the incident of a host that is clean again gets its note. STIG Manager is only read. Click by click: STIG_DRIFT.md, "Setting it up".


34. Network performance (hourly)



Step	Template	Answers	Link
1	Network performance report	`target`: the group to measure from	(start)
2	ServiceNow tickets	`servicenow_min_severity: critical` (optional: the warnings stay in the report)	**Run always**, from 1

Schedule: hourly, **Concurrent jobs** off on the workflow. The trend - each path against the host's own usual - needs a few runs before it says anything. When users say "the network is slow", launch the template on its own with the group they use: the report shows where. NETWORK_PERF.md.


38. Add or remove an SMTP relay whitelist address, with an approval



Two workflows with these steps: *Mail relay - add an IP* (Variables `mail_relay_action: add`, a survey with the IP addresses - one, a subnet or several separated by commas - and the required comment) and *Mail relay - remove an IP* (`mail_relay_action: remove`, the IP addresses). The plan emails the exact lines "waiting for approval"; nothing to change stops it before the approval. Started from Orchestrator: launch the workflow (MAIL_RELAY.md). No schedule.

A third, *Mail relay - remove unused addresses*, has *Mail relay - unused addresses plan* (`playbooks/mail_relay_unused.yml`) as its first step: it reads the relays' mail logs and plans the removal of the addresses that sent no mail in six months; the approval and the apply step are the same (MAIL_RELAY.md). No survey; a schedule if you like (twice a year) - nothing unused stops it before the approval. *Mail relay - format the whitelist* (one address per line, each named) is a job of its own, run as Check first.

8. Database watch: MariaDB and MySQL (hourly)




Step	Template	Answers	Link
1	Database health - MariaDB / MySQL	none; it targets `mariadb_hosts`, `mysql_hosts` and `database_hosts` by default (a **Limit** narrows it)	(start)
2	ServiceNow tickets		**Run always**, from 1

The database template runs only the MariaDB / MySQL check (host installs and podman containers), so it is quick and the database team can own it and its tickets (MARIADB.md). Prefer to keep it in the general Health check? Use the *Health check* as step 1 with `health_checks` = `disk`, `services`, `mysql` (`mariadb` and `database` are the same check) and a **Limit** of your database group. The template *Database health* also supports `use_act=true`.

Schedule: hourly. It is quick, and a ticket comes within the hour of a problem.

9. Investigate a host (on demand)

One launch gives the troubleshooting commands, ACT's explanation and every check:




Step	Template	Answers	Link
1	Troubleshoot	`ts_area` = `overview` (or asked at launch), `use_act` = `yes`, `site_act_level` = `explain`	(start)
2	Health check	`health_checks` = `all`	**Run always**, from 1

Give the workflow **Prompt on launch** for **Limit** and launch it with one host. No tickets: you are already looking. Add `[ServiceNow tickets]` after step 2 (**Run always**) if you want them.

10. STIG Manager deploy with checks

The template *STIG Manager - deploy*: playbook `playbooks/stigman_deploy.yml`; the inventory with the group `stigman`; credentials Machine (ssh + sudo), *STIG Manager database*, *TLS certificate* (and *Container registry login (hosts)* when you pull with an account); **Prompt on launch** ticked for **Job type** and **Show changes**, so the workflow can run it as Check, then as Run. Its Variables: `aap/extra_vars/stigman_deploy.yml`.



Step	Template	Answers	Link
1	STIG Manager - deploy	**Job type** `Check` (and **Show changes**)	(start)
2	*Approval*	`Apply the changes the dry run listed?`, **Timeout** 8 hours	**Run on success**, from 1
3	STIG Manager - deploy	**Job type** `Run`	**Run on success**, from 2
4	Service watch - check		**Run always**, from 3
5	Health check	`health_checks` = `certs`, `services`	**Run always**, from 4


The dry run shows which files and units would change, and how. The approver approves only changes they expected. (This dry run has not been tried on a real server yet: run step 1 on its own once, on the test server, before you build the workflow.)

11. Service watch

The approval or self-heal workflow for containers: SERVICE_WATCH_DEMO.md, Part 6.


If you schedule it every 15 minutes, turn **off** "Enable concurrent jobs" on the workflow (edit the workflow), because its approval waits up to 30 minutes: without that, a new run starts every 15 minutes while the last one still waits for a person.

42. Disk space and the tmp cleanup, with an approval



The report never fails (it is a report: filesystems and LVM thin pools at 85% amber, 90% red); its email's last table is what the cleanup deletes after the approval - the old files of `/tmp` and `/var/tmp` on a full filesystem, nothing else. The last step shows the space after it. **Schedule:** every day 06:30, the workflow (or only the report, without the cleanup). Click by click: DISK_SPACE.md.

43. STIG Manager availability, with tickets




Every 5 to 15 minutes (**Concurrent jobs** off). The availability check is quiet while STIG Manager answers and fails when it does not; *Run always*, so a run that finds it back reaches the tickets job too and the incident is resolved. Add *STIG Manager - health* as a daily template of its own (or the same workflow's first node, every morning). For ServiceNow's own availability no ticket (it is ServiceNow that is down): give *ServiceNow - availability* an email **notification on failure** instead. Click by click: STIGMAN_HEALTH.md, AVAILABILITY.md.

Windows workflows

Build them the same way, with the Windows templates (WINDOWS.md). The ServiceNow tickets step is the same template as for Linux: it runs on AAP itself.

12. Windows daily health



Schedule: every day 06:15.


13. Windows weekly compliance



The last step is optional: a CSR for each of the server's own certificates that expires, on its ticket (WINDOWS.md).

Schedule: Mondays 07:15.

14. Windows patch with a dry run first




Step	Template	Answers	Link
1	Windows health check	`health_checks` = `disk`, `services`	(start)
2	Windows patch	**Job type** `Check`	**Run on success**, from 1
3	*Approval*	`Install what Software Center offers (listed in the dry run)?`, **Timeout** 8 hours	**Run on success**, from 2
4	Windows patch	**Job type** `Run`; `automatic_restarts` as you decide	**Run on success**, from 3
5	Windows health check	`health_checks` = `daily`	**Run always**, from 4
6	ServiceNow tickets		**Run always**, from 5

No automatic restarts unless step 4 gets `automatic_restarts` = `yes`: the servers that need a restart are listed, and the post-check's `patching` finding ("a restart is pending") keeps them visible. **Schedule:** inside the servers' ConfigMgr maintenance window. Outside it, ConfigMgr holds the updates and the patch step stops and says so.

15. ACT for Windows rollout


The template *ACT for Windows - install*: playbook `playbooks/win_act_install.yml`; your Windows inventory and its **Machine (Windows)** credential; the execution environment your Windows jobs use; **Prompt on launch** ticked for **Job type** and **Limit** (WINDOWS.md, "ACT on the servers").



Step	Template	Answers	Link
1	ACT for Windows - install	**Job type** `Check`	(start)
2	*Approval*	`Install or update ACT on these servers?`, **Timeout** 8 hours	**Run on success**, from 1
3	ACT for Windows - install	**Job type** Run	**Run on success**, from 2

The dry run lists, per server, whether ACT would be installed, updated, or is already current. Launch the workflow with a Limit (a group; tick **Prompt on launch** for Limit on the workflow too) to roll out group by group. Run it again after every update of this repository.

16. Windows: investigate a server (on demand)




Launch with one server in the Limit.

Linux and Windows together

17. Everything, every morning

One workflow, two independent chains (each first box added with **Add step**). Each step uses its own template's inventory, so leave the workflow's Inventory empty:




Schedule: every day 06:00. It replaces workflows 1 and 12, and the first two steps of 7 (keep 7 for its CSR step).

VMware workflows


The VMware templates run on the AAP side against vCenter: no Limit, and each uses its own template's credentials (VMWARE.md).

18. VMware daily checks: health, alarms, then ACT's analysis (daily)



Always, not On success: a report is red when `vm_health_fail` / `vm_alarm_fail: true` is set, and the next step should run anyway. The health report covers every datacenter, cluster and host (HA, DRS, vCLS, hardware); the alarms report the alarms and the day's events; the analysis ACT's likely cause and fix for each. Each step sends its own email (`report_email_to` on each template, or a workflow survey question `report_email_to` for all). **Schedule:** every day 06:00. Only the analysis is wanted? Schedule `VM - alarms ACT analysis` on its own: its email lists every problem.


19. Snapshot cleanup with approval



Click by click, with the survey and the dry run: VMWARE.md, "Snapshots".

26. Delete picked snapshots, with approval (on demand)


The workflow's survey: tick the snapshots. Its choices come from *VM - refresh the pick lists*, on a schedule every 30 minutes.



The **same** job template twice. Its survey question `vm_snapshot_picks` (Multiple choice, multiple select) is on the **workflow** - inside a workflow only the workflow's survey is asked, and an approval takes no input, so the picking is at launch. The first run plans (it never deletes inside a workflow), the approval reads that plan, the second run deletes exactly what it listed, each snapshot checked again live. Nothing left that can be deleted = the plan step fails and the workflow stops. Click by click: VMWARE.md, "Pick lists".

27. Restart picked (or hung) VMs, with approval (on demand)

The workflow's survey: tick the VMs, and How (guest or hard).



As 26, with `vm_reboot_picks` and `vm_power_mode` (`guest` / `hard`) on the workflow's survey. For a service desk list of **hung** VMs (no heartbeat, or VMware Tools not running): the refresh with `vm_pick_reboot_only_hung: true`, and How = `hard` - a guest restart needs VMware Tools running. Never the AAP server or a protected VM, whatever is picked.

20. ESXi security settings (nightly)

No workflow needed: a schedule on the `ESXi - security settings` template, every day at 00:00 in **your** time zone (VMWARE.md, "ESXi security settings").

22. vSphere capacity planning (weekly)

No workflow needed: a schedule on `VM - capacity planning`, e.g. every Monday at 07:00. One template per cluster (`vm_capacity_clusters`) gives each cluster's owners their own report (VMWARE.md, "Capacity planning").


23. VMs created this week (weekly)

No workflow needed: a schedule on `VM - VMs created report`, every Friday at 12:00 in your time zone (Repeat frequency *Week*, on *Friday*). It reports the VMs created in the 7 days up to the run (VMWARE.md, "VMs created").

25. vCenter and ESXi certificates (weekly)

No workflow needed: the `VMware - certificate renewal` template opens the incidents and attaches the CSRs itself. A schedule on it, e.g. every Monday at 07:00 in your time zone - and, if you want the list by email without tickets, one on `VMware - certificate report` (VMWARE.md, "Certificates of vCenter and the ESXi hosts").

39. vCenter and ESXi certificate install, with an approval



Step	Template	Link
1	VMware - certificate install - check	(start)
2	*Approval*: `Install the VMware certificates the check listed?`, **Timeout** 8 hours. Description: `Open the check job: its READY lines say what each one changes - vCenter's own may restart its services.`	**Run on fail**, from 1
3	VMware - certificate install - approved	**Run on success**, from 2

Survey on the workflow: `Request (RITM) with the issued certificate` -> `vmware_cert_install_ritm` (Text). Launch it with the RITM that *VMware - certificate request* printed, once the PKI has put the certificate on it. **Schedule** (later, when you want it automatic): `vmware_cert_install_search: true` on the check template, the question not required, every day e.g. 07:30 - with the weekly renewal ordering from the catalog (`cert_renew_servicenow: catalog`). The check finds the certificate the PKI put on the request and fails on purpose when one is ready (`NEEDS APPROVAL`); the install puts the hosts' certificates in place (in use, no maintenance mode), then vCenter's own - before vCenter 8.0 Update 2 its services restart, so approve that one when vCenter may be away 10 to 20 minutes. Everything else: VMWARE.md.


21. NetApp ONTAP health (daily)

No workflow needed: a schedule on the `NetApp ONTAP health report` template, e.g. every day at 06:00 in your time zone (NETAPP.md). With `ontap_report_fail: true` the job turns **red** when it finds a problem: put a notification on the template (its **Notifications** tab: on failure) to hear about it. The *ServiceNow tickets* job does not take this report's results - it only works after the checks that hand it findings (JOB_TEMPLATES.md, "What one job hands to the next").

24. Active Directory health (daily)

No workflow needed: a schedule on the `Active Directory health report` template, every day at 06:30 in your time zone, with `ad_report_hours: 24` (the default) so each change is in exactly one report (ACTIVE_DIRECTORY.md). With `ad_report_fail: true` the job turns **red** when it finds a problem: put a notification on the template (its **Notifications** tab: on failure) to hear about it. The *ServiceNow tickets* job does not take this report's results - it only works after the checks that hand it findings (JOB_TEMPLATES.md, "What one job hands to the next").

28. VM outage watch (every 5 to 15 minutes)




Run always, so a clean run reaches the tickets job too and the incident of a condition that cleared is noted (or resolved). **Concurrent jobs** off on the workflow, and `vm_watch_window_minutes` set to the schedule's interval. Click by click: VM_OUTAGE_WATCH.md, "Set it up".

Horizon workflows


The Horizon templates run on the AAP side against a Connection Server: no Limit, the "Horizon API" credential (HORIZON.md).

30. Fix broken desktops, with an approval




The check fails on purpose when there is a desktop to fix (`NEEDS APPROVAL: ...`), and hands the list on. The fix job reads each desktop again and fixes only the approved ones still broken. Click by click, and a rehearsal as Check: HORIZON.md. **Schedule:** e.g. every hour in working hours.

31. Push a new golden image, with an approval



A survey on the workflow (the pools, the golden image VM, its snapshot, the start, the log-off policy). A plan with a problem fails and never reaches the approval (HORIZON.md).

41. ESXi host maintenance, with an approval



A survey on the workflow (the host, the message). Then the host into maintenance in vCenter; after it, *Horizon - host maintenance end* with the host (HORIZON.md).

32. Horizon reports and the session cleanup

No workflow needed: schedules on `Horizon - health report` (every day 06:00), `Horizon - events report` (every day 06:10), `Horizon - capacity report` (every Monday 07:00), `Horizon - settings report` (every Monday 07:10, once its baseline is set), `Horizon - sessions report` (every day 07:30), `Horizon - logon times report` (every day 10:00), `Horizon - FSLogix profiles report` (every Monday 07:20), `Horizon - internal VMs report` (every Monday 07:30) and `Horizon - session cleanup` (every night 02:00, after a first run as Check).

Schedules

What. A schedule launches a template or workflow at set times.

How. Open the workflow (or template) › **Schedules** tab › **Create schedule**:

1. **Name**, **Start date/time**, **Time zone** (use your site's, not UTC, so "06:00" means 06:00).
2. **Repeat frequency** and its details: *Day* (every 1 day), *Week* (on Monday), *Month* (on the second Wednesday)...

3. **Prompts**: the survey answers, the Limit and the Job type **for this schedule**. Without them, the schedule uses the template's **defaults**. A schedule can only change what the template **prompts on launch** or asks in its survey.
4. **Finish**. The schedule's page shows the next run times. Check them once.

What	When	Launches
Daily health (or *Everything, every morning*)	every day 06:00	workflow 1 (or 17)
Certificate watch	every day 06:30	workflow 7
Database watch	hourly	workflow 8
ServiceNow health	hourly	template *ServiceNow health*, with an email **notification on failure**
ServiceNow - availability	every 5 to 15 minutes (**Concurrent jobs** off)	template *ServiceNow - availability*, with an email **notification on failure**
STIG Manager - availability	every 5 to 15 minutes (**Concurrent jobs** off)	workflow 43
STIG Manager - health	every day 06:15	template *STIG Manager - health*
ServiceNow - weekly activity report	weekly: Friday 15:00 (the last 7 days), or Monday 07:00 with `servicenow_war_period: last-week`	template *ServiceNow - weekly activity report* (SERVICENOW_WAR.md)
ServiceNow - ticket insights	monthly: the 1st, 02:00 (the last 6 months), or quarterly with `servicenow_insights_months: 3`	template *ServiceNow - ticket insights* (SERVICENOW_INSIGHTS.md)
Weekly compliance	Monday 07:00	workflow 2
Security posture	Wednesday 07:00	workflow 6
Patch preview	the Monday before patch night	template *Patch hosts*, **Prompts › Job type** `Check`
Patch with checks	monthly, in your window	workflow 3 or 4
Disk space (and the tmp cleanup)	06:30 daily	workflow 42
Service watch	every 15 minutes (with **Enable concurrent jobs** switched off on the workflow)	workflow *Service watch - approve or self-heal*
Windows daily health / weekly compliance	06:15 daily / Monday 07:15	workflows 12 and 13
Windows patch	monthly, in the ConfigMgr maintenance window	workflow 14
VMware daily checks (health, alarms, ACT analysis)	every day 06:00	workflow 18

What	When	Launches
Active Directory health	every day 06:30	template *Active Directory health report* (24)
vCenter and ESXi certificates	Monday 07:00	template *VMware - certificate renewal* (25)
vCenter and ESXi certificate install	on demand (its survey: the RITM); daily 07:30 with `vmware_cert_install_search: true`	workflow 39
Pick lists (the surveys of workflows 26 and 27)	every 30 minutes	template *VM - refresh the pick lists*
Snapshot cleanup	Monday 07:00	workflow 19 (VMWARE.md, "Snapshots")
ESXi security settings	every day 00:00	template *ESXi - security settings* (20)
NetApp ONTAP health	every day 06:00	template *NetApp ONTAP health report* (21)
vSphere capacity planning / VMs created	Monday 07:00 / Friday 12:00	templates (22, 23)
Certificate install	every day 07:00	workflow 29
DoD PKI bundle check (the CA bundle the certificate installs complete a chain from)	Monday 06:00	template *PKI - DoD bundle check* (CERT_INSTALL.md)
fapolicyd	every day 07:00	workflow 36
STIG drift	weekly, e.g. Sunday 02:00, and after patch night	workflow 33
STIG Manager updated from the recheck	on demand, or after patch night	workflow 37
Checklists imported into STIG Manager	on demand, after new checklists are on the share	workflow 40
Network performance	hourly (**Concurrent jobs** off)	workflow 34
Horizon: broken desktops / reports	hourly in working hours / daily	workflows 30 and 32
VM outage watch	every 5 to 15 minutes (**Concurrent jobs** off)	workflow 28
Report website - copy	every 15 minutes	template *Report website - copy* (WEB_REPORTS.md)
VM deploy tickets	every 15 minutes	template *VM - pick up deploy tickets* (VM_DEPLOY_GUIDE.md)
Network config backup	every day	template *Network config backup* (NETWORK_CONFIG.md)

Notifications (optional). **Automation Execution › Administration › Notifiers › Create notifier** (type *Email*, your mail relay). Then on a template or workflow › **Notifications** tab › switch on **Failure**. Use it where a ticket cannot help. ServiceNow health is the main case: if ServiceNow is down, it cannot take a ticket about itself.

Things that trip people up

- **Red is not broken.** A check job with findings is red by design. Read `Report | result for this host`: findings mean the playbook worked.
- **Save the visualizer.** Closing without **Save** loses the graph.
- **One tickets box per check box.** Artifacts from two parents overwrite each other.
- **A step can only be set to Check** (or given a Limit, or survey answers) if its template has **Prompt on launch** for it, or a survey.
- **Schedules use survey defaults** unless the schedule sets its own answers (Prompts step).
- **Approvals need a timeout.** Otherwise a forgotten approval keeps the workflow open forever. After the timeout it counts as denied.
- **Workflow variables override node answers.** Leave the workflow's **Variables** empty, and set answers on each step.
- **Leave the workflow's Inventory empty** unless every step should use it: it only reaches steps whose template prompts for the inventory, and a Linux inventory on a Windows step matches no host.
- **Limit on the workflow** applies to every step whose template prompts for a Limit. The controller-side templates (ServiceNow tickets, ServiceNow health, POA&M status) must **not** prompt for one, or a workflow Limit makes them match no host and silently do nothing.
- **A tickets step fails when nothing reached it.** If the check step died before checking any host (credential, project sync, execution environment), the tickets step fails too, so a broken schedule shows red instead of green. Read the first red job.
- **No automatic restarts** unless a patch step gets `automatic_restarts` = `yes`.

14. Every job template: what it is, and where its how-to is

One line for each playbook in `playbooks/`, under the name the docs give its job template. Each line says what kind of job it is and links to its how-to.

Every template starts the same way: **Project** this repository, the **Playbook**, an **Inventory**, an **Execution environment**, the **Credentials**. Its **Variables** come from its own file in `aap/extra_vars/`: the file's first lines name the template, the playbook and the credentials. Copy the file into the template's Variables box and switch on only what you change (SETUP_AAP.md).

The kinds.

- **Report**: runs, reports, emails and publishes. Its how-to is its settings file; the linked section says what to schedule and what the report shows.
- **On demand**: a person launches it, with a Limit or a survey.
- **Workflow step**: it is one step of a workflow and hands results to the next step (the table What one job hands to the next).
- **After an approval**: the step after an approval. It does exactly what was approved, and nothing when launched on its own.
- **Watch**: on a schedule, often every few minutes.
- **Setup or test**: run once, or after a change, to set something up or to prove a connection.

Linux servers

Job template	Playbook	Kind	How-to
Health check	playbooks/health_check.yml	Workflow step	SETUP_AAP.md, the checks: RUNBOOKS.md, workflows 1-5: WORKFLOWS_AND_SCHEDULES.md
Troubleshoot	playbooks/troubleshoot.yml	On demand	SETUP_AAP.md, workflow 9: WORKFLOWS_AND_SCHEDULES.md
Patch hosts	playbooks/patch_hosts.yml	Workflow step	SETUP_AAP.md, workflows 3 and 4: WORKFLOWS_AND_SCHEDULES.md
Linux - disk space report	playbooks/disk_report.yml	Report	DISK_SPACE.md, workflow 42: WORKFLOWS_AND_SCHEDULES.md
Linux - tmp cleanup	playbooks/tmp_cleanup.yml	After an approval (on its own: Check, then tmp_cleanup_confirm)	DISK_SPACE.md
Apply approved ACT fix	playbooks/act_fix_approved.yml	After an approval	SETUP_AAP.md, workflow 5: WORKFLOWS_AND_SCHEDULES.md
Database health - MariaDB / MySQL	playbooks/database_health.yml	Watch	MARIADB.md, workflow 8: WORKFLOWS_AND_SCHEDULES.md
Service watch - check	playbooks/service_watch.yml	Workflow step	SERVICE_WATCH_DEMO.md, the workflow: Part 6
Service watch - apply approved fix	playbooks/service_fix_approved.yml	After an approval	SERVICE_WATCH_DEMO.md
POA&M status	playbooks/poam_status.yml	Report	SETUP_AAP.md, RUNBOOKS.md
STIG drift report	playbooks/stig_drift_report.yml	Report	STIG_DRIFT.md, workflow 33: WORKFLOWS_AND_SCHEDULES.md
Windows STIG drift report	playbooks/win_stig_drift_report.yml	Report	STIG_DRIFT.md
STIG recheck	playbooks/stig_recheck.yml	Report	STIG_DRIFT.md
Windows STIG recheck	playbooks/win_stig_recheck.yml	Report	STIG_DRIFT.md
Evaluate-STIG - update	playbooks/evaluate_stig_update.yml	Change (Check first)	EVALUATE_STIG_UPDATE.md

Job template	Playbook	Kind	How-to
STIG Manager - update	`playbooks/stigman_update.yml`	Change (STIG Manager's reviews), only as workflow 37's (and 40's) step after the approval	STIG_DRIFT.md
STIG Manager - import checklists	`playbooks/stigman_ckl_import.yml`	Report (reads only); workflow 40's check; on a schedule as STIG Manager Watcher (`stigman_ckl_import_auto`: writes)	CKL_IMPORT.md
STIG Manager - health	`playbooks/stigman_health.yml`	Watch (daily, or after a change)	STIGMAN_HEALTH.md
STIG Manager - availability	`playbooks/stigman_availability.yml`	Watch (every 5 to 15 minutes)	STIGMAN_HEALTH.md, AVAILABILITY.md
STIG Manager - deploy	`playbooks/stigman_deploy.yml`	Setup or test	workflow 10: WORKFLOWS_AND_SCHEDULES.md
Network performance report	`playbooks/net_perf_report.yml`	Report	NETWORK_PERF.md, workflow 34: WORKFLOWS_AND_SCHEDULES.md
Log analysis	`playbooks/log_analysis.yml`	On demand	LOG_ANALYSIS.md
fapolicyd denials	`playbooks/fapolicyd_denials.yml`	Report	RUNBOOKS.md
fapolicyd	`playbooks/fapolicyd.yml`	Report; with approved changes, a change; workflow 36 (as *fapolicyd - check* and *fapolicyd - approved*)	RUNBOOKS.md, WORKFLOWS_AND_SCHEDULES.md

Windows servers

Job template	Playbook	Kind	How-to
Windows connection test	playbooks/win_connection_test.yml	Setup or test	WINDOWS.md
Windows health check	playbooks/win_health_check.yml	Workflow step	WINDOWS.md, workflows 12 and 13: WORKFLOWS_AND_SCHEDULES.md
Windows troubleshoot	playbooks/win_troubleshoot.yml	On demand	WINDOWS.md
Windows patch	playbooks/win_patch.yml	Workflow step	WINDOWS.md, workflow 14: WORKFLOWS_AND_SCHEDULES.md
ACT for Windows - install	playbooks/win_act_install.yml	Setup or test	WINDOWS.md, workflow 15: WORKFLOWS_AND_SCHEDULES.md
Active Directory health report	playbooks/ad_health_report.yml	Report	ACTIVE_DIRECTORY.md
Active Directory - account lockout	playbooks/ad_lockout.yml	On demand	ACTIVE_DIRECTORY.md

Certificates and trust stores

Job template	Playbook	Kind	How-to
Certificate report	playbooks/cert_report.yml	Workflow step	SETUP_AAP.md, workflow 7: WORKFLOWS_AND_SCHEDULES.md
Certificate renewal - CSRs	playbooks/cert_renew_csr.yml	Workflow step	SETUP_AAP.md, RUNBOOKS.md, with the PKI's catalog item: CERT_RENEWAL_CATALOG.md
Certificate install - check	playbooks/cert_install_check.yml	Workflow step	CERT_INSTALL.md, workflow 29: WORKFLOWS_AND_SCHEDULES.md
Certificate install - approved	playbooks/cert_install_approved.yml	After an approval	CERT_INSTALL.md
Certificate restore	playbooks/cert_restore.yml	On demand	CERT_INSTALL.md
Windows certificate report	playbooks/win_cert_report.yml	Workflow step	WINDOWS.md, workflow 13: WORKFLOWS_AND_SCHEDULES.md
Windows certificate renewal - CSRs	playbooks/win_cert_renew_csr.yml	Workflow step	WINDOWS.md
Windows certificate install - check	playbooks/win_cert_install_check.yml	Workflow step	CERT_INSTALL.md
Windows certificate install - approved	playbooks/win_cert_install_approved.yml	After an approval	CERT_INSTALL.md
Windows certificate restore	playbooks/win_cert_restore.yml	On demand	CERT_INSTALL.md
Trust store report	playbooks/trust_report.yml	Report	TRUST_STORES.md
Windows - trust store report	playbooks/win_trust_report.yml	Report	TRUST_STORES.md
VMware - trust store report	playbooks/vmware_trust_report.yml	Report	TRUST_STORES.md
VMware - certificate report	playbooks/vmware_cert_report.yml	Report	VMWARE.md
VMware - certificate renewal	playbooks/vmware_cert_renew.yml	Watch	VMWARE.md
VMware - certificate request	playbooks/vmware_cert_request.yml	On demand	VMWARE.md

Job template	Playbook	Kind	How-to
VMware - certificate install - check	playbooks/vmware_cert_install_check.yml	Workflow step	VMWARE.md, workflow 39: WORKFLOWS_AND_SCHEDULES.md
VMware - certificate install - approved	playbooks/vmware_cert_install_approved.yml	After an approval	VMWARE.md
VMware - version report	playbooks/vmware_version_report.yml	Report	VMWARE.md
VMware - hardware inventory	playbooks/vmware_hardware_report.yml	Report	VMWARE.md
Network device certificate report	playbooks/net_cert_report.yml	Report	NETWORK_CERTS.md
Network device certificate renewal	playbooks/net_cert_renew.yml	Watch	NETWORK_CERTS.md
PKI - DoD bundle check	playbooks/pki_bundle_check.yml	Watch	CERT_INSTALL.md

The certificate inventory for a dashboard (CSV, JSON, SQL Server) is a setting of the certificate reports, not a template of its own: CERT_INVENTORY.md.

VMware (vCenter)

Every VMware template: no Limit, the **VMware vCenter** credential, an execution environment with the VMware collection (VMWARE.md).

Job template	Playbook	Kind	How-to
VM - restart	playbooks/vm_reboot.yml	On demand	VMWARE.md (each template's survey)
VM - shut down	playbooks/vm_shutdown.yml	On demand	VMWARE.md
VM - snapshot	playbooks/vm_snapshot.yml	On demand	VMWARE.md
VM - delete snapshot	playbooks/vm_snapshot_delete.yml	On demand	VMWARE.md
VM - notes	playbooks/vm_notes.yml	On demand	VMWARE.md
VM - change VLAN	playbooks/vm_vlan.yml	On demand	VMWARE.md
VM - secure boot report	playbooks/vm_secure_boot_report.yml	Report	VMWARE.md

Job template	Playbook	Kind	How-to
VM - datastore report	playbooks/vm_datastore_report.yml	Report	VMWARE.md
VM - inventory report	playbooks/vm_inventory_report.yml	Report	VMWARE.md
VM - VMware Tools inventory	playbooks/vm_tools_report.yml	Report	VMWARE.md
VM - right-sizing report	playbooks/vm_rightsizing_report.yml	Report	VMWARE.md
VM - snapshot report	playbooks/vm_snapshot_report.yml	Workflow step	VMWARE.md, workflow 19: WORKFLOWS_AND_SCHEDULES.md
VM - snapshot cleanup	playbooks/vm_snapshot_cleanup.yml	After an approval	VMWARE.md
VM - refresh the pick lists	playbooks/vm_pick_refresh.yml	Watch	VMWARE.md
VM - delete picked snapshots	playbooks/vm_snapshot_delete_picked.yml	Workflow step	VMWARE.md, workflow 26: WORKFLOWS_AND_SCHEDULES.md
VM - restart picked VMs	playbooks/vm_reboot_picked.yml	Workflow step	VMWARE.md, workflow 27: WORKFLOWS_AND_SCHEDULES.md
VM - health report	playbooks/vm_health_report.yml	Report	VMWARE.md, workflow 18: WORKFLOWS_AND_SCHEDULES.md
VM - alarms report	playbooks/vm_alarm_report.yml	Report	VMWARE.md
VM - alarms ACT analysis	playbooks/vm_alarm_act_analysis.yml	Report	VMWARE.md
VM - ask a question	playbooks/vm_ask.yml	On demand	VM_ASK.md
VMware ask - deploy	playbooks/vmware_ask_deploy.yml	Setup or test	VMWARE_ASK.md
VM - outage watch	playbooks/vm_outage_watch.yml	Watch	VM_OUTAGE_WATCH.md, workflow 28: WORKFLOWS_AND_SCHEDULES.md
VM - vCenter log analysis	playbooks/vm_log_analysis.yml	On demand	LOG_ANALYSIS.md
VM - capacity planning	playbooks/vm_capacity_report.yml	Report	VMWARE.md
VM - VMs created report	playbooks/vm_created_report.yml	Report	VMWARE.md

Job template	Playbook	Kind	How-to
ESXi - security settings	playbooks/esxi_security.yml	Watch	VMWARE.md
ESXi - network check	playbooks/esxi_network_check.yml	Report	VMWARE.md
VM - deploy settings finder	playbooks/vm_deploy_inventory.yml	Setup or test	VM_DEPLOY_GUIDE.md
VM - deploy from ServiceNow ticket	playbooks/vm_deploy_from_ticket.yml	Workflow step	VM_DEPLOY_GUIDE.md, the approval workflow: step 8
VM - pick up deploy tickets	playbooks/vm_deploy_poll.yml	Watch	VM_DEPLOY_GUIDE.md

Horizon 8 (VDI)

Every Horizon template: any inventory (the jobs run on the AAP side), the **Horizon API** credential, read only or acting (HORIZON.md).

Job template	Playbook	Kind	How-to
Horizon - API test	playbooks/horizon_api_test.yml	Setup or test	HORIZON.md
Horizon - health report	playbooks/horizon_health_report.yml	Report	HORIZON.md
Horizon - capacity report	playbooks/horizon_capacity_report.yml	Report	HORIZON.md
Horizon - events report	playbooks/horizon_events_report.yml	Report	HORIZON.md
Horizon - settings report	playbooks/horizon_settings_report.yml	Report	HORIZON.md
Horizon - sessions report	playbooks/horizon_sessions_report.yml	Report	HORIZON.md
Horizon - logon times report	playbooks/horizon_logon_report.yml	Report	HORIZON.md
Horizon - FSLogix profiles report	playbooks/horizon_fslogix_report.yml	Report	HORIZON.md
Horizon - internal VMs report	playbooks/horizon_internal_vms_report.yml	Report	HORIZON.md
Horizon - message users	playbooks/horizon_message_users.yml	On demand	HORIZON.md
Horizon - host maintenance plan	playbooks/horizon_host_maintenance_plan.yml	Workflow step	HORIZON.md

Job template	Playbook	Kind	How-to
Horizon - host maintenance start	playbooks/horizon_host_maintenance_start.yml	After an approval	HORIZON.md
Horizon - host maintenance end	playbooks/horizon_host_maintenance_end.yml	On demand	HORIZON.md
Horizon - desktops check	playbooks/horizon_desktops_check.yml	Workflow step	HORIZON.md
Horizon - fix the approved desktops	playbooks/horizon_desktops_fix_approved.yml	After an approval	HORIZON.md
Horizon - golden image check	playbooks/horizon_image_check.yml	Report	HORIZON.md
Horizon - image push plan	playbooks/horizon_image_push_plan.yml	Workflow step	HORIZON.md
Horizon - push the approved image	playbooks/horizon_image_push_approved.yml	After an approval	HORIZON.md
Horizon - user help	playbooks/horizon_user_help.yml	On demand	HORIZON.md
Horizon - session cleanup	playbooks/horizon_session_cleanup.yml	Watch	HORIZON.md

Network devices, mail relays and storage

Job template	Playbook	Kind	How-to
Network config backup	playbooks/net_config_backup.yml	Watch	NETWORK_CONFIG.md
Network config load	playbooks/net_config_load.yml	Workflow step	NETWORK_CONFIG.md
Mail relay - whitelist plan	playbooks/mail_relay_plan.yml	Workflow step	MAIL_RELAY.md, workflow 38: WORKFLOWS_AND_SCHEDULES.md
Mail relay - apply the approved whitelist change	playbooks/mail_relay_approved.yml	After an approval	MAIL_RELAY.md
Mail relay - unused addresses plan	playbooks/mail_relay_unused.yml	Workflow step	MAIL_RELAY.md, workflow 38: WORKFLOWS_AND_SCHEDULES.md
Mail relay - format the whitelist	playbooks/mail_relay_format.yml	On demand (Check first)	MAIL_RELAY.md
NetApp ONTAP health report	playbooks/ontap_health_report.yml	Report	NETAPP.md
NetApp ONTAP hardware inventory	playbooks/ontap_hardware_report.yml	Report	NETAPP.md
Cisco UCS inventory	playbooks/ucs_inventory_report.yml	Report	UCS.md

Tenable.sc (ACAS)

Any inventory with the hosts to scan (they come from `tenable_scan_target`, not the Limit), the **Tenable.sc API** credential (TENABLE.md).

Job template	Playbook	Kind	How-to
Tenable.sc - scan	playbooks/tenable_scan.yml	On demand or scheduled; a change (scans are launched) - a report only until a policy and a repository are set	TENABLE.md

ServiceNow, AAP and the reports

Job template	Playbook	Kind	How-to
ServiceNow - test ticket	`playbooks/servicenow_test_ticket.yml`	Setup or test	SERVICENOW_SETUP.md
ServiceNow - catalog test	`playbooks/servicenow_catalog_test.yml`	Setup or test	CERT_RENEWAL_CATALOG.md
ServiceNow tickets	`playbooks/servicenow_tickets.yml`	Workflow step	SETUP_AAP.md, RUNBOOKS.md
ServiceNow health	`playbooks/servicenow_health.yml`	Watch	SETUP_AAP.md
ServiceNow health - nodes	`playbooks/servicenow_health.yml` (`servicenow_health_part: nodes`; a self-hosted instance)	Watch	SETUP_AAP.md
ServiceNow - availability	`playbooks/servicenow_availability.yml`	Watch (every 5 to 15 minutes)	AVAILABILITY.md
ServiceNow - weekly activity report	`playbooks/servicenow_war.yml`	Report	SERVICENOW_WAR.md
ServiceNow - ticket insights	`playbooks/servicenow_insights.yml`	Report	SERVICENOW_INSIGHTS.md
AAP - report email question	`playbooks/aap_email_question.yml`	Setup or test	EMAIL_REPORTS.md
AAP - set execution environment	`playbooks/aap_ee.yml`	Setup or test	SETUP_AAP.md, EXECUTION_ENVIRONMENT.md
AAP - health check	`playbooks/aap_health_check.yml`	Report	AAP_HEALTH_CHECK.md
AAP - template variables audit	`playbooks/aap_template_audit.yml`	Report	TEMPLATE_AUDIT.md
Report website - copy	`playbooks/report_web_copy.yml`	Watch	WEB_REPORTS.md

Outage documents (AAR and SOP)

Job template	Playbook	Kind	How-to
Outage AAR - Word document	`playbooks/incident_aar.yml`	On demand (a survey)	INCIDENT_DOCS.md
SOP - Word document	`playbooks/incident_sop.yml`	On demand (a survey)	INCIDENT_DOCS.md
AAP - incident document surveys	`playbooks/incident_docs_survey.yml`	Setup or test	INCIDENT_DOCS.md

What one job hands to the next

In a workflow, a job hands its results to the steps after it as **job artifacts** (`set_stats`; on a finished job: **Details** > **Artifacts**). Only these hand-overs exist. Without its hand-over, a job after an approval stops and says why - nothing is changed. The exceptions work on their own too: the snapshot cleanup finds its own candidates, and a pick-list template's first run is its plan (VMWARE.md).

From	Hands over	To	Workflow
Health check, Windows health check, Troubleshoot, Windows troubleshoot, Database health, Certificate report, Windows certificate report, Trust store report, Windows - trust store report, POA&M status, VM - outage watch, STIG drift report, Network performance report	`site_health`, `site_health_targets` (the findings, per host)	ServiceNow tickets	1, 2, 6, 7, 8, 12, 13, 17, 28, 33, 34
Health check or Troubleshoot with ACT (`use_act`, `site_act_level: diagnose`)	`act_triage` (ACT's proposed fix), `site_health`	Apply approved ACT fix	5
Service watch - check	`service_watch_fix`	Service watch - apply approved fix	SERVICE_WATCH_DEMO.md, Part 6
Certificate install - check, Windows certificate install - check	`cert_install_plan`	Certificate install - approved, Windows certificate install - approved	29
Linux - disk space report	`disk_cleanup_plan`, `disk_cleanup_plan_workflow` (only for the cleanup in the same workflow)	Linux - tmp cleanup	42

From	Hands over	To	Workflow
VM - snapshot report	`vm_snapshot_cleanup_candidates` (only for the cleanup in the same workflow)	VM - snapshot cleanup	19
VM - delete picked snapshots (its plan run)	`vm_snapshot_pick_plan`	the same template, after the approval	26
VM - restart picked VMs (its plan run)	`vm_reboot_pick_plan`	the same template, after the approval	27
Horizon - desktops check (`horizon_desktops_mode: approval`)	`horizon_desktops_fix`	Horizon - fix the approved desktops	30
Horizon - image push plan	`horizon_push_plan`	Horizon - push the approved image	31
VM - deploy from ServiceNow ticket (proposal)	not an artifact: the ticket's `[AAP] Checked` work note	the same template, after the approval	VM_DEPLOY_GUIDE.md, step 8
every report job, with `report_web_copy: true`	`site_report_page` (the page, packed)	Report website - copy, read through AAP's API - no workflow	WEB_REPORTS.md

The other reports keep their results as artifacts too (`vm_health`, `ad_health`, `log_analysis`...), for your own use - no step here reads them. They do **not** feed *ServiceNow tickets*: put a notification on failure on those templates instead (the `*_fail: true` settings make them red when they find a problem).

The numbers are the workflows in WORKFLOWS_AND_SCHEDULES.md, with every link and every answer.

15. Dry runs: try anything, change nothing

A **dry run** runs a job without changing anything. Ansible calls it *check mode*; AAP calls it **Job type: Check**. Every step that would change something only says what it *would* change. The steps that only read (the health checks, looking at logs, asking ServiceNow what is open) still run, so the answers are real.

Use a dry run the first time you use any template, on one host, and before every change you are not sure about: patching, applying an approved fix, installing ACT.

Where to set it

There are five places. Pick the one that fits:

Where	How	Good for
1. The template	Template › **Edit** › **Job type** `Check`	a template that is *always* a dry run, e.g. a copy named `Patch hosts (dry run)` that more people may launch
2. At launch	Template › **Edit** › tick **Prompt on launch** next to **Job type**. Then at launch, pick `Check` or `Run`	the usual way: the same template, you choose each time
3. A workflow step	(needs 2 on the template) Workflow › **Visualizer** › click the step › **Edit** (pencil) › **Job type** `Check` › **Save**	rehearsing a whole workflow, or a "dry run first, then real" workflow
4. A schedule	(needs 2) Template or workflow › **Schedules** › the schedule › **Prompts** › **Job type** `Check`	a regular preview, e.g. "what would patch night install" a week before
5. Command line	`ansible-playbook ... --check` (add `--diff` to see file changes)	testing from a shell

Show changes. Tick **Show changes** on the template (or `--diff`) and a dry run also shows the line-by-line changes it would make to files, for example in STIG Manager's configuration.

How to tell. The job's **Details** tab says **Job type: Check**. Our playbooks also print `DRY RUN (Check mode): would ...` where it matters.

What each template does in a dry run

Template	In a dry run it...
Health check, Database health, Troubleshoot, Certificate report	runs **exactly as usual**: they only read, so you get the same findings. Nothing is written: no syslog lines, no disk-forecast sample, and on Windows no event log entries
POA&M status	as usual: reads the CSV and asks STIG Manager
ServiceNow tickets	asks ServiceNow what is already open, then prints `would open: ...`, `would add a note to: ...`, `would resolve: ...`. **Nothing is sent**
ServiceNow health	as usual: only reads
ServiceNow - test ticket	logs in and checks the assignment group and caller (it only reads), then prints the incident it would open, note and resolve. **Nothing is created**
Patch hosts (Linux)	lists the packages dnf would update. Installs nothing, restarts nothing
Apply approved ACT fix	`DRY RUN on <host>: approved, and would run: <commands>`. Runs nothing. A command the apply-time guard would refuse (reboot, `mkfs`, ...) shows `Refused on <host>: ...` and that host goes red, as in the real run
Service watch - check	checks the containers and shows what it would propose. Writes no incident, does not call ACT
Service watch - apply approved fix	`DRY RUN on <host>: approved, and would run: <commands>` (or `Refused on <host>: ...`, as above)
STIG Manager - deploy	says which files and units would change (with Show changes: how), and verifies nothing (nothing was started). Changes nothing. *Not yet tried on a real server: try it once on the test server*
STIG Manager - update	reads each review the plan names, and prints `would write - ...` (or `changed since`, `already so`). **Nothing is written to STIG Manager**
VMware ask - deploy	the same: which files, units and secrets would change, nothing started or verified; STIG Manager's nginx is never changed (VMWARE_ASK.md)
Windows health check, troubleshoot, certificate report, connection test	as usual: they only read
Windows patch	asks Software Center to rescan (without starting anything) and prints `DRY RUN (Check mode): would install <updates>`
ACT for Windows - install	`DRY RUN: would install ACT in C:\ProgramData\act because ...`, or that it is already current

Template	In a dry run it...
VMware jobs (restart, shut down, snapshot, delete snapshot, notes, change VLAN)	finds the VMs and runs every check (the AAP VM is refused as in a real run), then prints `Would restart ...`, `Would take snapshot ...`, `would delete ...`, the notes `AFTER`, `would move ...`. **vCenter is not changed**, and no report email is sent (`DRY RUN: would email ...`)
VM - secure boot report, VM datastore report, VM snapshot report, VM alarms report	as usual: only read. No report email is sent
VM - alarms ACT analysis	reads vCenter and lists the problems it would give ACT (`A dry run (Check): ACT was not called`). ACT is not called, no email is sent
NetApp - ONTAP health report	as usual: it only reads (GET requests), and prints the same report. No email is sent
Horizon - every template	reads as usual and says what it would do: `would recover`, `would log off`, the push it would schedule. Nothing is sent to Horizon but reads - not even a login for an action. No email is sent
VM - capacity planning	as usual: it only reads. With `vm_capacity_act`, ACT is not called (`ACT did not run: A dry run`). No email
VMware - certificate report	as usual: only read (it never talks to ServiceNow). No email is sent
VMware - certificate renewal	reads every certificate and the incidents, then lists what it would do (`would open: ...`, `would make the CSR, and would attach it to INC...`). **No CSR is made** (vCenter and the hosts keep any key waiting), nothing is sent to ServiceNow, no email
ESXi - security settings	reads every host's SSH service, timeouts and lockdown mode and lists what it would change (`ESXi security settings (dry run): 3 of 40 host(s) would change`). **No host is changed**, no email is sent
VM - snapshot cleanup	lists what it would delete (`WOULD DELETE ...`), deletes nothing, sends no email. In the approval workflow: set the cleanup step's Job type to Check (docs/VMWARE.md, "Dry run")

ACT does not run in a dry run. It would call the model, and ACT could change things. A dry run with `use_act` = `yes` reports the checks and says ACT gave no result. To see ACT's ideas without changes, do a *real* run with `site_act_level` = `diagnose`: ACT then only reads and proposes (ADDING_ACT.md).

Examples

Before patching one server. Launch **Patch hosts** › **Job type** `Check`, **Limit** `web01`. The output lists every package that would be updated. Nothing is installed.

```
TASK [patch : Patch | what was updated (dry run - what WOULD be updated)]
ok: [web01] => {"msg": "DRY RUN (Check mode), nothing was installed - would make 4 change(s):
  Installed: expat-2.5.0-6.el9_8.5.x86_64; Installed: libxml2-2.9.13-14.el9_8.5.x86_64;
  Removed: libxml2-2.9.13-14.el9_8.4.x86_64; Removed: expat-2.5.0-6.el9_8.3.x86_64"}
```

(`Removed` is the old version that the new one replaces.)

Before patch night, every month. On **Patch hosts** add a schedule for the Monday before patch night, with **Prompts** › **Job type** `Check`. The job output shows what patch night will install on every host, in time to exclude something.

A dry-run copy for the team. Template **Patch hosts** › **…** › **Copy**. Rename the copy `Patch hosts (dry run)`, set **Job type** `Check`, untick **Prompt on launch** for it, and give your team **Execute** on the copy only. They can preview; only you can patch.

Which tickets would a run open? In the *Daily health* workflow click the **ServiceNow tickets** step › **Edit** › **Job type** `Check`. Run the workflow: the tickets job prints what it would open, note and resolve. Set it back to `Run` when the tickets look right.

A Windows server, before its first real patch. Launch **Windows patch** › **Job type** `Check`, **Limit** one server:

```
"DRY RUN (Check mode): would install 2026-09 Cumulative Update (KB5040001); Malicious Software
  Removal Tool (KB890830)"
```

The approve-and-fix path, end to end. See WORKFLOWS_AND_SCHEDULES.md, "Fix with approval (ACT)": set the apply step to `Check`, run the workflow, approve. The apply job shows what it would run.

From a shell (on a machine with Ansible and this repository):

```shell
ansible-playbook -i <inventory> playbooks/patch_hosts.yml --check --diff -l web01
ansible-playbook -i <windows inventory> playbooks/win_patch.yml --check -l web01
```

What a dry run cannot tell you

- Whether the updates will **install cleanly**, or how long they take: it only lists them.
- Whether a **restart** would succeed: nothing restarts in a dry run.
- Anything that **depends on an earlier change**. In a dry-run workflow the post-check after "patching" still sees the unpatched host, because nothing was patched.
- What **ACT** would say (see above).

16. The runbooks: every check and what to do

For each runbook: what it answers, its settings (defaults in `roles/<role>/defaults/main.yml`; change them in your settings files or AAP's Variables boxes, as VARIABLES.md shows), and each finding with what usually fixes it. The `look:` command printed with a finding is always the first thing to run.

Health check (playbooks/health_check.yml)

Runs the checks you pick on each host: a list of names, or the shortcuts:

- `daily` = disk, mounts, services, performance, time, network, logging, mariadb (the database check: MariaDB or MySQL; `mysql` and `database` also pick it), containers (podman containers, rootful and rootless), sso (can domain users still log in)
- `weekly` = selinux, fapolicyd, auditd, accounts, certs, trust, patching
- `all` = both

A host with a finding at a severity in `site_fail_on` (default: critical and warning) fails. That is what a workflow reacts to. A template that only emails its report to people: `site_fail_on: []` keeps the job green (EMAIL_REPORTS.md). A check that itself breaks becomes a warning finding (`the X check could not run: ...`, id `<check>:check-error`) and the other checks still run. That finding fails the host even when `site_fail_on` is `[critical]` (a check that did not run is not a healthy result); only `site_fail_on: []` never fails. Its ServiceNow incidents from earlier runs stay open: a check that did not run to its end clears nothing it found before (no "passes again" note, nothing resolved).

A host that cannot be reached (switched off, no network, ssh or WinRM refused, its login refused) does not fail the job. It is listed as `NOT REACHED - <why>` and left out; the other hosts are checked as usual. It still counts as checked-for, so the ServiceNow step opens its "no result" ticket. The same goes for the certificate report and renewal, database health, the service watch and troubleshoot, Linux and Windows. Two cases still fail the job:

- **no host at all is reached**: that is what a wrong or expired machine credential looks like;
- `site_unreachable_fails: true`: a host not reached fails the job, as before.

The ACT and service fixes, the STIG Manager deploy and the Windows connection test always fail for a host they cannot reach: a workflow must not go on as if it had been fixed. *Patch hosts* leaves a host it cannot reach **when it starts** out and patches the others (`patch_skip_unreachable`, below). A host lost later in a job (it went down halfway) still fails it.

All settings of this job, with their defaults: site_findings.

disk

Finding	Means	Usually
`/var is 96% full`	local filesystem space (`check_disk_warn_pct` 85, `check_disk_crit_pct` 95)	find what grew with the `look:` command: old logs, core dumps, a runaway log file. `journalctl --vacuum-size=500M` for the journal
`... has used 97% of its inodes`	too many small files (space may still be free)	usually a directory with millions of small files (session/cache/spool); `look:` finds it
`/var will be full in about 3.2 days`	growth-rate forecast from earlier runs (needs a day of history)	same as above, before it becomes an outage
`could not read filesystem usage`	`df` failed or timed out	a hung mount; see the mounts check
`LVM thin pool rhel/pool data is 92% full`	a thin pool's data (or metadata) is filling: full, every volume in it stops (`check_disk_lvm`)	`lvextend -L +10G rhel/pool` from the volume group's free space (`vgs`); metadata: `lvextend --poolmetadatasize +1G rhel/pool`
`LVM snapshot rhel/snap ... is 88% full` / `filled up and is no longer valid`	an old-style snapshot is filling / has filled up and is lost	grow it (`lvextend -L +5G rhel/snap`) or remove it once it is not needed (`lvremove rhel/snap`)

Per-mount limits: `check_disk_overrides: {/var/log/audit: {warn: 70, crit: 85}}`. A report of every full filesystem across the hosts that never fails, and the tmp cleanup: DISK_SPACE.md. The forecast keeps a small history in `/var/lib/site-health/disk-history.json` (the only file the checks write; a Check-mode run does not write it).

All settings of this check, with their defaults: check_disk.

mounts

Finding	Means	Usually
`/data (xfs) is in /etc/fstab but is not mounted`	it did not mount at boot, or was unmounted	`journalctl -b` for the mount error; a missing disk or LUN; a typo in fstab
`/var is mounted READ-ONLY`	the kernel remounted it read-only after disk/filesystem errors	**urgent**: `journalctl -k` for I/O errors; storage team; plan an fsck
`network mount /mnt/share does not answer within 5s`	NFS/CIFS server down, network, or a stale handle	check the server and the network; diagnose only (NetApp is vendor-managed)
`network mount ... is 96% full`	the share is full	the storage owner

All settings of this check, with their defaults: check_mounts.

services

Finding	Means	Usually
`systemd unit X has FAILED`	a unit crashed or exited with an error	`systemctl status X`, `journalctl -u X`; fix the cause, then `systemctl restart X`
`required service X is inactive`	a service that must run (`check_services_required` + `_extra`) is stopped	same; find out why it stopped before starting it
`required service X is not installed`	the unit does not exist here	remove it from the list for this group, or install it
`required service X is disabled`	it will not start after a reboot	`systemctl enable X`
`X has restarted 5 times`	a restart loop: it keeps crashing	its log shows the crash

Per group: `check_services_required_extra: [mariadb]`. To ignore a failed unit: `check_services_ignore_failed: ['^dnf-makecache']`.

All settings of this check, with their defaults: check_services.

performance

Finding	Means	Usually
`15-minute load is 14.2 on 4 CPUs (3.55 per CPU)`	more work than CPUs, for 15 minutes	the top CPU processes are in the finding; a runaway job, or undersized
`only 4% of memory is available`	memory is nearly exhausted	the top memory processes are in the finding; a leak, or undersized
`63% of swap is in use`	the host is short of memory	as above
`CPUs spend 35% of their time waiting for disk`	slow or overloaded storage	`iostat -x` shows which device; storage latency
`the hypervisor takes 15% of CPU time (steal)`	the VM host is overcommitted	the virtualization team
`the kernel killed processes for lack of memory`	OOM kills in the last 24 h (with the victims)	the victim's memory limit, or the host's memory
`27 zombie processes`	a parent process is not reaping its children	restart the parent (`look:` shows it)

All settings of this check, with their defaults: check_performance.

time

Finding	Means	Usually
`the clock is NOT synchronized`	chrony uses no time source	`chronyc sources -v`: unreachable servers, firewall (UDP 123)
`chrony is installed but not answering`	chronyd is not running	`systemctl start chronyd`
`the clock is 2.4s ahead of NTP time`	offset above `check_time_offset_warn`	chrony corrects it slowly; very large offsets break Kerberos/AD logins at 5 minutes

All settings of this check, with their defaults: check_time.

network

Finding	Means	Usually
`there is no default route`	the host cannot reach other networks	NetworkManager connection, gateway
`this host's own name ... does not resolve`	its FQDN is not in DNS or /etc/hosts	DNS record
`ldap.example.mil does not resolve (DNS)`	a name in `check_network_dns_names` fails	`/etc/resolv.conf`, DNS server
`LDAP (ldap.example.mil:636) does not answer within 5s`	a TCP port in `check_network_tcp` is unreachable **from this host**	firewall (local or network), the service down, routing

All settings of this check, with their defaults: check_network.

logging

Finding	Means	Usually
`the journal is kept in memory only`	`/var/log/journal` missing: logs vanish at reboot	`mkdir /var/log/journal && systemctl restart systemd-journald` (or `Storage=persistent`)
`log server SIEM (...) does not answer`	forwarding target unreachable	network/firewall; the SIEM collector
`rsyslog has 850 MB of undelivered messages queued`	the log server has been unreachable for a while	as above; the queue drains once it answers
`1203 error messages in the journal`	something complains a lot (top senders listed)	look at the top sender first

All settings of this check, with their defaults: check_logging.

sso

What it means: can domain users still log in? A Linux host joined to Active Directory or IdM (sssd, realmd, or winbind for Samba) keeps letting users in from its cache for a while after it loses the domain - then logins fail, often at night. Hosts joined to no domain are skipped.

Finding	Severity	What it says	Look / fix
`sso:sssd-down`, `sso:winbind-down`	critical	configured but not running	`systemctl status sssd`; `journalctl -u sssd -n 50`; `sssctl config-check`
`sso:offline:<domain>`	critical	sssd reaches none of the domain's servers now	`sssctl domain-status <domain>`; `sssctl domain-status -s <domain>` (the servers it found); DNS SRV records, the firewall to 389/636/88
`sso:keytab`	critical	the host's keytab gets no Kerberos ticket: the computer account was reset, deleted or disabled, or its password changed elsewhere	`klist -k /etc/krb5.keytab`; re-join (`realm leave`, `realm join`)
`sso:testjoin:<domain>`	critical	`adcli testjoin` fails	`adcli testjoin -D <domain> -v`; the computer object in AD
`sso:user:<user>`	critical	a user in `check_sso_test_users` does not resolve	`getent passwd <user>`; `sssctl user-checks <user>`
`sso:went-offline`	warning	sssd went offline `check_sso_offline_warn` times in `check_sso_hours` (online now)	`journalctl -u sssd --since -24h | grep -i offline`: the servers or the network flap
`sso:kdc`	warning	no KDC (domain controller) could be reached, `check_sso_kdc_warn` times	DNS `_kerberos._tcp` SRV records; the `time` check (clock skew breaks Kerberos)

The keytab test asks a KDC for a ticket with the host's own key into a memory cache: nothing is written, no login session is made (`check_sso_keytab_test: false` turns it off). Windows servers: the broken trust with the domain is `network:secure-channel` (the Windows network check).

selinux

Finding	Means	Usually
`SELinux is Permissive, it must be enforcing`	not enforcing (STIG)	`setenforce 1` after checking denials; `SELINUX=enforcing` in `/etc/selinux/config`
`/etc/selinux/config says SELINUX=permissive`	a reboot would change the mode	fix the config file
`locally added permissive domain(s)`	SELinux only logs for those domains	`semanage permissive -d <domain>` once the policy is right
`12 SELinux denial(s) since yesterday - top: nginx (httpd_t) denied read on a file labeled user_home_t`	SELinux blocked something	a wrong label (fix: `restorecon -Rv <path>`), a boolean (`setsebool -P ...`), or a real policy need. `audit2why` says which
`SELinux boolean X is off, expected on`	a boolean in `check_selinux_booleans` differs	`setsebool -P X on`
`N file(s) under /etc/nginx have the wrong SELinux label`	a dry-run `restorecon` would relabel them (`check_selinux_relabel_paths`)	`restorecon -Rv <path>`

All settings of this check, with their defaults: check_selinux.

fapolicyd

Finding	Means	Usually
`fapolicyd is inactive`	application allow-listing is off	`systemctl start fapolicyd`; its log says why it stopped - the fapolicyd job finds why and fixes it after approval
`fapolicyd is in permissive mode`	it logs but blocks nothing	`permissive = 0` in `/etc/fapolicyd/fapolicyd.conf`
`N file(s) no longer match the fapolicyd trust database`	files changed outside RPM	`fapolicyd-cli --update`, or re-add the file's trust entry
`N fapolicyd denial(s) since yesterday - top: /usr/bin/bash -> /opt/app/tool`	it blocked programs	a legitimate program needs a trust entry (`fapolicyd-cli --file add <path>`), after review

`check_fapolicyd_required: true` (the example inventory sets it) makes a missing fapolicyd a finding. What the denials were and what to do about them, with ACT's analysis, in a report of their own: fapolicyd denials.

All settings of this check, with their defaults: check_fapolicyd.

auditd

Finding	Means	Usually
`auditd is failed`	nothing is being audited	`systemctl status auditd`; often a full audit log partition
`auditing is DISABLED in the kernel`	`auditctl -s` says enabled 0	`audit=1` on the kernel command line
`only 1 audit rule(s) are loaded`	the STIG rules are missing or failed to load	`augenrules --check`, `augenrules --load`; a syntax error in `/etc/audit/rules.d/`
`N audit event(s) were LOST`	the kernel backlog overflowed	raise `-b` (backlog) in the rules
`the audit log filesystem is 92% full`	auditd may stop, or halt the host, when it fills	rotate/offload; check `space_left_action`
`audit records are not forwarded`	au-remote is not active (`check_auditd_remote_required`)	configure audisp-remote
`audit volume is 850 MB a day (... events in 24 h, at most N in one hour) - mostly account svc_x (60%), rule key delete (55%), program /usr/bin/python3 (40%)`	more audit records than `check_auditd_volume_warn_mb_day` (200), excluded accounts not counted	what the named account/program does that the named STIG rule records: a job deleting temp files in a loop, an app in a rootless container (its processes keep the user's login ID)
`the audit logs on disk reach back only 9.5 h (5 files of 8 MB, then the oldest is deleted)`	with `max_log_file_action = ROTATE` older records are gone (`check_auditd_retention_warn_hours` 24)	bigger `max_log_file` / more `num_logs` in `/etc/audit/auditd.conf`, or fewer records (the finding names who makes them)
`auditd dropped records N time(s) ... on the way to its plugins`	the queue to au-remote / the SIEM forwarder was full: the SIEM copy is missing records	fewer records; a larger `q_depth` in `auditd.conf`
`audit rule(s) stop recording auid=1234 (someone) altogether`	a `-a never` (or `-a always,exclude`) rule hides an account that is not in `check_auditd_exclude_accounts`	remove the rule, or approve the account (below)
`too much to break down by account within 120 s`	very large logs	`aureport` with the `look:` command, or a larger `check_auditd_volume_timeout`

How much is audited, and the vulnerability scanner. The volume, retention and rule findings come from the audit logs themselves. The breakdown (which account, which STIG rule key, which program) is read only when the volume or the retention is over its limit, at low priority, and is always printed in the job output (`Auditd | how much is audited`), with excluded accounts shown separately.

A credentialed vulnerability scan logs in to every host and runs thousands of commands with sudo: during a scan its account usually makes most of the audit records. List it in `check_auditd_exclude_accounts` (in `playbooks/group_vars/all.yml`, so it applies to every host) and it no longer counts toward the volume warning. It still counts for retention and disk space, which are physical: if the scan rotates a week of records

away in an hour, that is still reported, with the scanner named as the cause. The job output shows how much of the scanner's volume comes from syscall rules and how much from sudo/PAM records, which tells you what an audit rule exclusion would remove.

To stop auditd recording that account at all (a host change, not part of the health check):

- It is a deliberate exception to the STIG audit requirements: get it approved and recorded first.
- The rules `-a never,exit -F arch=b64 -S all -F auid=<UID>` and the same with `arch=b32` (the form of audit's own sample rules), placed before the STIG rules, remove the syscall records: a file like `/etc/audit/rules.d/05-exclude-scanner.rules` (`augenrules` merges the files in name order). The sudo/PAM records (USER_CMD, USER_START, CRED_*) come from user space and need `-a never,user -F auid=<UID>`. Leaving that one out keeps the sudo records, which still show what the account ran.
- Use the numeric UID. A name is looked up when the rules load at boot, before IdM/AD (sssd) can answer, and a rule that fails to load can stop the rest of the rules from loading.
- STIG hosts make the rules immutable (`-e 2`): a new rule takes effect only at the next reboot.
- The auditd check then reports rules like this only for accounts that are NOT on `check_auditd_exclude_accounts`.

All settings of this check, with their defaults: check_auditd.

accounts

Finding	Means	Usually
`account(s) other than root have UID 0`	full root power under another name	**investigate first**; remove or renumber the account
`account(s) with an EMPTY password`	log in without a password	`passwd -l <user>`
`3 account(s) not used for 35+ days`	inactive and not locked (STIG)	lock them (`usermod -L`), or list break-glass accounts in `check_accounts_ignore_inactive`
`sudo without a password (NOPASSWD) for: alice`	a sudoers entry skips the password	remove it, or allow it on purpose in `check_accounts_nopasswd_allowed` (e.g. `svc_aap`)
`the password of svc_aap expires in 6 days`	an account in `check_accounts_expiry_watch` expires soon	**change it before it breaks automation** (and update the Machine credential)

All settings of this check, with their defaults: check_accounts.

certs

Finding	Means	Usually
`certificate CN=... in /etc/stigman/stigman.crt expires in 9 days`	a certificate file expires within `check_certs_crit_days` (critical) / `warn_days` (warning)	renew it. For STIG Manager: update the *TLS certificate* credential and run *STIG Manager - deploy*; it restarts only nginx
`... in STIG Manager (https://127.0.0.1:443) expires in ...`	the certificate a TLS endpoint serves	the service's certificate, even if the file on disk was already replaced (restart the service)
`... in /opt/.../agent_keystore (alias mid) expires in ...`	a Java keystore entry	renew in the keystore (MID Server: ServiceNow's procedure)
`could not check the certificate in X`	unreadable file, endpoint not answering, or a PKCS12 keystore without its password	fix the path, or add the Keystore password credential
a certificate file is not in the report at all	its folder is not searched (a home folder, an application's own folder), or it is a bundle of more than 10 certificates (listed under *Found but not checked*)	add the folder to `check_certs_discover_extra_dirs` (two levels deep: `[/home, /root]` finds `/home/you/x.crt`), or the file to `check_certs_files`

What it looks at: `check_certs_files` (globs), the usual directories (`check_certs_discover_dirs`, plus your own in `check_certs_discover_extra_dirs`; skipping CA bundles), `check_certs_endpoints`, `check_certs_keystores`. Text (PEM) and binary (DER) certificate files both, the names in any case (`.crt`, `.CRT`, `.pem`, `.cer`, `.der`). For a PKCS12 keystore, name the variable that holds the password (`password_env: KEYSTORE_PASSWORD`), never the password.

All settings of this check, with their defaults: check_certs.

trust

Which trust stores on the host still hold a certificate authority that was compromised or that the browsers dropped - the list ships with the check (October 2026: the eight eMudhra intermediates and their roots; yours in `check_trust_extra`) - and the software that carries its own trust logic. Every certificate is matched by its fingerprint and by its public key. TRUST_STORES.md.

Finding	Means	Usually
`the system trust (tls-ca-bundle.pem and 1 more, ca-certificates ...) trusts emSign ECC Root CA - G3 - ...`	the system bundles still hold a dropped root: every OpenSSL / Go / Python / curl client on the host accepts the compromised chains	update `ca-certificates`; or blocklist it (a copy in `/etc/pki/ca-trust/source/blocklist/`, `update-ca-trust`)
`... trusts EM DV TLS CA - G3B - its private key is computable from the certificate ...` (**critical**)	a compromised intermediate itself is in a store or an application's bundle	take it out; find out who put it there
`2 Python certifi bundles (...) trusts ...`	requests / pip carry their own roots, per environment	`pip install -U 'certifi>=2026.10.19'` in each environment the finding lists

Finding	Means	Usually
`/usr/lib/jvm/.../cacerts 17.0.9 (Java cacerts) trusts ...`	a JDK's own trust store	update the JDK, or `keytool -delete`; a `cacerts` linked to `/etc/pki/java/cacerts` follows the system trust
`/usr/bin/node (built-in roots) 22.23.1 ... trusts ...`, `Node.js 22.23.1 is below 22.23.4`	Node carries its own roots	update Node, or start it with `--use-openssl-ca`
`container web (root) ... trusts ...`	the image's own bundle	pull or rebuild the image, restart the container
`3 Go programs built with a Go before the fix: ...`	a Go program verifies certificates itself; 1.27.3 / 1.26.10 reject the compromised keys	rebuild each with a fixed Go, or get the vendor's build
`NSS 3.126.0 is below 3.131.1`	the roots NSS carries (Firefox, NSS clients without p11-kit)	update `nss`
`no system CA bundle was read on this host`	none of `check_trust_bundles` exists here	name the host's bundle in `check_trust_bundles`

A certificate that is in the blocklist is *blocked*: no finding. *AAA Certificate Services* (Sectigo's root that cross-signed the compromised intermediates) is a **notice** by default - in the report, no finding - because nearly everything chains to it; `check_trust_severity: {"AAA Certificate Services": warning}` once you decide to blocklist it. The **Trust store report** (below) shows every store read on every host, and vCenter and ESXi.

All settings of this check, with their defaults: check_trust.

patching

Finding	Means	Usually
`12 security advisories pending, 2 of them rated Critical`	updates that fix security issues are waiting	patch (the *Patch with checks* workflow)
`a reboot is needed to finish earlier updates`	new kernel or core libraries are not in use yet	reboot in a window
`no package has been updated for 60 days`	older than `check_patching_max_age_days`	patch
`cannot check for updates`	dnf cannot reach its repositories (Satellite, mirror)	repository configuration, network, subscription

All settings of this check, with their defaults: check_patching.

mariadb and mysql (health only): the database check

Checks **MariaDB and MySQL** (5.7, 8.0, 8.4; MariaDB 10.x and 11.x; Percona). Pick it in the Health check as `mariadb`, `mysql` or `database` (the same check), or run it alone with the **Database health - MariaDB / MySQL** template (`playbooks/database_health.yml`: only this check, on every database server it is pointed at; it fails a host that has findings, so a workflow can open a ticket). In the Health check it runs on hosts in `mariadb_hosts`, `mysql_hosts`, `database_hosts`, `mariadb` or `mysql`, and on any host that has a container name set. It runs status queries only: no data is read and nothing is changed. It handles a database installed on the host and one in **podman containers** (one, several, found automatically, or rootless): the client inside each container is used. **How to set it up, step by step, and how to verify it: MARIADB.md.**

Finding	Means	Usually
`MariaDB is not running`	the service or container is down	its log; disk full; a crash
`MariaDB is running but the status query failed`	cannot log in, or it hangs	the login (see below); `max_connections` reached
`MariaDB refused the login of U (the MariaDB monitor credential) in container X: Access denied ...` (or `in 2 containers (X, Y)`)	the credential's password is not the one U has there: each container has its own root password	the finding's *How to look*: the container's root password, the login by hand, one monitor account for every container (see below)
`MariaDB restarted 12 minutes ago`	a restart nobody may have planned	the error log: crash, OOM kill
`143 of 151 connections in use (95%)`	clients are about to be refused	the `look:` query shows which user and client hold them; a connection leak in an app
`N client connection(s) were REFUSED`	`max_connections` was reached since the last start	as above; raise `max_connections` only if the load is real
`40 queries are executing at this moment`	a pile-up: locking or one slow query	`look:` lists the oldest
`2 query/queries running longer than 300s`	long-running queries (user / db / seconds / state; never the query text)	the owner decides; `KILL <id>` only after that
`replication (default) is broken: IO thread No`	a replica stopped copying	`Last_IO_Error` / `Last_SQL_Error` in the finding
`replica ... is 1900 seconds behind`	replication lag	load on the replica; long transactions on the primary
`Galera node is not healthy` / `cluster has 2 node(s), expected 3`	Galera cluster trouble	the node's error log; network between nodes

Finding	Means	Usually
`MySQL Group Replication is not healthy` / `has 2 ONLINE member(s), expected 3`	a Group Replication member is not ONLINE, or the group is short (`check_mariadb_group_size`)	`SELECT ... FROM performance_schema.replication_group_members` (in the finding); the member's error log
`could not read the replication status` / `... Group Replication members`	the monitoring account lacks a privilege	the grant named in the finding (MARIADB.md)
`only 91% of reads come from memory`	`innodb_buffer_pool_size` may be too small	the DBA
`3 [ERROR] line(s) in the MariaDB log`	errors in its log in the last day (latest shown)	read them
`the MariaDB data directory is on a filesystem 93% full`	MariaDB stops writing when it fills	disk space

Performance (all warnings; `check_mariadb_performance: false` turns them off). Counters that count since the server started are judged as an average since then, and only after it has run `check_mariadb_perf_min_uptime_hours` (2): cold caches right after a start are normal. Old transactions, lock waits, purge lag and open files are judged as they are now. The job's status line prints the numbers either way: `performance since start, 6 days: 100 queries/s, 3 slow/h, 4% temporary tables on disk, ...`.

Finding	Means	Usually
`mariadb:slow-queries: 504 slow queries per hour ...`	queries slower than `long_query_time`, on average since the start	the slow query log (the finding says whether it is on) or `performance_schema` (the `look:` query lists the costliest statements) shows which; an index or a rewrite
`mariadb:tmp-disk: 60% of the temporary tables ... went to disk`	sorts and GROUP BYs spill to disk	`tmp_table_size` and `max_heap_table_size` (the smaller one counts); TEXT/BLOB columns always spill
`mariadb:full-joins: 1,440 joins per hour ... read a whole table`	joins with no usable index	the DBA adds the index; they get slower as the tables grow
`mariadb:table-locks`	MyISAM / Aria tables locked as a whole are busy	convert them to InnoDB (the `look:` query lists them)
`mariadb:row-locks: queries waited on average 2,000 ms for a row ...`	transactions wait for each other's row locks	long transactions, or many writers on the same rows
`mariadb:deadlocks`	InnoDB rolled back one transaction of each deadlock	the application's order of updates; `SHOW ENGINE INNODB STATUS` shows the latest

Finding	Means	Usually
`mariadb:lock-waits`: `waiting for a lock for 30 s or longer right now ...`	sessions blocked NOW (metadata, table or row locks; who / db / seconds / state, never the query)	the session holding the lock: usually an open transaction or an `ALTER TABLE`. The owner decides before any `KILL`
`mariadb:long-transactions`: `2 transaction(s) open longer than 600 s ...`	transactions left open hold their locks and stop purge; `idle (Sleep)` = the application never committed	the application owner; a connection pool that does not commit
`mariadb:purge-lag`: `2,500,000 old row versions wait to be purged`	InnoDB history list length: reads slow down, undo grows	the long transaction above
`mariadb:open-files`	close to `open_files_limit`	raise `open_files_limit` (and the unit's `LimitNOFILE`)
`mariadb:table-cache`	the table cache is full and tables are reopened all the time	`table_open_cache`
`mariadb:bufferpool-wait`, `mariadb:log-waits`	InnoDB waited for a free buffer pool page / a full log buffer	`innodb_buffer_pool_size` / `innodb_log_buffer_size`
`mariadb:aborted-connects`	many failed connection attempts per hour	wrong passwords, a health probe that does not log in, or a scan

The performance query reads `information_schema.INNODB_TRX` (needs `PROCESS`, which the monitoring account already has) and `INNODB_METRICS`; without the privilege those findings are simply not made, the rest still are.

Logging in (the full steps are in MARIADB.md). Without a credential, the check logs in as root through the local socket. That is MariaDB's default for a host install on RHEL (no password needed with sudo); MySQL's root usually has a password. **A database in a container usually gives root a password** (the official images do), and the check then reports `Access denied ... attach the "MariaDB monitor" credential`. **Each container has its own root password** (set when it was created, in its environment: `podman inspect <container> | grep -i ROOT_PASSWORD`), so a credential with root's password logs in to one container and is refused by the others: `MariaDB refused the login of root (the MariaDB monitor credential) in 2 containers (db1, db2): Access denied ... - most likely its password is wrong for these containers` - one critical finding for the host, naming every container that refused it, with how to look one command per line. The fix is one monitoring account with the same password in every container (below), or `check_mariadb_containers` to read only the ones the credential may log in to. For containers, or whenever you prefer not to use root, ask the DBA to create a monitoring account with **no data access**, inside that database with host `localhost`, and attach the *MariaDB monitor* credential to the Health check template:

SQL

```
CREATE USER 'aap_monitor'@'localhost' IDENTIFIED BY '<password>';
GRANT PROCESS, REPLICATION CLIENT ON *.* TO 'aap_monitor'@'localhost';   -- MySQL; MariaDB before
  10.5.9
GRANT PROCESS, REPLICA MONITOR ON *.* TO 'aap_monitor'@'localhost';      -- MariaDB 10.5.9 and
  newer instead
GRANT SELECT ON performance_schema.* TO 'aap_monitor'@'localhost';       -- MySQL Group
  Replication only
```

`PROCESS` shows other sessions (for long queries). Replication status needs `REPLICATION CLIENT` (MySQL) or, on MariaDB 10.5.9 and newer, `REPLICA MONITOR`: `REPLICATION CLIENT` **alone is not enough there.** The password reaches the client only through its environment, never its command line.

All settings of this check, with their defaults: check_mariadb.

containers: podman containers, root's and every user's

Finds the podman containers on the host by itself - you list nothing - and checks each one. Hosts without podman are skipped (`skipped: podman is not installed`, no finding). It is read-only: it runs `podman ps`, one `podman container inspect` and `systemctl show`, and nothing that starts, stops or creates anything.

Which containers. Root's (rootful podman) and each user's (rootless podman: only that user can see them). A user is looked at when a podman process runs as them, when they have *linger* on (a file in `/var/lib/systemd/linger/`), or when they are in `/etc/subuid` and have container storage in their home (`~/.local/share/containers/storage`). A user's containers are read **as that user** (`runuser -u USER -- env XDG_RUNTIME_DIR=/run/user/UID podman ...`), and only when `/run/user/UID` exists: otherwise podman would create it, and a check must not change anything. Such a user is listed as `not checked` instead (and reported, below).

User namespaces off (a STIG setting). With `user.max_user_namespaces = 0` no user can run podman at all (`podman ps` as a user fails with `cannot clone ... user namespaces are not enabled in /proc/sys/user/max_user_namespaces`). The check reads that setting first: at 0 it does not try any user, reads only root's containers, and says so in one line, `INFO: rootless podman is off on this host (user.max_user_namespaces = 0): only root's containers read` - no finding. Only a user you named in `podman_discover_users` gets one warning, naming the setting. A user's `podman ps` that fails with `user namespaces are not enabled` is taken the same way (no `could not be read` warning).

Which should be running. A container should be running when a systemd unit runs it and starts it at boot (a Quadlet `.container` file with an `[Install]` section, or an enabled unit from `podman generate systemd` or written by hand), or when its restart policy is `always` or `unless-stopped`. A container that has neither and stopped with exit code 0 was stopped on purpose: no finding. A Quadlet or `--new` unit removes its container while the unit is stopped, so the check also reads the Quadlet files and unit files: a container that should run but does not exist at all is found too (state `missing`).

Pods and compose projects too. Some units start several containers whose names the unit does not say: a Quadlet `.kube` file or a `podman-kube@` unit (`podman kube play` of Kubernetes YAML), a unit that runs `podman pod start`, `podman-compose` / `podman compose` / `docker-compose`, or `podman run` without `--name`. Each such unit is a row of its own (the name of the unit, kind `pod`, `compose project` ...), and it is down when its unit is not active. A `Type=oneshot` unit that finished successfully since boot (`podman-compose up -d`) counts as up: its containers run on without it. Root's units are read from `podman_discover_unit_dirs` (`/etc/systemd/system`, `/usr/local/lib/systemd/system`), a user's from `~/.config/systemd/user`. Podman's own tools (`podman-auto-update`, `podman-restart`, the API service) are left out. The containers of a running pod are listed as containers when they carry the unit's label (Quadlet sets it).

The output has a table of what was found:

```
OWNER        NAME                       STATE             UNIT                            SHOULD
  RUN
root         systemd-db                 running           db.service (active)             yes
root         web                        running           -                               yes
alice        web                        missing           web.service (failed)            yes
bob          web                        exited (3)        -                               no
not checked: carol - no /run/user/1003 (the user is not logged in and linger is off): ...
```

Every finding names the owner, and its `look:` command runs as that owner (paste it as root):

Finding	Means	Usually
`container X (owner O) should be running (...) but it does not exist / it exited with code N` (critical)	a container that should run is down, or its systemd unit failed	read the `look:` output (the unit's status, the container's log, the journal). Start it the right way: `systemctl start UNIT` for a unit (as a user: `runuser -u O -- env XDG_RUNTIME_DIR=/run/user/UID systemctl --user start UNIT`), `podman start X` for a plain container. Service watch does this for you, with approval
`required container X ... does not exist` / `is not running` (critical)	a container in `check_containers_required` is missing or stopped	create or start it; fix its name in the setting
`container X (owner O) is running but its healthcheck reports unhealthy` (critical)	its own healthcheck fails	`podman inspect X` shows the last healthcheck output (`State.Health.Log`); the container's log
`container X (owner O) stopped with an error: it exited with code N, 2.5 hours ago` (warning)	a container that is not meant to run all the time stopped with an error in the last `check_containers_recent_hours` (24) hours	its log. Older crashes are not reported
`container X (owner O) has restarted N times - a restart loop` (warning)	more restarts than `check_containers_restart_warn` (3), counted by podman or by its systemd unit	its log shows why it keeps stopping
`container X (owner O) was killed by the out-of-memory killer` (warning)	the kernel killed it for memory	more memory on the host, or a higher memory limit on the container
`user U (uid N) has containers that should run (...) but linger is off` (warning)	the user's containers stop when they log out and do not start at boot	`loginctl enable-linger U` (as root)

Finding	Means	Usually
`user U (uid N) has podman containers ... and N unit(s) that should start at boot, but they could not be checked: no /run/user/N` (warning)	the user has units that should start at boot (a Quadlet with `[Install]`, an enabled unit) but is not logged in and has no linger: none of their containers run now. A user with only container storage (an admin who once ran podman) is listed under `not checked:` and gets no finding	if they should run: `loginctl enable-linger U`. If not, leave them out: `podman_discover_ignore: ['U/.*']`
`the containers of O could not be read: podman ps failed ...` (warning)	podman (or systemctl) failed for that owner: a blind spot	run the `look:` command to see the error (storage problems, `podman system migrate` needed after an upgrade ...)
`podman_discover_users names U, but rootless podman is off on this host (user.max_user_namespaces = 0, a STIG setting ...)` (warning)	you asked for U's containers, but no user can run podman on this host	run U's containers as root, or take U out of `podman_discover_users`. The other users get no finding: `INFO: rootless podman is off on this host`

Settings (roles `podman_discover` and `check_containers`; VARIABLES_REFERENCE.md):

Setting	Default	What it does
`podman_discover_enabled`	`true`	`false` = do not look for containers (the check says `skipped`)
`podman_discover_rootless`	`true`	also look at users' containers
`podman_discover_users`	`[]`	more users to look at, e.g. `[appsvc]` when the rules above miss one
`podman_discover_unit_dirs`	`[/etc/systemd/system, /usr/local/lib/systemd/system]`	where root's own units that run podman are looked for (a user's: `~/.config/systemd/user`)
`podman_discover_ignore`	`[]`	containers to leave out: regular expressions that must match the **whole** name or `OWNER/NAME`, e.g. `['test-.*', 'alice/.*', 'root/scratch']`
`check_containers_required`	`[]`	containers that must exist and run: a name (any owner) or `OWNER/NAME`, e.g. `[stigman-api, alice/web]`
`check_containers_recent_hours`	`24`	how recent a crash must be to be reported

Setting	Default	What it does
`check_containers_restart_warn`	`3`	restarts above this = a restart loop

To verify it on one host: run the Health check with `health_checks: containers` and a Limit of that host; compare the table with `sudo podman ps -a` and, for a user, `sudo runuser -u alice -- env XDG_RUNTIME_DIR=/run/user/$(id -u alice) podman ps -a`. Service watch uses the same way of finding containers (SERVICE_WATCH_DEMO.md).

All settings of this check, with their defaults: check_containers, podman_discover.

containers, database, service watch: which one does what

Three jobs look at podman containers. They find the containers the same way (`roles/podman_discover`), but each answers a different question:

	containers (Health check)	mariadb (Health check, or *Database health* alone)	Service watch
Asks	is every container alive and stable?	is the database *inside* working, and fast?	something is down: why, and what fixes it
Looks at	every container, pod and compose project (`podman ps -a`, Quadlet files, systemd units): down, unhealthy, crashed, restart loops, OOM kills, linger	connections, long queries, replication, Galera / Group Replication, its log, its disk, and performance (slow queries, lock waits, open transactions ...)	the containers that should run: down or unhealthy
Then	a finding (a ticket)	a finding (a ticket)	ACT's root cause and a recommended fix, which waits for approval (`watch_mode: approval`, the default)
Run it	daily, every host	daily with the Health check; hourly alone for the database team	from its AAP workflow, when you want a diagnosis and a fix to approve (on demand, or on a schedule for the hosts that matter)

One outage, one finding. When a database container is down and both checks run in the same Health check, the outage is reported once: as `containers:down` (or `:unhealthy`), whose summary then says *it is a MariaDB/MySQL database container, so the database is down too (mariadb:down is not reported separately)*. The containers check has the better finding for that: how the container is run and how to start it. The database check still reports `mariadb:down` when the containers check does not (it is not running in the same job, or it does not report that container - one that has no unit and no restart policy, so nothing says it should run), and the *Database health* template always reports it.

The same goes for the **services** check: root's systemd unit that runs a container (or a pod) that is down is reported by the containers check, and the services check's `unit-failed:UNIT` (or `unit-down` / `unit-flapping`) for that unit is left out and named in that finding (*the services check sees its systemd unit web.service fail too (unit-failed:web.service is not reported separately)*). A failed unit that runs no container stays the services check's.

Service watch and the Health check can both see the same container down: the watch acts on it (within minutes), the Health check records it (once a day). On hosts where Service watch runs, a daily `containers:down` for a watched container usually means the watch could not bring it back.

Troubleshoot (playbooks/troubleshoot.yml)

For "something is wrong on this host": pick the area and the job runs the commands an experienced admin runs first. Each is printed under a line saying what it shows, and the matching health checks run too. Read-only. Findings do not fail this job: you asked for a look, not a verdict.

Area	Commands (what they show)	Checks
overview	uptime, failed units, disk, memory, recent errors, recent reboots	disk, mounts, services, performance, time, logging
disk	space and inodes, biggest directories on the fullest filesystem, deleted-but-open files, files over 1 GiB, journal size	disk, mounts
performance	load, top, vmstat, memory users, disk latency (iostat), load history (sar), OOM kills	performance
service (`ts_service`)	its status, why it stopped (result, exit code, restarts), its log, dependencies, unit file, listening ports	services (plus that unit)
network (`ts_target` host:port)	addresses, routes, DNS servers, name lookup, TCP connect, route taken, firewall, connection counts	network (plus that target)
selinux	mode, today's denials, audit2why, changed booleans, local file labels	selinux
fapolicyd	status, today's denials, rules, enforcing?	fapolicyd
login	sshd log, faillock lockouts, failed logins, SSSD domain status, authselect, clock offset	accounts
time	chrony tracking and sources, timedatectl, configured servers	time
logs	errors, top error senders, rsyslog and its queue, journal size	logging
mariadb (or mysql)	(the MariaDB / MySQL health check)	mariadb

Add `use_act=true` and ACT reads everything collected and explains the root cause (ADDING_ACT.md).

All settings of this job, with their defaults: troubleshoot.

fapolicyd denials (playbooks/fapolicyd_denials.yml)

What fapolicyd blocked, and what to do about it: each host's denials from the audit log, ACT's analysis of them, and one report of every host - emailed (`report_email_to`) and on the report website, as every report job. ACT only reads: the job collects the evidence (the denials, the rules, and for each denied file its package, hash, trust entry and SELinux label) and ACT explains it. It runs nothing on the host. It is ACT's own playbook (`vendor/act/ansible/playbooks/fapolicyd_denials.yml`, which posts a Teams card when the Teams webhook credential is attached), then the report.

The template: Playbook `playbooks/fapolicyd_denials.yml`; your Linux inventory; credentials **Machine** and **ACT model key** (ADDING_ACT.md), and the Teams webhook one if you want the card too. Variables: `target` (the group; or a Limit of hosts - no `localhost` needed) and, optional, `fapolicyd_since: yesterday` (an `ausearch -ts` keyword: `recent` = 10 minutes, `today` the default, `yesterday`, `this-week`, `boot`). A daily schedule just after midnight with `yesterday` reads the whole day before. A template that runs `vendor/act/ansible/playbooks/fapolicyd_denials.yml` itself posts to Teams only and sends no email: change its Playbook to this one.

The report shows	Means	Do
a host with denials, ACT's analysis and `ACT proposes (for your security approval): fapolicyd-cli --file add ...`	fapolicyd blocked a program; ACT says whether it looks legitimate and the narrowest trust entry or rule	review it with your ISSO - a trust entry or a rule is a security-control change - then apply it by hand
`fapolicyd not running` (red)	application allow-listing is off	the fapolicyd job: why, and the fix to approve
`auditd` not active	denials are not recorded: the job sees none	`systemctl start auditd`
No denials while things are blocked	the deny rules do not audit (`deny` or `deny_syslog` instead of `deny_audit`)	`deny_audit` in the rules (the RHEL default rules use it)
Not read	the host could not be reached	as for any job: the inventory, the credential

ACT runs only on a host with denials or a problem; the others cost no model call. A host whose ACT status is in `fapolicyd_fail_on` (`[error]`: ACT could not answer) fails after the report; `[]` never fails one. The health check's `fapolicyd` check (above) counts the denials without ACT.

ACT uses the provider and model of every ACT job (`site_act_provider`, `site_act_models`, `site_act_model` - ADDING_ACT.md). Before 0.45.5 this job passed neither: ACT used its own default model (`gemini-3.1-pro-preview`), or the one in root's `~/.config/act/config.json` on a host where someone set up ACT by hand, and a model your team has no access to fails with *HTTP 403: Your team does not have access to this model*. A template whose Playbook is `vendor/act/ansible/playbooks/fapolicyd_denials.yml` still has that problem: change it to `playbooks/fapolicyd_denials.yml`.

fapolicyd (playbooks/fapolicyd.yml)

fapolicyd in one pass on each host, one report, one list of changes to approve - and, every morning, workflow 36: the check, an approval step in AAP, the changes made. It reads (a Check run too), proposes one line per change, and makes only the lines approved.

What it looks at, in this order:

1. **What keeps fapolicyd down.**
   - Trust files it cannot read: `fapolicyd.trust`, `trust.d` and each file in it, against the owner, group and mode the fapolicyd package gives its own (`root:fapolicyd`, `0644`, folders `0750`). `fapolicyd-cli --file add` under a STIG umask of 077 leaves `root:root 0600`.
   - SELinux labels not the policy's (`restorecon -n`).
   - `db_max_size` too small: fapolicyd's own journal lines, or - while it is down - an estimate from the trust files and the RPM files. `auto` where fapolicyd 1.4+ sizes its database itself (RHEL 9), else a number (RHEL 8). The new value is checked with `fapolicyd-cli --check-config` before any restart.
   - Not enabled at boot: `enable fapolicyd at boot (it is disabled)`.
   - Not running: `permissive: 0 -> 1` and `restart fapolicyd (it is ...)` - it starts **blocking nothing**, logging what it would block.
2. **What it blocked - or, permissive, would block** (since `fapolicyd_since`).
   - A file on the host: `trust file: <file> size <n> sha256 <hash>` - that file as it is now, added to `trust.d/site-approved`, set to the package's `root:fapolicyd 0644`. A changed file is a new line.
   - A container's file - a container's SELinux label, a container program (`crun`, `conmon`, `podman` ...), a path in container storage, or a process in a podman container's cgroup: `allow rule: ...` into `rules.d/36-site-approved.rules`
   - that program and that file for a file bind-mounted from the host, container storage's folder (`allow perm=any all : dir=/var/lib/containers/storage/overlay/`) for a file inside an image, whose path in the audit log names nothing on the host. That rule lets anything in container storage run: prefer rootful containers (quadlet units) on a STIG host.
   - **A podman host, before anything is blocked:** a host whose podman storage has images - root's (`/var/lib/containers/storage`, or `graphroot` in `/etc/containers/storage.conf`), or a user's own (`~/.local/share/containers/storage`, or `rootless_storage_path`) - gets that same `allow rule: allow perm=any all : dir=<storage>/overlay/` as a line to approve, so the containers keep running when fapolicyd starts enforcing. Not offered when a rules file already has it. A user's own storage says so in the line: anything they put there may then run. `podman` in `fapolicyd_rules_offer` (on by default; take it out to wait for a block, as before).
   - What a person had to do by hand before 0.52.0 is now a line to approve too:
   - `trust update: <file> size <n> sha256 <hash>`: a trusted file that changed since. Its entry in the trust file that holds it (the vendor's too) gets the file's size and hash as they are now.
   - `reload trust database (fapolicyd-cli --update)`: a file trusted as it is (or an RPM file that still matches its package) that fapolicyd has not loaded.
   - `reinstall package: <name-version> (<file> does not match it)`: an RPM file `rpm -V` says changed. The package is reinstalled at the same version (`dnf reinstall`), checked with `rpm -V` after. A reinstall is not put back if fapolicyd fails later: it only restores the package's own files.
   - A file over `fapolicyd_rules_hash_max_mb` (512 MB), up to `fapolicyd_rules_large_mb` (4096): a `trust file:` line like any other, marked *a large file* in the report.
   - `fapolicyd_rules_offer` turns each of these off (`[]`: all for a person, as before).

- Still for a person: a file in a folder users can write (move it to a system folder first, and the next run offers its trust entry), a file too large even so, one whose path a trust line cannot hold, rules in fapolicyd's own files.

3. **The rules files' clean-up** - `remove rule: <file>: <rule>` (commented out, marked, never deleted) and `rename rules file: <a> -> <b>`:
   - no change in what runs: a repeated rule, a wildcard (`dir=/home/*/bin/` - fapolicyd has none, it matches nothing), a rule for an RPM-owned file;
   - **blocks more** - a rule that allows everything, or a system folder (`/usr/lib/`) or user folder opened to any program; a renamed file that holds deny rules: made **only while fapolicyd is permissive** (or `fapolicyd_rules_when_enforcing: true`), and never beside `permissive: 1 -> 0`;
   - lets more through: a file that sorts after `41-shared-obj.rules`, renamed `39-...`.

fapolicyd's own files and `35-site-containers.rules` are reviewed, never changed.

4. **Back to enforcing:** `permissive: 1 -> 0`, on a quiet day.

After the changes, fapolicyd is restarted, or its rules (`fagenrules --load`) or trust (`fapolicyd-cli --update`) reloaded, and checked in the same go on the host - once it says it took them (*Ruleset identity*, *Updated*), running, and a program (python) starting twice. **Running before and not after - or a program no longer starts: everything put back** (owner, mode, label, fapolicyd.conf, the rules and trust files) and fapolicyd restarted. Down before and still down: the fixes stay, its journal in the report, the host fails after the report. When getting fapolicyd running fails on a host (put back, still down, refused), the trust and rules changes approved for it wait - they come again once it runs. Then `compiled.rules` is checked against the rules files (`fagenrules --check`).

ACT (`fapolicyd_act: true`, the *ACT model key* credential): ACT explains what fapolicyd blocked, in the report, by its own headings - evidence only, it runs nothing. The **fapolicyd denials** job (above) remains for that alone.

The templates: see workflow 36 - *fapolicyd - check* and *fapolicyd - approved*, both `playbooks/fapolicyd.yml`, your Linux inventory, the *Machine* credential (sudo). By hand, without the workflow: one template of the same playbook, **Check** on launch, the approved lines in `fapolicyd_approved` exactly as the report gives them, a Check run, then for real. A line is made only on a host where this run proposes it again; a line the job never gives (or one copied with a host name after it) changes nothing anywhere.

Bringing a host back without an outage: the workflow does it by itself, one morning at a time - the first approval gets fapolicyd running permissive (its trust files, `db_max_size`, enabled, started); the next ones let through what it would block and clean up the rules; on the first quiet day it offers `permissive: 1 -> 0`. A RHEL STIG requires `permissive = 0`: the report shows a permissive host in red. The audit log must keep a day (`ls -l /var/log/audit/`; `num_logs`, `max_log_file` in `/etc/audit/auditd.conf`).

The report shows	Means	Do
Would be blocked (permissive)	fapolicyd let it through and logged it	approve its change before enforcing
rolled back (red)	fapolicyd failed after the change, or a program no longer started: all put back	its journal in the report
still down (red)	it was down, the fixes are made, it still does not start	its journal; the next cause

The report shows	Means	Do
refused	a line the job never gives, `auto` where fapolicyd cannot, or a change that blocks more while enforcing	correct the line, or approve permissive first
Approved, made on no host	made already, outside the Limit, a file that changed since, or not the report's exact line	nothing - or copy the line again
a rule's number without its text	the rules changed since that block	read the rule from the time of the block

All settings, with their defaults: fapolicyd, and the advanced ones of its two parts, fapolicyd_fix and fapolicyd_rules.

Certificate report (playbooks/cert_report.yml)

The certs check on every host, and **one table**, soonest expiry first: days left, date, host, subject, and where the certificate is. Hand it to whoever renews certificates. It fails the hosts with a certificate inside `check_certs_warn_days`, so a workflow can open tickets (`site_fail_on: []` keeps it green: a report only).

Emailed with `report_email_to` (Linux and Windows: `win_cert_report.yml`). In the email the table is coloured: **red** = expired, **amber** = expires within `check_certs_warn_days` (30), **blue** = within `check_certs_notice_days` (60), the rest plain with a green "ok". Windows: `win_check_certs_warn_days` / `win_check_certs_notice_days`.

Found by itself (the report only; `cert_report_discover: false` turns it off):

- **TLS ports:** every listening TCP port is asked once for its certificate, on the address it listens on, with a 3-second limit (`check_certs_probe_timeout`), at most 25 ports (`check_certs_discover_ports_max`). Ports that are plain text are never touched (`check_certs_discover_ports_skip`: 22, 25, 53, 80, 389, 3306, 5432 ...), nor the ones you listed in `check_certs_endpoints`. Shown as `TLS port 8443, java (https://127.0.0.1:8443)`.
- **Java keystores:** `*.jks`, `*.keystore`, `*.p12`, `*.pfx` in `check_certs_discover_keystore_dirs` (`/etc`, `/opt`, `/srv`, Tomcat's folders), and the ones running Java programs use (`-Djavax.net.ssl.keyStore=...`). A JKS is read without its password; a PKCS12 that needs one is listed under **Found but not checked** - no password is ever guessed. To check it, add it to `check_certs_keystores` with `password_env` and a *Keystore password* credential. The JDK's own trust stores (`cacerts`) are skipped.
- **The trust store:** every file in `check_certs_trust_dirs` (`/etc/pki/ca-trust/source/anchors`, where `update-ca-trust` takes the CA certificates the host trusts, such as the DoD roots), whatever its name, text or binary. Shown as `/etc/pki/ca-trust/source/anchors/DoD_Root_CA_3.crt (trust store)`, with its date and colour, but **never a finding, a ticket or a CSR**. A certificate there is not this host's own: its CA renews it. When it does, put the CA's new certificate in that folder and run `update-ca-trust`. The system bundle `update-ca-trust` builds from it (`/etc/pki/tls/certs/ca-bundle.crt`) is never read: it holds hundreds of public roots.
- **Bundles:** a found file with more than 10 certificates (`check_certs_discover_max_per_file`) is listed under **Found but not checked**, with how many. To check each certificate in it, add it to `check_certs_files`.

Windows (`win_cert_report.yml`): every machine store is read, not only Personal, Web Hosting and Remote Desktop: Trusted Root, Intermediate Certification Authorities, Other People, ... (where *Automatically select the certificate store* puts a `.cer` file). A certificate there with its private key is checked like the others; one

without is listed as `... (trust store)` when it expires within `win_check_certs_notice_days`, never a finding or a ticket (`win_check_certs_trust`, details in WINDOWS.md). Remote Desktop's certificates are left out of the report and the renewal (Windows renews them): `win_check_certs_remote_desktop: true` puts them in.

The weekly health check (`certs` in `health_checks`) does not search by itself, so it opens no tickets for certificates nobody listed; set `check_certs_discover_ports` / `_keystores: true` on it when you want that.

Placeholders: postfix makes its own certificate when it is installed, `/etc/pki/tls/certs/postfix.pem` (subject `O=SomeOrganization, OU=SomeOrganizationalUnit, C=--`), self-signed for one year and never renewed. On every host with postfix it expires a year after the install. A found one is listed under **Found but not checked** (one row for all the hosts) and is never a finding, a ticket or a CSR, in the report and in the health check (`check_certs_placeholder_subject`). A real certificate put in its place (a host that relays mail) has a real subject, so it is checked and renewed. A ticket already open for a placeholder gets the usual "passes again" note on the next run (resolved with `servicenow_resolve_cleared`).

Left out: hosts whose certificates something else renews, such as Satellite and its Capsules (`satellite-installer`, never by hand). They are listed under **Found but not checked** and get no ticket. Name them in either setting, or both; each takes a list or one string with commas:

Setting	Leaves out	Example
`cert_skip_hosts`	hosts by name, as in the AAP inventory: any case, `*` and `?` wildcards, a short name matches the full one	`[sat01, '*capsule*']` or `sat01, *capsule*`
`cert_skip_groups`	every host in these AAP inventory groups (default `[sat]`)	`[sat, appliances]`

Set them in the template's Variables, or in `all.yml` so the report and the renewal both get them. The health check still checks these hosts (with `[sat]`: the Satellite web UI's certificate, `playbooks/group_vars/sat.yml`).

Reported, but renewed by hand - IdM, AAP, any server whose certificates are put in place by its own tool: name it in `cert_renew_skip_hosts` (or its group in `cert_renew_skip_groups`), not in `cert_skip_hosts`. It stays in the report, and the Certificate watch still opens its tickets, each one saying *Renewed by hand: this host is named in cert_renew_skip_hosts (idm01) - the certificate renewal job makes no CSR for it*. The renewal lists its certificates with that reason and makes no key, no CSR. The same forms: a list or one string with commas, any case, `*` and `?`, short names.

Trust store report (playbooks/trust_report.yml)

The trust check on every Linux host, and **one table** of every trust store and program read - the system bundles, p11-kit, Java cacerts, Python certifi, Node, podman containers, an application's own files, Go programs - with what each holds, worst first: the proof of what was looked at, and the checklist of what to update. Read-only - with `check_trust_remove: true` it takes the listed certificates out (the system trust blocklisted, Java entries deleted, certifi and application bundles cut, every file backed up first; Check mode shows the plan) and reads the hosts again. Fails the hosts that (still) hold a compromised or dropped CA, so a workflow can open tickets. Emailed (`report_email_to`). Weekly, and on demand when a CA incident is announced (add its certificates to `check_trust_extra`). TRUST_STORES.md.

Windows trust store report (playbooks/win_trust_report.yml)

The Windows servers' certificate stores (Trusted Root, Intermediate CAs, the roots Windows Update keeps, Trusted Publishers, the connecting account's), every Java `cacerts` and Python `certifi` bundle, against the same list as the Linux report; the same tables, worst first, emailed. A certificate in the Disallowed store is blocked. `check_trust_remove: true` puts the certificate in the Disallowed store (Windows' blocklist, it wins over every other store) and deletes it from the store it was in, deletes Java entries, cuts certifi bundles, backups first; Check mode shows what would go. The Windows health check's `weekly` set runs the check `trust` too. TRUST_STORES.md.

VMware trust store report (playbooks/vmware_trust_report.yml)

vCenter's trusted root store and each ESXi host's trusted CA certificates, against the same list, from the controller with a *VMware vCenter* credential (no inventory; `vmware_vcenters` for several). One table, worst first, emailed as the other VMware reports; the job fails when vCenter or a host holds a listed certificate. `vmware_trust_esxi: false` reads vCenter only. `check_trust_remove: true` deletes the chain from vCenter's trusted roots and replaces each host's trusted CA list without it (Check mode shows what would go; the account needs *Certificate Management* > *Manage*). TRUST_STORES.md.

Certificate renewal: the CSRs (playbooks/cert_renew_csr.yml)

For every certificate the certificate report flags (it expires in 30 days or less, `check_certs_warn_days`, or has expired), the job makes a new private key and a certificate signing request (CSR) on the host: a certificate in a file (text or binary), one served on a port, one in a keystore. It attaches the CSR to the certificate's ServiceNow incident. The renewal sends no email: the CSR goes on the ticket (ServiceNow's own notifications tell its assignment group). Making a CSR changes nothing in use: the old certificate works until it expires.

No incidents, the PKI's catalog item instead: with `cert_renew_servicenow: catalog` each CSR is ordered from your PKI's catalog item (one request per certificate, the CSR in its CSR question): CERT_RENEWAL_CATALOG.md. It applies to the Windows, VMware and network device renewals too. vCenter's and the ESXi hosts' certificates have a job of their own, which opens the incidents and makes the CSRs on vCenter and the hosts: `VMware - certificate renewal` - and a report of them alone, `VMware - certificate report` (VMWARE.md, "Certificates of vCenter and the ESXi hosts"). The three use the same window: the report flags, the CSR is made and the incident is opened at 30 days. Change it on the workflow (`check_certs_warn_days`) and all three follow. The PKI person submits the CSR and attaches the issued certificate to the same ticket. This job changes nothing a service uses. With the catalog item, the issued certificate is then installed from its request after an approval - *Certificate install*, Linux and Windows (CERT_INSTALL.md), vCenter and ESXi (VMWARE.md); the PKI may send only the .cer when you keep the DoD PKI's CA bundle (`cert_install_ca_bundle`). With incidents, a person installs it.

Per certificate:

1. It reads the certificate: the subject and the names (subjectAltName: DNS, IP, email, URI) - from its file (a binary, DER, file too), from the port that serves it, or from its keystore entry (the entry with a key; a keystore password from `check_certs_keystores`).
2. It makes a new key on the host and a CSR with exactly the same subject and names, signed with `cert_renew_digest` (sha256).
   - RSA keys are at least `cert_renew_key_bits` (2048); a bigger old key keeps its size.
   - An EC certificate gets a new key on the same curve.

- It uses the `openssl` command, so it works on RHEL 8 (OpenSSL 1.1.1) and RHEL 9 (3.x), in FIPS mode.

3. It checks the CSR before keeping it: the CSR verifies, its key is the new key, and its subject and names are exactly the old certificate's. If not, it keeps nothing and says "make this CSR by hand".
4. It keeps the files in `cert_renew_dir` (`/etc/pki/tls/renew`, made 0700):
   - `<name>-<8 characters>.key` (0600);
   - the `.csr`;
   - a `.json` with where it came from, the old serial and expiry, and the AAP job.

The key never leaves the host and never appears in the job output.

5. It finds the certificate's open incident, or opens one. The incident is the one *Certificate watch* opened, found by the same correlation ID (workflow 7). It attaches the CSR (`<common name>-<8 characters>.csr`) and adds a work note: the certificate, where it is, who issued it, the names, where the new key is, and the next steps. Every CSR gets a ticket, whatever `servicenow_min_severity` says: critical (14 days or less, `check_certs_crit_days`, or expired) or warning (15 to 30 days).

Run again:

- The pending key and CSR are reused, so the CSR the PKI already has stays valid.
- A CSR already on its ticket is not attached again. A daily run adds nothing until the certificate changes.
- Once the new certificate is installed, the old one is no longer flagged.
- The folder keeps its files until you remove them.

One certificate in several places (its file, a chain file, served on a port) gets one CSR, and the work note lists every place. The watch opens a ticket for each place; the CSR goes on one of them, and each of the others gets a work note saying which ticket has the CSR.

Where the issued certificate goes - step 3 of the next steps on the ticket:

The certificate is	Step 3 says
in a file	install it with the new key in place of the file
in a binary (DER) file	the same, converted first: `openssl x509 -in <issued> -outform DER -out <file>`
in a Java keystore or a PKCS12 file	the commands that put the new key and the issued certificate in the keystore, under the same alias, after a copy of the keystore (`cp -p <keystore> <keystore>.bak`, `openssl pkcs12 -export`, `keytool -importkeystore`)
served on a port, its file not found	find where that service keeps its certificate and key, and replace both

A certificate served on a port is matched to its file when the file is in `check_certs_files` or in one of the folders the report searches (`check_certs_discover_dirs`, two levels deep: `/etc/pki/tls/certs`, `/etc/pki/nginx`, `/etc/nginx`, `/etc/httpd/conf.d`, `/etc/stigman`, and `/etc/stigman/nginx/tls` where *STIG Manager - deploy* puts nginx's certificate, plus `check_certs_discover_extra_dirs`). Its file not found, it gets its CSR from the port, and the ticket says to find the file. Add the file to `check_certs_files` and the next CSR names it. Certificates of services that renew their own (AAP's internal CA, for one) are left out by their issuer: `cert_renew_exclude_issuer`. To see what the job would do with a certificate that is not expiring yet, run it with **Check**, a **Limit** of that host and `check_certs_warn_days: 400`: it says "would make the CSR" or why not, and changes nothing.

Step 3 of the next steps says to install the issued certificate in place of the file. When something else deploys that file, a copy by hand is overwritten, so `cert_renew_install_notes` writes another step 3 for paths that start with a given folder. The default covers STIG Manager (`/etc/stigman/`): put the issued certificate and the new key in the AAP credential *TLS certificate*, then run *STIG Manager - deploy*. Add your own: `{'/opt/app/certs/': 'App: ...'}`.

Never renewed here (each listed in the job output with the reason):

What	Why
a host in `cert_skip_hosts` or `cert_skip_groups` (`[sat]`)	Satellite renews its own certificates with `satellite-installer`; left out of the certificate report too
a host in `cert_renew_skip_hosts` or `cert_renew_skip_groups`	renewed by hand (IdM, AAP ...): still in the certificate report, and its tickets say no CSR comes from here
a file found only in `check_certs_discover_extra_dirs` (`/home`, `/root` ...), unless `cert_renew_extra_dirs: true`	those folders are searched so the report shows what is there (a test certificate, a copy someone left); a CSR for each would only add work. A file there that is also under `check_certs_discover_dirs`, or listed in `check_certs_files`, is renewed
a path matching `cert_renew_exclude`	something else renews it: Satellite and Capsule (katello, foreman, candlepin, pulp, puppet), and subscription-manager on every registered host (`/etc/rhsm`, `/etc/pki/consumer`, `entitlement`, `product`). Check the report's *Where* column and add your own paths
issued by a CA matching `cert_renew_exclude_issuer` (`O=Katello`, `Puppet CA`)	Satellite's or Puppet's own CA
a CA certificate in a chain file	a CA has no CSR from you: put the CA's new certificate in the chain file
a self-signed certificate (unless `cert_renew_self_signed: true`)	it does not come from a PKI. With the setting on, it gets a CSR, so the PKI issues a real certificate in its place (a STIG wants PKI certificates); `cert_renew_issuer` does not apply to it
a CA's own certificate (a root: key usage *Certificate Sign*)	a CA has no CSR from you, even with `cert_renew_self_signed`
a self-signed certificate only for `localhost`	a PKI issues no certificate for it, even with `cert_renew_self_signed`
a package's placeholder: postfix's `postfix.pem` (subject `O=SomeOrganization`, `check_certs_placeholder_subject`)	not a real certificate: a PKI issues nothing for that subject, even with `cert_renew_self_signed`. A found one is not even checked

What	Why
in the trust store (`check_certs_trust_dirs`, `/etc/pki/ca-trust/`)	a certificate the host trusts, not its own: its CA renews it. Put the CA's new certificate in the anchors folder and run `update-ca-trust`. Your server's own certificate belongs in `/etc/pki/tls/certs` (its key in `/etc/pki/tls/private`)
a keystore's trusted entry (`trustedCertEntry`), or a certificate in a PKCS12 without its key	one the program trusts, not its own
not matching `cert_renew_only` / `cert_renew_issuer`	your filters, e.g. DoD PKI only: `cert_renew_issuer: 'O=U\.S\. Government'`

A certificate whose CSR cannot be made fails the job with the reason, for example a subject openssl cannot write back, or a kind of name it cannot copy. The other certificates are still done.

Earlier than 30 days: the CSR comes when the certificate report flags the certificate. For a longer PKI round trip, set `check_certs_warn_days: 60`, as a survey on the workflow, so the report, the tickets and the CSRs use the same number.

Attachment refused: some instances only allow some file extensions or types (`File extension not allowed: csr`, `Invalid file type: text/plain`). A refused CSR is attached again as `<name>.txt` (`cert_renew_attach_retry_txt`, on), and the work note names that file. Refused again, the CSR goes in the work note instead, and the job fails and says so: copy it from the note, and ask for `.csr` (or `.txt`) attachments to be allowed on the instance (`glide.attachment.extensions`). To name every CSR `.txt` from the start: `cert_renew_attach_ext: txt`. A run again finds the CSR under either name and attaches nothing more. The ServiceNow account needs to add attachments to incidents (the `itil` role does).

Try it first:

- Run with **Check** (`--check`): it lists what it would make and attach, and writes nothing on the hosts or in ServiceNow.
- Without the ServiceNow API credential, the job prints each CSR so you can copy it by hand.

All settings of this job, with their defaults: check_certs (`cert_skip_hosts`, `cert_skip_groups`, `cert_renew_*`).

POA&M status (playbooks/poam_status.yml)

Reads `poam/poam.csv` (see poam/README.md for the columns and how to export from eMASS):

Finding	Means
`POA&M 1001 [CAT II]: ... - OVERDUE by 12 days`	open item past its scheduled completion date (critical)
`POA&M 1002 ...: due in 20 days`	due within `poam_due_soon_days` (30)
`... scheduled completion date "TBD" is missing or not a date`	fix the date in the list
`open CAT I finding V-123456 (...) on 2 asset(s) in collection Production has no POA&M item`	STIG Manager cross-check: an open CAT I/II finding that no POA&M item covers

It also lists "maybe ready to close": items whose STIG findings are no longer open in STIG Manager.

The STIG Manager cross-check is optional. It needs a Keycloak client that may use the client-credentials grant, with the scope `stig-manager:collection:read`, and a grant in the collections it reads. **Your realm owner creates that client**; nothing here changes the realm. Then create the *STIG Manager API* credential (token URL `https://<keycloak>/realms/<realm>/protocol/openid-connect/token`, client ID, secret), and set `poam_stigman_api: https://<stigman>/api`.

All settings of this job, with their defaults: poam.

ServiceNow tickets (playbooks/servicenow_tickets.yml)

A workflow step after a check. For each finding at or above `servicenow_min_severity`:

- **no open ticket** for that problem on that host › it opens an incident: short description `[site-health] host: summary`; description with the host, check, finding, the `look:` command, and ACT's analysis if ACT ran; urgency/impact from the severity; assignment group, category and configuration item from the settings.
- **an open ticket exists** › it adds a work note `Still failing at ...` (`servicenow_note_repeats`).
- **a host that was targeted but never reported** › a ticket too (not reached, login failed). The check job stays green for a host it could not reach (`site_unreachable_fails`); this ticket is where it shows.
- **a problem that cleared** (its check ran again and passed) › a work note on its ticket, or it resolves it with `servicenow_resolve_cleared: true`. A finding still there, but below `servicenow_min_severity`, has not cleared: its ticket stays open (a certificate renewal ticket at warning, for one).

Tickets are matched by a correlation ID (`site-health:<host>:<check>:<finding>`, hashed), never by text, so the same problem always updates the same ticket. Without the ServiceNow API credential it only prints what it would open. If no check results reach it at all (the check step died before checking any host), it fails, so a broken schedule shows red instead of green.

All settings of this job, with their defaults: servicenow.

ServiceNow - test ticket (playbooks/servicenow_test_ticket.yml)

Proves the ServiceNow setup end to end, with the same calls and settings as the tickets step. Six steps, each PASS, WARN or FAIL with what usually causes a failure:

Step	What it does	FAIL usually means
1 connection	logs in and reads one incident	certificate (CA), DNS, firewall or proxy; HTTP 401 = user or password; 403 = no `itil` role; 404 = a path after the host name in the Instance URL
2 settings	`servicenow_assignment_group` and `servicenow_caller` exist	the name differs from ServiceNow's
3 open	opens a low-priority incident: `[site-automation test] ... safe to close`	the account may not create incidents (`itil`), or ServiceNow refused a value (it says which)
4 read back	reads it back: number, state, group, caller; prints a link	the account may not read it; WARN if the group did not stick

Step	What it does	FAIL usually means
5 work note	adds a work note	the account may not update incidents
6 resolve	resolves it (`servicenow_test_resolve: false` leaves it open)	WARN only: your instance needs another resolved state or close code (`servicenow_resolved_state`, `servicenow_close_code`)

As *Check* (a dry run) steps 1 and 2 run, and 3 to 6 are only printed. Set up, run and verify it: SERVICENOW_SETUP.md.

ServiceNow health (playbooks/servicenow_health.yml)

From the controller: does the instance answer its REST API, and how fast (`servicenow_slow_seconds`)? Is every MID Server **Up**, **validated** and reporting, on one version, its queue moving, without open MID Server Issues? And on the MID Server **hosts** (Windows, the group `servicenow_mid_hosts` of the Windows inventory): each MID service running, its agent log written lately, SEVERE lines, JVM restarts, the drive, the instance URL - all in this one job and its report (SERVICENOW_SETUP.md). Hourly is a good schedule. Alert with an AAP **notification** (email) on failure when the API is down: a broken ServiceNow cannot take tickets.

A **self-hosted** instance: its front-end nodes (group `servicenow_nodes`, over SSH: each `snc_<env>.service` running and starting at boot, the node's stats page on 127.0.0.1 - JVM memory, semaphores, the scheduler, transactions -, its localhost log, `/glide` and `/`, memory and swap, fapolicyd's denials), its database host (`servicenow_db_hosts`: MariaDB, `/database` and the data dir's disk, the database's size against it, its largest schemas and tables, its growth and when the disk fills - the size kept in a small JSON file there, the job's one write -, fapolicyd) and the cluster (`sys_cluster_state`) - in the same report, usually from a second template, *ServiceNow health - nodes* (`servicenow_health_part: nodes`, the Linux inventory) (SERVICENOW_SETUP.md).

All settings of this job, with their defaults: servicenow.

Patch hosts (playbooks/patch_hosts.yml)

Installs updates with dnf - on RHEL 7 and its clones with yum (0.89.0: `yum check-update`, then `yum -y update`; any ansible-core) - (`patch_security_only` for security fixes only, `--security` on yum; `patch_exclude` for packages never updated here). Then:

0. **The updates each host has, first** (1.1.0): before any snapshot, each host is asked which updates it has - `dnf check-update` (`yum check-update` on RHEL 7), read-only, in Check mode too, with the same `patch_security_only`, `patch_exclude` and `patch_packages` as the update. A host with none is listed as `UP TO DATE - nothing to patch` and left out - **no snapshot, not patched** - the job not failed for it; the last lines list them: `2 host(s) up to date, nothing to patch: ...`. A check that does not answer (a repository not reached) leaves the host in, as before, and the update itself says what is wrong. `patch_update_check: false`: no check - every host gets its snapshot and its update run.
1. **One host at a time** by default. For batches, set `patch_serial` in the template's Variables or the survey (`patch_serial: 10`; in `all.yml` it does nothing). The rollout **stops at the first host that fails**: with batches, the rest of that batch finishes and no later batch starts.
2. **A host that cannot be reached when the job starts** (switched off, a firewall, ssh or its login refused) is listed as `NOT REACHED - <why>` and left out - not patched, no snapshot - and the other hosts are patched; the job is not failed for it. Its last lines list them all: `2 host(s) not reached, not patched: web07... (...); web09... (...)` - fix the network, then run it again for those (Limit). No host reached at all fails

the job (look at the machine credential). A host lost **later** (it went down halfway, or did not come back from its reboot) still fails and stops the rollout. `patch_skip_unreachable: false`: a host not reached fails the job, as before 0.87.0. **A host with neither dnf nor yum** (not a RHEL-like Linux) is listed as `NO DNF OR YUM - <its OS>` and left out the same way, the job not failed for it, and the last lines list them: `1 host(s) with neither dnf nor yum, not patched: ...`. `patch_skip_unsupported: false`: such a host fails at the update.

3. **A host that is not ready** - it answers, but the job cannot become root on it (sudo refused, its password wrong or missing: the template's Machine credential needs *Privilege Escalation Method* `sudo` and, when sudo asks for one, the *Privilege Escalation Password*), or it has less than `patch_min_free_mb` free in `/var` - is listed as `NOT READY - <why>` (the login banner left out; for a refused sudo, sudo's own last line, such as `sudo: a password is required`) and left out, the job not failed for it; nothing is changed or cleaned up on it. The last lines list them: `1 host(s) not ready, not patched: ...`. Fix it, then run again for those. `patch_skip_not_ready: false`: such a host fails the job and stops the rollout, as before 0.89.0.
4. **No automatic restarts** unless `automatic_restarts: true` (the survey or the template's Variables). Without it, a host that needs a reboot is listed ("reboot it by hand, or run again with automatic_restarts: true"). With it, the job reboots only when `needs-restarting -r` says so (`patch_reboot: when_needed`), and **never** hosts in `patch_never_reboot_groups` (`aap_hosts`). A host without `needs-restarting` (install `dnf-utils`), or where it fails, counts as needing a reboot after updates were installed - the job says so.
5. After the update (and reboot), **every service that was running before and starts at boot (`systemctl is-enabled`: enabled) must be running again**. If one is not, the host fails and the rollout stops. A service started on demand (static, indirect, transient - by D-Bus, a socket or another unit, like SELinux troubleshooting's `dbus-:1.1-org.fedoraproject.SetroubleshootPrivileged@83.service`) that ended on its own is listed (`on_demand_not_running_now`), never failed (0.89.0; `patch_compare_services: all` compares every one, as before).
6. Never patches hosts in `no_patch` (vendor appliances), `aap`, `aap_hosts`, `sat`, `netapp` or `netapp_console_hosts`. The AAP host is **always** protected: even a list you write yourself (`patch_never_patch_groups`) cannot remove `aap` or `aap_hosts`. It also refuses a host that is the machine running the job, but only when the connection is `local` or the name is `localhost`; a normal SSH host that happens to be the controller is stopped by the group rule above, not by this one.
7. Never patches a host on the **VMware protected lists** - the VMs the snapshot cleanup never touches: one of its groups is in `vmware_protected_groups`, or its name, short name, `vmware_vm_name` or VM in vCenter matches `vmware_protected_vms` or `vm_snapshot_cleanup_exclude_vms` (`*` and `?` allowed, any case). Set those lists in `all.yml` (not only in the snapshot cleanup template's Variables), so this job sees them too. To patch them anyway, each one after its own snapshot: "Protected VMs" below.

Run it as **Job type: Check** first: it lists what would be updated and changes nothing (DRY_RUNS.md).

The last lines (1.1.0) are a table of every host: its updates (`3 pending`, `up to date`, or why it was left out: `NOT REACHED`, `NOT READY`, `NO DNF OR YUM`) and its snapshot (`took "patching" of VM web01`, `reused "patching" from 2026-11-09 08:12 UTC of VM web01`, `none - physical (...)`, `not needed - up to date`, `none (patch_snapshot is false)`; in a dry run: `would take`, `would reuse`).

Snapshot before patching

With `patch_snapshot: true`, vCenter takes a snapshot named `patching` of each host's VM **right before that host is patched**: in each batch, the batch's snapshots, then the batch's updates. The snapshot is taken without memory (the VM keeps running), and its description records the host, the AAP job, the user and the time. Attach a **VMware vCenter** credential to the template as well as the Machine one (VMWARE.md).

```yaml
patch_serial: 10        # 10 hosts at a time
patch_snapshot: true    # a snapshot "patching" of each VM before it is patched
```

Each host's VM is found first, before any host is patched. The first of these that finds a VM decides:

1. The host variable `vmware_vm_name`: the VM's name in vCenter (when the names differ). Nothing else is tried.
2. A VM named like the host: `web01.yoursite.mil`, or `web01`.
3. The VM whose guest host name (reported by VMware Tools) is the host's.
4. The VM with the host's `ansible_host` address.

A host whose VM is in no vCenter is a physical server: it is patched without a snapshot, and the plan says `NO VM - ... (a physical server: patched without a snapshot)`. Only when every vCenter was read: a vCenter that could not be read may hold its VM, so then the job stops (below). `patch_snapshot_required: true` stops the job for such a host too (every host must be a VM).

The job then **stops before any host is patched** when:

The job says	What to do
`web01...: no VM by its name, ...` and `A vCenter was not read, so these may be VMs there`	fix that vCenter or its credential (`vmware_vcenters`), or leave the host out of the run (Limit)
`web01...: no VM by its name, ...` and `No vCenter has them (physical servers?)`	only with `patch_snapshot_required: true`. A VM: set `vmware_vm_name` for it (in the inventory, on the host). A physical server: leave it out of the run, or set `patch_snapshot_required: false`
`web01 matches more than one VM (...)`	set `vmware_vm_name` for it
`... still has the snapshot "patching" from ...`	the last patching's snapshot is still there, older than `patch_snapshot_reuse_hours`. Delete it once that patching is proven, or run with `patch_snapshot_replace: true` (the old one is deleted, a new one taken)
`attach a credential of type "VMware vCenter"`	the template has no vCenter credential

Run again soon after (1.1.0) - the job stopped at a host, or was run twice: a snapshot `patching` younger than `patch_snapshot_reuse_hours` (24) is that patching's own. It is **reused**: no second snapshot, nothing stopped, and the plan says `reusing the snapshot "patching" from <time> (N h ago)`. A host patched in full by the first run is up to date now, so it gets neither (rule 0). Older than that: the job stops as above (or `patch_snapshot_replace`). `patch_snapshot_reuse_hours: 0` = never reused, as before 1.1.0.

A snapshot that fails stops that host: it is **not** patched, and the rollout stops after its batch. The AAP hosts and the other protected groups are never patched, so they get no snapshot either. A dry run (*Check*) finds the VMs and says which snapshots it would take, but takes none. The job result shows each host's `snapshot:` line (`took "patching" of VM web01`).

Protected VMs. A host on the VMware protected lists (rule 7 above) is skipped - with `patch_snapshot: true` it shows as `PROTECTED - not patched (...)` in the list of VMs, and its VM stops nothing (no VM, two VMs, an old snapshot). To patch them **after a snapshot**:

```yaml
patch_snapshot: true
patch_protected_with_snapshot: true            # every protected VM
# patch_protected_with_snapshot: [DB*, app07]  # or only these (host or VM names, * and ?)
```

Such a host is patched only when its VM was found and its own snapshot was taken right before (a protected host in no vCenter is never patched, physical server or not). The AAP hosts are never patched, whatever this says.

Delete the snapshots once the patching is proven, typically a few days later. A snapshot left in place keeps growing and slows the VM. Use the snapshot cleanup with `vm_snapshot_cleanup_name_words: [patching]`: it deletes the `patching` snapshots 5 days or older (`vm_snapshot_max_age_days`), after an approval (VMWARE.md, "Snapshots"). A VM that still has one when the next patching starts stops that run, as above.

All settings of this job, with their defaults: patch.

Apply approved ACT fix (playbooks/act_fix_approved.yml)

The step after an approval in the *Fix with approval (ACT)* workflow. It runs **exactly** the commands ACT proposed and a person approved, then re-runs the checks that found the problem. It refuses to run on its own, and skips diagnose-only hosts (`aap_hosts`, `netapp_console_hosts`): there a person applies the fix by hand. See ADDING_ACT.md.

All settings of this job, with their defaults: site_act.

VMware jobs and reports (playbooks/vm_*.yml)

Restart, shut down, snapshot, notes, change VLAN; the secure boot, datastore, snapshot and alarms reports; the snapshot cleanup; ACT's analysis of the alarms. They work through vCenter: setup, every report's sections and troubleshooting are in VMWARE.md.

All settings of this job, with their defaults: vmware_vm.

Account lockout (playbooks/ad_lockout.yml)

On demand, for the service desk: give it the account (`jdoe`, `CORP\jdoe`, a UPN), or nothing for every account locked out now. Every DC reads its own bad password count and its Security log; the report ranks the computers the failed sign-ins came from and says what each one usually is. Setup, the audit policy it needs, the survey and the unlock are in ACTIVE_DIRECTORY.md.

You see	Means	Usually
`kept trying after the account was locked out`	that computer still has the old password	it locks out again right after an unlock: fix it first
`tries about every 5 minutes`	a steady pace: a saved password retrying	a service, a scheduled task, a mapped drive or an application on that computer
`is a mail server`	the sign-ins came through Exchange (ActiveSync, Outlook)	a phone with the old password
`The DC did not record which computer`	a server signed in for the user	NPS / RADIUS (Wi-Fi, VPN), Exchange / OWA, a web application

You see	Means	Usually
`has a DISCONNECTED session` (with `ad_lockout_check_sources`)	a Remote Desktop session left open	sign it out (`logoff <id>` on that computer)
`No failed sign-in ... the DCs may not audit`	no 4740 / 4771 / 4776 events	the DCs' audit policy, or the Security log rolled over

All settings of this job, with their defaults: ad_lockout.

Horizon 8 (VDI) (playbooks/horizon_*.yml)

The API test, the health and capacity reports, the broken desktops check and its fix after an approval, user help for the service desk, the disconnected session cleanup, and the golden image push after an approval. They read the Connection Server's REST API; the account, the templates, the two workflows and every message are in HORIZON.md.

All settings of these jobs, with their defaults: horizon.

VMware pick lists (playbooks/vm_pick_refresh.yml, vm_snapshot_delete_picked.yml, vm_reboot_picked.yml)

Choose from a list instead of typing VM names: a scheduled refresh writes what may be done right now

- the snapshots the cleanup could delete, the VMs that may be restarted, or only the hung ones (no

heartbeat, or VMware Tools not running) - as the choices of a multiple-select survey question. The pick jobs find every pick again in vCenter, live, skip what is gone or no longer allowed (with the reason), and in their workflow plan first, wait for an approval, then do exactly the plan. Never the AAP server or a protected VM; never more than `vm_pick_max` (20) at once. Setup and limits: VMWARE.md, "Pick lists".

All settings of these jobs (`vm_pick_*`): vmware_vm.

Windows hosts

Windows has its own playbooks, checks and troubleshooting areas (for example `updates` and `security` in *Windows troubleshoot*). They are described, with their settings, in WINDOWS.md. Settings for them are read the same way as any other: VARIABLES.md.


Not built yet (and why)

Idea	Why not yet
SCAP scan › import into STIG Manager	Needs the same Keycloak client as the POA&M cross-check, plus a decision on SCC vs OpenSCAP content. STIG Manager's own importer (stigman-watcher) is the supported path
AAP self-health (job failure rate, execution environment and token age)	Needs an AAP API credential; AAP's own dashboards cover most of it today
Container runbooks (image updates with rollback, drift)	Deferred on purpose; *Service watch* covers container outages
MariaDB backups, security baseline, password rotation	Out of scope for now: health only, as asked

17. Adding ACT (GenAI) later

The runbooks work without ACT. Add it when the checks are running well and you want the next step done for you: **why** it broke and **what** fixes it. This page shows how the runbooks and ACT fit together, how to turn it on per template, and how to write your own check so it works with ACT automatically.

How they fit: checks find WHAT, ACT finds WHY



Report, ServiceNow tickets and the approval workflow read the same findings - with or without ACT.

Checks find WHAT is wrong; ACT finds WHY. A new check works with ACT automatically through its findings' hints.

- The **checks** decide *whether* something is wrong. They are plain Ansible: the same answer every time, and they are free. The model is only called for hosts with findings.
- Every finding carries a **hint**: the read-only command a person would run next. ACT gets those commands' output as evidence. A new check you write is therefore usable by ACT with no extra work.
- `roles/site_act` is the only place that talks to ACT. Every runbook uses it the same way. Turning ACT on is a variable, not a code change.
- Host names, IP addresses and user names are **pseudonymized** before anything reaches the model (ACT 0.6.18 and newer). Its replies are translated back on the host.

The three levels

Level	ACT does	Changes to hosts	Approval step?
`explain`	reads the evidence (the hint commands' output, collected by Ansible) and writes the root cause and a suggested fix. **It runs no commands itself**	none	no
`diagnose`	investigates by running **read-only** commands itself, then proposes exact fix commands. Every change is refused and waits for a person	only after approval	yes: the job fails with `NEEDS APPROVAL` › approval step › *Apply approved ACT fix*
`self-heal`	like `diagnose`, but may **run fixes that match** `site_act_allow` by itself (for example `systemctl restart chronyd`). Anything else still waits for approval. The checks then run again to prove the fix worked	only fixes you listed	only for the other fixes

Start with `explain`. Move a runbook to `diagnose` when ACT's explanations have been right for a while. Use `self-heal` only for fixes you would let a junior admin do unasked: start a stopped service, restart a hung one.

Never fixed automatically, at any level: hosts in `site_act_diagnose_only_groups` (default: `aap`, `aap_hosts`, `sat`, `idm`, `netapp`, `netapp_console_hosts`; `aap` and `aap_hosts` are always kept, whatever list you write). There `self-heal` becomes `diagnose`, and the apply step skips them: it prints the approved command for a person to run by hand.

Turn it on

ACT can be off for a whole AAP: `site_act_enabled: false` in `all.yml` (an enclave without a model) - then no job asks it, needs a key or fails for it, and each report says *ACT is off (site_act_enabled false)* in one line (ENCLAVES.md, "ACT").

1. The ACT model key credential

Create the credential type `ACT model key` (`aap/credential_types/act_model_key.yml`) and one credential with your key: the GenAI key for GenAI.mil, or the AskSage key for Ask Sage (SETUP_AAP.md, steps 2-3). For the GenAI beta proxy, also create `ACT GenAI beta key` (`act_genai_beta_key.yml`). Attach the credential(s) to the **Health check** and **Troubleshoot** templates (and *Service watch - check*), next to `Linux ssh (sudo)`. This is the only place a key lives. The apply steps do not call the model: they run the approved commands themselves, so they need no key.

2. Pick the model provider

ACT can talk to three providers. Pick one with `site_act_provider`. **GenAI.mil (`genai`) is the default and the one to use: Ask Sage is retired for now.** Its settings stay below, unused, in case it comes back.

site_act_provider	Provider	Key (credential)	Also set
`genai` (default)	GenAI.mil	*ACT model key*, **GenAI API key** field	nothing (optional: `site_act_model`)
`asksage`	Ask Sage (**retired for now**: do not pick it)	*ACT model key*, **AskSage API key** field	`site_act_url`: your organization's Ask Sage API URL. The default is `https://api.genai.army.mil/server/openai/v1/chat/completions`
`genai-beta`	GenAI.mil beta proxy (preview models)	*ACT GenAI beta key* (`aap/credential_types/act_genai_beta_key.yml`)	nothing

The settings:

Setting	What	Default
`site_act_provider`	`genai`, `asksage` or `genai-beta`	`genai`
`site_act_models`	the model **for each provider**, so the model follows the provider you pick, e.g. `{genai: gemini-4-argon-withtools, asksage: gpt-5.6-sol-gov}`	ACT's default for the provider
`site_act_urls`	the API URL for each provider, e.g. `{asksage: https://<host>/server/openai/v1/chat/completions}`	ACT's default for the provider

Setting	What	Default
`site_act_model`, `site_act_url`	one model / URL for this run, whatever the provider (a survey answer)	empty: use the two above
`site_act_ca`	a CA bundle file **on the hosts**, if the provider's certificate comes from a CA the hosts do not trust yet (for example a DoD CA not in `/etc/pki/ca-trust`)	the host's normal trust store

Where to set them:

- **For everyone**: `playbooks/group_vars/all.yml` in this project (the file has these lines ready as comments). A setting there beats the *inventory's* Variables box in AAP, so put it in one of the two places, not both. Which place wins in every case: VARIABLES.md.

```yaml
site_act_provider: genai                # the default provider
site_act_models:                        # the model follows the provider you pick
  genai: gemini-4-argon-withtools
  asksage: gpt-5.6-sol-gov
site_act_urls:                          # only if your Ask Sage is not ACT's default URL
  asksage: https://<your ask sage host>/server/openai/v1/chat/completions
```

(Ask Sage is retired for now: keep `site_act_provider: genai`.)

- **For one group**: the group's settings file (`playbooks/group_vars/<group>.yml`), or the group's **Variables** box in AAP. For example `site_act_provider: asksage` there, and only that group's hosts use Ask Sage (with its model from `site_act_models`).
- **For one template**: its **Variables** box (*Extra variables*), for example `site_act_provider: asksage`. It beats everything above, for every run of that template.
- **Per launch**: the survey questions in step 3 (a survey answer beats everything too).

The API **key** is never a variable: it comes from the *ACT model key* credential on the template.

These settings apply to every runbook that uses ACT, including *Service watch* and *Apply approved ACT fix*. If the key for the chosen provider is missing, ACT does not run: the job says `ACT did not run: this job has no API key for provider asksage. Attach ...`, and the findings are still reported.

Network: ACT runs **on each host**, not in AAP. So each host must be able to reach the provider's URL over HTTPS. If they go through a proxy, add it: `site_act_env: {HTTPS_PROXY: "http://proxy.yoursite.mil:8080"}`.

Models served only on `/v1/messages` (ACT 0.6.19 and newer). Some gateways offer a model only through the Anthropic endpoint and answer HTTP 400 for it on `.../v1/chat/completions`. ACT tries the other endpoint by itself, with nothing to set. To test your models and set the switches on purpose, follow Both endpoint formats and `:probe` below.

How long ACT may take. `site_act_model_timeout` (default **600** seconds) is the time the model may take for one answer, retries after a provider error included (ACT's `GENAI_TIMEOUT`; ACT's own default, 90, is too short for a long analysis or a busy provider). `site_act_timeout` (default **1200**) is the whole ACT run, several answers. They apply to every ACT job: the runbooks with `use_act`, the VMware alarms and capacity analyses, *Service watch*. A `model turn exceeded the 600s total timeout after a transient provider failure` means the provider was failing and retrying for that long: run it again; if it repeats, raise both in `all.yml` (`site_act_model_timeout: 900`, `site_act_timeout: 1800`).

Streaming. Every ACT job has the model stream its answer (`ACT_STREAM=1`): data keeps flowing while it writes, so a firewall or proxy that cuts quiet connections (`network error reaching API: connection reset by peer`, often on the longer answers only) no longer does. Where a gateway cannot stream, ACT notices and sends normal requests by itself. To turn it off: `site_act_env: {ACT_STREAM: "0"}`.

A plain answer when ACT only reads (0.44.5). When a job only asks ACT a question - the evidence mode of the WAR, the VMware alarms, capacity planning, log analysis, right-sizing, VM - ask a question, the VM deploy's GenAI proposal and the `explain` level - ACT gets `ACT_TOOLS=0`, `ACT_JSON_MODE=0` and `ACT_PREFILL=0`: the model is offered none of ACT's own steps (tools, the action schema, a `{` to go on from) and answers in plain text. With them it could only answer as a step - `{'action': 'plan', ...}` or `{'message': ...}` instead of the answer. `site_act_env` wins over them. ACT's loop (`diagnose`, `self-heal`) keeps its tools.

"ACT gave no analysis: the model answered as a chat". Now and then a model loses the thread and answers like a chat window ("I am ready. What task or command would you like me to assist you with?") instead of analysing the findings; whatever it tried to run then is no fix. The report says so (ACT status `no_analysis`) and nothing is passed on for approval. Run the job again; if it repeats with one model, switch that template to another (`site_act_models`).

Anything else ACT should know about your site goes in the same places (for example `playbooks/group_vars/all.yml`):

YAML

```
site_act_extra_instructions: >-
  RHEL 9 servers under DISA STIG. fapolicyd and SELinux are enforcing. Never suggest disabling
    them.
```

All settings, with their defaults: site_act.

3. Survey questions

On **Health check** and **Troubleshoot** › **Survey** › **Create survey question**:

Question	Variable	Type	Choices	Default
Ask ACT (GenAI) about the findings?	`use_act`	Multiple Choice (single select)	`no`, `yes`	`no`
What may ACT do?	`site_act_level`	Multiple Choice (single select)	`explain`, `diagnose`, `self-heal`	`explain`
Which model provider? (optional)	`site_act_provider`	Multiple Choice (single select)	`genai`, `genai-beta` (leave `asksage` out while Ask Sage is retired)	the one in your settings
Which model? (optional, blank = the provider's model from `site_act_models`)	`site_act_model`	Text, not required		blank

Leave out the last two if everyone uses the same provider. Your setting (section 2) then applies.

4. Try explain by hand

Launch **Troubleshoot** on a host with a known problem: `ts_area` = `service`, `ts_service` = the unit, `use_act` = `yes`, `site_act_level` = `explain`. In the output, read `ACT | what ACT says`. With ACT on, the host's ServiceNow ticket includes this analysis too.

5. diagnose with the approval workflow

Build *Fix with approval (ACT)* (WORKFLOWS_AND_SCHEDULES.md). What happens:

1. The health check finds, for example, `required service chronyd.service is inactive`.
2. ACT (`diagnose`) looks at the unit, its log and the config, and proposes `systemctl start chronyd`. The command is refused, so the job fails: `NEEDS APPROVAL - ... ACT proposes: systemctl start chronyd`.
3. The workflow stops at the approval step. The approver reads ACT's report and approves.
4. **Apply approved ACT fix** runs **exactly** `systemctl start chronyd` itself: no model and no key, so nothing can be reworded between the approval and the fix. A last check refuses a few commands even after approval (reboot, `mkfs`, `usermod` ...; see APPROVED_COMMANDS.md).
5. The same checks run again, without ACT, and the job is green only if the problem is gone. The tickets step notes the ticket as cleared.

6. self-heal for the fixes you trust

playbooks/group_vars/all.yml (or the settings file of one group)

```
site_act_allow:
  - 'systemctl (start|restart) (chronyd|rsyslog|crond)'
```

Each entry is a regular expression that must match the **whole** command. Keep them narrow: name the services, never `.*`. Then pick `site_act_level` = `self-heal`. After ACT applies an allowed fix, the checks with findings run again. The report shows `cleared: ...` or `still there: ...` and reflects the state **after** the fix.

Both endpoint formats and :probe (ACT 0.6.19 and newer)

What this is for. A model gateway can offer a model on two web addresses: the *OpenAI* one (the provider URL, ending in `/v1/chat/completions`) and the *Anthropic* one (ending in `/v1/messages`). Some models answer on only one of them. If ACT prints `HTTP 400 ... bad request` for a model that the gateway lists, this is the usual cause. ACT can now speak both, and `:probe` tests which one each model needs.

Two facts that shape the steps:

- `:probe` is a command you type at the ACT prompt. **It cannot run inside an AAP job** (jobs are not interactive). So you run it **once, by hand, on one lab host**, and then put the result into settings the jobs read.
- In a job, ACT already works out the format by itself (one refused request, then it switches), so the jobs may need no change at all. The settings below only save that one wasted request per run, or point at an Anthropic address that is not the default.

Not verified against a real gateway. These steps were written from ACT's own documentation and tests. Nobody has run them against your gateway yet; treat the first run as the test.

Step 1: check which ACT the project carries

`vendor/act/VERSION` must say `0.6.19` or newer. This release carries **0.6.25** (0.6.25: a model answer cut off on its way back is asked again instead of ending ACT; 0.6.24 changes only ACT's own example playbook `podman_app_health.yml`: see CHANGELOG.md). It sends the key only to an `https://` provider URL (an `http://` URL is refused unless `site_act_env: {ACT_ALLOW_HTTP: "1"}`), and more dangerous commands always need a person (see APPROVED_COMMANDS.md). New in 0.6.22 and 0.6.23, all automatic:

- **A bigger output limit for thinking models (0.6.23).** Gemini 2.5 and later, GPT-5 and the o-series think before they answer, and the thinking counts against the output limit. At ACT's old limit (4096 tokens) the

thinking could use it all and the answer came back **empty** - on GenAI.mil every Gemini model did that in `:probe`. These models now get 16384 (others keep 4096). It is a ceiling, not a charge: you pay for the tokens used. To force one value: `site_act_env: {ACT_MAX_TOKENS: "8000"}`.

- **Temperature per model.** Gemini 3 models (and GPT-5 / o-series reasoning models) get **no** temperature, so they use their own default (1.0): Google's Gemini 3 developer guide says to keep it at 1.0 and that lower values can make the model loop. Other models keep 0.2. To force a value for every model: `site_act_env: {ACT_TEMPERATURE: "0.2"}`.
- **Fewer empty answers.** A reply cut off at the output limit (the model's thinking used it all) is asked again once with a higher limit; an empty reply is asked again once with a strict JSON schema of ACT's actions; a reply the gateway's content filter blocked is reported as that.
- **Structured output.** When a model refuses ACT's function-calling format, ACT asks for a strict JSON schema instead of "any JSON object", so the gateway itself guarantees a valid answer.
- **HTTP 429 (too many requests):** ACT waits as long as the gateway asks (`Retry-After`). A spent credit quota still stops the run (it would not help to wait).
- **Clearer errors.** A model alias the gateway retired (GenAI.mil retires aliases 60 days after deprecation) is reported as that, not as a missing endpoint or a permission problem; a locked or wrong key says to enter a new one.
- **Interactive only:** replies stream in (a counter shows progress) and **Esc** cancels a reply that is still coming. Jobs do not stream (nothing to watch, and some proxies break streaming).
- **Tool-result turns** (command results sent back the way function-calling models expect): only for models `:probe` confirmed - see step 5. If it is older, update it first: README section

"Updating ACT" (`scripts/update-act.sh`).

Step 2: put ACT on one lab Linux host

Any host that can reach the gateway will do; it does not have to be one of your managed hosts. Copy the file `vendor/act/act` there (WinSCP, or `scp` in PowerShell), then on the host:

```shell
chmod 700 act
```

Step 3: give it your key without writing the key anywhere

Type this on the host. It asks for the key without showing it, and keeps it only in that terminal session (use `GENAI_BETA_KEY` or `ASKSAGE_KEY` for the other providers):

```shell
read -rs GENAI_KEY; export GENAI_KEY
```

Paste the key, press Enter, and do not `echo` it. If the provider URL is not ACT's default, also `export GENAI_URL='https://<your gateway>/v1/chat/completions'`.

Step 4: run :probe

```shell
./act
```

At the ACT prompt:

```
:probe all
```

`:probe all` tries every model the key lists, on both endpoints, with a small request and then ACT's full request. For each it shows what worked and, for a refusal, **the gateway's own reason**. `:probe <model name>` tests just one; `:probe model1 model2` (spaces or commas) tests several. Write down, for each model, which endpoint worked (`openai` or `anthropic`). Leave ACT with an empty line (or Ctrl-D). From 0.6.23 `full OK` means the model gave a usable answer; `full empty (...)` or `full no action (...)` says what came back instead (for example `finish_reason=length`: the model ran out of output room), and a test that needed more room says `OK (needed a higher output limit: N)` - ACT remembers that limit for the model.

From 0.6.22 each model also gets these lines (under its `basic` / `full` lines):

Line	Meaning	What to do
`stream OK` / `stream not supported (...)`	whether replies can stream in (interactive use only)	nothing
`structured output OK (strict)` / `OK (non-strict)` / `not supported (...)`	whether the gateway enforces ACT's JSON schema for this model	nothing: ACT uses the best one that works
`tool results OK` / `tool results not supported (...)`	whether this model accepts command results as tool turns	**write it down**: step 5
`temperature: model default` / `temperature: 0.2`	what ACT sends	nothing (to force a value: `ACT_TEMPERATURE`)
`output limit 16384 (thinking model)` / `output limit 4096`	the most the model may write per answer, thinking included (0.6.23)	nothing
`full empty (finish_reason=length ...)`	even the higher limit was not enough for that test	tell the maintainer; or `ACT_MAX_TOKENS` higher

The result is remembered for the session. If a setup file already exists for your user on that host (`~/.config/act/config.json`), ACT also saves the format there (only the format table, never the key).

Windows. ACT for Windows (`vendor/act-windows/act.ps1`) has the same `:probe` command. Run it the same way on a lab Windows host, in PowerShell, and enter the key with `:setup`. Its result goes into the Windows jobs' settings as above. (Not run by hand for this page.)

Step 5: tell the jobs

A job does not read the lab host's file (it runs as another account, on another host), so put the result in settings, in the same places as the other ACT settings (section 2):

Your probe result	Setting in playbooks/group_vars/all.yml (or a group file)
All the models you use work on the OpenAI endpoint	nothing to set
Some models work only on the Anthropic endpoint	nothing to set (ACT learns it during the run); optional, to skip the one refused request per run when **every** model you use is Anthropic-only: `site_act_env: {ACT_API_FORMAT: anthropic}`

Your probe result	Setting in playbooks/group_vars/all.yml (or a group file)
The Anthropic endpoint is at a different address than the OpenAI one with `/messages` in place of `/chat/completions`	`site_act_env: {GENAI_ANTHROPIC_URL: "https://<host>/.../v1/messages"}` (`ASKSAGE_ANTHROPIC_URL` or `GENAI_BETA_ANTHROPIC_URL` for the other providers)
A model you want is listed for the key but works on neither	it is not available to your key; ask the gateway's owner. Choose another model in `site_act_models`
`tool results OK` for the model your jobs use (0.6.22)	optional: `site_act_env: {ACT_TOOL_RESULTS: tool}`. Jobs then send command results as tool turns, which function-calling models handle best on long runs. If a model refuses them anyway, ACT switches that model back by itself
`tool results not supported`	nothing to set (the default sends results as ordinary messages, as before)

`ACT_API_FORMAT: anthropic` applies to **every** model ACT uses in the job. If you use both kinds, leave it out.

Many hosts at once: site_act_concurrency

Every host in one job uses the same key, and GenAI.mil's default quota is **60 requests and 200,000 tokens a minute** per key (and a daily credit budget). A Health check with `use_act` on 20 hosts with findings would otherwise run ACT on as many hosts at once as the job's forks allow, and the gateway answers HTTP 429. `site_act_concurrency` (default **3**) caps how many hosts run ACT at the same time; the rest wait their turn. `0` = no cap. ACT itself also waits when the gateway sends a 429 with `Retry-After`.

Many items at once: site_act_batch

The jobs where ACT reads evidence - the VMware alarms analysis, capacity planning and log analysis - ask ACT about **5 items per question** (`site_act_batch`): 15 alarms are three questions of 5, each with only its items' evidence, and the answers make one report. One long answer about many items is what a gateway or proxy cuts off (`the reply was cut off`), or what runs past `site_act_model_timeout`. When one question fails, the others' analyses are still in the report and the job names the items that were not analyzed (`P6-P10 not analyzed: ...`). `site_act_batch: 3` for a slow model or a strict gateway; `0` asks everything in one question. Each job has its own setting too: `vm_alarm_act_batch`, `vm_capacity_act_batch`, `log_analysis_act_batch`.

How to verify

1. **The probe result:** in step 4 every model you plan to use shows one endpoint that worked.
2. **A job:** launch **Troubleshoot** with `use_act` = `yes`, `site_act_level` = `explain`, and the model in `site_act_model` (or set through `site_act_models`) on a host with a known finding. In the output, task `ACT | what ACT says` holds an analysis, not an `HTTP 400` message.
3. **The old symptom is gone:** search the job output for `400`. A line saying ACT switched to the other endpoint is fine; a final `HTTP 400` for the model is not (then the probe said neither endpoint works: step 5, last row).

If a step fails, the message after `HTTP 400` is the gateway's reason: copy it exactly when you ask its owner for help, but remove the key and host names first.

ACT for vCenter alarms (it runs on the AAP side)

`VM - alarms ACT analysis` (VMWARE.md, "Alarms") uses ACT differently from the health checks: ACT runs **inside the job's execution environment on the AAP node**, not on a managed host, and only reads the evidence the job collected from vCenter (it runs no command). So the ESXi hosts need nothing; the **AAP node** needs HTTPS to the model's URL, and the job checks that first. It uses the same settings as everything else here: `site_act_provider`, `site_act_models`, `site_act_url`, `site_act_env` (a proxy), `site_act_ca` (a CA file **in the execution environment**, e.g. one from the project: `"{{ playbook_dir }}/files/ca/model-ca.pem"`), and the **ACT model key** credential on its template.

The **log analysis** (LOG_ANALYSIS.md: `Log analysis` for a group of Linux or Windows servers or a vCenter appliance, `VM - vCenter log analysis` for vCenter and its ESXi hosts) works the same way: the job reads the logs, groups the lines into patterns on the AAP side, and ACT explains the top ones in evidence mode - one call per job, whatever the number of hosts.

Write your own check (it works with the report, tickets and ACT automatically)

A check is a role named `check_<name>` that **adds findings** to `site_findings`. That is the whole contract. As an example, here is a check that `/tmp` is not world-writable without the sticky bit.

1. Create `roles/check_tmp/defaults/main.yml`, with its settings and a comment saying what it checks:

```yaml
---
# TMP: /tmp and /var/tmp must have the sticky bit (mode 1777).
check_tmp_paths: [/tmp, /var/tmp]
```

2. Create `roles/check_tmp/tasks/main.yml`. Collect with read-only commands, and always use `changed_when: false` and `check_mode: false`: read commands then run in a dry run too. Turn what you saw into findings, and add them:

```yaml
---
- name: tmp | modes
  ansible.builtin.command:
    argv: "{{ ['stat', '-c', '%a %n'] + check_tmp_paths }}"
  register: _tmp
  changed_when: false
  failed_when: false
  check_mode: false

- name: tmp | findings
  ansible.builtin.set_fact:
    _tmp_findings: >-
      {%- set f = [] -%}
      {%- for line in _tmp.stdout_lines if line.split()[0] != '1777' -%}
      {%-   set path = line.split()[1] -%}
      {%-   set _ = f.append({'check': 'tmp', 'id': 'tmp:' ~ path, 'severity': 'warning',
                              'summary': path ~ ' has mode ' ~ line.split()[0] ~ ' (expected
                                1777)',
                              'hint': 'stat ' ~ path ~ '; findmnt ' ~ path}) -%}
      {%- endfor -%}
      {{ f }}

- name: tmp | add them to this host's findings
  ansible.builtin.set_fact:
    site_findings: "{{ site_findings | default([]) + _tmp_findings }}"
```

3. Let the health check know it: in `playbooks/health_check.yml`, add `tmp` to `_health_sets` (to `weekly` and `all`), and add `tmp` to the survey choices of the Health check template.
4. Test it on one host: `ansible-playbook playbooks/health_check.yml -l <host> -e health_checks=tmp`. Then break the condition on purpose (`chmod 777 /tmp` on a test host) and check that the finding appears. A check that never fires proves nothing.

That is all. The report prints it, set_stats publishes it, ServiceNow tickets it (the `id` keeps it on one ticket), and with `use_act=yes` ACT receives the summary and runs the `hint` as evidence.

Rules for a good finding:

- `summary`: one line a person understands, with the number and the limit (`/var is 96% full (critical at 95%)`).
- `id`: stable across runs, with no numbers that change (`disk:/var`, not `disk:/var:96`). Otherwise every run opens a new ticket.
- `hint`: **read-only**, runs in under a minute (`timeout 60 ...`), and shows the cause, not just the symptom. It runs as root when ACT is on (Ansible runs it in `explain` mode and hands ACT the output), so never put a command that changes something there.
- `severity`: `critical` = act now (outage, security); `warning` = act soon.

Use ACT in a playbook of your own

Any playbook that fills `site_findings` can hand them to ACT the same way:

```yaml
- name: My check
  hosts: my_hosts
  become: true
  gather_facts: false
  tasks:
    - ansible.builtin.include_role: {name: site_findings, tasks_from: start.yml}
    - ansible.builtin.include_role: {name: site_findings, tasks_from: run_check.yml}
      vars: {_site_check: tmp}                              # runs roles/check_tmp
    - ansible.builtin.include_role: {name: site_act}
      when: use_act | default(false) | bool and site_findings | length > 0
    - ansible.builtin.include_role: {name: site_findings, tasks_from: report.yml}
```

`report.yml` goes last. It prints, publishes (for tickets and the approval workflow), and fails the host when there are findings or a fix waits for approval.

What ACT is told, and what it cannot do

- Its task: the findings (one line each), "find WHY, confirm it with evidence, give the exact fix; several findings may share one cause", plus your `site_act_extra_instructions`.
- `explain`: it runs nothing. Ansible ran the hint commands.
- `diagnose`: only commands ACT can prove are read-only run on their own. Everything else is refused and becomes a proposal.
- `self-heal`: in addition, only commands matching `site_act_allow`.
- Apply step: no model at all. The playbook runs only the approved commands, character for character, in order, and stops at the first one that fails. Run as *Check*, it only shows what it would run (a dry run: see WORKFLOWS_AND_SCHEDULES.md, "Rehearse it").
- Every run is recorded in the AAP job output. The ticket carries ACT's analysis. For the service-watch style incident log, see SERVICE_WATCH_DEMO.md.

18. Windows servers

The Windows runbooks work the way the Linux ones do. Checks find what is wrong and say it in plain words, with a command to look further. The same report, the same ServiceNow tickets and POA&M, and the same workflows and schedules follow. Only the checks themselves are different: each one is a PowerShell script that runs on the server over WinRM.

Nothing extra to install on AAP or on the servers. The playbooks use only Ansible's built-in `script` module, so no Ansible collection is needed. The execution environment needs the Python library for WinRM (`pywinrm`); step 2 shows how to check. The servers need WinRM, which you already use: over HTTPS (5986), or over HTTP (5985) with Kerberos or NTLM encrypting each message (step 1). The check scripts run in Windows PowerShell 5.1 and PowerShell 7, and also in Constrained Language Mode (see step 5).

Template	Playbook	What it does
Windows connection test	`playbooks/win_connection_test.yml`	run it first: can AAP reach the servers, with the right account?
Windows health check	`playbooks/win_health_check.yml`	the checks below; daily and weekly sets
Windows troubleshoot	`playbooks/win_troubleshoot.yml`	on demand: an admin's first PowerShell commands for one kind of problem
Windows certificate report	`playbooks/win_cert_report.yml`	every certificate on every server, soonest expiry first
Windows certificate renewal - CSRs	`playbooks/win_cert_renew_csr.yml`	for each of the server's own certificates that expires: a new key and a CSR (`certreq`) on the server, the CSR on the certificate's ServiceNow ticket
Windows certificate install - check / approved	`playbooks/win_cert_install_check.yml`, `win_cert_install_approved.yml`	the issued certificate from the catalog request: `certreq -accept`, the old certificate's bindings moved to it, after an approval (CERT_INSTALL.md)
Windows certificate restore	`playbooks/win_cert_restore.yml`	the bindings back on the old certificate
Windows patch	`playbooks/win_patch.yml`	install what Software Center offers (ConfigMgr); restart only with `automatic_restarts: yes`; prove the server is back
Windows STIG drift report	`playbooks/win_stig_drift_report.yml`	Evaluate-STIG on the servers, each STIG's checklist against STIG Manager (read-only) and the earlier scans (STIG_DRIFT.md)

Template	Playbook	What it does
Windows STIG recheck	`playbooks/win_stig_recheck.yml`	only the rules STIG Manager has Open or Not Reviewed, checked again by Evaluate-STIG (-SelectVuln), and what to update in STIG Manager (STIG_DRIFT.md)
ACT for Windows - install	`playbooks/win_act_install.yml`	put ACT on the servers in `C:\ProgramData\act`, locked down and unblocked; keep it current
ServiceNow tickets, POA&M status	the ones you have	unchanged: they take the Windows results the same way

The checks (`roles/win_check_<name>`):

Set	Check	Finds
daily	`disk`	volumes too full
daily	`services`	required services not running; automatic services that stopped with an error; services that keep crashing
daily	`performance`	CPU, memory or page file too busy; names the busiest processes
daily	`time`	Windows Time not running, not synchronized, synced too long ago, clock off
daily	`network`	no gateway or DNS; names that do not resolve; ports that do not answer; a broken domain trust
daily	`eventlog`	unexpected shutdowns, crashes, disk errors, a cleared Security log, many errors, full logs
weekly	`security`	Defender real-time protection off or old signatures; endpoint services down; firewall off; SMBv1; RDP without NLA; UAC off; TLS 1.0/1.1
weekly	`audit`	audit policy settings the STIG asks for; event log sizes; the log forwarding agent
weekly	`accounts`	Guest enabled; local passwords old or never expiring; inactive local accounts; unexpected local Administrators
weekly	`certs`	certificates that expire or expired, including the WinRM listener AAP connects through
weekly	`patching`	a restart pending for installed updates; days since the last update
by name	`stig`	STIG drift: Evaluate-STIG's checklists against STIG Manager and the earlier scans - in no set (it takes minutes); its own template is the Windows STIG drift report (STIG_DRIFT.md)

Everything is read-only. The one write is one Application event log entry per finding (source `site-health`), so a SIEM that collects event logs sees the findings too - and `stig` keeps its scans in its own folder on the server (`win_check_stig_dir`).

Step 1. WinRM on the servers

You already use it. To see it on a server:

```
winrm enumerate winrm/config/listener
```

- **A listener with** `Transport = HTTPS`**,** `Port = 5986` and a `CertificateThumbprint`: the connection is TLS. The `certs` check warns before that listener's certificate expires: when it expires, AAP can no longer connect.
- **Only** `Transport = HTTP`**,** `Port = 5985` (often set by a GPO): that works too. Kerberos and NTLM encrypt every message themselves; `ansible_winrm_message_encryption: always` (step 4) makes the connection fail rather than ever send in clear. Never use `basic` sign-in over HTTP.

The firewall must let that port in from the AAP execution nodes.

Step 2. The execution environment

The job runs inside an execution environment (EE), and that EE needs these Python libraries:

- `pywinrm`, always;
- `requests-ntlm`, for NTLM (the usual choice);
- or `requests-kerberos` plus a Kerberos client (`kinit`), for Kerberos.

AAP's *Default execution environment* has them. Your own EE (for example `platforms-ee`) may not. **The Windows connection test tells you**: its first part runs inside the EE and prints `YES` or `no` for each library. If `pywinrm` is missing, you have two options:

- use AAP's Default execution environment for the Windows templates; or
- add the libraries to your EE's definition and rebuild it:

```yaml
dependencies:
  python:
    - pywinrm
    - requests-ntlm
```

- or build the all-in-one EE: it has these, Kerberos for a FIPS host, and the VMware, NetApp, database and Cisco collections too (EXECUTION_ENVIRONMENT.md).

Step 3. The credential

Automation Execution › Infrastructure › Credentials › Create credential:

- **Name**: `Windows (WinRM)`; **Credential type**: *Machine*.
- **Username**: `YOURDOMAIN\svc_aap` for NTLM. For Kerberos, use `svc_aap@YOURDOMAIN.MIL`, with the domain in capitals. On a **FIPS** system (STIG) NTLM does not work at all - use Kerberos (see *If something goes wrong*).
- **Password**: the account's password.
- **Privilege escalation**: leave it empty. An administrator's WinRM session is already elevated.

The account must be in the **local Administrators group** on every server, usually through a domain group added by GPO. The checks need that to read the Security log, the audit policy, local accounts and certificate stores.

Step 4. The Windows inventory

Keep the Windows servers in their **own inventory**. Go to **Inventories › Create inventory**, name it `Windows servers`, and paste this in its **Variables** box:

```yaml
ansible_connection: winrm
ansible_port: 5986
ansible_winrm_scheme: https
ansible_winrm_transport: ntlm                  # or kerberos
ansible_winrm_server_cert_validation: validate  # needs your CA bundle in the EE, see below
ansible_winrm_ca_trust_path: /etc/pki/ca-trust/source/anchors/your-ca.pem   # path inside the EE
```

Servers with **only an HTTP listener (5985)**, step 1, take these lines instead (no certificate lines: Kerberos or NTLM encrypts the messages):

```yaml
ansible_connection: winrm
ansible_port: 5985
ansible_winrm_scheme: http
ansible_winrm_transport: kerberos              # or ntlm (not on a FIPS system)
ansible_winrm_message_encryption: always       # encrypted by Kerberos / NTLM, or no connection
```

- **Certificate validation** (HTTPS). `validate` means the EE checks the server's WinRM certificate against the CAs it trusts. EEs usually do not include your organisation's root CAs, so `validate` fails with `CERTIFICATE_VERIFY_FAILED` until you add your CA bundle to the EE and point `ansible_winrm_ca_trust_path` at it (the path inside the EE, as shown above). **Use this setting for real servers.** `ignore` keeps the traffic encrypted but does not check who the server is, so anyone who can intercept the connection could pose as it: use it **only** for a short test on a lab network, then switch back.
- **Hosts.** Add them by full name (`web01.yoursite.mil`); Kerberos needs the full name.
- **Groups.** Use whatever helps: by site, by role (`win_dc`, `win_web`...). The settings below can be set per group. `inventories/example-windows/hosts.yml` shows an example.

Linux and Windows do not mix: the Linux templates skip Windows servers, and the Windows templates skip Linux servers. So a template pointed at the wrong inventory changes nothing and opens no tickets.

Step 5. Test the connection

Create a job template, then launch it with **Limit** set to one server:

Field	Value
Name	`Windows connection test`
Inventory	`Windows servers`
Project	`site-automation`
Playbook	`playbooks/win_connection_test.yml`
Execution environment	one with `pywinrm` (step 2)
Credentials	`Windows (WinRM)`
Limit	empty, **Prompt on launch** ticked

A good result ends with:

```
Connected: WEB01 (Microsoft Windows Server 2022 Standard, build 20348), domain yoursite.mil
PowerShell 5.1.20348.2849, FullLanguage
Logged on as yoursite\svc_aap; local administrator: yes
OK: the Windows runbooks can run here.
```

`ConstrainedLanguage` instead of `FullLanguage` means WDAC or AppLocker restricts PowerShell on that server. The check scripts are written and tested for that mode; only two optional parts are skipped in it (TLS endpoints and the search for missing updates). Whether Ansible itself can run on such a server depends on your ansible-core version and the policy: if this test got through and printed its result, it can.

Step 6. The job templates

For all of these, use: **Inventory** `Windows servers`, **Project** `site-automation`, the EE from step 2, **Credentials** `Windows (WinRM)`, **Limit** empty with **Prompt on launch** ticked. Leave **Variables** empty: with no `target`, they run on every server in the inventory.

Windows health check

Field	Value
Playbook	`playbooks/win_health_check.yml`
Survey: `health_checks`	*Multiple Choice (multiple select)*: `daily`, `weekly`, `all`, `disk`, `services`, `performance`, `time`, `network`, `eventlog`, `security`, `audit`, `accounts`, `certs`, `patching`. Default `daily`

Windows troubleshoot

Field	Value
Playbook	`playbooks/win_troubleshoot.yml`
Survey: `ts_area`	`overview`, `disk`, `performance`, `service`, `network`, `login`, `time`, `logs`, `updates`, `security`. Default `overview`
Survey: `ts_service`	*Text*, not required. "Service name (for area = service), e.g. W3SVC"
Survey: `ts_target`	*Text*, not required. "host:port it cannot reach (for area = network)"
Survey: `ts_hours`	*Integer*, default 2. "How many hours of event logs to read"

Each command's output appears under a `### what it shows` line, followed by the matching health checks. Findings do not fail this job.

All settings of this job, with their defaults: win_troubleshoot.

Windows certificate report

Field	Value
Playbook	`playbooks/win_cert_report.yml`
Survey	none

It reads **every machine store** (`Cert:\LocalMachine\*`), not only Personal, Web Hosting and Remote Desktop. *Automatically select the certificate store* puts a `.cer` file in **Trusted Root**, **Intermediate Certification Authorities** or **Other People**, so a certificate imported that way is found too:

- **With its private key** (the server's own certificate, in an unusual store): checked like the ones in Personal: a warning within 30 days, critical within 7, a ticket.
- **Without** (a certificate the server trusts): in the table as `LocalMachine\Root (Trusted Root Certification Authorities) (trust store)` when it expires within `win_check_certs_notice_days` (60) or expired in the last `win_check_certs_expired_report_days` (30). Never a finding or a ticket: its CA renews it. The older Windows roots that expired long ago are left out.
- **In use** (an https binding, the WinRM listener): always checked, whatever its store.
- **Remote Desktop: left out.** Windows (or your GPO's autoenrollment) renews these itself, so they are not in the report, the findings or the renewal: the **Remote Desktop** store (the self-signed one RDP makes), the certificate RDP uses, and one whose only purpose is *Remote Desktop Authentication*. One also used by an https binding or WinRM is still checked. `win_check_certs_remote_desktop: true` checks them like the others (weekly health check too).
- **Never read:** `Disallowed` (the untrusted certificates), `AuthRoot` (the roots Windows Update keeps), `REQUEST` (pending requests: a CSR's new key) and `SMS` (the MECM client's own certificates, which it renews itself): `win_check_certs_trust_skip_stores`.


`win_check_certs_trust: false` in the template's Variables reads only `win_check_certs_stores`. The weekly health check reads only those stores. To list what a server has, on the server: `Get-ChildItem Cert:\LocalMachine -Recurse | Where-Object NotAfter -lt (Get-Date).AddDays(60) | Format-List PSParentPath, Subject, NotAfter, HasPrivateKey`.

Windows certificate renewal - CSRs

With `cert_renew_servicenow: catalog` the CSRs are ordered from your PKI's catalog item instead of going on incidents: CERT_RENEWAL_CATALOG.md. Then the issued certificate is installed from that request, after an approval - `certreq -accept` and each binding of the old certificate moved: *Windows certificate install* (CERT_INSTALL.md).

Field	Value
Playbook	`playbooks/win_cert_renew_csr.yml`
Credentials	the Windows machine credential (an administrator: `certreq -machine` writes to the machine key store), `ServiceNow API`
Variables	`servicenow_assignment_group: <your PKI or Windows team>`: who gets a ticket this job opens (a certificate with no ticket yet)
Job type	try it as **Check** first: it makes and sends nothing

The Windows twin of the Linux renewal (RUNBOOKS.md, "Certificate renewal"). Put it in the weekly workflow after the tickets step, so each CSR lands on the ticket the report opened:



For each certificate the report flags (within `win_check_certs_warn_days`, 30 days, or expired) that is the server's own: in Personal or Web Hosting, or in any machine store with its private key. Remote Desktop's certificates are not in the report, so they get no CSR (`win_check_certs_remote_desktop: true` puts them in both).

1. **On the server**, `certreq -new -machine` makes a new key in the machine key store and a CSR. The CSR has the same subject, names (subjectAltName: DNS, IP, e-mail, URL) and purposes (EKU) as the old certificate. The key is RSA 2048 (`win_cert_renew_key_bits`); a bigger old key keeps its size, and an EC certificate gets a new key on the same curve. The key **cannot be exported** (`win_cert_renew_exportable: false`) and never leaves the server. Until the issued certificate is installed, it waits as a pending request (certlm.msc > *Certificate Enrollment Requests*). The CSR, with its `.inf` and a `.json` saying which certificate it renews, goes in `C:\ProgramData\site-automation\renew` (`win_cert_renew_dir`, administrators and SYSTEM only).
2. **On the ticket**, the CSR is attached (as for Linux: a refused `.csr` is tried again as `.txt`), with a work note saying what to do. Step 3 of that note is the Windows one: `certreq -accept -machine <issued>.cer` on the server, as an administrator. That pairs the certificate with its key and puts it in Personal. Then use it where the old one is used, and the note says how:
   - the https binding (IIS Manager, or `netsh http update sslcert`)
   - the WinRM HTTPS listener AAP connects through (`Set-Item WSMan:\localhost\Listener\...\CertificateThumbprint`)
   - Remote Desktop (with `win_check_certs_remote_desktop: true`)
3. **A run again** finds the pending request and reuses its CSR, so nothing changes on the ticket. Once the new certificate is installed, the old one is passed over: *a newer certificate for the same subject is in the store already: use it, then remove the old one*.

Never renewed here (each listed in the job output with the reason):

What	Why
a trust store's certificate (Trusted Root, Intermediate CAs, Other People ... without its key)	one the server trusts, not its own: its CA renews it
a CA certificate	a CA has no CSR from you
a self-signed certificate (unless `win_cert_renew_self_signed: true`)	it does not come from a PKI; with the setting on, the PKI issues a real one in its place (never one only for `localhost`)

What	Why
Remote Desktop's (its store, the one RDP uses, one only for Remote Desktop), unless `win_check_certs_remote_desktop: true`	Windows or the GPO renews them; not in the report
a certificate seen only on a port (`win_check_certs_endpoints`)	its store is not known: the one in its store gets the CSR
a host in `cert_renew_skip_hosts` / `cert_renew_skip_groups`	renewed by hand: still in the report
issued by `win_cert_renew_exclude_issuer`, not by `win_cert_renew_issuer`, or not matching `win_cert_renew_only`	your filters
names (subjectAltName) with an otherName (a UPN, a GUID) or a directory name	certreq cannot copy them from here: the job fails for that one certificate and says to make it by hand (certlm.msc > the certificate > *All Tasks* > *Advanced Operations*)

Every setting: win_check_certs (`win_cert_renew_*`).

Active Directory health report

For the domain controllers (group `win_dc`): one report for the whole domain - replication, dcdiag, FSMO, SYSVOL, DNS, time, and what changed in the last day. It needs an account with administrator rights on the DCs, in a credential of its own: ACTIVE_DIRECTORY.md. No such account? A plain domain user reads the domain from the AAP side instead (reader mode, 1.4.0): Without a domain admin.

Field	Value
Playbook	`playbooks/ad_health_report.yml`
Credentials	`Windows DCs (WinRM)`
Variables	`report_email_to: ad-team@yoursite.mil`

Step 7. Workflows and schedules

These are the same as for Linux, with the Windows templates. The full list, with every step and link, is in WORKFLOWS_AND_SCHEDULES.md (workflows 12 to 17):

Workflow	Steps	Schedule
Windows daily health	Windows health check (`daily`) › ServiceNow tickets (**Run always**)	every day 06:15
Windows weekly compliance	Windows health check (`weekly`) › tickets; Windows certificate report › its own tickets box (both **Run always**)	Monday 07:15
Windows patch with a dry run first	Windows health check (`disk`, `services`) › Windows patch as **Check** › *Approval* › Windows patch › Windows health check (`daily`) › tickets	monthly, inside the servers' ConfigMgr maintenance window

The ServiceNow tickets template runs on AAP itself, so it stays as it is.

Start small: the pilot order

Everything Windows here is new, so try it on **one** server that does not matter much, in this order, and widen only when each step looks right:

1. **Windows connection test**: the account, WinRM and PowerShell work.
2. **Windows health check**: the findings make sense for that server.
3. **Windows patch as Check** (the dry run): it lists what Software Center would install.
4. **Windows patch for real**, inside that server's ConfigMgr maintenance window.
5. **ACT for Windows - install** on the same server (tell your security team first, see below).

Every step can be a dry run first: DRY_RUNS.md.

Patching through Software Center

`playbooks/win_patch.yml` does, on each server, what an admin does in Software Center: install every software update your ConfigMgr admins deployed to it ("Install all"), required and available alike. AAP decides nothing about *which* updates: ConfigMgr does, as it does today. Applications listed in Software Center are not installed; only software updates are. Then:

1. **No automatic restarts** unless you ask for them with `automatic_restarts: yes` (the survey, or the template's Variables). Without it, the job installs the updates and lists the servers that need a restart: `A RESTART IS NEEDED to finish the updates ... automatic restarts are off`. A person restarts them (the post-check's `patching` finding keeps them visible). With it, the job restarts a server only when the updates or the ConfigMgr client say so, and never one in `win_patch_never_reboot_groups`.
2. **Prove the server is back** (after a restart, and also when none was needed). A new boot time, and every automatic service that ran before runs again - checked after every install and every restart, also a restart that was only pending with nothing to install. Delayed services get `win_patch_services_grace_min` (5 minutes) to start.
3. **Look again.** After a restart, servicing-stack and cumulative updates often reveal more updates. There is a second round (`win_patch_max_rounds: 2`), only when it restarted.

Safety.

- One server at a time (`win_patch_serial`, in the template's Variables - in `all.yml` it does nothing), and the rollout stops at the first server that fails.
- By default it only patches the group `win_patch_hosts`. Set `target:` in the template's Variables (for example `target: all`) and pick the servers with the Limit at launch.
- Servers in `win_patch_never_patch_groups` (default `no_patch`) are skipped.
- **Maintenance windows still apply.** Outside the server's ConfigMgr maintenance window, ConfigMgr holds the updates. The job then stops with `ConfigMgr will not install these now ... (waiting for a maintenance window)` instead of waiting forever. Run it inside the window, or ask the ConfigMgr admin for a window that covers the patch time.
- **A dry run first:** run the template as *Check*. It rescans and lists what it would install, and changes nothing (DRY_RUNS.md). The *Windows patch with a dry run first* workflow puts that list in front of the approver.

Needs: the ConfigMgr client (Software Center) on the servers, and full PowerShell (not Constrained Language Mode) for the install call. Restarts use `shutdown.exe`, and AAP watches the WinRM port go down and come back. No Ansible collection is needed.

Scheduling. With `target: all` and no Limit, a scheduled run patches every server in the Windows inventory, one after another. Choose that on purpose. Otherwise, make one schedule per group (for example the test servers the week before the others), each with its own Limit.

The job template:

Field	Value
Name	`Windows patch`
Playbook	`playbooks/win_patch.yml`
Credentials	`Windows (WinRM)`
Job type	Run, with **Prompt on launch** ticked (Check = the dry run)
Variables	`target: all` (or a group), and pick servers with the Limit
Survey: `automatic_restarts`	"Restart servers automatically when the updates need it?" Choices `no`, `yes`. Default `no`

If a server fails:

What you see	What to do
`has no working ConfigMgr client`	the SMS Agent Host service (CcmExec) is missing or stopped
`waiting for a maintenance window`	run inside the window, or ask the ConfigMgr admin
`these updates failed: ... (error 0x...)`	`C:\Windows\CCM\Logs\UpdatesDeployment.log` and `WUAHandler.log` on the server
`still not done after 120 minutes`	Software Center on the server; `C:\Windows\CCM\Logs\UpdatesHandler.log`
`did not accept a logon after the restart`	look at the server's console
`... ran before patching and do not run now`	the service did not come back: `Get-Service <name>`, System log

All settings of this job, with their defaults: win_patch.

ACT on the servers (C:\ProgramData\act)

`playbooks/win_act_install.yml` puts ACT for Windows (`vendor/act-windows/act.ps1`) on the servers in `C:\ProgramData\act` (setting `win_act_dir`). Run it again after you update this repository, and every server gets the new version.

The job template *ACT for Windows - install*: playbook `playbooks/win_act_install.yml`; your Windows inventory and its **Machine (Windows)** credential; the execution environment your Windows jobs use; **Prompt on launch** ticked for **Limit** and **Job type**. Launch it as **Check** with a Limit of one server first. To roll out group by group with an approval: workflow 15 in WORKFLOWS_AND_SCHEDULES.md.

- **Locked down.** Ordinary users may create folders and files in `C:\ProgramData` (and in `C:\temp`). Someone could then place, or swap, `act.ps1` before an administrator runs it, and their code would run with

administrator rights. So the job:

- refuses a `C:\ProgramData\act` that is a link (a junction or symbolic link) and changes nothing - the install and the removal stop with a plain message; remove the link itself, not its target (`rmdir` in cmd.exe), and run it again;
- takes ownership of `C:\ProgramData\act`;
- lets only Administrators and SYSTEM in (nothing inherited from `C:\ProgramData`);
- checks the file's SHA256 against the one in the repository, every run, and replaces it if it differs.
- **Unblocked.** The file is written on the server itself, so Windows never marks it as "downloaded from the internet", and the job runs `Unblock-File` on it anyway. Every run also checks it is not blocked, and fixes it if it is.
- **Using it on a server:** an administrator opens PowerShell and runs `powershell -ExecutionPolicy Bypass -File C:\ProgramData\act\act.ps1`. The first time, `:setup` asks for their own GenAI or Ask Sage key and keeps it in their profile. No key is put on the server for everyone.
- **Dry run:** run as *Check* and it says what it would install or fix. To remove it: `win_act_state: absent`.
- **Tell your security team before the first run.** The installer is a large PowerShell script that writes a `.ps1` file, and some endpoint-protection products (Defender for Endpoint, Trellix) flag that pattern. Let them know it is coming from AAP, and try one server first.
- **Versions and `:probe`.** ACT for Windows has the same endpoint formats and `:probe` command as the Linux one (see ADDING_ACT.md); the copy in `vendor/act-windows/` is refreshed when the repository's vendored ACT is. On Windows, an unattended run never approves the danger tier of commands: only a person at the prompt can. See APPROVED_COMMANDS.md.
- ACT itself needs full PowerShell. Where WDAC or AppLocker enforce Constrained Language Mode, ACT's own notes (sign it with your code-signing certificate) apply.

All settings, with their defaults: win_act.

Settings: what each check looks at, and how to change it

Every setting is in `roles/win_check_<name>/defaults/main.yml`, with a comment saying what it does. To change one:

- **for all Windows servers**, use the `Windows servers` inventory's **Variables** box;
- **for a group**, use the group's **Variables** box, or a settings file named after the group (for example `playbooks/group_vars/win_web.yml` for a group called `win_web`);
- **for one server**, use the host's **Variables** box.

The settings you will most likely want:

network: what every Windows server must resolve and reach

```
win_check_network_dns_names: [dc01.yoursite.mil]
win_check_network_tcp:
  - {name: LDAPS, host: dc01.yoursite.mil, port: 636}
  - {name: SIEM, host: siem.yoursite.mil, port: 9997}

# security: your endpoint protection's services (for example Trellix / McAfee)
win_check_security_av_services: [masvc, mfemms]

# audit: your log forwarding agent
win_check_audit_forwarder_services: [SplunkForwarder]

# accounts: who may be a local administrator (wildcards allowed)
win_check_accounts_admins_allowed: ['*\Administrator', 'YOURDOMAIN\Domain Admins',
  'YOURDOMAIN\svc_aap']

# services: more services that must run, on a group (for example IIS servers)
win_check_services_required_extra: [W3SVC, WAS]
```

A few defaults worth knowing:

- **disk**: warning at 85% used, critical at 95%. Per volume: `win_check_disk_overrides: {'D:': {warn: 92, crit: 98}}`.
- **services**: `EventLog`, `RpcSs`, `Dnscache`, `W32Time`, `WinRM` and `mpssvc` (the firewall) must run. Automatic services that stop cleanly by design are not reported.
- **security**: Defender is checked only when it is the active antivirus (`win_check_security_av: auto`). With another product, list its services instead.
- **certs**: warning 30 days before expiry, critical 7 days before. Old expired certificates that nothing uses are listed in the report, not raised as findings.
- **patching**: warning when the last update is 35 days old, critical at 60 days.

All settings, with their defaults: win_check_accounts, win_check_audit, win_check_certs, win_check_disk, win_check_eventlog, win_check_network, win_check_patching, win_check_performance, win_check_security, win_check_services, win_check_time.

If something goes wrong

What you see	What to do
`winrm or requests is not installed` / connection test: `no winrm`	the EE has no pywinrm: step 2
`CERTIFICATE_VERIFY_FAILED`	the CA bundle (step 4); `ansible_winrm_server_cert_validation: ignore` only as a short lab test
`the specified credentials were rejected by the server`	username format (`DOMAIN\user` for NTLM), password, or the account is locked
`Connection refused` / `timed out` on 5986	the firewall, or no HTTPS listener (step 1): a server with only HTTP takes port 5985 (step 4)
`kerberos: ... kinit` or `Server not found in Kerberos database`	no Kerberos in the EE, or a short host name: use NTLM, or full names
`ntlm: ... [digital envelope routines] unsupported`	the system is in FIPS mode: NTLM needs MD4 and RC4, which FIPS forbids. Use Kerberos (`svc_aap@YOURDOMAIN.MIL`, `ansible_winrm_transport: kerberos`)
`KDC has no support for encryption type` (Kerberos, FIPS)	the EE's Kerberos follows the host's FIPS policy and offers only AES with SHA-2, while Active Directory's keys are AES with SHA-1. Build your Windows EE with the file `/etc/krb5.conf.d/crypto-policies` removed and a file in `/etc/krb5.conf.d/` holding `[libdefaults] permitted_enctypes = aes256-sha2 aes128-sha2 aes256-sha1 aes128-sha1` (no RC4, no DES); check it inside the EE with `kinit svc_aap@YOURDOMAIN.MIL` - it asks for the password when Kerberos is fixed
`local administrator: NO`	add the account to the local Administrators group
`the <name> check could not run: ...`	the text after it is PowerShell's error. The other checks still ran
`skipping: no hosts matched`	the template's inventory is not `Windows servers`, or the Limit matches no server there
`... is not digitally signed` or `running scripts is disabled on this system`	a GPO sets the PowerShell execution policy for the machine (for example AllSigned), which overrides what Ansible asks for. Set it to RemoteSigned by GPO for these servers, or sign the scripts with your code-signing certificate

Not in this release (next)

- ACT in the Windows jobs: `use_act` on the Windows health check and troubleshoot (explain, propose fixes for approval), like on Linux. ACT is already on the servers (above).
- Service watch for Windows services and IIS application pools.
- Checks for IIS and SQL Server. (Domain controllers have their own report: ACTIVE_DIRECTORY.md.)

19. VMware jobs (vCenter): restart, snapshots, VLAN, reports, alarms and ACT

Small jobs for virtual machines, done through vCenter (they replace the vCenter runbooks of System Center Orchestrator):

Job template	Playbook	What it does
VM - restart	`playbooks/vm_reboot.yml`	restarts VMs. `guest` (default): the operating system restarts itself through VMware Tools. `hard`: a reset, like the reset button
VM - shut down	`playbooks/vm_shutdown.yml`	shuts VMs down and waits until they are off. `guest` (default) through VMware Tools; `hard`: power off at once
VM - snapshot	`playbooks/vm_snapshot.yml`	takes a snapshot **without memory** (the disks only). The AAP job number and user go into its description
VM - delete snapshot	`playbooks/vm_snapshot_delete.yml`	deletes one snapshot by its exact name, or every snapshot of the VM. Lists what the VM has first
VM - notes	`playbooks/vm_notes.yml`	edits the VM's Notes in vCenter: append a line (with date and user), replace, or clear. Prints the old notes
VM - change VLAN	`playbooks/vm_vlan.yml`	moves one network adapter to another port group (VLAN). The VM's other adapters are not touched
VM - secure boot report	`playbooks/vm_secure_boot_report.yml`	read-only: every VM's firmware and secure boot. Lists BIOS VMs and EFI VMs with secure boot off separately
VM - datastore report	`playbooks/vm_datastore_report.yml`	read-only: every datastore's capacity, free space, used and provisioned %; the ones at 85 / 90 % used listed apart
VM - inventory report	`playbooks/vm_inventory_report.yml`	read-only: every VM of every vCenter, by vCenter and folder - power, the ESXi host it runs on, cluster, guest OS, IP address, vCPUs, memory - and the count; the VMs without encryption, EFI or a vTPM; the hardware versions and VMware Tools; the email attaches every VM as an Excel workbook ("The VM inventory report")

Job template	Playbook	What it does
VM - VMware Tools inventory	`playbooks/vm_tools_report.yml`	read-only: every VM's VMware Tools version and status (current, upgrade available, not installed, not running, guest managed), hardware version and guest OS, by vCenter and folder; the Tools versions, hardware versions and guest OSes in use with how many VMs each; the email attaches every VM as an Excel workbook ("The VMware Tools inventory")
VM - right-sizing report	`playbooks/vm_rightsizing_report.yml`	read-only: every powered-on VM's vCPUs and memory next to what vCenter's statistics say it used (30 days, and its busiest days of the year) - too big, about right or too small, with a suggested size and how sure it is (High, Medium, Low); memory the host took back, guest disks nearly full; optional ACT review. Suggestions only ("The VM right-sizing report")
VMware - version report	`playbooks/vmware_version_report.yml`	read-only: the version and build of each vCenter and every ESXi host, the builds in use and how many hosts run each, the hosts by vCenter and cluster; amber when a host is newer than its vCenter; the email attaches every host as an Excel workbook ("The VMware version report")
VMware - hardware inventory	`playbooks/vmware_hardware_report.yml`	read-only: every ESXi host's vendor, model, serial number, BIOS version and date, CPUs, memory, ESXi build, image profile, NICs and storage adapters with their drivers, the drivers and firmware its hardware status shows, and every VIB; the models in use with their BIOS versions; the email attaches all of it as an Excel workbook ("The VMware hardware inventory")
VM - snapshot report	`playbooks/vm_snapshot_report.yml`	read-only: every snapshot of every VM - name, when taken and by whom, age, size, folder - oldest first; the ones 5 days or older listed apart
VM - snapshot cleanup	`playbooks/vm_snapshot_cleanup.yml`	deletes the snapshots 5 days or older - never "keep" ones, excluded VMs, datacenters or clusters, the AAP server or ones over 1 TB; or only the patching snapshots (`vm_snapshot_cleanup_name_words`) - then reports what it deleted. Best run in the workflow below, after an approval

Job template	Playbook	What it does
VM - refresh the pick lists	`playbooks/vm_pick_refresh.yml`	on a schedule, read-only in vCenter: writes what may be done right now - the snapshots that may be deleted, the VMs that may be restarted (or only the hung ones) - as the choices of a question in the survey of the templates below ("Pick lists")
VM - delete picked snapshots	`playbooks/vm_snapshot_delete_picked.yml`	deletes the snapshots picked in the survey, each checked again live; in its workflow: plan, approval, then exactly the plan
VM - restart picked VMs	`playbooks/vm_reboot_picked.yml`	restarts the VMs picked in the survey (`guest` or `hard`), each checked again live - never the AAP server; in its workflow: plan, approval, then exactly the plan
VM - health report	`playbooks/vm_health_report.yml`	read-only: every datacenter, cluster and host of every vCenter - vSphere HA and DRS working or not (HA agents, failover capacity, DRS recommendations and faults, vCLS retreat mode), hosts not connected or in maintenance, hardware sensors not green, hosts that need a restart, CPU and memory used, configuration issues and alarms - coloured, with what to do for each problem
VM - alarms report	`playbooks/vm_alarm_report.yml`	read-only: the triggered alarms on vCenter, datacenters, clusters and hosts; the alarms that fired in the last 24 hours (also the ones that cleared since); hosts not connected; the last 24 hours' failed logins, VM shutdowns / HA restarts and other errors and warnings; configuration issues - coloured by severity
VM - alarms ACT analysis	`playbooks/vm_alarm_act_analysis.yml`	read-only: the same problems, with ACT's likely cause, fix and confidence for each. ACT runs on the AAP side, never on the hosts

Job template	Playbook	What it does
VM - ask a question	`playbooks/vm_ask.yml`	read-only: a question in plain words (*all VMs with dbv in the name*, *VMs on datastores under 10% free*, *hosts in maintenance mode*) - GenAI turns it into a query the job checks against a whitelist, the job reads every vCenter and answers, joins of VMs, hosts, clusters, datastores, snapshots, alarms, virtual disks and guest drives included; power, last restart, last vMotion, disk sizes and free space. A question that asks for a change is refused. VM_ASK.md
VM - outage watch	`playbooks/vm_outage_watch.yml`	every 5 to 15 minutes, read-only: is something down or hung right now - a host not responding, an HA agent isolated, a datastore not accessible, all paths down, an HA restart or failure, a VM waiting on a question, a hung VM (no heartbeat AND no answer on the network). One line when clean; a report, a ServiceNow incident and a red job when not. Restarts nothing (phase 1). VM_OUTAGE_WATCH.md
VM - vCenter log analysis	`playbooks/vm_log_analysis.yml`	read-only: vCenter's own log and each ESXi host's (hostd, vmkernel, vpxa), read through vCenter's API - no SSH - grouped into patterns across hosts, with ACT's likely cause, fix and confidence for each (LOG_ANALYSIS.md)
VM - capacity planning	`playbooks/vm_capacity_report.yml`	read-only: overall and per cluster - CPU, memory (also with a host down), vCPUs per core, VMs that still fit, hosts recommended, datastores - with growth from vCenter's own history and the days until each limit; optionally GenAI's estimate next to it
VM - deploy from ServiceNow ticket	`playbooks/vm_deploy_from_ticket.yml`	builds the VM - or VMs, one per name - a ServiceNow ticket asks for, from a template - checked against your rules, placed by site, name rule or free room, the result on the ticket. Best run in its workflow (propose, approval, build)

Job template	Playbook	What it does
VM - deploy settings finder	`playbooks/vm_deploy_inventory.yml`	read-only: every vCenter's datacenters, clusters, templates, datastores, folders and networks, by the names the deploy's settings use - with the lines to paste into the deploy template's Variables
VM - pick up deploy tickets	`playbooks/vm_deploy_poll.yml`	on a schedule: finds new VM request tickets in ServiceNow and starts the deploy workflow for each. Builds nothing itself; the approval stays
VM - VMs created report	`playbooks/vm_created_report.yml`	read-only: how many VMs were created in the last 7 days and each one - when, by whom, how (cloned, deployed from a template, new), the ticket when the AAP deploy built it, where, its size - by person and by day, and the ones created and deleted since. Schedule it weekly (e.g. Fridays at noon)
ESXi - security settings	`playbooks/esxi_security.yml`	on every ESXi host: SSH off, the shell timeouts at 600 s, lockdown mode normal; the vCenter appliance's SSH Login, DCUI, Console CLI and Bash Shell when set (`esxi_security_vcsa_*`). Changes only what differs, so it can run every night and puts back whatever drifted
ESXi - network check	`playbooks/esxi_network_check.yml`	read-only: every host's VMkernel adapters and MTUs; vmkping between the hosts of each cluster on the vMotion network, full size with don't fragment (jumbo frames proven end to end); pings to targets you name; the storage latency each host sees. No VM is moved ("The ESXi network check")
VMware - certificate report	`playbooks/vmware_cert_report.yml`	read-only: every certificate of vCenter and its ESXi hosts, soonest expiry first, and for each one due what the renewal would do. Never ServiceNow, never a CSR
VMware - certificate renewal	`playbooks/vmware_cert_renew.yml`	the certificates of vCenter and every ESXi host: each one that expires within 30 days gets a ServiceNow incident, and a CSR - made where its key stays, by vCenter or the host - attached to it with what to do next. The days can be raised to try it on certificates years from expiring

Job template	Playbook	What it does
VMware - certificate request	`playbooks/vmware_cert_request.yml`	on demand, for the vCenters and hosts you name: a CSR made where the key stays, ordered from the PKI's catalog item now - the job prints the request (RITM)
VMware - certificate install - check / approved	`playbooks/vmware_cert_install_check.yml` , `vmware_cert_install_approved.yml`	the certificate the PKI put on the catalog request (the RITM you name) of a CSR of vCenter or a host, installed there after an approval: the hosts in use (the CA chain in vCenter's trusted roots, the host reconnected, vCenter must show it), then vCenter's Machine SSL certificate (port 443 must serve it)

They run on the AAP side and talk to vCenter. They never log in to the VMs.

Never the AAP server. Restart, shut down and VLAN change refuse the AAP server's VM. A job would cut off the system running it, and AAP must never be restarted from AAP. The VM is recognised by its name, its guest host name or its IP address, matched against the hosts in your inventory groups `aap` and `aap_hosts`. If the template's inventory has no such group and you have not named the AAP VM (below), these three jobs refuse to run at all. Snapshots, notes and the report are allowed on every VM, since they do not stop it.

Before you start

1. The execution environment must have the VMware collection

The jobs use Red Hat's certified collection `vmware.vmware` (2.11 or later) and its Python libraries (pyVmomi and the vSphere Automation SDK). Find out whether your execution environment (EE) has them. On the AAP server, as the user AAP runs as:

```
podman images | grep -i ee-
podman run --rm <the EE image your templates use> ansible-galaxy collection list vmware.vmware
podman run --rm <the EE image your templates use> python3 -c "import pyVmomi, vmware.vapi;
  print('ok')"
```

- **Both answer:** nothing to do.
- **Not there:** build an EE that has it, with `ansible-builder`. Start from your AAP version's `ee-minimal` image, and pull the collection from your Private Automation Hub when the network is air-gapped. ansible-builder reads the collection's Python requirements by itself:

execution-environment.yml

```
version: 3
images:
  base_image:
    name: registry.redhat.io/ansible-automation-platform-27/ee-minimal-rhel9:latest
dependencies:
  galaxy:
    collections:
      - name: vmware.vmware
```

Then in AAP: **Execution Environments > Add** (the image you pushed). Pick it on the VM templates. The all-in-one EE has it, with everything else: EXECUTION_ENVIRONMENT.md.

Do **not** add a `collections/requirements.yml` to this repository for it. AAP would then try to download from Galaxy on every project sync, and on an air-gapped network every sync would fail.

vCenter 7 or 8 is needed: the jobs also use vCenter's REST API.

2. A vCenter account for AAP

A service account with a vCenter role that has only what the jobs need:

Job	vCenter privileges
restart	Virtual machine > Interaction > Reset
shut down	Virtual machine > Interaction > Power off
snapshot / delete snapshot	Virtual machine > Snapshot management > Create snapshot / Remove snapshot
notes	Virtual machine > Change configuration > Set annotation
change VLAN	Virtual machine > Change configuration > Modify device settings, and Network > Assign network on the port groups
ESXi network check (the pings)	Host > CIM > CIM interaction, on the hosts: the pings run as esxcli on each host through vCenter. Without it the report says so once, and still shows the adapters and the storage latency
ESXi security settings	Host > Configuration > Security profile and firewall (the SSH service), Advanced settings (the timeouts), Change settings (lockdown mode and its exception users). If one is missing, the job's error names it (e.g. `lacks the privilege Host.Config.Settings`)
ESXi security settings: the vCenter appliance's access (`esxi_security_vcsa_*`, since 0.68.0)	the account in the single sign-on group **SystemConfiguration.Administrators** (Administration > Single Sign On > Users and Groups > Groups > SystemConfiguration.Administrators > Add members); administrator@vsphere.local is in it. Without it vCenter answers 403 and the job says so
certificate renewal: an ESXi host's CSR	Certificates > Manage certificates, on the hosts. If it is missing, the job's error names it
certificate renewal: vCenter's CSR	Certificate Management (`CertificateManagement.Manage` and `CertificateManagement.Administer`), in a role given as a **Global Permission** - or the account in the single sign-on group **CAAdmins** (Administration > Single Sign On > Users and Groups > Groups > CAAdmins > Add members), as the vSphere Client's own CSR needs; administrator@vsphere.local has it
certificate install (since 0.71.0): a host's certificate, the CA chain in vCenter's trusted roots, vCenter's own	Certificates > Manage certificates (and Host > Configuration > Connection, to reconnect a host vCenter lost), on the hosts; Certificate Management (`CertificateManagement.Manage` and `CertificateManagement.Administer`) as a **Global Permission**, or the account in **CAAdmins** - for the trusted roots and the Machine SSL certificate. administrator@vsphere.local has them all
all (to read), and the alarms report	Read-only, which every vCenter role includes

Give it the role on the folders or clusters of the VMs these jobs may touch, and nowhere else.

3. The credential

AAP: **Credentials > Add**, type **VMware vCenter**: vCenter Host (its name, e.g. `vcsa01.yoursite.mil`), Username, Password. It hands the jobs `VMWARE_HOST`, `VMWARE_USER` and `VMWARE_PASSWORD`. Nothing about vCenter goes in Git.

vCenter's certificate: the jobs check it. If the EE does not trust your CA, a job fails with `certificate verify failed`. The right fix is to add your CA to the EE. Until then, `vmware_validate_certs: false` turns the check off, in the template's Variables (not recommended).

Several vCenters: the reports (alarms, datastores, snapshots and their cleanup, capacity planning) and the ESXi security settings read **every vCenter in one job, into one report**: keep one VMware vCenter credential and list the vCenters in `vmware_vcenters` (see "Several vCenters, one report" below). The jobs that act on VMs by name (restart, shut down, snapshot, notes, VLAN, secure boot) still use the credential's vCenter only: for a VM in another vCenter, use a second credential with that vCenter's address, or tick **Prompt on launch** for Credentials and pick it at launch.

5. Several vCenters, one report

With two or more vCenters (for example in Enhanced Linked Mode, as one tree in the vSphere Client), list them all in `playbooks/group_vars/all.yml` (for every job) or in a template's Variables:

```yaml
vmware_vcenters: [vc01.yoursite.mil, vc02.yoursite.mil]
```

- **One credential** is enough: the jobs log in to every vCenter with its user name and password. In Enhanced Linked Mode the vCenters share single sign-on, so the same account works on all of them. Give its role as a **Global Permission** (vSphere Client: **Administration > Access Control > Global Permissions**), or on each vCenter's root with **Propagate to children**.
- The credential's own vCenter is always read. Listing it again (or by another name, its IP) is fine: each vCenter is read once.
- A vCenter on another port: `vc03.yoursite.mil:8443`.
- **The report:** one email for all. The **Datacenter** column says which vCenter (`vc02 / DC1`); the footer lists the vCenters read. A cluster or datastore name that exists in two places is shown with its vCenter and datacenter, e.g. `PROD (vc02 / DC1)`, and never added together.
- **A vCenter that cannot be read** (down, a firewall, a refused login) does not stop the others: the report covers the others, lists it in red on top ("vCenters not read") and its title ends with "- 1 vCenter(s) not read". The job stays **green**: the report completed (`vmware_vcenter_fail_unread: true` makes it fail, e.g. for a workflow's failure path).
- **Snapshot cleanup:** each snapshot is deleted on its own vCenter. A VM's ID repeats in every vCenter (both have a `vm-42`), so the report hands the cleanup the vCenter with each snapshot, and the cleanup deletes only that one.
- The ESXi security settings set the hosts of every vCenter listed.

4. Name the AAP VM (and vCenter's)

In your `playbooks/group_vars/all.yml`:

```yaml
vmware_protected_vms: [AAP01, VCSA01]      # the exact VM names in vCenter
```

This covers the case where the AAP VM's name differs from its host name and VMware Tools is not running, so neither the guest host name nor the IP is known. More groups to refuse: `vmware_protected_groups: [aap, aap_hosts, my_group]` (aap and aap_hosts are always refused anyway). Given as text (a survey, an extra variable), both are names separated by commas or line breaks - not spaces: `File Server 01, VCSA01` is two VMs, `dcs` one group. The same list holds for restart, shut down, VLAN change, the snapshot cleanup and the snapshot pick list; each of them is refused when the inventory has no `aap` (or `aap_hosts`) group and `vmware_protected_vms` is empty.

A name that matches no VM is said. A typo in `vmware_protected_vms` protects nothing. Restart, shut down, VLAN change and the snapshot cleanup read every VM's name in each vCenter they use (one read per vCenter). Each protected name, or pattern, that matches none is a warning line (`WARNING: ...`) in the job's output and on top of its report:

```
Protected name matches no VM: VCSA1 - check the spelling
Excluded name matches no VM (vm_snapshot_cleanup_exclude_vms): NOPE01 - check the spelling
Protected group not in this inventory: dcs (vmware_protected_groups) - check the spelling
```

It never fails the job and never changes what it does. When the names cannot be read, it says *Could not check the protected names* once. `vmware_protected_check: false` turns the check off.

How a list written as text is read (a survey, an extra variable; a YAML list is used as it is): names are separated by commas, semicolons, tabs or line breaks - never spaces. A list as YAML or JSON writes it (`[AAP01, VCSA01]`, `- AAP01` lines) gives its names; a quoted name is one name, its commas too (`"Server, Main"`), curly quotes from Word, Outlook or Teams as well; a pattern's brackets stay in it (`vm[0-9]*`), and `[Test] VM01` is a name that matches itself. A `#` is part of a name (`Build #3`); only a line that starts with `#` is left out. A name with a `;` is also read whole (a VM's name may have one). A `[` that is not closed on its line is a plain character: the names after it are still read one by one (`vm[0-9*, AAP01` gives `vm[0-9*` and `AAP01`). And every name 1.22.0 read from the same text still counts, beside the names read the new way - a text is never read as fewer names than before; the warnings above name only the names as you wrote them.

Which VMs a job acts on

You type them. Every job (except the report) asks for **VM names**, one per line: one VM, or several. These are the names as vCenter shows them in its inventory. They are exact, upper/lower case included, with no wildcards.

The job runs on the AAP server and asks vCenter for each name. It does **not** use the template's inventory hosts or a Limit to choose VMs; it uses the inventory only to recognise the AAP server. So a VM does not have to be in any AAP inventory to be restarted or snapshotted.

- Names that do not exist, or exist twice in vCenter, stop the job before anything is done.
- With several VMs, every check is done for all of them first. If one is refused (the AAP server, no VMware Tools for a clean restart), nothing is done to any of them.
- Several VMs are handled in the order given. Restarts are requested one right after the other, without waiting for each to come back up, so restart the members of a cluster (two database nodes, for example) in separate runs. A shutdown waits for each VM to be off before the next.

The templates

Make one job template per job:

- **Inventory:** your Linux inventory, the one with the group `aap`. The jobs need it for the AAP check; they run nothing on its hosts.
- **Credentials:** the VMware vCenter credential.
- **Playbook:** one of the files in the table at the top.
- **Execution environment:** the one with `vmware.vmware`.
- **Limit:** leave it **empty** and do **not** prompt for it. These jobs run on the AAP side (`localhost`); a Limit, or a workflow's Limit, would make them skip without doing anything.
- **Job type:** tick **Prompt on launch** if you want dry runs. As **Check**, every job says what it would do and changes nothing.

Surveys (**Survey > Add**, then switch the survey **on**):

Template	Question (variable)	Type	Default / choices
all but the report	VM names, one per line (`vm_names`)	Textarea, required	
restart, shut down	How (`vm_power_mode`)	Multiple choice	`guest`, `hard`; default `guest`
snapshot	Snapshot name (`vm_snapshot_name`)	Text, optional	empty = `aap-<date>-<time>`
snapshot	Why / change number (`vm_snapshot_description`)	Text	
delete snapshot	Snapshot name (`vm_snapshot_name`)	Text	
delete snapshot	Delete ALL snapshots (`vm_snapshot_delete_all`)	Multiple choice	`false`, `true`; default `false`
notes	Text (`vm_notes`)	Textarea	
notes	How (`vm_notes_mode`)	Multiple choice	`append`, `replace`, `clear`; default `append`
change VLAN	Network adapter number (`vm_nic`)	Integer	`1`
change VLAN	Port group (`vm_portgroup`)	Text, required	its name as vCenter shows it
any (optional)	Email the result to (`report_email_to`)	Text, not required	empty = no email ("Email the report" below)

The secure boot and datastore reports need no survey. Schedule them weekly with `report_email_to` in their Variables. They stay green when they find VMs or datastores to fix - the report and email say which; `vm_secure_boot_fail: true` / `vm_datastore_fail: true` mark the job failed instead, for a notification on failure (the *ServiceNow tickets* job does not take these reports' results). `vm_secure_boot_folder` limits the secure boot report to one vCenter folder; `vmware_datacenter` limits either report to one datacenter; `vm_datastore_warn_pct` / `vm_datastore_crit_pct` (85 / 90) set the datastore thresholds.

The VM inventory report

VM - inventory report (`playbooks/vm_inventory_report.yml`) lists every VM of every vCenter (`vmware_vcenters`; `vmware_datacenter` for one datacenter) - no survey, read-only. At the top, the counts: VMs, powered on, powered off, folders, ESXi hosts, vCenters - and how many VMs are **not encrypted**, **without EFI** and **without vTPM**. Then:

- **VMs without encryption, EFI or vTPM** - one row per VM that lacks any of the three, the most missing first: Encrypted, Firmware (EFI or BIOS), Secure Boot and vTPM as chips (a word and its mark - a check for OK, ! for missing - never colour alone), then its vCenter, folder, power, guest OS and hardware version. *Encrypted* is VM Encryption (vCenter's `config.keyId`: a key from a key provider); *Secure Boot* needs EFI (`config.bootOptions.efiSecureBootEnabled`); the vTPM is vCenter's `summary.config.tpmPresent`, or - a vCenter older than 6.7 - a Virtual TPM among the VM's devices (read only for those VMs). A vTPM vCenter could not tell shows `?` and is not counted.
- **Hardware versions and Tools** - how many VMs have each virtual hardware version (`vmx-21` shown as 21, with the oldest ESXi that runs it) and each VMware Tools status: current, upgrade available, unsupported, not installed, not running (a powered-on VM whose Tools do not run), guest managed (open-vm-tools, updated with the OS).
- **VMware Tools to upgrade or not running** - the powered-on VMs whose Tools need an upgrade, are not supported, not installed or not running, with the Tools version (`12.3.5`, from vCenter's number for it).
- a table per vCenter and folder (`vc01 - DC1 / Linux / Web`, as vSphere's *VMs and Templates* view shows it; a VM in no folder under `DC1 (no folder)`), each VM with its power state, the ESXi host it runs on, cluster, guest OS, IP address, vCPUs and memory.

On the report website the VM tables also have Encrypted, Firmware, Secure Boot, vTPM, hardware version, Tools status and Tools version - short headers (`Enc`, `EFI`, `SB`, `vTPM`, `HW`, `Tools`, `Tools ver.`; the full name when you point at one, in the Columns menu and on a phone's cards), the ESXi host by its short name. **Columns** above each table hides any of them; the choice is kept in your browser for every VM table, this report and the next. `vm_inventory_hidden_columns` starts some hidden (Secure Boot and Tools version: the tables then fit a 1366 px laptop screen beside the sections list); the Columns menu still lists them. An email cannot hide columns: its VM tables keep the lean list above, and the new fields are in its sections and the workbook. (The website's other looks - `report_web_theme` standard, command, portal, glass - have no Columns menu and show the email's tables.)

The email attaches every VM as an Excel workbook, `vm-inventory-report_2026-10-27.xlsx`: one sheet, a line per VM with its vCenter, datacenter and folder too, and Encrypted, Key provider, Encrypted vMotion (`disabled`, `opportunistic`, `required` - in the workbook only), Firmware, Secure Boot, vTPM, Hardware version, Compatible with, VMware Tools, Tools version and Tools running - to sort and filter. Schedule it weekly with `report_email_to` on its Variables; on the report website it is on the VMware tab.

Setting	Default	
`vm_inventory_templates`	`false`	`true` = templates counted and listed as VMs (else left out, their number in the subtitle)
`vm_inventory_by_folder`	`true`	`false` = one table of every VM, with vCenter and folder columns
`vm_inventory_max_rows`	`2000`	VMs listed in the email and on the page at most (2000 make an email of about 2.5 MB) - the workbook always has every VM
`vm_inventory_xlsx`	`true`	`false` = no workbook attached

Setting	Default	
`vm_inventory_security`	`true`	read each VM's encryption, Secure Boot and vTPM: the section, its three counts, the website's columns and the workbook's (`false`: not read - the firmware, hardware version and Tools still are)
`vm_inventory_security_skip_templates`	`true`	templates left out of that section and its counts (when `vm_inventory_templates` lists them)
`vm_inventory_security_skip_off`	`false`	`true` = powered-off VMs left out of that section and its counts
`vm_inventory_hidden_columns`	`[SB, Tools ver.]`	the website's VM tables: these columns start hidden - a header or its full name (`Secure Boot`), any column (`Cluster`); a list, or text with commas. `[]` = all shown

Green unless a vCenter could not be read (it is then listed in red on top, its VMs not counted): the counts of VMs without encryption, EFI or a vTPM are information (blue), never a warning. The counts are also the job artifact `vm_inventory`. The account needs nothing more than for the rest of the report (Read-only on the VMs): VM Encryption's key ID, the boot options and the vTPM are read with the VM's other properties.

The VMware Tools inventory

VM - VMware Tools inventory (`playbooks/vm_tools_report.yml`) lists every VM of every vCenter (`vmware_vcenters`; `vmware_datacenter` for one datacenter) with its **VMware Tools version**, **hardware version** and **guest OS**, by vCenter and **folder** - no survey, read-only; the read-only vCenter account is enough. At the top, the counts: VMs, Tools current, upgrade available, guest managed, no Tools, not running, not supported, how many Tools and hardware versions. Then:

- **To look at** - powered-on VMs with no VMware Tools, Tools not running, or a Tools version vCenter does not support on the host the VM runs on (too old, too new, or one with a known problem);
- **VMware Tools versions** - each version (`12.3.5`), how many VMs run it and how many are on, what vCenter says of it (current, upgrade available ...) and how it was installed (open-vm-tools, MSI on Windows);
- **Hardware versions** - each virtual hardware version (`vmx-21`), the oldest ESXi that runs it (`ESXi 8.0 U2 and later`), how many VMs;
- **Guest OS** - each guest OS with the Tools and hardware versions its VMs have;
- a table per vCenter and folder (`vc01 - DC1 / Linux / Web`, as in the VM inventory report), each VM with its power state, guest OS, Tools version, Tools status and hardware version; an upgrade available in blue, a VM to look at in amber.

Tools status is vCenter's own verdict for the ESXi host the VM runs on (`guest.toolsVersionStatus2`): *current*, *upgrade available*, *too old (not supported)* ... The report keeps no list of versions of its own. **Guest managed**: open-vm-tools installed from the guest's OS (RHEL, most Linux) - it is updated with the OS (`dnf update`), not from vCenter, and vCenter does not judge its version. The **guest OS** is the one VMware Tools reports (`Red Hat Enterprise Linux 9.4 (64-bit)`), else the one the VM is configured with; the workbook has both. A VM that is off keeps the Tools version vCenter last saw, and is not listed under *To look at*.

The email attaches an Excel workbook (`vm-vmware-tools-inventory_2026-11-03.xlsx`): **VMs** - a line per VM with its vCenter, datacenter, folder, power, both guest OS names, Tools version, status (in words and as vCenter says it), running or not, how it was installed, heartbeat, hardware version, what it is compatible with, firmware, ESXi host, cluster and IP address; **Tools versions** and **Hardware versions** with their counts.

Amber when a VM is to look at; red only when a vCenter could not be read. The job output has a line per Tools version (`VMware Tools 12.3.5: 140 VM(s) - current (120), guest managed (updated by the OS) (20)`), per hardware version, and each VM to look at; the artifact `vm_tools` has the versions and the counts.

Set it up: a template *VM - VMware Tools inventory*, playbook `playbooks/vm_tools_report.yml`, the VMware vCenter credential (read-only is enough), the execution environment of your other VMware jobs, no Limit, no survey; `report_email_to` on its Variables, and a schedule (monthly, or after patching). On the report website it is on the VMware tab.

Setting	Default	
`vm_tools_templates`	`false`	`true` = templates counted and listed as VMs (else left out, their number in the subtitle)
`vm_tools_by_folder`	`true`	`false` = one table of every VM, with vCenter and folder columns
`vm_tools_max_rows`	`2000`	VMs listed in the email and on the page at most - the workbook always has every VM
`vm_tools_xlsx`	`true`	`false` = no workbook attached

The VM right-sizing report

VM - right-sizing report (`playbooks/vm_rightsizing_report.yml`) puts every powered-on VM's vCPUs and memory next to what it actually used, and suggests a size: **too big**, **about right** or **too small**. It reads vCenter's own statistics only - the hypervisor's measurements, no login to the guests - so it needs nothing but the VMware vCenter credential, and it changes nothing: the suggestions are for you to act on, at a time you choose.

What it reads, per VM: the last 30 days of vCenter's past-month statistics (2-hour averages) - CPU used, CPU ready, active memory, consumed, ballooned and swapped memory - and its busiest days of the last year (daily averages), so a month-end or yearly peak keeps its size. Statistics level 1, vCenter's default, is enough (swapped memory needs level 2; the report says when something is missing). VMware Tools' guest disks are read too.

How it decides (each number is a setting below):

- **CPU** (firm: the hypervisor measures it). The busiest 5% of the time is left out (the 95th percentile); vCPUs are suggested so that use would be about 70%, an even number from 4 up, never fewer than 2, never more than half fewer at once.
- **More vCPUs or memory** only from the last 30 days, and only from a pattern: 85% CPU (90% active memory) or more at the 95th percentile, **and** busy on 3 separate days or more (`vm_rightsize_grow_days`; a day counts when its busiest 2-hour average got there). Busy on fewer days: the VM is listed under *Watch: busy on a few days* - not enough to grow; ballooned or swapped memory is said on its own.
- **The year's busiest day never adds**: it only holds a cut back (a month-end peak keeps the vCPUs it needs), and the reason says how many days of the year were within 10 points of it

(`vm_rightsize_year_near_pts`) - *a one-off*, or a pattern. A day above 100% is not a real reading: it is left out (the next busiest is used) and said in the reason. A day's average is a percent of the vCPUs (or memory) the VM had **that day**: vCPUs added since then make an old day read high, which only holds a cut back; vCPUs removed since make it read low.

- **CPU ready** is time the VM waited for a physical CPU. 5% or more is said: on a VM that is too big it usually means too many vCPUs; on a busy one, a busy host - check the host before adding vCPUs.
- **Memory** (the less certain one). vCenter sees the memory a guest touched in the last minutes (active memory), not what it needs - file caches and databases want more. So the suggestion is active memory plus 100%, never more than half less at once, at least 2 GB (Windows 4), and only when it is 25% and 2 GB smaller or more. Active memory at 90% or more of what the VM has is too small.
- **Memory taken back**: a VM the host ballooned or swapped (100 MB or more), or one with a memory limit below its size, is listed apart - that is its host or the limit, not the VM's size.
- Fewer than 7 days of statistics (a new VM): **not enough history**, no suggestion.
- **Confidence** of each suggestion: *High* with no doubt, *Medium* with one, *Low* with two or more. A doubt: fewer than 21 days of history (`vm_rightsize_conf_days`); a suspect day left out; the year's busiest day holding the cut back; the 95th percentile within 10 points of the line it crossed - the 70% target for a cut, the 85% / 90% mark for growth when it was busy on fewer than half the days (`vm_rightsize_conf_margin_pts`); less memory for a VM of 32 GB or more with 10% or less active (`vm_rightsize_conf_mem_large_gb`, `vm_rightsize_conf_mem_low_pct`) - active memory understates what databases and Java hold, so check the application's own memory setting first. Start with the *High* ones.
- When CPU ready is low on every VM, the report says so first: fewer vCPUs then free capacity for other VMs - they do not make anything faster.

The email (and the page on the report website's VMware tab) has the counts on top - VMs checked, too big, too small, about right, the vCPUs and memory the suggestions would free - then the tables: *Too small* (amber), *Memory taken back by the host*, *Too big* (the suggested size in green; each the most certain first, then the most freed), *Watch: busy on a few days*, *Guest disks nearly full*, *Not enough history*, *About right*, and *How the suggestions are worked out*. Each size table has a *Confidence* column. The workbook it attaches, `vm-right-sizing-report_2026-10-28.xlsx`, has every VM with every number (confidence and why, busy days, average, 95th percentile and peak CPU, CPU ready, active memory, the busiest day, ballooned and swapped memory, the fullest disk) on one sheet and every guest disk on another, to sort and filter. The job's output lists each VM to change: `web01: Too big (High) - vCPUs 8 › 4, memory 32 › 16 GB`; the job artifact `vm_rightsize` has the counts and the changes, each with its confidence.

Before you resize a VM: check its own peaks the statistics may not show (patching, backups, a yearly job older than a year), and plan the change - removing vCPUs or memory needs the VM shut down, and adding them too unless CPU / memory hot add is on (the report says so).

ACT's review (`vm_rightsize_act: true`, an ACT model key credential on the template, as for the capacity planning): ACT reads the same numbers and the job's suggestion for each VM to change (too small first, then the most freed, at most `vm_rightsize_act_max_items`) - with the job's own confidence and its doubts - and answers *Agree* or *Adjust* with its own size, its reasoning and a confidence of its own; it often knows that a name or guest OS means a database or Java and keeps more memory. Its review comes after the job's own tables, as a table with a line per VM, and then ACT's short summary (a line per batch it was asked in). Names are masked before anything reaches the model.

Set it up: a template *VM - right-sizing report*, playbook `playbooks/vm_rightsizing_report.yml`, the VMware vCenter credential, no Limit; `report_email_to` on its Variables; a schedule, monthly. Its settings, to change

on the template's Variables (`aap/extra_vars/vm_rightsizing_report.yml` has them all):

Setting	Default	
`vm_rightsize_days`	`30`	days of history (at most 30: what vCenter keeps of 2-hour averages)
`vm_rightsize_year`	`true`	also each VM's busiest days of the last year (they only hold a cut back)
`vm_rightsize_year_near_pts`	`10`	days of the year within this many points of the busiest are counted in the reason
`vm_rightsize_min_days`	`7`	fewer days of statistics = not enough history
`vm_rightsize_clusters` / `vm_rightsize_vms` / `vm_rightsize_exclude`	`[]`	only the VMs of these clusters / only these VMs / never these VMs (names, `*` and `?`)
`vm_rightsize_cpu_target_pct`	`70`	vCPUs suggested for about this % busy (95th percentile)
`vm_rightsize_cpu_high_pct`	`85`	CPU at this % or more (and on `vm_rightsize_grow_days` days) = too small
`vm_rightsize_grow_days`	`3`	more vCPUs or memory only when busy on this many separate days of the last 30 or more
`vm_rightsize_cpu_max_cut_pct`	`50`	never more than this % fewer vCPUs at once
`vm_rightsize_min_vcpus` / `vm_rightsize_min_vcpus_windows`	`2` / `2`	never fewer vCPUs
`vm_rightsize_ready_warn_pct`	`5`	CPU ready at this % or more is said
`vm_rightsize_mem_headroom_pct`	`100`	memory suggested = active memory plus this %
`vm_rightsize_mem_high_pct`	`90`	active memory at this % or more (and on `vm_rightsize_grow_days` days) = too small
`vm_rightsize_mem_max_cut_pct`	`50`	never more than this % less memory at once
`vm_rightsize_min_change_pct`	`25`	a smaller memory size only when this % (and 2 GB) smaller or more
`vm_rightsize_min_mem_gb` / `vm_rightsize_min_mem_gb_windows`	`2` / `4`	never less memory (GB)
`vm_rightsize_taken_mb`	`100`	ballooned or swapped memory from this many MB is said
`vm_rightsize_conf_days` / `vm_rightsize_conf_margin_pts`	`21` / `10`	confidence: fewer days of history, or the 95th percentile within this many points of its line, is a doubt
`vm_rightsize_conf_mem_large_gb` / `vm_rightsize_conf_mem_low_pct`	`32` / `10`	confidence: less memory for a VM this large with this little active is a doubt
`vm_rightsize_disk_warn_pct`	`90`	guest disks this % used or more are listed

Setting	Default	
`vm_rightsize_max_rows`	`500`	rows per table in the email (the workbook has every VM)
`vm_rightsize_xlsx`	`true`	`false` = no workbook attached
`vm_rightsize_batch` / `vm_rightsize_workers`	`10` / `4`	VMs per statistics query, and queries at a time (lower the batch if vCenter refuses: `vpxd.stats.maxQueryMetrics`)
`vm_rightsize_act`	`false`	ACT reviews the suggestions (`vm_rightsize_act_max_items` 40, `vm_rightsize_act_batch`, `vm_rightsize_act_model_timeout`)

The job is green unless a vCenter could not be read, or ACT was asked and did not answer (the report is still emailed). The vCenter account needs no more than read-only: the statistics come with it.

The VMware version report

VMware - version report (`playbooks/vmware_version_report.yml`) lists the version and build of each vCenter (`vmware_vcenters`; `vmware_datacenter` for one datacenter's hosts) and of every ESXi host it manages - no survey, read-only, the version and build exactly as vCenter reports them. At the top, the counts: vCenters, ESXi hosts, ESXi versions, ESXi builds, clusters on more than one build. Then:

- **vCenters** - each with its version, build and product name, its number of hosts and their versions (`8.0.3 (12), 8.0.2 (4)`);
- **ESXi builds in use** - each version and build, the newest first, with how many hosts run it, in which vCenters and clusters;
- **a table per vCenter** - every host by datacenter and cluster, with its version, build and state (not responding, maintenance mode). A cluster whose hosts run more than one build is named above its table (an update in progress, or a host left behind). A host that is not connected may have no version to report: `-`.

Amber only when an ESXi host is at a newer version than the vCenter that manages it - vCenter must be at its hosts' version or newer, so update vCenter first (listed on top, *ESXi newer than its vCenter*); red only when a vCenter could not be read. Update names (*Update 3*, *P05*) and support dates are not in the report: they are not something vCenter says, and a table of them in this job would go out of date - look a build up in VMware's release notes. The email attaches every vCenter and host as an Excel workbook (`vmware-version-report_2026-10-28.xlsx`: a sheet of vCenters, a sheet of ESXi hosts); the job output has a line per vCenter (`vc01.example.mil: vCenter 8.0.3 build 24322831; ESXi 8.0.3 build 24022510 (12)`); the artifact `vm_versions` has the vCenters, the builds in use and the counts.

Set it up: a template *VMware - version report*, playbook `playbooks/vmware_version_report.yml`, the VMware vCenter credential (read-only is enough), the execution environment of your other VMware jobs, no Limit, no survey; `report_email_to` on its Variables, and a schedule (monthly, or after patching). On the report website it is on the VMware tab.

The VMware hardware inventory

VMware - hardware inventory (`playbooks/vmware_hardware_report.yml`) lists the hardware and software of every ESXi host of each vCenter (`vmware_vcenters`; `vmware_datacenter` for one datacenter's hosts) - no survey, read-only, all from vCenter's API: nothing is run on a host, and the read-only vCenter account is enough. At the top, the counts: ESXi hosts, models, BIOS versions, ESXi builds, hosts with a serial number. Then:

- **Models** - each server model (vendor and model), how many hosts, the BIOS versions they run and how many hosts run each (`1.10.2 (12), 1.9.0 (2)`: two hosts left behind by a BIOS update), and their ESXi builds;
- **ESXi hosts** - every host: vCenter, cluster, vendor, model, **serial number** (the service tag), BIOS version and date, CPUs (sockets, model, cores), memory, ESXi version and build, its NICs (`2x bnxtnet 25G`) and storage adapters (`lpfc (Fibre Channel)`), and its state;
- **Not all read** - what could not be read for a host (its VIBs or image profile), with the rest of the host in.

The email attaches all of it as an Excel workbook (`vmware-hardware-inventory_2026-11-02.xlsx`), a row each:

Sheet	What
ESXi hosts	everything above, plus the asset tag, CPU threads and the image profile (the vendor's ESXi image, e.g. `(Updated) DEL-ESXi-...`)
NICs	each physical NIC: driver, speed (`down` when it has no link), MAC, PCI slot
Storage adapters	each adapter: kind (Fibre Channel, iSCSI, local / RAID, SAS, NVMe), model, driver, status
Software components	what vCenter's *Hardware Status* > *Software components* shows for the host: the drivers and the firmware the server's vendor reports (CIM), each with its version
VIBs	every installed VIB: name, version, vendor, install date (`vm_hardware_vibs: false` to leave them out)

Firmware: vCenter has no field for a NIC's or adapter's firmware. The BIOS version is in the report, and the other firmware versions are in *Software components* only as far as the server vendor's CIM provider reports them there (Dell, HPE and Lenovo images usually do; a plain VMware image shows the drivers only).

Amber when a host is not connected (what vCenter last knew of it; its software not read); red only when a vCenter could not be read. The job output has a line per model (`Dell Inc. PowerEdge R750: 14 host(s); BIOS 1.10.2 (12), 1.9.0 (2); ESXi 8.0.3 build 24022510 (14)`); the artifact `vm_hardware` has the models and the counts.

Set it up: a template *VMware - hardware inventory*, playbook `playbooks/vmware_hardware_report.yml`, the VMware vCenter credential (read-only is enough), the execution environment of your other VMware jobs, no Limit, no survey; `report_email_to` on its Variables. Run it when you need the inventory, or on a schedule (monthly). On the report website it is on the VMware tab.

Setting	Default	
`vm_hardware_vibs`	`true`	`false` = the VIBs not read (one call per host)
`vm_hardware_max_rows`	`2000`	ESXi hosts listed in the email and on the page at most - the workbook always has every host

Setting	Default	
vm_hardware_xlsx	true	false = no workbook attached

Snapshots: the report, the cleanup, and the approval workflow

The idea, in one picture

```
1. SNAPSHOT REPORT          looks at every VM and makes a list of its snapshots.
        |                   It changes nothing. It emails you the list.
        v
2. APPROVAL                 AAP stops and waits. A person reads the list and
        |                   clicks Approve (go ahead) or Deny (stop).
        v  (only on Approve)
3. SNAPSHOT CLEANUP         deletes the old snapshots that were ON THAT LIST -
                            nothing else - and emails what it deleted.
```

Think of it like cleaning out a fridge: first someone writes down everything old in it (the report), then a grown-up says "yes, throw those out" (the approval), then the helper throws out **only what is on the paper** (the cleanup). Anything someone put a "keep" label on stays.

What the report shows

For every snapshot of every VM: the VM, the snapshot's name, when it was taken, **who took it**, how many days old it is, how big it is (MB, GB or TB), the VM's folder and the description. Oldest first. **Every snapshot is in that list, whatever its age** - even one taken an hour ago. Then two short lists on top:

- **To delete:** snapshots older than 5 days (vm_snapshot_max_age_days).
- **Held back:** old snapshots the cleanup will never delete, each with the reason.

The email's heading and subject always say the limit, e.g. VMware snapshot report (older than 2 days): 4 to delete (310 GB); 23 snapshot(s) on 17 VM(s).

To use another number of days than 5:

Where	Change
In the workflow	the survey answer when you launch it - or for good: the workflow > **Survey** tab > the question > **Default** 2. The report and the cleanup both use it: after the approval, snapshots older than 2 days are deleted.
The report template on its own	Templates > VM - snapshot report > Edit > **Variables**: vm_snapshot_max_age_days: 2

In the workflow, the survey answer wins over the template's Variables.

"Who took it" comes from vCenter's history. vCenter forgets old history (often after 30 days), so for an old snapshot it may say **unknown**. Snapshots taken by the "VM - snapshot" job also have the AAP user in their description.

What the cleanup never deletes

Never deleted	Why	Change it with (in playbooks/group_vars/all.yml)
A snapshot whose name or description says **keep** or **do not delete**	someone wants it kept	`vm_snapshot_keep_regex`
Any snapshot of the VMs on your do-not-touch list	domain controllers, vCenter, ...	`vm_snapshot_cleanup_exclude_vms: [DC*, VCSA*]` (* = anything)
Any snapshot of a VM in a datacenter on your list	a datacenter (DR site, a lab) whose snapshots someone else looks after	`vm_snapshot_cleanup_exclude_datacenters: [DRSITE]` (the datacenter's name in vCenter)
Any snapshot of a VM running in a cluster on your list	a cluster (SQL, management) whose snapshots are done by hand	`vm_snapshot_cleanup_exclude_clusters: [SQL*, MGMT*]` (a VM on a host in no cluster is not matched)
Any snapshot of the VMs in `vmware_protected_vms` and of the hosts in `vmware_protected_groups`	the same protected VMs as for restart	`vmware_protected_vms`, `vmware_protected_groups`
Any snapshot of the AAP server	AAP must never be put at risk by AAP	(always)
With words in `vm_snapshot_cleanup_name_words`: a snapshot whose **name** contains none of them	only the patching snapshots are cleaned up (any case; `Patch` also matches `Patching`, `Patches` - and `dispatch`). Empty (the default) = any name	`vm_snapshot_cleanup_name_words: [Patching, Patches, Patch]`
A snapshot bigger than **1 TB**, or whose size is unknown	merging a huge snapshot can take hours and slow the VM: do it by hand, at a quiet time	`vm_snapshot_cleanup_max_size_gb: 1024`
More than 50 snapshots in one run	a typo in the days would otherwise delete everything	`vm_snapshot_cleanup_max: 50`
Anything that was not on the approved list	the approver only said yes to that list	(always, in the workflow)

Set it up (once)

Step 0 - what you need first (see "Before you start" above): the VMware vCenter credential, the execution environment with `vmware.vmware`, and the mail relay in `all.yml` ("Email the report").

Step 1 - your do-not-touch list. In VS Code, in `playbooks/group_vars/all.yml`, add (with your VM names; `*` matches anything) - then Commit, Sync Changes, and sync the project in AAP:

```yaml
vm_snapshot_cleanup_exclude_vms: [DC*, VCSA*, AAP*]
```

Step 2 - the report template. Templates > Create template > Create job template:

- Name: `VM - snapshot report`
- Inventory: your inventory with the `aap` group
- Project: site-automation. Playbook: `playbooks/vm_snapshot_report.yml`
- Execution environment: the one with `vmware.vmware`
- Credentials: your **VMware vCenter** credential
- Leave Limit empty. No survey. Save.

Step 3 - the cleanup template. The same again:

- Name: `VM - snapshot cleanup`
- Playbook: `playbooks/vm_snapshot_cleanup.yml`
- Tick **Prompt on launch** next to **Job type** (this lets you do a dry run - below).
- No survey. Save.

Step 4 - the workflow. Templates > Create template > **Create workflow job template**:

- Name: `VM snapshot cleanup (with approval)`, your organization. Save.
- **Survey** tab > Create survey question - two questions, then switch the survey **on**:

Question	Answer variable name	Answer type	Default
Delete snapshots older than how many days?	`vm_snapshot_max_age_days`	Integer, required, minimum 1	`5`
Email the reports to	`report_email_to`	Text	your team's address

The workflow hands these answers to both jobs, so the report and the cleanup use the same days.

- **Visualizer** (the boxes):

1. Click **Add step**. Node type: **Job template**. Pick `VM - snapshot report`. Save.
2. Hover over that box > **Add step and link** (the plus sign). Node type: **Approval**. Name: `Delete the snapshots listed in the report?`. Timeout: e.g. `1 day` (no answer by then = no). Run type: **Run on success**. Save.
3. Hover over the approval box > **Add step and link**. Node type: **Job template**. Pick `VM - snapshot cleanup`. Run type: **Run on success** (after an approval, that means: approved). Save. **Never Run always here:** the cleanup would then also run when the approval is denied or times out - and it still gets the report's list, so it would delete. (Check the link's label in the Visualizer: green *Run on success*, not blue *Run always*.)
4. Click **Save** at the top of the Visualizer.

Step 5 - who may approve. On the workflow: **User Access** (or Team Access) > Add > pick the people > role **Approve**. They need no other rights. Optional: **Notifications** tab > turn on the approval notification so they get an email when something waits for them.

Step 6 - when it runs. On the workflow: **Schedules** > Create schedule (e.g. every Monday 7:00). Or launch it by hand.

Run it

1. Launch the workflow (or the schedule does). Answer the survey (or keep 5 days).
2. The report runs and **emails the list**: what will be deleted, what is held back, and why.
3. AAP waits at the approval. Open **Automation Execution > Administration > Workflow Approvals** (or the workflow job's view) > the approval > **Approve** or **Deny**.
4. On **Approve**: the cleanup deletes the snapshots from that list that are still there, and still that old, and **emails what it deleted** (and how much space came back). On **Deny** or timeout: nothing is deleted.

The cleanup's email can be sent only when something was actually deleted: `vm_snapshot_cleanup_email_only_if_deleted: true` (in the cleanup template's Variables).

Dry run: try it, delete nothing

- **The safest first try: say no.** Launch the workflow, read the report email, then **Deny** the approval. The report only reads, so nothing changed anywhere.
- **See exactly what the cleanup would delete, without deleting:** in the workflow's Visualizer, click the `VM - snapshot cleanup` box > **Edit** (pencil) > Job type **Check** > Save, and save the Visualizer. Run the workflow and **Approve**: the cleanup job's output lists `WOULD DELETE ...` for each snapshot and deletes nothing (and sends no email). Set the box back to **Run** afterwards. (This needs the Step 3 tick "Prompt on launch" for Job type.)
- **Without the workflow:** launch `VM - snapshot cleanup` on its own. With no approved list and no `vm_snapshot_cleanup_confirm: true` it only lists what it would delete - it never deletes.

Without the workflow

To clean up by hand, make a separate template (not the one in the workflow) on `playbooks/vm_snapshot_cleanup.yml` with a survey: `vm_snapshot_max_age_days` (Integer, 5) and `vm_snapshot_cleanup_confirm` ("Delete them?", Multiple choice `false` / `true`, default `false`). With `false` it only lists; with `true` it deletes - with every rule above still in place.

Only the patching snapshots, without the approval

Until the workflow's approval works, the cleanup can run on its own, on a schedule, and delete **only** the snapshots whose name contains `Patching`, `Patches` or `Patch` - every other snapshot is left alone and listed as held back, with the reason `its name has none of: Patching, Patches, Patch`.

1. In `playbooks/group_vars/all.yml` (so the snapshot report lists the same ones as "To delete"):

```yaml
vm_snapshot_cleanup_name_words: [Patching, Patches, Patch]
```

Any case matches, anywhere in the name: `Pre-Patching 10/14`, `PATCHES oct`, `patch-web01`. The name only, not the description. `Patch` alone already matches the other two; keep all three if you like the list to say what you mean. A phrase works too: `[Patch Tuesday]`. The snapshots *Patch hosts* takes right before patching (`patch_snapshot`, RUNBOOKS.md) are named `patching`: these words match them.

2. Make a separate template (not the one in the workflow): `VM - snapshot cleanup (patching)`, playbook `playbooks/vm_snapshot_cleanup.yml`, credential `VMware vCenter`, **Variables**:

```yaml
vm_snapshot_cleanup_confirm: true
```

3. **First, a dry run:** launch it with Job type **Check** (tick "Prompt on launch" for Job type). The output and email list `WOULD DELETE ...` for each patching snapshot and `HELD BACK ...` for the others - nothing is deleted. Check the list; then launch it for real, and schedule it (e.g. daily, after the patching window).

Still in force: the age (`vm_snapshot_max_age_days`, 5 - a patching snapshot taken yesterday waits; `0` = any age), the keep words, the do-not-touch VMs, the AAP server, the 1 TB limit and at most 50 in one run. The email's subject says it: `VMware snapshot cleanup: deleted 4 snapshot(s) older than 5 days whose name has Patching, Patches or Patch (120 GB)`. When the workflow works, the setting can stay: the report then lists only the patching snapshots for approval - or set it back to `[]`.

Pick lists: choose what to restart, which snapshots to delete

The other jobs ask for VM names typed in. Here whoever launches the job **picks from a list** in the survey - the snapshots that may be deleted right now, or the VMs that may be restarted (or only the ones that look hung) - and ticks the ones to do.

Why the list needs a job of its own

AAP cannot fill a survey from vCenter when you click Launch: a survey's choices are fixed text, saved with the template. And inside a workflow nothing can ask a question halfway: an **approval step takes no input** (only Approve or Deny), and the surveys of the job templates inside a workflow are **never asked** - only the workflow's own survey, at launch. So the picking happens at launch, from a multiple-choice question whose choices a scheduled job keeps current:

```
VM - refresh the pick lists     every 30 minutes: reads vCenter, writes what may be done NOW as
  the
       (schedule)               choices of the question in the survey of the templates you name
       .
       .   later, a person launches:
       v
workflow survey                 ticks the snapshots (or VMs) in the list
       |
1. PLAN  (the pick job)         finds each pick again in vCenter, live, and lists exactly what
  will be
       |                        done - the ones that are gone or no longer allowed are skipped,
         with
       |                        the reason. Changes nothing.
2. APPROVAL                     a person reads the plan and clicks Approve or Deny
       |  (only on Approve)
3. DO IT (the same pick job)    does exactly the plan - checked live once more - nothing else
```

Each choice is readable text that ends with the item's IDs in brackets, e.g.

```
DC0_C0_RP0_VM1: "Pre-Patching-Oct" (12.4 GB, 6.2 days old, taken 2026-10-14 08:12 UTC)
  [vc01.yoursite.mil/vm-42/7]
web01 (no heartbeat, up 3.2 days, DC1 / PROD-CL01, guest web01.yoursite.mil 192.0.2.20)
  [vc01.yoursite.mil/vm-42]
```

The brackets are the vCenter, the VM's ID and (for a snapshot) the snapshot's ID: two snapshots with the same name, or two VMs with the same name in different vCenters, are never mixed up.

What may be picked

List	Offered	Never offered (counted in the refresh's output, with the reason)
Snapshots	every snapshot the **snapshot cleanup could delete**: the same holds (table "What the cleanup never deletes" above), at least `vm_pick_snapshot_min_age_days` old (0 = any age)	a name or description that says keep, the excluded VMs, datacenters and clusters, `vmware_protected_vms` and `vmware_protected_groups`, the AAP server, bigger than 1 TB. **Not** the name words: they only narrow the automatic cleanup
VMs	every VM that is **powered on**, among `vm_pick_reboot_vms` / `vm_pick_reboot_clusters` / `vm_pick_reboot_folders` (empty = all)	templates, VMs that are off, the AAP server and the protected VMs (the same rules as every restart), `vm_pick_reboot_exclude_vms`
Hung VMs (`vm_pick_reboot_only_hung: true`)	powered on, VMware Tools **installed**, but **no heartbeat** (red in vCenter) or Tools **not running** - and up for `vm_pick_hung_min_minutes` (15) at least	a VM that is still starting (it has neither yet), a VM without VMware Tools (vCenter cannot tell if it is hung)

A list has at most `vm_pick_max_choices` (200) choices; the refresh's output says how many more there were. With nothing to pick, the list has one line `(nothing to pick: ... - list of <time>)`, which the pick jobs ignore. The question's description ends with when the list was made, e.g. `[pick list of 2026-10-20 10:00 UTC: 12 snapshot(s) that may be deleted]`.

Set it up (once)

Step 1 - the pick job templates. Templates > Create template > Create job template, twice:

Name	Playbook	Credentials	Job type
`VM - delete picked snapshots`	`playbooks/vm_snapshot_delete_picked.yml`	VMware vCenter	tick Prompt on launch (dry runs)
`VM - restart picked VMs`	`playbooks/vm_reboot_picked.yml`	VMware vCenter	tick Prompt on launch (dry runs)

Inventory: your inventory with the `aap` group. Execution environment: the one with `vmware.vmware`. Leave Limit empty. **Do not tick Prompt on launch for Variables** (the step after the approval must get its plan from the step before, not from whoever launches). No survey.

Step 2 - the workflows, one per list. Templates > Create template > Create workflow job template:

- `VM - delete picked snapshots (workflow)`. **Survey** tab > Create survey question:

Question	Answer variable name	Answer type	Required	Choices
Snapshots to delete	`vm_snapshot_picks`	**Multiple choice (multiple select)**	yes	type one placeholder, e.g. `(nothing to pick yet)` - the refresh replaces it

- `VM - restart picked VMs (workflow)`. **Survey**:

Question	Answer variable name	Answer type	Required	Choices / default
VMs to restart	`vm_reboot_picks`	**Multiple choice (multiple select)**	yes	a placeholder, as above
How	`vm_power_mode`	Multiple choice	yes	`guest`, `hard`; default `guest` (`hard` for the hung list)

Switch each survey **on**.

- **Visualizer** of each: (1) **Add step**: Job template `VM - delete picked snapshots` (or `restart picked VMs`). (2) On it, **Add step and link**: **Approval**, e.g. `Do exactly this plan?`, timeout e.g. 4 hours, Run type **Run on success**. (3) On the approval, **Add step and link**: the **same** job template again, Run type **Run on success** - never Run always. Save.

The first run of the job plans (inside a workflow it never deletes or restarts before an approval, whatever its Variables say); its plan goes to the approval and on to the second run (job artifact `vm_snapshot_pick_plan` / `vm_reboot_pick_plan`), which does exactly that. When nothing that was picked can be done any more, the plan step fails and the workflow stops there.

Step 3 - who may launch and approve. On each workflow: User Access > the service desk > role **Execute** (launch) and the approvers > role **Approve**.

Step 4 - the refresh. One more job template:

- Name: `VM - refresh the pick lists`. Playbook: `playbooks/vm_pick_refresh.yml`.
- Credentials: **VMware vCenter** and **Red Hat Ansible Automation Platform** (its AAP user needs the **Admin** role on the two workflows - to write their surveys).
- **Variables** (`aap/extra_vars/vm_pick_refresh.yml` has every setting):

```yaml
vm_pick_snapshot_templates: ["VM - delete picked snapshots (workflow)"]
vm_pick_reboot_templates: ["VM - restart picked VMs (workflow)"]
# vm_pick_reboot_only_hung: true        # the restart list: only the hung VMs
# vm_pick_reboot_clusters: [PROD-*]     # ... of these clusters
```

A job template and a workflow with the same name: `{template: "<name or ID>", kind: workflow}`.

- **Schedules** > every 30 minutes (or what suits you). Run it once by hand first: its output lists every choice it wrote, and what it held back and why.

To have both a list of every VM and a list of only the hung ones, make two refresh templates (one with `vm_pick_reboot_only_hung: true`) writing into two workflows.

Run it

1. Launch the workflow. The survey shows the list as it was at the last refresh (its time is in the question's description). Tick what to do; pick **How** for a restart.
2. The plan step lists `WOULD DELETE ...` / `WOULD RESTART ...` for each pick that can still be done, and `SKIPPED ... - <reason>` for the others: deleted or renamed since the list was made, held back now, powered off, no longer hung, a guest restart of a VM without VMware Tools running.
3. The approver reads that plan (the plan step's output) and approves or denies.
4. On **Approve**: the same checks again, then exactly the plan - `DELETED ...` / `RESTARTED ...`.

Never more than `vm_pick_max` (20) in one run: more picks are refused, nothing done. As **Check** (a dry run), no step changes anything.

Without a workflow: launch `VM - delete picked snapshots` or `VM - restart picked VMs` on its own with a survey of its own (the same question, and name that template in the refresh's settings). It only lists the plan, unless `vm_pick_confirm: true` (a survey question "Do it now?", `false` / `true`) - then it does the picks at once, with every check above. Inside a workflow `vm_pick_confirm` is never used.

Limits

- **The list is as fresh as the last refresh.** Every pick is checked again, live, before anything is done - a pick that is gone or no longer allowed is skipped, never guessed - but something new since the refresh is not in the list until the next one.
- **The approval is all or nothing.** The approver approves the whole plan or none of it. To leave one out: Deny, launch again and pick fewer.
- AAP checks a survey answer against the choices: if the refresh replaced the list while someone had the survey open, AAP may refuse their launch - open the survey again.
- The heartbeat comes from VMware Tools. A VM without VMware Tools is never in the hung list.
- Tested against vcsim and a fake AAP (`tests/vmware/run_vmware_test.sh`, `tests/test_aap_survey.py`), not a real AAP survey: run the refresh once by hand and look at the workflow's survey before you schedule it.

Health: every datacenter, cluster and host

The read-only **VM - health report** answers "is the virtual infrastructure healthy?" for every vCenter (the credential's and `vmware_vcenters`), every datacenter, every cluster and every host - in one email, coloured by severity, with what to do for each problem. The alarms themselves, failed logins and the day's events are in the **alarms report** below: run both every morning (workflow 18 in WORKFLOWS_AND_SCHEDULES.md).

What the report shows

Section	What is in it
Needs attention	every problem found, most severe first: severity, the object (vCenter, datacenter, cluster or host), the problem, **what to do**, and where it is (datacenter / cluster)
Datacenters	each datacenter with everything in it: clusters, hosts, hosts running VMs, in maintenance, not connected, its problems
Clusters	each cluster: hosts running VMs, **vSphere HA** (on or OFF, what admission control reserves, host agents not OK), **DRS** (on or OFF, automation level, score, recommendations waiting), **vCLS** (normal or RETREAT MODE), CPU and memory used, alarms, problems
Hosts	every host, by datacenter and cluster (standalone hosts too): connection, maintenance mode, the **HA agent** (primary, secondary, isolated, partitioned ...), **hardware** (sensors and hardware status not green), CPU and memory used, days up, the **clock** against vCenter's, ESXi version and build, alarms
vCenter	each vCenter's version and the alarms on vCenter itself
Single sign-on and OCSP	below
Network drops and errors	each ESXi host and powered-on VM that dropped packets or had network errors, by NIC - below
How it was read	how long each stage of the read took, and any host that gave no answer in time ("Read speed", below)

On top: the counts in coloured boxes (hosts not connected, HA problems, DRS problems, hosts with hardware faults, triggered alarms). The subject says it in one line, e.g. `[AAP] VMware health report: 2 critical, 3 warning(s) - 3 datacenter(s), 7 cluster(s), 26 host(s)`.

Colour	What
Red (critical)	a host not connected to vCenter (or powered off); a host's HA agent isolated, partitioned, unreachable or in error; vCLS retreat mode on a cluster with DRS (DRS stops); a red hardware sensor; a red alarm; CPU or memory from 95 %; a host's clock 5 minutes or more off vCenter's
Amber (warning)	HA or DRS off on a cluster of 2 or more hosts; HA host monitoring off; HA failover capacity below what admission control reserves; DRS recommendations waiting, or DRS faults; retreat mode without DRS; a yellow sensor; a host that needs a restart; a configuration issue (SSH on, ...); a yellow alarm; CPU from 85 %, memory from 90 %; a host's clock a minute or more off vCenter's, no NTP server set on it, or its NTP service stopped; vCenter's clock a minute or more off the AAP job's
Blue (info)	a host in maintenance mode or standby; HA admission control off; DRS in manual mode - worth knowing, not broken

A one-host cluster without HA or DRS is fine, and so is a host in maintenance mode whose HA agent is not configured (that is what maintenance mode does).

Set up the report

1. **Templates > Create template > Create job template:**

- Name: `VM - health report`
- Inventory: any (the job runs on the AAP side)
- Project: site-automation. Playbook: `playbooks/vm_health_report.yml`
- Execution environment: your VMware one
- Credentials: your **VMware vCenter** credential. A read-only vCenter account is enough.
- Variables: `report_email_to: vmteam@yoursite.mil` (and `vmware_vcenters: [...]` for more vCenters, if not already in `all.yml`)
- Save, then **Launch** it once and read the email.

2. **Schedules > Create schedule:** e.g. every day at 06:00 - or put it in front of the alarms report in workflow 18.

Setting (template Variables)	Default	What it does
`vm_health_require_ha`	`true`	a cluster of 2 or more hosts without vSphere HA is a warning; `false` if that is on purpose
`vm_health_require_drs`	`true`	the same for DRS; `false` where DRS is not licensed (e.g. vSphere Standard)
`vm_health_cpu_warn_pct` / `vm_health_cpu_crit_pct`	`85` / `95`	CPU used (a host, or a cluster's hosts running VMs): amber from, red from
`vm_health_mem_warn_pct` / `vm_health_mem_crit_pct`	`90` / `95`	the same for memory
`vm_health_sensors`	`true`	read the hosts' hardware sensors
`vm_health_clock`	`true`	read each host's clock and NTP setting ("Times and clocks", below)
`vm_health_clock_warn_seconds` / `vm_health_clock_crit_seconds`	`60` / `300`	a host's clock this far off vCenter's, ahead or behind: amber from, red from
`vm_health_workers`	`8`	hosts asked at a time for their clock and their events ("Read speed", below)
`vm_health_host_timeout`	`20`	seconds to wait for one host's answer; past it the host is said as not read, not judged
`vm_health_events_days` / `vm_health_events_max`	`30` / `100`	how far back, and how many events at most, to read for a host not connected
`report_time_zone`	`""` (UTC only)	the times in that time zone too, e.g. `America/New_York` - best in `all.yml` (below)
`vm_health_fail`	`false`	`true` = the job shows **failed** on a critical problem, for a workflow
`vmware_datacenter`	(all)	one datacenter only

vCLS retreat mode is read from vCenter's advanced settings (`config.vcls.clusters.<cluster id>.enabled = false`). If the account may not read them, the report says so in blue, and retreat mode still shows as vCenter's own alarm on the cluster.

Read speed

Most of the read is one question to vCenter for every host at once. Two parts are asked **per host**, and they are the slow ones on a large or busy vCenter:

- **Each connected host's clock** (`vm_health_clock`) - vCenter passes the question on to the host, so a host slow to answer is slow here.
- **When a host not connected lost vCenter** - its newest event of it, from vCenter's event database.

Both are asked `vm_health_workers` (8) hosts at a time, and one host's answer is waited for at most `vm_health_host_timeout` (20) seconds: a host that takes longer is said as **not read** - "clock not read (no answer in 20 s)" in its row, the Clock column `not read`, and a line in **How it was read** - never as a clock problem, and the other hosts are read meanwhile. The events are read only for the last `vm_health_events_days` (30) days, at most `vm_health_events_max` (100) per host, the newest: an outage older than that shows without its "since".

The job's output says how long each stage took, in one line, e.g. `read in 41 s: hosts 3 s, clocks 22 s, events 15 s, alarms 1 s` - a slow run says where it was slow. *hosts* is every datacenter, cluster and host with their hardware sensors; *alarms* the triggered alarms. There is no limit on the whole read: a report that looks complete but is not would be worse, so a stage that skipped a host says so, and the report's subtitle says "not everything was read in time".

Times and clocks

"The report says the host went down at 14:03, its log says something else" has three causes, and the report shows each:

- **The time zone.** vCenter, ESXi and their log files (hostd, vmkernel, vobd, vpxd) keep UTC, and so does the report. The vSphere Client shows times in the browser's time zone, so 14:03 UTC is 10:03 there in New York in summer. Set the time zone people read the reports in, once, in `all.yml`:

```yaml
report_time_zone: America/New_York        # a name as `timedatectl list-timezones` prints it
```

Each time then shows in that zone first, then in UTC: `2026-10-25 10:03:12 EDT (14:03 UTC)`, with summer time as it was on that day. The VMware health and alarms reports use it; the ACT (GenAI) analysis keeps UTC. A name the execution environment does not know leaves UTC, and the report's subtitle says so.

- **Which event.** A host not connected shows **since** the newest event of it losing vCenter (not responding, connection lost, disconnected, shut down) - the time the vSphere Client's **Monitor > Events** shows for it. A triggered alarm's "since" is when the alarm turned that colour, which can be later.
- **The host's clock.** A host writes its own logs by its own clock, vCenter its events by vCenter's: a host 3 minutes behind logs the disconnection 3 minutes "before" vCenter's event. The **Clock** column shows each connected host's clock against vCenter's (`+` ahead, `-` behind, `?` = vCenter would not say, `not read` = no answer in `vm_health_host_timeout`). From `vm_health_clock_warn_seconds` (60) it is amber, from `vm_health_clock_crit_seconds` (300) red - Active Directory logins to a host fail from 5 minutes off. No NTP server set on a host, or its NTP service stopped, is amber: fix it under **Host > Configure > System > Time Configuration**. vCenter's own clock is compared with the AAP job's: a minute or more apart is amber, as one of them is off.

Single sign-on and OCSP (vCenter 8.0)

Every user and every job logs in to vCenter through its single sign-on. When SSO breaks - a service stopped, the STS signing certificate expired, the identity source lost its domain controllers - nobody can log in. The health report has a section **Single sign-on and OCSP** (`vm_sso: true`, the default), and the **outage watch** asks every run whether SSO is down *now* (`vm_watch_sso`):

What	Severity	Health report	Watch
An SSO service in `vm_sso_services` (sts, lookupsvc, trustmanagement, vmdird, vmafdd) not started	critical	yes	yes
The test domain account cannot log in to vCenter	critical	yes	yes
The credential's own login refused (single sign-on, or the credential)	critical	yes	yes
The STS signing certificate expired, or expires within `vm_sso_sts_crit_days` (14)	critical	yes	-
... within `vm_sso_sts_warn_days` (60)	warning	yes	-
An OCSP responder (`site_ocsp_certs` or `vm_sso_ocsp`) does not answer, answers not successful, stale, or not good, or its address or issuer could not be read from the certificate	`vm_sso_ocsp_severity` (critical)	yes	yes
The CRL of a certificate there cannot be downloaded, is not a CRL, is not the CA's (issuer or signature), is stale (its next update passed), or lists the test certificate	`vm_sso_crl_severity` (warning)	yes	no

The section also lists each vCenter's identity providers. Only reads reach vCenter.

The test login. The surest proof that domain users can log in: a domain account logs in to vCenter each run and logs out again. Create an AD account for it (not a person's), give it **Read-only** on vCenter's root without propagating (or nothing: a login that is authenticated but has no permission still proves SSO works), and a **vCenter SSO test account** credential (`aap/credential_types/vcenter_sso_test.yml`) on the health report and the watch templates. Without it, there is no login test.

OCSP. Smart card (CAC) logins to vCenter check each card's certificate with an OCSP responder: when it does not answer, they fail. Put a certificate the responder knows - any user's, from a smart card or the PKI's site - in your repository as a PEM file (it is not a secret), and name it in `all.yml`:

```yaml
site_ocsp_certs: [files/ocsp/test-user.pem]     # playbooks/files/ocsp/test-user.pem; the network
                                                # performance report uses it too
```

The responder's address and the certificate of the CA that issued it are read from the certificate itself (its *Authority Information Access*: every DoD certificate names its OCSP responder and where its CA's certificate is); the CA's certificate is downloaded from the AAP node. When the AAP node cannot reach that address, put the CA's certificate after the user's in the same file. Commit the files: the repository's `.gitignore` leaves out `*.crt` and `*.pem` except in `playbooks/files/ca/` and (since 0.31.1) `playbooks/files/ocsp/` - elsewhere,

or with an older `.gitignore`, add them with `git add -f`. Then push and sync the project in AAP. `vm_sso_ocsp`, when set, is used instead - to give an address or an issuer yourself, or ask another responder:

```yaml
vm_sso_ocsp:
  - cert: files/ocsp/test-user.pem       # the address and issuer from the certificate
  - url: http://ocsp2.example.mil        # or all three given
    cert: files/ocsp/test-user.pem
    issuer: files/ocsp/issuing-ca.pem
```

With a certificate, each run sends a real OCSP request and reads the answer: it must be successful, the certificate **good**, and the answer fresh (its next update not passed). With a `url` only, it is sent an OCSP request about a made-up certificate, as a smart card login's would be: any OCSP response ("unauthorized", usually) is the responder up. No answer, an HTTP error, or an answer that is not OCSP is the problem. (A plain GET or `curl -I` proves less: some responders close a bare GET unanswered.) The responders are asked from the AAP node; vCenter itself must reach them too (a proxy or firewall between vCenter and the responder is not seen from here).

CRL. vCenter checks a smart card's certificate against its CA's CRL when OCSP does not answer (or only by CRL, when set so). For every entry with a certificate, the health report also downloads that CA's CRL - from the certificate's CRL Distribution Point, or `crl_url` in a `vm_sso_ocsp` entry - from the AAP node, each address once, and checks that it is a CRL issued and signed by the CA, that it is fresh (its next update not passed: vCenter refuses cards it cannot check against a current CRL), and that the test certificate is not on it. The row shows how many certificates it lists, its size and its next update. A failing CRL is a warning (`vm_sso_crl_severity`), since OCSP still answers logins; the outage watch never downloads it (DoD CRLs are tens of MB). `vm_sso_crl: false` turns it off; `crl: false` in one entry skips that one; `vm_sso_crl_timeout` (120 s) and `vm_sso_crl_max_mb` (200) bound the download.

The account of the **VMware vCenter** credential reads the services (read access to the appliance) and the STS certificate (CertificateManagement.Administer, read); what it may not read is listed in the section's notes, not as a problem. `vm_sso: false` turns it all off.

Network drops and errors

A NIC or uplink at its limit, a bad cable or SFP, a VM whose guest cannot keep up: they drop packets long before anything is down. The health report has a section **Network drops and errors** (`vm_net_drops: true`, the default): every connected ESXi host and every powered-on VM that dropped packets or had network errors, received and sent, by NIC (a host's `vmnic0`, a VM's `Network adapter 1 (its port group)`). Only those with a drop or an error are listed; the text above the table says how many were read.

What	Severity
a host or VM dropped `vm_net_drops_warn_per_hour` (100) packets an hour or more, received + sent	warning
a host or VM had `vm_net_errors_warn_per_hour` (10) network errors an hour or more	warning
a vCenter whose counters could not be read (its health could)	warning

Never critical: drops slow things down, they do not stop them, so `vm_health_fail` does not fail on them.

Where the counts come from, and vCenter's statistics level. The counts are vCenter's performance counters `net.droppedRx`, `net.droppedTx`, `net.errorsRx` and `net.errorsTx` - the same as the host's and the VM's network charts in the vSphere Client. They are not in the logs vCenter and the hosts send to a syslog

server or SIEM: vCenter keeps them in its own database. vCenter keeps them for the **past day** only when its 5-minute statistics are at **level 2** or more; the default is level 1. The section says, for each vCenter, what it read:

- **Level 2 or more:** the past `vm_net_drops_hours` (24) hours - the totals of each host and VM (by NIC from level 3).
- **Level 1:** the **last hour**, from the hosts' real-time statistics (ESXi keeps every counter for an hour), by NIC, with a note on how to raise the level. A daily report then sees only the hour before it ran.

To check or raise the level: vSphere Client > the vCenter > **Configure > Settings > General > Edit > Statistics**. The row whose interval duration is **5 minutes**: set its statistics level to **Level 2**. The dialog shows the database size it estimates before you save; level 2 adds more counters for every host and VM, kept a day at 5 minutes (and longer at the coarser intervals only if you raise those too - not needed here). Check vCenter's database partition has room (the appliance's management page, port 5480 > Monitor > Disks, `/storage/seat`).

Setting (template Variables)	Default	What it does
`vm_net_drops`	`true`	read the drops and errors (`false` = no network section)
`vm_net_drops_vms`	`true`	the powered-on VMs too (`false` = the hosts only, quicker with thousands of VMs)
`vm_net_drops_hours`	`24`	hours to read when vCenter keeps the past day (at most 24)
`vm_net_drops_warn_per_hour`	`100`	dropped packets an hour, received + sent, of one host or VM: a warning from
`vm_net_errors_warn_per_hour`	`10`	network errors an hour of one host or VM: a warning from

The account of the **VMware vCenter** credential needs nothing more: read-only reads the statistics. The Linux guests' own interface counters are in the network performance report (NETWORK_PERF.md): there the drops are counted inside the guest, here at the host.

VMs created: the weekly report

The read-only **VM - VMs created report** answers "how many VMs were created this past week?" for every vCenter (the credential's and `vmware_vcenters`): the count up front, then each VM.

Section	What is in it
On top	VMs created, of them by AAP from tickets, deleted since; vCPU, memory and disk added
VMs created, oldest first	when (UTC), the VM, **by whom**, **how** (deployed from template X, cloned from Y, created new), the **ticket** when the AAP deploy built it, cluster, folder, vCPU, memory, disk, operating system, power
By whom	each person (account) and how many VMs - and how many of them came from tickets
By day	how many VMs each day

Section	What is in it
Created and deleted since	VMs created in the week that are gone now (counted on top too), and when they were deleted

The subject says it in one line, e.g. `[AAP] VMware: 5 VMs created in the last 7 days (3 by AAP from tickets, 1 deleted since)`.

- **When:** the VM's own creation date (vSphere 6.7 and later), else its creation event. **By whom and how:** vCenter's events. vCenter keeps events for a limited time (often 30 days): a week is well inside that. A VM whose event is gone still counts, by its date, with "By" empty.
- **The window** is the last `vm_created_days` (7) days up to the moment the job starts. Run every Friday at noon, each report covers about Friday noon to Friday noon (a job that starts a minute late moves the window by that minute).
- **The ticket** comes from the notes the deploy writes on each VM - their first line, *"INC0012345 - built 2026-10-20"*, and *"Template: ..."* under it (VMs built by older releases: *"Deployed from ... for INC... by ..."*); a VM built by hand has none. Templates are not counted.

Set up the report, every Friday at noon

1. **Templates > Create template > Create job template:**
   - Name: `VM - VMs created report`
   - Inventory: any (the job runs on the AAP side)
   - Project: site-automation. Playbook: `playbooks/vm_created_report.yml`
   - Execution environment: your VMware one
   - Credentials: your **VMware vCenter** credential. A read-only vCenter account is enough (it reads the VMs and the events).
   - Variables: `report_email_to: vmteam@yoursite.mil` (and `vmware_vcenters: [...]` for more vCenters, if not already in `all.yml`)
   - Save, then **Launch** it once and read the email.
2. **Schedules tab > Create schedule:**
   - Name: `Weekly - VMs created`
   - Start date/time: the next Friday, **12:00**, and **Time zone: your site's** (not UTC - so 12:00 is your noon)
   - Repeat frequency: **Week**, every **1** week, on **Friday**
   - Save. The schedule's next run shows on the template's Schedules tab.

Setting (template Variables)	Default	What it does
`vm_created_days`	`7`	the window: the last this many days (e.g. `14` for a report every other Friday, `30` for a monthly one)
`vmware_datacenter`	(all)	one datacenter only

Alarms: the report, and ACT's analysis

Two read-only jobs. The **report** shows what is wrong in vCenter now and what happened in the last 24 hours. The **ACT analysis** has ACT (the AI assistant) work out the likely cause and the fix of each of those problems, and say how sure it is. Neither changes anything.

What the report shows

Section	What is in it	Colour
Triggered alarms	the alarms vCenter shows now on vCenter itself, the datacenters, clusters and hosts: severity, object, alarm, since when, acknowledged by whom	red = critical, amber = warning
Alarms that fired in the last 24 h	every alarm that turned yellow or red in the window, one row per alarm and object: how many times it went red and yellow, first and last change, and how it is now - still on, or cleared since (an alarm that comes and goes is worth a look too)	red / amber = still on, blue = cleared
Host connection	hosts not connected to vCenter now, and hosts that lost the connection in the last 24 h and came back	red / amber
Failed logins	wrong user name or password: one row per user, source address and server, with the count and the first and last time	amber; red from 10 failures
Virtual machine events	guest shutdowns and restarts, power-offs, resets, HA restarts and failures, and who did it	blue = someone did it, amber = HA or nobody, red = a failover or power-on failed
Other errors and warnings	every other error and warning event; the same event on the same object counted once	red = error, amber = warning
Configuration issues	what vCenter shows as configuration issues (SSH left on, HA problems, ...)	amber
All hosts	every host: connection, maintenance mode, ESXi version and build, hardware, its alarms and its errors / warnings	red / amber / blue row

On top: the counts in coloured boxes. The subject says the most important ones, e.g. `[AAP] VMware alarms report: 1 critical, 2 warning alarm(s), 47 failed login(s) (events: last 24 h)`.

Set up the report

1. **Templates > Create template > Create job template:**
   - Name: `VM - alarms report`
   - Inventory: any (e.g. your VMware one: the job runs on the AAP side)
   - Project: site-automation. Playbook: `playbooks/vm_alarm_report.yml`
   - Execution environment: your VMware one (this job needs only pyVmomi, which it has)
   - Credentials: your **VMware vCenter** credential. A read-only vCenter account is enough.
   - Variables: `report_email_to: vmteam@yoursite.mil`
   - Save.
2. **Schedules > Create schedule:** e.g. every day at 06:00.

Setting (template Variables)	Default	What it does
`vm_alarm_hours`	`24`	the events of the last this-many hours (168 for a weekly report; 0 = alarms and hosts only)
`vm_alarm_types`	`[vcenter, datacenter, cluster, host]`	whose alarms; add `vm`, `datastore` or `network` for theirs too
`vm_alarm_login_critical`	`10`	this many failed logins of one user from one place, or more, is red
`vm_alarm_fail`	`false`	`true` = the job shows **failed** on a critical alarm or a host not connected, for a workflow
`vmware_datacenter`	(all)	one datacenter only

The ACT analysis

What you get: an email "VMware alarms ACT analysis". First "What to do first", then one row per problem (P1, P2, ...): severity, object, the problem, the **likely cause**, the evidence, the **fix** and a **confidence**. The confidence is ACT's own estimate, from 0 to 100: green 80 and up (the evidence shows it), amber 50-79 (likely), red under 50 (a guess: check first). These are likely causes, not certain ones: check before you change anything. ACT runs no command and changes nothing.

Where ACT runs, and what about the hosts? ACT runs inside this job's execution environment, on the AAP server (or the execution node that runs the job). Not on the ESXi hosts, not on the VMs. So:

- The **ESXi hosts need nothing**: no Python, no network path to ACT.
- **Python** is in every execution environment (Ansible itself runs on it; ACT needs 3.8 or later).
- The **AAP node must reach the model's address over HTTPS** (port 443): `https://api.genai.mil` for GenAI.mil, or your `site_act_url`. The job checks this first and says plainly when it cannot:
- *"cannot reach the model ... Open HTTPS ... or set a proxy"*: ask for a firewall rule from the AAP node to that address, or set your proxy in `playbooks/group_vars/all.yml`: `site_act_env: {HTTPS_PROXY: "http://proxy.yoursite.mil:8080", NO_PROXY: "localhost,.yoursite.mil"}`
- *"Its certificate is not trusted"*: the execution environment does not trust the model's certificate authority. Put that CA certificate (public, `.pem`) at `playbooks/files/ca/model-ca.pem`, add `site_act_ca: "{{ playbook_dir }}/files/ca/model-ca.pem"` to `all.yml`, and add the line `playbooks/files/ca/` to `.site-local` (so an update keeps it).

Privacy: before anything leaves, ACT replaces host, cluster, datacenter and VM names, IP addresses and user names with placeholders, and puts the real names back into its answer.

Set it up:

1. **The key.** If your other ACT jobs have an **ACT model key** credential, use it. If not: create the credential type from `aap/credential_types/act_model_key.yml`, then a credential of that type with your GenAI.mil (or Ask Sage) key (SECRETS.md).
2. **Templates > Create template > Create job template:**
   - Name: `VM - alarms ACT analysis`

- Inventory, project, execution environment: as for the report. Playbook: `playbooks/vm_alarm_act_analysis.yml`
- Credentials: **VMware vCenter** and **ACT model key** (both)
- Tick **Prompt on launch** next to **Job type** (for the dry run)
- Variables: `report_email_to: vmteam@yoursite.mil`
- Save. The provider and model are your usual ACT settings (`site_act_provider`, `site_act_models` in `all.yml`); the default is GenAI.mil.

3. **First run, as a dry run:** Launch, Job type **Check**. It reads vCenter, lists the problems it would give ACT, and calls nothing. Then launch it normally.

Both in one go: a workflow with `VM - alarms report`, then `VM - alarms ACT analysis` linked with **Always**. Each sends its own email. Or schedule just the ACT analysis: its email lists every problem too.

Green or red: nothing wrong = ACT is not called and no email is sent (`vm_alarm_act_email_if_none: true` sends one anyway). The job is **red** when ACT could not run (no key, no network, an ACT error): the email still lists the problems, and says why.

Setting	Default	What it does
`vm_alarm_act_max_items`	`40`	give ACT at most this many problems, the most severe first (the rest are listed as not analyzed)
`vm_alarm_act_batch`	`site_act_batch` (5)	problems per question to ACT: 15 problems are three questions of 5, each with only its problems' evidence, in one report. A long answer about many problems is what a gateway or proxy cuts off, or what runs past the model's time. `0` = all in one question (before 0.31.1)
`vm_alarm_act_config_issues`	`true`	configuration issues too
`vm_alarm_act_check_url`	`true`	check that the AAP node can reach the model first
`vm_alarm_act_model_timeout`	`site_act_model_timeout` (600)	seconds the model may take for its answer (a `GENAI_TIMEOUT` in `site_act_env` wins)
`site_act_timeout`	`1200`	seconds the whole ACT run may take (keep it above the model's)

Outage watch: what is down or hung right now

`playbooks/vm_outage_watch.yml`, every 5 to 15 minutes, in a workflow before the ServiceNow tickets job. It reads only what means an outage: hosts not responding, HA agents isolated, datastores not accessible, all paths down and device loss, HA restarts and failures, VMs waiting on a question, and hung VMs. A VM is hung only when it has no guest heartbeat AND does not answer a ping (or `vm_watch_probe_port`) from the AAP node, in every check of the run. A clean run is one line, with no email. Watch only: it restarts nothing, and lists the hung VMs a later phase would restart, so the false alarms can be counted first. Everything - what it reads, the settings, the workflow, the phase 2 plan - is in VM_OUTAGE_WATCH.md.

Ask a question: plain words, read-only

`playbooks/vm_ask.yml`, on demand. Someone types a question in the survey's box, for example *all VMs in the acas folder in all vCenters*, *VMs on datastores under 10% free* or *snapshots older than 7 days on hosts in maintenance mode*. GenAI turns it into a query of the job's own form, which is checked against a whitelist. The job reads every vCenter and answers, with joins across VMs, hosts, clusters, datastores, snapshots and alarms. It only reads: a question that asks to restart, delete, move or change anything is refused before GenAI sees it. The setup, the survey, what you can ask about and the query are in VM_ASK.md.

Capacity planning: overall and per cluster

`playbooks/vm_capacity_report.yml` answers "how much room is left, and for how long?" - for all clusters together and for each cluster. It only reads. The history comes from **vCenter's own daily statistics** (it keeps a year of them at the default statistics level), so it works from the first run: nothing has to be collected first.

What the report shows

Section	What it shows
Overall	all clusters together: CPU and memory capacity, used, used with a host down in each cluster, growth per month and the days until the target - written `to 80% N-1`: 80 % of what is left with a host down, not full hosts; hosts usable and **hosts recommended** (now, and within 12 months); vCPUs per core and room for more VMs; shared storage with its growth and runway
Clusters: CPU and memory	per cluster: hosts usable, CPU and memory used, **memory used if the biggest host fails** (N-1: the cluster must still run everything), vCPUs per core, VMs and their average size, memory growth, **memory runway** (days and date until memory reaches `80% N-1`, the target with a host down - not until the hosts are full), **room for more VMs** of the average size (and what limits it), **hosts recommended**, VMs added / removed in the last 30 days
Clusters: storage	per cluster, its shared datastores together: capacity, free, used, provisioned (thin disks at full size), growth, days until 85 % and until full
Datastores: runway	each shared datastore, the one that fills first on top: growth, days (and date) until 85 %, 90 % and full, and how well a straight line fits its history
Math vs GenAI (with `vm_capacity_act: true`)	for every item, the job's runway (the math) next to ACT's own estimate (GenAI), whether they agree, ACT's recommendation and reasoning, and its confidence
Hosts per cluster	every host: state, cores, CPU and memory used, VMs - an unbalanced cluster shows here

Hosts recommended is a count of hosts of the cluster's average size (cores, memory) that keeps memory and CPU at their targets (80 %) with one host down - for example `1 now (memory 59% on average then); 2 within 12 months`. "Within 12 months" applies the current growth. It is a sizing guide in hosts, not a list of models.

How the runway is worked out: a straight line through the last 90 days of vCenter's daily values (memory consumed, CPU used, datastore space used), continued at that rate until it reaches the limit. It assumes the last 90 days repeat. Growth usually comes in jumps (VMs deployed in batches): a 30-day window turns one build-out into the rate and reads "9 days to full" when it is months, so the default fits 90 days, which averages the batches out (`vm_capacity_trend_days: 30` reacts faster to a real change of rate). "Not growing" means the line is flat or falling. The **trend fit** (R^2) says how straight the history is: poor means jumps (VMs moved, snapshots deleted, a datastore grown), and the runway is a rough guide then.

What the cluster runway runs to: `80% N-1`, written in every cell - 80 % of the memory (or CPU) left with one host down, not 100 % of what is installed. A cluster at 65 % used today can be at 76 % with its biggest host taken out of the math, so `9 days (2026-11-06) to 80% N-1` means nine days until that figure crosses 80 % - the point at which the cluster can no longer lose a host and stay under its target - not nine days until the hosts are full. `80% N-1 reached` is a cluster past that point today. Datastore runways are plainer: to 85 %, to 90 % and to full.

Math vs GenAI

With `vm_capacity_act: true`, ACT (the AI assistant, GenAI.mil or Ask Sage) reads the same numbers and makes **its own estimate** for the overall picture, each cluster and each datastore: when it needs action (in days), what to do, why, and how sure it is. The report puts the two side by side:

Math (straight line)	GenAI (ACT)	Agreement
102 days (90% full)	55 days	GenAI 47 days sooner
0 days (memory 80% N-1)	0 days	agree

They **agree** when they are within 30 days or 25 % of each other. Where they differ, read ACT's reasoning (a recent jump, a limit that comes first, a poor fit), and plan for the sooner one. ACT states needs in hosts, cores, GB and TB, and timing in days or months. It runs on the AAP side and runs no command (as in "The ACT analysis" above: the same key, URL, proxy and CA settings).

Set it up

1. **Templates > Create template > Create job template:**
   - Name: `VM - capacity planning`
   - Inventory: any (e.g. your VMware one). Project: site-automation. Playbook: `playbooks/vm_capacity_report.yml`
   - Execution environment: your VMware one. Credentials: **VMware vCenter** (read-only is enough)
   - Tick **Prompt on launch** next to **Variables** (to try one cluster)
   - Variables: `report_email_to: vmteam@yoursite.mil`
   - Save. Launch it once and read the report.
2. **Per cluster:** the same report for one or a few clusters - Variables `vm_capacity_clusters: [PROD-CL01]` (`*` works: `[PROD-*]`). A second template with that variable gives each cluster its own report.
3. **GenAI's estimate (optional):** add the **ACT model key** credential to the template, and `vm_capacity_act: true` to its Variables. Launch.
4. **Schedule: Schedules > Create schedule**, e.g. every Monday at 07:00 (your time zone).

Setting	Default	What it does
`vm_capacity_clusters`	`[]` (all)	only these clusters
`vm_capacity_failover_hosts`	`1`	hosts down to plan for (`N-1` in the report); a larger HA admission control failover level wins
`vm_capacity_mem_target_pct` / `_cpu_target_pct`	`80` / `80`	memory / CPU used at most this, with those hosts down
`vm_capacity_vcpu_per_core_max`	`4`	vCPUs per physical core (amber from here)
`vm_capacity_storage_warn_pct` / `_crit_pct`	`85` / `90`	datastore used % (the storage runway is to 90 %)
`vm_capacity_runway_warn_days` / `_crit_days`	`90` / `30`	a runway shorter than this is amber / red
`vm_capacity_horizon_months`	`12`	"hosts recommended within N months"
`vm_capacity_trend_days` / `vm_capacity_history_days`	`90` / `120`	the days the trend is fitted on / read: 90 averages growth that comes in batches; 30 reacts faster to a real change of rate
`vm_capacity_include_local_datastores`	`false`	count a host's own datastores too
`vm_capacity_act`	`false`	GenAI's estimate next to the math
`vm_capacity_act_batch`	`site_act_batch` (5)	items per question to ACT: 30 items are six questions, each with the whole evidence (an estimate needs the overall numbers) and asking about its 5 items; `0` = all in one question
`vm_capacity_fail`	`false`	`true` = the job shows failed when a cluster or datastore is critical

Deploy a VM from a ServiceNow ticket

Four templates make up the VM deploy from a ServiceNow ticket - a change, its task, an incident or a catalog task:

Job template	Playbook	What it does
VM - deploy from ServiceNow ticket	`playbooks/vm_deploy_from_ticket.yml`	reads the ticket, checks the request against your rules, builds each VM from a template, writes the result on the ticket. Check = a dry run

Job template	Playbook	What it does
VM - deploy from ServiceNow ticket (workflow)	- (a workflow)	the deploy as *propose*, a person's approval, then *build* - one launch
VM - pick up deploy tickets	`playbooks/vm_deploy_poll.yml`	on a schedule: starts the workflow for each new VM request ticket. Builds nothing itself
VM - deploy settings finder	`playbooks/vm_deploy_inventory.yml`	read-only: your clusters, templates, datastores and folders, with the lines to paste

Its complete guide is its own document: VM_DEPLOY_GUIDE.md, also a PDF - `docs/pdf/Site-Automation-VM-Deploy-Guide.pdf`. It has the setup in AAP step by step (the execution environment, the vCenter role and its privileges, the credentials, the job template and its survey, the approval workflow, the scheduled pickup, the server's service and its AAP inventory, launching from AAP's API), how a run works, what requesters write, where each VM goes (sites, name rules, automatic placement, empty templates for MECM or kickstart), ready-made configurations, every message and what to do, where the logic lives - and every `vm_deploy_*` setting with its default, an example and when to set it.

Trust stores: vCenter's trusted roots and the ESXi hosts' trusted CAs

The *VMware - trust store report* (`playbooks/vmware_trust_report.yml`, a *VMware vCenter* credential, no inventory) reads vCenter's trusted root store (the same list as Administration > Certificates > Trusted Root Certificates; the account needs *Certificate Management* > *Manage* for the API call) and each ESXi host's trusted CA certificates (`vmware_trust_esxi: false`: vCenter only), and says which hold a compromised or dropped certificate authority - the same list as the trust check on the Linux hosts. Read-only; a hit fails the job; emailed as the other VMware reports. With `check_trust_remove: true` the chain is deleted from vCenter's trusted roots and each ESXi host's trusted CA list is replaced without it (Check mode shows what would go). TRUST_STORES.md.

ESXi security settings (every night): SSH off, timeouts, lockdown - and the vCenter appliance's access

One job, `playbooks/esxi_security.yml`, sets these on every ESXi host, through vCenter:

What	Setting	Default
SSH off: the service stopped, and set to start manually	`esxi_security_ssh`	`disabled` (`enabled`, or `""` = leave it)
ESXi Shell off (the host's local shell, a separate service from SSH): the same	`esxi_security_shell`	`disabled` (`enabled`, or `""` = leave it)
Timeouts at 600 s (10 minutes): SSH and the ESXi Shell stop by themselves 600 s after someone starts them (`UserVars.ESXiShellTimeOut`), and an idle SSH or shell session is logged out after 600 s (`UserVars.ESXiShellInteractiveTimeOut`)	`esxi_security_settings`	those two, at `600`

What	Setting	Default
Lockdown mode normal: the host is managed only through vCenter; the DCUI (the host's console) still works	`esxi_security_lockdown`	`normal` (`disabled`, or `""` = leave it). **strict is refused**, and a host already in strict is left alone

The vCenter appliance itself (since 0.68.0) - its VAMI's Access page (`https://<vcenter>:5480` > Access) - on every vCenter of the job, when you set one (all are `""` by default, so nothing changes until you do):

VAMI says	Setting	Values
SSH Login	`esxi_security_vcsa_ssh`	`disabled`, `enabled`, or `""` = leave it
DCUI (the appliance's console screen)	`esxi_security_vcsa_dcui`	the same
Console CLI (the appliance shell on its console)	`esxi_security_vcsa_consolecli`	the same
Bash Shell	`esxi_security_vcsa_shell`	the same; turned on, it turns itself off after `esxi_security_vcsa_shell_timeout` seconds (3600)

YAML

```
esxi_security_vcsa_ssh: disabled      # SSH off every night, as on the hosts
esxi_security_vcsa_shell: disabled
# DCUI and Console CLI left as they are: the console is the way in when the network is not
```

No new credential: the job uses its **VMware vCenter** credential through vCenter's API (`/api/appliance/access`, vCenter 7 and 8; `/rest` on 6.7). Its account must be in the single sign-on group **SystemConfiguration.Administrators** (administrator@vsphere.local is); otherwise vCenter answers 403, the report says so for that vCenter, and the job fails after the hosts are done. Each setting is read back after it is set. The report has a section **vCenter appliance access** (each setting before, what changed) and the email goes out when one changed or failed, as for the hosts.

It changes **only what differs**: a host that already matches is not touched. So it is safe to run every night: it puts back whatever someone changed (SSH turned on, a timeout changed, lockdown turned off) and the email says which host and what. A dry run (Check) changes nothing and lists what it would change. Hosts not connected to vCenter are skipped and listed.

Another timeout? `esxi_security_settings` is a list of advanced settings, name: value. Add or remove lines, e.g. the DCUI and Host Client idle timeouts:

YAML

```
esxi_security_settings:
  UserVars.ESXiShellTimeOut: 600
  UserVars.ESXiShellInteractiveTimeOut: 600
  UserVars.DcuiTimeOut: 600
  UserVars.HostClientSessionTimeout: 600
```

Before the first real run: who logs in to the hosts directly?

Lockdown mode **blocks direct logins** to the hosts: SSH, the Host Client (`https://<host>/ui`), and any tool that connects to a host instead of vCenter. Most often that is the **vulnerability scanner** with ESXi credentials, and sometimes a monitoring or backup tool. Ask those teams first. For each such account, add it to the host's **exception users**: the job adds them **before** it turns lockdown on, and never removes one.

```yaml
esxi_security_lockdown_exception_users: [svc_scanner, svc_monitor]
```

Exception users must be **local accounts on the host**, or **Active Directory accounts with their own permission on the host**. A `vsphere.local` account or an AD group does not work. Your vCenter service account for AAP is not affected: lockdown keeps vCenter's access.

Set it up

1. **The vCenter account** needs the privileges in "Before you start", step 2 (the ESXi security settings row), on the hosts or their cluster.
2. **Templates > Create template > Create job template:**
   - Name: `ESXi - security settings`
   - Inventory: any (e.g. your VMware one). Project: site-automation. Playbook: `playbooks/esxi_security.yml`
   - Execution environment: your VMware one. Credentials: your **VMware vCenter** credential
   - Tick **Prompt on launch** next to **Job type** (for the dry run) and next to **Variables** (to try it on one host)
   - Variables: `report_email_to: vmteam@yoursite.mil` and, if you have them, `esxi_security_lockdown_exception_users: [...]`
   - Save.
3. **Dry run:** Launch, Job type **Check**. Read the report: every host and what it would change.
4. **One host for real:** Launch, Job type **Run**, Variables `esxi_security_hosts: [esx01.yoursite.mil]`. Check the host in the vSphere Client: **Configure > System > Services** (SSH and ESXi Shell stopped, policy Start and stop manually), **Advanced System Settings** (the two timeouts), **Security Profile > Lockdown Mode** (Normal). Have the scanner team run a scan of it.
5. **All hosts:** Launch again without `esxi_security_hosts`.
6. **Every night at midnight:** the template's **Schedules** tab > **Create schedule**:
   - Name: `Nightly 00:00`
   - Start date: tomorrow, start time **00:00**
   - **Time zone: yours** (e.g. `America/New_York`). AAP does not assume your local time: with the wrong zone, "midnight" runs at another hour.
   - Repeat: **Daily**, every 1 day. No end. Save.

The nightly email comes only when a host was changed or failed (an empty night sends nothing); `esxi_security_email_only_if_changed: false` emails every night.

A host that needs SSH (a support case)

The nightly run would turn SSH off again. Exempt the host while the case is open, in the template's Variables:

```yaml
esxi_security_exclude_hosts: [esx07.yoursite.mil]
```

Then turn SSH on in the vSphere Client (and lockdown off if the vendor needs the Host Client). Remove the line when the case is closed: the next night sets the host back. To **undo** on purpose for every host: `esxi_security_lockdown: disabled`, and `esxi_security_ssh: ""` to leave SSH as it is.

Setting	Default	What it does
`esxi_security_hosts`	`[]` (all)	only these hosts (names, `*` and `?` allowed; the short name works)
`esxi_security_clusters`	`[]` (all)	only the hosts of these clusters
`esxi_security_exclude_hosts`	`[]`	never these hosts
`vmware_datacenter`	(all)	one datacenter only

The ESXi network check: vmkping, vMotion, MTU, storage latency

ESXi - network check (`playbooks/esxi_network_check.yml`) answers "would vMotion work between these hosts, at full speed?" without moving a VM. Read-only, nothing is changed on the hosts, SSH stays off: each ping is esxcli's `network diag ping` (the same as `vmkping` on the host), run on the host through vCenter - as `govc host.esxcli` and PowerCLI's `Get-EsxCli` do. No survey; schedule it weekly, or run it after a network change.

What it does, per vCenter:

1. **Every host's VMkernel adapters** - address, MTU, network stack, the services on each (vMotion, vSAN, management...) and the MTU of its switch (standard or distributed).
2. **vmkping between the hosts of each cluster**, on each adapter with vMotion (`vm_hostnet_services`): from every host to every other host, the adapter's full size with "don't fragment" - 8972 bytes on an MTU of 9000 - so jumbo frames are proven end to end. When that fails, a small ping too: small passes, big fails = an MTU smaller on the way (a switch port, an uplink, a router); both fail = no path at all (address, VLAN, port group, gateway).
3. **Pings to your targets** (`vm_hostnet_targets`) from every host - an NFS or iSCSI array, a gateway.
4. **The storage latency** each host sees on each datastore, from the hosts' real-time statistics (the last hour).

The report puts the problems first - one line per cause: a host whose path drops jumbo frames is one line, not one per ping; a datastore slow from every host is one line (the array), from one host that host (its paths) - then the adapters, every ping (status, bytes, answered, average and highest round trip) and the latency, the worst first.

Status	When
critical	full-size pings fail while small ones pass (an MTU on the way); no answer at all; a round trip from 150 ms (`vm_hostnet_rtt_crit_ms`, vMotion's limit); a datastore's average latency from 50 ms (`vm_hostnet_latency_crit_ms`)

Status	When
warning	some pings lost; a round trip from 5 ms (`vm_hostnet_rtt_warn_ms`); latency from 20 ms (`vm_hostnet_latency_warn_ms`); the hosts of a cluster on different MTUs; an adapter's MTU above its switch's; a host without vMotion while the others have it, or a cluster with none; a ping that could not run

Set up the network check

1. **The privilege.** The vCenter account needs **Host > CIM > CIM interaction** on the hosts, for the pings (step 2 of "Before you start"). Read-only reads the rest.
2. **The template.** *ESXi - network check*, playbook `playbooks/esxi_network_check.yml`, the VMware vCenter credential, the execution environment of your other VMware jobs, no Limit. `report_email_to` on its Variables to email it.
3. **The first run** with `vm_hostnet_raw: true` on its Variables (or at launch): the job prints the first ping, and the first one that failed, whole - the host's ESXi version, its own parameters of `esxcli network diag ping`, what was sent, the request and the answer or the fault as the host sent it. If the round trips in the report look a thousand times off, or a host says `could not ping: InvalidArgument` (it refused a parameter of the ping), send that output - ESXi versions name the fields and the parameters differently. Then take the setting off.
4. Optional: `vm_hostnet_targets`, e.g. `[{name: NFS array, host: 192.0.2.50, interface: vmk2}]` (`interface` - the adapter to ping from; default the management one); `vm_hostnet_services: [vmotion, vsan]` for vSAN's network too.

Setting	Default	
`vm_hostnet_services`	`[vmotion]`	the adapters' services pinged between the hosts of a cluster: `vsan`, `management`, `vSphereProvisioning`...
`vm_hostnet_targets`	`[]`	pinged from every host
`vm_hostnet_hosts` / `_clusters` / `_exclude`	`[]`	only these hosts / clusters, never these (names, `*` and `?`)
`vm_hostnet_ping`	`true`	`false` = the adapters and the latency only
`vm_hostnet_ping_count`	`3`	pings per pair
`vm_hostnet_max_pairs`	`400`	pings at most per vCenter: a cluster of n hosts makes n x (n-1) - 16 hosts, 240
`vm_hostnet_workers`	`4`	pings at the same time
`vm_hostnet_rtt_warn_ms` / `_crit_ms`	`5` / `150`	round trip
`vm_hostnet_latency`	`true`	read the storage latency
`vm_hostnet_latency_warn_ms` / `_crit_ms`	`20` / `50`	a datastore's average read or write latency
`vm_hostnet_raw`	`false`	print the first ping, and the first one that failed, whole: the host's parameters of the command, what was sent, the request, the answer or the fault

Setting	Default	
`vm_hostnet_fail`	`false`	`true` = the job shows failed on a warning or worse, for workflows

Each ping is sent the way the host's own esxcli describes the command: its parameter list is read once per host (as govc and PowerCLI do), the arguments go in the host's order and only the ones it knows - a parameter the host does not have (`df` on an old host) is left out and the ping's note says so. The adapters table shows each host's ESXi version and build, so hosts that answer differently show their version next to their adapters.

A host in maintenance mode or not connected is listed under "Hosts not checked" and not pinged from or to. A cluster is its datacenter's: when two datacenters both have a *Production*, they are two clusters - the hosts of one are never pinged from the other's, and the report names them `DC1/Production` and `DC2/Production`. The result is also the job artifact `esxi_network` (the counts and every ping).

Certificates of vCenter and the ESXi hosts: incidents and CSRs (weekly)

With `cert_renew_servicenow: catalog` there is no incident: each CSR is ordered from your PKI's catalog item, and that request is the CSR's record (no second CSR while it is open): CERT_RENEWAL_CATALOG.md.

Two jobs, with the same settings:

Template	Playbook	Credentials	What it does
`VMware - certificate report`	`playbooks/vmware_cert_report.yml`	VMware vCenter	**the report only**: every certificate, soonest expiry first, and for each one due what the renewal would do. Never ServiceNow, never a CSR - even with the ServiceNow credential attached. Printed and emailed
`VMware - certificate renewal`	`playbooks/vmware_cert_renew.yml`	VMware vCenter, ServiceNow API	the same report, **and** an incident and a CSR for each certificate due (below)

No inventory of hosts. Both run on the AAP side and talk to vCenter only: each host's certificate is read through vCenter, and its CSR is made through vCenter's API - no SSH, no ESXi account. vCenter's own certificate is read on its address, port 443. The template needs an inventory picked (any one); leave **Limit** empty - pick hosts with `vmware_cert_only`.

The renewal, `playbooks/vmware_cert_renew.yml` (template `VMware - certificate renewal`):

1. It reads **vCenter's certificate** - its Machine SSL certificate, the one its web pages show - and the certificate of **every ESXi host** connected to it (`vmware_cert_esxi: false`: vCenter's only). Reading changes nothing.
2. Each certificate that expires within `vmware_cert_warn_days` (30) - or has expired - is **due**, and gets a **ServiceNow incident**: critical within `vmware_cert_crit_days` (7), else warning, whatever `servicenow_min_severity` says.
3. For each due certificate, a **CSR** (certificate signing request) is made **where its key stays** and attached to the incident, with a work note: the certificate, the names in the CSR, and what to do next.

- **vCenter** makes its own, through its API - the same as the vSphere Client's *Generate Certificate Signing Request*. The subject and names are the current certificate's. The new key stays in vCenter's certificate store.
- **An ESXi host** makes its own - the same as the vSphere Client's *Generate CSR using FQDN*. The new key stays on the host.

4. While a certificate is due, each run adds a note to its incident. Once it is renewed, the next run notes the incident as cleared (`servicenow_resolve_cleared: true` resolves it).

Nothing in use is changed. A CSR only makes a new key that waits: vCenter and the hosts keep their certificates, no service restarts. Installing the issued certificate is a later step, by a person, as the work note says (that step does restart vCenter's services before 8.0 Update 2; a host may need a reconnect). It is emailed (`report_email_to`), and a dry run (Check) makes no CSR and sends nothing.

One incident per certificate. 15 hosts due: 15 incidents, each with its own CSR and steps, all for `servicenow_assignment_group`. A run again adds a work note to the same incident - never a second incident or a second CSR for the same certificate. A renewed certificate's incident is noted as cleared (resolved with `servicenow_resolve_cleared: true`); when it comes due again years later, that is a new incident.

The certificate	Incident	CSR	The work note says (step 3)
vCenter's, signed by your PKI (or self-signed)	yes	made by vCenter	Administration > Certificate Management > Machine SSL Certificate > Import and Replace Certificate > *Replace with external CA certificate where CSR is generated from vCenter Server (private key embedded)*: the issued certificate, and the CA chain. A snapshot first; vCenter HA off
An ESXi host's, signed by your PKI (or self-signed)	yes	made by the host	ESXi 8.0 Update 3 and later: the CA chain in vCenter's Trusted Root Certificates, `vpxd.certmgmt.mode` = `custom`, then the host > Configure > System > Certificate > Manage with External CA > Import and Replace > *Replace with external CA certificate where CSR is generated by ESXi (Private key embedded)*
Signed by vCenter's own CA (VMCA - how vCenter gives hosts their certificates unless told otherwise)	yes: it says to renew it in vCenter (its **Renew**)	none (`vmware_cert_vmca_csr: true`: one, to replace it with a certificate of your PKI)	-

One CSR per renewal. vCenter and each host keep **one** waiting key: a second CSR replaces it, and the certificate the PKI issues for the first one no longer fits. So the job makes a CSR once. Before it makes one, it looks at the certificate's incident: a CSR attached, or in a work note (when ServiceNow refused the

attachment) - and then it makes none. For the same reason, **make no CSR in the vSphere Client** while the PKI signs this one. A CSR lost? Close the incident: the next run opens a new one, with a new CSR. Without the ServiceNow credential nothing would record the CSR, so none is made (`vmware_cert_csr_without_servicenow: true` makes them and prints them).

Try it on certificates that are years from expiring

Every certificate you have is far from expiring, and you cannot add one that is not. Raise `vmware_cert_warn_days` for a run: with `200`, every certificate that expires within 200 days is due (`3650`: within 10 years). It is one number for both: the report's amber, and the renewal's incident and CSR. Each incident says the number it was opened with (`Due: it expires within vmware_cert_warn_days (200 days)`).

0. **The report of every host:** the `VMware - certificate report` template with `vmware_cert_warn_days: 200` - every certificate, and what the renewal would do for each one due. Nothing is sent anywhere but the email.
1. **Dry run.** Launch with Job type **Check** and these Variables:

```yaml
vmware_cert_warn_days: 200
vmware_cert_only: [esx01.yoursite.mil]       # one host; e.g. [esx01, esx02] or ["esx0*"]; your
                                             # vCenter by its name
```

The output says what it would do: `would open: esx01.yoursite.mil: ESXi host certificate ...` and `would make the CSR, and would open a ticket and attach it`.

2. **The incident only.** The same Variables plus `vmware_cert_make_csr: false`, Job type **Run**. One incident, for that host.
3. **With the CSR.** Remove `vmware_cert_make_csr: false` and run again. The host makes the CSR; it is attached to the same incident with the work note. Run it once more: no second CSR (`CSR on the ticket already`). Pick a host whose certificate is not being renewed right now: its CSR replaces any CSR the host already had waiting.
4. **vCenter.** The same with `vmware_cert_only: [vc01.yoursite.mil]`. vCenter's CSR needs the account's certificate rights ("Before you start", step 2). One vCenter first.
5. **Clean up.** Run without those lines (back to 30 days) and with `servicenow_resolve_cleared: true`: the test incidents are noted and resolved. Leave none open - an open test incident would be used again when that certificate really comes due.

Set it up

1. **The vCenter account**: the certificate rows in "Before you start", step 2.
2. **Templates > Create template > Create job template** - the report first:
   - Name: `VMware - certificate report`. Playbook: `playbooks/vmware_cert_report.yml`. Inventory: any. Execution environment: your VMware one. Credentials: your **VMware vCenter** credential only
   - Variables: `report_email_to: vmteam@yoursite.mil`. Tick **Prompt on launch** next to **Variables**. Save.
   - Schedule it weekly if you like (Monday 07:00): the list to hand to whoever renews certificates.

Then the renewal - **Create job template** again:

- Name: `VMware - certificate renewal`
- Inventory: any (e.g. your VMware one). Project: site-automation. Playbook: `playbooks/vmware_cert_renew.yml`

- Execution environment: your VMware one. Credentials: your **VMware vCenter** credential and your **ServiceNow API** credential
- Tick **Prompt on launch** next to **Job type** and next to **Variables** (to try it)
- Variables: `servicenow_assignment_group: YOUR GROUP NAME` (who gets the incidents) and `report_email_to: vmteam@yoursite.mil` - the rest: aap/extra_vars/vmware_cert_renew.yml
- Save.
- Optional - the days asked at launch instead of typed into Variables: the template's **Survey** tab > **Create question**, three times, then switch the survey **on**:

Question	Answer variable name	Answer type	Default	Required
Days to expiry (raise it to try the job)	`vmware_cert_warn_days`	Integer	`30`	yes
Only these vCenters or hosts (empty = all)	`vmware_cert_only`	Text	(empty)	no
Make the CSRs	`vmware_cert_make_csr`	Multiple choice (single select): `true`, `false`	`true`	yes

A schedule runs with the defaults (30, all, true).

3. **Try it**, as above.
4. **Every week:** the template's **Schedules** tab > **Create schedule**, e.g. every Monday at 07:00 in your time zone. 30 days gives four runs before a certificate expires; the incident is open from the first.

Setting	Default	What it does
`vmware_cert_warn_days`	`30`	a certificate that expires within this many days is due. Raise it to try the job
`vmware_cert_crit_days`	`7`	within this many days (or expired) the incident is critical
`vmware_cert_only`	`[]` (all)	only these vCenters and hosts (names, `*` and `?` allowed; the short name works)
`vmware_cert_make_csr`	`true`	`false` = the incidents only
`vmware_cert_esxi`	`true`	`false` = vCenter's certificate only
`vmware_cert_vmca_csr`	`false`	`true` = a CSR also for a certificate signed by VMCA
`vmware_cert_vmca_issuers`	`[]`	more issuers to take as VMCA (`*` and `?` allowed)
`vmware_cert_csr_fields`	`{}`	subject fields for vCenter's CSR (`organization`, `organization_unit`, `locality`, `state_or_province`, `country`, `key_size`) over the current certificate's
`vmware_cert_csr_without_servicenow`	`false`	`true` = make the CSRs without the ServiceNow credential, and print them

The attachment's name and type are the Linux renewal's settings: `cert_renew_attach_ext` (`csr`; `txt` for an instance that refuses `.csr`) and `cert_renew_attach_retry_txt`.

Whoever gets the incident


1. Submit the attached CSR to the PKI for a server certificate (the same names).
2. Attach the issued certificate (Base64 `.cer` / `.crt`) and its chain to the incident.
3. Install it as the work note says. The next run reads the new certificate and notes the incident as cleared.

With the CSRs ordered from the catalog instead (`cert_renew_servicenow: catalog`), the install can be the automation's, after an approval: Installing the issued certificates.

Installing the issued certificates of vCenter and the ESXi hosts (with an approval)

With the CSRs ordered from your PKI's catalog item (`cert_renew_servicenow: catalog`, CERT_RENEWAL_CATALOG.md), the PKI puts the issued certificate on the request (RITM), and two jobs with an approval between them put it in place - no file to copy, no `rui.crt` / `rui.key` to name, no key to handle: the key was made by vCenter or the host with its CSR and never left it.

VMware - certificate request (on demand) makes the CSR on the host you name and orders it: `RITM0012345`. The PKI puts the issued certificate on that request. Then the workflow, with that number:



By hand first, more automation when you want it. You name the request (the workflow's survey asks the RITM); the check reads that request alone. Two steps further, each a switch: the weekly renewal orders the CSRs of the certificates due by itself (`VMware - certificate renewal` with `cert_renew_servicenow: catalog`), and the check looks up the request of every certificate without being told (`vmware_cert_install_search: true`, a schedule on the workflow) - then only the approval is left to a person.

Request a certificate now

VMware - certificate request (`playbooks/vmware_cert_request.yml`): the vCenters and ESXi hosts you name (`vmware_cert_request_for`, exact names - the template's survey asks them; no `*` or `?`, never all) each get a CSR made where the key stays - vCenter's Machine SSL certificate, or the host's - ordered from your PKI's catalog item at once, whatever the certificate's expiry (VMCA-signed ones too). The job prints the request:

```
ORDERED RITM0012345 (REQ0010001) | esx01.yoursite.mil |
  esx01.yoursite.mil-1a2b3c4d-exp20261130.csr | the CSR is in the request (its question csr_file)
```

A certificate already on order gets **no second CSR** - it would replace the key that waits for the issued certificate: `ORDERED ALREADY RITM0012345 (Work in Progress)`. A request rejected or cancelled (Closed Incomplete, Closed Skipped) counts as none: a new CSR, a new order. The catalog item's settings are the renewal's (`cert_renew_catalog_item`, `cert_renew_catalog_variables` ...): CERT_RENEWAL_CATALOG.md. Check (a dry run) makes and sends nothing.

The check (reads only)

1. **The request named** (`vmware_cert_install_ritm`, e.g. `RITM0012345`): the check reads it in ServiceNow, finds the CSR the renewal or the request job attached (`esx01.yoursite.mil-1a2b3c4d-exp20261130.csr` - vCenter's `vc01.yoursite.mil-machine-ssl-...`), and so which vCenter or host it is for; only that one is read in vCenter. A number ServiceNow does not have, a request with no such CSR (a Linux or Windows one: their own jobs install those), or a host none of the job's vCenters has: said, nothing read. **No request named:** refused - unless `vmware_cert_install_search: true`, which reads every certificate of vCenter and its hosts (`vmware_cert_only`, `vmware_cert_esxi`) and looks up each one's request by its CSR's name and the old certificate's expiry date, as the renewal ordered it (a certificate never ordered is counted, nothing more).
2. **The CSR is read from the request** (the file the renewal attached, `esx01.yoursite.mil-1a2b3c4d-exp20261130.csr`), and the certificate counts only when **its public key is the CSR's** - whatever else is on the request is listed, never used. Where the PKI may put it, and in which form (PEM, DER, .p7b, a zip, pasted into a work note; on the RITM, its REQ or its catalog task): CERT_INSTALL.md - the same reader, the same settings (`cert_install_min_days`, `cert_install_fewer_names` ...).
3. **What installing it would do**, read from vCenter:
   - **An ESXi host:** it must be connected, and **vCenter's** `vpxd.certmgmt.mode` **must be** `custom` - in the default `vmca` mode vCenter may put its own certificate back on the host. Not custom: `HELD`, saying so; setting it is a vCenter-wide change, left to a person (vCenter > Configure > Settings > Advanced Settings, `vpxd.certmgmt.mode` = `custom`), and the next run plans it. **vCenter must trust the issuer**, or it refuses the host after the replacement: the job reads vCenter's trusted roots and, when the CA chain that came with the certificate is not there, the plan says it adds it (`add the CA chain to vCenter's trusted roots`). The PKI sent only the .cer: the chain comes from your CA bundle (`cert_install_ca_bundle`, the DoD PKI's - CERT_INSTALL.md); neither: `HELD` (ask the PKI for the .p7b).
   - **vCenter's own (Machine SSL) certificate:** whether its services restart - **before vCenter 8.0 Update 2 they do, about 10 to 20 minutes without vCenter**; 8.0 Update 2 and later replace it without a restart. The approval is the time to take the snapshot VMware advises (vCenters in linked mode: all of them, together) and to turn vCenter HA off.
4. **Ready ones go to the approval:** the job lists them and ends red - `NEEDS APPROVAL: ...` - so the workflow takes its *Run on fail* path. Nothing ready: it stays green.

```
READY | esx01.yoursite.mil | ESXi host | RITM0012345 | add the CA chain to vCenter
  vc01.yoursite.mil's trusted roots (CN=DOD ID CA-70,...) ; install it on the host
  (InstallServerCertificate: the key the host made with its CSR) and tell the host's services ;
  reconnect the host in vCenter vc01.yoursite.mil if it shows disconnected; then vCenter
  vc01.yoursite.mil must show the new certificate | the new one: serial 4A3F..., expires
  2027-12-05 14:02 UTC (from esx01.cer) | the host stays in use: no maintenance mode, its VMs keep
  running
READY | vc01.yoursite.mil | vCenter Machine SSL | RITM0012346 | replace vCenter
  vc01.yoursite.mil's Machine SSL certificate (the key vCenter made with its CSR) and add the CA
  chain ; then port 443 must serve it | ... | vCenter 7.0.3 (24322831): its services RESTART -
  about 10 to 20 minutes without vCenter ...
WAITING | esx02.yoursite.mil | ESXi host | RITM0012347 | RITM0012347 (Work in Progress): no
  certificate for this key on it yet
HELD | esx03.yoursite.mil | ESXi host | RITM0012348 | vCenter vc01.yoursite.mil's
  vpxd.certmgmt.mode is vmca, not custom: ...
```

The approved install (after the approval)

It takes only the plan of **its own workflow's** check step: the check hands on the plan with its workflow job's ID (`vmware_cert_install_plan_workflow`), and a plan from another workflow, or the job launched on its own, is refused before anything is read. Each approved certificate is **planned again first** - still ready (the mode, the connection, the certificate in use still the one it was ordered for), or it is `REFUSED` and nothing is done to it. Then:

- **The ESXi hosts, one by one, in use** - no maintenance mode, their VMs keep running: the CA chain added to vCenter's trusted roots when the plan said so; the certificate installed (`InstallServerCertificate` - the host's waiting key); the host's services told to take it; the host reconnected if vCenter lost it; and **vCenter must then show the new certificate** (`vmware_cert_install_host_wait`, 300 seconds).
- **Then vCenter's own**, last: its Machine SSL certificate replaced with the issued one and the CA chain (vCenter's waiting key), and **port 443 must serve it** (`vmware_cert_install_vcenter_wait`, 1800 seconds - its services may restart).
- A **work note** on each request: what was installed, where, by which AAP job.
- **Nothing is put back.** The CSR already replaced the old key on vCenter or the host, so the old certificate cannot return: a failure is said with what to do (a host that does not show it: the vSphere Client > the host > Configure > System > Certificate, Connection > Connect). The job is red when one was not installed.
- A key mismatch (*did not take the certificate*, *the host refused the certificate*) means a CSR was made on vCenter or the host after the ordered one - its key is gone: close the request; the renewal orders again.

It refuses to run on its own: *Nothing to install: no approved plan* - outside the workflow nothing was approved.

Set it up

1. **The renewal orders from the catalog** (`cert_renew_servicenow: catalog`): CERT_RENEWAL_CATALOG.md. The PKI attaches the issued certificate to the request or its catalog task - with its chain (.p7b), or only the .cer when you keep the DoD PKI's CA bundle in your repository (`cert_install_ca_bundle`: CERT_INSTALL.md).
2. **The vCenter account** of the *VMware vCenter* credential: administrator@vsphere.local, or a member of the single sign-on group **CAAdmins** - it replaces certificates, reads and adds trusted roots (the certificate rows in "Before you start", step 2).
3. `vpxd.certmgmt.mode` **=** `custom` on each vCenter whose hosts get PKI certificates (vCenter > Configure > Settings > Advanced Settings). Until then the hosts' certificates are `HELD` (vCenter's own is not).

4. **Two job templates** (inventory: any; execution environment: your VMware one; no Limit):

Template	Playbook	Credentials	Options
VMware - certificate install - check	`playbooks/vmware_cert_install_check.yml`	VMware vCenter, ServiceNow API	Job type **Check** allowed
VMware - certificate install - approved	`playbooks/vmware_cert_install_approved.yml`	VMware vCenter, ServiceNow API	Variables **not** prompted on launch

The settings: aap/extra_vars/vmware_cert_install_check.yml, aap/extra_vars/vmware_cert_install_approved.yml.

5. **The workflow** (workflow 39 in WORKFLOWS_AND_SCHEDULES.md), with a **Survey** (the workflow's Survey tab > Create question, then switch the survey on): question `Request (RITM) with the issued certificate`, answer variable name `vmware_cert_install_ritm`, Text, required (not required once the search is on: empty = every request). The answer reaches the check; the approved job ignores it.

Step	Node	Link
1	*VMware - certificate install - check*	(start)
2	*Approval* - name `Install the VMware certificates the check listed?`, **Timeout** e.g. 8 hours. Description: `Open the check job: its READY lines say what each one changes - vCenter's own may restart its services.`	**Run on fail**, from 1
3	*VMware - certificate install - approved*	**Run on success**, from 2

6. **The request job:** *VMware - certificate request*, playbook `playbooks/vmware_cert_request.yml`, the same credentials and execution environment, any inventory, no Limit; a **Survey** question `vCenter or ESXi host names (exact)`, answer variable name `vmware_cert_request_for`, Text, required. Tick **Prompt on launch** next to **Job type** (to try it as Check).
7. **Try it:** the request job as **Check** for one host (`would make the CSR, and order it`), then for real - its RITM. When the PKI has put the certificate on it, the workflow with that RITM: its READY line. The approved job launched as **Check** from the workflow says `WOULD INSTALL` and changes nothing.
8. **More automation, later:** `vmware_cert_install_search: true` on the check template, the survey question not required, and a daily schedule on the workflow (e.g. 07:30); and the weekly *VMware - certificate renewal* with `cert_renew_servicenow: catalog` orders the CSRs of the certificates due by itself.

Setting	Default	What it does
`vmware_cert_install_ritm`	`""`	the request to install from (the survey)
`vmware_cert_install_search`	`false`	`true` = without a request named, look up every certificate's request (for a schedule)
`vmware_cert_request_for`	`[]`	the request job: the vCenters and hosts to order a certificate for (exact names; required)

Setting	Default	What it does
`vmware_cert_install_trust_check`	`true`	read vCenter's trusted roots and add the CA chain a host's certificate needs. `false` = neither (you know vCenter trusts the issuer, or its trusted roots cannot be read: the hosts are `HELD` saying so)
`vmware_cert_install_host_wait`	`300`	seconds until vCenter must show a host's new certificate
`vmware_cert_install_vcenter_wait`	`1800`	seconds until vCenter's port must serve its new certificate
`vmware_cert_only`	`[]` (all)	only these vCenters and hosts

Email the report

Every VMware job can email its result: the secure boot report its whole list, the other jobs what they did. Email is off until there is an address to send to.

Step 1 - ask your mail admins for:

- the mail relay's name and port (e.g. `smtp.yoursite.mil`, port 25);
- whether it uses encryption: STARTTLS (usual on 25 and 587), SSL (port 465), or none;
- whether it needs a login, or instead accepts mail from allowed servers. Then the **AAP server's IP address** must be on its allowed list: the email leaves from the AAP server (with separate AAP execution nodes, from the node that runs the job - list those);
- which sender address to use (e.g. `aap-noreply@yoursite.mil`).

Step 2 - the relay, in your `playbooks/group_vars/all.yml` (VS Code, then Commit and Sync Changes; AAP picks it up at the next project sync):

YAML

```
report_email_smtp_host: smtp.yoursite.mil       # the relay from step 1
report_email_from: aap-noreply@yoursite.mil     # the sender from step 1
```

Add these lines only when step 1 says so:

The relay	Add to all.yml
port 25 or 587 with STARTTLS	nothing: that is the default
a port other than 25	`report_email_smtp_port: 587` (its port)
SSL on port 465	`report_email_smtp_port: 465` and `report_email_security: ssl`
no encryption at all	`report_email_security: none` (then no login can be used)
its certificate is from your own CA (DoD) and the job says `certificate verify failed`	put the CA certificate (`.pem`, public) at `playbooks/files/ca/smtp-ca.pem` in the repository, `report_email_ca_path: "{{ playbook_dir }}/files/ca/smtp-ca.pem"`, and the line `playbooks/files/ca/` in `.site-local` (so an update keeps it)

Step 3 - only if the relay needs a login: a credential, so the password stays out of Git.

1. AAP: **Automation Execution > Infrastructure > Credential Types > Create credential type**. Name it `SMTP relay`. Paste the `inputs:` part of `aap/credential_types/smtp_relay.yml` into **Input configuration** and the `injectors:` part into **Injector configuration**. Save.
2. **Credentials > Create credential**: type **SMTP relay**, the user name and password. Save.
3. On each VMware template: **Edit > Credentials**, add it next to the vCenter credential.

Step 4 - who gets it. One of:

- every VMware job, always: `report_email_to: [vmteam@yoursite.mil]` in `all.yml`;
- one template: its **Variables** box, `report_email_to: vmteam@yoursite.mil, ops@yoursite.mil`;
- whoever launches it: a survey question, variable `report_email_to`, type **Text**, not required. Left empty = no email.

Several addresses: separate them with commas. Copies: `report_email_cc`, the same way.

Step 5 - test it with the secure boot report: it only reads, so it is safe to run any time. Launch it with `report_email_to` set. In the job output, the task **Email | result** says `emailed "[AAP] VMware secure boot report: ..." to vmteam@yoursite.mil`, and the email arrives.

The other reports (health checks, certificate reports, ...) email the same way: EMAIL_REPORTS.md lists them, and explains when a report job is green or red.

What arrives: a formatted email, subject `[AAP] VMware secure boot report: 29 VM(s) to fix` (or `[AAP] VM restart: web01`, `[AAP] VM snapshot before-patch: web01`, ...). The secure boot report has number boxes (VMs checked, secure boot on / off, BIOS) and a table per problem: each VM with its folder, ESXi host, guest host name, IP, power state and guest OS - so VMs with the same name can be told apart. At the end: the AAP job, who started it, when, and which vCenter. The email also carries a plain-text copy. A dry run (Check) sends nothing; it says `DRY RUN: would email ...`. To change the look of the email: EMAIL_REPORTS.md.

The same report is in the job's **Details > Artifacts** (`vm_report`, and for the secure boot report `vm_secure_boot` with every VM's details), which is also what the next step of a workflow receives.

If it fails, the job fails (so nobody misses it) and says why:

The job says	Fix
`set report_email_smtp_host ... and report_email_from`	step 2 is missing (or not synced to AAP yet)
`could not send the email through ...: [Errno 111] Connection refused` / `timed out`	wrong name or port, or a firewall between the AAP server and the relay
`does not offer STARTTLS`	the relay uses SSL (port 465) or no encryption: see step 2
`TLS with the mail relay ... failed: ... certificate verify failed`	your own CA: the last row of step 2
`refused the login`	the user name or password in the SMTP relay credential
`could not send ...: 530 ... authentication required`	the relay needs a login (step 3), or the AAP server's IP on its allowed list

The job says	Fix
`refused every recipient` / `(refused: x@...)`	the relay does not accept that address (wrong address, or outside mail not allowed)
`the password would cross the network unencrypted`	a login with `report_email_security: none`: use starttls or ssl

AAP's own **Notifications** (the template's Notifications tab) only say that a job succeeded or failed. This sends the report itself.

What you see

- **restart:** `Restart requested for (operating system restart through VMware Tools): web01`. The job does not wait for the server to come back up; check its services afterwards, or run the health check.
- **shut down:** `Shut down (...): web01.`, once the VM is off (up to `vm_power_timeout`, 600 s). VMs that were already off are listed as such.
- **snapshot:** `Took snapshot "before-patch" (no memory) of: web01`.
- **delete snapshot:** `web01: deleted before-patch`. If the name is not there: `no snapshot named "x" (it has: ...)`.
- **notes:** the notes `BEFORE` and `AFTER`, for each VM.
- **change VLAN:** `web01: Network adapter 2 moved VLAN200`, or `already on VLAN200`.
- **secure boot report:** a count, then one line per VM to fix, with what to do.
- **datastore report, snapshot report, alarms report:** the report as text (the same tables as the email), with the counts in the task name, e.g. `VMware alarms report: 1 critical, 2 warning alarm(s), 47 failed login(s) (events: last 24 h)`.
- **alarms ACT analysis:** `VMware alarms ACT analysis: likely causes and fixes for 12 problem(s)`, then one row per problem with ACT's cause, fix and confidence.

Refusals, and what to do:

- `VMware Tools is not running`: a `guest` restart or shutdown cannot work. Fix Tools, or use `hard` if losing unsaved data is acceptable.
- `No VM is named ...`: names are exact (case included), with no wildcards.
- `2 VMs are named ...`: rename one, or set `vmware_datacenter` if they are in different datacenters.
- `Refused: ... is the AAP server or a protected VM`: by design. Do it in vCenter yourself.

Troubleshooting

Find the message in the job's output (the red task near the end), or in the email, then do what the last column says.

Every VMware job

You see	It means	Do
`No vCenter to talk to: attach a credential of type "VMware vCenter"`	the template has no vCenter credential	Template › Edit › Credentials › add your **VMware vCenter** credential
`vCenter ... refused the login`	the message says which: no domain in the user name (a local vCenter account is `name@vsphere.local`), a wrong user name or password, a locked account or an expired password - or that vCenter does not know the account (the jobs log in to every vCenter of `vmware_vcenters` with it; a `vsphere.local` account works only on the vCenters of its own single sign-on domain, in linked mode)	fix the credential (type **VMware vCenter**); log in to the vSphere Client of **that** vCenter with the same account to test it. The deploy stops when any vCenter refuses: it checks the new name is free in all of them
`vCenter ... accepted the login, but the account has no permission in that vCenter` (before: `NoPermission ... System.View ... group-d1`)	the account logs in (single sign-on) but has no role anywhere in that vCenter, so vCenter refuses the session	give it its role there: a **Global Permission** (Administration > Access Control > Global Permissions, Propagate to children) covers every vCenter of its single sign-on domain. Read-only is enough on a vCenter the job only reads - the deploy reads every vCenter of `vmware_vcenters` to check the new name
`Could not connect to vCenter ...: ... CERTIFICATE_VERIFY_FAILED`	the execution environment does not trust vCenter's certificate	add vCenter's CA to the execution environment; to test only, `vmware_validate_certs: false` in the template's Variables
`Could not connect to vCenter ...: timed out` or `Connection refused`	the AAP node cannot reach vCenter on port 443	a firewall rule from the AAP node (or execution node) to vCenter, port 443
`pyVmomi is not installed in the execution environment`, or `couldn't resolve module/action 'vmware.vmware...'`	the template uses an execution environment without the VMware parts	pick your VMware execution environment on the template ("Before you start", step 1)
A VM, host or datastore you see in vSphere is missing from a report	the vCenter account cannot see it	give its role on that folder or cluster, with **Propagate to children** ("Before you start", step 2)
A whole vCenter's datacenters and clusters are missing (the vSphere Client shows two or more vCenters)	the jobs read the credential's vCenter, plus only those in `vmware_vcenters`	`vmware_vcenters: [vc01..., vc02...]` in `all.yml` ("Before you start", step 5)

You see	It means	Do
Red **vCenters not read** on top, `- 1 vCenter(s) not read` in the title (the job failed at `every vCenter was read` only with `vmware_vcenter_fail_unread: true`)	that vCenter could not be reached, or refused the login; the rest of the report covers the others	the reason is in the row: `refused the login` = the account is not known there (in linked mode: give it a Global Permission); `timed out` / `Connection refused` = a firewall rule to that vCenter, port 443
`Could not find imported module support code for ... site_vmware_... Looked for ... ansible.module_utils.site_vcenters`	the folder `roles/vmware_vm/module_utils/` is missing: an update copied the changed files but not that new folder	copy `roles/vmware_vm/module_utils/` from the release into your repository, commit, sync the project
`the same vCenter as ...: read once` in the artifacts	a vCenter listed twice (a short name and its FQDN, or its IP)	nothing: it is read once
`Refused: ... is the AAP server or a protected VM`	by design	do it in vCenter yourself
`report_time_zone ... is not a time zone this execution environment knows: times are in UTC`	a misspelt name, or an execution environment without time zone data	a name as `timedatectl list-timezones` prints it (`America/New_York`, `Europe/London`); if the name is right, add `tzdata` to the execution environment's build
A report's time and a host's log time differ	the time zone, the event, or the host's clock	health report: "Times and clocks" above

VM inventory report

You see	It means	Do
Every VM in *VMs without encryption, EFI or vTPM* as not encrypted, though some are	the account cannot see VM Encryption on them, or they use vSAN encryption (the datastore's, not the VM's: vCenter gives the VM no key ID)	look at one in the vSphere Client: VM > Summary > *VM Encryption*. vSAN encryption is not VM Encryption - the report counts only the VM's own
vTPM `?`	vCenter gave no `tpmPresent` for that VM and its devices could not be read	look at the VM's hardware in the vSphere Client (Virtual TPM); a vCenter before 6.7 reads it from the devices - a later run usually has it
A VM table scrolls sideways on the website	more columns shown than fit (Columns: *Show all*, or a narrow window)	take some off with **Columns** (kept in your browser), put the sections list away (its `<<` button), or set `vm_inventory_hidden_columns` for everyone
The website's VM tables have no Enc / SB / vTPM columns	`vm_inventory_security: false`, or `report_web_theme` is not atlas or brief (those looks show the email's tables)	set `vm_inventory_security: true`; use the atlas or brief look

Datastore and snapshot reports, snapshot cleanup

You see	It means	Do
The datastore heading still says 80%	`vm_datastore_warn_pct: 80` is set somewhere (it wins over the default 85)	remove it from `all.yml` and the template's Variables, or set the number you want
`vm_snapshot_max_age_days must be a number of days`	a survey or variable answer like `three`	a number: `1`, `2`, `3`
The snapshot report says 3 days although you set 2 (or the default is now 5)	in the workflow, the **survey answer** wins over the template's Variables and the default - a survey made from an earlier release still has Default `3`	change the survey's answer or its Default (section "Snapshots")
`Refused: N snapshots are older than ... - more than vm_snapshot_cleanup_max`	more than 50 at once (often a wrong number of days)	check the days; for a big cleanup on purpose, raise `vm_snapshot_cleanup_max`
`NOT DELETED ...: no longer there, or no longer old enough / now kept`	the snapshot changed between the report and the approval	nothing: it is safe. Run the workflow again
`Taken by` says `unknown`	vCenter no longer keeps the event (often after 30 days)	nothing: the snapshot's description may name the AAP user
`HELD BACK ...: its name has none of: Patching, Patches, Patch`	`vm_snapshot_cleanup_name_words` is set: only those names are cleaned up	nothing, if that is what you want; `[]` = any name
A patching snapshot was not deleted	it is younger than `vm_snapshot_max_age_days` (it waits), its name or description says keep, or the word is only in its **description** (only the name counts)	read its line in the job output: `HELD BACK` gives the reason; a young one is not listed as old at all

Pick lists

You see	It means	Do
`NOT UPDATED ...: its survey has no question whose variable is vm_snapshot_picks`	the workflow's survey has no such question, or its Answer variable name differs	add the question (section "Pick lists", Step 2), or set `vm_pick_snapshot_question` / `vm_pick_reboot_question` to its variable name
`NOT UPDATED ...: the question ... is a text question`	the question is not multiple choice	make it **Multiple choice (multiple select)**
`NOT UPDATED ...: no job template or workflow job template ... that the AAP user can see`	a typo in the name, or the AAP credential's user has no role on it	the name as AAP shows it; the **Admin** role on that template for the user
`2 templates are named ...`	a job template and a workflow share the name	`{template: "<its ID>", kind: workflow}`
`WARNING: the survey of ... is turned off`	the list was written, but nobody is asked	the workflow > Survey > switch it on
`SKIPPED ... - not a choice of the pick list`	a line that does not end with `[vCenter/VM...]` (typed by hand, or from an old list)	pick from the list
`SKIPPED ... - VMware Tools is not running in it`	a guest restart needs VMware Tools	pick it again with How = `hard`
`Refused: the approved plan is for a hard restart, this run says vm_power_mode guest`	the step after the approval got another answer than the plan	nothing was done: launch the workflow again
`None of the picks can be ... now`	everything picked is gone, held back or not allowed now (the reasons are listed)	nothing: the workflow stopped before its approval

ESXi security settings

You see	It means	Do
`... the vCenter account lacks the privilege Host.Config.... on this host`	the vCenter role misses that privilege	add it to the role ("Before you start", step 2), on the hosts or their cluster
`lockdown strict is refused`	`esxi_security_lockdown: strict`	use `normal`
`No host matches (hosts: ...)`	a typo in `esxi_security_hosts` / `_clusters`, or `vmware_datacenter`	the names as the vSphere Client shows them
`X: the host has no such setting`	that advanced setting does not exist on this ESXi version	check the name (case matters), or remove it from `esxi_security_settings`
`lockdown exception users: ... - lockdown left disabled, so they are not locked out`	the exception users could not be added, so lockdown was not turned on (on purpose)	fix the cause (often a privilege, or an account the host does not know) and run again
`lockdown is strict: left as it is`	someone set strict on that host	nothing, or set it to normal in vCenter if strict was a mistake
A host is listed as **skipped**	it is not connected to vCenter	reconnect it; the next run sets it
The scanner (or another tool) cannot log in to a host any more	lockdown blocks direct logins	add its account to `esxi_security_lockdown_exception_users` and run again, or exempt the host
SSH is off again on a host you opened for support	the nightly run did its job	`esxi_security_exclude_hosts` while the case is open
The ESXi Shell stays on, and the report does not mention it	`esxi_security_shell: ""` is set somewhere (leave it as it is)	remove it: the default is `disabled`
Every night's email lists the same host as changed	something turns the setting back every day (a host profile, a script, a person)	find what it is: two tools fighting over one setting

Certificate renewal

You see	It means	Do
`vCenter X refused to make the CSR (HTTP 403 ...)`	the account may read vCenter but not make its certificates	give it Certificate Management as a Global Permission, or add it to CAAdmins ("Before you start", step 2); or make that one CSR in the vSphere Client and attach it to the incident by hand
`vCenter X refused the login to its API (HTTP 401)`	the credential's user name (`name@domain`) or password	fix the VMware vCenter credential
`the vCenter account lacks the privilege Certificate.Manage` (an ESXi host's CSR)	the role misses Certificates > Manage certificates	add it to the role, on the hosts
`vCenter X has no certificate API`	vCenter older than 6.7 Update 2	make the CSR in the vSphere Client and attach it to the incident by hand
`vCenter X did not make the CSR (HTTP 400: ...)` naming a field	vCenter wants a subject field the certificate does not have	set it in `vmware_cert_csr_fields` (the PKI sets the subject by its own rules anyway)
`the attachment was refused ... as a .txt file too`	the instance does not take `.csr` or `.txt` attachments	the CSR is in the incident's work note, to copy from there; the next run makes no other. To have them attached: allow `.csr` or `.txt` on the instance, or `cert_renew_attach_ext`
`no ServiceNow API credential: the CSR is made only with its ticket`	the template has no ServiceNow credential	attach it; or `vmware_cert_csr_without_servicenow: true` to have the CSRs printed
`vm_cert_warn_days: not a setting of this job`	a setting named like the other VMware jobs' (`vm_...`): it would be ignored, and the job would run at 30 days	the settings start with `vmware_cert_`: `vmware_cert_warn_days`, `vmware_cert_only`
The report says `within vmware_cert_warn_days (30)` though you set another number	a survey question for `vmware_cert_warn_days` (its answer, default 30, wins over the Variables box), or the name misspelt	change the survey's default, or the name
`vmware_cert_only (...) matches none of the vCenters and hosts read`	a typo, or a host of another vCenter	the names as the vSphere Client shows them; add the vCenter to `vmware_vcenters`
A host under **Not checked**, `not connected`	it is not connected to vCenter	reconnect it; the next run reads it
`CSR on the ticket already`, but the PKI lost the CSR	the incident has its CSR	close the incident: the next run opens a new one with a new CSR

You see	It means	Do
An incident says to renew in vCenter (VMCA), but your hosts use your PKI's certificates	that host still has the certificate vCenter gave it	`vmware_cert_vmca_csr: true` makes a CSR for it, to replace it with one of your PKI
Test incidents still open	they were opened with the days raised	run with the real days and `servicenow_resolve_cleared: true`, or close them

Deploy from a ServiceNow ticket

Every message of the deploy, its workflow and the scheduled pickup, with what to do: VM_DEPLOY_GUIDE.md, *When something goes wrong*.

Capacity planning

You see	It means	Do
`not enough history` / `No trend: vCenter has fewer than 7 daily samples`	a new vCenter, or its statistics level or daily interval was changed	wait a week; check vCenter > Configure > General > Statistics: the 1-day interval enabled, level 1 or more
`vCenter's daily statistics interval is turned off: no history`	the 1-day interval is disabled	enable it (same place); usage now is still shown
A runway that jumps from run to run	the trend fit is poor: VMs were moved, snapshots deleted, a datastore grown	read the Trend fit column; use `vm_capacity_trend_days: 60` for a longer, steadier line
`cannot lose a host`	the cluster has as many hosts down (or in maintenance) as it plans to survive	bring hosts back; or set `vm_capacity_failover_hosts: 0` for a cluster that needs no failover
`No cluster matches ...`	a typo in `vm_capacity_clusters`	the cluster's name as the vSphere Client shows it
`ACT did not run: ...` (the report), `ACT did not estimate: ...` (the job's last line)	as for the alarms analysis (key, network, certificate, a reply cut off)	the ACT rows above
Math and GenAI differ a lot	ACT weighed something the line does not (a jump, a limit that comes first)	read ACT's reasoning; plan for the sooner of the two

VMs created report

You see	It means	Do
By is unknown	vCenter no longer has the VM's creation event (it keeps them for a limited time), or the VM was created on a host directly	nothing: the VM still counts, by its creation date
Ticket is - for a VM the deploy built	its notes in vCenter were edited, so they no longer have the ticket's line ("*<ticket> - built <date>*")	nothing for the count; the ticket's own notes say which VM it built
a VM restored from a backup is listed	a restore creates a new VM in vCenter	nothing: to vCenter it is new
`vm_created_days must be a number of days`	the setting is not a number	`vm_created_days: 7`

Health report

You see	It means	Do
`vSphere HA is off` / `DRS is off` on a cluster that should not have them	your design	`vm_health_require_ha: false` / `vm_health_require_drs: false` on the template
`vCLS in retreat mode`	someone set `config.vcls.clusters.<id>.enabled` to `false` in vCenter's advanced settings (often for maintenance) and it was not set back	vCenter > Configure > Settings > Advanced Settings: set it to `true` when the work is done; DRS starts again
`vSphere HA agent: network isolated` / `network partitioned`	the host's management network cannot reach the other hosts (or its isolation address)	the host's management VLAN, uplinks and switch ports; then **Reconfigure for vSphere HA** on the host
`HA can survive 0 host failure(s) now`	the cluster is too full to restart a failed host's VMs	add capacity or move VMs: see the capacity planning report
HA agent `?` on every host	vCenter did not say (some versions or a limited account)	the HA state shows in the vSphere Client: cluster > Monitor > vSphere HA
`Could not read vCLS retreat mode` (blue)	the account may not read vCenter's advanced settings	nothing needed: retreat mode still raises vCenter's own alarm on the cluster
`vCenter ... has no datacenter named ...`	a typo in `vmware_datacenter`	the exact name, as the vSphere Client shows it
`Reading the health of datacenters, clusters and hosts from vCenter ... failed: ...`	something this job did not expect from your vCenter	send that line to the people who maintain this repository
Network drops and errors: `the last hour only: vCenter keeps no drop counts for the past day`	vCenter's 5-minute statistics are at level 1 (the default)	raise them to level 2 (Network drops and errors), or leave it: each run then covers the hour before it
a VM with many **received** drops (`Dropped in`)	the guest does not empty its receive ring in time: busy, too few vCPU, an E1000 adapter, small rings	VMXNET3; larger rings in the guest (Linux `ethtool -G`, Windows the adapter's *Rx Ring* settings); more vCPU
a host with network **errors**	the physical side: NIC, cable, SFP, switch port	the switch port's own error counters; swap the cable or SFP
`the network drop and error counters: ...`	the account could not read that vCenter's statistics	the VMware vCenter credential's account needs a role on the inventory (Read-only)

Alarms report

You see	It means	Do
`types: unknown object type(s) ...`	a typo in `vm_alarm_types`	use `vcenter`, `datacenter`, `cluster`, `host`, `datastore`, `vm`, `network`
`vCenter ... has no datacenter named ...`	a typo in `vmware_datacenter`	the exact name, as the vSphere Client shows it
An alarm the vSphere Client shows is missing	it is on a VM, datastore or network (not read by default), or in another datacenter	add its type to `vm_alarm_types` (e.g. `[vcenter, datacenter, cluster, host, vm]`); check `vmware_datacenter`
No events at all, or fewer than in the vSphere Client	`vm_alarm_hours: 0`, or the account sees only part of the inventory (vCenter shows an account only the events of what it can see)	give the role at the top of the vCenter inventory, with Propagate to children
`Only the newest 5000 events were read`	a busy vCenter	lower `vm_alarm_hours`, or raise `vm_alarm_max_events`
`Only the newest 2000 alarm changes were read`	an alarm that flaps (on, off, on ...) all day	find it in *Alarms that fired* (the highest counts) and fix its cause; or raise `vm_alarm_max_alarm_changes`
`Only the first 200 are shown`	a long table	the job's **Artifacts** (`vm_alarms`) have all of them; or raise `vm_alarm_max_rows`
The job shows **failed** with `critical alarm(s) ... host(s) not connected`	`vm_alarm_fail: true` is set	expected (for a workflow); remove it for a report only
`Reading alarms and events from vCenter ... failed: ...`	something this job did not expect from your vCenter	send that line to the people who maintain this repository

Alarms ACT analysis

You see	It means	Do
`nothing to analyze`, and no email	nothing is wrong: no alarm, no problem in the window	nothing. `vm_alarm_act_email_if_none: true` sends an email anyway
`A dry run (Check): ACT was not called`	the job ran as Check	launch it with Job type Run
`This job has no API key for provider genai: attach ...`	no **ACT model key** credential on the template, or its GenAI field is empty	add the credential (with the key for your provider) to the template
`This AAP node cannot reach the model at ... (... timed out / Connection refused / Name or service not known ...)`	a firewall, DNS or a missing proxy between the AAP node and the model	ask for HTTPS (443) from the AAP node to that address, or set your proxy: `site_act_env: {HTTPS_PROXY: "http://proxy.yoursite.mil:8080"}` in `all.yml`
`... Its certificate is not trusted: set site_act_ca ...`	the execution environment does not trust the model's certificate authority	put that CA certificate at `playbooks/files/ca/model-ca.pem`, `site_act_ca: "{{ playbook_dir }}/files/ca/model-ca.pem"` in `all.yml`, and `playbooks/files/ca/` in `.site-local`
`ACT failed: ...` with `401` or `Unauthorized`	the key is wrong or expired	a new key in the credential
`ACT failed: ...` with `429` or `Too Many Requests`	the key's quota per minute	run it less often, or lower `vm_alarm_act_max_items`
`model turn exceeded the 600s total timeout` (older releases: `90s`, `300s`), often `after a transient provider failure`	the model (or the provider, retrying after an error) took longer than ACT allows for one answer: `site_act_model_timeout`, 600 s	run it again (a provider hiccup passes); `site_act_model_timeout: 900` in `all.yml` (keep `site_act_timeout` above it); fewer items (`vm_alarm_act_max_items: 20`); or a faster model
`ACT failed: ... the reply was cut off after N bytes ... (after 4 attempts)` (before 0.17.1: `ACT failed: crash: IncompleteRead: IncompleteRead(N bytes read)`)	the model's answer was cut off on its way back: the gateway or a proxy closed the connection partway through it. Since 0.17.1 (ACT 0.6.25) ACT asks again, so this means every attempt was cut	run it again (a dropped connection passes); if it keeps failing at about the same size, the answer is too long for something on the way: fewer items (`vm_capacity_act_max_items: 10`, `vm_alarm_act_max_items: 10`); tell the network team the size and how long it took
`ACT produced no result (it timed out after 1200s ...)`	a slow model, or a lot of evidence	`site_act_timeout: 1800`, or `vm_alarm_act_max_items: 20`
`ACT's answer is below as text`	the model did not use the table format	the answer is still in the email. Run it again, or try another model (`site_act_models`)

You see	It means	Do
`The 'file' lookup had an issue accessing the file 'files/ocsp/...'` (0.31.0), or an OCSP row `not found in the project: files/ocsp/...`	the certificate is not in the project AAP synced: the repository's `.gitignore` leaves out `*.crt` / `*.pem` (before 0.31.1 also in `playbooks/files/ocsp/`), so it was never committed - VS Code shows such files greyed out	`git add -f playbooks/files/ocsp/*.crt`, commit, push, sync the project; or add `!playbooks/files/ocsp/*.crt` to `.gitignore`
A row says `ACT gave no answer for this one`	the model skipped that problem	run it again; fewer problems (`vm_alarm_act_max_items`) help a small model
The analysis works with a few problems, not with more (cut off, timed out, or no readable answer)	one answer about many problems is too long for the gateway, a proxy, or the model's time	`site_act_batch` (5) asks every ACT job 5 items at a time (the alarms since 0.31.1, capacity planning and log analysis since 0.32.0); `site_act_batch: 3` if 5 still fails, or the job's own `vm_alarm_act_batch` / `vm_capacity_act_batch`
`ACT did not analyze every problem: P6-P10 not analyzed: ...`	one batch failed, the others were analyzed (the report has them)	the reason after it, as in the rows above; run it again
The job is red, but the email came	ACT could not run; the email lists the problems and says why	fix what the email says, then run it again

Test the way to the model by hand, from the AAP server (the execution environment uses the same network):

```shell
curl -sS -o /dev/null -w '%{http_code}\n' https://api.genai.mil/v1/chat/completions
```

Any number (401, 404, 405) means the way is open. `Could not resolve host`, a timeout, or `SSL certificate problem` is the problem the job reports.

Limits

- **Change VLAN between a standard and a distributed switch.** Moving an adapter from a standard switch port group to a distributed one, or back, fails inside the `vmware.vmware` collection (2.11); the job says so and changes nothing. Do that one in vCenter. Moves between port groups of the same kind of switch work.
- The guest keeps its IP settings after a VLAN change. A new VLAN usually needs new ones.
- `vm_names` are exact VM names. To act on many VMs, list them.
- The pick lists: see "Pick lists" > Limits.
- Tested against vcsim, VMware's vCenter simulator (`tests/vmware/run_vmware_test.sh`), not against a real vCenter. Run each job once as **Check**, then on a test VM, before you use it on real servers. The simulator raises no alarms: the alarms report's alarm handling is tested with recorded data (`tests/test_filters.py`, `tests/test_vmware_modules.py`). The ACT analysis is tested with the real ACT against a scripted model (`tests/test_alarm_act_contract.py`), not a real one.

20. VM outage watch: what is down or hung right now

A quiet job that asks vCenter one question, every few minutes: **is something down or hung right now?** When nothing is, it prints one line and stops: no email, no web page, no ticket. When something is, it reports it, hands it to the ServiceNow tickets job, and fails, so a workflow can react.

It is **not** the alarms report or the health report. Those are the morning overview and stay on their daily schedule. The watch reads only what means an outage, so it can run every 5 to 15 minutes without anyone noticing it.

Phase 1 - watch only (this release). The watch restarts nothing. For every VM it finds hung, it says what a later phase *would* do, so you can check each one by hand and count the false alarms before any action is turned on. Phase 2 (the response workflow: guest restart, approval, reset) is described at the end; it is not built yet.

Job template	Playbook	Credential
VM - outage watch	`playbooks/vm_outage_watch.yml`	VMware vCenter (read-only is enough); no Limit

What it looks at

Every vCenter of the job (the credential's, and `vmware_vcenters`), or one datacenter (`vmware_datacenter`).

Condition	Severity
An ESXi host not responding or disconnected, and not in maintenance mode	critical
A host's vSphere HA agent isolated, partitioned from the primary, host down, or in error	critical
A host's HA agent unreachable, or it failed to uninitialize	warning
A datastore not accessible (and not in maintenance mode)	critical
All paths down, a permanent device loss, or a VMFS heartbeat timeout in the window, **not cleared** since	critical
The same, cleared since (the clear event came later, on the same host and device)	warning
HA could not restart a VM, or found a host failed or isolated (events of the window)	critical
HA restarted or reset a VM, or started a failover (events of the window)	warning
A VM waiting for an answer in vCenter (a question: "moved or copied?", a locked file)	critical

Condition	Severity
A VM **hung**: no guest heartbeat AND no answer on the network, in every check of the run	critical
A VM with no guest heartbeat that answers on the network, or could not be probed (one signal only)	warning (`vm_watch_one_signal_severity`)
A vCenter that could not be read	critical
vCenter's single sign-on down now: an SSO service stopped, the test domain account refused, an OCSP responder not answering (`vm_watch_sso`; VMWARE.md)	critical

"The window" is the last `vm_watch_window_minutes` (15): set it to the schedule's interval, so every event is seen once.

When is a VM hung?

Only when **three independent signals agree**, in **every** check of the run:

1. **vCenter's signal.** The VM is powered on, has VMware Tools installed, has been up at least `vm_watch_min_up_minutes` (15; a VM still starting has no heartbeat yet), and its guest heartbeat is red - or Tools stopped answering and the heartbeat is gray.
2. **The network.** The AAP node probes the VM: a ping, and a TCP connect to `vm_watch_probe_port` - by default 22, or 3389 for a Windows guest. It tries the IP addresses VMware Tools last reported, then the guest's host name and the VM's name in DNS (Tools that stopped often leave no IP). A connection made or refused counts as an answer: the guest's network stack is alive. A timeout is no answer - but a firewall between AAP and the guest gives one too, so it never makes a VM hung on its own.
3. **The traffic vCenter saw** (`vm_watch_traffic`, on). For a VM silent on both, the watch reads vCenter's real-time statistics: the network packets the VM sent since the first check (20-second samples). A hung guest sends none; a VM that sent any is alive - Tools died or a firewall stops the probe - and is reported with one signal, not hung. This needs no network path from AAP to the guest.

Only the VMs that fail the first signal are probed. The rest of the estate is never pinged.

Then the watch waits `vm_watch_confirm_seconds` (120) and reads those VMs again, for `vm_watch_confirm_checks` (3) checks in all. This happens in the same run, because an AAP execution environment keeps nothing between runs. What one signal alone means:

- **No heartbeat, but it answers the network.** VMware Tools died in a guest that still runs (common after a Tools upgrade, or under memory pressure). This is a warning and a ticket, never "hung".
- **No heartbeat, but it could not be probed.** There was no address, or no ping in the execution environment. This is also a warning, never "hung".
- **The heartbeat came back in a later check** (or the VM restarted, or someone powered it off). It is listed under "Not judged this run".
- **A vCenter task was running on it** (snapshot, consolidation, migration, clone, power operation). It is skipped this run and listed with the task's name. A VM stuns or loses its network for a moment during those.

A VM without VMware Tools is never judged on its heartbeat: vCenter has none to give.

What you see

Nothing down - the job is green, one line:

```
No outage: 24 host(s), 31 datastore(s), 812 powered-on VM(s) checked (vCenter vc01.yoursite.mil).
```

Warnings below `vm_watch_report_on` are listed under that line, each on its own line, and do not make a report.

Something down - the report (in the job output; emailed with `report_email_to`, on the report website with `report_web_dest`), then the job fails:


- **Down or hung now.** Each condition with its severity, where it is, and what to do.
- **Would be restarted in phase 2 (nothing was done).** The hung VMs a response would restart, with the signals and when they were checked. Check each by hand now. Was it really hung? Count the ones that were not.
- **Protected: ticket only.** Hung VMs that would never be restarted, with the reason: the AAP server, `vmware_protected_vms` / `vmware_protected_groups`, `vm_watch_protect`, or over `vm_watch_max_actions` (that many hung VMs at once means a host, the storage or the network, not the VMs).
- **Not judged this run.** Busy VMs, and VMs that recovered during the run.
- **How it judged.** The probe used.

Job artifacts, for the next step of a workflow:

- `vm_watch`: the conditions, the counts, `would_restart`, `protected`, `over_limit`, `not_judged`.
- `site_health` and `site_health_targets`: what the ServiceNow tickets job reads. There is one entry per vCenter, the check is `vm_watch`, and each condition is one finding.

Set it up

1. **The job template** "VM - outage watch": playbook `playbooks/vm_outage_watch.yml`, the VMware vCenter credential, the inventory that has your `aap` group (the AAP server is found by it), no Limit.
2. **Try it** once by hand. A clean estate is one green line; a red run shows the report.
3. **The workflow** "VM - outage watch (workflow)":



Always, not *On failure*. The tickets job opens one incident per condition, adds a work note while it lasts, and notes (or with `servicenow_resolve_cleared: true` resolves) the incident once a clean run no longer finds it. That only works when the clean runs reach it too. The incidents carry the vCenter's name and the object's, e.g. `[site-health] vc01.yoursite.mil: VM app01 is hung: ...`. `servicenow_min_severity: critical` keeps the one-signal warnings out of ServiceNow.

4. **The schedule.** Put it on the workflow, every 5 to 15 minutes, with **Concurrent jobs off** on the workflow so that a slow run never overlaps the next. Set `vm_watch_window_minutes` to the interval. Leave the daily health and alarms reports as they are.

5. **Email** (optional): `report_email_to` on the job template. Only runs that find something at `vm_watch_report_on` (critical) send it.

Settings


Setting	Default	What
`vm_watch_window_minutes`	15	how far back HA and storage events are read; the schedule's interval
`vm_watch_min_up_minutes`	15	a VM up for less than this is not judged
`vm_watch_confirm_checks`	3	checks of a suspect in one run (1 = once, no waiting)
`vm_watch_confirm_seconds`	120	seconds between them
`vm_watch_probe`	true	false = no probe: no VM is then hung, only one-signal warnings
`vm_watch_probe_port`	auto	also a TCP connect: auto = 22, 3389 for a Windows guest; a port; 0 = ping only
`vm_watch_traffic`	true	a silent VM that vCenter saw send network packets is alive, not hung
`vm_watch_traffic_packets`	1	packets from which it counts as alive
`vm_watch_probe_timeout`	3	seconds per address
`vm_watch_max_suspects`	50	suspects probed and confirmed per run; the rest are "not probed"
`vm_watch_one_signal_severity`	warning	`info` keeps one-signal VMs out of the tickets
`vm_watch_skip_vms`	[]	VM names never judged (`*` and `?`)
`vm_watch_skip_folders`	[]	VM folders never judged, e.g. `/DC1/vm/Lab*`
`vm_watch_protect`	[]	VMs a response would never restart (on top of `vmware_protected_vms` and the AAP server)
`vm_watch_max_actions`	5	the most VMs one run would restart; beyond it, ticket only
`vm_watch_fail_on`	[critical]	severities that make the job red; `[]` = always green
`vm_watch_report_on`	[critical]	severities that make a report (email, web page); `[critical, warning]` for the warnings too

Also used: `vmware_vcenters`, `vmware_datacenter`, `vmware_validate_certs`, `vmware_protected_vms`, `vmware_protected_groups`, `report_email_to`, `report_web_dest`, and the `servicenow_*` settings of the tickets job.

The probe and the execution environment. The ping runs inside the AAP execution environment. Without a `ping` program there (or without the right to send ICMP), every suspect is "could not be probed" and nothing is ever called hung. The job says so ("unavailable"). The TCP connect (22, or 3389 for Windows, by default) needs nothing from the execution environment; set `vm_watch_probe_port` to another port your VMs listen on if those are closed. The AAP node must be allowed to reach the VMs on that port, or ping them, through the firewalls in between.

Phase 2 - the response (not built yet)

Phase 2 will be built only once phase 1 has run long enough to show its false alarms. It will be conservative by default:



- **Only the VMs in "Would be restarted in phase 2".** Confirmed hung (both signals, every check), not protected, at most `vm_watch_max_actions`. Everything else stays a ticket.
- **A guest restart first, always.** It goes through VMware Tools, so the operating system shuts down cleanly. A wrongly judged, healthy guest reboots cleanly instead of losing what was in memory. When Tools is dead, the step says "not possible" and goes to the approval.
- **A hard reset only after a person approves it.** The approval node carries which VMs, how long each has been dark, and the diagnosis. A fully automatic reset would be a separate, opt-in mode for labs and stateless desktop pools.
- **Every action written down.** It goes in the VM's Notes in vCenter (the existing notes job: date, job, why) and in the incident's work notes.
- **Never a host.** No host reboot, agent restart or evacuation: those stay manual.

Event-driven, later

When an Aria Operations alert or an SNMP / mail receiver is available, an Event-Driven Ansible rulebook can start the same workflow from the vCenter alarm. The watch job would still be the workflow's first step, so the response always works from a fresh look, never only from the event. Nothing in the jobs would change.

Troubleshooting

You see	What it means
Every suspect "could not be probed (unavailable)"	no `ping` in the execution environment, or ICMP not allowed: set `vm_watch_probe_port`
"could not be probed (no address)"	VMware Tools reported no IP, and neither the guest host name nor the VM name is in DNS
A VM that answers is reported hung	the firewall between the AAP node and the VM drops the ping and the TCP port, and vCenter's statistics show no packets sent (the line says *vCenter saw no network packets sent*). Before 0.45.3: ping only, no traffic signal - update. Still: set `vm_watch_probe_port` to a port the firewall allows
it still sends network traffic (vCenter's real-time statistics ...)	no heartbeat, no answer to the probe, but the VM sends packets: alive. VMware Tools stopped (on container hosts open-vm-tools can stall on many container network interfaces - check `vmtoolsd`), and the probe is blocked
vCenter's statistics not read (...)	the VM is hung on the first two signals; the third could not be read (the reason is given). It is still called hung
The same one-signal warning every run	VMware Tools is stopped in that guest: restart or update Tools, or add the VM to `vm_watch_skip_vms`
An all-paths-down condition stays after the storage came back	the clear event names another device, or came after the window: it ages out after `vm_watch_window_minutes`
"does not say which VM is the AAP server"	run the template with the inventory that has the `aap` group, or list the AAP VM in `vmware_protected_vms`

21. VM - ask a question: vCenter in plain words, read-only

Type a question about vCenter in plain words and get the answer as a report:

- *give me all VMs with dbv in the name*
- *all VMs in the acas folder in all vCenters*
- *VMs on datastores with less than 10% free*
- *hosts in maintenance mode, and how many VMs each has*
- *the 10 biggest snapshots older than a week*
- *powered-off Windows VMs in cluster PROD-CL01*
- *how many VMs per cluster*
- *VMs and their hardware versions, and how many of each*
- *VMs not restarted in 90 days*, *VMs powered off for more than 2 weeks*
- *which VMs were vMotioned today, and from which host*
- *drives under 10% free on the SQL servers*, *the biggest virtual disks on DS-PROD-01*

As a web page, for people without AAP - at STIG Manager's /ask/, with the card, the answer in seconds: VMWARE_ASK.md.

The job reads every vCenter it is given and answers. It shows how it read the question, so a wrong reading is plain to see. The answer is printed in the job's output, and can be emailed with a workbook of every row and published on the report website.

Job template	Playbook	Credentials
VM - ask a question	`playbooks/vm_ask.yml`	VMware vCenter (read-only is enough), ACT model key; no Limit

It only reads

The job can only look. It cannot restart, shut down, delete, move, snapshot or change anything, and it never puts a host in or out of maintenance mode. Four things make sure of that:

1. **A guard before GenAI.** A question that asks for a change is refused before GenAI sees it. This covers *reboot dbv01*, *find the dbv VMs and shut them down*, *put esx02 in maintenance mode* and *delete the old snapshots*. The job fails with `Refused: this job only reads vCenter ...` and names the template made for that change, such as **VM - restart**, which has its own checks and protections. A question that only asks to *see* such things still works: *hosts in maintenance mode*, *VMs that were restarted*.
2. **GenAI writes no code and no command.** It only turns the question into a query in the job's own form, described in The query below. It is told to refuse a change too. The query has no place for an action.
3. **A whitelist.** Before anything is read, the query is checked against eight objects, their fields and a few operators. Anything else stops the job with the reason: an unknown field, an unknown key such as `action`, or a malformed pattern.
4. **The job has only readers.** The job runs the read-only modules that the VMware reports already use, and only the ones the question needs:

- `site_vmware_vms`
- `site_vmware_health`
- `site_vmware_datastores`
- `site_vmware_snapshots`
- `site_vmware_alarms`

`tests/test_vm_ask.py` fails if the job's tasks ever use any other module.

What GenAI gets. It gets the question and the list of fields, and nothing from vCenter: no VM names, hosts or addresses. The answer is worked out in the job, on the AAP side.

Set it up in AAP

1. **The credentials.** The job uses two credentials you probably already have:
   - **VMware vCenter**, a read-only account: VMWARE.md.
   - **ACT model key**, the GenAI API key: ADDING_ACT.md.
2. **The template.** *Templates* > *Add* > *Job template*:
   - **Name:** `VM - ask a question`
   - **Inventory:** any. The job runs on the AAP side and needs no hosts.
   - **Project:** this repository.
   - **Playbook:** `playbooks/vm_ask.yml`
   - **Execution environment:** the one your VMware reports use. It needs pyVmomi.
   - **Credentials:** VMware vCenter, and ACT model key.
   - **Variables:** copy `aap/extra_vars/vm_ask.yml` and switch on only what you change.
3. **The survey.** *The template* > *Survey* > *Add*, then turn the survey on:
   - **Question:** `What do you want to know?`
   - **Description:** `e.g. all VMs with dbv in the name; hosts in maintenance mode; snapshots older than 7 days`
   - **Answer variable name:** `vm_ask_question`
   - **Answer type:** Textarea
   - **Required:** yes
4. **Emailing the answer.** To be asked who to email at each launch, run the template **AAP - report email question** once: EMAIL_REPORTS.md. To always email the same people, set `report_email_to` in the template's Variables.
5. **Several vCenters.** Set `vmware_vcenters` (in `all.yml`) as for the other VMware reports: VMWARE.md. Every vCenter is read for every question. *in all vCenters* needs nothing extra, and *in vCenter vc02* is a condition on the vCenter field.

Test it. Launch it with *all VMs with dbv in the name*, or with any part of a name you know. The job's output shows these lines, then the rows:

```
Asked: all VMs with dbv in the name
Read as: VMs whose name contains 'dbv'; templates left out; in every vCenter read
Read by: GenAI (genai, ...)
Found: 12 VMs
```

What you can ask about

Eight objects. A question asks for one of them; its fields can be conditions, columns, the sort or a count.

Object	Fields
VMs	name, vCenter, datacenter, folder (`DC1 / ACAS / Scanners`: a folder's subfolders count), cluster, ESXi host, power (on, off, suspended), template, guest host name, IP address (and every IP), guest OS, VMware Tools, heartbeat (green, yellow, red, gray), hardware version (`21` for vmx-21; *older than vmx-19* works), VMware Tools version (`12.3.0`, or *guest managed* for open-vm-tools), firmware (bios, efi), vCPUs, memory (GB), days up, when powered on; **restarts**: last restart, by what (power on, guest restart, reset, HA restart), days since, last powered off, days since; **vMotion**: last vMotion, its kind (vMotion, DRS vMotion, relocate), from which host, by whom, days since; **disks**: size of all its virtual disks, how many, datastore space used, its guest drives' size and free space, the free % of its fullest drive
ESXi hosts	name, vCenter, datacenter, cluster, connection, power, maintenance mode, status, HA state, CPU and memory used %, CPU (GHz), memory (GB), days up, reboot required, ESXi version and build, vendor, model, configuration issues
Clusters	name, vCenter, datacenter, status, HA, DRS (and its automation), EVC mode, hosts, hosts working, CPU and memory used % (of its hosts), configuration issues
Datastores	name, vCenter, datacenter, datastore cluster, type, capacity, free (GB and %), used %, provisioned %, accessible, maintenance, hosts, VMs
Snapshots	name, VM, vCenter, datacenter, folder, cluster, description, when taken, age (days), size (GB), with memory, quiesced, taken by
Alarms (triggered now)	alarm, the object it is on and its type, severity (critical, warning), vCenter, datacenter, cluster, since, age (hours), acknowledged, by whom
Virtual disks (each VM's vmdk)	VM, label (Hard disk 1), size (GB), datastore, file, thin, and the VM's vCenter, datacenter, folder, cluster, host, power
Guest drives (inside the guest, from VMware Tools)	VM, drive or mount point (`C:\`, `/var`), size, free (GB and %), used, and the VM's vCenter, datacenter, folder, cluster, host, guest OS

Templates are left out of VM answers unless the question asks about templates. The report says how many were left out.

Restarts and vMotion. A VM's *last restart* is the latest of its power on (vCenter knows it for every VM that is on) and a restart inside the guest, a reset or an HA restart found in vCenter's events. *Last powered off* and *last vMotion* come from the events only. The events read are those of the last `vm_ask_event_days` (30), in one query, and only when the question asks about these. vCenter keeps events for a limited time, often 30 days, so an empty *last vMotion* means none in that time, not never. Ask *VMs not vMotioned in the last 30 days*

rather than *in a year*.

Disks and free space. A VM's virtual disks, and its datastore space, are always known. Its guest drives come from VMware Tools, so a VM that is off, or has no Tools running, has none: its drive fields are empty, not 0. A template's disks are left out. The disks are read only when the question asks about them.

Taken by is read from vCenter's events, one query per VM with snapshots, so it is read only when the question asks for it. It is empty once vCenter has dropped the event, which is often after 30 days.

Questions across objects (joins)

A question may combine objects. The answer lists the first object, and shows only the related ones that match.

From	Related
a VM	its ESXi host, cluster, datastores, snapshots, alarms
an ESXi host	its VMs, cluster, datastores (mounted), the snapshots of its VMs, its alarms
a cluster	its VMs, hosts, datastores (those its hosts mount), snapshots, alarms (on it or on anything in it)
a datastore	its VMs, hosts, clusters (of its hosts), snapshots (of its VMs), alarms
a snapshot	its VM, that VM's host and datastores, its cluster, the VM's alarms
an alarm	the VM, host, cluster or datastore it is on, the VM's snapshots
a virtual disk or guest drive	its VM, and through it that VM's host, cluster, datastores, snapshots and alarms (a virtual disk: its own datastore)
anything	its virtual disks and guest drives: those of its VMs

Examples:

- *VMs on datastores under 10% free* lists each VM with the full datastore and its free %.
- *VMs with no snapshots*
- *hosts with their VM count* gives a count column.
- *clusters with a critical alarm*
- *snapshots on hosts in maintenance mode*
- *VMs with a drive under 1 GB free*, *clusters with the most full guest drives*
- *datastores with the number of virtual disks on each*

The settings

In the template's Variables (`aap/extra_vars/vm_ask.yml`):

Setting	Default	What it does
`vm_ask_question`	`""`	The question. The survey sets it.
`vm_ask_query`	`{}`	A query in the job's own form instead, as JSON or YAML (The query). GenAI is not asked.

Setting	Default	What it does
`vm_ask_genai`	`true`	`false` = GenAI is never asked; only the job's own reader runs (simple questions only).
`vm_ask_local_fallback`	`true`	When GenAI did not run (no key, not reachable), or its answer held no query, the job's own reader tries the question, and the report says so.
`vm_ask_genai_retry`	`true`	When GenAI's answer holds no query (a plan or a step of its own instead, or prose), it is asked once more and told what it answered. `false` = asked once.
`vm_ask_extra_instructions`	`""`	More words for GenAI, such as your naming: *"A name with DBV is a database server; ACAS is the scanner team's folder."* Text, not true/false.
`vm_ask_model_timeout`	`120`	Seconds GenAI may take.
`vm_ask_event_days`	`30`	The days of vCenter's events read for the last restart, power off and vMotion.
`vm_ask_max_events`	`50000`	Events read per vCenter at most (the newest).
`vm_ask_max_rows`	`500`	Rows in the email and on the page at most. The workbook has every row.
`vm_ask_print_rows`	`50`	Rows printed in the job's output.
`vm_ask_artifact_rows`	`200`	Rows in the job artifact `vm_ask`, for a workflow's next step.
`vm_ask_xlsx`	`true`	Attach every row as an Excel workbook to the email.

These shared settings apply as for every VMware report:

- `vmware_vcenters`
- `vmware_datacenter`
- `vmware_validate_certs`
- `report_email_to` (and the rest of the email settings)
- `report_web_dest`
- `site_act_provider`, `site_act_model` and `site_act_env` for GenAI (ADDING_ACT.md)

Without GenAI. The job's own reader handles only simple questions:

- *VMs with X in the name*, or *named X* (`web*` works)
- *in the X folder*
- *in cluster X*
- *on host X*
- *in vCenter X*
- *powered on* or *powered off*

- *in maintenance mode*
- *older than N days*
- *under N% free*

Anything more, such as a join, a count or a sort, needs GenAI. The reader answers only when it understood every word of the question (besides words like *all*, *show me*, *the*). When it cannot take a question, the job fails and says so. It never answers part of a question: *all VMs vMotioned this week* is not read as *all VMs*.

The query

What GenAI writes, and what `vm_ask_query` takes:

```
{"object": "vm",
 "where": [{"field": "folder", "op": "contains", "value": "acas"},
           {"any": [{"field": "power", "op": "eq", "value": "off"}, {"field": "cpus", "op": "gte",
             "value": 8}]}],
 "join": [{"object": "datastore", "has": true, "where": [{"field": "free_pct", "op": "lt",
   "value": 10}]},
          {"object": "snapshot", "has": false}],
 "columns": ["name", "cluster", "datastore.name", "datastore.free_pct"],
 "sort": [{"field": "memory_gb", "desc": true}], "limit": 20, "count_by": "cluster"}
```

Key	What it is
`object`	`vm`, `host`, `cluster`, `datastore`, `snapshot`, `alarm`, `disk` (virtual disk) or `drive` (guest drive): the rows of the answer.
`where`	Conditions that must all hold. `{"any": [...]}` = one of them is enough. `"not": true` turns one round.
`join`	Conditions on related objects. `has: true` keeps rows with a related one that matches; `has: false` keeps rows with none.
`columns`	Fields of the object, and `object.field` or `object.count` of related ones. Left out = the usual columns.
`sort`	`[{"field": ..., "desc": true}]`, or `"-memory_gb"` for descending.
`limit`	Only the first N rows.
`count_by`	A field: a table of how many per value.

Operators:

- On text, any case: `eq`, `ne`, `contains`, `not_contains`, `starts`, `ends`, `matches` (`*` and `?`), `regex`, `in`, `not_in`, `empty`, `not_empty`.
- On numbers: `eq`, `ne`, `gt`, `gte`, `lt`, `lte`, `in`, `not_in`.
- On true/false fields: `eq`.
- On a list field, such as IP addresses or configuration issues, a text operator matches when any item matches.

The field names are listed in the prompt GenAI gets: `vm_ask_task` in `plugins/filter/vmware_ask_filters.py`.

What you get

- **The job's output:** the question, how it was read, by whom (GenAI, the job's own reader, or `vm_ask_query`), the count, and the first rows.
- **The report**, when emailed or on the report website:
- "The question, as the job read it"
- the count table, when the question asks for one
- the answer
- the vCenters not read, in red on top
- **The workbook:** every row on one sheet, and the counts on another.
- **The job artifact** `vm_ask`**:** the question, the query, the count and the first rows, for a workflow's next step.

The job is green whenever it answers, even with no rows. It fails when it refuses the question, cannot read it, or the query is not one it runs. With `vmware_vcenter_fail_unread: true`, it also fails when a vCenter could not be read.

When something goes wrong

The job says	Why	Do this
`Refused: this job only reads vCenter ...`	The question asks for a change.	Ask what you want to see, or use the template it names.
`Refused by GenAI: the question asks to change something`	GenAI read a change into it.	Ask it as a question: *which VMs are ...*
`... has no field 'owner'`	vCenter has no such thing, as far as the job reads it.	See What you can ask about. Ask it in other words.
`Not answered: the question asks for VM tags, and this job does not read that`	Nothing the job reads holds it. GenAI says so instead of answering the rest of the question, which would look like an answer and be a different one (before 0.45.2: every VM, listed).	See What you can ask about; ask without it, or ask for the field to be added.
`GenAI's answer has no query in it`	GenAI answered in prose, twice.	Ask again, more plainly. The job's output shows what GenAI answered.
`GenAI answered with a step of its own (action 'plan' ...) ... (asked twice)`	The model replied as if it would take several steps (a plan, then the query). Here it gets one call, so the plan is all it said; it was asked once more and did it again.	Since 0.44.5 ACT no longer offers the model its own steps here (docs/ADDING_ACT.md, "A plain answer"), which is what made it answer with one: update first. Still there: launch it again; if it keeps happening with one model, set `site_act_model` to another one in the template's Variables.
`GenAI did not run: This job has no API key ...`	No ACT model key credential on the template.	Attach it. Simple questions still work without it.
`This AAP node cannot reach the model ...`	Firewall or proxy.	VMWARE.md: the firewall rule or the proxy setting.
`Read as:` is not what you asked	GenAI read it differently.	Ask it in other words, or set `vm_ask_extra_instructions` with your naming.

22. VMware ask: the web page at STIG Manager's /ask/, the card's certificate, read-only

VM - ask a question (VM_ASK.md) as a web page. People open it with their card (CAC), type a question about vCenter in plain words and get the answer on the page in seconds, with no AAP job to launch:

- *all VMs with dbv in the name*
- *VMs on datastores with less than 10% free*
- *hosts in maintenance mode, and how many VMs each has*
- *the 10 biggest snapshots older than a week*
- *VMs not restarted in 90 days*

It is the job's engine: the same guard, the same GenAI prompt, the same whitelist and the same readers. A question reads exactly as it does in the job, and everything VM_ASK.md says about what you can ask applies here too. Each answer shows how the question was read and when vCenter was read, the rows (a CSV of every row to download), and *Edit and ask again*.

It lives **behind the reverse proxy you have** - STIG Manager's nginx - at `/ask/`: `https://stigman.yoursite.mil/ask/`. That nginx already does TLS and checks the card's certificate (mTLS); the page needs no Keycloak, no certificate of its own and no port of its own.

Job template	Playbook	Credentials
VMware ask - deploy	`playbooks/vmware_ask_deploy.yml`	Machine, VMware vCenter (read-only is enough), ACT model key (Container registry login (hosts): optional)

It only reads

The page can only look. It cannot restart, shut down, delete, move, snapshot or change anything:

1. **A read-only vCenter account.** Give the account of its *VMware vCenter* credential the built-in **Read-only** role at the top of each vCenter, propagated (VMWARE.md). Even a bug could then change nothing.
2. **The job's four locks.** A question that asks for a change is refused before GenAI sees it; GenAI only turns the question into a query, never code or a command; the query is held to the whitelist; only the read-only readers run (VM_ASK.md).
3. **No code that writes.** The service has no call that changes vCenter. Its vCenter reads are `roles/vmware_ask_stack/files/refresh.yml`: the job's five readers and nothing else, and `tests/test_vmware_ask.py` fails if anything else is added.

What GenAI gets. The question and the list of fields, as with the job. No VM names, hosts, addresses or anything else read from vCenter, not who asked, and not the vCenter account: the service starts ACT without it.

How it works

```
browser --TLS + the card--> STIG Manager's nginx --/--> STIG Manager (as before)
                                  |
                                  +--/ask/--> the service --read-only--> vCenter(s)
                                              (podman)    |
                                                          +--the question only--> GenAI
                                                          +--who asked what--> SQLite
```

- **One container**, `vmware-ask-app`, on podman, run by systemd (Quadlet). It joins the **podman network of STIG Manager's nginx container** (`vmware_ask_network`) and publishes **no port**: only the containers on that network reach it - STIG Manager's nginx (by its name), and STIG Manager's own other containers (its API, its database). Who asks rests on that: anything on that network could send the two headers below, so keep only STIG Manager's containers on it.
- **Who asks** is the card's certificate that nginx verified. nginx hands the service two headers on every request - `X-SSL-Client-Verify` (`SUCCESS`) and `X-SSL-Client-S-DN` (the certificate's subject) - set by nginx over anything the browser sent. The person is the subject's name (CN): `DOE.JANE.Q.1234567890`. **Anyone whose certificate your nginx accepts may ask** (with DoD CAs: every card holder): it only reads, and every question is kept with who asked. No certificate, or one nginx did not accept: the page says so and answers nothing.
- **What the job does on the server** - and only this: the folder `/etc/vmware-ask`, the container `vmware-ask-app` with its unit file (`/etc/containers/systemd/vmware-ask-app.container`, and `vmware-ask-data.volume`), its volume `vmware-ask-data`, the podman secrets `vmware-ask-vcenter` and `vmware-ask-genai`. Then `systemctl daemon-reload`, so systemd reads the new unit file: that reads every unit file again - STIG Manager's too - but starts, stops or restarts nothing but `vmware-ask-app`. With the *Container registry login (hosts)* credential, it also logs root's podman in to that registry (`podman login`), which replaces a login saved for that same registry. **It never changes STIG Manager**: not its nginx, its files, its network, its containers or their units. It only reads the network's DNS address. The lines nginx needs are written to `/etc/vmware-ask/nginx-ask.conf`, and **you** add them (step 4), once.
- **STIG Manager does not need the service.** nginx looks the service up when a request for `/ask/` comes, not when it starts: if the service is stopped, or the server restarts before it, nginx starts and STIG Manager works as always; only `/ask/` answers *502* until the service is back.
- **The service runs in your execution environment image** (the all-in-one EE: EXECUTION_ENVIRONMENT.md). Python, ansible-core and pyVmomi are in it already, so nothing is installed on the server and nothing is downloaded when it starts.
- **vCenter is read every 10 minutes** (`vmware_ask_refresh_minutes`), with everything a question may need: VMs with their disks and events, hosts, clusters, datastores, snapshots (and who took them), triggered alarms. Each answer is from the last read, and says when that was. The page's header says it too, with any vCenter that could not be read. A read that fails keeps the last good one, and says so.
- **Several vCenters**: the credential's, and `vmware_vcenters` (`vmware_ask_vcenters`), with the same account, as for the VMware reports.
- **No key, or GenAI not reachable**: the job's own reader answers the simplest questions (*VMs with dbv in the name*, *hosts in maintenance mode*), and says so on the answer.

Set it up

Five steps. Steps 1 and 2 only look; step 3 is the job; step 4 is the one change to STIG Manager's nginx, by hand.

1. Look at STIG Manager's nginx

On the STIG Manager server (`sudo` throughout: STIG Manager's containers are root's):

```shell
sudo podman ps --format "{{.Names}}  {{.Networks}}  {{.Ports}}"
```

Note the **nginx container's name** (the one with `443` in its ports) and its **network**. Then check the network has DNS - its containers find each other by name:

```shell
sudo podman network inspect <the network> --format "{{.DNSEnabled}}"      # must say: true
```

`true`: good. `false`, or the network is `podman` (podman's default, without DNS) or `host`: stop here - the page needs a network with DNS; ask before changing STIG Manager's.

Find the nginx config file on the server, the one with STIG Manager's `server { ... }` block:

```shell
sudo podman inspect <nginx> --format '{{range .Mounts}}{{.Source}} ->
  {{.Destination}}{{println}}{{end}}'
```

The line ending in `/etc/nginx/conf.d/default.conf` (or another `.conf`) is it - the left side is the file on the server. Open it, read only, and check its `server` block has:

- `ssl_client_certificate` (your CA bundle: the DoD CAs) and `ssl_verify_client on` or `optional` - the mTLS. Without them nginx checks no card, and the page refuses everyone (*No client certificate was accepted (NONE)*).
- a `location / { ... }` - STIG Manager. The page's lines go just above it.

2. The server, in the inventory

It is the STIG Manager server: it can already reach your automation hub, and needs to reach

- vCenter on 443 (each of them),
- the GenAI API (`https://api.genai.mil` - or through your proxy: `site_act_env: {HTTPS_PROXY: http://proxy.yoursite.mil:8080}`).

Put it in your inventory in the group `vmware_ask` (or give the job `target: <its name>`). Its podman must be 4.4 or later (RHEL 9.2+ / 8.8+): it is already, if STIG Manager runs with Quadlet.

3. The job template

Templates > *Add* > *Job template*:

- **Name:** `VMware ask - deploy`
- **Inventory:** the one with the server. **Limit:** the server.
- **Playbook:** `playbooks/vmware_ask_deploy.yml`
- **Credentials:** Machine (ssh and sudo on the server), VMware vCenter (the read-only account), ACT model key; Container registry login (hosts) when the image needs a login to pull.
- **Variables:** copy `aap/extra_vars/vmware_ask_deploy.yml` and set at least:

```yaml
vmware_ask_network: stigman              # step 1: the network of STIG Manager's nginx container
vmware_ask_image: hub.yoursite.mil/site-ee-all:1
vmware_ask_public_url: https://stigman.yoursite.mil/ask/
```

GenAI's settings are ACT's, as for every job: `site_act_provider`, `site_act_models`, `site_act_urls` (roles/site_act/defaults/main.yml). `vm_ask_extra_instructions` (your naming) applies here too.

Launch it with Job type **Check** first: it lists what it would write - only `/etc/vmware-ask`, the `vmware-ask-*` unit files and secrets - and writes, starts and makes nothing (tested on a server with nothing of it yet). Then **Run**. It starts the service, checks it answers, and its last task shows **the lines to add to nginx** (also in `/etc/vmware-ask/nginx-ask.conf` on the server).

After an update of this repository, run the template again: it copies the service and the job's engine, and restarts the service if they changed. A second run with nothing changed changes nothing. nginx's lines stay as they are (they change only if you change `vmware_ask_path` or STIG Manager's network: the job then says so).

4. Add /ask/ to your nginx

Once, by hand, on the STIG Manager server, with the file and the container name from step 1:

1. **Keep a copy:** `sudo cp <the file> <the file>.before-ask`
2. **Paste** the lines of `/etc/vmware-ask/nginx-ask.conf` (`sudo cat /etc/vmware-ask/nginx-ask.conf`) **inside** STIG Manager's `server { ... }` block, just **above** its `location / {`. Edit the file **in place** - `sudo nano` does; in vim first `:set backupcopy=yes` - because the container sees that one file: an editor that saves a new file in its place leaves nginx reading the old one. They are two `location` blocks:

```
location = /ask {
    absolute_redirect off;
    return 301 /ask/;
}
location /ask/ {
    resolver 192.0.2.1 valid=30s ipv6=off;   # the podman network stigman's DNS
    set $vmware_ask_app http://vmware-ask-app:8080;
    rewrite ^/ask/(.*)$ /$1 break;
    proxy_pass $vmware_ask_app;
    proxy_http_version 1.1;
    proxy_set_header Host               $host;
    proxy_set_header X-Real-IP          $remote_addr;
    proxy_set_header X-Forwarded-Proto  https;
    proxy_set_header X-SSL-Client-Verify $ssl_client_verify;
    proxy_set_header X-SSL-Client-S-DN  $ssl_client_s_dn;
    proxy_read_timeout 60s;
    client_max_body_size 64k;
}
```

(Use the file's lines, not these: its `resolver` is your network's address.)

Check the container sees them - this must print `1`, with the path from step 1's `->`: `sudo podman exec <nginx> grep -c 'location /ask/' /etc/nginx/conf.d/default.conf`. A `0`: the editor saved a new file - put the copy back, edit again in place.

3. **Test it:** `sudo podman exec <nginx> nginx -t` - it must say *syntax is ok* and *test is successful*. Anything else: put the copy back (`sudo cp <the file>.before-ask <the file>`), and nothing has changed.

4. **Load it:** `sudo podman exec <nginx> nginx -s reload`. nginx reloads without dropping anyone: STIG Manager keeps working, and its sessions too.

To take it out again: put the copy back, `nginx -t`, `nginx -s reload`; then, if you like, `sudo systemctl stop vmware-ask-app` (and remove `/etc/containers/systemd/vmware-ask-*` and `/etc/vmware-ask`).

If STIG Manager's nginx file is written by a job - this repository's *STIG Manager - deploy* writes it on each run (*Managed by Ansible*) - that run takes the lines out again: paste them again after it (steps 1-4), or ask for them to be added to that job.

5. Try it

Open `https://stigman.yoursite.mil/ask/` with your card, and ask *all VMs with dbv in the name* (or a part of a name you know). The header shows your name from the card. The answer says *Read by: GenAI (genai, ...)*. If it says *the job's own reader*, its note says why GenAI was not used. STIG Manager, at `/`, is as it was.

Browsers and a web proxy. The page is a path on STIG Manager's own name, so it goes wherever STIG Manager goes: if your browsers reach STIG Manager without the web proxy (its name on the proxy bypass list), the page does too.

Who asked what

Every question is kept with who asked it (the name on the card), from which address, when, how it was read and what came of it:

- **in the journal**, one JSON line each: `journalctl -u vmware-ask-app` (or `podman logs vmware-ask-app`). Requests refused for want of a certificate are there too (*refused*, with the reason). Forward it to your SIEM with the rest of the server's journal.
- **in a database** on the server, `ask.db` in the volume `vmware-ask-data`, for `vmware_ask_keep_days` (365):

```shell
sudo sqlite3 "$(sudo podman volume inspect vmware-ask-data --format '{{.Mountpoint}}')/ask.db" \
  "select at, user, question, status, total from asks order by at desc limit 20"
```

Settings

Every setting, with its default: `aap/extra_vars/vmware_ask_deploy.yml` and VARIABLES_REFERENCE.md. The ones you are likely to change:

Setting	Default	What it does
`vmware_ask_network`		the podman network of STIG Manager's nginx container (required; it must exist, with DNS)
`vmware_ask_image`		your execution environment image (the all-in-one EE)
`vmware_ask_path`	`/ask/`	the page's path on nginx (the lines' `location`)
`vmware_ask_public_url`	`https://<the server>/ask/`	the page's address, as people open it (said at the end, logged)
`vmware_ask_classification`	`U`	the banner: U, CUI, C, S, TS, SCI, NONE

Setting	Default	What it does
`vmware_ask_refresh_minutes`	10	how often vCenter is read
`vmware_ask_genai`	true	false = only the job's own reader (simple questions)
`vmware_ask_max_rows`	500	rows shown on the page (the CSV has every row)
`vmware_ask_keep_days`	365	how long who asked what is kept (0 = for ever)
`vmware_ask_per_user`	2	questions one person may have running at once
`vmware_ask_trust_host_cas`	true	the service trusts the CAs the server trusts (`/etc/pki/ca-trust`): for vCenter and GenAI

When something is wrong

What you see	What to do
The job stops: *Set vmware_ask_network to the podman network ...*, or *... does not exist*, or *... has no DNS*	step 1: the network of STIG Manager's nginx container, as `podman ps` names it
`nginx -t` fails	put the copy back (step 4). *unknown directive* or *"location" directive is not allowed here*: the lines went outside the `server { }` block, or inside another `location`
`/ask/` says *502 Bad Gateway*	the service is not running: `sudo systemctl status vmware-ask-app`, `journalctl -u vmware-ask-app`. Or it is on another network than nginx: run the job again with the network nginx is on
404 Not Found for `/ask/`	the lines are not loaded: in the right file? `nginx -s reload` done? Does the container see them (step 4's `grep -c`)? A `0`: the editor saved a new file - edit it in place and reload
No client certificate was accepted (NONE)	nginx asked for no certificate: its `server` block needs `ssl_verify_client on` (or `optional`) and `ssl_client_certificate`. Or the browser sent none: card in the reader, pick its authentication certificate (not the e-mail one); close the browser and try again
No client certificate was accepted (FAILED: ...)	nginx did not accept the certificate: expired, revoked, or of a CA not in `ssl_client_certificate`
vCenter has not been read yet, or the header says the last read failed	`journalctl -u vmware-ask-app`: the `vcenter_read` line says why. A wrong password: update the credential and run the template again. A certificate not trusted: put its CA in the server's trust (`update-ca-trust`) and run the template again.
Not in this answer - not read: vc02 ...	that vCenter could not be read at the last read; the others were
GenAI did not run: ... on an answer	the note says why: no key (attach the ACT model key credential and run the template again), the URL not reachable from the server (firewall, proxy: `site_act_env`), a certificate
Refused: this job only reads vCenter	the question asks for a change; ask what you want to see

Not yet

- **Tried on a real vCenter, STIG Manager and GenAI.MIL?** Not yet: it was tested end to end on podman with vcsim (the vCenter simulator), an nginx with client certificates standing in for STIG Manager's (the lines of step 4 in its `server` block), the real ACT with a stand-in GenAI API, and an execution environment built from `ee/all-in-one` - as a user (rootless podman, `vmware_ask_scope: user`), not yet as root, as on your server (`vmware_ask_scope: system`, the default: the same tasks with `/etc/containers/systemd` and `systemctl`). Try it on a test server first, or run step 3 as Check and read what it would do.
- **Follow-up questions.** Each question stands alone: *now only the powered-off ones* does not know the question before. Use *Edit and ask again*.

- **Answers are as of the last read** - up to `vmware_ask_refresh_minutes` old. For an answer read live, run the job *VM - ask a question*.

23. Log analysis: the patterns in a group of servers' logs, explained by ACT

Two jobs read logs and have ACT (GenAI) explain what they show. Both are read-only.

Job template	Playbook	What it reads
Log analysis	`playbooks/log_analysis.yml`	the hosts of the job's target or Limit: Linux (the journal, units, podman containers, text logs), Windows over WinRM (event logs, providers, event IDs, text logs), a vCenter appliance over SSH
VM - vCenter log analysis	`playbooks/vm_log_analysis.yml`	vCenter's own log (vpxd) and each ESXi host's (hostd, vmkernel, vpxa), through vCenter's API: no SSH, nothing to switch on at the hosts

What it does

1. **Read.** Each host's **warning, error and critical** lines of the window: the last `log_analysis_hours` (24), or a fixed window such as the outage, `log_analysis_since` .. `log_analysis_until`. The journal and the event logs say how bad a line is; a text log's line is read when it matches `log_analysis_match` (error, fail, fatal, denied, refused, timeout ...). At most `log_analysis_max_lines` (500) lines per log, the newest.
2. **Group, on the AAP side.** Each line becomes a pattern: the line with its numbers, times, IP addresses, IDs and quoted values taken out. The same pattern on five hosts is **one** row, "on 5 hosts, 212 lines, first 07:02, last 07:58". Patterns are ranked: critical, then error, then warning; within a level, the most hosts and then the most lines first.
3. **Explain.** ACT gets the top `log_analysis_max_items` (30) patterns, with up to three example lines each, and answers for each: the **likely cause**, the **evidence**, the **fix**, and a **confidence** from 0 to 100. It is told to say when a pattern is harmless noise and to name the patterns that share a cause. ACT runs in **evidence mode**: on the AAP side, reading what the job collected, running **no command** on any host. Before anything leaves, ACT replaces the host names (and `log_analysis_names_extra`) with placeholders.
4. **Report.** One report, every run, in the same look as the other reports: printed in the job output, kept as the job artifact `log_analysis` (every pattern, ACT's answer merged in), **emailed** (`report_email_to`, and the "Also email the report to" box: EMAIL_REPORTS.md) and **published** on the report website (`report_web_dest`: WEB_REPORTS.md). It has:
   - the hosts **not read**, in red, with why (unreachable, login refused, a log it may not read);
   - your question, if you asked one, and ACT's "What to do first";
   - **Likely causes and fixes**: one row per pattern ACT analyzed, with the confidence coloured (green 80+, amber 50-79, red under 50);
   - **Patterns**, always - also without ACT: level, hosts, log, lines, first and last seen, an example;
   - the hosts read, with the logs each one gave;
   - **What was read**: the window, the profiles per host, how many lines the ignore list left out.

A run that finds nothing is not emailed unless `log_analysis_email_if_clean: true` (the website gets every run). The job is **green** when it reports; **red** when ACT was wanted and could not run (no key, no network: the report still lists the patterns and says why), when no host at all could be read, and - with `log_analysis_fail: true`, for a workflow - when a critical or error pattern was found. A host that cannot be reached is listed, and does not fail the job.

What it reads, per kind of host

`log_analysis_source` says what a host is: `auto` (Windows when its connection is WinRM or PSRP, else Linux), `linux`, `windows` or `vcsa`. Set it per group in the inventory.

Kind	Read	How
Linux	the journal at `log_analysis_priority` (`err`) or worse; the units in `log_analysis_units` and the syslog identifiers in `log_analysis_identifiers` at `log_analysis_units_priority` (`warning`); the containers in `log_analysis_containers` (`podman logs --since`); the text logs in `log_analysis_files` (+ `_extra`, + the profiles') that changed in the window	journalctl, podman, find and grep, as root (`log_analysis_become`) - read-only. A journal line two reads return is counted once
Windows	the event logs in `log_analysis_win_logs` (+ `_extra`): critical, error and (`log_analysis_win_level: 3`) warning events; the providers in `log_analysis_win_providers` at every level up to information; the event IDs in `log_analysis_win_event_ids` whatever their level; the text logs in `log_analysis_win_files` (+ `_extra`)	`files/log_collect.ps1` over WinRM - no collection needed. PowerShell 5.1 and 7, also in Constrained Language Mode
vCenter appliance (`vcsa`)	as Linux, plus the `vcsa` profile: vpxd, vpxd-svcs, vmon, SSO (STS), envoy, rhttpproxy, vsphere-ui, applmgmt, vpostgres, vmdird, certificate management, EAM, content library	over SSH as root. **The appliance's login shell must be bash** for Ansible: on the appliance, `chsh -s /bin/bash root`. Its Machine credential: root, or an account that may sudo
vCenter and ESXi through the API	vCenter's `log_analysis_vcenter_logs` (`vpxd`); each host's `log_analysis_esxi_logs` (`hostd`, `vmkernel`, `vpxa`; also e.g. `fdm`, `vobd`) - the last `log_analysis_read_lines` (20000) lines of each, then the window; a line ESXi or vCenter marks warning, error or critical, or one that matches `log_analysis_match`	`playbooks/vm_log_analysis.yml`, vCenter's DiagnosticManager (what the vSphere Client's "Export System Logs" reads). The **VMware vCenter** credential's account needs **Global > Diagnostics** besides read-only. A host not connected to vCenter is listed as not read

The settings

Every setting can be set for all hosts (`all.yml`), per group or host in the inventory, on the job template, or as a **survey** answer. A list may be typed as `a, b` or one per line.

Setting	Default	What
log_analysis_hours	24	the window: the last this-many hours
log_analysis_since, log_analysis_until	empty	a fixed window, UTC, e.g. 2026-10-23 08:00 and 2026-10-23 10:30 ("what happened during the outage"). Since alone = until now
log_analysis_question	empty	what you want to know, in your words: ACT answers it first ("users report slow logins since 09:00"). A good survey box
log_analysis_profiles	[]	one word switches on a product's logs (below)
log_analysis_profiles_extra	{}	your own profiles, or a shipped one changed: {stigman: {files: [/opt/stigman/logs/*.log], units: [stigman-api]}}
log_analysis_source	auto	auto, linux, windows, vcsa
log_analysis_priority	err	the journal's lines this bad or worse (crit, err, warning ...)
log_analysis_journal	true	false = no general journal read (units, containers and text logs only)
log_analysis_units, log_analysis_identifiers	[]	units (sssd, dirsrv@*) and syslog identifiers (sudo) read at log_analysis_units_priority (warning) - lower than the rest
log_analysis_containers	[]	podman containers: name for root's, user/name for a user's (rootless)
log_analysis_files, log_analysis_files_extra	[]	Linux text logs (globs). _extra adds to the base list and to the profiles' - it never replaces them
log_analysis_win_logs, log_analysis_win_logs_extra	[System, Application], []	event log channels, e.g. Microsoft-Windows-TaskScheduler/Operational, Directory Service, DNS Server
log_analysis_win_level	3	1 critical, 2 + error, 3 + warning
log_analysis_win_providers	[]	providers read at every level up to information (Service Control Manager); log_analysis_win_providers_only: true = only these
log_analysis_win_event_ids	[]	IDs always read: "System:7031", or a number for every log read plus Security (4625, 4740)
log_analysis_win_files, log_analysis_win_files_extra	[]	Windows text logs (wildcards), e.g. 'D:\Apps*\logs*.log'
log_analysis_match, log_analysis_match_extra	error, fail, fatal ... / []	the words a text log's line (or a container's) is read for; _extra adds words (SEVERE)

Setting	Default	What
`log_analysis_ignore`, `log_analysis_ignore_extra`	two harmless Windows events / `[]`	lines left out before they are grouped (regular expressions, matched against "program line"): known noise. `_extra` adds yours
`log_analysis_names_extra`	`[]`	more names ACT replaces with placeholders (host names always are)
`log_analysis_act`	`true`	`false` = the patterns only, no ACT, no key needed
`log_analysis_max_items`	`30`	ACT gets at most this many patterns, the most severe first; the rest are in the patterns table
`log_analysis_act_batch`	`site_act_batch` (5)	patterns per question to ACT, each question with only its patterns' evidence; the answers make one report. A long answer about many patterns is what a gateway or proxy cuts off. `0` = all in one question
`log_analysis_max_lines`, `log_analysis_max_line_chars`	`500`, `400`	per log: the newest lines kept; a longer line is cut
`log_analysis_max_chars`	`60000`	the evidence ACT reads is cut here
`log_analysis_min_count`	`1`	a pattern seen fewer times is left out
`log_analysis_email_if_clean`	`false`	`true` = email also when nothing was found
`log_analysis_fail`	`false`	`true` = the job is red when a critical or error pattern was found
`log_analysis_esxi_hosts`	`[]`	`vm_log_analysis.yml`: only these hosts (`esx0*`)
`log_analysis_vcenter_logs`, `log_analysis_esxi_logs`, `log_analysis_read_lines`	`[vpxd]`, `[hostd, vmkernel, vpxa]`, `20000`	`vm_log_analysis.yml`: which logs, and how far back each is read

ACT's own settings are the usual ones (ADDING_ACT.md): `site_act_provider` (GenAI.mil by default), `site_act_models`, `site_act_env` (a proxy), `site_act_ca`; `log_analysis_act_model_timeout` (600 s) for one answer.

Profiles

A profile is a product's standard log locations and units, switched on with one word. They ship in `roles/log_analysis/vars/main.yml`; yours go in `log_analysis_profiles_extra` (an entry of the same name replaces the shipped one). What your site moved elsewhere goes in the `_extra` lists.

Profile	Reads
`vcsa`	the vCenter appliance's logs (on by itself with `log_analysis_source: vcsa`)
`mid_server`	a ServiceNow MID Server on Windows: `agent0.log*` and `wrapper.log*` under `C:\ServiceNow\*\agent\logs` and `D:\...`; its service stopping or crashing (System 7023, 7024, 7031, 7034); lines with SEVERE
`iis`	WAS / W3SVC / worker process events; the HTTP.sys error logs (`HTTPERR`)

Profile	Reads
`sql_server`	the MSSQLSERVER and SQL Agent events; `ERRORLOG*`; severity 16-25, deadlocks, failed logins
`nginx`, `httpd`	their error logs and units
`mariadb`	MariaDB and MySQL error logs, `mariadb` and `mysqld` units
`podman`	the podman units and the `podman` / `conmon` identifiers
`sssd`	the SSSD logs and unit
`idm`	an IdM (FreeIPA) server: Directory Server errors, the KDC, kadmin, httpd, named, custodia, the CA
`auditd`	`audit.log`'s failed results (`res=failed`, `success=no`) and the unit
`aap`	an AAP node installed from RPMs: `/var/log/tower/*.log`, the controller, receptor, gateway, nginx and redis units. A containerized AAP: name its containers in `log_analysis_containers` (`user/automation-controller-task` ...)

The **MID Servers run on Windows**: put them in a group of the Windows inventory with

YAML

```
log_analysis_profiles: [mid_server]
# installed elsewhere than C:\ServiceNow or D:\ServiceNow:
log_analysis_win_files_extra: ['E:\MID\*\agent\logs\agent0.log*']
```

Set it up in AAP

1. **The key.** The **ACT model key** credential your other ACT jobs use (or create it: `aap/credential_types/act_model_key.yml`). Not needed with `log_analysis_act: false`.
2. **Log analysis** (`playbooks/log_analysis.yml`) - one template per inventory:
   - Linux servers: the Linux inventory and its **Machine** credential (an account that may sudo).
   - Windows servers: the Windows inventory and its **Machine (Windows)** credential (WinRM).
   - The vCenter appliance: a host in a group with `log_analysis_source: vcsa`, its Machine credential root (or a sudo account), the appliance's shell bash (above).
   - Credentials: the Machine credential **and** ACT model key. **Prompt on launch** for the **Limit** (hosts only - since 0.32.0 a Limit needs no `localhost`; one with it works too), and a **survey** with `target` (the group), `log_analysis_question` (text, not required), `log_analysis_since` / `log_analysis_until` (text, not required) and, if you like, `log_analysis_profiles` (multiple choice).
   - Variables: `report_email_to: ops@yoursite.mil` (or empty, with `report_web_dest` only).
3. **VM - vCenter log analysis** (`playbooks/vm_log_analysis.yml`): inventory, project and execution environment as the other VM templates; credentials **VMware vCenter** (Global > Diagnostics) and **ACT model key**; no Limit. Several vCenters: `vmware_vcenters`, as the other VM jobs.
4. **First run as a dry run:** Job type **Check**. Everything is read and reported; ACT is not called.

Sizes and the GenAI quota

ACT is called **once per job**, whatever the number of hosts: the grouping does the shrinking (20 hosts x 500 lines become a few dozen patterns), and the evidence is capped at `log_analysis_max_chars` (60000 characters, roughly 15000 tokens) - well inside GenAI.mil's default quota of 200,000 tokens a minute per key. The lines themselves travel from each host to the AAP node: at most `log_analysis_max_lines` per log, `log_analysis_max_line_chars` each. Raise `log_analysis_max_items` for more patterns explained, or lower it (and set `log_analysis_min_count: 3`) when a noisy group crowds the list; quiet known noise for good with `log_analysis_ignore_extra`.

24. NetApp ONTAP health report

One job, `playbooks/ontap_health_report.yml`, reads every NetApp ONTAP cluster you list and emails one report: what is broken first, then capacity, protection and services. A second, *NetApp ONTAP hardware inventory*, lists their hardware - models, serial numbers, firmware (The hardware inventory). Each row is coloured: red = critical, amber = warning, green = OK, blue = for your information.

It only reads. It sends GET requests to each cluster's REST API (the same API System Manager uses) and nothing else: the code refuses any other kind of request. It runs on the AAP side, like the VMware jobs: no inventory of the clusters is needed, no SSH, no Limit.

What the report shows

At the top: the title with the number of critical and warning findings, then boxes with the main counts (nodes down, health alerts, hardware, full volumes and aggregates, SnapMirror, network, certificates). Then, in this order:

Section	What it shows	Colours
Clusters	each cluster (the address it was read at under its name): ONTAP version, system health, nodes up, space used on its aggregates, NTP servers. A cluster that could not be read is listed in red with the reason	health, nodes, space
Nodes	state, uptime (days hours:minutes), model, version, whether the partner could take over (storage failover), service processor, NVRAM battery, the node's clock against the AAP server's	green UP / red DOWN, and each status
Volumes	volumes 85 % full or more, and volumes offline or restricted, with their aggregate, state, type, size, available, used %. Volumes under 50 GB (`ontap_volume_min_gb`) are left out, full or not online - root volumes and other small ones run full by design; the table says how many	amber 85 %, red 90 %, red offline
System health	ONTAP's health monitors (`system health subsystem show`) that are not OK	amber degraded
Hardware: controllers and shelves	each controller and disk shelf: power supplies, fans, temperature, failed parts (FRUs)	red failed
Disks	broken disks; disks rebuilding, copying or in maintenance; unassigned disks	red / amber / blue
Spare disks	spare disks per node (a failed disk is rebuilt onto a spare)	red none, amber few

Section	What it shows	Colours
Network interfaces (LIFs)	LIFs down, not on their home port (the home port under the one it is on), or disabled	red / amber / blue
Ports down	enabled Ethernet and FC ports that are not up	red in use, blue no cable / not used
Port errors (CRC)	ports with receive errors or CRC errors since the node booted (CRC counters: ONTAP 9.11+)	amber from 1, red from 10,000
Aggregates	every data aggregate, fullest first: node (its home node under it when away), space (used of size, available), used %, RAID type and disks	amber 85 %, red 90 %
Aggregates not on their home node	after a takeover, aggregates still on the partner	amber
Inodes (files)	volumes using 85 % or more of their inodes (no new file can be created when they run out)	amber 85 %, red 90 %
Snapshot space	the 25 volumes whose snapshots hold the most: type, volume size, snapshot count, reserve, snapshot used, % of reserve, % of volume	amber from 100 % of the reserve (spilling into the volume)
SnapMirror	relationships that are unhealthy, lagging, broken off, paused or uninitialized, and transfers running now: source, destination, state (the transfer status under it), healthy, lag, reason	red unhealthy / 48 h lag, amber 24 h lag, blue transferring
SnapMirror transfers	the same relationships in the same order: last transfer, progress, progress updated, policy	blue running
Cluster and SVM peers	cluster peers not available, SVM peers not peered	red / amber
SVMs not running	stopped storage VMs (a stopped DR destination is normal: blue)	red
CIFS (SMB) servers	each CIFS server: enabled or not, and its domain controllers in one cell (`2 OK · 12 not contacted`, `1 not reachable`) with the ones not reachable named; under the table, the `vserver` commands for the SVMs where no DC is OK, none is listed or one is not reachable	red stopped, or ONTAP tried every DC it lists and reached none; amber a DC not reachable (said when preferred); blue every DC not contacted, or none listed - ONTAP's normal state, never a finding

Section	What it shows	Colours
CIFS domain controllers	every server ONTAP lists for each SVM, one row per DC and type: address, type (DC / LDAP / KDC), preference (preferred / favored / adequate), state (OK, *not contacted*, or what ONTAP said), the nodes when they differ; not reachable first. Folded on the website when it is long (click its title)	amber not reachable; blue not contacted
LUNs	LUNs not mapped to any host (forgotten?) and LUNs not online	amber / red
Certificates expiring	certificates expiring within 60 days or expired	amber 60 days, red 14 days
Health alerts	what the health monitors raised (`system health alert show`): node, severity, subsystem, alert, resource, since	red critical / major, amber minor
Health alerts: cause and what to do	each alert above, in the same order: probable cause, corrective action	-
Error events (last 24 h)	ONTAP's event log (EMS): emergency, alert and error events, the same event on the same node counted once. On a cluster where no SVM has an LDAP client configured, events with "ldap" in their name are left out (`ontap_ems_ignore_ldap`), and so are the names in `ontap_ems_ignore`; the section says how many	red alert / emergency, amber error

The health alerts and the error events come last (since 0.31.1): the tables above them say what is wrong, these say what ONTAP raised about it - often the same thing again, and many lines. The volumes come third, after the nodes (since 0.34.0): the table most often acted on.

A section with nothing to report says so in one line ("Every LIF is up and at home."). Long tables show the problems first and are cut at 50 rows (`ontap_report_max_rows`); the job's artifacts (`ontap_health`) have every finding.

Before you start

1. A read-only account on every cluster

The report needs an ONTAP account with the built-in **readonly** role, for the **http** application (the REST API). On each cluster, as an administrator (`cluster1` is the cluster's admin SVM, its name):

```
security login create -vserver cluster1 -user-or-group-name svc_aap_ro -application http
  -authentication-method password -role readonly
```

Use the **same user name and password on every cluster**: the job has one credential for all. (An Active Directory account works too, with `-authentication-method domain`, if the cluster is set up for AD logins.)

2. The way from AAP to the clusters

The AAP server (or the execution node that runs the job) must reach each cluster's **management address** on HTTPS, port 443. Test from the AAP server (it asks for the password):

```
curl -sk -u svc_aap_ro "https://cluster1.yoursite.mil/api/cluster?fields=version"
```

A short JSON answer with the version means the account, the network and the API are fine.

That `curl` is not the job. The job runs **in the execution environment** (a container on the AAP execution node), checks the certificate (`-k` above skips that), and uses the EE's OpenSSL, DNS and proxy settings. When the curl works and the report still says **UNREACHABLE**, read the reason on the cluster's row: it says which of these it is and what to set. To run the same test the way the job does, on the execution node:

```
podman run --rm -it <your EE image> curl -s -u svc_aap_ro
  "https://cluster1.yoursite.mil/api/cluster?fields=version"
```

3. The cluster's certificate

ONTAP's management certificate is often self-signed, or from your own CA. The job checks it by default. Either:

- put the CA certificate (public, `.pem`) at `playbooks/files/ca/ontap-ca.pem`, add `ontap_ca_path: "{{ playbook_dir }}/files/ca/ontap-ca.pem"` to `playbooks/group_vars/all.yml`, and the line `playbooks/files/ca/` to `.site-local` (so an update keeps it); or
- set `ontap_validate_certs: false` (the password still travels encrypted; the job just does not check who answers).

4. The credential

1. **Automation Execution > Infrastructure > Credential Types > Create credential type**: name `NetApp ONTAP`; paste the `inputs` block of `aap/credential_types/netapp_ontap.yml` into **Input configuration** and the `injectors` block into **Injector configuration**. Save.
2. **Credentials > Create credential**: type **NetApp ONTAP**, name e.g. `NetApp ONTAP read-only`, the user name and password from step 1. Save.

Set it up

1. **Templates > Create template > Create job template:**
   - Name: `NetApp ONTAP health report`
   - Inventory: any (e.g. your VMware one: the job runs on the AAP side)
   - Project: site-automation. Playbook: `playbooks/ontap_health_report.yml`
   - Execution environment: any with Python 3 (no NetApp collection is needed)
   - Credentials: **NetApp ONTAP read-only**
   - Tick **Prompt on launch** next to **Variables** (to try one cluster first)
   - Variables:

YAML

```
ontap_clusters: [cluster1.yoursite.mil, cluster2.yoursite.mil]
report_email_to: storage-team@yoursite.mil
```

- Leave Limit empty. Save.

2. **First run: one cluster.** Launch with Variables `ontap_clusters: [cluster1.yoursite.mil]`. Read the report in the job's output. Lines that start with `cluster1: could not read ...` or `... reduced detail ...` under a section say what this cluster's ONTAP version or the account's role did not allow: see Troubleshooting.
3. **All clusters**, then a schedule: **Schedules > Create schedule**, e.g. every day at 06:00 (set **your** time zone).

A dry run (Check) reads and prints the same report, and sends no email.

SnapMirror relationships are read on their **destination** cluster: list the destination clusters too, or the relationships into them are not checked.

The hardware inventory

NetApp ONTAP hardware inventory (`playbooks/ontap_hardware_report.yml`) lists the hardware of every cluster in `ontap_clusters`, like *VMware - hardware inventory* does for the ESXi hosts - no survey, read-only (GET requests to the REST API, the same read-only account and credential as the health report). At the top, the counts: clusters, controllers, models, ONTAP versions, shelves, disks, controllers with a serial number. Then:

- **Models** - each controller model, how many controllers, and the ONTAP, system firmware and service processor (SP / BMC) versions they run, with how many run each (`11.10 (6), 11.9 (2)`: two controllers left behind by a firmware update);
- **Controllers** - every controller (node): cluster, model, **serial number**, system ID, ONTAP version, HA partner, CPU, memory, system firmware, SP / BMC and its firmware, NVRAM battery, Flash Cache modules, its ports (`2x 25G, 4x 10G; 4x 32G FC`: the physical Ethernet ports by speed, then the FC ports), time up, state;
- **Shelves** - every disk shelf: model, serial number, its modules (IOM12, NSM100 ...) and their firmware, how it is connected (SAS, NVMe), how many disks, state;
- **Disks by model** - each disk model of each cluster: vendor, model, type, size, how many, how many are spares, and the firmware versions they run (`NA02 (46), NA01 (2)`: two disks the disk firmware update did not reach);
- **Not all read** - what a cluster's ONTAP or the account's role did not give (`reduced detail`), the rest in.

The email attaches all of it as an Excel workbook (`netapp-ontap-hardware-inventory_2026-11-03.xlsx`), a row each:

Sheet	What
Clusters	each cluster: address, ONTAP, location, contact, how many controllers, shelves and disks; a cluster not read with the reason
Controllers	everything above, plus the vendor serial number, board, CPU count and the SP / BMC address and state
Shelves	each shelf: model, serial, module type, module firmware, connection, internal or not, disks, state
Shelf modules	each shelf module (IOM): part number, serial number, firmware, state

Sheet	What
Disks	every disk: owner and home node, shelf and bay, vendor, model, **serial number**, **firmware**, type, class, size, usable size, RPM, container (aggregate, spare, shared ...), state
Ethernet ports	each port: type (physical, VLAN, interface group), speed (down without a link), state, MAC, broadcast domain
FC ports	each FC port: WWPN, protocol, speed, state, its transceiver (form factor, maker, part number)

Firmware: ONTAP reports the system firmware (the controller's BIOS / LOADER), the SP / BMC firmware, each shelf module's firmware and each disk's firmware - all four are in. It has no field for a network card's or HBA's firmware. The report says what ONTAP says: it does not know which versions are current (NetApp's *Upgrade Advisor* in Active IQ does).

Amber when a controller is not up (what the cluster last knew of it) or a shelf is not OK; red when a cluster could not be read (the others are still in; `ontap_hardware_fail: true` also marks the job failed, for workflows). The job output has a line per model (`AFF-A400: 4 controller(s); ONTAP 9.14.1P3 (4); firmware 11.10 (4); SP / BMC BMC 13.10 (4)`) and per cluster; the artifact `ontap_hardware` has the models and the counts.

Set it up: a template *NetApp ONTAP hardware inventory*, playbook `playbooks/ontap_hardware_report.yml`, the **NetApp ONTAP read-only** credential, any execution environment with Python 3, no Limit, no survey; on its Variables `ontap_clusters` (unless it is in `all.yml`) and `report_email_to`. Run it when you need the inventory, or on a schedule (monthly). On the report website it is on the *Network and storage* tab.

Setting	Default	
`ontap_hardware_max_rows`	`2000`	controllers, shelves and disk models listed in the email and on the page at most - the workbook always has all
`ontap_hardware_xlsx`	`true`	`false` = no workbook attached
`ontap_hardware_fail`	`false`	`true` = the job is marked failed when a cluster could not be read

The connection settings (`ontap_clusters`, `ontap_validate_certs`, `ontap_ca_path`, `ontap_timeout`, `ontap_tls_legacy`) are the health report's: set them once in `all.yml` for both.

Settings

Set them in the template's Variables, or in `playbooks/group_vars/all.yml` for every run.

Setting	Default	What it does
`ontap_clusters`	`[]`	the clusters' management addresses
`ontap_validate_certs` / `ontap_ca_path`	`true` / (none)	check the clusters' certificates; the CA file to check them with
`ontap_volume_warn_pct` / `_crit_pct`	`85` / `90`	volume used % for amber / red

Setting	Default	What it does
ontap_volume_min_gb	50	volumes smaller than this (GB) are left out of the Volumes table, full or not online (0.31.1: full only); 0 = every volume, as before 0.31.1
ontap_aggr_warn_pct / _crit_pct	85 / 90	aggregate used %
ontap_inode_warn_pct / _crit_pct	85 / 90	inodes used %
ontap_snapshot_reserve_warn_pct / _crit_pct	100 / 150	snapshot space as % of the snapshot reserve
ontap_snapmirror_lag_warn_hours / _crit_hours	24 / 48	time since the last good SnapMirror transfer
ontap_cert_warn_days / _crit_days	60 / 14	days before a certificate expires
ontap_time_drift_warn_seconds / _crit_seconds	60 / 300	a node's clock against the AAP server's
ontap_port_errors_warn / _crit	1 / 10000	receive or CRC errors on a port, since boot
ontap_min_spares	1	fewer spare disks than this on a node is amber (0 is red)
ontap_ems_hours / ontap_ems_max	24 / 500	the event log window, and the most events read per cluster
ontap_ems_ignore_ldap	auto	leave out events with "ldap" in their name: auto on a cluster where no SVM has an LDAP client configured (vserver services name-service ldap show is empty), true always, false never
ontap_ems_ignore	[]	event names to leave out, as regular expressions (any case), e.g. ['^secd\.ldap\.', 'callhome\.battery\.low']
ontap_report_max_rows	50	rows per table
ontap_snapshot_top	25	volumes in the snapshot space table
ontap_report_fail	false	true = the job shows **failed** on a critical finding or a cluster not read (for a workflow)
ontap_timeout	30	seconds for one request (no answer: asked once more). The job output lists every request that took over 10 seconds, to pick a number
ontap_tls_legacy	false	connect to older ONTAP whose TLS the EE refuses (see Troubleshooting)

All settings of this job, with their defaults: ontap_report.

Troubleshooting

You see	It means	Do
`No ONTAP account: attach a credential of type "NetApp ONTAP"`	the template has no NetApp ONTAP credential	add it (Before you start, step 4)
`ontap_clusters is empty`	no cluster listed	`ontap_clusters: [...]` in the template's Variables
A cluster **UNREACHABLE** with `timed out` or `Connection refused`	the AAP node cannot reach the cluster on port 443 (each request is asked twice)	a firewall rule from the AAP execution node to the cluster's management address; test with the `podman run ... curl` above
UNREACHABLE ... `it went through the proxy ...`	the EE has `https_proxy` set, and the cluster is not in `no_proxy`	add the clusters (or `.yoursite.mil`) to `no_proxy` in the EE or the job's environment
A table says `no answer within 30 s, asked twice` and the rest of the cluster is there	that one table is slow on a big cluster	`ontap_timeout: 120`
UNREACHABLE with `UNSAFE_LEGACY_RENEGOTIATION_DISABLED`, `KEY_TOO_SMALL`, `MD_TOO_WEAK`, `UNSUPPORTED_PROTOCOL` or `HANDSHAKE_FAILURE`	an older ONTAP whose TLS the EE (OpenSSL 3) refuses; curl on a host with another crypto policy still connects	update ONTAP, or `ontap_tls_legacy: true` for those clusters' template
UNREACHABLE with `Hostname mismatch`	the cluster is listed by a name (or IP) that is not on its certificate	list it by the name on its certificate
UNREACHABLE with `Name or service not known`	the name does not resolve on the AAP node	use the name DNS knows, or the IP address
UNREACHABLE with `CERTIFICATE_VERIFY_FAILED`	the cluster's certificate is not trusted	Before you start, step 3
`the ONTAP account was refused (HTTP 401)`	wrong user or password, the account does not exist on **that** cluster, it is locked, or it lacks the `http` application	create it the same on every cluster (step 1); unlock it (`security login unlock`)
`cluster1: could not read alerts - HTTP 403 ... the account's role may not allow this`	the role does not allow that command	use the built-in `readonly` role (step 1)
`... reduced detail - ONTAP refused a field ...`	this ONTAP version does not know a field; the job asked again with fewer	nothing: the section is still shown, a column may say `?`. Send the line to the people who maintain this repository

You see	It means	Do
CIFS *DCs* `2 OK · 12 not contacted`, or `14 not contacted` with no DC OK (blue)	ONTAP lists **every** DC of the domain and marks those it has not needed to probe `undetermined` (`vserver cifs domain discovered-servers show`) - other sites, preference *adequate*, or every DC while CIFS works: ONTAP's normal state	nothing (1.6.1; 1.6.0 showed red when no DC was OK). To see them: `vserver cifs domain discovered-servers show -vserver <svm>`; to make ONTAP probe them again: `vserver cifs domain discovered-servers reset-servers -vserver <svm>` - a change, run it in a quiet window
CIFS `dc2 (unavailable)` (amber), or `ONTAP reports no DC it is connected to - it tried them and reached none` (red)	ONTAP tried that DC and could not reach it; red: it tried every DC it lists and reached none - the SVM cannot authenticate users	`vserver cifs domain discovered-servers show -vserver <svm>`, then the DC, DNS (`vserver services name-service dns check -vserver <svm>`) and the route from the SVM's LIFs; then `reset-servers` (above)
CIFS *DCs* `none listed` (blue)	ONTAP lists no DC for the SVM: the discovery has not run, or finds none	`vserver cifs domain discovered-servers discovery-mode show -vserver <svm>`, then `reset-servers` (above)
`CRC counters need ONTAP 9.11 or later`	older ONTAP has no CRC counter in its REST API	nothing: receive errors are still shown
SnapMirror is empty, but you have relationships	they are read on the destination cluster	add the destination cluster to `ontap_clusters`
An aggregate you know is missing	root aggregates are not returned by ONTAP's REST API	by design: root aggregates are not listed
A volume shows `-` for available and used %	it is offline or restricted: ONTAP reports its size but no usage for it	it is listed in red as offline (or restricted)
The email is too long	many findings	lower `ontap_report_max_rows` / `ontap_snapshot_top`; the artifacts keep everything
`could not read ems - ... only the first 500 records were read`	many error events	raise `ontap_ems_max`, or lower `ontap_ems_hours`

Limits

- The fields the job reads were checked against NetApp's ONTAP REST API reference for ONTAP 9.10 to 9.16. It was tested against a fake ONTAP API (`tests/netapp/`), not a real cluster: run it on one cluster first, and send any `could not read` or `reduced detail` line you see.

- The CLI commands it reads through REST (system health, storage failover, SnapMirror progress) are ONTAP `show` commands at admin level, which the `readonly` role may run.
- It reports; it changes nothing. Fixes are done in System Manager or the ONTAP CLI.

25. Network device certificates: report and renewal

The TLS certificate each **switch, firewall, router, printer, iLO / iDRAC, UPS, storage array** ... presents, read from the controller with a TLS hello - **no login to the devices, nothing changed on them**. Two jobs:

Template	Playbook	Does
Network device certificate report	`playbooks/net_cert_report.yml`	every certificate, soonest expiry first, and for each one due what the renewal would do. Read-only: never ServiceNow, never a CSR
Network device certificate renewal	`playbooks/net_cert_renew.yml`	a ServiceNow incident per certificate due (critical within 7 days, else warning), with the device, port, subject, names, issuer and how to renew it. Optionally, on Cisco IOS / IOS-XE, a CSR made on the device and attached

Both can also write every certificate to the certificate inventory (CSV / SQL Server, CERT_INVENTORY.md).

Which devices

An inventory group (the default, and the safest: only what you list). Put the devices in the group `net_cert_devices` (`net_cert_group`) of the inventory the template uses:

```yaml
net_cert_devices:
  hosts:
    sw01.example.mil:                        # connected to by name (or ansible_host)
    pr01.example.mil: {ansible_host: 192.0.2.30}
    ilo-esx01.example.mil: {net_cert_ports: [443, 17990]}
    rtr01.example.mil: {ansible_network_os: cisco.ios.ios, ansible_connection:
      ansible.netcommon.network_cli}
  vars:
    net_cert_ports: [443]                    # the ports read (default net_cert_ports: [443])
```

Per host: `net_cert_ports`, `net_cert_address` (what is connected to; default `ansible_host`, else the name), `net_cert_servername` (the name sent in the TLS hello; default the host's name). The jobs never log in to these hosts - a device needs no credential to be read.

Subnets - finds devices nobody listed. `net_cert_targets: subnets` (or `both`, with the group):

```yaml
net_cert_targets: both
net_cert_subnets: ['192.0.2.0/24', '198.51.100.0/25']
net_cert_ports: [443, 8443]
net_cert_exclude: ['192.0.2.1', 'ups*']        # never connected to: addresses, CIDR ranges, names
```

Every address of each subnet, each port. A swept address that answers is named by its DNS name (PTR) in the report. A port that does not answer is only counted. **Ask your network and security teams first:** a sweep is a port scan, and an intrusion detection system may alert on it. `net_cert_max_addresses` (4096) refuses a bigger sweep - a `/16` by mistake would take hours. Try the group first; sweep to find what it misses.

What is due

`net_cert_warn_days` (30): due - an incident (warning); `net_cert_crit_days` (7) or expired: critical; `net_cert_notice_days` (60): blue in the report, no incident. `net_cert_only: ['sw01*']` limits a run to some devices - to try the renewal on one. `net_cert_unanswered_finding: true` opens an incident for an inventory device whose port gives no certificate (off: listed under *No certificate read*).

Old devices speak old TLS (1.0, weak ciphers): the jobs accept it - only the certificate is read, nothing is sent. An expired, self-signed or untrusted certificate is read like any other.

The renewal

With `cert_renew_servicenow: catalog` there is no incident: a CSR made on a Cisco device (`net_cert_cisco_csr`) is ordered from your PKI's catalog item, and the other devices are in the report only: CERT_RENEWAL_CATALOG.md.

The incident only (the default, `net_cert_cisco_csr: false`): one incident per certificate due, for `servicenow_assignment_group`, with the steps: make the CSR on the device (its web interface or CLI - the key stays there), have the PKI sign it, import the issued certificate and its chain the way the vendor says. A run again notes the same incident; once the certificate is renewed the incident is noted as cleared (`servicenow_resolve_cleared: true` resolves it). A renewed certificate that comes due years later is a new incident.

Cisco IOS / IOS-XE CSRs (`net_cert_cisco_csr: true`) - for a due certificate of an inventory host with `ansible_network_os: cisco.ios.ios`, the job logs in (network_cli, the template's Machine credential for the devices) and, on the device:

1. `crypto key generate rsa general-keys label SA-RENEW-<expiry> modulus 2048` - a new key, **not exportable**: it never leaves the device (`net_cert_cisco_key_bits`; the label: `net_cert_cisco_trustpoint_prefix`);
2. `crypto pki trustpoint SA-RENEW-<expiry>` - `enrollment terminal pem`, the old certificate's subject and DNS names (`subject-name`, `subject-alt-name`), `rsakeypair` the new key;
3. `crypto pki enroll SA-RENEW-<expiry>` - the CSR, printed, attached to the incident with what to do next: `crypto pki authenticate` (the CA), `crypto pki import ... certificate` (the issued one), then `ip http secure-trustpoint` and restart HTTPS. **Then** `write memory` - the new key and trustpoint are in the running configuration only, and a reload before that loses the key (the issued certificate would not fit).

Nothing in use changes: the device keeps its certificate until someone imports the new one. A CSR is made once

- its incident is the record; a run again makes none while the incident has one. Other vendors (and NX-OS, ASA):

the incident only. **Try it first on one lab or spare device** (`net_cert_only: ['rtr-lab*']`), and in Check: the CLI's prompts differ between IOS releases. `subject-alt-name` needs IOS-XE 16 or later; on older IOS the job says it did not work (the incident stays, without a CSR).

The subject and names come from the certificate the device served, and each goes into a configuration line. One that is not a plain DN or host name - control characters, a line break, quotes, a backslash, a semicolon, non-ASCII letters - is refused for that certificate: nothing is sent to the device, the incident says why (without a CSR). Make that CSR by hand.

Templates

Field	Report	Renewal
Inventory	the one with `net_cert_devices`	the same
Execution environment	any (the minimal one); the all-in-one EE for the Cisco CSRs (`cisco.ios`) and SQL Server	
Credentials	none	`ServiceNow API`; with `net_cert_cisco_csr`, a Machine credential that logs in to the Cisco devices
Variables	(optional) `net_cert_targets`, `net_cert_subnets`, `report_email_to`	`servicenow_assignment_group: <your network team>`
Limit	empty, **no** Prompt on launch (it runs on the controller)	the same
Job type	Run	**Check** first: it opens nothing, makes no CSR

The Variables of each: `aap/extra_vars/net_cert_report.yml`, `net_cert_renew.yml`.

A workflow (daily): `[Network device certificate renewal]` alone - it reads, opens the incidents and emails the report (`report_email_to`). The report template is for a look on demand, or a weekly email.

Troubleshooting

You see	Means / do
`The inventory group net_cert_devices ... has no hosts`	put the devices in that group of the template's inventory, or sweep (`net_cert_targets: subnets`)
No certificate read: `refused`	nothing listens on that port: the device's `net_cert_ports`
`no answer (timeout)`	a firewall between the AAP node and the device, or a slow device: `net_cert_timeout`
`not TLS, or a TLS this controller cannot speak`	a plain-text port, or a device so old even TLS 1.0 fails
`the sweep would be more than 4096 addresses`	smaller subnets, or `net_cert_max_addresses`
`no CSR came back from the device`	the job could not log in to the Cisco device: its credential, `ansible_network_os`, `ansible_connection`
`crypto pki enroll printed no CSR`	the device's prompts differ: run the three commands above by hand once, and tell us what it printed

26. Trust stores: who still trusts a compromised or dropped CA

When a certificate authority is compromised, the browsers block it within hours. Everything else keeps trusting it until *its own* trust store is updated - and a server has many: the system's bundle, every Java's `cacerts`, every Python environment's `certifi`, Node's built-in roots, the image inside every container, the bundle an application ships. A Go program does not even read a store for this: it carries its verification in the binary and has to be rebuilt.

The **trust check** reads all of them on every Linux host, and vCenter's and the ESXi hosts' trust stores through vCenter, and says which still hold a certificate on its list. Read-only - until you switch the removal on (below).

- the check `trust`, in the health check's **weekly** set (`playbooks/health_check.yml`: `health_checks: [trust]` runs it alone)
- the **Trust store report** (`playbooks/trust_report.yml`): the same check on every Linux host, one table of every store read, emailed (`report_email_to`). The hosts that hold one fail, so a workflow can open tickets.
- the **VMware trust store report** (`playbooks/vmware_trust_report.yml`): vCenter's trusted root store and each ESXi host's trusted CAs, from the controller with a *VMware vCenter* credential - its own template, so it runs on its own.

The list

It ships with the check (`roles/check_trust/vars/main.yml`): **October 2026, the eMudhra (emSign) compromise** - eight intermediate CAs whose private keys were weak enough to compute from the certificates themselves (six for TLS, two for code signing), each issued twice: by eMudhra's own root and cross-signed by Sectigo's *AAA Certificate Services*. All sixteen are revoked. The roots:

Certificate	Severity	Why
the 8 intermediates (16 certificates, `EM DV / OV / EV TLS CA - G3B / G3C`, `EM OV CS CA - G3B / G3C`)	**critical**	anything that trusts one accepts certificates anyone can sign
`emSign ECC Root CA - G3`	warning	it cross-signs the issuer of the compromised intermediates; removed by Mozilla (NSS 3.131.1), Chrome, certifi 2026.10.19, webpki-roots 1.0.10, curl's bundle. A store that still has it accepts the compromised chains
`emSign Root TLS CA - G3`, `emSign Root CS CA - G3`	warning	the direct issuers (Microsoft's root store only)

Certificate	Severity	Why
`AAA Certificate Services`	notice	Sectigo's root that cross-signed all eight. It is in nearly every trust store and many unrelated certificates chain to it. Red Hat's advisory says to blocklist it: decide first what breaks. *Notice* = in the report, no finding, no ticket - `check_trust_severity: {"AAA Certificate Services": warning}` once you decide

Every certificate is matched by its SHA-256 fingerprint **and by its public key**: a certificate not on the list but carrying one of the compromised keys - a cross-sign nobody listed - is a hit too (shown as *the same key, as ...*).

Your own list. `check_trust_extra` adds certificates (a retired internal root, the next incident):

```yaml
check_trust_extra:
  - {name: "Old Corp Root CA", sha256: "AB:CD:...", kind: root, severity: warning, why: "retired 2026-01"}
```

`openssl x509 -in the.pem -noout -fingerprint -sha256` gives the fingerprint (with or without colons). A name that is already on the shipped list takes your entry's severity and words.

What it reads, on a Linux host

Store	Where	Fix
the system bundles	`/etc/pki/ca-trust/extracted/pem/tls-ca-bundle.pem` and the OpenSSL trust bundle (RHEL), `/etc/ssl/certs/ca-certificates.crt` (Debian, Ubuntu, Alpine), SUSE's - the same file under two names once	update `ca-certificates`, or blocklist the certificate: copy its PEM into `/etc/pki/ca-trust/source/blocklist/` and run `update-ca-trust`
p11-kit's live view	`trust extract`: the anchors NSS and GnuTLS clients see, and the blocklist	a blocklisted certificate is reported as *blocked*, no finding; still in a bundle too = `update-ca-trust` was not run (the finding says so)
Java	every `cacerts` / `jssecacerts` under `/usr/lib/jvm`, `/opt`, `/usr/local` ... and the ones running java programs use, with the JDK's version	update the JDK, or `keytool -delete`; a `cacerts` that links to `/etc/pki/java/cacerts` follows the system trust
Python	every `certifi/cacert.pem` (requests, urllib3, pip carry their own roots) under `/usr/lib`, `/opt`, `/home` ..., with the certifi version	`pip install -U 'certifi>=2026.10.19'` in each environment (the finding lists them)
Node	its built-in roots (`tls.rootCertificates`) and version, per node binary found	update Node to its line's fixed version (22.23.4, 24.22.1, 26.12.1), or run it with `--use-openssl-ca`
podman containers	**off unless** `check_trust_containers: true` (0.34.0): the bundle inside every running container, root's and each logged-in user's (`podman exec ... sh -c`: endpoint security flags it as certificate discovery - clear it with them first)	pull or rebuild the image, restart the container
certificate files	every `*.pem`, `*.crt`, `*.cer`, `*.der`, `cacert*`, `ca-bundle*` under `/etc`, `/opt`, `/srv`, `/usr/local`, `/var/lib`, `/root`, `/home` - only the files with a hit are listed; container image layers and the copies `update-ca-trust` extracts are skipped	an application's own bundle: update the application, or take the certificate out
Java keystores with other names	every `*.jks`, `*.keystore`, `keystore*`, `*truststore*` under the same folders (JKS natively, no password needed to read the trusted entries); `*.p12` / `*.pfx` with keytool and the default password	`keytool -delete` the entry
NSS databases	`/etc/pki/nssdb` (the system's: curl and other NSS clients on older RHEL), root's and each user's `~/.pki/nssdb` (Chrome, Evolution), read with `certutil -L` by nickname	`certutil -D -d sql:<dir> -n <nickname>`

Store	Where	Fix
Go programs	the running ones, and the executables under `/usr/local/bin`, `/opt`, `/srv`: the Go version each was built with (from the binary's build information)	rebuild with Go 1.27.3 / 1.26.10 or later (CVE-2026-111943: they reject every chain with one of the compromised keys); a program built with an older line has no fixed version to go to
NSS, ca-certificates	the packages' versions (`nss` below 3.131.1 is a finding; `check_trust_ca_certificates_fixed` compares `ca-certificates` once the errata is out)	update the packages

Not read: Firefox and Thunderbird profiles (add the profile folder to `check_trust_nss_dirs` to read one), Rust programs built with `webpki-roots` (the roots are compiled in: rebuild with 1.0.10), Docker containers (podman only; the image layers under `/var/lib/docker` are skipped on purpose), keystores that need a password other than `changeit`. What could not be read is listed under *Not read*.

The vCenter appliance itself is a Linux (Photon) host with its own bundle, a bundled JRE and Python: put it in the Linux inventory (root over SSH, the shell enabled) and the same check reads it. vCenter's *trust store* is another thing: the VMware report below.

The folders searched, the limits and the fixed versions are settings: check_trust. Each search stays on the host's own filesystems (no NFS) and stops after `check_trust_timeout` seconds; a bigger server gets a longer timeout.

The findings

One finding per *kind* of store on a host, so a host with four certifi bundles gets one finding that names all four, and a host with eighteen Go programs built before the fix gets one that names them:

Finding	Severity	Means
`the system trust (tls-ca-bundle.pem and 1 more, ca-certificates 2025.2.80-7.el9) trusts emSign ECC Root CA - G3 - ...`	the worst certificate it holds	the system bundles still have it: every OpenSSL, Go, Python and curl client on the host accepts the compromised chains. Update `ca-certificates` or blocklist
`/opt/app/certs/bundle.pem (certificate file) trusts EM DV TLS CA - G3B - its private key is computable ...`	**critical**	a compromised intermediate itself, in an application's bundle
`2 Python certifi bundles (...) trusts emSign ECC Root CA - G3`	warning	`pip install -U certifi` in each environment
`3 Go programs built with a Go before the fix: ...`	warning (`check_trust_software_severity`)	rebuild them, or get the vendor's build made with a fixed Go

Finding	Severity	Means
`Node.js 22.23.1 (/usr/bin/node) is below 22.23.4`	warning	update Node
`NSS 3.126.0 is below 3.131.1`	warning	update the `nss` package
`no system CA bundle was read on this host`	warning	none of `check_trust_bundles` exists: name the host's bundle there

The email is laid out in the order to act, then the proof:

1. **Remove now** - the stores that hold a compromised intermediate (red): what to do, per store
2. **Remove next** - the stores that still hold the distrusted root (amber), the ones the removal can clear: the system trust, Java, certifi, an application's file, vCenter, ESXi
3. **Then update** - what cannot be edited: Node's built-in roots, a container's image, Go programs, NSS, below the version that fixed it
4. **Listed only** - notice-level, nothing to do until you decide (AAA Certificate Services)
5. *Removed* - when the removal ran: what was done, each backup
6. **Everything read** - every store and program on every host with what it holds, worst first: also the ones that hold nothing (green) and the ones with only a notice-level certificate (blue). The count is how many certificates the store holds, not a problem count.
7. *Not read* - what could not be opened

Windows

The **Windows trust store report** (`playbooks/win_trust_report.yml`, template *Windows - trust store report*) and the check `trust` in the Windows health check's **weekly** set read, with the same list:

Store	Where	Fix
the machine certificate stores	Trusted Root (`Root`), Intermediate CAs (`CA`), the roots Windows Update keeps (`AuthRoot`), Trusted Publishers, Trusted People; the connecting account's Root and CA	put the certificate in the **Disallowed** store - that is Windows' blocklist, it wins over every other store, also over the roots Windows Update re-adds - and delete it from the store it is in (`check_trust_remove` does both; an AuthRoot entry is left in place, Disallowed covers it)
the Disallowed stores	a certificate there is *blocked*: listed, no finding	
Java	every `cacerts` under Program Files (Java, Adoptium, Corretto, Zulu, Microsoft, Red Hat): JKS natively, PKCS12 with the JDK's keytool	update the JDK, or `keytool -delete`
Python	every `certifi\cacert.pem` under the Python installs and Anaconda	`pip install -U certifi` in each

Expect the two Microsoft-only emSign roots (`emSign Root TLS CA - G3`, `emSign Root CS CA - G3`, warning) on most Windows servers: Microsoft's root program ships them. They are the amber rows there until

Microsoft moves them to its disallowed list, or you do with the removal. The Windows report has the same sections and the same `check_trust_extra`, `check_trust_severity` and `check_trust_remove` - which removes only on the Windows trust store report: the health check's `trust` check only reads, whatever `check_trust_remove` says. A JKS `cacerts` is rewritten only when it was read to its end and its integrity digest matches the keystore password given (the **Keystore password** credential, else `check_trust_keystore_password`, `changeit`); otherwise it is listed as not removed, unchanged.

VMware

The **VMware trust store report** (`playbooks/vmware_trust_report.yml`, template *VMware - trust store report*, a *VMware vCenter* credential, no inventory) reads, from the controller:

- **vCenter's trusted root store** (Administration > Certificates > Trusted Root Certificates: the REST API `certificate-management/vcenter/trusted-root-chains`, vCenter 6.7 Update 2 and later). The account needs *Certificate Management* > *Manage* for this call; without it the row says so.
- **each ESXi host's trusted CA certificates** (the host's certificate manager, through vCenter).

A hit fails the job; one table, worst first, emailed as the other VMware reports. `vmware_trust_esxi: false` reads vCenter only. Several vCenters: `vmware_vcenters`, as the other VMware reports. The same `check_trust_extra` and `check_trust_severity` apply; `check_trust_remove: true` deletes (above).

Removing them

The report only reads. `check_trust_remove: true` on the *Trust store report* takes the listed certificates out of the stores that hold them, then reads every host again, so the report and the findings show what is left. **Run it as Check first** (Job type *Check*): the same plan, per store, nothing changed. Off by default; it never runs from the health check.

Store	What happens	Undo
the system trust	the certificate is **blocklisted**: its PEM goes to `/etc/pki/ca-trust/source/blocklist/` (SUSE: `/etc/pki/trust/blacklist/`) and `update-ca-trust` runs; Debian and Ubuntu: its line in `/etc/ca-certificates.conf` is switched off and `update-ca-certificates` runs. The package's bundle is never edited (an update would put it back; the blocklist survives updates)	delete the file from the blocklist folder (or the `!` in the conf), run the update command again
Java `cacerts`	the entry is deleted (JKS natively, with the keystore's integrity digest rewritten; PKCS12 with `keytool` - the password from the **Keystore password** credential when it is attached, else `check_trust_keystore_password`, `changeit`; `keytool` reads it from its environment, never the command line). A `cacerts` that follows the system trust (`/etc/pki/java/cacerts`, `/etc/ssl/certs/java/`) is left to the blocklist. A running JVM keeps the old trust until it restarts: restart the Java services that use the keystore	copy the backup back

Store	What happens	Undo
Python `certifi`	the certificate's block (and its comment lines) is cut out of `cacert.pem`. One a package owns is left alone (update the package); one that holds nothing else is left alone (cut, requests would have no roots: `pip install -U certifi` there)	copy the backup back
an application's file	a bundle loses the block; a file that **is** the certificate (a DER or a single PEM) is moved to the backup folder	copy the backup back
vCenter, ESXi	`check_trust_remove: true` on the *VMware trust store report*: the chain is deleted from vCenter's trusted root store; each ESXi host's trusted CA list is replaced by the same list without it (its CRLs kept). The account needs *Certificate Management* > *Manage*	add the certificate again in vCenter
containers, Node, Go programs, NSS	nothing: pull or rebuild the image, update Node, rebuild the Go program, update `nss`. They stay in the report	

Every file changed is copied first to `check_trust_remove_backup_dir` (`/var/backups/site-automation/trust/<date-time>/`, the path with __ for `/`); the report's *Removed* table names the backup of each. Only certificates at `check_trust_remove_severities` go (critical and warning): *AAA Certificate Services* at notice is never touched unless you put `notice` there or raise its severity - and that one you decide on first, because much chains to it. `check_trust_remove_kinds` narrows it to, say, `[system]`.

A changed file is written as a new file next to it under a fresh name, with the old one's owner and mode, then renamed over it (`keytool` works on a copy in a private folder); it is written only when it is still the file that was read. A keystore or bundle that is a **symbolic link**, or whose folder another user can write (not only root and the file's owner; a sticky folder like `/tmp` is fine), is left alone and listed with why in *Not removed* - take the certificate out of it by hand.

YAML

```
check_trust_remove: true                  # the switch (Check mode first) - on either report
check_trust_remove_kinds: [system, java, python, file]
```

After a run, the hosts that still hold something (Node, a Go program, a container) still fail the job: the finding says what to update. A host where everything went passes.

Set it up

Field	Value
Job template	*Trust store report*, `playbooks/trust_report.yml` (the Linux hosts)
Credentials	`Linux ssh (sudo)`
Variables	`aap/extra_vars/trust_report.yml`; `report_email_to` as the other reports
Job template	*VMware - trust store report*, `playbooks/vmware_trust_report.yml` (vCenter and the ESXi hosts; `aap/extra_vars/vmware_trust_report.yml`)
Credentials	`VMware vCenter`
Job template	*Windows - trust store report*, `playbooks/win_trust_report.yml` (the Windows servers; `aap/extra_vars/win_trust_report.yml`); the check `trust` is in the Windows health check's weekly set too
Credentials	`Machine (Windows)`
Schedule	weekly with the health check's weekly set (it is in it), and on demand when a CA incident is announced: add the certificates to `check_trust_extra`, run the report

In a workflow: *Trust store report* > *ServiceNow tickets* (Run always), like the certificate report. The tickets are per finding, so one per host for the system trust, one per host for Python, and so on.

When the fixes land

An updated `ca-certificates` drops `emSign ECC Root CA - G3`; the extracted bundles, Java's `/etc/pki/java/cacerts` and p11-kit's view follow (`update-ca-trust` runs in the package's update). The report then shows the system rows green. The certifi, Node, Java (own `cacerts`), container and Go rows clear one by one as each is updated - the report is the checklist. `AAA Certificate Services` stays, at notice, until you decide.

27. STIG drift: has a server moved away from its checklist?

A server is STIG'd, reviewed and its checklist accepted in STIG Manager. Then a package update, a hand edit or another team's change quietly undoes a setting, and nobody knows until the next assessment. The **STIG drift report** finds that on the next scheduled run.

- Each Linux host is **scanned** against the DISA STIG with OpenSCAP: `oscap` and the SCAP Security Guide's STIG profile for its RHEL version (scap-security-guide 0.1.82: RHEL 9 **V2R9**, RHEL 10 **V1R2**, RHEL 8 too). Or with **Evaluate-STIG**, if your checklists come from it (below). The scan's report, results and summary are **kept on the host**.
- The result is **compared with the host's checklist in STIG Manager** - read-only: the job never writes to STIG Manager - and with the **host's earlier scans** (every rule that ever passed on it).
- What moved is a finding; the hosts with one fail, so a workflow can open tickets. The report is emailed (`report_email_to`) and published (`report_web_dest`) like every other report.

Windows servers have their own template, the **Windows STIG drift report**: Evaluate-STIG on each server, every STIG that applies, each checklist compared the same way (Windows servers). VMware has its own STIG tooling (the appliance).

To check only what STIG Manager has **Open or Not Reviewed** - after fixing hosts, or before updating the checklist - run the **STIG recheck** (below): only those rules, in minutes.

What it reports

	When	Finding
Drifted	the scan fails a rule that STIG Manager has as **Not a Finding** (or **Not Applicable**), and the rule **passed on this host in an earlier scan**	yes: CAT I **critical**, CAT II and III **warning** (`check_stig_severity`) - every run until the host is fixed or the review changes
New fail	the scan fails a rule that **passed in an earlier scan** (and STIG Manager does not have it Open, nor as Not a Finding - that is drift)	yes, the same severities
Disagree	the scan fails a rule STIG Manager has as **Not a Finding**, and it has **failed in every scan of the host** - nothing moved that the job saw	no: report only (`check_stig_disagree_severity`: `warning` or `critical` makes it a finding). Below: "When OpenSCAP and DISA's checks do not line up"
Fixed, still Open	the scan passes a rule STIG Manager still has **Open** - the checklist is behind	no: report only. Update the review (and close its POA&M item)
Left out	a rule in `check_stig_ignore_rules` fails	no: listed, so the list is seen
No review	the scan fails a rule STIG Manager has no review for	no: report only
By hand	a rule the checklist has a review of that the scan gives no result for (DISA's manual checks)	no: counted per host
Not compared	the host's asset was not found in STIG Manager, or matched two	`check_stig_stigman_missing_severity` (warning; or `none`)
Not scanned	no `oscap` or no STIG content on the host (Evaluate-STIG: not there, or no checklist of the host's RHEL STIG), or the scan failed	warning

The report, on the website (atlas) and in the email: the tiles, **Start here** - one card per **CAT I** rule that drifted or fails new (at most 6): the rule, its host, when it last passed, STIG Manager's review, and the command that checks it again on the host (`sudo oscap xccdf eval --profile ... --rule ...`, with a **Copy** button on the website); no CAT I moved, no Start here - then a table per kind above (CAT II and III there), each rule's CAT, the scan's result and STIG Manager's as chips with their icon (the drifted rule's **Fail** beside STIG Manager's **Not a Finding**), every host with its counts, and the hosts with nothing to report under *Healthy* with a check mark.

A rule is matched with STIG Manager by its **STIG rule ID** (`SV-257985`), whatever the revision (`SV-257985r1069364_rule` in the scan, `SV-257985r1045000_rule` in an older checklist): a new STIG release does not break the comparison. Only the reviews with a status in `check_stig_stigman_statuses` count as the checklist (saved, submitted, accepted - a rejected review does not); `[accepted]` is stricter.

All zeros on a host means the scan and the checklist agree: every rule that fails is Open in STIG Manager already (known, not a difference), and nothing that passed before fails now. The job shows only what moved or disagrees, not the host's known open findings.

The first scan of a host has nothing of its own to compare with: a rule STIG Manager has as Not a Finding that fails in it is listed under **Disagree**, not as drift - the job cannot tell whether it moved before that scan. From then on, a rule that passed and fails later is drift (with STIG Manager) or a new fail (without). The same goes for a host's first scan with another scanner (`check_stig_scanner`). With rules in Disagree and none drifted, the report's card says **No drift - but the scan and the checklist disagree** and how many (before 0.45.4 it said every host passes). To have them fail the job - the scan says Open, the checklist says Not a Finding - set `check_stig_disagree_severity: warning` (or `critical`) in `all.yml`.

When OpenSCAP and DISA's checks do not line up

OpenSCAP does not run DISA's checks: the SCAP Security Guide has its own (`sshd_disable_root_login`), each naming the DISA STIG rules it covers by their SV id. That is what the job compares by. Measured on scap-security-guide 0.1.82's STIG profile:

	RHEL 9 (V2R9)	RHEL 8 (V2R8)	RHEL 10 (V1R2)
SCAP checks in the profile	481	397	473
STIG rules they cover	440	366	434
Several SCAP checks for one STIG rule (the worst result counts)	17 rules	22 rules	15 rules
One SCAP check for several STIG rules (its result counts for each)	8 checks	9 checks	5 checks
SCAP checks that name no STIG rule (`enable_authselect`: listed as itself)	1	1	0

Where they still do not line up, and what the job does:

- **DISA's manual checks** (a document, a procedure, an approved list) have no SCAP check. The scan never gives them a result, so they are never compared: the every-host table counts them under **By hand** - the checklist's reviews the scan has nothing for.
- **OpenSCAP checks a rule another way than DISA's check text.** A reviewer marked it Not a Finding - the site meets it another approved way - and OpenSCAP fails it every scan. Such a rule never passed on the host, so it is listed under **Disagree**, report only, and not as drift. Look at each once: fix the host, set the review to Open, or - if OpenSCAP is wrong for your site - add it to `check_stig_ignore_rules`:

group_vars of those hosts, or all.yml

```
check_stig_ignore_rules:
  - V-257779                  # our banner is set by the login portal (review 2026-10-30)
  - RHEL-09-271010            # a STIG id works too, or the SCAP check's name:
                              # dconf_gnome_banner_enabled
```

A rule on that list is never a finding; when it fails it is listed under *Left out on purpose*, so the list is seen and can be cut when a newer scap-security-guide fixes the check. A tailoring file (`check_stig_tailoring`) is the other way: the scan then does not run the check at all.

- **The checklist is on an older STIG release** than the scan (the every-host table shows both, *V2R7* and *V2R9*): a rule new in the scan's release has no review - listed under *Fails STIG Manager has no review for*.
- **Before 0.44.0**, a SCAP check that covers several STIG rules gave a result to the last one only: 7 STIG rules of RHEL 9 (the GNOME ones) and 11 of RHEL 8 (FIPS crypto policy, faillock, empty passwords) were never compared. They are now.

Closer to the checklist: DISA's own SCAP benchmark

If your checklists were filled from SCC (SCAP Compliance Checker) or Evaluate-STIG, scanning with the same **DISA SCAP benchmark** brings the job's results closer to them: its rules are DISA's (their ids are the SV ids), with nothing to map. Get the RHEL SCAP 1.3 benchmark zip from cyber.mil, put its XML in your repository, list its profiles with `oscap info` and set:

YAML

```
check_stig_datastream_src: files/stig/<the benchmark's XML>     # copied to the host first
check_stig_profile: xccdf_mil.disa.stig_profile_MAC-1_Classified # a profile oscap info lists
```

DISA's benchmark may check fewer rules automatically than the SCAP Security Guide's profile (the rest count under *By hand*), and the report's STIG column then shows no release (it is read from the profile's title). Run it once as **Check** with a Limit of one host before you schedule it; the rules that passed before carry over (they are kept by SV id).

Evaluate-STIG instead of OpenSCAP

If your checklists in STIG Manager are filled by **Evaluate-STIG**, scan with it too: the job then compares DISA's own checks (and your answer files) with the checklist, so the *Disagree* rows that come from OpenSCAP checking a rule its own way go away. The rest of the job is the same: the comparison with STIG Manager, the host's earlier scans, the findings and the report.

all.yml, or the template's Variables

```
check_stig_scanner: evaluate_stig
check_stig_evaluate: /opt/Evaluate-STIG          # the folder it is in on your hosts (or the
                                                 # script's own path)
check_stig_evaluate_select: {"8": RHEL8, "9": RHEL9}   # optional: scan only the RHEL STIG
                                                       # (faster)
check_stig_evaluate_args: ["--AnswerKey", "SITE"]  # optional: your own arguments (answer key,
                                                   # scan type ...)
```

- The job runs `Evaluate-STIG_Bash.sh` (found in that folder or in its `Src/Evaluate-STIG`; `Evaluate-STIG.ps1` with `pwsh` if there is no Bash script) as root, with `--Output CKLB --OutputPath` a folder of its own that is deleted after. Your own Evaluate-STIG runs and their output are not touched, and nothing is sent to STIG Manager.
- It reads the checklist of the host's RHEL STIG (`check_stig_stigman_benchmarks`: `RHEL_9_STIG` ...); the other STIGs Evaluate-STIG scanned are left. **Not a Finding** is a pass, **Open** a fail, **Not Applicable** not applicable, **Not Reviewed** is counted *By hand*.
- `check_stig_evaluate_select` gives `--SelectSTIG` for each RHEL version: use the short names your Evaluate-STIG lists. Without it Evaluate-STIG scans every STIG that applies to the host, which takes longer.
- Evaluate-STIG already runs on its own schedule? `check_stig_evaluate_read: /opt/STIG_Compliance` reads the newest checklist (`.cklb` or `.ckl`) it wrote under that folder instead of running it. The job is then only as fresh as that checklist.
- On the report, the scan's column says *V2R10 (Evaluate-STIG)*. A **Start here** card shows what Evaluate-STIG found for the rule (its finding details) instead of an `oscap` command, and the rule's checklist is kept on the host (`<time>_results.cklb.gz`, which STIG Manager imports). The Disagree table's last column has the first line of what it found; **What Evaluate-STIG found - in full**, below the tables, has all of it for every drifted, new and disagree rule (up to 4,000 characters each). Evaluate-STIG's own header in it - *Evaluate-STIG 1.2607.0 (Scan-RHEL8_Checks) found this to be OPEN on ...*, its *ResultHash* and the `~~~~` and

`----` lines - is left out.

- **Switching scanners starts the history again.** The first run with the other scanner is not compared with the scans before it: each scanner checks rules its own way, and a rule one passed and the other fails is not drift. The every-host table says so for that run.
- **Its own schema check rejects a checklist** - it prints `'<host>_RHEL8_V2R7_<time>.cklb' : failed schema validation. Moving to /tmp/Evaluate-STIG/Bad_CKL` and leaves none in the results; a check of its that failed (`Scan-RHEL8_Checks (Get-V244531) : Failed`) can do that. The job then reads that checklist from where it was moved, and the every-host table says so, with the checks that failed and Evaluate-STIG's log: look there, and report it to Evaluate-STIG's team as its output asks. `check_stig_evaluate_rejected: false` lists the host as not scanned instead; `check_stig_evaluate_output: CKL` asks for the older XML checklist, if your version writes that one right.
- Evaluate-STIG needs PowerShell 7 (`pwsh`) on the host and takes longer than OpenSCAP: raise `check_stig_timeout` (1800 seconds) if a host needs more. The job never installs or updates Evaluate-STIG.

Answer files from a Windows share (Linux)

If your Evaluate-STIG answer files live on a Windows file share, the job can copy them to each Linux host before Evaluate-STIG runs. That way every scan uses the same, current answers. It applies to the STIG drift report and the STIG recheck. Windows servers are not touched: their own Evaluate-STIG run uses their answer files.

all.yml, or the template's Variables

```
check_stig_evaluate_answers: '\\fileserver.yourdomain.mil\stig\AnswerFiles'   # or a folder in
                                                                              # your repository:
                                                                              # files/stig/answers
```

Then attach a **Windows file share** credential (`aap/credential_types/windows_share.yml`) to the template. Its account needs only Read on the share and the folder; write the user name as `user@YOURDOMAIN.MIL`.

What happens on each run:

1. **The share is read once**, from the AAP side, over SMB (smbprotocol in the execution environment). Nothing is mounted, and nothing on the share is written. It takes the `.xml` files of that folder (`check_stig_evaluate_answers_patterns`), not its sub-folders.
2. **They are copied to each host**, into a root-only folder made for this run.
3. **Evaluate-STIG is given that folder** (`--AFPath`, `check_stig_evaluate_answers_arg`). The job first checks that your Evaluate-STIG has that option: run `Evaluate-STIG_Bash.sh --help` on a host to see its name, and set `check_stig_evaluate_answers_arg` if it is spelled otherwise.
4. **The folder is removed after the scan**, on the host and on the AAP side. Nothing is kept, and a Check run copies them just the same.
5. **The report says it**: `with 2 answer files from \\fileserver.yourdomain.mil\stig\AnswerFiles; 42 rules answered from them (answer key DEFAULT)`, in the every-host table and the job output.

Were they used? The job output says it at each step. Search it for `answer files`:

```
answer files: USED - read from \\fileserver.yourdomain.mil\stig\AnswerFiles, copied to each host
  for this run
2 answer file(s) from \\fileserver.yourdomain.mil\stig\AnswerFiles as svc_stig@YOURDOMAIN.MIL:
  RHEL_9_STIG.xml, Firefox.xml
RHEL_9_STIG.xml - 48211 bytes, changed 2026-10-30 14:05 UTC, SHA-256 9f2c...
web01.yoursite.mil: given 2 answer file(s) from \\fileserver.yourdomain.mil\stig\AnswerFiles; 42
  rules answered from them (answer key DEFAULT)
```

- `NOT USED - ...` says why: the scanner is OpenSCAP; `check_stig_evaluate_answers` is not set *in this run* (look at the job's Details, Variables - a value in `all.yml` needs the project synced after the edit); or `check_stig_evaluate_read` is set (the job reads the checklist Evaluate-STIG already wrote, and runs nothing).
- **The SHA-256** is the file's own: compare it with the file on the share (`Get-FileHash` in PowerShell) to see that the job read the current one.
- **Rules answered from them** are the rules whose checklist entry says an answer file answered them (Evaluate-STIG writes *Evaluate-STIG answer file for Key 'DEFAULT' ...* in the rule's comment). **None answered** is a warning for the host in the report: each answer file names the STIG it answers (`<STIGComments Name="...">`, as Evaluate-STIG's `--ListSupportedProducts` names it) and holds answer keys - `DEFAULT`, or one you give with `check_stig_evaluate_args: ["--AnswerKey", "SITE"]`. A file for another STIG, or another key, answers nothing here.

If the share cannot be read (it is down, the password is wrong, the folder is not there), Evaluate-STIG is **not run**. Each host is then listed as not scanned, with the reason and what to check. Scanning without the answers would mark Open everything they answer, and that would show as drift.

Setting	Default	
`check_stig_evaluate_answers`	empty: none copied	the share's folder (`\\server\share\folder`, `smb://server/share/folder`), or a folder on the AAP side
`check_stig_evaluate_answers_arg`	`--AFPath`	Evaluate-STIG's option for the answer files' folder
`check_stig_evaluate_answers_patterns`	`["*.xml"]`	the files taken (any case)
`check_stig_evaluate_answers_auth`	`negotiate`	Kerberos, else NTLM; a FIPS execution environment needs Kerberos: `user@YOURDOMAIN.MIL` and the server's full name
`check_stig_evaluate_answers_max_files`, `_max_mb`	500, 20	more files, or a larger one: not read (a wrong folder)

How much each scanner checks

Measured against DISA's releases of 30 Sep 2026:

	RHEL 9 V2R10	RHEL 10 V1R3
STIG rules	445 (29 CAT I)	435 (31 CAT I)
OpenSCAP, scap-security-guide 0.1.82	440	433

	RHEL 9 V2R10	RHEL 10 V1R3
DISA's SCAP benchmark	-	396 (V1R1)

The scap-security-guide 0.1.82 has no check for these rules, so OpenSCAP leaves them *By hand*:

- **RHEL 9:**
- SV-288833: DoW-approved encryption in the OpenSSL package (CAT I);
- SV-257782: the hardware random number generator;
- SV-257823: the system files' hashes;
- SV-258228: logon UIDs protected from change;
- SV-288832: auditing useradd.
- **RHEL 10:**
- SV-288827: OpenSSL (CAT I);
- SV-288828: useradd.

Evaluate-STIG checks what DISA's content lets it.

On the host

`check_stig_dir` (`/var/lib/site-automation/stig`, root-only):

```
20261024T184350Z_report.html       oscap's HTML report (open it in a browser: every rule, why it
  failed, the fix)
20261024T184350Z_results.xml.gz    the XCCDF results (STIG Manager and eMASS can import them);
  Evaluate-STIG: _results.cklb.gz, its checklist
20261024T184350Z_summary.json      one result per STIG rule, and every rule that passed on the
  host so far: what the next scan is compared with
latest-report.html, latest-summary.json
```

The last `check_stig_keep` (10) scans are kept. A dry run (Job type **Check**) scans and compares but keeps nothing. A scan takes from a few seconds to a few minutes and only reads; it runs as root (`become`).

STIG Manager: the login and finding each host's asset

The job logs in as a **Keycloak client** with the client credentials grant - your **autostig** client, or another one. Give it:

- the scope `stig-manager:collection:read` (or `stig-manager:collection`);
- a grant in each collection to read, for its service account user (`service-account-autostig`): **Full** sees every asset in the collection; **Restricted** sees only the assets and STIGs assigned to it, so a host whose asset it was not given is reported as not found. With only the read scope, the token cannot write whatever the grant.

In AAP, attach a **STIG Manager API** credential (`aap/credential_types/stigman_api.yml`: the token URL, the client ID, the secret) to the template, and set `check_stig_stigman_api`:

YAML

```
check_stig_stigman_api: https://stigman.example.mil/api
# from the command line instead of the credential (keep the secret in a vault):
# check_stig_stigman_token_url:
# https://keycloak.example.mil/realms/stigman/protocol/openid-connect/token
# check_stig_stigman_client_id: autostig
# check_stig_stigman_client_secret: "{{ vault_stigman_secret }}"
```

Only GET requests reach STIG Manager (and one POST to Keycloak for the token). Behind nginx with `ssl_verify_client optional` the API answers the token without a client certificate. A private CA: `check_stig_stigman_ca_path`.

The right asset in the right collection. Set each host's collection where your hosts are grouped - group_vars, host_vars, or the inventory's variables in AAP:

inventory group rhel_servers

```
check_stig_stigman_collection: RHEL Servers
```

The job then looks for the host's asset only there: an asset whose **name or FQDN** is the host's inventory name, then its short name (`web01` for `web01.example.mil`), case-blind, assigned the host's STIG (`check_stig_stigman_benchmarks`: `RHEL_9_STIG` for RHEL 9 ...). An asset named differently: `check_stig_stigman_asset: WEB01-PROD` for that host. Without a collection, every collection the client can read is searched (or only `check_stig_stigman_collections`); a host that matches assets in two of them is listed - *2 assets match: web01 in RHEL Servers, web01 in Lab* - and not compared until its collection is set.

The report's every-host table shows what was matched - *RHEL Servers / web01 (V2R7)*, the collection, the asset and the checklist's STIG revision - beside the scan's (*V2R9*).

Setting it up

1. On the hosts: `openscap-scanner` and `scap-security-guide`, from your RHEL repositories (Satellite). Or `check_stig_install: true` installs them on the first run. With Evaluate-STIG: it and `pwsh`.
2. In STIG Manager: the client and its grants (above).
3. In AAP: the job template (docs/SETUP_AAP.md, "STIG drift report"): `playbooks/stig_drift_report.yml`, the machine credential and the STIG Manager API credential; `aap/extra_vars/stig_drift_report.yml` has its settings.
4. Run it once as **Check** with a Limit of one host, then for real, then schedule it weekly - as workflow 33, with the tickets step after it (WORKFLOWS_AND_SCHEDULES.md)
   - and in the patching workflow after the patch job.

Windows servers

`playbooks/win_stig_drift_report.yml` (the **Windows STIG drift report** template) does the same on Windows, with Evaluate-STIG - there is no free SCAP content for Windows to run OpenSCAP with:

- **Evaluate-STIG runs on the server as SYSTEM**, in a one-time scheduled task the job deletes after (`win_check_stig_run_as: task`): outside the WinRM session's memory and time limits, with the rights Evaluate-STIG wants. It writes CKLB into a folder of the job's own (deleted after); **every STIG that applies** is scanned - Windows Server 2019, 2022 or 2025, Defender, Firewall, .NET, IIS, Edge, and so on - unless `win_check_stig_evaluate_select` names some (Evaluate-STIG's short names, `-SelectSTIG`).

- **Where it is**: `win_check_stig_evaluate` (its folder, e.g. `C:\Evaluate-STIG`). Empty, the job finds it: a scheduled task that runs `Evaluate-STIG.ps1` (its path, and where it writes), else a folder named `Evaluate-STIG*` on the local drives, four levels down (`C:\Users\admin\Desktop\Evaluate-STIG` is four). The report's **Every host** table and the job output say where it was found. Not found, the server is listed as not scanned, with where it looked and what to set.
- **A script the job found is run as SYSTEM only when nobody else can change it**: its folder, every file in it and the folders above it owned by and writable only by SYSTEM, the Administrators or TrustedInstaller (a scheduled task that runs as SYSTEM: its script is used as it is - only an administrator can make such a task). Otherwise the server is not scanned and the report says who else can change which file: make SYSTEM and the Administrators the folder's only owners and writers, or set `win_check_stig_evaluate` to it (a folder you name is run as it is). Found in **more than one place**, none is picked: set `win_check_stig_evaluate` to the one to run.
- **Or read what it already wrote**: `win_check_stig_evaluate_read: auto` reads the checklists your own Evaluate-STIG runs leave - the folder its scheduled task writes to (`-OutputPath`), else its default, `C:\Users\Public\Documents\STIG_Compliance` - or name a folder. Each STIG's newest checklist of this server is read (its own `<server>\Checklist` folder; never `Previous`, never another server's); the report says the checklist's date (*its checklist of 2026-10-29*). Drift is then as fresh as your runs.
- **Each checklist is a result of its own**: a STIG, or a STIG of one IIS web site or database instance. Its rows read *win01 - Microsoft Windows Server 2022*, its findings name it, and it is kept in its own folder on the server (below).
- **STIG Manager**: the server's asset (`check_stig_stigman_asset`, `check_stig_stigman_collection` - the same settings and credential as Linux) and each STIG of it. A **web site or database checklist** is the asset STIG Manager named when it imported it: `<server>-<site>-<instance>`, `NA` for none (*win01-Default Web Site-NA*). A STIG the asset **does not have** in STIG Manager (Evaluate-STIG scans more than a site may track) is listed - *not compared: the asset win01 (Windows Servers) does not have MS_Edge_STIG assigned* - and is **no finding**. The server's asset not there at all is one finding for the server, not one per STIG.
- Drift, new fails, disagree, fixed but Open, left out (`check_stig_ignore_rules`), the severities and the report are the Linux ones; the `check_stig_*` settings for STIG Manager and the findings apply to both.

On the server, `win_check_stig_dir` (`C:\ProgramData\site-automation\stig`, only SYSTEM and Administrators can open it; a folder that is there already is used only when SYSTEM, the Administrators or the job's own account alone own and can change it and everything in it - else the server is not scanned and the report says who else can), one folder per checklist:

```
Windows_Server_2022_STIG\20261030T120500Z_summary.json     one result per rule, and when each last
  passed
Windows_Server_2022_STIG\20261030T120500Z_checklist.cklb   Evaluate-STIG's checklist (STIG Manager
  imports it)
Windows_Server_2022_STIG\latest-summary.json
IIS_10-0_Site_STIG_Default_Web_Site\...
```

Setting it up: the **Machine (Windows)** credential (an administrator - the scheduled task runs as SYSTEM) and the **STIG Manager API** credential on the template (SETUP_AAP.md), `aap/extra_vars/win_stig_drift_report.yml`; run it once as **Check** with a Limit of one server (it runs Evaluate-STIG and compares, keeps nothing), then for real, then weekly. The Windows health check runs it when asked by name (`health_checks: [stig]`).

Setting	Default	
win_check_stig_evaluate	empty: found	Evaluate-STIG's folder on the server (or Evaluate-STIG.ps1)
win_check_stig_evaluate_read	empty: run it	auto, or a folder: read the checklists it already wrote
win_check_stig_evaluate_select, _exclude, _args	[]	-SelectSTIG, -ExcludeSTIG (short names), your own arguments (-ScanType, -AnswerKey)
win_check_stig_run_as	task	direct: in the job's WinRM session, as its user
win_check_stig_timeout	3600	seconds Evaluate-STIG may take (all STIGs: five to thirty minutes)
win_check_stig_search, _search_depth	the local drives, 4	where and how deep to look for it
win_check_stig_dir, win_check_stig_keep	C:\ProgramData\site-automation\stig, 10	where the scans are kept, and how many per checklist

The STIG recheck

playbooks/stig_recheck.yml (Linux) and playbooks/win_stig_recheck.yml (Windows) - the **STIG recheck** and **Windows STIG recheck** templates - answer "is what STIG Manager says is open still open?" without a full scan:

1. **STIG Manager is read first** (read-only): each host's rules it has **Open** (a review that counts, check_stig_stigman_statuses) or **Not Reviewed** (no review that counts - none, Not Reviewed, or one that was rejected). Linux: the host's RHEL STIG. Windows: every STIG of the server's asset **and of its web site and database assets** (<server>-<site>-<instance>, as STIG Manager names them when it imports a checklist). check_stig_recheck: [open] leaves the Not Reviewed out.
2. **Only those rules are checked on the host**: Evaluate-STIG with -SelectVuln and the rules' V-numbers (Linux and Windows), or oscap with a --rule for each of their SCAP checks. The scanner and its settings are the drift report's (check_stig_scanner, check_stig_evaluate*, win_check_stig_*). An Evaluate-STIG from before -SelectVuln runs in full - the same answers, a full scan's time - and the report says so (*checked: in full*); so does one that writes no checklist when given -SelectVuln (a version that wants -SelectSTIG with it): it runs once more, in full, and the report says what it printed the first time.
3. **Each rule is sorted**, and the report says what to do in STIG Manager:

	STIG Manager	The host now	Do
Fixed	Open	passes	set the review to Not a Finding (close its POA&M item)

	STIG Manager	The host now	Do
Not Applicable now	Open	Not Applicable	set it to Not Applicable
Answered	Not Reviewed	pass, fail or n/a	set it as the scan says (a fail is Open: fix it or put it on the POA&M)
Still open	Open	fails	nothing: the review is right
Manual review	Open or Not Reviewed	no answer (DISA's manual checks; a rule not in the scan's STIG revision)	a person reviews it
Held back	Open or Not Reviewed	an answer to **a rule that changed** since the scan's STIG (below)	update Evaluate-STIG (or carry forward, below)

The scan's STIG revision and STIG Manager's (since 0.67.0). Evaluate-STIG checks with the STIG content of its own release; STIG Manager with the revision your collection uses. When they differ - *V2R8 (Evaluate-STIG)* beside *… (V2R9)* in the *Every host* table:

- **A rule DISA added** in the newer revision (V-288829, say) is not in the older one at all: *Manual review*, "not in the scan's checklist".
- **A rule DISA changed** gets a new rule id (`SV-230223r1017xxx_rule`), and STIG Manager does **not** carry its review over to the new revision: it shows *no review* there, though the old revision still has the answer and comment. The recheck compares the rule's id in the scan with STIG Manager's: when they differ, the scan answered the old check, so its answer is **never written** - **Held back** (since 0.69.0 a tile, a section and an *Every host* column of their own; 0.67.0 counted them under Manual review), "the rule changed - the scan checked …, STIG Manager has …" (without the ids to compare, a rule of a scan of another revision is held back the same way). The *Every host* row is amber and says how many; the job's output has a *REVISION* line. They need a newer scan, not a person.
- **A rule that did not change** has the same id in both: written as before.
- *STIG Manager* says the earlier revision's review beside *no review*: *no review in V2R9 - V2R8: Not a Finding (accepted)*.

The fix is on the host: **update Evaluate-STIG** (`check_stig_evaluate`) to a release with the revision STIG Manager uses (and add answers for its new manual rules to your answer files), then run the recheck again.

Until then: carry forward (since 0.69.0, off by default). With `check_stig_recheck_carry_forward: true`, a held-back rule that STIG Manager has **no review** of in its revision is written after all when the review of the rule's earlier revision **counts** (`check_stig_stigman_statuses`) and **says what the scan says** - Not a Finding and the scan passes, or Not Applicable and the scan says n/a. It goes through the approval like the rest, in a section of its own (*4. Carried forward from an earlier revision*), to the rule of STIG Manager's revision, with the comment *Carried forward by the STIG recheck (site-automation), approved in AAP: Not a Finding (accepted) in V2R8, and Evaluate-STIG on web01 on … checked it against V2R8 - not against V2R9*. A fail is never carried, nor an Open rule, nor an earlier review that does not count or says something else. Be clear what it means for an audit: the new revision's check was not run - the comment says so on every review it writes. Turn it off again once Evaluate-STIG is updated.

It is **report only**: what it finds is no finding, and the job does not fail for it - a host it could not recheck (the asset not in STIG Manager, Evaluate-STIG not found) is a warning. Its report never says *no findings* over open rules. Its title says what is open and what to update - *STIG recheck: 2 rules open (CAT I: 1), 5 status*


updates in STIG Manager, 1 for manual review. Its tiles (since 0.67.0): **Open findings** (they fail on the host now: fix them, or put them on the POA&M), **Status updates** (only STIG Manager's reviews change - the hosts pass, no longer apply, or were answered; nothing to fix for them, except a fail answered, which is an open finding too), **Manual review** (no automatic check), **Held back: scan's STIG older** (since 0.69.0, when there are any: update Evaluate-STIG) and **Not rechecked**. Its status is red when a CAT I rule is open, amber when another rule is open, and blue when there is only something to update. The job's output says *REPORT ONLY*, never *HEALTHY*. It **leaves the drift report's history alone**: nothing is compared with the earlier scans or kept with them. The checklist it wrote (Evaluate-STIG) or oscap's results are kept on the host as `check_stig_dir/recheck/latest-checklist.cklb` (`latest-results.xml`), on Windows `win_check_stig_dir\recheck\<checklist>.cklb`: STIG Manager can import it - every rule not rechecked is Not Reviewed in it, so look at your collection's import options before you do. This job never writes to STIG Manager; workflow 37 does, after an approval.

Then the **STIG drift report** checks every rule, as before, on its schedule: the recheck is for the rules you are working on, the drift report for everything.

Setting it up: two templates like the drift reports, with the same credentials (SETUP_AAP.md) and `aap/extra_vars/stig_recheck.yml`, `win_stig_recheck.yml`; `check_stig_stigman_api` is required (what to recheck comes from it). Run it on demand, or as the step after a patch or fix job in a workflow. **Check** mode checks and sorts, and keeps nothing on the hosts.

Updating STIG Manager, with an approval

Workflow 37 (WORKFLOWS_AND_SCHEDULES.md) does the recheck's "update the review" for you, once a person approves it:



1. **The check** is the STIG recheck with `check_stig_update_workflow: true`. Its report starts with **Approve writes these reviews to STIG Manager**: each review, as STIG Manager has it now and as it will be written. It hands that list on to the next steps and fails on purpose (`NEEDS APPROVAL`). With nothing to write it stays green, and no approval is asked for.
2. **The approval**: open the check's report, then Approve or Deny.
3. **STIG Manager - update** (`playbooks/stigman_update.yml`) writes those reviews - and creates the new assets listed, with `check_stig_update_create_assets` (below) - and nothing else.

What it writes (`check_stig_update`):

The recheck found	Written as	Detail	Comment
Fixed: Open, passes now	Not a Finding	what the scan found	the review's own, kept
Not Applicable now: Open	Not Applicable	what the scan found	the review's own, kept
Answered: Not Reviewed, the scan passes it	Not a Finding	what the scan found	the review's own, kept (or the job's line if it has none)
Answered: Not Reviewed, the scan fails it	Open	what the scan found	the job's line: *Set by the STIG recheck (site-automation), approved in AAP: ...*

- **Never written:** Still open, Manual review, Held back (an answer to a rule that changed since the scan's STIG revision - above; unless carried forward), the rules in `check_stig_ignore_rules`, and **a review with attachments** in STIG Manager (below).
- **Status:** each review is written with the status `check_stig_update_status`. The default is `submitted`, which leaves Accept to your reviewers in STIG Manager. `accepted` works only if the collection allows Accept and the client's grant is Manage or higher.
- **Result engine:** set to the scanner, OpenSCAP or Evaluate-STIG, as STIG Manager shows it for an imported scan.
- **History:** STIG Manager keeps each review's history, so the earlier review stays there.

How the update keeps your STIG Manager safe:

- **Only the approved reviews.** Its only requests to STIG Manager are a GET of each review and one POST of an asset's reviews (`/collections/{id}/reviews/{asset}`) - and, for an approved new asset (below), a GET of the collection's assets and one `POST /assets`. It never changes a collection, user, grant or STIG, nor an asset that is there.
- **Only if nothing changed since.** Each review is read again first. If a person changed it after the check read it, it is left as it is, and the report says so (*changed since*).
- **Never a review with attachments.** When a person attached evidence to a review in STIG Manager (the paper clip in the review panel: a screenshot, a POA&M document), that review is left as it is - the evidence stays with the result it was attached for. STIG Manager keeps the attachments in the review's metadata (the key `artifacts`); the job reads only that key's list (`GET .../reviews/{asset}/{rule}/metadata/keys`), never the files. Twice:
- **the check** leaves those reviews out of what it hands to the approval, and its report lists them under *Left as they are: reviews with attachments*, with the files' names - to review by hand if the scan's result is right;
- **the update** reads each review's attachments again just before writing, so one attached between the check and the approval is left too (*has attachments*).

A review whose attachments cannot be read is left out as well. `check_stig_update_skip_attachments: false` writes them like the others. This is about attachments only: answer files change what Evaluate-STIG reports, not what is attached in STIG Manager.

- **Read back.** Each review is read again after it is written. If STIG Manager refused one (the collection requires a field, a grant is missing), the report says why and the job fails.
- **Check mode** (Job type **Check** on the update template) reads everything and writes nothing. It says what it would write.

- **Run twice**, it writes nothing the second time (*already so*).

A host with no asset in STIG Manager (0.72.0)

Off by default. With `check_stig_update_create_assets: true` on workflow 37's check, and the host's collection set (`check_stig_stigman_collection` - one setting in `all.yml` when every host is in one collection, or per group or host), a Linux host that has no asset in its collection gets one, behind the same approval:

1. **The check** looks for the host's asset as always (by `check_stig_stigman_asset`, else the inventory name and its short name, by name or FQDN). Not in its collection:
   - an asset of the host's **in another collection** the client can read: **not created** - the host is listed as not rechecked (*... but web01 is in Lab: not created*); set its collection;
   - **nowhere**: the host is scanned **in full** (every rule of the STIG, at the collection's revision of it - or the newest STIG Manager has), and its report has **New in STIG Manager**: one row per host - the asset's name, FQDN, collection and STIG, and how many rules pass, fail, do not apply or need a person - and the rules it fails. **Approve** lists *NEW ASSET web01 (web01.example.mil) in RHEL Servers with RHEL_9_STIG V2R8 - then 312 review(s) ...*.
2. **STIG Manager - update**, after the approval: the collection's assets are read again - an asset of the host's made since the check is **left** (*there since the check*), nothing is written to it and the job fails (1.24.0); run the recheck again. One made by an earlier run of the same approved plan (its name in the plan's collection, the description the job gives it - a run that then failed) is used: its reviews are read again and written as below. Else the asset is created (`POST /assets`: the name, the FQDN, the STIG) and the scan's answers written as its reviews (Not a Finding, Open - with the job's comment - and Not Applicable; the status `check_stig_update_status`), then read back. Manual checks, held back and left out stay Not Reviewed.

Its name: `check_stig_stigman_asset` when set, else the short name (`web01`); the FQDN is the inventory name when it has a dot. Look at the name in the report before you approve - the next recheck finds the asset by it.

The grant: creating an asset needs **Manage** in the collection - *Full* is refused (`HTTP 403`, proven on STIG Manager 1.6.17). Give the update's client Manage in the collection where the assets go. The reports' read-only client needs **Full** there (not Restricted): with Restricted it does not see the assets that are not assigned to it, and would plan them again - the update then finds them and leaves them.

The client that writes. The update gets its own *STIG Manager API* credential:

- The reports keep their read-only client.
- Ask your Keycloak realm owner for a client with the client-credentials grant and the scope `stig-manager:collection`.
- In STIG Manager, give its service account a grant in each collection: **Restricted** with the assets it may write, or **Full**. **Manage** is needed for `accepted`, and to create assets (`check_stig_update_create_assets`).
- In AAP, create a *STIG Manager API* credential with that client, and attach it to *STIG Manager - update* only.

Tested end to end against STIG Manager 1.6.17 with its demo Keycloak (`tests/stig/run_stigman_real_test.sh`; since 0.72.0 also a new asset - not created when it is in another collection, created once, Full refused): a collection that requires a detail always and a comment for findings, Accept for Manage, Open reviews with POA&M comments.

Checklists from files (0.75.0)

Checklists you have as files - VMware's InSpec checklists, which STIG Manager's own import rejects (their STIG id is the profile's name), Evaluate-STIG's, a person's - go through the same approval and the same update: workflow 40, CKL_IMPORT.md.

Settings

Every one is in `roles/check_stig/defaults/main.yml` and docs/VARIABLES_REFERENCE.md. The ones you are most likely to set:

Setting	Default	
`check_stig_stigman_api`	empty	STIG Manager's API; empty = compared with the host's earlier scans only
`check_stig_stigman_collection`	empty	the host's collection (per group or host)
`check_stig_stigman_asset`	the inventory name	the host's asset name, when it differs
`check_stig_scanner`	`openscap`	`evaluate_stig`: scan with Evaluate-STIG (above)
`check_stig_evaluate`	empty	Evaluate-STIG's folder on the host (or its script)
`check_stig_evaluate_select`, `_args`, `_read`	`{}`, `[]`, empty	`--SelectSTIG` per RHEL version; your own arguments; read its own checklists instead of running it
`check_stig_evaluate_answers`	empty	Linux: Evaluate-STIG's answer files from a Windows share (or a folder here), copied to each host for the run (above)
`check_stig_evaluate_rejected`, `_output`	`true`, `CKLB`	read a checklist its own schema check rejected; CKLB or CKL
`check_stig_profile`	`stig`	`stig_gui` for a host with a desktop, or a full profile id
`check_stig_tailoring` / `_src`	empty	your site's tailoring file (on the host / in your repository)
`check_stig_datastream` / `_src`	the host's SSG	another datastream - newer content, or a DISA SCAP benchmark
`check_stig_severity`	CAT I critical, II and III warning	the finding's severity by CAT
`check_stig_disagree_severity`	`none`	a rule STIG Manager has as Not a Finding that never passed on the host: `none` = report only, or `warning` / `critical`

Setting	Default	
`check_stig_ignore_rules`	`[]`	rules OpenSCAP gets wrong at your site (SV-, V-, STIG id or SCAP check name): never a finding, listed as left out
`check_stig_stigman_statuses`	saved, submitted, accepted	the reviews that count as the checklist
`check_stig_dir`, `check_stig_keep`	`/var/lib/site-automation/stig`, 10	where the scans are kept, and how many
`check_stig_recheck`	`[open, not_reviewed]`	the STIG recheck: what STIG Manager has for a rule it checks again
`check_stig_update_workflow`	`false`	`true` on workflow 37's check: what to write, handed on, `NEEDS APPROVAL`
`check_stig_update`, `check_stig_update_status`	`[fixed, now_na, answered]`, `submitted`	workflow 37: what is written, and with which status
`check_stig_update_create_assets`	`false`	workflow 37: a host with no asset gets one in `check_stig_stigman_collection`, once approved (the client needs Manage)

Updating Evaluate-STIG

The STIG jobs never install or update Evaluate-STIG. *Evaluate-STIG - update* (`playbooks/evaluate_stig_update.yml`) does, on the RHEL hosts, from the zip you keep in your own repository - only where it is newer: EVALUATE_STIG_UPDATE.md. After it, the recheck's *STIG (scan)* column should match STIG Manager's revision and *Held back* drop to about 0; `check_stig_recheck_carry_forward` can then be off again.

Not in this version

- The drift report and the recheck never write to STIG Manager. Workflow 37 writes the recheck's reviews after an approval (and creates a Linux host's missing asset, with `check_stig_update_create_assets`). Drift (a rule that passed and fails now) is not written yet. To import a whole scan, the results file is on the host.
- A Windows server with no asset is not created yet (its web site and database assets would be too): it is listed as not rechecked. Nor is a STIG assigned to an asset that is there without it (*does not have RHEL_9_STIG assigned*).
- Linux scans one STIG per host (its RHEL STIG); Windows every STIG Evaluate-STIG finds. The other STIGs Evaluate-STIG writes on Linux (Firefox, ...) are not compared yet.
- No remediation. A drifted rule's fix is in the HTML report; fixing it automatically, behind an approval, is a possible later step.
- In no health check shortcut (daily, weekly, all): a scan takes minutes. The health check runs it when asked by name (`health_checks: [stig]`); its own template is the usual way.

28. Network performance: is the network slow, and where?

"The network is slow" is hard to act on. The **Network performance report** measures it from where it matters - each server - to what that server depends on, and compares it with the server's own usual:

- **latency, jitter and loss** to each target (ping), and the time to open a target's port (a timed TCP connect) - from every Linux host of the job;
- the **OCSP responders**, asked a real question from each host: smart card logins and certificate checks fail when they do not answer;
- each host's **interfaces**: packets dropped and errors since the last run, per hour;
- the **trend**: each path against the median of the host's last runs (kept on the host), so "3 ms, usually 1 ms" stands out even below the thresholds;
- **throughput** with iperf3, only between the pairs you name, one at a time, for a few seconds.

Read-only, but for the few files of each host's own history (`net_perf_dir`). The hosts with a finding fail (`site_fail_on`), so a workflow can open tickets; the report is emailed and published like every other report.

What it reports

Finding	Severity	When
`netperf:loss:<target>`	warning / critical	packet loss from `net_perf_loss_warn_pct` (1 %) / `net_perf_loss_crit_pct` (10 %); 100 % = the target does not answer
`netperf:rtt:<target>`	warning / critical	the average round trip from `net_perf_rtt_warn_ms` (50) / `net_perf_rtt_crit_ms` (200)
`netperf:tcp:<target>`	critical / warning	the target's port refuses every connect / some of them
`netperf:slower:<target>`	warning	`net_perf_slower_factor` (2x) the host's usual, and at least `net_perf_slower_min_ms` (5) more
`netperf:drops:<interface>`	warning	dropped packets (in + out) from `net_perf_drops_warn_per_hour` (100), or errors from `net_perf_errors_warn_per_hour` (10), per hour since the last run
`netperf:ocsp:<name>`	`net_perf_ocsp_severity` (critical)	the responder does not answer, answers not successful, says the test certificate is not good, or its answer is stale
`netperf:ocsp-slow:<name>`	warning	it answers, slower than `net_perf_ocsp_warn_ms` (2000)
`netperf:iperf:<server>`	warning	on the client of a pair: below the pair's `min_mbps`, or the test did not run

A target far away can have thresholds of its own: `{name: Remote site, host: ..., rtt_warn_ms: 300}`. An interface's first run (or after a reboot: its counters start over) is counted from then on.

Set it up

1. **The targets** - in `all.yml` for every host, more per group in its group_vars (`net_perf_targets_extra`):

```yaml
net_perf_targets:
  - {name: Gateway, host: 192.0.2.1}
  - {name: DC01, host: dc01.example.mil, port: 389}
  - {name: STIG Manager, host: stigman.example.mil, port: 443}
```

2. **The OCSP responders** (optional). Put a certificate the responder knows - any user's, from a smart card or the PKI's site - in your repository as a PEM file (it is not a secret), and name it once in `all.yml`; the VMware health report uses the same setting:

```yaml
site_ocsp_certs: [files/ocsp/test-user.pem]     # playbooks/files/ocsp/test-user.pem
```

The responder's address and the certificate of the CA that issued it are read from the certificate itself (its *Authority Information Access*: every DoD certificate names its OCSP responder and where its CA's certificate is). The CA's certificate is downloaded on the AAP side; when the AAP node cannot reach that address, put the CA's certificate after the user's in the same file (or give it as `issuer`). Commit the files (since 0.31.1 the repository's `.gitignore` lets `playbooks/files/ocsp/` through; before, `git add -f`), push, and sync the project. Each host then sends a real OCSP request - made once on the AAP side - and the answer is read there. `net_perf_ocsp`, when set, is used instead - to name a responder, give its address, or ask a second one:

```yaml
net_perf_ocsp:
  - {name: DISA OCSP, cert: files/ocsp/test-user.pem}           # the address and issuer from the
                                                                # certificate
  - {name: OCSP 2, url: "http://ocsp2.example.mil", cert: files/ocsp/test-user.pem, issuer:
    files/ocsp/issuing-ca.pem}
```

With a `url` only, each host sends it an OCSP request about a made-up certificate: any OCSP response ("unauthorized", usually) is the responder up; no answer, an HTTP error or an answer that is not OCSP is the problem.

3. **iperf3** (optional): `iperf3` installed on both hosts of a pair, TCP port 5201 open on the server. Both hosts must be in the job. One pair at a time: the server is started for that pair's test only (as the login user, not root), answers one test, and is stopped after the client's step - also when the client never connected; it also stops by itself 60 seconds after the test time. Pairs may share a server.

```yaml
net_perf_iperf_pairs:
  - {server: app01.example.mil, client: db01.example.mil, min_mbps: 900}
```

4. **The template** (docs/SETUP_AAP.md, "Network performance report"): `playbooks/net_perf_report.yml`, the machine credential, `target:` the group to measure from. Run it as **Check** first (it measures and keeps nothing), then schedule it - hourly gives the trend something to compare with. With tickets:

workflow 34 (WORKFLOWS_AND_SCHEDULES.md).

On the host

`net_perf_dir` (`/var/lib/site-automation/netperf`, root-only): `history.jsonl` (each run's average round trip and loss per target; the last `net_perf_keep`, 30) and `counters.json` (the interfaces' counters at the last run).

The hosts' and VMs' drops seen by vCenter

The drops counted here are the Linux guest's own. What the ESXi hosts' physical NICs and every VM's virtual NIC dropped - Windows VMs too - is in the daily **VM - health report**, section *Network drops and errors*, from vCenter's own counters: VMWARE.md.

Not in this version

- Paths between two hosts other than iperf3 pairs and the targets: add the other host as a target.

29. Network device configurations: backup and load

Two jobs for **Cisco IOS / IOS-XE** and **Palo Alto Networks PAN-OS** devices:

Template	Playbook	Does
Network config backup	`playbooks/net_config_backup.yml`	every device's running configuration, kept in a **private git repository** (one commit when any changed - its history is the record of every change) and / or on a **file share** (the latest and dated copies). The report shows what changed, with the diff; optionally a ServiceNow incident for each change. Read-only on the devices
Network config load	`playbooks/net_config_load.yml`	**lines** sent to the devices (IOS configuration lines; PAN-OS changes at an xpath), or a device **restored** to a backup - after an approved change request. Try it in **Check** first: what would change, nothing sent. A real run first keeps each device's running configuration, to undo it

The backups hold the devices' secrets - password hashes, SNMP communities, VPN and API keys - so that a restore puts back exactly what was there. Keep them in a **private, internal** repository or share that only the devices' admins can read - never in this (public) repository. What the jobs *show* - the report, the email, an incident, the note on a change - has the secret values replaced by `<hidden>`; the job output never shows a configuration (every task that has one runs with `no_log`).

What is hidden on a shown line (1.41.0):

- **IOS**: all that follows `password`, `secret`, any `xxx-password` (`area-password`, `domain-password`), `key`, `key-string`, `pre-shared-key`, `authentication-key` and `md5`. A `level N` and the encryption type digit stay.
- **IOS HSRP, VRRP, GLBP**: the text after `authentication` (and `authentication text`). A `md5 key-chain` keeps the chain's name.
- **IOS SNMP**: the `snmp-server community` string, also on a `no snmp-server` line, and the community of `snmp mib community-map` and `snmp-server community-map` (1.44.0). Everything after the address of an `snmp-server host` is hidden, and everything after `v3` (or NX-OS `auth`, after any group words) of an `snmp-server user`. Contact and location lines stay readable.
- **Kept as written**: `description` lines, banners, and the number of a key chain's `key 1`.
- **PAN-OS**: the text of every element named for a password, key or secret (`phash`, `password`, `authpwd`, `auth-key`, `shared-key`, `private-key`, `community`, any tag ending in `community-string` and the like), attributes or not. A body over several lines is hidden line by line.

Which devices

An inventory group, `net_config_devices` (`net_config_group`), in the template's inventory:

```yaml
net_config_devices:
  hosts:
    rtr01.example.mil:
      ansible_network_os: cisco.ios.ios
      ansible_connection: ansible.netcommon.network_cli
    sw01.example.mil: {ansible_host: 192.0.2.21, ansible_network_os: cisco.ios.ios,
      ansible_connection: ansible.netcommon.network_cli}
    fw01.example.mil: {ansible_network_os: paloaltonetworks.panos}
```

- **Cisco IOS / IOS-XE**: over its CLI (network_cli, SSH), logged in with the template's **Machine** credential (the user needs privilege 15 - or `ansible_become: true`, `ansible_become_method: enable` and the enable password in the Machine credential). The backup runs `show running-config` (`net_config_ios_command`).
- **Palo Alto PAN-OS**: over its **XML API**, from the controller (HTTPS, port 443: `net_config_panos_port`), with the **Palo Alto PAN-OS API** credential (`aap/credential_types/panos_api.yml`): an API key, or a username and password. The firewall's certificate is checked (`net_config_panos_validate_certs`, `net_config_panos_ca_path` for your CA). The backup is the running configuration as *Export named configuration snapshot* gives it. No collection is needed - the job's own module talks to the API.
- The platform comes from `ansible_network_os`, or set `net_config_platform: ios` / `panos` on the host. `net_config_address` connects to another address than `ansible_host` (PAN-OS).
- `net_config_only: ['rtr-lab*']` limits a run to some devices - to try a job on one first.
- The template's **Limit** works too, with `localhost` in it (`rtr-lab01,localhost`): the job keeps and reports its work on localhost. A Limit without it is refused before anything runs.

The backup

git (`net_config_store: git`, the default) - set `net_config_git_repo` to the repository (`ssh://git@git.example.mil/netops/configs.git`, or `https://...`), with the **Network config git repository** credential (`aap/credential_types/net_config_git.yml`): an SSH **deploy key with write access**, or for https a username and an access token. Each run clones `net_config_git_branch` (`main`; made when the repository is new and empty), compares each device with its file - `configs/<device>.cfg` (IOS) or `.xml` (PAN-OS) in `net_config_git_path` - and commits the new and changed ones in **one commit** ("Backup 2026-10-21 06:00 UTC: 2 changed (rtr01..., fw01...)"), then pushes. Nothing changed: no commit. The git server's SSH host key is learned on the first connection (`net_config_git_host_key_checking: accept-new`), or give it (`net_config_git_known_hosts`, `net_config_git_host_key_checking: yes`). In an execution environment ssh's own `known_hosts` starts empty every job, so `accept-new` learns the key every time and checks nothing: give the key (`ssh-keyscan -t ed25519 git.example.mil`, compared with what the git server's admin says) with `yes` - the only real check. An https token goes to git as a header in a git config file in the job's work folder (mode 0600, deleted at the end), never on a command line or in the environment. `git log -p configs/rtr01.example.mil.cfg` is then every change of rtr01, with its date.

A file share (`net_config_store: share`, or `both`) - `net_config_share_dir` on the AAP node (only kept if AAP exposes that path to jobs) or on `net_config_share_host` (a Linux host, or a Windows file server; its credential on the template): a folder per device with the latest (`rtr01.example.mil.cfg`) and, each time it changed, a dated copy (`rtr01.example.mil-20261021T060000Z.cfg`); the oldest beyond `net_config_share_keep` (30) go. With `both`, the report and the incidents compare with git.

IOS prints lines that change on every read although nothing changed (*Current configuration : N bytes*, *Last configuration change at ...*, `ntp clock-period`): they are left out, so an untouched router is never "changed".

ServiceNow (`net_config_tickets: true`, the **ServiceNow API** credential, `servicenow_assignment_group`): an incident (warning) when a device's configuration changed - one per change, with the diff (secrets hidden), "if the change was not planned (no change request), find out who made it" - and one when a device could not be backed up. The next good backup notes them as cleared (`servicenow_resolve_cleared: true` resolves them). `net_config_ticket_changes` / `net_config_ticket_failures` switch either off.

A device that could not be backed up (unreachable, the login, the API) is listed under *Not backed up* with the reason; its last good backup stays as it was, and the job fails (red) so the schedule shows it (`net_config_fail_on_failed: false` keeps it green).

The load

Always run it in **Check** first: it reads each device and shows what would change - the lines it would send, or the restore's diff - and sends nothing. A Check needs no change request.

The job itself does not check that a Check ran first: to make it a rule, launch the load through the workflow below (Check, an approval, then Run).

Before the change. A real run (not Check) first reads each device's running configuration and keeps it where the backup keeps them (`net_config_store`), named `<time>-before-<change>` - e.g. `20261111T140500Z-before-CHG0012345`: in git a tag on the commit that holds it, on the share a dated copy `<device>-20261111T140500Z-before-CHG0012345.cfg`. The report, the work note and the job's artifacts (`net_config_load.before`) give the name. To undo the load: `net_config_load_mode: restore` with `net_config_restore_ref` set to that name. A device whose copy could not be kept (the repository or the share not reachable, the device not read) gets nothing sent and counts as failed. `net_config_keep_before: false` loads without that copy (as before 1.22.0) - then the last backup is the only way back.

A real run needs the **change request** it belongs to - `net_config_change: CHG0012345`, in state **Implement** (`net_config_change_states`) - and the **ServiceNow API** credential: the job reads the change first and stops when it is in another state, and afterwards writes a work note on it (`net_config_change_note`): each device, what was sent or restored, the result. At most `net_config_max_devices` (10) devices at once - narrow it with `net_config_only` or the template's Limit.

Lines (`net_config_load_mode: lines`):

YAML

```
net_config_change: CHG0012345
net_config_only: [rtr-lab01*, fw-lab01*]
# IOS: configuration lines, as typed in configuration mode - only the ones not there yet are sent
net_config_lines:
  - ntp server 192.0.2.123
  - logging host 192.0.2.50
net_config_parents: []          # e.g. ["interface GigabitEthernet1"] for lines under one
# PAN-OS: changes at an xpath - set (adds or replaces the element's children), edit (replaces it),
# delete
net_config_panos_entries:
  - xpath: "/config/devices/entry[@name='localhost.localdomain']/deviceconfig/system"
    element: "<login-banner>Authorized use only</login-banner>"
```

- IOS: then `write memory` (`net_config_save: false` leaves only the running configuration - a reload undoes it).
- PAN-OS: the changes go into the candidate configuration, are **validated**, then **committed** (the commit's description: the change number and the AAP job). A change that does not validate is reverted - nothing

is committed. The firewall must have **no uncommitted changes** first: someone's half-done work in the web interface would be committed with ours - the job refuses (`net_config_panos_allow_pending: true` overrides).

A restore (`net_config_load_mode: restore`): each device put back to its backup - git: the newest, or `net_config_restore_ref` (a commit, tag or branch: `git log configs/rtr01.example.mil.cfg` shows which); share: the latest, or a dated copy (`net_config_restore_ref: 20261021T060000Z`).

- IOS: the backup is copied to the device's flash by **SCP** (`net_config_ios_file`, `flash:site-automation-restore.cfg`; the device needs `ip scp server enable`, and the user privilege 15), then `configure replace flash:site-automation-restore.cfg force` - IOS works out the difference itself and leaves what is the same untouched; the copy is deleted, the result read back, then `write memory`. On IOS-XE the file system may be `bootflash:` - set `net_config_ios_file`.
- PAN-OS: the backup is imported as a named configuration, loaded as the candidate, validated and committed.
- A device already as its backup: unchanged, nothing sent.

Templates


Field	Backup	Load
Inventory	the one with `net_config_devices`	the same
Execution environment	the all-in-one EE (`cisco.ios`, `ansible.netcommon`)	the same (with `scp` for IOS restores)
Credentials	Machine (the Cisco devices), Palo Alto PAN-OS API, Network config git repository; ServiceNow API with `net_config_tickets`	Machine, Palo Alto PAN-OS API, ServiceNow API; Network config git repository for a restore from git
Variables	`net_config_git_repo` (or `net_config_store: share` and `net_config_share_dir`), `report_email_to`	`net_config_git_repo`; `net_config_change`, the lines or the restore at launch (a survey, or the API's `extra_vars`)
Limit	empty	empty, or the devices (with `net_config_only`)
Job type	Run	**Check** first, then Run

The Variables of each: `aap/extra_vars/net_config_backup.yml`, `net_config_load.yml`.

A schedule (daily): *Network config backup*.

A load, with an approval

The approver sees the dry run's report - exactly what will be sent - before anything is.



1. On the template *Network config load*, tick **Prompt on launch** for **Job type**.
2. **Create workflow job template** `Network config load (workflow)`. Tick **Prompt on launch** for its **Variables**: each launch, paste the change there - every step gets the workflow's Variables:

```yaml
net_config_change: CHG0012345
net_config_load_mode: lines
net_config_only: [rtr-lab01*]
net_config_lines:
  - ntp server 192.0.2.123
```

(A survey cannot carry the lines: they are a list.)

3. **Add step** *Network config load*, Job type **Check**. On it, **+** › **Run on success** › **Approval**: name `Send these changes?`, timeout e.g. 4 hours, description `Open the Check job: its report lists each device and the lines or the diff.`
4. On the approval, **+** › **Run on success** › *Network config load*, Job type **Run**. **Save**.

The Check step needs no change request in state Implement; the Run step does, and stops if the change moved on meanwhile.

Troubleshooting

You see	Means / do
`which platform? Set ansible_network_os ...`	the host has no `ansible_network_os` (or `net_config_platform`): `cisco.ios.ios` or `paloaltonetworks.panos`
`Could not clone ...`	the git credential (the deploy key on the server, with write access; or the username and token), the URL, the server's host key (`net_config_git_known_hosts`)
`Unable to connect to port 22` / `command timeout`	the AAP node cannot reach the device's SSH, or the login is slow: the Machine credential, `ansible_command_timeout`
PAN-OS `Invalid Credential` / `HTTP 403`	the API key or the user (its admin role must allow the XML API: export for the backup, configuration and commit for the load)
`the firewall has uncommitted changes`	someone's changes wait in the candidate: commit or revert them first (the web interface: *Commit* / *Revert Changes*)
`validation failed - nothing committed, the candidate reverted`	the change refers to something that is not there (a zone, an object): fix the entries
`entry 2 of 3 (set /config/...): ... - nothing committed, the candidate reverted`	the firewall refused that entry (a wrong xpath or element); the entries before it were taken back too: fix that entry
`the copy to the device failed (scp ...)`	`ip scp server enable` on the device, the user's privilege 15, the file system (`net_config_ios_file`)
`configure replace failed`	IOS refused the backup (a command this release does not know - a backup from another model or release?); nothing was replaced
`still different: N line(s)` after a restore	IOS added defaults of its own (a newer release): look at the diff in the next backup
`change CHG... is Scheduled - a load needs it in Implement`	move the change to Implement, or (your process permitting) `net_config_change_states`


30. Mail relay whitelist: one address per line; add or remove with an approval

One job puts the list one address per line, each named (Format the list). Two AAP workflows change the list of addresses your mail relay accepts mail from - Postfix's `mynetworks` (a third removes the ones that sent no mail in six months: Remove the addresses that sent no mail):

- **Mail relay - add an IP**: the IP address(es) and a **required comment** (the name and/or service they are for).
- **Mail relay - remove an IP**: the IP address(es).

The IP field takes one address, a subnet, or several separated by commas: `198.51.100.3`, `198.51.100.0/24`, `198.51.100.3, 198.51.100.4, 203.0.113.0/28` (spaces, semicolons or one per line work too).

Each workflow has three steps:



1. The **plan** checks the request, reads the list on every relay and emails "waiting for approval" with the exact lines. It changes nothing.
2. A person **approves** or denies it.
3. The **apply** step writes exactly the lines the email showed, checks the configuration, reads the list back as Postfix does, reloads Postfix and emails the result.

By default the list is the `mynetworks` line of `/etc/postfix/main.cf`, kept as it is: an add puts `, 198.51.100.3` at the end of the line (as a `lineinfile` with `'\1, {{ IP_address }}'` does) and one comment line per address just above it, so the lines above `mynetworks` read as a table of who asked for what:

```
# 198.51.100.3       Payroll app (svc-payroll)  [added 2026-10-22 by jdoe]
# 203.0.113.0/28     Scanners, room 210  [added 2026-10-23 by asmith]
mynetworks = 127.0.0.0/8, 192.0.2.10, 198.51.100.3, 203.0.113.0/28
mynetworks_style = host
```

Once the list is one address per line (the format job), an add puts each address on a line of its own in its place in the order, its comment line just above it, and a removal takes the address's line and the comment lines just above it:

```
mynetworks =
    127.0.0.0/8
    # Scanners, room 210  [added 2026-10-23 by asmith]
    203.0.113.0/28

    # Payroll app (svc-payroll)  [added 2026-10-22 by jdoe]
    198.51.100.3

    # web01.example.mil  Payroll [AAP]
    198.51.100.7
mynetworks_style = host
```

Only the `mynetworks` line (the last one in the file, as Postfix reads it, with its continuation lines) and these comment lines are ever changed - `mynetworks_style`, `relayhost` and every other line stay byte for byte. A removal takes the address out of the line, and its comment line when an add of this workflow wrote it; comments you wrote by hand stay. Remove everything that was added and `main.cf` is the file it was before.

After writing, the apply step runs `postfix check` and `postconf -h mynetworks`: Postfix must read exactly the list that was planned. If either fails, `main.cf` is put back from its backup and Postfix is not reloaded.

Format the list: one address per line

The job **Mail relay - format the whitelist** (`playbooks/mail_relay_format.yml`) rewrites each relay's `mynetworks` one address or subnet per line, the way the example above reads:

- **The order:** anything that is not an IPv4 address first (`[::1]/128`, a `cidr:` table, `$parameter`), as it was; then the subnets; then the single addresses - each in number order. A blank line between the single addresses (`mail_relay_format_blank_lines: false` for none). Postfix skips comment and blank lines inside a parameter.
- **A name for each single address** with no comment yet (subnets are not looked up):
- its **name in DNS**, looked up **on the relay** - what `nslookup` would say from there (`getent hosts`: DNS and `/etc/hosts`, `mail_relay_format_dns_timeout` seconds each);
- the **VM that has it** in vCenter - by its IP address (VMware Tools), else by that DNS name as the VM's name or guest host name - and the **folder the VM is in** (only that one, not the folders above it), which usually says the service: `/DC1/vm/Finance/Payroll` gives `Payroll`. Two VMs in different folders: no service (no guess). This needs the *VMware vCenter* credential on the template; without it the names are from DNS only, and the report says so.
- Neither: no comment line, the address as it is.

The comment line: `# NAME SERVICE [AAP]` - the DNS name, two spaces, the service (the VM's folder), and `[AAP]`: this job wrote it. No name and no VM found (`-` in the report's *Each address looked up*): no comment line, the address as it is. Lines an older version wrote (`# NAME - SERVICE [AAP mail relay format DATE job N]`) are still known as this job's: `mail_relay_format_refresh: true` looks those addresses up again and writes them the new way.

- **Comments kept:** a comment line an add wrote above `mynetworks` (`# 198.51.100.3 Payroll app ... [added ...]`) goes onto its address, and that address is not looked up. A comment you wrote inside the list stays above its address (or at the top of the list). Comment lines above `mynetworks` you wrote by hand stay where they are.
- **The list keeps exactly its addresses**: only their order and the comment lines change. The job checks that before it writes, and after: `postfix check`, then `postconf -h mynetworks` must read the new list.

- **A copy first:** `main.cf.before-format-DATE-TIME`, next to `main.cf` on each relay (the report names it). A failed check or read-back puts that copy back. Postfix is not reloaded (the list is the same; `mail_relay_format_reload: true` to reload anyway).
- **Run it again** any time: a list that is one address per line already, with nothing new to name, is left as it is. `mail_relay_format_refresh: true` looks up again the addresses this job named before (yours stay).


Do it: a job template *Mail relay - format the whitelist*, playbook `playbooks/mail_relay_format.yml`, credentials **Machine** and **VMware vCenter** (read-only is enough), Variables `mail_relay_group: <your group>` and `report_email_to`. Launch it as **Check** first: nothing is written, and its report is printed and **emailed** too, titled *dry run* (`mail_relay_format_check_email: false` to only print it). It shows:

- **vCenter:** how many VMs each vCenter gave, how many addresses matched a VM (by its IP address or its DNS name) and how many of those are in a folder - and, when that is none, why that usually is (the account sees no VM; or the addresses are not the VMs' own: NAT, a load balancer, servers that are not VMs).
- **Each address looked up:** every single address with no comment yet - its DNS name, the VM and its folder, or `-` where nothing was found.
- **The list on each relay,** as a Run would write it.

Then **Run**. To go back: copy `main.cf.before-format-...` over `main.cf` (`postfix check`, `systemctl reload postfix`).

Remove the addresses that sent no mail

A third workflow, **Mail relay - remove unused addresses**, finds the addresses on the list that sent no mail through any relay in the last six months, and removes them after an approval:



1. **The plan** (`playbooks/mail_relay_unused.yml`, read-only) reads on each relay its list and its **mail logs** - `/var/log/maillog` and every rotated copy next to it (`maillog-20260501`, `maillog.1`, gzipped or not), and an archive folder of old mail logs (`/var/log/maillog_archive`, and any folder the patterns name: every file in it and its folders with "mail" in its path, gzip, bzip2 or xz too; `mail_relay_unused_logs`), or the journal when there is no log file. The email's *How far back the logs go* table says how many files were read on each relay. A log line without a year gets it from its file's name (`maillog-20260101.gz`), else from when the file last changed. Months of logs on a busy relay can be gigabytes: reading them takes minutes per relay (line by line, little memory). A `.zip` archive is not read - unzip it into the folder. An address **sent mail** when a relay accepted a message from it: Postfix's `smtpd[...]: 4AbCd1: client=name[198.51.100.7]` line. A connection without a message (`connect from ...` only - a monitor, a scanner, a load balancer's health check) does **not** count; the table shows those connections apart. All

relays' logs are read together: an address that sends through one relay only is in use on all.

2. **How far back the logs go**, per relay: the oldest line read. When a relay's logs do not reach back the six months asked (`mail_relay_unused_days`, 183), nothing is proposed - a quiet address could not be told from an unused one - and the email says how far back each relay's logs go. (RHEL's default keeps about 5 weeks of `/var/log/maillog`: keep them longer in `/etc/logrotate.d/syslog`, or set `mail_relay_unused_accept_short_logs: true` to go by what they cover.)
3. **The removal** of the single addresses that sent nothing goes on as a plan of the remove workflow: the email *Mail relay whitelist - waiting for approval: unused - remove ...* has the exact lines to be removed, each address with its last mail, and the table of every address on the list. Never proposed: `127.0.0.0/8`, anything that is not an address, `mail_relay_unused_keep`, and **subnets** - a subnet that sent nothing is listed, to remove with *Mail relay - remove an IP* if it is no longer needed. At most 50 at once (`mail_relay_unused_max`; the next run takes the rest).
4. **Approve** it, and the apply step removes exactly those lines (with their comment lines), as for *Mail relay - remove an IP*: the file backed up, `postfix check`, the read-back, the reload, the result emailed.
5. Then run **Mail relay - format the whitelist** to put the list in order and name what has no name yet.

Nothing unused, logs too short, or a relay that could not be read: the email says so, the job fails, and nothing waits for approval.

The email's tables:

Table	What
How far back the logs go	each relay: its oldest and newest log line, how many days back, whether that covers the days asked, how many log files (or the journal) were read, any file it could not read
Each address on the list	address, address or subnet, on which relays, its **last mail** (the newest message any relay accepted from it, or from an address inside the subnet - `never in the logs`), how many messages the logs hold, how often it connected, and the verdict: *in use*, **UNUSED**, *UNUSED subnet - listed only*, *kept*

Set it up: a job template **Mail relay - unused addresses plan**, playbook `playbooks/mail_relay_unused.yml`, credential **Machine** (sudo on the relays: the logs are root's), Variables `mail_relay_group: <your group>`. Then the workflow **Mail relay - remove unused addresses**: Variables `report_email_to: [mail-team@yoursite.mil]` (and `mail_relay_group`); steps *Mail relay - unused addresses plan* -> **Run on success** -> *Approval* (`Remove these unused addresses from the mail relay whitelist?`) -> **Run on success** -> *Mail relay - apply the approved whitelist change*. No survey. Try the plan template alone with Job type **Check** first: it reads the logs and prints the same report (`DRY RUN: would email`) - the plan itself changes nothing either way.

Setting	Default	
`mail_relay_unused_days`	`183`	days without mail that make an address unused (six months)

Setting	Default	
`mail_relay_unused_logs`	`["/var/log/maillog*"]`	the log files on each relay (patterns; a folder - `/var/log/maillog_archive` - its mail log files, its folders too - an archive elsewhere: add its folder, e.g. `["/var/log/maillog*", "/data/mail-archive"]`; a relay's own `host_vars` may differ)
`mail_relay_unused_journal`	`auto`	`auto`: the journal when no log file is there; `true`: as well; `false`: never
`mail_relay_unused_keep`	`[]`	addresses or subnets never proposed, e.g. a backup server that mails twice a year
`mail_relay_unused_max`	`50`	the most addresses one plan removes
`mail_relay_unused_accept_short_logs`	`false`	`true` = propose even when a relay's logs do not reach back the days asked

What it refuses

- An address that is not IPv4 (`198.51.100`, `198.51.100.300`, `abc`, `0.0.0.0`). A subnet wider than `/24` (`mail_relay_min_prefix`): a relay open to a wide range is an open relay. A subnet not written from its first address (`198.51.100.5/24` - the message gives `198.51.100.0/24`). One bad address refuses the whole request and names it. More than 20 at once (`mail_relay_max_ips`).
- An add without a comment, or a comment with characters other than letters, digits, spaces and `. _ , : ; ( ) / @ & ' + -` (no `#`, no `[ ]`, no line breaks: the comment goes into `main.cf`).
- Nothing to do: an add of addresses all already on the list, a removal of ones not on it - the plan says so in its email (with who added them, when it knows) and stops; nothing waits for approval. Some already there: the others go on and the email's *Note* says which were skipped.
- A removal that would leave `mynetworks` empty.
- A relay that cannot be read (unreachable, the file is missing, no `mynetworks =` line): nothing waits for approval.
- The apply job on its own: it changes only what an approved plan says.

The approval email's *Note* also says when an address already relays through a subnet on the list (`198.51.100.9 can relay already: it is inside 198.51.100.0/24`), when a removed address **still** can (`... can STILL relay after this: it is inside 198.51.100.0/24`), and which listed addresses sit inside a subnet being added or removed.

Set it up (once)

1. **Inventory:** put the mail relay server(s) in a group named `mail_relays`, or put `mail_relay_group: mail` (your group's name) in both workflows' Variables (and the format template's). Every relay in the group is changed (a template's Limit narrows it - with `localhost` in it, e.g. `relay1,localhost`; a Limit without `localhost` is refused). The job templates need the **Machine** credential of an account that may use sudo on the relays.
2. **Where the list is** - the defaults are the `mynetworks` line of `/etc/postfix/main.cf`; nothing to set for that:

Setting	Default	Change it when
`mail_relay_style`	`main_cf`	`file`: the list is a file with one address per line (below)
`mail_relay_file`	`/etc/postfix/main.cf`	main.cf is elsewhere (`host_vars` for a relay whose file differs)
`mail_relay_parameter`	`mynetworks`	the list is another parameter
`mail_relay_postconf`	`postconf`	`""`: do not read the list back after a change
`mail_relay_check_command`	`postfix check`	another check; `""` = none
`mail_relay_reload_service`	`postfix`	the service to reload; `""` = none (a reload is enough for `mynetworks`)
`mail_relay_allow_subnets` / `mail_relay_min_prefix`	`true` / `24`	single addresses only / a wider subnet

A list **file** instead (`mynetworks = 127.0.0.0/8, /etc/postfix/mynetworks`): `mail_relay_style: file`, `mail_relay_file: /etc/postfix/mynetworks`; each address on its own line, its comment on the line above. A Postfix access map: also `mail_relay_entry_suffix: " OK"` and `mail_relay_postmap: true` (a `hash:`/`lmdb:` map cannot hold a subnet - the plan refuses one; use a `cidr:` table, `mail_relay_postmap: false`).

A map line that refuses its address (`REJECT`, `DISCARD`, `554 ...`) is never changed by the jobs (1.41.0). That address is not on the list: a remove leaves the line, and an add says to change the line by hand.

Put them in `playbooks/group_vars/all.yml`.

3. **Email:** the `report_email_*` settings in `all.yml` (your other report jobs use them already). Who gets both emails: `report_email_to`, set on each workflow. These reports are emailed only, not put on the report website (`mail_relay_web: true` to publish them there too; this needs `report_web_dest` in `all.yml`, as the website setup says - typed in a template's Variables it beats everything).
4. **Three job templates** (Automation Execution > Templates > Create template > Create job template):

Name	Playbook	Credentials	Notes
Mail relay - whitelist plan	`playbooks/mail_relay_plan.yml`	Machine	
Mail relay - apply the approved whitelist change	`playbooks/mail_relay_approved.yml`	Machine	do **not** tick *Prompt on launch* for Variables

Name	Playbook	Credentials	Notes
Mail relay - format the whitelist	playbooks/mail_relay_format.yml	Machine, VMware vCenter	above; no workflow

Both workflows use the first two templates. Leave *Concurrent jobs* off on the apply template (the default): the apply step reads the whole file, changes it and writes it back, so an add and a remove approved at the same moment then run one after the other instead of overwriting each other.

5. **Two workflows** (Create template > Create workflow job template), see WORKFLOWS_AND_SCHEDULES.md for the editor:
   - **Mail relay - add an IP.** Variables:

```yaml
mail_relay_action: add
report_email_to: [mail-team@yoursite.mil]
```

Steps: *Mail relay - whitelist plan* -> **Run on success** -> *Approval* (name `Add this address to the mail relay whitelist?`, Timeout e.g. 24 hours) -> **Run on success** -> *Mail relay - apply the approved whitelist change*. Survey:

Question	Variable	Type	Required
IP address(es) - one, a subnet, or several separated by commas	mail_relay_ip	Textarea, max 400	yes
Name and/or service they are for	mail_relay_comment	Text, min 3, max 200	yes
Requested by (optional)	mail_relay_requested_by	Text	no

   - **Mail relay - remove an IP.** The same, with `mail_relay_action: remove`, the approval named `Remove this address from the mail relay whitelist?`, and only the IP question in the survey.

The survey variable may be named `IP_address` instead of `mail_relay_ip` (the name your older playbook used) if Orchestrator already sends that.

Who may approve: the workflow > User Access > Add roles > **Approve**. The email says where: Automation Execution > Administration > Workflow Approvals. `mail_relay_approve_url` puts a link in the email (copy that page's address from your browser).

Starting it from Orchestrator (or any other tool)

Launch the **workflow**, not a job template: a job template has no approval. With a survey, AAP takes only the survey's variables from a launch, so send exactly these names:

```
POST https://<aap>/api/controller/v2/workflow_job_templates/<id>/launch/      (AAP 2.4:
  /api/v2/...)
{"extra_vars": {"mail_relay_ip": "198.51.100.3, 198.51.100.4", "mail_relay_comment": "Payroll app
  (svc-payroll)",
               "mail_relay_requested_by": "jdoe"}}
```

Without `mail_relay_requested_by` the comment names the AAP user that launched it (Orchestrator's account). A value with a trailing line break is fine (it is trimmed). The launch answers with the workflow job's

id: its status is `successful` once applied, `failed` when the plan refused or the change failed, and the approval shows in the workflow job while it waits.

Try it without changing anything

Launch the add workflow with an address that is already on the list: the plan emails *nothing to approve* and stops. Or set the apply step's *Job type* to **Check** (and *Show changes* on): after the approval it shows the lines it would write and changes nothing.

When something goes wrong

You see	It means	Do
`mail_relay_action is '': set it to add or remove`	the workflow's Variables lack it	add `mail_relay_action: add` (or `remove`) to the workflow's Variables
`No relay server to change: the inventory has no host in 'mail_relays'`	no such group in the inventory	name the group, or put `mail_relay_group: <your group>` in both workflows' Variables
`mail_relay_ip '...': ...`	an address is not usable; the message names it and says why	launch it again with IPv4 addresses or subnets, separated by commas
`mail_relay_comment is required: ...`	empty, too short, or a character that is not allowed	the name and/or service, letters and digits
`nothing to approve: ... is already on the list`	an add of addresses already there (the email says who added them)	nothing to do
`... is not on <relay>: set mail_relay_file` / `no 'mynetworks =' line in it`	the list is elsewhere	`mail_relay_file` (or `mail_relay_style: file`) in `all.yml` or the relay's `host_vars`
`would leave mynetworks empty`	a removal of every address on the list	keep at least one (`127.0.0.0/8`)
`Nothing to change: no approved plan (mail_relay_plan) reached this job`	the apply template was launched by itself	launch the workflow
`The new list did not pass: ... is back as it was`	`postmap`, `postfix check` or the read-back (`Postfix reads mynetworks as ...`) failed after the change	the file was put back byte for byte and nothing was reloaded; read the message, launch again
`The list would not keep exactly its words` (format)	the new list would not hold the same addresses - a bug	nothing was written; send the job's output
No VMware vCenter credential on the template (format)	the names are from DNS only	attach the *VMware vCenter* credential and run it again with `mail_relay_format_refresh: true`
`... already on the list now (changed since the plan)`	someone changed the list between the plan and the approval	nothing to do; the email says which relay and address

Tests: `bash tests/mail_relay/run_mail_relay_test.sh` (main.cf files of two relays in a temporary folder, a list file and an access map, a fake mail relay; the format, then an add and a removal on the formatted list), `python3 tests/test_mail_relay.py` (reading and changing the list, the format, the names) and the format's VM and folder against vcsim in `tests/vmware/run_vmware_test.sh`.

31. The certificate inventory: CSV, JSON and SQL Server, for a dashboard

Every certificate report can also write **every certificate it found**, with the same fields from each, for a dashboard (Power BI, Excel, Grafana ...). Turn it on in the template's Variables (or `all.yml`):

Report	Template	Its rows in the inventory (source)
Linux	*Certificate report* (`playbooks/cert_report.yml`)	`linux`: files, ports, keystores, the trust store
Windows	*Windows certificate report* (`playbooks/win_cert_report.yml`)	`windows`: every machine store, bindings, TLS endpoints
VMware	*VMware - certificate report* (`playbooks/vmware_cert_report.yml`)	`vmware`: vCenter's Machine SSL certificate, each ESXi host's
Network devices	*Network device certificate report* (`playbooks/net_cert_report.yml`)	`net`: switches, firewalls, printers, iLO / iDRAC ... (NETWORK_CERTS.md)

Two ways, each on by itself - **files** (CSV and JSON) and a **SQL Server table**. A report with neither writes nothing (the default). A Check run (dry run) writes nothing either.

What each certificate has

Field	Example	What it is
`id`	`9c1f...` (64 hex)	the same host, place and certificate keep their id from run to run (the SQL table's key)
`source`	`linux`	linux, windows, vmware, net
`host`	`web01.example.mil`	the server or device
`location`	`/etc/pki/tls/certs/web.crt`, `LocalMachine\My, used by https 0.0.0.0:443`, `https://192.0.2.10:443`	where it is
`subject`, `issuer`	`CN=web01.example.mil,O=Example,C=US`	
`sans`	`DNS:web01.example.mil; IP:192.0.2.10`	its names (a list in the JSON)
`not_after`, `days`	`2027-01-31`, `103`	when it expires; days left when it was read (negative: expired)
`status`	`warning`	expired, critical, warning, notice, ok - the report's own days (warn, crit, notice)
`tier`	`ca-signed`	**root** (a self-signed CA that signs certificates, or one a host trusts), **intermediate** (a CA signed by another), **ca-signed** (issued by a CA), **self-signed**
`trust_store`	`false`	true: a certificate the host trusts (Trusted Root, the trust store), not its own
`in_use`	`true`	bound to a service (an https binding, WinRM, a port, vCenter, a device); empty: not known
`public_key`, `sig_alg`	`RSA 2048`, `sha256WithRSAEncryption`	
`serial`, `sha1`, `sha256`		the serial number; the fingerprints (sha1 is Windows' thumbprint)
`scanned_at`, `job`	`2026-10-20T06:00:00Z`, `4711`	when, and the AAP job that read it

The same certificate in two places (a file and the port it is served on) is two rows - one per place - with the same `sha256`: count `DISTINCT sha256` for certificates, rows for places.

Files: CSV and JSON

```yaml
cert_inventory_files: true
cert_inventory_dir: /var/lib/site-automation/cert-inventory
cert_inventory_host: files01.example.mil      # optional - see below
cert_inventory_history: false                  # true: also a dated copy each run
```

Each report writes `<source>-certificates.csv` and `.json` (`linux-certificates.csv` ...), replaced each run.

Where they go. A job runs in a container that is gone when it ends, so the files must land somewhere that stays:

- `cert_inventory_host` (recommended): a host in the job's inventory - a Linux host with the share mounted, or a Windows file server (then `cert_inventory_dir` is a Windows path, e.g. `D:\Shares\Certificates`). The job template must carry a credential that logs in to it. A Windows file server needs the `ansible.windows` collection in the execution environment (the all-in-one EE has it).
- **The AAP node itself**, `cert_inventory_host` empty: only when an administrator exposes the folder to jobs - **Settings > Job settings > Paths to expose to isolated jobs**: `/var/lib/site-automation/cert-inventory:/var/lib/site-automation/cert-inventory:rw`, and the folder exists, writable, on every execution node. Otherwise the job writes into its container and the files are lost - the job's last line says so.

Power BI: *Get data* > *Folder* on the share, *Combine & Transform*: one table of every source.

SQL Server

```yaml
cert_inventory_sql: true
cert_inventory_sql_server: sql01.example.mil
cert_inventory_sql_database: Certificates
cert_inventory_sql_table: dbo.cert_inventory      # schema.table
cert_inventory_sql_create: true                   # the first time: make the table and its view
```

1. **The credential.** Create the credential type *SQL Server (certificate inventory)* (`aap/credential_types/cert_inventory_sql.yml`), then one credential: a SQL login, or `DOMAIN\account` for Windows authentication. Attach it to each certificate report template that writes the table.
2. **The account** needs `SELECT, INSERT, UPDATE` on the table - and, once, `CREATE TABLE` and `CREATE VIEW` for `cert_inventory_sql_create: true` (or have the DBA run the table's script: `roles/cert_inventory/templates/create.sql.j2`, with `{{ _ci_table }}` replaced by the table name).
3. **SQL Server 2016 or later** (the rows go in as one JSON parameter, `OPENJSON` - no certificate's text is ever part of the SQL). The execution environment needs `pymssql` and `community.general` (the all-in-one EE has both).

The table: a row per host, place and certificate, with every field above and `first_seen`, `last_seen` and `present`. Each run adds the new rows and updates the ones it saw again; on the hosts it read, a row it did not see again (the certificate was replaced or removed) gets `present = 0` - kept, for the history. A host the run did not read (unreachable, left out) keeps its rows as they were. **The view** `<table>_current` is the rows present now - what the dashboard shows.

Power BI: *Get data* > *SQL Server*, the database, the view `dbo.cert_inventory_current` (Import, refreshed after the reports run). Useful measures: certificates by `tier` and `status`; expiring in 30 / 60 / 90 days (`days`);

self-signed in use (`tier = 'self-signed' AND in_use = 1`); weak keys (`public_key = 'RSA 1024'`) or signatures (`sig_alg LIKE 'sha1%'`); trend (`first_seen` by month).

Schedule

Run the four reports weekly (the Certificate watch workflows run them daily - WORKFLOWS_AND_SCHEDULES.md), with the same `cert_inventory_*` settings - in `all.yml` they apply to every report at once.

Troubleshooting

You see	Means / do
`... on localhost (AAP node: only kept if AAP exposes that path to jobs ...)` and no files on the share	set `cert_inventory_host`, or expose the folder (above)
`cert_inventory_host '...' is not in this job's inventory`	add the file server to the inventory, with a credential on the template
`cert_inventory_sql: true needs cert_inventory_sql_server ...`	a setting, or the SQL Server credential, is missing
`pymssql` / `mssql_script` not found	the execution environment lacks them: the all-in-one EE (EXECUTION_ENVIRONMENT.md)
`Invalid object name 'dbo.cert_inventory'`	the table is not there: `cert_inventory_sql_create: true` once, or the DBA's script
`Login failed`	the credential's login, or the database's permissions

32. Certificate renewal through the PKI's ServiceNow catalog item

The certificate renewals - **Certificate renewal - CSRs** (Linux), **Windows certificate renewal**, **VMware - certificate renewal** and **Network device certificate renewal** - make a new key and a CSR for each certificate that expires soon. By default each CSR goes on a ServiceNow **incident**, and a person submits it to the PKI.

With `cert_renew_servicenow: catalog` there is no incident: the job **orders your PKI's catalog item** (for example *DoD PKI Certificate Request*) for each certificate, with the CSR in the item's *Please add CSR* question - exactly what a person would do on the portal.

	incident (the default)	catalog
Per certificate	an incident, the CSR attached, a work note with the next steps	a request (REQ / RITM) on the PKI's catalog item, the CSR in its CSR question
Who sends it to the PKI	a person, by hand	the job
A run again	finds the incident; no second CSR	finds the request by the CSR on it; no second order
Once the certificate is replaced	the incident is noted as cleared (or resolved)	nothing to close: the PKI closes the request

What a run does

For each certificate that expires within the warning days (30 by default):

1. **The CSR** is made where the key stays, as always: on the Linux or Windows server, on vCenter or the ESXi host, on the Cisco device. The key never leaves it.
2. **Already ordered?** The job looks for a request carrying this CSR. The CSR's name in the order says which certificate it is for and when that certificate expires: `web01.example.mil-1a2b3c4d-exp20261114.csr`.
   - found **open, in progress, or Closed Complete** (the PKI issued it - install it): not ordered again.
   - found only **Closed Incomplete or Closed Skipped** (rejected, cancelled - `cert_renew_catalog_reorder_states`): ordered again. On vCenter, an ESXi host or a Cisco device that also means a new CSR.
   - not found: ordered.
3. **The order**: one request per certificate. Your answers (`cert_renew_catalog_variables`), the CSR in the CSR question, and - if you name a question for it (`cert_renew_catalog_names_variable`) - the certificate's names (subjectAltName).
4. **Checked**: the job reads the requested item (RITM) back and makes sure the CSR is on it. If ServiceNow did not move the CSR into the request, the job attaches it to the RITM (the paperclip) - the PKI sees it either way, and the next run finds the order by it.

The job output lists every certificate:

```
ORDERED RITM0012345 (REQ0012344) | web01.example.mil | web01.example.mil-1a2b3c4d-exp20261114.csr
  | the CSR is in the request (its question csr_file)
ORDERED ALREADY RITM0012001 (Work in Progress) | app01.example.mil |
  app01.example.mil-77aa1c2e-exp20261102.csr
ORDERED ALREADY RITM0011876 (Closed Complete) | db01.example.mil | ... | the PKI issued it:
  install it
ORDERED RITM0012350 (REQ0012349) (again: RITM0011990 closed Closed Incomplete) | ...
FAILED  | web02.example.mil | ... | the order was refused: HTTP 400: Mandatory Variables are
  required - ...
```

A certificate that could not be ordered fails the job (the others are still ordered), so a schedule shows red.

Not ordered here: a network device without a CSR made by the job (anything but Cisco IOS / IOS-XE with `net_cert_cisco_csr`): it is in the report; make its CSR on the device and order it by hand. A VMCA-signed vCenter or host certificate: renew it in vCenter, as before.

Before you start

- **The item's sys_id.** Open the item on the portal: the address ends in `?id=sc_cat_item&sys_id=a3034a7325933210361adc6bd7ce8c93`. That sys_id is the surest way to name it.
- **The account that orders.** The renewal orders as the account in the *ServiceNow API* credential. That account must be allowed to order the item (the item's *Available for* / user criteria) and to read the requests it made. Ask the PKI team whether they accept requests from a service account, and who should be *Requested For*.
- **Same instance.** The job orders on the instance in the credential. If the PKI's catalog is on another ServiceNow, give the renewal templates a *ServiceNow API* credential for that one.

Step 1 - the item's questions (their internal names)

The settings need each question's **internal name** (e.g. `requested_for`), not its label ("Requested For"). Two ways to see them:

In your browser, no job needed. Logged in to ServiceNow, open:

```
https://<your-instance>/api/sn_sc/servicecatalog/items/<the item's sys_id>
```

It shows the item as JSON (Firefox lays it out as a tree). Under `variables`, each question has:

Field	Means
`name`	its internal name - what the settings use
`label`	what the form shows
`mandatory`	`true`: it needs an answer
`type`	33 attachment (the CSR's), 31 requested for, 8 reference, 5 select box, 6 single line text, 2 multi line text, 11 label (nothing to fill in)
`reference`	for a reference: the table (`sys_user`, `cmn_location` ...)
`choices`	for a select box: each `value` and `label`

This is what *your* account sees. The job sees what the credential's account sees - step 3 checks that.

With catalog admin rights there is also the list:
`https://<your-instance>/item_option_new_list.do?sysparm_query=cat_item=<the item's sys_id>`
(columns Name, Type, Mandatory).

Or run the catalog test (step 3): it prints the same, one line per question.

Step 2 - the settings

In `playbooks/group_vars/all.yml` (every renewal job reads them). An example for a form like the DoD PKI one - **the internal names are examples**: use the ones step 1 shows.

YAML

```
cert_renew_servicenow: catalog
cert_renew_catalog_item: a3034a7325933210361adc6bd7ce8c93     # or its name: "DoD PKI Certificate
                                                              # Request"
cert_renew_catalog_variables:
  requested_for: svc_aap_sn            # a reference: a user name, a name, or a sys_id
  title_rank: CTR
  email: sysadmins@yoursite.mil
  dsn: "314-555-0100"
  directorate: 0f1e2d3c4b5a69788796a5b4c3d2e1f0   # a reference to a table of your own: its sys_id
  room_number: "010"
  contact_method: Email                # a select box: its label or its value
  location: "Building 100"             # a reference: the location's name, or its sys_id
cert_renew_catalog_csr_variable: ""    # empty = the item's only attachment question
cert_renew_catalog_names_variable: additional_sans   # the "List any additional SANs" box gets the
                                                     # certificate's names
```

- **A reference** (Requested For, Location ...): the record's **name** works - the job looks it up and sends its sys_id (a user: user name or full name). For a table of your own the job can only look up a `name` column: if it says "no record named", give the **sys_id** (open the record, or the reference field's lookup, and copy it).
- **A select box**: its label (`Email`) or its value (`email`).
- **In an answer**, `{host}`, `{subject}`, `{names}`, `{expires}`, `{issuer}` and `{where}` become the certificate's - for a free-text question such as a justification: `justification: "Renewal of {subject} on {host}, expires {expires}"`.
- **Not every question needs an answer** - only the mandatory ones (and the CSR's, which the job fills in).

Setting	Default	What it does
`cert_renew_servicenow`	`incident`	`catalog` = order the item, no incident
`cert_renew_catalog_item`	`""`	the item: its name as the catalog shows it, or its sys_id
`cert_renew_catalog_variables`	`{}`	the answers, by the questions' internal names
`cert_renew_catalog_csr_variable`	`""`	the attachment question for the CSR (empty = the only one)
`cert_renew_catalog_names_variable`	`""`	a question that gets the certificate's names

Setting	Default	What it does
`cert_renew_catalog_reorder_states`	`["4", "7"]`	a request closed this way (Closed Incomplete, Closed Skipped) is ordered again
`cert_renew_catalog_upload_table`	`ZZ_YYsc_cart_item`	where the CSR is uploaded before the order (ServiceNow moves it to the request)
`servicenow_catalog_test_order`	`false`	the catalog test also orders once, with a test CSR

Step 3 - the catalog test

A job template: **ServiceNow - catalog test**, playbook `playbooks/servicenow_catalog_test.yml`, inventory any, credential **ServiceNow API** (the account that will order). Variables: aap/extra_vars/servicenow_catalog_test.yml. Launch it:

```
PASS 1 item: DoD PKI Certificate Request (sys_id a3034a73...), 11 question(s), read as svc_aap_sn
  at https://...
     2 questions: requested_for | Requested For | requested for (31) | MANDATORY | a sys_user
       record: its name or sys_id
                 contact_method | Preferred method of contact | select box (5) | MANDATORY |
                   choices: email = Email, phone = Phone
                 csr_file | Please add CSR | attachment (33) | MANDATORY | the CSR goes here
                 ...
PASS 3 settings: the order would send these answers (references as sys_ids), the CSR in csr_file
  ...
SKIP 4 order: servicenow_catalog_test_order is false
```

Steps 1-3 only read. A FAIL says what to change: the item not found (or not orderable by that account), a question name that is not on the item, a mandatory question left empty, a choice it does not have, a name with no record.

One real test order (optional): `servicenow_catalog_test_order: true`. It orders the item once, exactly as the renewal does, with a test CSR (`CN=site-automation-test.invalid`, named `site-automation-TEST-...csr`). **The PKI gets a real request** - tell them first, then cancel it. Run again, it finds that order and makes no second one (until it is cancelled: Closed Skipped).

Step 4 - the renewals

- Set `cert_renew_servicenow: catalog` (step 2). Nothing else changes on the renewal templates: the same playbooks, the same *ServiceNow API* credential.
- **Try it first** with Job type **Check** and a **Limit** of one host: the output says `would order it`, or `ordered already: RITM...`, and nothing is sent.
- **The workflows:** the certificate workflows run *Certificate report -> ServiceNow tickets -> Certificate renewal*. The *ServiceNow tickets* step opens incidents for the report's findings: with no incidents wanted, take that step out (link the report straight to the renewal, **Run always**).
- **The VMware and network renewals** make no incident either: the request is the CSR's record (vCenter, a host and a Cisco device keep one pending key - a second CSR would replace it).

After the PKI issues the certificate

The request shows **Closed Complete** (each run says `the PKI issued it: install it`).

Installed by the job, after an approval: *Certificate install - check* (on a schedule) finds the certificate on the request - whatever the PKI attached or pasted, as long as its public key is the CSR's - and says what installing it would do; after the approval, *Certificate install - approved* puts it in place, reloads the service, checks the port, and puts the old one back if anything is wrong. Linux and Windows: CERT_INSTALL.md; vCenter and ESXi: VMWARE.md. The PKI may attach only the .cer when you keep the DoD PKI's CA bundle (`cert_install_ca_bundle`): the chain comes from it (CERT_INSTALL.md).

By hand - a keystore, a service that needs a restart, Cisco, or vCenter and ESXi without the install workflow - where the key is:

Where	How
Linux	the new key is in `cert_renew_dir` next to the CSR: RUNBOOKS.md, "Certificate renewal: the CSRs"
Windows	`certreq -accept -machine <issued.cer>` on the server: WINDOWS.md, "Windows certificate renewal - CSRs"
vCenter, ESXi	the vSphere Client's *Import and Replace*: VMWARE.md, "Certificates of vCenter and the ESXi hosts"
Cisco	`crypto pki import <trustpoint> certificate`: NETWORK_CERTS.md, "The renewal"

Once the new certificate is in place, it has another expiry date: nothing more is ordered until it is due.

When it goes wrong


The job says	Means	Do
`no catalog item named "..." that the API account can see`	the name differs, or the account may not order it	use the sys_id from the portal address; ask the catalog owner to make it available to the account
`the item has no question X (its questions: ...)`	an internal name that is not on the item	take the names from step 1
`X (Label) is mandatory: give it a value`	a mandatory question without an answer	add it to `cert_renew_catalog_variables`
`'Fax' is not one of its choices (email = Email, ...)`	a select box answer it does not have	one of the listed values or labels
`X: no record named 'Building 9' in cmn_location` / `2 records named`	a reference by name: none, or several	the sys_id
`the order was refused: HTTP 400: ...`	ServiceNow's reason (a mandatory answer, a value it does not take, a rule of the item)	fix what it says; the catalog test shows the same
`ordered (REQ...), but its requested item could not be read`	the account cannot read the RITM it ordered	let it read its own requests; check the request by hand - the next run would order again
`ordered (RITM...), but the CSR is not on it`	ServiceNow refused the attachment on the RITM	attach the CSR by hand (the job output names it); allow `.csr` / `.txt` attachments
`the CSR could not be uploaded`	the instance refused the file (an extension it does not allow)	`cert_renew_attach_ext: txt`
The PKI says the CSR question is empty	the instance did not take the uploaded file for the question	the CSR is attached to the request (the paperclip): point them there; tell us the instance's version

Limits

- **Tested against a stand-in ServiceNow** (`tests/servicenow/snmock.py`): the Service Catalog API calls are the documented ones (`/api/sn_sc/servicecatalog/items`, `order_now`, the Attachment API), but how an instance handles an attachment question filled through the API differs between releases and customizations. Run the catalog test with one test order first.
- **A catalog item, not a record producer**: the job uses `order_now`. A record producer (it makes some other record, not a request) is not supported yet.
- **One request per certificate.** The form's paperclip takes more CSRs, but one request each keeps each certificate's order findable, and the PKI can fulfil them one by one.

33. Installing the issued certificate: from the request, with an approval

The certificate renewal makes a new key and a CSR where the old certificate is, and - with `cert_renew_servicenow: catalog` - orders it from your PKI's catalog item (CERT_RENEWAL_CATALOG.md). The PKI admin then puts the certificate from DISA on **that same request**. The certificate install takes it from there and puts it in place of the old one - after a person approved what it will do.



The same for Windows: *Windows certificate install - check* › approval › *Windows certificate install - approved*. vCenter and the ESXi hosts: *VMware - certificate install - check* › approval › *VMware - certificate install - approved*, with this reader and its settings - the key and the CSR stay on vCenter or the host, so the CSR is read from the request: VMWARE.md.

What it does

The check (on a schedule - reads only)

1. **What waits.** On each host, the renewals still waiting for their certificate: the key, CSR and info file in `cert_renew_dir` (Linux), the pending request in `win_cert_renew_dir` (Windows).
2. **The request.** On the AAP side - the hosts never get the ServiceNow credential - the request carrying each CSR (by the CSR's name in the order, as the renewal finds its orders), and what the PKI put there:
   - files attached to the RITM, to one of its attachment questions, to its REQ, or to its catalog task (SCTASK - where the PKI team often works the request);
   - a certificate pasted into a work note or comment of the RITM or its task;
   - each one PEM (.cer, .crt, .pem), DER, PKCS7 (.p7b, text or binary) or a zip of them.

The certificate counts only when its public key is the CSR's. Anything else there - someone else's certificate, a form - is listed and never used. The CA certificates with it are its chain; when the PKI sent only the .cer, the chain comes from your CA bundle (below).

3. **The plan**, on the host: what installing it would do - or why a person does it (below).
4. **Ready ones go to the approval:** the job lists them, hands the plan on, and ends red - `NEEDS APPROVAL: ...` - so the workflow takes its *Run on fail* path. Nothing ready: it stays green.

The job output says, per certificate:

```
READY | web01.example.mil | CN=web01.example.mil,... | RITM0012345 | install in
  /etc/pki/tls/certs/web01.crt, /etc/pki/tls/private/web01.key | reload httpd.service | then port
  443 must serve it | the new one: serial 4A3F..., expires 2027-11-28 09:35 UTC
WAITING | app01.example.mil | CN=app01.example.mil,... | RITM0012346 | RITM0012346 (Work in
  Progress): no certificate for this key on it yet
HELD | db01.example.mil | CN=db01.example.mil,... | RITM0012350 | the old key of
  /etc/pki/tls/certs/db01.crt is in several files (...): name the one in use in
  cert_install_key_files
BY HAND | jboss01.example.mil | CN=jboss01... | RITM0012351 | in a keystore (/opt/app/keystore.jks
  (alias server)): its program needs a restart ... | steps: ...
```

The approved install (after the approval)

For each approved certificate, the plan is **made again first**: the same certificate, the same files (Linux) or bindings (Windows), the same services - or it is refused ("changed since the approval"). Then:

Linux

1. Each file it replaces is copied aside - `cert_renew_dir/backup/<date>-<certificate>/` (0700, the copies 0600: the old key is among them).
2. The new files are written **in the old ones' layout** - text or binary (DER), with the chain if the old file had one (the PKI's chain; a root only if the old file had one), with the key if the old file held it - and with the old file's owner, mode and SELinux label. The old key's file gets the new key. Each is written as a new file next to the old one under a fresh name, then renamed over it; a folder on the way, or the file itself, that has become a symbolic link since the check is not written through - the install is rolled back.
3. The service's configuration is tested (`apachectl configtest`, `nginx -t`, `haproxy -c`, `postfix check` ...).
4. The service is **reloaded** - never restarted.
5. The port must then serve the new certificate (`cert_install_verify_wait` seconds).

Any step fails: **the copies go back** and the service is reloaded again; the job says what failed and ends red. The copies are checked against their checksums before any file is written back, and they go back all together or not at all - never an old certificate next to a new key. When the reload fails again, or the port does not serve the old certificate again, the job says `FAILED` and what to check by hand - `ROLLED BACK` only when the old certificate is in place and served again. Installed: the renewal's key and CSR move to `cert_renew_dir/installed/`, and a work note on the request says what was installed where.

Windows

1. Its chain's intermediate CAs go into *Intermediate Certification Authorities* - **never a root** (a root is trusted by policy, not by this job: with the DoD roots in place, as on every DoD server, nothing is needed).
2. `certreq -accept -machine` puts it together with its pending key in *Personal*.
3. The new key gets the old key's extra permissions (read) - a service account that used the old one - and, for Remote Desktop, NETWORK SERVICE.
4. Each binding of the old certificate moves to the new one, and is read back:
   - **https** in HTTP.sys (IIS, WSUS, any `netsh http` binding - IP:port and hostname:port), the same application and its settings (client certificate negotiation, the CTL store, the revocation checks... given back to `netsh` and read back unchanged), the new certificate from *Personal* (`My`) - also for a binding that took the old one from another store such as *Web Hosting* (a restore puts that store back);
   - **Remote Desktop** (RDP-Tcp);
   - **the WinRM HTTPS listener**.

5. With full PowerShell, each https port is asked which certificate it serves (in Constrained Language Mode the bindings are read back only).

Anything fails: the bindings go back to the old certificate. **The old certificate stays in its store**, so putting it back is only a rebinding. A binding that cannot be put back makes the result `FAILED ... rollback FAILED: <binding>`, never `ROLLED BACK`.

The renewal folder (`win_cert_renew_dir`) is used only when SYSTEM, the Administrators or the job's own account alone own and can change it and everything in it: one that others can change (any account can make a folder in ProgramData) holds every certificate of that server (`HELD`), and the renewal makes no CSR there - the reason names who and which file. Delete the folder (the next renewal makes it again) or fix its owner and permissions.

A request you name (opened by hand, or after an incident)

The check finds each renewal's request by itself: the renewal ordered it, and the request carries its CSR. When the certificate came another way - someone opened the PKI's request by hand and pasted the renewal's CSR into the form, the CSR went on an incident (`cert_renew_servicenow: incident`) and a person ordered it, or the PKI opened a new request - **name the request** and the check reads that one instead:

```yaml
cert_install_ritm: RITM0012345           # or several: "RITM0012345, RITM0012346"
```

- **What it reads:** the requests named - the RITM, its REQ, its catalog tasks (SCTASK), their attachments and pasted certificates, as always - however they were opened. The renewal's CSR need not be on them.
- **What it takes:** the certificate whose public key is the public key of a renewal waiting on a host - the key and CSR the renewal left in `cert_renew_dir` (Linux) or the pending request (Windows). The CSR saved on the host is what the certificate is compared with; nothing else on the request is ever used.
- **Then as always:** the plan, `NEEDS APPROVAL`, the approval, the install, the work note on the request named.
- **The other renewals** (no certificate for them there) are counted in one line, not listed: `NOT ON IT | 2 renewal(s) waiting on these hosts have no certificate on RITM0012345 - they wait for their own request`. Nothing on the request fits any of them: `NOTHING TO INSTALL | RITM0012345: no certificate there fits a key waiting on these hosts`, with the certificates found there - the PKI signed some other CSR.
- **The CSR must be the renewal's.** A CSR made by hand on the server has a key the job does not know (where it is, which service uses it): install that certificate by hand. The renewal's CSR is on its incident, or on the host - `/etc/pki/tls/renew/<name>.csr` (Linux), `C:\ProgramData\site-automation\renew\<name>.csr` (Windows).

In AAP: a **Survey** on the workflow (its Survey tab > Create question, then switch the survey on): question `Request (RITM) with the issued certificate - empty: every renewal's own request`, answer variable name `cert_install_ritm`, Text, **not required**. The daily schedule leaves it empty (automatic); launch the workflow by hand with a number for the one-off. The approved job needs nothing: it installs the approved plan.

Never automatic - a person installs it (BY HAND)

The job lists these with the steps, and never touches them:

Linux	Windows
a keystore (Java: its program needs a restart)	SQL Server uses it (a restart)
a certificate seen only on a port (its file not known)	a Central Certificate Store binding (a file on the share)
	an https binding with a setting the job does not give back (Disable HTTP2, Reject Connections... set), or one `netsh` prints in another language than English (its settings are not read)
a service that cannot reload (only a restart)	the WinRM HTTPS listener **AAP connects through** (it would cut the job)
the port is served by a container or a user's program	a binding kind not in `win_cert_install_rebind`
a path in `cert_renew_install_notes` (something else deploys it - STIG Manager's comes from an AAP credential)	
a service in `cert_install_never_reload`	
an AAP host (groups `aap`, `aap_hosts` - its installer manages its certificates)	**an AAP host**

Held for a person (HELD)

Something to look at first; the next run checks again.

- the certificate is not for the key on the host, not valid yet, expired, or valid fewer than `cert_install_min_days` (30) more days;
- it lacks names (subjectAltName) the old one had (`cert_install_fewer_names: true` installs it anyway);
- its chain does not build up to a root - keep a CA bundle that has its issuer (below), or attach the chain (.p7b) to the request (or `cert_install_trust_check: false`);
- the file no longer holds the certificate the CSR was made for (replaced since);
- the old key not found, or found in several files - name it: `cert_install_key_files`;
- the old key is also another certificate's key (replacing it would break that one);
- no service found that uses the file - name it: `cert_install_services`;
- Windows: the pending request (the new key) is gone from the server - the next renewal makes a new CSR.

When the PKI sends only the .cer: a CA bundle

The PKI usually puts only the issued certificate (.cer) on the request. vCenter must trust its issuer before an ESXi host gets it, and a Linux or Windows server needs the chain to build, so without the chain the check says `HELD`. Keep the DoD PKI's CA bundle in **your** repository once, and every certificate install check - Linux, Windows, VMware - completes the chain from it:

1. Download the bundle: cyber.mil's PKI/PKE pages, *PKI CA Certificate Bundles: PKCS#7 for DoD PKI Only* - the zip `unclass-certificates_pkcs7_DoD.zip`. (The job *PKI - DoD bundle check*, below, downloads and checks it for you and emails the checked file.)
2. Put the bundle's `Certificates_PKCS7_v5_xx_DoD.der.p7b` in your repository as `playbooks/files/dod_pki_bundle.p7b` (the zip as downloaded works too). Commit and push it; sync the

project in AAP.

3. In `all.yml`: `cert_install_ca_bundle: files/dod_pki_bundle.p7b`.

Your copy is yours: the release zips never carry a file the public repository does not have, so pasting an update never touches it. (If you use `scripts/update-from-release` instead of pasting, add the line `playbooks/files/dod_pki_bundle.p7b` to `.site-local` - that script deletes files it does not know, except the ones listed there.)

What is taken from it: only the CAs that signed the certificate - its issuing CA and that CA's root - each found by its name **and checked by its signature**, none expired. A CA of the same name with another key is never taken. A chain on the request comes first; the bundle fills only what it lacks. vCenter gets only those (`add the CA chain to vCenter's trusted roots` - nothing when it already trusts them), never the whole bundle. The job output lists what was read: `cert_install_ca_bundle (48 CA certificate(s)): the chain's CN=DOD ID CA-70,...; CN=DoD Root CA 6,...`.

A bundle set but not there or not a bundle: the check stops and says so, rather than holding everything for a reason that would mislead.

Keeping the CA bundle current

DISA adds issuing CAs now and then (a new ID CA-xx); a certificate from one your copy lacks is `HELD` again. The job **PKI - DoD bundle check** (`playbooks/pki_bundle_check.yml`), on a schedule (weekly), downloads the bundle, checks it, compares it with your copy, and emails you when it differs - the checked `.p7b` attached:

```
NEWER - it differs from yours: put it in your repository (below) |
  Certificates_PKCS7_v5_15_DoD.der.p7b | version 5.15 | 50 CA certificates; yours 48 (version
  5.14)
DISA signature on its list of files: verified | the files' SHA-256: match
ADDS CN=DOD ID CA-82,OU=PKI,OU=DoD,O=U.S. Government,C=US (until 2032-03-01)
The checked bundle: Certificates_PKCS7_v5_15_DoD.der.p7b - attached to the email; save it as
  playbooks/files/dod_pki_bundle.p7b in your repository
```

You save the attachment over your copy, commit and push - the job writes nothing in your repository.

How it is checked, before it is offered:

- **DISA's signature.** The zip carries a list of its files' SHA-256, signed by the DoD PKE code signing certificate. The job checks that signature against the roots of **your** copy, and each file's SHA-256 against the list. DISA signs it with SHA-1, which a FIPS-mode system refuses: then the job says `not checked: this system refuses SHA-1 signatures` and relies on the next check alone. (The signature check needs the `openssl` command in the execution environment; without it, also `not checked`.)
- **Every CA, by its signature, up to a root of yours.** A root that is not in your copy (DISA adds one) is listed with its SHA-1 - compare it with DISA's before you use the bundle; with DISA's signature verified it counts, without it the CAs under it are refused and the job fails.
- **No copy of yours yet** (`cert_install_ca_bundle` empty): its roots are taken on trust and listed with their SHA-1
- compare them with the ones DISA publishes (the bundle's README.txt says where) the first time.
- **Signature not checked** (a FIPS-mode execution environment, or a copy on a share without DISA's signed list): a bundle that differs from yours is `NOT VERIFIED` - listed with what it adds and removes, but not attached and not offered. Check it where the signature can be checked, or compare its roots' SHA-1 with DISA's and download it by hand; `pki_bundle_accept_unverified: true` makes the job offer such a

bundle anyway.

- CAs in it that have already **expired** are listed (`EXPIRED`), as are the ones expiring soon.

Setting	Default	
`pki_bundle_url`	DISA's zip (`https://dl.dod.cyber.mil/../unclass-certificates_pkcs7_DoD.zip`)	or a copy on a file share the execution environment mounts (a path) when AAP has no way out
`pki_bundle_proxy`	`""`	`http://proxy.yoursite.mil:8080` when the way out is through a proxy
`pki_bundle_validate_certs` / `pki_bundle_ca_path`	`true` / `""`	the download site's certificate
`pki_bundle_email` / `pki_bundle_email_when`	`true` / `newer`	email it (to `report_email_to`) only when it differs or the check fails; `always` = every run
`pki_bundle_fail_when_newer`	`false`	`true` = the job ends red on a newer bundle (an AAP notification on failure tells you)
`pki_bundle_warn_days`	`90`	CAs of the bundle expiring within these days are listed
`pki_bundle_accept_unverified`	`false`	`true` = offer a bundle that differs from yours although DISA's signature on it could not be checked (FIPS mode, a copy without the signed list)

The template: **PKI - DoD bundle check**, playbook `playbooks/pki_bundle_check.yml`, the execution environment of the other jobs, no credential (the email goes through the relay in `all.yml`), no Limit; a weekly schedule.

Which service, which key (Linux)

Found by itself:

- **the service** - the configuration of httpd, nginx, haproxy, postfix, dovecot, slapd or cockpit that names the certificate's file (`cert_install_known_services` to change the list), and the program listening on the port the certificate report saw it on;
- **the old key** - the file the same configuration names (`SSLCertificateKeyFile`, `ssl_certificate_key` ...), else the one file with the old certificate's key in the certificate's folder, a `private/` next to it, and the usual folders (`/etc/pki/tls/private` ... - `cert_install_key_dirs` adds yours).

For the rest, in `all.yml`:

```yaml
cert_install_services:                    # a file no configuration names -> the service to reload
  - {path: '/opt/app/tls/*.crt', service: app}
cert_install_key_files:                   # when the old key cannot be found, or is in several
                                          # files
  /etc/pki/tls/certs/db01.crt: /etc/pki/tls/private/db01.key
cert_install_never_reload: ['slapd*']     # services the job never reloads: their certificates are
                                          # installed by a person
```

Setting it up

1. **The renewal orders from the catalog** (`cert_renew_servicenow: catalog`) - CERT_RENEWAL_CATALOG.md.
2. **The PKI puts the certificate on the request.** Ask them to attach DISA's files to the RITM or to its catalog task (or paste the certificate into a work note there) - the .cer, and the chain (.p7b) if they have it; only the .cer is fine with a CA bundle (above). The API account must be able to read the request's and its tasks' attachments and journal (and, for the note after the install, write a work note on the RITM).
3. **The job templates** (project: this repository, the same inventory as the renewal):

Template	Playbook	Credentials	Options
Certificate install - check	`playbooks/cert_install_check.yml`	Machine, ServiceNow API	Job type **Check** allowed
Certificate install - approved	`playbooks/cert_install_approved.yml`	Machine, ServiceNow API	Variables **not** prompted on launch; no Limit
Certificate restore	`playbooks/cert_restore.yml`	Machine	Limit and Variables prompted on launch
Windows certificate install - check	`playbooks/win_cert_install_check.yml`	Machine (Windows), ServiceNow API	
Windows certificate install - approved	`playbooks/win_cert_install_approved.yml`	Machine (Windows), ServiceNow API	Variables **not** prompted on launch; no Limit
Windows certificate restore	`playbooks/win_cert_restore.yml`	Machine (Windows)	Limit and Variables prompted on launch

The settings each one reads: `aap/extra_vars/<playbook>.yml`.

4. **The workflow** (Templates › Add › Add workflow template), one for Linux, one for Windows:

Step	Node	Link
1	*Certificate install - check*	(start)
2	*Approval* - name `Install the certificates the check listed?`, **Timeout** e.g. 8 hours. Description: `Open the check job: its READY lines say what each one changes.`	**Run on fail**, from 1
3	*Certificate install - approved*	**Run on success**, from 2

The approved job **must have the check job's inventory and no Limit**: a host of the plan it does not run on makes it stop before anything is installed.

5. **The survey** (optional, for a request opened by hand): on the workflow, a question with the answer variable `cert_install_ritm`, not required (above).
6. **The schedule:** the workflow daily (e.g. 07:00, after the certificate watch), or a few times a day during working hours.
7. **Try it first:** the check with Job type **Check** and a Limit of one host - the same READY lines, nothing sent. The approved job launched as **Check** from the workflow says `WOULD INSTALL` and changes nothing.

Put the old certificate back

Linux - *Certificate restore*, with a Limit:

- Job type **Check**, no variables: it lists the backups on the host (`backup <date>-<certificate> | subject | made ... | files`).
- Then `cert_restore_only: web01` (the newest backup of each certificate whose name or subject matches) or `cert_restore_backup: <a backup's folder name>`: the files go back with their owner, mode and SELinux label, the configuration is tested, the service reloaded, and the port must serve the old certificate again.

Windows - *Windows certificate restore*: the same, with `win_cert_restore_only` / `win_cert_restore_backup` - each binding the install moved goes back to the old certificate (it stayed in Personal).

After a restore the renewal **waits again**: the next install check finds its certificate and asks for the approval again. Leave it waiting while you look at what went wrong (deny the approval), or let the old certificate run out and renew again.

When it goes wrong

The job says	Means	Do
`WAITING ... no certificate for this key on it yet`	the PKI has not put it there, or put another one	look at the request: `others` lists certificates there for another key
`NOT ORDERED ... no catalog request carries this CSR`	the CSR went another way (by hand, an incident)	name its request: `cert_install_ritm` (the survey); or order with the catalog
`NOTHING TO INSTALL - RITM...: no certificate there fits a key waiting on these hosts`	the request named has no certificate yet, or one for another CSR (made by hand, or a renewal on a host the job did not run on)	the certificates found there are listed; check the Limit, or install it by hand
`CLOSED ... its request was closed Closed Incomplete`	the PKI rejected it	the renewal orders it again
`HELD ... its chain does not build up to a root`	the chain did not come with it, or its root is not trusted on the host	a CA bundle with its issuer (`cert_install_ca_bundle`; a newer one from *PKI - DoD bundle check*), or attach the chain (.p7b) to the request; or `cert_install_trust_check: false`
`cert_install_ca_bundle ... cannot be read` / `holds no CA certificate`	the file is not in the project (not pushed, not synced) or not a bundle	push it, sync the project; the .p7b, a .pem or the zip
PKI - DoD bundle check: `could not be downloaded`	no way out from the execution environment	`pki_bundle_proxy`, or a copy on a share in `pki_bundle_url`
PKI - DoD bundle check: `FAILED`	a file not as DISA signed it, or CAs under a root that nothing vouches for	do not use it; download it again by hand and compare
PKI - DoD bundle check: `NOT VERIFIED`	it differs from yours, but DISA's signature could not be checked (FIPS mode, no signed list with the copy)	check it on a system that can, or compare its roots' SHA-1 with DISA's; `pki_bundle_accept_unverified: true` to have it offered
`HELD ... no service found that uses ...`	no known configuration names the file, no port known	`cert_install_services`
`ROLLED BACK ... the configuration test of httpd.service failed`	the new files do not fit the configuration	the job output has the test's message; the old files are back
`ROLLED BACK ... after the reload, 127.0.0.1:443 serves ...`	the service still serves something else after the reload	the configuration may name another file - the old files are back

The job says	Means	Do
`FAILED ... the old files are back, but systemctl reload httpd.service failed again`	the old files went back, but the service did not reload: it may still run on the rejected certificate, or be down	`systemctl status httpd.service` on the host, then reload or restart it by hand - the files on disk are the old ones
`FAILED ... the old files are back, but 127.0.0.1:443 does not serve the old certificate again`	reloaded, but the port serves something else	the configuration may name another file; look at what the port serves
`FAILED ... the old files could NOT all be put back` (also the restore: `nothing was put back`)	a copy in `cert_renew_dir/backup/<name>/files` is missing or damaged	the reason says which: `nothing was put back` leaves the new files in place; otherwise it names which files hold the old and which the new - put them right by hand
`REFUSED ... changed since the approval`	between the check and the approval, a file, a binding or a service changed	the next check plans it again
`The approved plan has certificates for X, which this job does not run on`	the approved template's inventory or Limit	the check job's inventory, no Limit
`FAILED ... certreq -accept -machine did not put it in Personal` (Windows)	its chain is not trusted on the server (0x800b0109), or the pending request is not this one	the DoD roots in Trusted Root; nothing else was changed
`ipport=0.0.0.0:443: the port was not asked (... does not answer)` (Windows)	nothing listens on that port now (the site is stopped), or Constrained Language	the binding was read back and is on the new certificate; browse to the site to see it
`the work note was refused`	the API account may not write to the request	nothing else: the job output says what was installed

Limits

- **Tested** against a stand-in ServiceNow (`tests/servicenow/snmock.py`), a test CA and a stand-in web server (`tests/certs/run_cert_install_test.sh`); the Windows script with stand-ins in Windows PowerShell 5.1 and 7, normal and Constrained Language (`tests/windows/test_win_checks.ps1`), and for real on a Windows Server runner: the renewal's CSR, `certreq -accept`, an HTTP.sys binding moved and served, the restore (`.github/workflows/check.yml`, *Windows certificate install, for real*).
- **Not automatic:** Cisco certificates (install them as NETWORK_CERTS.md says); a service that needs a restart. vCenter and ESXi have their own install with an approval (VMWARE.md).
- **The CA bundle:** one certificate of the DoD bundle (DoD Root CA 4, an EC root) is written in a way the Python library of the execution environment (cryptography 50) no longer reads; it is left out - a certificate under that root still needs its chain on the request. The others (48 of 49 in version 5.14) are read.

- **One host at a time per certificate:** a certificate found on several hosts (a wildcard) has a CSR - and a key - per host, so each host installs its own.

34. Emailed reports: the formatted email and its look

Jobs can email what they found or did, as a **formatted (HTML) report** with a plain-text copy for mail clients that do not show HTML. One email per job run, whatever the number of hosts.

Which jobs email

Template	Playbook	The email
Health check (Linux)	`health_check.yml`	findings of every host (critical first), hosts that did not report, healthy hosts
Windows health check	`win_health_check.yml`	the same, for Windows servers
Database health	`database_health.yml`	the same, for the database check
Certificate report (Linux / Windows)	`cert_report.yml`, `win_cert_report.yml`	findings, plus every certificate, soonest expiry first: red expired, amber within 30 days, blue within 60
POA&M status	`poam_status.yml`	overdue, due-soon and missing items
ServiceNow health	`servicenow_health.yml`	the instance and the MID Servers
Troubleshoot (Linux / Windows)	`troubleshoot.yml`, `win_troubleshoot.yml`	what the checks found
Apply approved ACT fix	`act_fix_approved.yml`	the checks after the fix
VM secure boot report	`vm_secure_boot_report.yml`	VMs with secure boot off, BIOS VMs (folder, host, guest, IP)
VM datastore report	`vm_datastore_report.yml`	datastores 85 / 90 % used or more, then every datastore, fullest first
VM snapshot report	`vm_snapshot_report.yml`	snapshots older than N days, kept ones, then every snapshot with size and age
VM snapshot cleanup	`vm_snapshot_cleanup.yml`	what was deleted (and the space freed), what could not be
VM alarms report	`vm_alarm_report.yml`	triggered alarms, host connection, failed logins, VM events, other errors and warnings, configuration issues, every host - each row coloured by severity
VM alarms ACT analysis	`vm_alarm_act_analysis.yml`	per problem: ACT's likely cause, evidence, fix and confidence (coloured); what to do first
Active Directory health report	`ad_health_report.yml`	domains, domain controllers, FSMO, replication, dcdiag, DNS, time, events, clients in no site, certificates, trusts, sites, then the day's changes (privileged groups, accounts, GPOs, schema and configuration) - problems first, coloured (ACTIVE_DIRECTORY.md)

Template	Playbook	The email
NetApp ONTAP health report	`ontap_health_report.yml`	clusters, nodes, health alerts, events, hardware, disks, network, aggregates, volumes, inodes, snapshots, SnapMirror, SVMs, CIFS, LUNs, certificates - problems first, coloured (NETAPP.md)
Cisco UCS inventory	`ucs_inventory_report.yml`	domains, not operable, fabric interconnects, chassis with IO modules, server models with BIOS and CIMC versions, every server, firmware in use, critical and major faults; an Excel workbook of all of it
Horizon health report, capacity report, desktops check, session cleanup, image push plan	`horizon_*.yml`	Connection Servers, gateways, vCenter, AD, event database, license, pools; each pool's use; the broken desktops; the sessions logged off; the push plan (HORIZON.md)
VM capacity planning	`vm_capacity_report.yml`	overall and per cluster: CPU, memory with a host down, vCPUs per core, VMs that fit, hosts recommended, datastores with runways; with GenAI, its estimate next to the math
VMware certificate report	`vmware_cert_report.yml`	every certificate of vCenter and its hosts, soonest expiry first (expired red, due amber), and for each one due what the renewal would do; the hosts not checked
VMware certificate renewal	`vmware_cert_renew.yml`	the certificates due (expired red, the rest amber): the ticket and the CSR of each, or why none; every certificate of vCenter and its hosts, soonest expiry first; the hosts not checked
ESXi security settings	`esxi_security.yml`	the hosts it changed (what), the ones that failed (why), every host's settings before the run. By default only when a host was changed or failed
VM deploy from a ServiceNow ticket	`vm_deploy_from_ticket.yml`	the VM (IP or MAC, where it went), the request with where each value came from; in the workflow's first step, where it would go - for the approver

Template	Playbook	The email
VM deploy settings finder	`vm_deploy_inventory.yml`	the clusters, templates, datastores and folders by the names the deploy uses, what to look at first, and the lines to paste into the deploy template's Variables
VM request pickup	`vm_deploy_poll.yml`	the tickets picked up and their workflow jobs, the ones not started (why), the ones skipped. Only when it started something or something failed
VM restart, shut down, snapshot, delete snapshot, notes, change VLAN	`vm_*.yml`	what was done to which VM

Turning it on

1. **The mail relay, once**, in your `playbooks/group_vars/all.yml` (then Commit, Sync Changes, and sync the project in AAP). A relay that accepts the AAP server by a whitelist needs nothing more:

```yaml
report_email_smtp_host: smtp.yoursite.mil
report_email_from: aap-noreply@yoursite.mil
report_email_security: none          # only if the relay does not offer STARTTLS
```

Encryption, your own CA and a relay login: VMWARE.md, "Email the report".

2. **Who gets each report: on each template.** Templates > the template > Edit > **Variables**:

```yaml
report_email_to: linux-team@yoursite.mil, ops@yoursite.mil
```

Or a survey question with the variable `report_email_to` (Text, not required) - but what is typed there **replaces** the list. To let people **add** someone for one run, use the "Also email the report to" question instead (next section). Putting `report_email_to` in `all.yml` instead makes **every** job in the table above email those people, each time it runs - usually more than you want.

Not in an AAP inventory **group's** Variables: the email is sent by the AAP side of the job, which never gets a group's variables. The template's Variables, a survey, the inventory's own Variables and `all.yml` all work.

Setting	Default	What it does
`report_email_to` / `report_email_cc`	(none)	who gets it; a list, or text with commas
`report_email_html`	`true`	send the formatted version too; `false` = plain text only
`report_email_xlsx`	`false`	`true` = attach the report's tables as an Excel workbook ("A workbook attached", below)

Setting	Default	What it does
report_email_theme	standard	the look: standard, command or portal ("The look", below)
report_logo_file	(none)	your logo in the header, e.g. files/report_logo.png
report_email_html_template	report.html.j2	your own look instead (below)
report_email_subject_prefix	[AAP]	put before every subject

The subject is the report's title with its counts, e.g. `[AAP] Health check: 3 finding(s) on 2 of 48 host(s)`. Every email ends with the AAP job number, the template, who started it and when. A dry run (Check) sends nothing. A job without `report_email_to` says `No email: report_email_to is not set`.

All settings, with their defaults: site_email.

Also email the report to (asked at launch)

Whoever launches a report template can send that run's report to more people: a box **Also email the report to** in the template's survey. What is typed there is **added** to the template's own `report_email_to` - never in its place - for that run only. A blank box changes nothing, so schedules and runs nobody fills in work as before. A template without `report_email_to` emails only the people typed in the box (and nothing when it is blank).

Add the question to every report template at once with the job template **AAP - report email question** (`playbooks/aap_email_question.yml`, nothing but the **Red Hat Ansible Automation Platform** credential, no inventory hosts needed - localhost). Its AAP user needs the **Admin** role on the report templates and their workflows. It finds them through AAP's API **by their playbook**, so your own template names work, and:

- adds the question at the end of each one's survey; a template without a survey gets one, with this question alone, turned on;
- adds it to every **workflow** that runs one of them too - AAP never asks a job its own survey inside a workflow, only the workflow's, and the answer then reaches every report step of it (in Certificate watch, the people typed get one email per step that emails);
- leaves a survey that is **turned off** off (turning it on would also ask its other questions, and their defaults would reach every run): the job lists those - turn the survey on by hand if you want it there;
- leaves a question that is already there as it is, so you can reword it in AAP and run the job again;
- points out a survey that asks `report_email_to` itself (that one replaces the list).

Run it with **Check** first: it then only reads and lists, per template, what it would do. Run it again after you add report templates. `aap_email_question_state: absent` takes the question out again (a survey left with no question is removed and turned off). Settings: aap_email_question

- e.g. `aap_email_question_project` (only your project's templates), `aap_email_question_exclude`, `aap_email_question_text` (the question's wording).

What people can type: addresses separated by commas, semicolons, spaces or one per line (a column pasted from Excel works), or pasted from Outlook (`Doe, Jane <jane.doe@yoursite.mil>; Roe, Rick <rick.roe@yoursite.mil>`). Each address gets one email, even when it is in `report_email_to` too. Text that is no address is listed in the job (`Email | not sent to these`) and the report still goes to everyone else.

Only your own domains - so a report never goes outside by a typo - in `all.yml`:

```yaml
report_email_also_domains: [yoursite.mil]     # a subdomain too (mail.yoursite.mil); empty = any
                                              # domain
```

An address in another domain is listed in the job, with why, and gets no email. The usual recipients in `report_email_to` are not checked against it.

The same rules as the usual recipients. A job that emails only when something happened - ESXi security settings (only when a host was changed or failed), the snapshot cleanup with `vm_snapshot_cleanup_email_only_if_deleted`, the VM request pickup - sends the people typed in the box nothing either when nothing happened; the job's output says why (`No email: ...`). And the mail relay must be set up (`report_email_smtp_host`, `report_email_from` in `all.yml`): without it, a report launched with an address in the box fails at its email step - the setup job warns when it is not set.

By hand instead: Templates > the template > **Survey** > Add question - question *Also email the report to*, answer variable name `report_email_also`, answer type **Textarea** (a one-line Text box drops the line breaks of a pasted list), **Required** off, no default; then turn the survey on. For a workflow, the same on the workflow.

Green or red: when a report finds problems

AAP shows a job as **successful (green)** or **failed (red)**, nothing in between. What a report job does when it finds problems:

Job	Default	Change it with (template Variables)
VM secure boot report, VM datastore report, VM snapshot report	**green**: the report and email say what to fix	`vm_secure_boot_fail: true` / `vm_datastore_fail: true` = red
VM snapshot cleanup	green; **red** when a deletion failed	-
VM alarms report	**green**: the report and email say what is wrong	`vm_alarm_fail: true` = red on a critical alarm or a host not connected
VM alarms ACT analysis	green; **red** when ACT could not run (no key, no network): the email still lists the problems	-
VM capacity planning	**green**; red when GenAI was asked for and could not run	`vm_capacity_fail: true` = red when a cluster or datastore is critical
ESXi security settings	green; **red** when a host could not be set (the email says why)	-
NetApp ONTAP health report	**green**: the report and email say what is wrong	`ontap_report_fail: true` = red on a critical finding or a cluster not read
Horizon health and capacity reports	**green**: the report and email say what is wrong	`horizon_health_fail: true` = red on a critical finding or a full pool
Health checks, certificate reports, database health, POA&M, ServiceNow health	**red** when there are findings: AAP workflows start tickets (and ACT) from that	`site_fail_on: []` = green, report only

So for a template whose job is to email a report to people, set `site_fail_on: []` and it stays green; the email is the alert. Keep the default on templates that feed a ticket workflow.

Red also means one of these, whatever the setting: a host could not be reached, or the job itself broke (a wrong setting, a missing credential). Those always need a look.

What a report looks like

A title (also the subject) in a coloured band - green, amber, red or blue - then summary boxes with numbers (each with a short line under it saying what it counts: *Critical 1 - act now*), then a **Start here** section where a report has something to act on, then sections: each a heading, a line of advice, and a table (or a list). In tables that have a severity, each row is tinted (light red, amber or blue) and the severity cell is filled in its colour, so the problems stand out at a glance. Every value from a host or vCenter is escaped, so a VM name cannot add markup to the email.

In the Checklist import email (workflow 40's check), a long collection, STIG or host name wraps after `_ . - / \` and commas, so its tables keep to 1280 px (1.45.0). A copied name is the name as it is, and other reports' tables are unchanged. Classic Outlook keeps a long name on one line.

Start here is the short list of what to act on first, as cards ordered by priority: a coloured bar and a chip (Critical, Warning, Not checked ...), what kind of thing it is on the right (Certificate, Storage, SLA ...), what was found, the host in monospace, and **Next ->** with the step - a command to look further in its own monospace box. The health checks, the certificate reports, database health and the other findings reports show their most urgent findings there (critical first, at most six; every finding stays in the tables below) and a *Not checked* card for the hosts that did not report. The ServiceNow weekly activity report has none: it summarizes the week's work.

The look: standard, command, portal or glass, your logo, the last runs

`report_email_theme` picks one of four looks, for every report job at once when it is in `all.yml`:

- **standard** (the default): the header band in the report's colour, number boxes under it - as described above. Since 1.18.0 the boxes go four to a row, as in portal and glass, so a report with many numbers fits an 800 px window. Since 1.30.0 the four are one width.
- **command**: a dark header with your logo, a small line of text above the title (`report_email_header_text`, default `Site automation report`) and the status as a label beside it; under it **the job's last runs** as a strip of bars, oldest first, this run last and outlined. A bar's colour is how that run went (green, amber, red; grey = cancelled); its height is the report's first plain number (the VMs checked, the snapshots deleted), against the highest of the strip. Then the numbers in one row, then the sections.
- **portal**: white cards on a pale mint background with a dark green accent, like the AAP portal pages. A header card with your logo, `report_email_header_text`, the AAP job and the status as a pill (Successful, Warning, Critical); the numbers as tiles - a tile that is amber or red gets an outline in that colour; a card with **the job's last runs** (the same bars, rounded) and a line `This run Critical, Last run Successful 2 days ago`; then one card per section. New Outlook, Outlook on the web and phones show the rounded cards and shadows; classic desktop Outlook shows the same layout with square corners.
- **glass**: see-through, frosted cards on a soft blue-green background. A header card with your logo (at most 80 px tall), `report_email_header_text`, the title and the status with what it asks of the reader (*Needs attention*, *Action required*); the numbers as tiles with an icon - a warning or critical tile tinted in its colour; **the job's last runs** with a colour key, beside *This run* and *Last run*; then one card per section, its

table on a near-solid white panel. Only the frame is see-through: every text stays on a surface solid enough to read as on paper (the lightest text is at least 4.5:1 against what is behind it). The inbox shows the subtitle and the warning and critical numbers as the line under the subject; with the report website (`report_web_dest`) the email ends with an **Open the full report** button. On a phone the tiles go two by two, and a table of up to 8 columns scrolls sideways in its card. A table of 9 columns or more becomes one block per row under 861 px, its cells as *LABEL value* pairs (1.46.0). A table of 11 columns or more has tighter cells, so it fits a 1280 px window; classic Outlook shows the table as it is. Mail programs that draw transparency, rounded corners and shadows show the glass; the others (classic desktop Outlook) show the same layout with solid white cards and square corners. On the report website (`report_web_theme: glass`) the page adds what a browser draws and a mail program does not: the blur behind the cards, line icons, and a plain print.

The report website has a look of its own, **atlas** - its default since 0.43.0: light and dark with a switch, status chips with check marks, tables that sort and filter (WEB_REPORTS.md, "The look") - or, since 0.92.0, **brief** (the same page read like a morning brief: "The brief look" there). Neither is ever an email's: `report_email_theme: atlas` (or `brief`) stops the job and says so. The emails keep their own look whichever the website has.

playbooks/group_vars/all.yml

```
report_email_theme: command                 # or portal, or glass
report_web_theme: atlas                     # the report website's look (the default, or brief;
                                            # docs/WEB_REPORTS.md)
report_logo_file: files/report_logo.png     # = playbooks/files/report_logo.png
```

The logo (every look): a PNG (best, with a transparent background), JPEG or GIF in your repository. Put it in `playbooks/files/` and set `report_logo_file` (a path from `playbooks/`, or a full path). It is attached to each email and shown from there - Outlook blocks pictures from links - so keep it small: about 160 px tall, under 100 KB. It is shown `report_logo_height` (84) pixels tall; in the portal look's header card at most 56, in the glass look's at most 80. Your logo belongs in your own repository only. If you update with `scripts/update-from-release`, add the line `playbooks/files/report_logo.png` to `.site-local`, or the update deletes it.

The last runs come from AAP - a single email has no memory, AAP does. At the end of each run the report asks AAP for its template's earlier jobs (the last `report_history_runs` - 14 - with this one). For that, attach a credential of type **Red Hat Ansible Automation Platform** to the template: the one the pick lists use works (VMWARE.md, "Pick lists"). Its user must be able to see the template's jobs: give it **Organization Auditor** on the template's organization (AAP 2.5 and later: **Access Management > Users >** the user **> Roles > Assign roles**, resource type **Organization**, your organization, **Organization Auditor**). That is read-only and covers every template in the organization, also new ones. A role on each template works too (JobTemplate Execute includes seeing its jobs, but also lets the user start it). Without it the email goes out as usual, without the strip, and the job says why: `No strip of past runs in the report: ...`. AAP gives no error for jobs its user may not see - it lists none - so before 0.31.1 the strip then showed only this run, every time. Each run keeps its report's status and number in AAP as the job artifact `site_report_run`; runs from before 0.20.0 have none, so their bar shows only how the job ended (green or red), half height. `report_history: false` turns the strip off.

The plain-text copy of the email has the strip as one line: `Last 14 runs, oldest first: ok ok warning ... critical (this run)`.

A workbook attached

`report_email_xlsx: true` - in `all.yml` for every report, or on one template's Variables - attaches the report's tables to its email as an Excel workbook (`.xlsx`): a sheet per table, named by the table's title, its first row the column names (bold, frozen, with filters), numbers as numbers. The file is named after the template and the day: `vm-datastore-report_2026-10-27.xlsx`. A report with no table gets one sheet of its lines. Some reports attach their own workbook whatever the setting says - *VM - inventory report*: every VM on one sheet (`vm_inventory_xlsx`). The workbook is made with Python's standard library: nothing to add to the execution environment. The website gets no workbook; a dry run (Check) makes none.

The classification banner

In a classified enclave every report carries its banner - at the top and bottom of every look and of the plain text, `(SECRET)` before the subject, the first row of the workbook (`site_enclave`, `report_banner`, `report_banner_text`; ENCLAVES.md).

Also on a web page

Every report can also be written as a web page - the same report, in the portal look - on a Windows server (over WinRM), into a folder or onto a web server, with a `latest.html` per template and an index of every report; the job prints the page's address, and the email links to it. With or without the email: WEB_REPORTS.md. Report templates whose execution environment cannot reach that server keep their report for one job that writes the pages for all of them (`report_web_copy`; WEB_REPORTS.md, "The copy job").

Changing the look

The look is one file, `roles/site_email/templates/report.html.j2` (Jinja and HTML, styles inline because Outlook ignores most style sheets). To change it without touching the repository's file:

1. Copy it (or `report_command.html.j2` / `report_portal.html.j2` / `report_glass.html.j2`, the other looks) to `playbooks/files/email/report.html.j2` in your repository and edit the copy: colours, fonts, a banner line your site requires.
2. In `all.yml`: `report_email_html_template: "{{ playbook_dir }}/files/email/report.html.j2"`.
3. Add the line `playbooks/files/email/` to the file `.site-local` at the top of your repository (create it if it is not there). Without it, the next update from a release **deletes** your copy: the release does not have that file.

Check your copy after an update that changes the report layout (the CHANGELOG says so when that happens).

The **title** of a report (the coloured band, also the subject) is written by the playbook, not the look file: for the VMware reports, `_vm_report_subject` in `roles/vmware_vm/tasks/<report>.yml`. An edit there is undone by the next update, unless that file is in `.site-local` - and then you no longer get the release's fixes to it either.

Emailing a report from another playbook

Describe the report as data, then include the role. For example, at the end of a play that runs on localhost:

YAML

```
- name: Email the report
  ansible.builtin.include_role:
    name: site_email
  vars:
    _report:
      title: "Certificate report: 3 expire within 30 days"   # also the subject
      status: warning                    # ok | warning | critical | info: the colour of the band
      subtitle: "212 certificates on 48 servers"           # optional
      summary:                           # optional: number boxes
        - {label: Certificates, value: 212}
        - {label: Expire within 30 days, value: 3, status: warning}
      sections:
        - title: Expire within 30 days
          status: warning
          text: "Renew them before the date shown."        # optional
          columns: [Server, Subject, Expires]
          rows: "{{ my_rows }}"          # a list of lists, one per row, in the order of columns
        - title: Notes
          lines: [one line, another line]                  # a bullet list instead of a table
      footer: "Source: playbooks/cert_report.yml"           # optional
  when: report_email_to | default([]) | length > 0 or report_email_also | default([]) | length > 0
```

A section has `columns` and `rows` (a table; an empty list shows "None."), or `lines`, or just `text`. To colour a table, add `row_status` (one status per row: `critical`, `warning`, `info`, `ok` or `''`; tints the row) and `cell_status` (per row, one status per cell; fills that cell), e.g. `row_status: [critical]` and `cell_status: [[critical, '', '']]` for a red row with a red first cell. A summary box can carry a `note` (the short line under its number), and a section `cards` - "Start here" cards: `cards: [{status: critical, chip: Critical, meta: Certificate, title: "...", subject: web01, next: "Look further:", code: "openssl x509 ..."}]` (chip, meta, subject, next and code optional), drawn with tables so Outlook shows them too. In a play that runs on many hosts, build the rows from `hostvars` and add `run_once: true` to the include, so one email goes out, not one per host.

Troubleshooting

The job's output says what happened to the email, in the task `Email | result` (or `No email`).

You see	It means	Do
`No email: report_email_to is not set`	no recipient for this template	add `report_email_to` to the template's Variables (or its survey)
`Email | not sent to these, from "Also email the report to"`	text in the box that is no address, or an address outside `report_email_also_domains`	the rest got the email; send it again with the address corrected
`Email question | ... FAILED: the AAP user may not change this job template`	the AAP credential's user has no Admin role on that template	give it the Admin role on the template (or its organization's job templates), or leave it out: `aap_email_question_exclude`
`To email the report, set report_email_smtp_host ...` on a report someone launched with an address in the box	the mail relay is not set up, so no report can email	step 1 of "Turning it on", in `all.yml` - or leave the box empty

You see	It means	Do
`... its survey is turned off, and was left off`	the template's survey is switched off	turn it on (Survey > the switch) if you want the question asked there; check its other questions' defaults first
`To email the report, set report_email_smtp_host ... and report_email_from ...`	the relay is not set up	step 1 of "Turning it on", in `all.yml`
`the mail relay ... does not offer STARTTLS`	the relay has no encryption on that port	`report_email_security: none` (or `ssl` with port 465)
`TLS with the mail relay ... failed: ... certificate verify failed`	the execution environment does not trust the relay's certificate	`report_email_ca_path` to the CA file (VMWARE.md, "Email the report"); list `playbooks/files/ca/` in `.site-local`
`could not send the email through ...: ... timed out` or `Connection refused`	the AAP node cannot reach the relay	a firewall rule from the AAP node (and every execution node) to the relay's port
`the mail relay ... refused every recipient`	the relay does not accept mail from the AAP node, or for those addresses	ask the mail admins to add the AAP node's address to the relay's allowed list
`emailed "..." to ...` but nothing arrives	the relay accepted it; something after it held it	look in junk / quarantine; ask the mail admins to trace it by the subject; check that `report_email_from` is an address they allow
`DRY RUN: would email ...`	the job ran as Check	nothing: a dry run never sends
The email shows plain text only	`report_email_html: false`, or a mail gateway removed the HTML part	ask the mail admins whether HTML mail is stripped; the text copy has the same tables
`No logo in the email: ... is not there, or not a PNG, JPEG or GIF`	`report_logo_file` points at nothing (a path from `playbooks/`, e.g. `files/report_logo.png`)	check the path and that the file is committed and synced
`No strip of past runs in the report: no AAP connection`	the template has no AAP credential	attach the "Red Hat Ansible Automation Platform" credential ("The look", above)
`No strip of past runs in the report: The AAP user ... cannot see this template's jobs` (before 0.31.1: the strip shows only this run, run after run)	AAP lists only the jobs its user may see: the credential's user has no role on the template or its organization - or the credential is for another AAP	give that user Organization Auditor on the template's organization ("The look", above), or attach the credential of this AAP
`No strip of past runs in the report: AAP refused the list of this template's jobs (HTTP 403)`	the credential's user may not see the template	give that user Organization Auditor on the template's organization ("The look", above)

You see	It means	Do
`No strip of past runs in the report: AAP refused the login (HTTP 401)`	the credential's user name or password is wrong	fix the credential
The job is red, but the email came	a check report found problems (`site_fail_on`)	by design for ticket workflows; `site_fail_on: []` on email-only templates ("Green or red")

35. The report website: every report as a web page

Every report job (EMAIL_REPORTS.md, "Which jobs email") can also write its report as a **web page**: the same report as the email, in the **atlas** look - made for a browser, light and dark ("The look", below) - with your logo. Each run gets its own page, each template a `latest.html` that is always its newest run, and an `index.html` lists every report, worst first, each opening to its last 5 runs, with a tab per area (VMware, Linux, Windows...). Older runs' pages are deleted. The report's data is written as JSON beside each page, so a web developer can build their own site on it.

It works **without email**: set `report_web_dest` and leave `report_email_to` empty. With both set, the email carries a link to its page ("Open this report in a browser").

Each report job writes its own pages. When some report templates run in an execution environment that cannot reach the web server (a Windows server needs WinRM, and with NTLM blocked Kerberos, in the execution environment), let **the copy job** write them instead: one template, in the execution environment your Windows jobs use, writes every report job's pages ("The copy job", below).

The job prints the page's address, and keeps it as the job artifact `site_report_url`:

```
TASK [site_email : Email | the report's address]
ok: [localhost] => {
    "msg": "Report:
      https://reports.yoursite.mil/linux-certificate-trust-report/2026-10-23_0605_job-907.html"
}
```

The look

The website has its own look, **atlas** (`report_web_theme: atlas`, the default) - or **brief** (0.92.0, below); the emails keep theirs (`report_email_theme`: standard, command, portal or glass - EMAIL_REPORTS.md, "The look"). Atlas and brief use what a browser draws and a mail program does not, so neither is ever an email's look:

Since 0.53.0:

- **Wide, and easy to read.** The page uses up to 1760 px, with side margins that grow with the window. Tables use all of it, while words stay at a length you can read (about 80 to 90 characters a line).
- **Columns sized by what they hold.** Each column is sized from its values:
- **numbers:** right-aligned, every digit the same width (`1,200` lines up with `37`);
- **short values** (hosts, dates, ids up to 24 characters): kept whole while the table fits (below);
- **ids like `V-257800 (RHEL-09-412035)`:** broken at a space only, not at a hyphen, while the table fits;
- **titles and findings:** given room to wrap;
- **paths, addresses and hashes:** shown in a fixed-width font and broken after a `/` or `\`. A long path never runs off the edge, and nothing is added to what you copy.
- **A table wider than its card fits anyway (1.21.0).** Nothing is cut off and no column is hidden. The page's script takes these steps, one at a time, only while the table still does not fit:
  1. Short values and long status chips wrap at their spaces and hyphens; long columns get smaller minimum widths.
  2. Cells get tighter, headings wrap at their spaces, and a word of over 12 characters in a text column (a long name inside a sentence) may break inside. A shorter word, and any word of a short value or a

status chip, never does. A text column keeps 10 characters.

3. Numbers wrap at their spaces (`12,050.0` / `GB`), never inside their digits; the table's type and its chips get smaller.
4. Before the last step, the section rail is put away for this page, so the tables get its room. The rail's button brings it back; this is not kept for the next page. Then long chips get narrower (3 to 4 lines) and cells tighter.

At every step these stay whole: a date, a time, an IP address (`2026-10-20`, `18:14`, `192.0.2.45`, `192.0.2.0/24`; a date and its time may sit on two lines), a number (`16,210`, `6338`, `59%`), a status chip of up to 12 characters (`3 of 4`) and every word of a heading. A longer chip wraps to 2 or 3 lines, not one word a line. A date inside a file name or a command (`app.2026-10-20.log`) is part of that name and may break with it.

Whole values come first: a table that does not fit with them whole after the last step goes back one step, breaks no text word inside (a path or a command still breaks where it must), and scrolls sideways inside its card, with a shadow at the edge. The page itself never scrolls sideways. Which tables do that depends on the browser, the width and how long the values are: in the tests, with the rail put away, a few of the widest (ONTAP hardware's controllers, VM health's hosts, VM capacity's clusters) at 1280 px and, in Firefox, at 1366 px; with the rail brought back by its button, at some wider widths too. Without the script (a blocked script), a wide table keeps its normal widths and scrolls inside its card.

- **Quick on big tables.** Each table remembers its card's width and its step: opening or closing a section, a filter or the search fits nothing again unless a card's width changed. A table of over 400 rows finds its step on its first 300 rows and checks once with all of them.
- **On a phone** each row is a card: each value beside its column's name, in one piece; a long value with no space (a hash, a path) breaks inside its card.
- **A bar at the top that stays:**
- the report's sections, with the one you are reading marked, and each table's row count;
- **Compact / Comfortable** rows;
- **Light / Auto / Dark**, which follows the reader's own setting on Auto;
- **Print**.
- The rows and light/dark choices are kept in that browser, for every page of the website.
- The two switches work even where the page's script is blocked (a web server whose Content-Security-Policy allows no inline script - common on a hardened IIS or nginx); the choice is then for that page only. Print needs the script, so it is not shown then.
- **Headings that stay at the top** of a long table while you scroll it, rows striped, and the row under the pointer marked.
- **Status chips with icons and their word**, never colour alone: a check mark for OK, ! for a warning, x for critical.
- **Where they appear:** the tables' Severity and Status columns, a cell that says PASSED or FAILED, the sections' and the cards' status, and a coloured edge on the header and on each tile that needs a look.
- **Contrast:** every text colour is at least 4.5:1 against what it is on, in light and in dark (most over 7:1).
- **Start here cards** with a **Copy** button for their command. The health check's healthy hosts each get a check mark, under *Every check passed* and the checks run.
- **Copy** on every number tile (its line: *Completed: 3 (resolved or closed)*) and on every section: all of it, with its lines as a list and its table as rows (only the rows the filter shows, in the order sorted).

- Over https the copy carries the HTML as well, so it pastes into Word or Outlook as a real table or bulleted list, and into Excel as cells.
- Over plain http or from a share, text only (columns separated by tabs, which Excel still splits).
- Sections that fold, tables that sort when a heading is clicked and, past 8 rows, a box to filter them. On a phone, a table's rows become small cards, each value under its column's name.
- Sorting (1.20.0): numbers as numbers (`1,234`, `4.5 %`, `-7`); IP addresses by their four parts (`192.0.2.5` before `192.0.2.45`); versions and names with a number in them in order (`8.0.2` before `8.0.10`, `vmx-9` before `vmx-21`, `host2` before `host10`). Numbers come before text. Empty cells and a lone dash (`-`, how a report writes a missing value) go last, either way.
- A click anywhere in the heading's cell sorts. A first click on a column whose values are already in order, as the rows stand (the VM tables come sorted by VM), sorts it the other way, so the click always shows.
- The arrows and the hand pointer appear only once the script runs: without it the headings are plain.
- **The index page** in the same look, with the same switch.
- **Printed:** white, landscape, every section open, each table's headings repeated on every page.
- **One file per page:** no fonts or scripts from elsewhere (system fonts: Segoe UI and Cascadia Mono on Windows), so a page opens from a share too. The page's script is in it, and since 0.63.0 also in `site-report.js` at the top of the website (below).

Since 0.63.0:

- **A rail of the sections** beside the report on a wide screen (1200 px and up; on a narrower one, the bar's list of them, with the switches and Print as icons beside the search): each section with its status dot and row count, the one you are reading marked, *Top* to go back up.
- **Put it away** (since 0.66.0): the **«** button at the top of the rail folds it to a narrow strip, so a wide table (the STIG recheck's, say) gets the whole width; the bar lists the sections again. **»** brings the rail back. It works without the script too; with it, this browser keeps the choice for the next report.
- **Search** in the bar, for the whole report: type a word, a host or an id and only the rows, lines and cards that have it stay, in every section; a section without any is put away (all of it stays when its title has the word). The rail shows how many each section has, the bar how many in all, and the words are marked where the browser can (Chrome and Edge 105 and newer). **/** or **Ctrl+K** goes to the box, **Enter** to the first section with a match, **Esc** clears it. The table's own filter box (past 8 rows) still works, with the search or alone.
- **Columns** above each table: tick the columns to see, *Show all* to have them back. It works without the script too, and what you take off is left out of Print, Copy and CSV as well. Your choice is kept in your browser (1.11.0) for every table with the same columns - on this page, and the next report's - and a report may start some hidden (the VM inventory's `vm_inventory_hidden_columns`). A column with a short header (`Enc`) shows its full name when you point at it, in the Columns menu and on a phone's cards.
- **CSV** above each table: the table **as shown** - its columns, the rows the search and the filter leave, in the order sorted - as a `.csv` file named after the report and the section, that opens in Excel (accents and all: it starts with a byte order mark). A value that Excel would read as a formula (`=`, `+`, `-` or `@` at its start, and not a number) gets a `'` before it, so a host name or log line can never run as one.
- **Copy beside every command** in a table (the *Look further*, *Command*, *Hint* and *Next step* columns), as on the Start here cards: it copies the command alone. Where the script is blocked, a click on a command selects all of it (then Ctrl+C).

- `site-report.js`: the job writes the pages' script beside the index too (into `report_web_dest`'s top folder, only when it changed - by the same login, the same way as the pages) and each page loads it from there. A web server whose Content-Security-Policy allows no inline script but scripts from the site itself (`script-src 'self'`, the usual hardening) runs it, so sorting, filtering, the search, CSV, Copy and Print work there now. The page still carries the script too, for a page saved or copied by itself; it runs once. The ticket insights pages have a script of their own: written the same way as `site-insights.js` (0.88.0), loaded by those pages only; the index never loads it.

Where the page's script is blocked.

What you see	Why, and what to do
Everything works	The script ran - from `site-report.js` or from the page
No search box, no CSV, no Copy buttons, no sort arrows on the headings; the rail, Columns and Light / Auto / Dark work	No script runs on the site at all (`script-src 'none'`, or `site-report.js` not there yet: the next report run writes it). F12 > Console says which: *Loading the script ... violates the following Content Security Policy directive* - allow scripts from the site itself on the report site only: `script-src 'self'`
F12 > Console: *Executing inline script violates ... 'script-src 'self''* (twice) and everything works	Expected: the copy of the script in the page was blocked and `site-report.js` ran instead. Nothing to do
A click on a heading does nothing; F12 > Console: *This document requires 'TrustedHTML' assignment*	The site's policy has Trusted Types (`require-trusted-types-for 'script'`) and its `site-report.js` is older than 1.20.0. From 1.20.0 the script writes no HTML, so it sorts under that policy. The next report run writes the new `site-report.js`, and every page uses it, older pages too. The ticket insights pages' own `site-insights.js` still writes HTML for its chart tips and its sort arrows: under this policy those two fail there

To see the policy the site sends (on any Linux box that reaches it; the site's own address in place of the example):

```shell
curl -skI --noproxy '*' https://reports.yoursite.mil/index.html | grep -i content-security
```

On Windows: F12 > Network > the page > Response Headers > `Content-Security-Policy`.

Where the design comes from - the guidance it follows, for anyone who wants to change it:

Source	What it gave the look
U.S. Web Design System - Table	Headings that stay at the top, striped rows for dense data, rows as cards on a narrow screen
U.S. Web Design System - Typography	Lines of 45 to 90 characters, line height of at least 1.5 for text
GitHub Primer - DataTable guidelines	Columns that grow within limits; wrapping preferred over cutting text off; numbers right-aligned in tabular figures; density steps
IBM Carbon - Data table	Row heights (the Compact and Comfortable steps); zebra stripes for reading across

Source	What it gave the look
IBM Carbon - Status indicators	Status shown with colour, shape and word together, so it still reads in grey
GOV.UK Design System - Table	Numbers aligned right; headings marked as column headings
Nielsen Norman Group - Data tables	Frozen headings; a readable identifier first; row highlighting to keep your place
WCAG 2.2 - Use of colour, Non-text contrast	Never colour alone; 4.5:1 for text, 3:1 for icons and borders
MDN - overflow-wrap, text-wrap, font-variant-numeric, position: sticky, Printing	How long paths break without widening a table, balanced headings, aligned digits, the headings that stay, the printed page

Everything it uses works in Microsoft Edge and Chrome 2024 or later. An older Edge draws the page the same, without the balanced headings.

The brief look (0.92.0; calm and soft since 0.94.0)

`report_web_theme: brief` draws the same pages read like a morning brief. Everything above stays - the bar, the rail, search, Columns, CSV, Copy, the switches, Print, the cards on a phone, `site-report.js` (both looks share it) - and the page is laid out to answer *what is wrong and what do I run* first, calmly - type at a reading size, nothing poster-sized:

- **The verdict as a chip** at the top, with its icon: *All good*, *Needs attention* or *Action required*, then the report's title as the page's heading. A report that only informs (an inventory, status *For information*) leads with its title and its status chip.
- **The key figures as one ruled strip** of numbers, not a row of boxes; a figure that needs a look has its colour, its icon and a coloured rule above it.
- **Start here as numbered steps** (01, 02, ...) on a tinted band, each with its command and Copy.
- **The sections under a rule** rather than in a box, so the tables get the width.
- **Percentages as bars.** A column whose every value is a percentage (`87%`) gets a small bar beside each number; where the report marks that cell (the disk report's *Used* past 85 or 90%, say) the bar and the number take its colour and icon, never colour alone. Sorting, CSV and Copy use the number.
- **The index is the list of reports, not an alarm** (0.94.0): a plain *Reports* title, one line - *9 reports · last run 2026-11-09 06:00 UTC* - and the counts as small chips (*2 Critical*, *1 Warning*, ...). Then every report, grouped by area (the tabs as before), each line with its status chip, its title and its last runs as small squares. Open a report that needs action and **the first step its report gives** is there (its first Start here card), above its last runs - kept short: its title in two lines at most, its command only when it is short (three lines at most, with Copy), and a link to the report for the rest (a STIG rule's whole check stays on its page).
- **The logo larger:** the site's logo (`report_logo_file`) up to 60 px tall on the index, 52 px on the report pages and ticket insights, 44 px on a phone - drawn from your own file, sized by the page.
- **The ticket insights pages** (they draw their own page) take the brief colours and type, their figures as one strip, and *Keeping up* or *Falling behind* as a chip at the top with the period's numbers.
- **Colour and type.** Light: a paper white with an ink near-black. Dark (0.94.0): soft neutral greys - the page #121212, cards a step lighter, text #e0e0e0 and #a3a3a3 - with the status colours desaturated so nothing glows. Both soft (0.94.0): the cards and lists translucent over a faint glow (a light blur behind

them where the browser has it, solid where it does not), hairline borders, chips tinted with their colour, the run squares and bars quieter; the table headers and the tables stay solid. Never pure black or white; every text colour 4.5:1 or better on every surface it is drawn on, the translucent layers counted (tests/test_report_history.py checks it). The system's own fonts: Segoe UI Variable (Display for the headings, Text for the rest) and Cascadia Mono on Windows - nothing loaded from elsewhere.

- **Motion only to say where to look:** the header and the figures fade in once when the page opens. Never with the reader's *reduce motion* setting, never in print.

A page drawn before 0.92.0 keeps its look; the next run of each report draws its page in the new one (the index on the next run of any report, the cards' first step as each report runs again). `report_web_theme: atlas` goes back.

`report_web_theme: portal` (or standard, command, glass) gives the website an email's look again, as before 0.43.0; the index page is then in the portal look.

playbooks/group_vars/all.yml

```
report_email_theme: command                 # the emails: standard, command, portal or glass
report_web_theme: atlas                     # the website (the default; brief, or an email look)
report_logo_file: files/report_logo.png     # both
```

The classification banner

In a classified enclave every page carries its banner at the top and bottom - each report's page, latest page, the index, the ticket insights pages and the pages the copy job writes - and in print on every sheet (`site_enclave`, `report_banner`; ENCLAVES.md).

The index lists many reports, so it carries the **highest** marking among the runs it lists (TOP SECRET, SECRET, CONFIDENTIAL, CUI, UNCLASSIFIED; a text of no known classification counts as SECRET) - whichever job wrote it last. A run without a banner never takes a classified report's banner off the index: each line of `index.json` keeps its runs' banner (1.24.0), and `index.json` the index's own. On a site updated from an older release, the banner the index already carries stays while any line or run from before is listed - until each of those runs has left its report's last runs (`report_web_history`, 5): a report that was classified before the update and runs unclassified after it still lists its classified run.

What it writes

```
index.html                                  every report, worst first, and its last runs; a tab
  per area
index.json                                  the same as data
linux-certificate-trust-report/
  2026-10-23_0605_job-907.html              this run's page - the address the job prints
  2026-10-23_0605_job-907.json              this run's data
  latest.html                               always the newest run (a link that never changes)
  latest.json
  2026-10-22_0600_job-901.html              the 4 runs before it (report_web_history: 5)
  ...
vmware-snapshot-cleanup/
  ...
```

- **The folder** is the AAP template's name, lower case with dashes: `Linux - Certificate trust report` becomes `linux-certificate-trust-report`. Outside AAP (the command line), the play's name.
- **The file** is the time the job wrote it (UTC) and the AAP job number: listing a folder sorts the runs oldest to newest, and the number leads straight to the job in AAP.

- Renaming a template in AAP starts a new folder for its new runs (the old runs stay in the old one). The index shows each folder's line; one that stopped can be deleted on the server.
- Every page stands alone: the logo is inside it (no separate image file), no scripts, no outside fonts or styles.

The index page: tabs, and each report's last runs

`index.html` has the four counts at the top (Critical, Warning, Successful, Info), then a row of tabs: **All**, then one per area - Certificates, VMware, Horizon, Windows, Network and storage, Linux, ServiceNow and AAP - each shown only when it has a report. A report is on the first tab whose names its AAP template's name matches (`report_web_tabs`, any case, `*` = anything): the names this guide gives the templates (docs/JOB_TEMPLATES.md) are all in it - `VM - health report` is on **VMware**, `Certificate report` and `VMware - certificate report` on **Certificates**, `Health check` on **Linux**. A name it does not know goes on the tab of its name up to `-` (`Backup - nightly`: **Backup**), else on **Other**. A new template gets its line - and its tab, when the tab is new - the first time it runs. A tab with a Critical or a Warning in it has a red or amber dot.

Your own names, or your own tabs: `report_web_tabs` in `all.yml` (for every template alike - the index is one page), in the order the tabs are shown:

```yaml
report_web_tabs:
  - {tab: Certificates, match: ["*certificate*", "*trust store*", "PKI *"]}
  - {tab: VMware, match: ["VM *", "VMware*", "ESXi*", "AB01 VM*"]}
  - {tab: Patching, match: ["*patch*"]}
```

The defaults are in `roles/site_email/defaults/main.yml`; yours replace them whole.

Each line is one report: its status, name (a link to its `latest.html`), title and last run. Click the line to open its last runs - each with its status, time (a link to that run's page), AAP job and title. All of it works without scripts, opened from a share or from a web server.

- **How many runs**: `report_web_history` (`5`). The index lists them, and when a run falls off a report's list its page and JSON are **deleted** - only pages the index listed for that report, never its `latest.html`, the index, or anything else in the folder. An email's link to a run that old no longer opens; its `latest.html` still does.
- **Keep every page**: `report_web_delete_old: false` - the index still lists the last `report_web_history` runs, and the older pages stay in the folder until you delete them (to keep, say, 90 days, a nightly job on the web server: `find /srv/reports -name '20??-*_job-*.*' -mtime +90 -delete`).
- **Only with a** `latest.html` (`report_web_latest`, set by default): a report's line is then one template's. With `report_web_latest: ""`, templates whose pages start with the same folder (`{site}/{template}/...`) can share a line, so nothing is deleted - the index still lists the last runs.
- **Deleting needs** the right to delete: Modify on the folder (a share, or `report_web_host`), `DELETE` on an upload address (nginx: `dav_methods PUT DELETE MKCOL;`). A page that cannot be deleted is a warning in the job's output, never a failure, and stays in the folder.
- **A report's folder deleted by hand**: the next report that writes the index takes that report's line off it (its `latest.html` is not there any more) and says so in its output (`taken off the index: ...`). `report_web_index_prune: false` keeps every line. Not with `report_web_host` (that server's folder is not read from the AAP side): there, delete the line from `index.json` by hand.
- **Pages from before 0.34.0** are not in the index's lists (it knew only each report's last run then): their pages stay. Delete them on the server once if you like - every run before your upgrade.

- **The page open in a browser** while a job writes it (Edge, from a share - `STATUS_ACCESS_DENIED`): the job writes it again a moment later, for up to about 10 seconds. `index.html` or a `latest.html` still open after that is a warning, not a failure - the run's own page and `index.json` are written, and the next run writes the index page again. Edge may hold a page from a share for as long as its tab is open: close the tab if the warning comes back.
- Per template: `report_web_history: 30` on one template's Variables keeps 30 runs of that report only - with the copy job too (the report job's setting is kept with its report).

Times in your time zone

Out of the box every time on the website is UTC: `2026-11-13 04:37 UTC`. To show your own time zone, set `report_time_zone` in `all.yml` (1.49.0; the same setting the VMware and ServiceNow reports already use):

```yaml
report_time_zone: Europe/Berlin        # a name as `timedatectl list-timezones` prints it
```

From the next run of any report, the website shows that time zone with its abbreviation:

Where	Before	With report_time_zone: Europe/Berlin
the index: each report's last run, and its runs	`2026-11-13 04:37 UTC`	`2026-11-13 05:37 CET`
the index: *updated*, and *last run* (the brief look)	`2026-11-13 04:38 UTC`	`2026-11-13 05:38 CET`
a report page: the strip of past runs	`2026-11-12 04:36`	`2026-11-12 05:36 CET`
a report page and its email: the footer line	the execution environment's clock	`2026-11-13 05:37 CET`

- **Summer time is per date.** A run in July shows `CEST`, one in November `CET`, side by side in one list.
- **Older runs change too.** The index is drawn again by every run, so the runs written before you set it show your time zone from the next run on. Nothing has to be converted.
- **What is stored stays UTC:** `index.json`, each run's `.json`, the file names (`2026-11-13_0437_job-4651.html`) and the order of the runs. Your own tools that read them need no change.
- **A report page shows what its own run wrote.** Pages written before the setting keep their footer line; the index's list of them is in your time zone.
- **The copy job** (below) draws the index too: `report_time_zone` in `all.yml` reaches it and the report jobs alike. Set on one template only, the next job without it draws the index in UTC again.
- **A name the execution environment does not know** (misspelt, or no `tzdata` package in the image): the times stay UTC and the job says so once - `report_time_zone ... is not a time zone this execution environment knows`. The job never fails for it.
- `report_time_zone: ""` (the default) or `UTC`: every page exactly as before.

Changing the names

Every name is a setting, with `{names}` filled in (`roles/site_email/defaults/main.yml`):

Setting	Default
`report_web_page`	`{template}/{date}_{time}_job-{job}.html` - each run's page

Setting	Default
report_web_latest	{template}/latest.html - "" for none
report_web_index	index.html - "" for none
report_web_index_prune	true - a line whose latest.html is gone (its folder deleted) is taken off the index
report_web_names	{} - your own names, e.g. {site: hq} for {site}/{template}/...

The names: {template}, {template_id}, {job} (local outside AAP), {status} (ok, warning, critical, info), {date} (2026-10-23), {time} (0605), {year}, {month}, {day}, and your own. For example a folder per site and per month:

YAML

```
report_web_names: {site: hq}
report_web_page: "{site}/{template}/{year}-{month}/{date}_{time}_job-{job}.html"
report_web_latest: "{site}/{template}/latest.html"
```

One fixed file per report (a dashboard tile, a bookmark): latest.html is that already, one per template - vm-health-report/latest.html, linux-log-analysis/latest.html. To have them side by side at the top of the folder instead, as vm-health-report.html, linux-log-analysis.html ... (the template's name, lower case with dashes):

YAML

```
report_web_latest: "{template}.html"
```

A name must end in .html and stay inside the report folder (no leading /, no ..); a value is made safe for a file name (letters, digits, ., -, _; the rest becomes -). A name that does not exist stops the job and lists the ones that do.

The JSON (for your own site)

Each run's .json (and latest.json):

```
{
  "report": {"title": "...", "subtitle": "...", "status": "warning",
             "summary": [{"label": "Hosts", "value": 34}, {"label": "Findings", "value": 752,
               "status": "warning"}],
             "sections": [{"title": "...", "status": "...", "columns": ["Host", "..."], "rows":
               [["web01", "..."]],
                           "row_status": ["critical"], "cell_status": [["critical", ""]]},
                          {"title": "Notes", "lines": ["..."]}],
             "footer": "..."},
  "job": 907, "template": "Linux - Certificate trust report", "template_id": 71,
  "when": "2026-10-23 06:05 UTC",
  "runs": [{"status": "ok", "value": 3, "label": "Findings", "when": "...", "ago": "2 days ago",
    "current": false}],
  "page": "linux-certificate-trust-report/2026-10-23_0605_job-907.html",
  "url":
    "https://reports.yoursite.mil/linux-certificate-trust-report/2026-10-23_0605_job-907.html",
  "latest": "linux-certificate-trust-report/latest.html", "index": "index.html"
}
```

report is the layout every report uses (EMAIL_REPORTS.md, "Emailing a report from another playbook"). runs is the strip of last runs (with an AAP credential on the template). index.json: {"generated": "...",

`"reports": [{"key", "name", "title", "status", "when", "job", "page", "latest", "runs"}, ...]}`, worst first; `runs` is that report's last runs on the website, newest first: `[{"page", "status", "when", "job", "title"}]` (`report_web_history` of them). Every `when` and `generated` here is UTC, also with `report_time_zone` set (only the pages show your time zone); the strip's `runs[].when` is the text the page shows.

Where the files go

Four ways; the pages are the same in each.

A Windows file share, over SMB

```yaml
report_web_dest: '\\fileserver.yourdomain.mil\its\aap\reports'   # the share's folder - there
                                                                 # already (single quotes)
```

The job writes the pages straight onto the share over SMB 2/3, logged in as the account of the **Report website** credential (`user@YOURDOMAIN.MIL`, Modify on that folder) - no mount on the execution nodes, no AAP setting, no web server that takes uploads. The execution environment needs `smbprotocol` (in the all-in-one EE since 0.33.0), or only the copy job's does (`report_web_copy`). A dry run (Check) logs in and checks the folder, and writes nothing. `report_web_smb_auth` (`negotiate` - Kerberos first, FIPS too; `ntlm`; `kerberos`), `report_web_smb_encrypt`, `report_web_smb_port`. The whole setup, step by step: REPORT_SHARE.md (also a PDF).

A Windows server, over WinRM

```yaml
report_web_host: web01.yoursite.mil       # the Windows server (a file server, or the IIS server
                                          # itself)
report_web_dest: 'D:\reports'             # the folder on it - there already
report_web_url: https://reports.yoursite.mil
```

The job makes the pages on the AAP side, as always, and writes them on that server over WinRM - the way the Windows jobs reach your servers. Nothing to mount on the execution nodes, no WebDAV, no share. Two steps there per run: one reads the folder's `index.json` back (to add this template's line), one PowerShell script writes the run's files (each to a temporary name, then over the old one). Both work in Windows PowerShell 5.1 and 7, and in Constrained Language Mode; the pages are written as ASCII (every other character as an HTML character reference, e.g. `é`), so no byte-order mark and no code page gets in the way.

1. **The folder**: e.g. `D:\reports`, made once by hand. The job makes the folders inside it.
2. **The account**: one that may use WinRM on that server (a local administrator, or a member of **Remote Management Users**) with **Modify** on the folder. A service account for it alone is best.
3. **The login**: create the **Report website** credential type (`aap/credential_types/report_web.yml`), a credential of it with that account (`DOMAIN\user` and its password), and attach it to each report template. It is a credential type of its own, so it goes beside the template's Machine credential (a Linux job's SSH key, say). Without it, the job logs in with the template's Machine credential.
4. **The connection**, as your Windows inventory's (docs/WINDOWS.md, step 4) - the defaults:

Setting	Default	
report_web_host_connection	winrm	or psrp
report_web_host_port	5986	
report_web_host_scheme	https	http with Kerberos or NTLM (they encrypt each message then)
report_web_host_transport	ntlm	kerberos (needs Kerberos in the execution environment), credssp, basic
report_web_host_cert_validation	validate	ignore only to try it; report_web_ca_path is the CA that signed the WinRM certificate

The execution environments from Red Hat do not trust DoD certificate authorities: with validate, set report_web_ca_path to your CA file inside the EE (as ansible_winrm_ca_trust_path in docs/WINDOWS.md), or the job stops with certificate verify failed.

5. **The website**: IIS on that server (or any web server reading the folder) serves D:\reports at report_web_url. Only reading - nothing is uploaded to IIS.

The server does not have to be in the job's inventory: the report jobs use many inventories, and the settings above are all it needs. Every report template must then run in an execution environment with WinRM (and Kerberos, if you use it) - or let the copy job write the pages ("The copy job", below). report_web_dest is a folder **on** that server (D:\reports), not a share (\\fileserver\reports): over WinRM that would be a second hop, which NTLM does not allow.

A web server that takes uploads (HTTP PUT)

report_web_dest: https://reports.yoursite.mil/upload - the job uploads each file with PUT (WebDAV), from the AAP side. Nothing to mount, nothing on the execution nodes. The job reads index.json back from the same address (GET) to add its line. A redirect (301, 302 ... to a login page, another host or http://) is never followed - the login is never sent on: the job stops and names the address it pointed to; set report_web_dest to the address that takes the upload itself. nginx, for example (the web developer's part):

```
server {
    listen 443 ssl;
    server_name reports.yoursite.mil;
    # ssl_certificate ... ;
    root /srv/reports;
    charset utf-8;

    location / {                          # reading: the pages
        index index.html;
        try_files $uri $uri/ =404;
    }
    location /upload/ {                   # writing: the jobs
        alias /srv/reports/;
        dav_methods PUT DELETE MKCOL;     # DELETE: older runs' pages (report_web_history)
        create_full_put_path on;
        client_max_body_size 50m;
        limit_except GET {                # GET (reading index.json back) open; PUT and DELETE need
                                          # the login
            auth_basic "report uploads";
            auth_basic_user_file /etc/nginx/reports.htpasswd;   # htpasswd -c ... aap-reports
        }
    }
}
```

`/srv/reports` must be writable by nginx (`chown nginx: /srv/reports`; with SELinux `semanage fcontext -a -t httpd_sys_rw_content_t '/srv/reports(/.*)?'` and `restorecon -R /srv/reports`). IIS works too, with the WebDAV Publishing feature and a login on the upload path; so does Apache with `mod_dav`, or any endpoint of your own that takes `PUT` (answering 409 when a folder is not there makes the job create it with `MKCOL`).

The upload's login: create the **Report website** credential type (`aap/credential_types/report_web.yml`), a credential of it (a user name and password - sent as basic authentication - or a token, sent as `Authorization: Bearer ...`), and attach it to each report template. Never put it in Variables.

YAML

```
report_web_dest: https://reports.yoursite.mil/upload
report_web_url: https://reports.yoursite.mil          # what people open; the job prints addresses
                                                      # under it
report_web_ca_path: /etc/pki/ca-trust/source/anchors/yoursite-ca.pem   # only if the EE does not
                                                                       # trust the server's CA
```

The report folder itself (`/upload/` here) must exist; the job makes only the folders inside it.

A folder: a share mounted on the execution nodes

`report_web_dest: /mnt/reports` - the job writes the files there, from the AAP side, so the folder must be visible inside the job's container:

1. Mount the share on **every execution node** that runs these jobs (the same path on each), writable by the user AAP runs jobs as (`awx`). An SMB share, e.g. in `/etc/fstab`: `//fileserver/reports /mnt/reports cifs credentials=/etc/reports.cred,uid=awx,gid=awx,file_mode=0664,dir_mode=0775,_netdev 0 0` (with SELinux add `context=system_u:object_r:container_file_t:s0`). An NFS export, e.g. in `/etc/fstab`: `nfs01.yoursite.mil:/export/reports /mnt/reports nfs4 rw,hard,_netdev,context="system_u:object_r:container_file_t:s0" 0 0`. NFS has no `uid=` option: on the NFS server, give the export's folder to the `awx` user's number (`id awx` on a node - the same on every node), or map every writer to it in `/etc/exports` (`/export/reports`

`aapnode*.yoursite.mil(rw,all_squash,anonuid=<that uid>,anongid=<its gid>)`). With SELinux, the `context=` above, or `setsebool -P virt_use_nfs 1` on each node.

2. In AAP: **Settings > Job settings > Paths to expose to isolated jobs**: `/mnt/reports:/mnt/reports:rw`.
3. The web server serves the same share (IIS on the file server, or nginx with the share mounted).

A folder that is not there stops the job with "is the share mounted?" - the job never creates it, so a share that failed to mount does not fill the node's own disk. No credential is needed.

Turning it on

For every report job, in `playbooks/group_vars/all.yml` (the address is the same for all of them):

```yaml
report_web_host: web01.yoursite.mil                    # a Windows server - or leave it out for
                                                       # an upload or a folder
report_web_dest: 'D:\reports'                          # (https://reports.yoursite.mil/upload,
                                                       # /mnt/reports)
report_web_url: https://reports.yoursite.mil
report_logo_file: files/report_logo.png                # your logo, in your repository
```

Or on one template's Variables to try it on one job first. Like the email, not in an inventory group's Variables: the page is written by the AAP side of the job, which never gets a group's variables.

Setting	Default	
`report_web_dest`	`""` (off)	the folder on `report_web_host` (`D:\reports`), the upload address (`https://...`) or the folder (`/mnt/...`)
`report_web_host`	`""`	a Windows server to write the pages on, over WinRM; `report_web_host_*` for the connection ("A Windows server")
`report_web_url`	`""`	the address people open; `""` = `report_web_dest` when it is `https://` (else the job prints where the page is: `web01:D:\reports\...`)
`report_web_theme`	`atlas`	the website's look ("The look"): `atlas`, `brief` (0.92.0, "The brief look"), or an email look - `standard`, `command`, `portal` or `glass` (`glass` with the blur behind the cards, icons and a plain print)
`report_web_json`	`true`	the JSON beside each page
`report_web_history`	`5`	the runs each report keeps: listed under its line of the index, older runs' pages deleted
`report_web_delete_old`	`true`	`false` = older runs' pages stay in the folder (the index lists only the last `report_web_history`)
`report_web_tabs`	the guide's areas	the index's tabs: `[{tab, match: [names]}]`, in `all.yml` ("The index page")
`report_web_ca_path`	`""`	a CA file for an `https://` upload address, or for `report_web_host`'s WinRM certificate

Setting	Default	
`report_web_retries`	`3`	a failure that passes (Kerberos `Message stream modified`, no KDC reached, a connection reset or timed out, an SMB session gone, HTTP 502/503/504, a stale mount) is tried again from the start - a new login, a new SMB session, a fresh Kerberos ticket - this many times; a real error (password, access, no such share or folder) is not. Each retry is one warning line. Not `report_web_host` (WinRM)
`report_web_retry_delay`	`30`	seconds between two tries
`report_web_required`	`false`	`false` = still not published after the retries: a warning in the job output, the email says it at the top ("The report website copy failed: ...; the email is the full report"), the job goes on (green). `true` = the job fails, as before 0.98.1
`report_web_page`, `_latest`, `_index`, `_names`	see "Changing the names"	

A dry run (Check) writes nothing and prints the address it would have used.

The copy job: report templates in any execution environment

With `report_web_copy: true` the report jobs **write nothing** on the web server and connect to nothing there. Each keeps its report in AAP, as part of the job (the job artifact `site_report_page`: the report, its strip of past runs, the file names and the address, compressed - a 750-row certificate report is about 12 to 40 KB). One job template, **Report website - copy** (`playbooks/report_web_copy.yml`), in an execution environment that reaches the server, then writes those pages - the same pages, at the same address. So:

- the report templates keep their own execution environments and credentials: no WinRM, no Kerberos, no Report website credential on each one;
- the copy job is the only template that knows the server. When `report_web_host` is a host of **its** inventory (by the same name), it reaches it the way your Windows jobs do - that host's connection settings (`ansible_port`, `ansible_winrm_transport` ...) and the template's Machine credential. The `report_web_host_*` settings are not needed then;
- each report job still prints the page's address, keeps it as `site_report_url`, and its email gets the button (**Open the full report**, *Open this report in a browser*) - the page is there once the copy job has run, so a link opened before that answers *not found*.

Setting it up

1. **The settings**, in `playbooks/group_vars/all.yml` (the report jobs and the copy job both read them):

```yaml
report_web_copy: true
report_web_host: web01.yoursite.mil      # the server's name as the copy job's inventory has it
report_web_dest: 'D:\reports'
report_web_url: https://web01.yoursite.mil/reports
report_web_theme: atlas                  # the pages' look (the default) - the copy job draws them
report_logo_file: files/report_logo.png
```

Hold on to `report_web_copy: true` until step 3 has passed. To try it, put it on one report template's Variables first, run that template (Run, not Check), and look at that job in AAP: **Jobs >** the job **> Details > Artifacts** has `site_report_page`.

2. **The template** *Report website - copy*: playbook `playbooks/report_web_copy.yml`; the **execution environment your Windows jobs work with**; the **inventory that has the web server** (your Windows inventory), no Limit; its **Machine credential** - an account with **Modify** on the folder; and a **Red Hat Ansible Automation Platform** credential whose user has **Organization Auditor** on the organizations of the report templates (the one of the strip of past runs works). Leave *Concurrent jobs* off: one copy at a time, so the index is never written twice at once.
3. **Launch it with Job type Check**: it lists each report job it would copy (`Would copy: job 907 ...`) and writes nothing. Then **Run**: `job 907 'Linux - Certificate trust report': https://...` for each page written, and how the server was reached: `web01.yoursite.mil (winrm, port 5985, from this job's inventory): its connection settings in this job's inventory`.
4. **A schedule**: every 15 minutes, say (*Templates* > the template > *Schedules*). Or add it as the last step of a workflow that runs reports, so their pages are there when the workflow ends - or both.

What each run copies

The report jobs that finished since the run before (a few minutes before it, leaving out those it already copied), oldest first, whatever their template or how they ended. Where a run got to is its own job artifact `site_report_copied`; a **Check** run, and a run with `report_web_copy_jobs`, keep none, so they never move it on. The first run (no run before it) copies the report jobs of the last `report_web_copy_hours` (24). A run copies at most `report_web_copy_max_pages` (50) pages and says when there are more: the next run copies the rest.

`report_web_copy_jobs: [907, 908]` (on the template's Variables, or a survey) copies those jobs' pages again, whatever was copied before - a page deleted on the server, say.

A page that fails (HTTP 413 for one big page, a path too long on the server, no Modify on one folder) is a warning that names the job and why - `WARNING - job 907 'Linux - Certificate trust report': its page ... was not copied: ...` - and the run goes on with the next page; at the end `Not copied: ...` lists each one. Where the run got to still moves on, and `site_report_copied` keeps those jobs (`failed`): the next run tries them again first and says so (`[WARNING]: The report website copy: job 907: its page was not copied by the last copy (...) - tried again now`), every run until the page is written. One page that always fails never holds back the reports after it. A job AAP has no more (deleted) is said once and not tried again.

File names: the copy job writes a kept report only at names inside `report_web_dest` - a path below the folder, `/` between its parts, ending in `.html` (no leading `/` or `\`, no drive or `:`, no backslash, no `.` or `..` part), as `report_web_files` makes them. A kept report with any other page, latest or index name is not copied: `job 907 (...): its page ... is not copied - ...: not a file name inside report_web_dest`, and the run goes on. The module checks the same before it writes anything, for a folder, a share, an upload and the Windows script alike.

An older run never takes the place of a newer one: the template's `latest.html` and its line in the index are only written over by a run at least as new as the one there (by its time); the older run gets its own page.

A report too big to keep (more than `report_web_copy_max_kb`, 256 KB, compressed) has its longest tables cut until it fits - the page says *This page shows the first N of M rows* - and the email always has the whole report.

Setting	Default	
report_web_copy	false	true = the report jobs keep their report for the copy job instead of writing their pages
report_web_copy_max_kb	256	the kept report's greatest size, compressed
report_web_copy_jobs	[]	the copy job: these job IDs only
report_web_copy_hours	24	the copy job's first run: the report jobs of the last hours
report_web_copy_max_pages	50	the copy job: pages a run writes at most

Good to know:

- The copy job sees only the jobs its AAP user may see: **Organization Auditor** on every organization that has report templates. A report template in another organization is left out, without a word.
- Per-template settings of the website (report_web_dest, report_web_url on one template's Variables) are the copy job's own: it writes everything into its own report_web_dest. The file names (report_web_page, report_web_names) are the report job's - they are kept with the report.
- A template with report_web_copy: false on its Variables writes its pages itself, as before. It then shares the index with the copy job, and the index has no lock: each job reads index.json, puts its own line in and writes it back. Into a folder, a share or an upload address the job reads it again just before it writes it (1.24.0) and keeps every other line as it is then, so only two writes in the same moment can lose one. On report_web_host (a Windows server) the index is read over WinRM before the pages are made and written by the second WinRM step, and the copy job carries it from page to page through its whole run: a job that writes the index in that time can lose its line, or put back a line the other took off. What that looks like: a report not listed (its page is there, but no line links it, and it is not deleted with the older runs) or a link to a run whose page was deleted - until that template's next run writes its line again.
- Two runs of the **same template** at once (its Concurrent jobs on): the one that finishes last writes its line, latest.html and the index - the older run can win, and the newer run's page then stays in the folder, not listed and not deleted, until that template's next run. Leave Concurrent jobs off on report templates that write the website.
- report_web_host not a host of the copy job's inventory (or under another name there, a short name, say): the copy job reaches it with the report_web_host_* settings and the Report website credential (else its Machine credential), as a report job would. The job says which it did.

Using the address in a workflow or another job

The job keeps the page's address as the artifact site_report_url. In a workflow, the next step gets it as a variable ({{ site_report_url }}) - for a Teams post or a ServiceNow work note. From AAP's API: GET /api/controller/v2/jobs/<id>/ - artifacts.site_report_url. From the job output, the line Report: https://....

Troubleshooting

The job says	Why, and what to do
`the folder /mnt/reports is not there - is the share mounted, and the path exposed to the job`	The share is not mounted on the execution node that ran the job, or not in "Paths to expose to isolated jobs"
`writing /mnt/reports/...: Permission denied`	The share is not writable by `awx` (the mount's `uid` / `file_mode`), or SELinux (`context=` on the mount)
`the folder https://.../upload is not there on the website`	The upload's own folder is missing on the server (`alias` / its directory)
`uploading ...: HTTP 401` or `403` ... `check the login`	Attach the Report website credential; check its user name and password or token
`uploading ...: HTTP 405`	The server does not take `PUT` at that address (nginx: `dav_methods PUT DELETE MKCOL;` in that location)
`[WARNING]: The report website: an older run's ... could not be deleted`	The account may write but not delete there: Modify on the folder, `DELETE` on an upload address - or `report_web_delete_old: false`
`[WARNING]: The report website: index.html was not written - it stayed open somewhere`	The index (or a `latest.html`) was open in a browser - Edge, from the share - the whole time; the next run writes it. Close that tab; a file open for longer: an editor, or a backup holding it
`[WARNING]: The report website: report_time_zone ... is not a time zone this execution environment knows`	A misspelt name (`timedatectl list-timezones` prints them: `Europe/Berlin`, `America/New_York`), or an execution environment without the `tzdata` package. The website shows UTC until it is fixed; nothing else changes
`uploading ...: HTTP 413`	The page is bigger than the server allows (nginx: `client_max_body_size`)
`Message stream modified` on a share, now and then	Kerberos's KRB_AP_ERR_MODIFIED - most often a file server's machine password that just changed (a NetApp SVM rotates it) while AD replicates: tried again by itself (`report_web_retries`). Every time: an alias or address in `report_web_dest`, or a duplicate SPN - REPORT_SHARE.md
`WARNING - The report website copy failed: ...` (the job green)	Not published after the retries, or a real error: the email carries the same line at the top. The reason's own row here; `report_web_required: true` makes it fail the job
`certificate verify failed`	Set `report_web_ca_path` to the CA that signed the server's certificate
`could not reach report_web_host web01... (winrm, port 5986): ...` - `the specified credentials were rejected`	The login: the Report website credential (`DOMAIN\user`), or the account is locked; without that credential, the template's Machine credential is used
`could not reach report_web_host ...: ... certificate verify failed`	`report_web_ca_path` (the CA of the server's WinRM certificate), or `report_web_host_cert_validation: ignore` to try it
`could not reach report_web_host ...: ... Connection refused` or timed out	WinRM is not on that port (`report_web_host_port`, `_scheme`), or a firewall between AAP and the server

The job says	Why, and what to do
`the folder D:\reports is not there on WEB01 (report_web_dest)`	Make the folder on that server; the job makes only the folders inside it
`The report website: Access to the path 'D:\reports\...' is denied`	The account has no Modify on the folder (NTFS)
`winrm or requests is not installed`	The execution environment has no `pywinrm` (docs/WINDOWS.md, step 2)
`report_web_page '...': there is no {x}`	A name that does not exist; the message lists the ones that do
A report missing from the index, or a link to a page that is gone	Two jobs wrote the index at the same time and one line was lost (on `report_web_host`, the copy job's whole run counts - "The copy job"); it is back after that template's next run
`HTTP 302 Found - the address answers with a redirect to https://...`	The upload address sends the job elsewhere (a login page, another host, `http://`): never followed, so the login is never sent on. Set `report_web_dest` to the address that takes `PUT` itself
`'../x.html': not a file name inside report_web_dest`	A page, latest or index name outside the folder (a hand-set `_web_files`, or a kept report): nothing written. The copy job skips that report and goes on
The copy job: `WARNING - job 907 '...': its page ... was not copied: ...`	That page failed (the reason's own row here); the other pages are written, and the next run tries the job again first, every run until it works
The copy job: `Nothing to copy: no report job kept its report for this job since ...`	No report job finished with `report_web_copy: true` since then: is it in `all.yml`, did the project sync? A report run with Check keeps nothing
The copy job: `AAP refused the list of jobs (HTTP 403)`	Its AAP credential's user needs Organization Auditor on the report templates' organizations
The copy job: `could not reach report_web_host web01..., a host of this job's inventory`	The template's Machine credential, and that host's connection settings in the inventory - as for your other Windows jobs
The copy job: `job 907 (...): its report cannot be read`	The report job's project is newer or older than the copy job's (sync both), or the artifact was cut; the other reports are still copied
The report job: `No web page for this run: its report is bigger than report_web_copy_max_kb`	Raise `report_web_copy_max_kb`, or let that template write its pages itself (`report_web_copy: false` on its Variables)
The email's button answers *not found*	The copy job has not run since that report: it runs on its schedule (or launch it)

36. Secrets: where they live

Recommendation

Store every secret as an AAP credential, and inject it into jobs as environment variables or files through custom credential types. Nothing secret goes into Git, inventory, job template variables, or surveys.

- AAP encrypts credential values at rest and never shows them again after you save them. People can be allowed to **use** a credential in a job without being able to **see** it.
- If your organization already runs **CyberArk, HashiCorp Vault, or Azure Key Vault**, keep the secrets there and link the AAP credential fields to it with AAP's credential lookup plugins (on the credential's form, the key icon next to a secret field). AAP fetches the value when a job starts; nothing else in this repository changes.
- Use **Ansible Vault** only for playbooks you must also run outside AAP. It is weaker: one vault password decrypts every value, and the encrypted values sit in Git forever (rotating the password does not un-publish old ciphertext).

Where each secret lives

Secret	AAP credential type	Reaches the playbook as
SSH key + sudo for the hosts	built-in **Machine**	the SSH connection (never visible to tasks)
WinRM login for Windows servers	built-in **Machine** (user name and password; Kerberos or NTLM)	the WinRM connection (never visible to tasks). Use a **separate** credential from the SSH one; see WINDOWS.md
Git access for the project	built-in **Source Control**	used only by the project sync
MySQL root / STIG Manager DB passwords	**STIG Manager database** (`aap/credential_types/stigman_database.yml`)	env `STIGMAN_MYSQL_ROOT_PASSWORD`, `STIGMAN_DB_PASSWORD`
TLS certificate, key, CA chain	**TLS certificate** (`tls_certificate.yml`)	files; env `TLS_CERT_FILE`, `TLS_KEY_FILE`, `TLS_CA_FILE` hold the paths
Docker Hub / quay.io login for hosts	**Container registry login (hosts)** (`registry_login.yml`)	env `REGISTRY_*`, used with `podman login --password-stdin`
ACT model key	**ACT model key** (`act_model_key.yml`)	env `GENAI_KEY` / `ASKSAGE_API_KEY` on the controller. **Note:** when ACT runs on a managed host, the job hands the key to that one ACT process on the task's stdin (never on a command line, so not in `ps` or the sudo log) and it is gone when the process ends. So the host's administrators and its process auditing can see it while ACT runs: use a key with a spending limit, and rotate it if a host is untrusted. `VM - alarms ACT analysis` runs ACT on the AAP node itself: there the key never reaches another server
ACT GenAI beta key	**ACT GenAI beta key** (`act_genai_beta_key.yml`)	env `GENAI_BETA_KEY`
Teams webhook URL	**Teams webhook** (`teams_webhook.yml`)	env `TEAMS_WEBHOOK_URL`
ServiceNow API account	**ServiceNow API** (`servicenow_api.yml`)	env `SN_HOST`, `SN_USERNAME`, `SN_PASSWORD` (basic auth on the controller; never sent to hosts)

Secret	AAP credential type	Reaches the playbook as
ServiceNow node stats account	**ServiceNow node stats login** (`servicenow_node_stats_login.yml`)	env `SN_STATS_USERNAME`, `SN_STATS_PASSWORD`; only with `servicenow_node_stats_auth: form`. Sent once per node per run to the node's own login page (HTTPS to its own name, or 127.0.0.1 on it); the session's cookies stay in memory; `no_log`, never in a result
MariaDB monitor account	**MariaDB monitor** (`mariadb_monitor.yml`)	env `MARIADB_MONITOR_USER` / `_PASSWORD`; the password goes to the client on stdin and reaches it only as `MYSQL_PWD` in its own environment (never a command line, never a fact)
STIG Manager API client	**STIG Manager API** (`stigman_api.yml`)	env `STIGMAN_TOKEN_URL`, `STIGMAN_CLIENT_ID`, `STIGMAN_CLIENT_SECRET` (token request is `no_log`)
Java keystore password	**Keystore password** (`keystore_password.yml`)	env `KEYSTORE_PASSWORD`; the inventory names the variable (`password_env`), never the value; the check reads it on stdin and `keytool` takes it with `-storepass:env` (never a command line). The trust store removal (`check_trust_remove`, Linux and Windows) takes the same credential when it is attached, else `check_trust_keystore_password` (keytool's default `changeit`) - `keytool` gets it the same way
vCenter account (VMware jobs)	built-in **VMware vCenter**	env `VMWARE_HOST`, `VMWARE_USER`, `VMWARE_PASSWORD` on the controller (the jobs talk only to vCenter)
NetApp ONTAP read-only account (ONTAP health report)	**NetApp ONTAP** (`netapp_ontap.yml`)	env `ONTAP_USERNAME`, `ONTAP_PASSWORD` on the controller; sent only to the clusters' REST API over HTTPS (basic auth); the job sends GET requests only
Cisco UCS Manager read-only account (UCS inventory)	**Cisco UCS Manager** (`cisco_ucs_manager.yml`)	env `UCSM_USERNAME`, `UCSM_PASSWORD` on the controller; sent only to UCS Manager's XML API over HTTPS (in the login request, never in a URL); the job sends logins, logouts and queries only, and always logs out

Secret	AAP credential type	Reaches the playbook as
Horizon service account (the `horizon_*.yml` jobs)	**Horizon API** (`horizon_api.yml`)	env `HORIZON_USERNAME`, `HORIZON_PASSWORD` (and `HORIZON_DOMAIN`) on the controller; sent only to the Connection Server's REST API over HTTPS (`POST /rest/login`), which answers a token for that job; the job logs out at the end
Mail relay login (emailed reports)	**SMTP relay** (`smtp_relay.yml`), only if the relay needs a login	env `SMTP_USERNAME` / `SMTP_PASSWORD`; sent only over STARTTLS or SSL (refused with `report_email_security: none`)

Create one credential of each type **per environment** (dev / test / prod) so a test job can never use production secrets.

Why environment variables and files, not extra variables

A credential type can inject into `extra_vars`, but then the secret is an ordinary play variable: any `debug` task, any failed task's error message, or `-vvv` output can print it. An environment variable or a file on the controller has to be read on purpose (`lookup('ansible.builtin.env', 'NAME')`), which keeps secrets out of the variable namespace unless a task asks for them. Files are the right choice for certificates and keys: AAP writes them to private temporary files that disappear when the job ends.

Rules for every playbook in this repository

1. `no_log: true` on every task that receives, compares, or writes a secret. On a loop, also set `loop_control: label:` to something harmless, or the item is printed.
2. `diff: false` on any task that writes secret material (copy/template of a key, a `.cnf` with a password). With AAP's *Show changes* enabled, a diff prints the file's contents.
3. **Never put a secret on a command line.** Command lines are visible in `ps`, in audit logs (`execve` records), and in verbose job output. Instead:
   - pass it on **stdin**: `podman secret create NAME -`, `podman login --password-stdin`;
   - or in a **file** the program reads (`--defaults-extra-file` for MySQL clients), created with mode `0600` and removed afterwards;
   - never `mysql -pPassword` or `curl -u user:password`.
   - never through Ansible's `environment:` keyword on a Linux host with become: Ansible puts those variables on the `sudo /bin/sh -c '...'` command line, which `ps` shows and sudo writes to the host's journal / `/var/log/secure` - `no_log` does not prevent that. Send the secret on the task's `stdin:` to a small `sh` that exports it (see `roles/check_mariadb/tasks/health.yml`).
4. **On the hosts, secrets are podman secrets**, not environment lines in unit files:
   - mounted as files where the image supports it (`MYSQL_ROOT_PASSWORD_FILE`, `MYSQL_PASSWORD_FILE`), with `mode=0400` and the container user's uid;
   - injected as an environment variable only when the application cannot read a file (`STIGMAN_DB_PASSWORD`): `Secret=NAME,type=env,target=VAR`.

Podman keeps the value out of the unit file and out of `podman inspect` (checked on podman 5.8; verify on your RHEL's podman). It is still readable by root on the host and inside the container, so protect root and the container.

5. **Private keys on disk:** `0600`, owned by root; certificate and CA files `0644`.
6. **Don't register command output that can contain secrets** without `no_log`, and never `debug: var=` a registered result from such a task.
7. **Fail closed**: assert a secret is present (with `no_log`) instead of letting a task run with an empty password.
8. **Changing a secret in AAP is not the same as rotating it.** For a database password the value inside MySQL must change too (`ALTER USER`). The deploy role refuses to silently swap a deployed database password; rotation is a separate, deliberate run.

The real trust boundary

AAP will not show a stored secret, but **any playbook it runs can print it**. So anyone who can:

- push to the branch or tag the AAP project uses,
- edit a job template (its playbook, credentials, or verbosity), or
- run a template with *Prompt on launch* for variables that change what the playbook does,

can extract every secret that template uses. Therefore:

- **protect the branch** (required reviews) and pin the project to a **tag**;
- give most people **Execute** on templates, not **Admin**; give only automation owners **Use** on credentials;
- keep *Prompt on launch* for variables off on templates that hold production credentials;
- review the **Activity Stream** (who changed which credential or template) regularly.

Keeping secrets out of Git

- `.gitignore` in this repository blocks common key/cert/vault-password file names.
- `.pre-commit-config.yaml` runs **gitleaks** on each commit (`pre-commit install`).
- The inventory in `inventories/example/` holds placeholders only; the real inventory lives in your work Git or as an AAP inventory.
- **No real host names or addresses either.** Every name in the repository is a placeholder (`vc01.example.mil`, `smtp.yoursite.mil`), every IP address is from the ranges kept for documentation (`192.0.2.x`, `198.51.100.x`, `203.0.113.x`), and the README and the changelog talk about features, never about one site. `tests/check_public.py` checks it in CI and on each commit. Your own site's words (a site code, a vCenter's name, a team, a ticket title) go in `~/.config/site-automation/private-words`, one per line, on the machine you commit from: they are looked for too, and the file never enters the repository.
- If a secret is ever committed: rotate it first, then remove it from history. Removing it from history alone is not enough, because clones and caches keep it.

Rotation checklist

Secret	How
TLS certificate	update the **TLS certificate** credential, re-run `stigman_deploy.yml` (nginx restarts)
Registry token	update the credential; the next run logs in with it
STIG Manager DB password	password-rotation run: `ALTER USER` in MySQL, update the podman secret, restart the API; then update the AAP credential - by hand, in that order (no playbook does it yet). Changing only the credential is refused by the next deploy (the password in MySQL would stay the old one). **Creating the database again** from nothing: launch the deploy once with `stigman_replace_secrets: true` (Prompt on launch, Variables) - never save it in the template
SSH key	add the new public key to the hosts, update the **Machine** credential, remove the old key
ACT / Teams	update the credential; nothing else
ServiceNow API account	change the password in ServiceNow, update the **ServiceNow API** credential, then run *ServiceNow - test ticket* (SERVICENOW_SETUP.md) to prove it works
MariaDB monitor account	change it in the database (`ALTER USER`), update the **MariaDB monitor** credential, run a health check with `health_checks=mariadb` (MARIADB.md)
WinRM login	change it in the directory, update the Windows **Machine** credential, run *Windows connection test*

37. Approved commands: what ACT may run by itself

ACT is a tool that runs **on each Linux server** when a job asks it to. This page explains, in plain words, which commands ACT runs by itself, which ones wait for a person, and how you add a command to the "run without asking" list.

Short version. There are three kinds of command:

Kind	Examples	What happens
Reading	`systemctl status chronyd`, `df -h`, `journalctl -u nginx`, `ss -tlnp`	ACT runs it. It never asks. **Nothing on this page limits reading.**
Changing, not on your list	`systemctl restart nginx`, `dnf -y install httpd`	Refused. The job says `NEEDS APPROVAL` and shows the exact command. A person approves it in the workflow.
Changing, on your list	the ones you wrote in `site_act_allow`	ACT runs it by itself (only at level `self-heal`).

The list is one setting: `site_act_allow`. You add a command by adding one line to it.

Read this first: two safety rules that you cannot switch off

1. **Some commands are never run by a job**, whatever you write. ACT itself never pre-approves a *catastrophic* command (recursive delete, disk or volume destruction, power off, reboot). And the step that applies an approved fix (the *Apply approved ACT fix* job, and the service-watch fix step) has its own last check: reboot, shutdown, `kexec`, `mkfs`, `fdisk`, `usermod`, `passwd`, recursive deletes of system folders and a few more are refused **even after a person approved them** - also with a path in front (`/sbin/reboot`) or inside `bash -c '...'` / `$( )`. Patching and restarts have their own job: RUNBOOKS.md, section "Patch hosts".
2. **AAP itself is never fixed by a job.** Hosts in the groups `aap` and `aap_hosts` are diagnose-only: ACT reads and proposes, and the apply step prints the command for a person to run by hand. Nothing you set can remove those two groups (they are built into the code).

Everything below works inside those two rules.

How a command becomes "approved": the three ways

Way 1: a person approves it (the workflow), nothing to configure

This is the default at level `diagnose`.

1. The health check finds a problem. ACT investigates by reading, then proposes the fix.
2. Because the fix changes something and is not on any list, ACT is **refused** and the job fails with `NEEDS APPROVAL - ... ACT proposes: systemctl start chronyd`.
3. The workflow stops at its **Approval** step. The approver reads the proposal and approves or denies.
4. *Apply approved ACT fix* runs **exactly the approved text**, no model involved, then the checks run again.

What the approver sees is what runs. To set this up, see ADDING_ACT.md and WORKFLOWS_AND_SCHEDULES.md.

Two details worth knowing:

- Only a **plain single command** can go through this path (see the character rule below). A proposal such as `cd /x && ./fix.sh` or `something | tee file` is listed in the report as a **manual fix**: a person runs it by hand. That is deliberate.
- The approval covers that command on the hosts that proposed it, once. It does not add the command to any list. Next week the same problem needs the same approval.

Way 2: you put it on the list (site_act_allow), for fixes you trust

Use this for boring, safe, repeated fixes: start a stopped service, restart a hung one. It only takes effect at level `self-heal`. At `explain` and `diagnose`, the list is ignored.

YAML

```
site_act_allow:
  - 'systemctl restart (chronyd|rsyslog|crond)'
  - 'systemctl start (chronyd|rsyslog|crond)'
```

Where to put it, step by step, is in the next section.

Way 3: --allow on the ACT command line (when you run ACT by hand)

If you run `act` on a server yourself, the same idea is `--allow`:

shell

```
act --allow 'systemctl restart (nginx|httpd)' "the web server is down; find out why and fix it"
```

`site_act_allow` is this, done for you: each list item becomes one `--allow` when the job calls ACT. (Full ACT reference: "Approved commands" in ACT's own README.)

At the prompt that ACT shows when you run it by hand (`run? [y]es / [n]o / [e]dit / [q]uit`) there is **no "always allow" answer**. This is on purpose: the list is the only way to make ACT stop asking, and the list is in Git, where a reviewer can see it.

Add an approved command, step by step

You need: VS Code with this repository, and the command as you would type it on the server.

Step 1: write the command exactly as ACT would run it

Try it by hand on a lab server first: `sudo systemctl restart chronyd`. Note the words in between: `systemctl restart chronyd` (drop `sudo`; ACT already runs as root on the host).

Step 2: turn it into a pattern

A pattern is a *regular expression* that must match the **whole** command, from the first character to the last. `systemctl restart chronyd` on its own is already a valid pattern that matches exactly that command and nothing else. Start there. Widen it only when you have to:

You want	Pattern	Matches	Does not match
exactly one command	`systemctl restart chronyd`	`systemctl restart chronyd`	`systemctl restart chronyd.service`
a short list of services	`systemctl restart (chronyd|rsyslog|crond)`	`systemctl restart rsyslog`	`systemctl restart sshd`

You want	Pattern	Matches	Does not match
restart or start	`systemctl (start|restart) (chronyd|rsyslog)`	`systemctl start rsyslog`	`systemctl stop rsyslog`
a unit name with a dot	`systemctl restart chronyd\.service`	`systemctl restart chronyd.service`	`systemctl restart chronydXservice`
a container	`podman restart (mysql|nginx)`	`podman restart nginx`	`podman rm -f nginx`

(In the YAML file, write `|` normally. The `\|` above is only how a table shows a bar.)

Rules for the pattern:

- **The whole command must match.** `systemctl restart .*` looks like "restart anything", but it can only match a plain command. It is also far too wide: it would let ACT restart `sshd` and the network. Name the services.
- **Only a plain single command counts.** The command may contain only letters, digits and these characters: `space _ . / : = @ % + , -`. Anything else is never pre-approved, however you write the pattern: no `; && ||` (chaining), no `|` (pipes), no `> <` (redirection), no `$( )` or backticks, no `*` or `?` (globs), no quotes, no `~`, no line breaks. Such a command still needs a person.
- **A dot in a pattern means "any character".** Write `\.` when the exact dot matters, as in `chronyd\.service`.
- **No file edits.** A pattern covers `run` commands only; ACT changing a file (edit or write) always needs a person.
- **Dangerous commands are never approved by a pattern**, whatever you write: ACT's danger tier (package removal such as `dnf -y remove httpd`, `usermod -aG wheel alice`, `chmod 777`, `podman rm -f mysql`, `rm -f`, ...) and reboots, power-off and disk tools always need a person (tested with ACT 0.6.21). They come back as `NEEDS APPROVAL` / manual fixes.
- **Never put these on the list** anyway: `.*` on its own, `systemctl (stop|disable|mask) .*`, `kill .*`. Those are ordinary changes a pattern *can* approve, and far too wide: `systemctl stop .*` would let ACT stop `sshd`.

Step 3: put it in the right settings file

`site_act_allow` is a setting like any other (VARIABLES.md explains where settings live). Pick the place that matches who should get it:

Who gets the command	Where to write it
Every host	`playbooks/group_vars/all.yml`: add the lines at the end of the file (copy the example below).
One group (for example `stigman`)	`playbooks/group_vars/stigman.yml` (the file name is the AAP group name)
One host	`playbooks/host_vars/<host name as in the inventory>.yml` (create the folder and file if they do not exist)
One template, every run	the job template's **Variables** box (extra variables), YAML: `site_act_allow: ['systemctl restart chronyd']`

A list replaces, it does not add. If `all.yml` has two commands and `stigman.yml` has one command, the stigman hosts get **only that one**. Repeat the ones you keep. (The exact order of who wins is in VARIABLES.md.)

Example, `playbooks/group_vars/all.yml`:

```yaml
site_act_allow:
  - 'systemctl (start|restart) (chronyd|rsyslog|crond)'
```

Use single quotes. Keep the indentation. Spaces, never tabs.

Step 4: save, commit, sync

In VS Code: save, **Commit**, **Sync Changes**. AAP picks the file up on the next run (the project syncs when *Update revision on launch* is ticked).

Step 5: use the level self-heal

Launch the check with `use_act` = `yes` and `site_act_level` = `self-heal` (the survey question on the Health check and Troubleshoot templates; ADDING_ACT.md).

How to verify it worked

Do all three. They take ten minutes and catch the usual mistakes.

1. Check the pattern matches (and only what you meant). No server needed. In PowerShell:

```
$p = 'systemctl restart (chronyd|rsyslog|crond)'      # your pattern, without the quotes' worth of
                                                      # YAML
foreach ($c in 'systemctl restart chronyd',            # should be True
               'systemctl restart sshd',               # should be False
               'systemctl restart chronyd; reboot') {  # should be False
  '{0,-40} {1}' -f $c, ($c -cmatch ('\A(?:' + $p + ')\z'))
}
```

Expected output: `True`, `False`, `False`. (Verified. The same test in Python, on a machine that has `vendor/act/act`: load it with `importlib` and call `compile_preapproved`/`preapproved_pattern`; ACT applies exactly `\A(?:your pattern)\Z`.) Add a line for every command you want to *stay* refused and check it prints `False`.

2. Check ACT itself agrees, on a lab server. Log in, put your key in the environment the way SECRETS.md describes, and run ACT in the same mode a job uses. It will not ask anything; it either runs what you allowed or refuses:

```shell
sudo systemctl stop chronyd                # break it on purpose (lab server only)
act --non-interactive --allow 'systemctl (start|restart) chronyd' \
    --result-file /tmp/r.json "chronyd is stopped; find out why and fix it"
echo "exit code: $?"                       # 0 = fixed, 4 = something was refused
python3 -m json.tool /tmp/r.json | less    # see commands[].approval and denied[]
```

In `/tmp/r.json`: `commands[].approval` says `pre_approved` for what your list allowed (with the `pattern` that matched) and `auto` for reads. `denied[]` lists what was refused, each with `pre_approvable`: `true` means "a pattern could approve this" (add one if you want it); `false` means a person has to do it.

3. Check the job. On the same lab server, launch **Health check** with `use_act` = `yes`, `site_act_level` = `self-heal`. In the output:

- `ACT | what ACT says` shows `APPLIED (pre-approved): systemctl start chronyd`;
- the report afterwards says `cleared: ...`.

Then break something that is **not** on your list and check the job says `NEEDS APPROVAL` and does not touch it. A dry run (job type *Check*) does not call ACT, so it cannot test this; see DRY_RUNS.md.

If it does not work

You see	Why	Fix
`NEEDS APPROVAL` for a command you listed	the pattern does not match the **whole** command; or a listed command contains a `;`, `|`, quote or glob; or the level is `explain`/`diagnose`, not `self-heal`	run check 1 with the exact command from the job output; fix the pattern or the level
the command is in `manual fixes`, not `proposed`	it is not a plain single command	ask ACT for a simpler fix, or apply by hand
the setting seems ignored	a more specific place wins (the group or host file, or the template's Variables box)	see the order in VARIABLES.md; the job prints a notice when a settings file overrides the AAP Variables box
an invalid pattern	ACT does not run: the job shows `ACT error ... invalid --allow pattern '...'` and the reason (for instance an unbalanced bracket)	fix the YAML/regex
a command on an AAP host does not run	by design: AAP is diagnose-only	run it by hand from the printed line
the approved command was refused at apply time	the apply-time guard (reboot, shutdown, `mkfs`, `usermod`, recursive delete of a system folder, ...)	do it by hand if you really mean it

Reference: what the guard rails are

Where	Rule	Can you change it?
ACT, every command	proven read-only commands run without asking; everything else asks	no (it is the design)
ACT, `--allow` / `site_act_allow`	anchored to the whole command; plain characters only; never catastrophic; never a file edit	you choose the patterns
ACT, `--auto`	runs reads and ordinary changes without asking, still asks for the danger tier. Not used by these jobs	not used
`site_act_diagnose_only_groups`	hosts where ACT never fixes; the list *you* write replaces the shipped one (`sat`, `idm`, ...), but `aap`, `aap_hosts` are always kept	you choose the groups; you cannot remove `aap`/`aap_hosts`
Apply-time guard (`_apply_refuse`, `roles/site_findings/vars/main.yml`)	last check before an approved command runs	edit the code to change it
Host log	`/var/log/site-automation-fix.log` on each host lists what the apply job ran, when, and for which AAP job and user	

The apply-time guard applies to the **approval** path (Way 1). Commands run by **self-heal** (Way 2) are run by ACT itself, so what protects you there is your list. Keep it short and boring.

Windows

`site_act_allow` is read by the Linux jobs. Windows servers use the approval path only (ACT proposes, a person approves); see WINDOWS.md. If you run ACT for Windows by hand, its `-Allow` option follows the same rules as Linux `--allow`:

	Linux ACT (--allow)	Windows ACT (-Allow)
A pattern that names a danger-tier command (for example `dnf -y remove httpd`, `podman rm -f mysql`)	**does not** approve it	**does not** approve it
A danger-tier command in an unattended run	**always refused**; only a person at an interactive prompt can approve it	the same
Catastrophic commands	never	never
`git`, cmd built-ins, aliases such as `ls` and `dir` in an unattended run	follow the rules above	**still ask**, because they were never on Windows ACT's unattended list
Result file (`--result-file` / `-ResultFile`)	written (since 0.6.16)	written (since 0.6.16; its `tokens` field is filled since 0.6.21)

(ACT 0.6.20 for Linux, released for a few minutes on 2026-09-30, let a pattern approve a danger-tier command; 0.6.21 and later (this project carries 0.6.22) do not. The Windows rows are taken from ACT-Windows 0.6.22 and its self-tests and were not run by hand on a Windows server.)

38. The MariaDB and MySQL check, step by step

There are **two ways to run the database check**, and both check **MariaDB and MySQL** (MySQL 5.7, 8.0 and 8.4, MariaDB 10.x and 11.x, and Percona), installed on the host or **in podman containers** (one, several, found automatically, rootless):

How	Job template	Use it when
Its own template	**Database health - MariaDB / MySQL** (`playbooks/database_health.yml`; SETUP_AAP.md)	the database team wants its own job, schedule and tickets. Runs only this check, on every database server it is pointed at
Part of the Health check	**Health check** with `health_checks` = `mariadb`, `mysql` or `database` (all three are the same check; `daily` includes it)	you already run the Health check and want the databases in it

This page shows how to turn the check on, how to give it a login, and how to see that it works. Nothing here needs you to know Ansible. It changes nothing on the database: the check only asks status questions and never reads your data.

Words used here:

- **container name** - the name podman gives a container. You read it with `podman ps -a`.
- **rootless** - the container belongs to an ordinary user (not root). Only that user can see it.
- **settings file** - a small file in `playbooks/group_vars/` that holds your choices for one group of hosts. See VARIABLES.md.

The short version

1. On the database host, find the container name: `sudo podman ps -a` (rootless: `sudo -u THE_USER podman ps -a`).
2. Put the name in the settings file for your MariaDB group (section 3).
3. Ask the DBA for a read-only monitoring account and put it in an AAP credential (section 4).
4. Run the **Database health** job (or the *Health check* with `health_checks` = `mariadb`) and read "How to verify" below.

1. Which hosts the check runs on

The check runs on a host when **any** of these is true:

- the host is in one of the inventory groups `mariadb_hosts`, `mysql_hosts`, `database_hosts`, `mariadb` or `mysql` (any of the five works, for either engine), or
- the host has a container name set (section 2), or
- you set `check_mariadb_enabled: true` for the host or its group.

The **Database health** template does not need this: every server it runs on is checked. It runs on the groups `mariadb_hosts`, `mysql_hosts`, `database_hosts`, `mariadb` and `mysql` (since 0.6.0; before that only the first three). A **Limit** only narrows that list; it cannot add a server that is in none of them. For a server outside those groups, put `target: <group or host>` in the template's **Variables** box, or add the server to one of those groups. If `target` matches no host, the job stops with a message that lists the groups your inventory does have. On every other host, in the Health check, the job prints `skipped: the MariaDB/MySQL check is`

`off for <host>` and moves on. That is normal; it is not an error.

2. Tell it where MariaDB is

Pick **one** of the four ways. Put the lines in the settings file (section 3).

Your situation	Setting
MariaDB or MySQL is installed on the host itself (a service)	nothing to set. The check finds the service `mariadb`, `mysqld` or `mysql` and tells the engine and version apart by itself. To name the service: `check_mariadb_service: mariadb`
In a podman container, with **no** database server installed on the host, or started by a unit that runs podman (`podman compose up -d`, `podman start` - such a unit shows `active (exited)` or `inactive` while the database runs)	usually nothing to set (0.7.0 and later): the check sees that and finds the container by its image. Naming it is still clearer: `check_mariadb_container: mariadb`
One container	`check_mariadb_container: snow-mariadb`
Several containers on the same host	`check_mariadb_containers: [snow-mariadb, other-db]`
You do not want to list them: find them	`check_mariadb_container_discover: true`

Details that matter:

- **Discovery** looks at every container on the host, running or not, and picks the ones whose **image name** matches `check_mariadb_container_image_regex` (default `(mariadb|mysql|percona)`). If your image has another name, change the pattern, for example `'(mariadb|snowdb)'`. Discovery that finds nothing is reported as a warning `mariadb:no-container`, so a wrong pattern is not silent.
- With **several** instances on one host, each is checked on its own. Their findings start with the container name, for example `[snow-mariadb] 143 of 151 connections in use`.
- The check runs the database's own client **inside** the container (`podman exec`), so you do not need a client on the host and you do not open any network port.
- The engine (MariaDB or MySQL) and its version are read from the server, so the same settings work for both.
- A container that is named but does not exist is reported as `mariadb:down` ("MariaDB/MySQL is not running (container ... is missing)"), not skipped.

Rootless containers

When the containers belong to a user, name that user:

```yaml
check_mariadb_container_user: appuser
```

The check then runs podman **as that user** (the job needs privilege escalation, which the templates in SETUP_AAP.md already have). If that user does not exist on the host you get the critical finding `mariadb:user`, with the hint `getent passwd <user>`. Leave the setting empty for containers that belong to root.

3. Where to put the settings

Open `playbooks/group_vars/mariadb.yml` (MySQL: `playbooks/group_vars/mysql.yml`) in VS Code. It already holds the lines below as comments. Remove the `#` in front of the ones you need and replace `CHANGE-ME`:

```yaml
check_mariadb_enabled: true
check_mariadb_container: snow-mariadb
# check_mariadb_container_user: appuser      # only for rootless containers
```

A settings file applies to the group with the same name as the file. `mariadb.yml` is for the group `mariadb`, `mysql.yml` for `mysql`. If your hosts are in a group with another name (the example inventory uses `mariadb_hosts` and `mysql_hosts`), copy the file to `playbooks/group_vars/<your group name>.yml`. The check accepts all five group names, but the *settings* are only read from the file that matches the group. (The **Database health** template runs on the `_hosts` groups only: for a group called `mariadb` or `mysql`, give it a `target`, see section 1.) One host that differs from the rest: `playbooks/host_vars/<host name>.yml` (create it). Which place wins, and how to set the same thing in AAP's own Variables boxes, is in VARIABLES.md.

Then commit, push, and run **Sync** on the project in AAP.

4. The login: the "MariaDB monitor" credential

Where the database runs	What to do
MariaDB installed on the host	Usually nothing. Run with privilege escalation and the check logs in as root through the local socket (RHEL's default).
MySQL installed on the host	Usually the credential: MySQL's root account normally has a password.
In a container (either engine)	Use the credential. The official images give root a password, and without it the job reports a finding that contains `Access denied` and ends with `attach the "MariaDB monitor" credential`. Each container has its **own** root password: with several on one host, create one monitoring account with the same password in each (below) rather than using root.

Steps:

1. Ask the DBA to run this **inside that database** (the account needs no data access). The privileges differ by engine:

```sql
CREATE USER 'aap_monitor'@'localhost' IDENTIFIED BY '<password>';

-- MySQL 5.7 / 8.0 / 8.4:
GRANT PROCESS, REPLICATION CLIENT ON *.* TO 'aap_monitor'@'localhost';
-- MySQL Group Replication only, also:
GRANT SELECT ON performance_schema.* TO 'aap_monitor'@'localhost';

-- MariaDB 10.5.9 and newer:
GRANT PROCESS, REPLICA MONITOR ON *.* TO 'aap_monitor'@'localhost';
-- MariaDB before 10.5.9:
GRANT PROCESS, REPLICATION CLIENT ON *.* TO 'aap_monitor'@'localhost';
```

On MariaDB 10.5.9 and newer, `REPLICATION CLIENT` **is not enough:** it no longer covers the replication status, so the account needs `REPLICA MONITOR`. `PROCESS` lets the check see other sessions (for long queries).

Without the replication privilege the check still works and reports `mariadb:replication-query` (below) with the grant to ask for. The host is `localhost` because the client runs inside the container.

2. In AAP create a credential of type **MariaDB monitor** (the type is in `aap/credential_types/mariadb_monitor.yml`; SETUP_AAP.md shows how to load it). Type the account name and password into the credential. **Never** put the password in a settings file, the inventory or Git: SECRETS.md.
3. Attach the credential to the **Database health**, **Health check** and **Troubleshoot** job templates. Credentials attach to templates, not to groups; the check only uses it on hosts that have a database.

The password reaches the client only through its environment (`MYSQL_PWD`, and `podman exec -e MYSQL_PWD` for containers), never on a command line. If your client needs other options, for example a socket path or a TCP address, use `check_mariadb_client_args: ['--socket=/var/lib/mysql/mysql.sock']`.

5. What it checks, and the limits you can change

Replication is read with the statement that fits the engine: `SHOW ALL SLAVES STATUS` (MariaDB), `SHOW REPLICA STATUS` (MySQL 8.0.22 and newer, 8.4) or `SHOW SLAVE STATUS` (older MySQL). The job's status line names the engine, for example `MySQL 8.4.11 - container snow-mysql (podman, image ...): up 312.4 h, 23/151 connections, ...`.

Each limit is a setting. The defaults are in the table; change one the same way as in section 3.

Finding	Turns on when	Setting (default)
`mariadb:down`	the service or container is not running, or the named container does not exist	-
`mariadb:connect`	it runs but the status query failed (login, hang)	-
`mariadb:restarted`	restarted less than this many minutes ago	`check_mariadb_restart_warn_minutes` (60)
`mariadb:connections`	connections in use, percent of `max_connections`	`check_mariadb_conn_warn_pct` (80), `check_mariadb_conn_crit_pct` (95)
`mariadb:refused`	clients were refused because the limit was reached	-
`mariadb:threads-running`	queries executing at this moment	`check_mariadb_threads_running_warn` (32)
`mariadb:long-queries`	a query ran longer than this many seconds (never the query text)	`check_mariadb_long_query_seconds` (300)
`mariadb:bufferpool`	percent of reads served from memory (judged after 1 million reads)	`check_mariadb_bufferpool_hit_warn` (95)
`mariadb:replica:<name>`, `mariadb:replica-lag:<name>`	replication stopped, or behind by seconds	`check_mariadb_replica_lag_warn` (300), `check_mariadb_replica_lag_crit` (1800)

Finding	Turns on when	Setting (default)
`mariadb:replication-query`	the replication status could not be read (usually a missing privilege; the finding names the grant)	section 4
`mariadb:galera`, `mariadb:galera-size`	Galera / XtraDB Cluster node not healthy; cluster smaller than expected	`check_mariadb_galera_size` (0 = not Galera; set 3 for three nodes)
`mariadb:group`, `mariadb:group-size`	MySQL Group Replication: a member is not ONLINE (or none is listed); fewer ONLINE members than expected	`check_mariadb_group_size` (0 = do not check the size; set 3 for three members)
`mariadb:group-query`	the Group Replication members could not be read (needs `SELECT` on `performance_schema`)	section 4
`mariadb:errorlog`	`[ERROR]` lines in its log this recent (days)	`check_mariadb_error_since_days` (1)
`mariadb:disk`	the disk holding the data directory is this full (percent)	`check_mariadb_disk_warn_pct` (85), `check_mariadb_disk_crit_pct` (95)
`mariadb:user`	`check_mariadb_container_user` names a user that does not exist	-
`mariadb:no-container`	discovery found no container with a matching image	`check_mariadb_container_image_regex`
performance (warnings): `mariadb:slow-queries`, `tmp-disk`, `full-joins`, `table-locks`, `row-locks`, `deadlocks`, `bufferpool-wait`, `log-waits`, `aborted-connects`, `table-cache`	averages since the server started, judged after it has run 2 hours: slow queries per hour, % of temporary tables on disk, joins without an index per hour, table lock waits, average row lock wait, deadlocks per hour ...	`check_mariadb_performance` (true), `check_mariadb_perf_min_uptime_hours` (2), `check_mariadb_slow_per_hour_warn` (60), `check_mariadb_tmp_disk_pct_warn` (25), `check_mariadb_full_join_per_hour_warn` (100), `check_mariadb_table_lock_wait_pct_warn` (1), `check_mariadb_row_lock_avg_ms_warn` (500), `check_mariadb_deadlocks_per_hour_warn` (1), `check_mariadb_innodb_waits_per_hour_warn` (1), `check_mariadb_aborted_connects_per_hour_warn` (60), `check_mariadb_table_open_per_hour_warn` (600)
performance, now (warnings): `mariadb:lock-waits`, `long-transactions`, `purge-lag`, `open-files`	a session waiting this many seconds for a lock; a transaction open this long (idle ones are named); InnoDB history list length; files open, % of `open_files_limit`	`check_mariadb_lock_wait_seconds` (30), `check_mariadb_long_trx_seconds` (600), `check_mariadb_history_length_warn` (1000000), `check_mariadb_open_files_warn_pct` (85)

The finding ids keep the `mariadb:` prefix for MySQL too, so existing tickets and filters still match. What each finding means and the usual cause are in RUNBOOKS.md. Every setting with its default is in VARIABLES_REFERENCE.md. With several containers on one host, the finding id includes the container

name, for example `mariadb:snow-mariadb:connections`.

All settings of this job, with their defaults: check_mariadb.

How to verify

1. **The names are right.** On the database host: `sudo podman ps -a` (rootless: `sudo -u THE_USER podman ps -a`). The name you put in the settings file is in the NAMES column.
2. **The account works.** On the host, run the client inside the container as the monitoring account (it asks for the password; type it here, not in a file):

```shell
sudo podman exec -it snow-mariadb mariadb --user=aap_monitor -p -e "SHOW GLOBAL STATUS LIKE
  'Uptime'"
```

A number back means the login and the `PROCESS` rights work. (Some images have `mysql` instead of `mariadb`.)

3. **Run the job.** In AAP launch **Database health - MariaDB / MySQL** (first as *Check*, then as *Run*; SETUP_AAP.md), or the **Health check** with `health_checks` = `mysql` (or `mariadb`, or `database`) and a Limit of the database host. In the output, find the task `MariaDB | status`. It prints one line per instance, like `MariaDB 11.8.9 - container snow-mariadb (podman, image ...): up 312.4 h, 23/151 connections, 1 running, 0 long queries, replication connections 0`. That line proves the check reached the database. Each host then prints `HEALTHY` or its findings, and the job ends with `N healthy, M with findings`.
4. **No findings** means the database is healthy by these limits. To see a finding on purpose, set a limit that is sure to trip, for example `check_mariadb_conn_warn_pct: 1`, run again, look for `mariadb:connections`, then remove the line.

What was tested, and what was not

Tested against real containers (throwaway rootless podman)	Tested only against a fake podman
MySQL 8.0.46, MySQL 8.4.11, MariaDB 11.8.9: the engine and version are recognised; a replication source that never connects is reported as broken; the error log is read; a login with no credential gives `mariadb:connect` with the grant to ask for; the `REPLICA MONITOR` grant and revoke on MariaDB behave as described above	MySQL 5.7, and MySQL Group Replication (`mariadb:group`, `group-size`, `group-query`). They follow the documented statements but have not met a real server. The **performance** findings (0.15.0): their queries use documented status variables and `information_schema` tables of both engines, but only the fake has answered them so far.

The fake-podman test (`bash tests/mariadb/run_mariadb_test.sh`) covers one container, several, discovery, a stopped and a missing container, a rootless user that does not exist, MySQL 5.7, 8.0 and 8.4, replication, Group Replication, a denied grant, and that the password never appears on a command line. Nothing here has been run against **your** database: step 3 is the real proof.

If it does not work

You see	Cause	Fix
`skipped: the MariaDB/MySQL check is off for <host>` (Health check only)	the host is in none of the five groups and no container is named	section 1, or use the **Database health** template
`mariadb:replication-query`	the account lacks the replication privilege (MariaDB 10.5.9+: `REPLICA MONITOR`, not `REPLICATION CLIENT`)	section 4
`mariadb:no-container`	discovery matched nothing, or podman is run as the wrong user	`podman ps -a` as the right user; set `check_mariadb_container_image_regex` or `check_mariadb_container_user`
`mariadb:user`	the rootless user name is wrong	`getent passwd <user>` on the host
`refused the login in container ...: Access denied ...` and `attach the "MariaDB monitor" credential`	container root has a password	section 4
`refused the login of root (the MariaDB monitor credential) in 2 containers (db1, db2): Access denied ... (using password: YES) - most likely its password is wrong for these containers`	each database container has its own root password (set when it was created); the credential has one of them, or none	see a container's: `podman inspect <container> | grep -i ROOT_PASSWORD`. Better: one read-only monitoring account with the same password in every container (section 4, in each container), or `check_mariadb_containers` to read only the ones the credential may log in to. The finding's *How to look* has the commands, one per line
`... is not running (container ... is missing)` but it is running	the name is wrong, or the containers belong to another user	compare with the `podman ps -a` output; `check_mariadb_container_user`
The check runs on the wrong host, or not at all after a rename	a settings file only applies to the group named like the file	section 3
`MariaDB is not running (service mariadb is inactive)` - or a login error from the host's client - but `podman ps` shows the database container up	the host's `mariadb.service` only starts the container (`podman compose up -d`); before 0.7.0 the check took it for the database	0.7.0 and later find the container by themselves; or name it: `check_mariadb_container: mariadb`
Database health says `skipping: no hosts matched` (0.5.0), or `target '...' matches no host`	the server is in none of `mariadb_hosts`, `mysql_hosts`, `database_hosts`, `mariadb`, `mysql` (a Limit cannot add it)	section 1: `target` in the template's Variables, or add it to one of those groups
Your setting has no effect	another place wins	VARIABLES.md

39. Active Directory health report and account lockout

One job, `playbooks/ad_health_report.yml`, reads every domain controller (DC) in the Windows inventory and emails one report for the whole domain: what is broken first, then replication, DNS, time and SYSVOL, then **what changed** in the last 24 hours (privileged groups, accounts, Group Policy, schema and configuration). Each row is coloured: red = critical, amber = warning, green = OK, blue = for your information.

It only reads. Each DC runs a PowerShell script over WinRM (the same way the Windows health check does) that queries Active Directory, runs `dcdiag` tests that only read, `repadmin /showrepl`, `/queue`, `/showutdvec` and `/showbackup`, `w32tm /query` and `/stripchart`, `nltest /sc_verify`, and reads the event logs. It changes nothing: it does not run dcdiag's `DnsDynamicUpdate` test (that one writes a test record), and it does not run `repadmin /syncall`, `/replicate` or anything else that acts.

A second job, `playbooks/ad_lockout.yml`, is for the service desk: is an account locked out, and **which computer is locking it out** - see Account lockout at the end.

No domain admin? Where only Domain Admins may log on to the DCs, the job reads the domain from the AAP side as a plain domain user instead - over LDAP, DNS and Kerberos, no WinRM: see Without a domain admin (1.4.0, `ad_health_mode`).

No second hop. Every DC asks only itself (`localhost`). AD is replicated, so the DC that reads the domain has every object in its own copy, and the replication metadata says on which DC a change was made. So the job works over WinRM with NTLM or Kerberos and needs no delegation or CredSSP.

What the report shows

At the top: the title with the number of critical and warning findings, then boxes with the main counts (DCs read, replication, dcdiag, services, SYSVOL / GPO, FSMO / DNS / time, privileged changes, accounts created / deleted, GPO changes). Then, in this order:

Section	What it shows	Colours
Domains	each domain: functional levels, schema version, DCs checked / in AD, the PDC emulator, tombstone lifetime, Recycle Bin, RID pool left, the oldest partition's last backup, the krbtgt password's age, the SYSVOL migration state	amber Recycle Bin off, krbtgt older than 180 days, FRS; red RID pool under 2 %, backup older than 30 days or the tombstone lifetime
Domain controllers	each DC: site, OS, GC / RODC, the FSMO roles it holds, LDAP answering (and synchronized), DC services not running, dcdiag's failed tests, SYSVOL, its clock, the least free space of its database, log and SYSVOL volumes, uptime. A DC in AD that is not in the inventory is listed in blue	red unreachable, LDAP down, not synchronized, a DC service stopped

Section	What it shows	Colours
Operations masters (FSMO)	who holds each role, whether that holder still exists as a DC, whether it answers on LDAP	red holder gone or not answering
Inbound replication	links with a problem only (`repadmin /showrepl` on each DC): partition, partner, failures, last success, last error with what the code means	amber 6 h without success, red 24 h, a failing link, or longer than the tombstone lifetime; amber 50+ requests in the queue
Replication from every DC (up-to-dateness)	how long ago each DC's latest change reached the DC that read the domain (`repadmin /showutdvec /latency`): this also catches a DC that is **not in the inventory** and stopped replicating	amber 6 h, red 24 h
dcdiag	the failed tests and what dcdiag said. `SystemLog` is skipped by default (the Events section covers it)	red Connectivity, Advertising, NetLogons, Replications, SysVolCheck, Services, KnowsOfRoleHolders, RidManager, MachineAccount; amber the others
DNS	dcdiag's DNS tests that only read (basic, forwarders, delegation, record registration), and the SRV records `_ldap` / `_kerberos` (`dc._msdcs`) and `_ldap._tcp.gc`: every DC must be registered	red record missing; amber a DC not registered, a DNS test failed
Time	each DC's source, stratum, last sync, offset: a DC against the PDC emulator, the PDC against its NTP source	red the PDC on its own clock, 60 s off; amber 5 s off, no sync for 24 h
Events	the Directory Service, DFS Replication and DNS Server logs, and the Netlogon, KDC, time and Group Policy entries of the System log: the events that matter on a DC, with what they mean (2042, 1388 / 1988 lingering objects, 2087, DFSR 2213 / 4012, LDAP signing 2887, Netlogon 5719 ...), and every other error in blue	per event
Clients in no site	client addresses in no AD subnet (`netlogon.log` NO_CLIENT_SITE), and subnets linked to no site	amber
Certificates (LDAPS and Kerberos)	the newest LDAPS and KDC certificate of each DC	amber 30 days, red 7 days; blue none
Trusts	every trust; outbound and two-way trusts verified (`nltest /sc_verify`)	red does not verify

Section	What it shows	Colours
Sites	each site, its DCs and subnets	blue no DC or no subnet
Privileged group changes	members added to or removed from Domain / Enterprise / Schema Admins, Administrators, Account / Server / Print / Backup Operators, Group Policy Creator Owners, Key Admins, Cert Publishers, DnsAdmins (and your own): when, which DC, **by whom**	amber (`ad_privileged_change_severity`)
Privileged groups	their direct members now	amber a group in `ad_groups_should_be_empty` with a member
Users, groups and computers created or deleted	when, where, by whom	blue
Accounts enabled, disabled, locked or unlocked	when, which DC, by whom; the accounts locked out now	blue
Group Policy changes	GPOs created, changed, deleted; OUs, domains and sites whose links changed (and what is linked there now)	blue
Group Policy: AD against SYSVOL	GPOs with no SYSVOL folder, GPOs whose version differs in AD and SYSVOL, SYSVOL folders with no GPO	amber / blue
Schema and configuration changes	schema version and new classes / attributes, sites, subnets, site links, DCs added or removed, new trusts	amber schema and trusts; blue the rest (`ad_dc_change_severity`)
Security log: notable events	the Security log cleared on a DC (red), the DSRM password set, trusts created / removed, the domain policy changed	per event
Not read	anything a script could not read, with the reason	

When and **which DC** come from AD's replication metadata, which every DC keeps: no audit policy is needed for them. **By whom** comes from the Security log of the DC the change was made on (events 4720, 4722, 4725, 4726, 4728-4733, 4741, 4743, 4756, 4757, 4767), so it is filled in only when *Audit Security Group Management*, *Audit User Account Management* and *Audit Computer Account Management* are on (the DISA STIG asks for all three), and that DC is in the inventory.

The job's artifacts (`ad_health`) have every finding, for a workflow or ServiceNow.

Before you start

1. The DCs in the Windows inventory

The DCs go in the group `win_dc` of your Windows inventory (the example has it: `inventories/example-windows/hosts.yml`). WinRM is set up as for every Windows server (WINDOWS.md, steps 1 to 5). Test it with *Windows connection test* and Limit `win_dc`. An inventory whose DCs are in a group named `domain_controllers` instead (and no `win_dc`) works as it is (1.1.0): with no `target`, both jobs read `win_dc` when the inventory has that group, else `domain_controllers`. Another name: `target: <your group>` on the templates.

Put **every** DC in the group if you can. A DC that is not there is still covered by the domain-wide sections (replication from every DC, SRV records, FSMO, the changes), but its own services, dcdiag, events, time and disks are not read, and changes made on it show no "by whom".

2. The account

`dcdiag` and `repadmin` need administrator rights **on the DCs**, and the local Administrators group of a DC is the domain's built-in Administrators group: there is no smaller group that lets them run. So the job needs an account in the domain's **Administrators** (or **Domain Admins**) group - or, without one, reader mode with a plain domain user (Without a domain admin).

- Make a **dedicated** account for it (e.g. `svc_aap_adhealth`), used by nothing else.
- Treat it as tier 0: allow it to log on to the DCs only (*Log on to* / an authentication policy silo), and add it to **Protected Users** if your AAP uses Kerberos (Protected Users blocks NTLM).
- Its password lives only in AAP, in a **Machine** credential of its own, e.g. `Windows DCs (WinRM)` (same fields as the `Windows (WinRM)` credential of WINDOWS.md, step 3).

Reading the **Deleted Objects** container (for "deleted" in the changes) also needs these rights; with less, that part is listed under *Not read* and the rest of the report is complete.

3. On the DCs

- The **ActiveDirectory** PowerShell module (`RSAT-AD-PowerShell`): installed with the AD DS role, so every DC has it unless it was removed. Without it the DC's LDAP checks and the domain-wide part are skipped and the report says so (amber).
- **English** dcdiag output: the job reads dcdiag's `passed test` / `failed test` lines. On a DC with another display language, dcdiag's results are reported as *not run* (amber).
- Windows Server 2012 R2 and later; Windows PowerShell 5.1. Constrained Language Mode (WDAC, AppLocker) is fine: the scripts are tested in it.

Set it up

1. **Templates > Create template > Create job template:**
   - Name: `Active Directory health report`
   - Inventory: `Windows servers`. Project: site-automation. Playbook: `playbooks/ad_health_report.yml`
   - Execution environment: your Windows EE (WINDOWS.md, step 2)
   - Credentials: **Windows DCs (WinRM)** (the account of step 2)
   - Tick **Prompt on launch** next to **Variables** and **Limit**
   - Variables:

```yaml
report_email_to: ad-team@yoursite.mil
```

- Leave Limit empty (with no `target`, it reads the group `win_dc`, else `domain_controllers`). Save.

2. **First run: one DC.** Launch with Variables `target: dc01.yoursite.mil`. The domain-wide part is read on that DC too. Read the report in the job's output; anything under *Not read* says what that DC or account could not read (see Troubleshooting).
3. **All DCs**, then a schedule: **Schedules > Create schedule**, every day at 06:30 (set **your** time zone). Keep `ad_report_hours` (24) equal to the time between runs, so every change is in exactly one report.

A dry run (Check) reads and prints the same report, and sends no email. It takes one to three minutes per DC (mostly dcdiag); the DCs are read in parallel (the template's **Forks**).

The **PDC emulator** reads the domain-wide part when it is in the job; otherwise the first DC of the domain whose LDAP answered. The job output says which (`corp.example.mil: read by ...`).

Settings

Set them in the template's Variables, or in `playbooks/group_vars/all.yml` (or `win_dc.yml`). Ready to paste, with every setting switched off: aap/extra_vars/ad_health_report.yml.

Setting	Default	What it does
`ad_report_hours`	`24`	the changes of the last this-many hours (match the schedule)
`ad_event_hours`	`24`	the event log entries of the last this-many hours
`ad_security_events`	`true`	read the Security log for "by whom"
`ad_privileged_groups_extra`	`[DnsAdmins]`	more groups to watch (names or SIDs)
`ad_groups_should_be_empty`	`[]`	groups that must have no member, e.g. `[Schema Admins]`
`ad_privileged_change_severity`	`warning`	a privileged group change: `warning`, `critical` or `info`
`ad_schema_change_severity` / `ad_dc_change_severity`	`warning` / `info`	the schema changed; a DC added or removed
`ad_dcdiag_skip`	`[SystemLog]`	dcdiag tests to skip
`ad_dcdiag_dns`	`true`	also dcdiag's DNS tests that only read
`ad_trust_verify`	`true`	verify outbound and two-way trusts
`ad_repl_warn_hours` / `_crit_hours`	`6` / `24`	a replication link without success for this long (keep warn above your inter-site schedule)
`ad_repl_queue_warn`	`50`	requests in a DC's inbound replication queue
`ad_time_warn_seconds` / `_crit_seconds`	`5` / `60`	a DC's clock offset

Setting	Default	What it does
ad_time_sync_warn_hours	24	no time sync for this long
ad_disk_warn_pct / _crit_pct	15 / 5	free % of the database, log and SYSVOL volumes
ad_cert_warn_days / _crit_days	30 / 7	the LDAPS / KDC certificate expires
ad_backup_warn_days / _crit_days	7 / 30	the last system-state backup of a partition
ad_krbtgt_max_days	180	the krbtgt password's age (the STIG asks for 180)
ad_rid_warn_pct / _crit_pct	10 / 2	RID pool left
ad_no_client_site_warn	1	client addresses in no subnet before it is amber
ad_max_events / ad_changes_max	2000 / 500	the most event log entries read per log and DC; the most changed objects per kind
ad_report_max_rows	50	rows per table (problems first; the artifacts have all)
ad_report_fail	false	true = the job shows **failed** on a critical finding or a DC not read (for a workflow)

All settings of this job, with their defaults: ad_report.

Troubleshooting

You see	It means	Do
A DC **UNREACHABLE** with `ntlm: ... rejected` / `timed out`	WinRM to that DC failed	*Windows connection test* with Limit that DC; WINDOWS.md, "If something goes wrong"
LDAP **not checked** and `ActiveDirectory PowerShell module` under *Not read*	the module was removed from that DC	`Install-WindowsFeature RSAT-AD-PowerShell`
dcdiag **not run**: `no test result in its output (is dcdiag in English?)`	dcdiag prints another language	run the job with an account whose display language is English, or accept it (the other sections do not need dcdiag)
dcdiag: `The term 'dcdiag.exe' is not recognized`	the host is not a DC	take it out of `win_dc`
`objects deleted (reading Deleted Objects needs ...)` under *Not read*	the account may not list Deleted Objects	use an account in Domain Admins, or give the account read access to `CN=Deleted Objects` (Microsoft documents it: `dsacls` with `/takeownership`, then `/G <account>:LCRP`)
"By" is `-` everywhere	the change was made on a DC not in the job, or the audit policy does not record it	add the DC to `win_dc`; turn on the audit subcategories above
Replication **amber** every night on site links	the link replicates on a schedule longer than `ad_repl_warn_hours`	raise `ad_repl_warn_hours` above the site link's interval
Many **5719** / **5807** events	clients in subnets AD does not know	add the subnets in *Active Directory Sites and Services* (the *Clients in no site* table lists them)
GPO **version AD x, SYSVOL y**	SYSVOL has not caught up with an edit, or a GPO is broken on this DC	wait for the next run; if it stays, check DFSR on this DC (`dfsrdiag backlog`)

Limits

- Group membership is **direct**: a member added to a group that is itself in Domain Admins shows as a change of that group only if that group is watched (add it to `ad_privileged_groups_extra`).
- "Created" and "changed" times of accounts are AD's own; "changed" GPOs use the reading DC's `whenChanged` (a GPO whose links changed shows under *links*, not as changed).
- A forest with several domains: put the DCs of every domain in `win_dc`; each domain is read by one of its own DCs. Schema and forest-wide FSMO roles are reported by the forest root domain.
- The report covers what the DCs say about themselves and the domain. It does not test logons from clients, and it does not read Azure AD / Entra ID.

Without a domain admin

At many sites only Domain Admins may log on to the DCs, and AAP's account cannot be one. Then the job runs in **reader mode** (1.4.0): no WinRM at all. Everything is read **from the AAP side**, over LDAP, DNS and Kerberos, as the template's Machine credential - a **plain domain user with nothing granted**. Nothing runs on a DC and nothing is written to AD.

`ad_health_mode` picks how:

Value	What it does
`auto` (default)	the job tries WinRM to the DCs as before; when **no** DC can be reached with the credential, it reads the domain in reader mode instead. The job output and the report's first section say which, and why
`admin`	always WinRM on each DC (this chapter above); a DC that refuses is red
`reader`	never WinRM: reader mode only

What reader mode reads

Check	How	Colours
The DCs	AD's own list (the server objects in Configuration with their NTDS Settings, and the DC computer accounts): site, OS, global catalog, read-only. Compared with the inventory's group	amber a DC in the inventory that AD does not have; a DC in AD not in the inventory is still checked
LDAP and LDAPS	each DC: 389 answers, 636 answers and binds as the account (else StartTLS on 389)	red no answer or the bind refused; amber LDAPS down but StartTLS works
Synchronized, clocks	each DC's rootDSE: `isSynchronized`, `isGlobalCatalogReady`, `currentTime` against the other DCs'	red not synchronized; clock amber 2 min, red 5 min (`ad_reader_clock_warn_seconds` / `_crit_seconds`)
LDAPS certificate	each DC's, read from the TLS handshake on 636: expiry, issuer, trusted here	amber 30 days, red 7 (`ad_cert_warn_days` / `_crit_days`); amber not trusted
Kerberos	each DC's KDC: a **ticket (TGT)** from it with `kinit` (the Windows EE has it) - else an **AS-REQ** it must answer (`ad_reader_kerberos`)	red no answer; amber the KDC answers but gives no ticket
FSMO roles	`fSMORoleOwner` of the five objects: the holder is still a DC, and answers	red
DNS	the SRV records `_ldap._tcp.dc._msdcs`, `_kerberos._tcp.dc._msdcs`, `_ldap._tcp`, `_kerberos._tcp`, `_ldap._tcp.gc._msdcs`: every DC (every GC) registered; each DC's A record, against the inventory's address	red a record missing; amber a DC not registered or a different address
Replication	each DC's own copy of each partition head, as far as a plain user may read it: `msDS-NCReplInboundNeighbors` (Windows builds it), else `repsFrom` (each partner, last success, consecutive failures, last error), else `replUpToDateVector` (when each partner's changes last arrived). The report says which it could read	amber 6 h, red 24 h (`ad_repl_warn_hours` / `_crit_hours`), as admin mode; **grey "not read (needs admin)"** when the account may read none of them - never a guess
Privileged groups	the same groups and `ad_privileged_groups_extra` / `ad_groups_should_be_empty`: their members now; when a member was added or removed and on which DC from `msDS-ReplValueMetaData`, when the account may read it; and who joined or left **since the last run**	amber (`ad_privileged_change_severity`)

Check	How	Colours
Accounts	locked out now (`lockoutTime` within the lockout duration; a lockout *until an administrator unlocks it* never runs out); created in the last `ad_report_hours` (`whenCreated`); enabled / disabled / locked / unlocked - when and on which DC from the replication metadata of `userAccountControl` and `lockoutTime`, else `whenChanged` (**best effort**, labelled so)	blue

Who made a change is only in the DCs' Security logs, which need admin: reader mode says *not known (needs the event logs)*.

Each list is read page by page to its end, up to `ad_changes_max` (500) entries; a list cut there says so (1.24.0: the locked-out and created lists too, not only the changed accounts).

What it cannot read

dcdiag, repadmin (the queue, backups), **the DC services, SYSVOL and DFSR, the disks, the event logs, w32tm** and the Security log need admin on the DCs. The report says so **once**, in grey, at the top - *Not run - needs admin on the DCs (reader mode)* - not as a row per DC, and the job stays green for it: red and amber come only from what was found. Deleted accounts (the Deleted Objects container) and anything else the account may not read are listed under *Not read*.

The account

A **plain domain user**. It needs nothing granted: reader mode reads only what any authenticated user may read, and what the account may not is said as *not read*. Make one for the job (e.g. `svc_aap_adreader`), and put it in the template's **Machine** credential (user name `svc_aap_adreader@CORP.EXAMPLE.MIL` or `CORP\svc_aap_adreader`). Reader mode binds with it - a **simple bind over LDAPS**, else StartTLS on 389; never in clear text. The certificate must be trusted by the EE (your CA in `ee/*/ca`) and name the DC before the password is sent (`ad_reader_validate_certs`, `ad_reader_ca_file`). A refused password is tried once per run, never against every DC, so the job does not lock the account out.

Use the same inventory as admin mode: the DCs in `win_dc` (or `domain_controllers`). They are compared with AD's own list, never logged in to. The domain is their names' (`dc01.corp.example.mil` -> `corp.example.mil`). With short names (`dc01`) it is learned, in this order: their `ansible_host` when that is an FQDN; each DC's rootDSE, read on 389 without a bind (no password sent); the EE's DNS search domain (`resolv.conf`). Each DC is then reached as the name its rootDSE gives (`dnsHostName`, the name on its LDAPS certificate), else `<short name>.<domain>`. *How this was read* says where the domain came from; only when all of these fail, the report says to set `ad_reader_domain`. The EE must reach the DCs on 389, 636 and 88, and a DNS server that has the domain's records (`ad_reader_dns_servers`, else the EE's).

Since the last run

Each run keeps the privileged groups' members as a **job artifact** (`ad_privileged_members`). The next run reads the last one through AAP's API - the **"Red Hat Ansible Automation Platform" credential** on the template, as the report strip (`report_history`) uses - and lists who joined or left in between. Without it, one grey line: *no earlier list: the first run, or the last run's artifact couldn't be read (the AAP credential?)*; that is never shown as a change.

Instead of AAP, a file: `ad_reader_history_file: /var/lib/site-health/ad-privileged-groups.json`. It is written on the AAP side, in the EE, after each run (never in Check mode) - so the folder must outlive the job: in AAP, **Settings > Job settings > Paths to expose to isolated jobs**, add `/var/lib/site-health:/var/lib/site-health:Z` (on every execution node, the folder made and owned by the user jobs run as). `ad_reader_history: false` keeps no list at all.

Settings (reader mode)

Setting	Default	What it does
`ad_health_mode`	`auto`	`auto`, `admin` or `reader` (above)
`ad_reader_domain`	`""`	the domain's DNS name (`""` = learned: the DCs' names, their `ansible_host`, their rootDSE, the EE's DNS search domain)
`ad_reader_user` / `ad_reader_password`	`""`	`""` = the Machine credential's
`ad_reader_validate_certs` / `ad_reader_ca_file`	`true` / `""`	the LDAPS certificate must be trusted; a CA file (`""` = the EE's)
`ad_reader_kerberos`	`auto`	`auto` (a TGT with kinit, else an AS-REQ), `tgt`, `probe` (AS-REQ only), `off`
`ad_reader_dns_servers`	`[]`	DNS servers to ask (`[]` = the EE's)
`ad_reader_ports`	`{ldap: 389, ldaps: 636, kerberos: 88, dns: 53}`	the ports
`ad_reader_endpoints`	`{}`	a DC reached at another address or port (NAT): `{dc01.corp.example.mil: {address: 192.0.2.11, ldaps: 636}}`
`ad_reader_timeout`	`5`	seconds per connection
`ad_reader_clock_warn_seconds` / `_crit_seconds`	`120` / `300`	a DC's clock against the others'
`ad_reader_history` / `ad_reader_history_file`	`true` / `""`	the members since the last run: the AAP artifact, or this file

Troubleshooting (reader mode)

You see	It means	Do
NOT READ with `the bind was refused - invalidCredentials ... data 52e`	the password is wrong (775: locked out, 533: disabled)	fix the Machine credential
NOT READ with `certificate verify failed`	the EE does not trust the DCs' LDAPS certificate	add your CA to `ee/*/ca` and rebuild the EE, or set `ad_reader_ca_file`
Replication **not read (needs admin)** in grey	the account may read none of the replication attributes on that DC	expected for a plain user on some domains; admin mode reads it with repadmin
Privileged group changes: **not read (needs admin)**	the account may not read `msDS-ReplValueMetaData`	the *since the last run* table still lists who joined or left
Kerberos **answers; no TGT**	the KDC answers but refused the account a ticket (its password, locked out, expired)	the error says which

Account lockout

`playbooks/ad_lockout.yml` answers the service desk's question: *is this account locked out, and what keeps locking it out?* Give it the account (`jdoe`, `CORP\jdoe` or `jdoe@corp.example.mil`); leave it empty and it lists **every account locked out now**, each with its source.

How it works. Every DC of the job (the group `win_dc` - else `domain_controllers` - or `target`) runs a PowerShell script over WinRM that asks only itself, as the health report does:

1. The **PDC emulator** finds the account (or every account locked out now) and the lockout policy that applies to it - the domain's, or its fine-grained password policy.
2. **Every DC** reads its own `badPwdCount`, last bad password and last logon of the account (these are **not replicated**: each DC counts the bad passwords it was given itself), and its **Security log** of the last `ad_lockout_hours` for the account:

Event	What it says	Where it came from
4740	the account was locked out	*Caller Computer Name*
4767	the account was unlocked	by whom
4771	Kerberos pre-authentication failed (`0x18` = bad password)	the client's address
4768	a Kerberos ticket was refused (`0x12` = asked for while locked out)	the client's address
4776	NTLM credential validation failed (`0xC000006A` = bad password)	the workstation
4625	a logon to the DC failed	workstation, address, logon type, process

Each address is resolved to a name (reverse DNS, asked of the DC), so the Kerberos and the NTLM failures of one computer are counted together.

3. The report ranks the **source computers**: the one that locked it out first, then the most failed sign-ins. For each it says what that usually means, in plain words - a steady pace ("about every 5 minutes") is a saved password retrying, not a person typing; attempts *after* the lock mean it will lock out again right after an unlock; logon type 4 is a scheduled task, 5 a service, 3 a mapped drive or an application, 10 Remote Desktop; a source that is one of your mail servers (`ad_lockout_exchange_servers`) is a phone or a mail app with the old password; an empty caller is a server signing in for the user (Exchange / OWA, NPS / RADIUS for Wi-Fi or VPN, a web application).

The report: **what to do** first, then the account (locked since, enabled, password last set or expired), **where the failed sign-ins came from** (source, address, bad passwords, after the lock, lockouts, first, last, pace, how, which DCs saw them, whether it is in the inventory), the **lockouts and unlocks**, and **each DC**'s own count (an unreachable DC in red). It is printed in the job's output, published as artifacts (`ad_lockout`) and emailed when `report_email_to` is set. The job stays green: it fails only when no DC could read its domain, an account asked for is in no domain (it stops before reading the Security logs), or an unlock was refused.

Optional:

- `ad_lockout_unlock: true` unlocks the account on the PDC emulator after reading, and reads it back - only an account asked for by name, and only when it is locked out. A dry run (Check) says *would be unlocked* and changes nothing. The report says it first: it locks out again as soon as the source tries its old password, so fix the source.
- `ad_lockout_check_sources: true` also looks on each source computer that is a host of the job's inventory (WinRM, the same credential, which needs administrator rights there) for what runs as the account: services (*Log On As*), scheduled tasks (*Run as*), its sessions - a **disconnected** Remote Desktop session keeps the old password - processes, and drives it has mapped. Read-only. A source that is not in the inventory (most workstations) is listed with what to check by hand.

Before you start

- **The DCs** in the group `win_dc`, as for the health report (step 1 above). Put every DC there: a DC that is not in the job does not show its bad password count or its Security log, and a lockout recorded there is missed.
- **The audit policy** on the DCs (*Advanced Audit Policy Configuration*, in the Default Domain Controllers Policy): **Account Lockout** (Failure; 4740 is in *Audit User Account Management*, Success), **Kerberos Authentication Service** (Failure: 4771, 4768) and **Credential Validation** (Failure: 4776). The DISA STIG asks for all of them. Without them the report says *No failed sign-in ... the DCs may not audit*.
- **A Security log big enough** to hold `ad_lockout_hours` of events (on a busy DC 24 h can be 1 GB or more); an older lockout has rolled out of it.
- **The account** for the job. The health report's account works. A smaller one is enough for this job alone - it only reads, and the unlock is one delegated right:
- **Reading the Security log** of the DCs: the built-in group **Event Log Readers** (of the domain: it applies on the DCs), plus **Remote Management Users** for WinRM.
- **Reading the accounts**: any domain user can.
- **Unlocking** (`ad_lockout_unlock`): *Active Directory Users and Computers*, right-click the OUs of the users > **Delegate Control** > the job's account > *Create a custom task* > *User objects* > the property permissions **Read lockoutTime** and **Write lockoutTime**. Nothing else.
- **Looking on the source computers** (`ad_lockout_check_sources`): an administrator of those computers (other users' processes and scheduled tasks are not readable otherwise). Use a separate template with

that credential if your DC account must not log on to workstations.

Set it up for the service desk

1. **Templates > Create template > Create job template:**
   - Name: `Active Directory - account lockout`
   - Inventory: `Windows servers`. Playbook: `playbooks/ad_lockout.yml`. Execution environment: your Windows EE. Credentials: the account above.
   - Variables (ready to paste: aap/extra_vars/ad_lockout.yml):

```yaml
ad_lockout_exchange_servers: [EXCH01, EXCH02]   # your mail servers, if any
```

   - Leave Limit empty (with no `target` it reads the group `win_dc`, else `domain_controllers`). Save.
2. **Survey** (template > *Survey* > *Add*), then switch the survey **on**:
   - *Account (jdoe, CORP\jdoe or a UPN; empty = every account locked out now)* - answer variable `ad_lockout_user`, **Text**, **not required**.
   - *Unlock it?* - answer variable `ad_lockout_unlock`, **Multiple Choice (single select)**, choices `false` and `true`, default `false`, not required. Leave this question out for a "look only" template, and keep the unlock template for the people allowed to unlock.
   - Optionally *Look on the source computers?* - `ad_lockout_check_sources`, the same way.
3. **Access** (template > *User Access* / *Team Access*): give the service desk team the **Execute** role only - they launch it and read the output, they cannot change it.
4. **Try it** on your own account: type a wrong password three times on a test machine, then launch with your name. The source table should show that machine.

Settings

Setting	Default	What it does
ad_lockout_user	""	the account(s): jdoe, CORP\jdoe, jdoe@corp.example.mil; several separated by commas; empty = every account locked out now
ad_lockout_hours	24	how far back the Security logs are read
ad_lockout_unlock	false	true = unlock it on the PDC emulator (an account asked for by name, locked out)
ad_lockout_check_sources	false	true = look on the source computers that are hosts of the inventory
ad_lockout_check_max	5	source computers looked on per account (the worst first)
ad_lockout_exchange_servers	[]	your mail servers by name or address (* and ? allowed)
ad_lockout_max_users	25	accounts per run (asked for, or locked out now)
ad_lockout_max_events	2000	Security log entries read per account and DC (the newest)
ad_lockout_resolve_max	50	addresses resolved to names per DC
ad_lockout_max_rows	50	rows per table (the artifacts have all)

All settings of this job, with their defaults: ad_lockout.

Troubleshooting

You see	It means	Do
`No account named jdoe in corp.example.mil`	the name is not the sign-in name, or the account is in another domain	the *User logon name (pre-Windows 2000)*, `CORP\jdoe` or the UPN; for another domain, put its DCs in `win_dc`
`No failed sign-in ... the DCs may not audit`	the audit subcategories above are off, or the events have rolled out of the Security log	turn them on; raise the Security log's size; a shorter `ad_lockout_hours` for a fresh lockout
`Security log for jdoe: Attempted to perform an unauthorized operation` under *Not read*	the account may not read the Security log	add it to **Event Log Readers**
A source shown only as an **address**	no reverse DNS (PTR) record for it	look the address up in DHCP; add PTR records
The source is the **DC itself** or the caller is **(not recorded)**	a server signed in for the user: NPS / RADIUS, Exchange, a web application, an LDAP bind	look at that server's own logs (NPS: *Network Policy Server* events 6273)
`NOT unlocked: Insufficient access rights` (the job fails)	the account has no *Write lockoutTime* on that user's OU	delegate it (above); an account in a protected group (Domain Admins) is protected by AdminSDHolder - unlock it by hand
It locks out again right after the unlock	the source still has the old password	fix the source first (the report's *what to do*), then unlock

Limits

- Failed sign-ins the DCs of the job did not see are missed: every DC should be in `win_dc`.
- A sign-in with cached credentials (a laptop off the network) does not reach a DC: it is counted only once the laptop reaches a DC again.
- Credential Manager entries, saved passwords in applications and phones cannot be read remotely: the report says where to look.
- One forest at a time per job: a trusted domain's lockouts are on its own DCs (put them in the inventory, or run the job there).

40. Horizon 8 (VDI): reports, broken desktops, user help, image push

Eleven job templates for Horizon 8 with instant clones. They talk to a Connection Server's REST API (`https://<connection-server>/rest/`) from the AAP side: no inventory, no login to the desktops, no collection to add to the execution environment.

Job template	Playbook	What it does	Changes anything?
Horizon - API test	`horizon_api_test.yml`	the first job to run: login, each API path and version that answers, the settings against the pools, one user	no
Horizon - health report	`horizon_health_report.yml`	Connection Servers (status, services, certificate, replication, configuration backup), gateways, vCenter, its ESXi hosts and datastores and AD from each Connection Server, the event database, SAML and True SSO, the license, pools that cannot provision or whose new image is held, agent versions, desktops left on an older image, 169.254 and duplicate addresses, broken desktops	no
Horizon - capacity report	`horizon_capacity_report.yml`	per pool: maximum, free, in use, broken, sessions, how full	no
Horizon - events report	`horizon_events_report.yml`	the last 24 hours of Horizon's event database: failed logons by user, errors by type, what administrators changed	no
Horizon - settings report	`horizon_settings_report.yml`	Horizon's global and Connection Server settings against your baseline (session timeouts, the pre-login message, FIPS, smart cards)	no
Horizon - sessions report	`horizon_sessions_report.yml`	old Horizon Clients, pending launches, sessions on broken desktops, long sessions, users with two desktop sessions, protocols and client versions	no

Job template	Playbook	What it does	Changes anything?
Horizon - internal VMs report	`horizon_internal_vms_report.yml`	instant clones' internal VMs in vCenter (cp-template, cp-replica, cp-parent): in use, probably left over (with the reason), inaccessible	no
Horizon - FSLogix profiles report	`horizon_fslogix_report.yml`	the FSLogix profile shares over SMB: each container's size against its cap, stale and duplicate containers, each share's free space	no
Horizon - logon times report	`horizon_logon_report.yml`	how long logons take, per pool (median, 95th percentile) and which phase is slow (profile, GPO, shell...)	no
Horizon - message users	`horizon_message_users.yml`	a message to the sessions of some pools, an ESXi host's desktops, some users or everyone	sends a message
Horizon - host maintenance plan	`horizon_host_maintenance_plan.yml`	before an ESXi host's maintenance: its desktops, the sessions on them (job 1 of the host maintenance workflow)	no
Horizon - host maintenance start	`horizon_host_maintenance_start.yml`	after the approval: the message, then the host's free desktops into Horizon maintenance mode (job 2)	yes
Horizon - host maintenance end	`horizon_host_maintenance_end.yml`	after the host's maintenance: its desktops out of Horizon maintenance mode	yes
Horizon - desktops check	`horizon_desktops_check.yml`	the broken desktops, desktops vCenter no longer has, desktops stuck in a passing state, what fixes each, and why some are held back (job 1 of the broken desktops workflow)	no
Horizon - fix the approved desktops	`horizon_desktops_fix_approved.yml`	after the approval: fixes exactly the approved desktops (job 2)	yes
Horizon - user help	`horizon_user_help.yml`	for the service desk: a user's sessions and desktops; log off, disconnect, reset, restart or recover them	only when asked
Horizon - session cleanup	`horizon_session_cleanup.yml`	logs off sessions disconnected for 8 hours or more	yes

Job template	Playbook	What it does	Changes anything?
Horizon - golden image check	`horizon_image_check.yml`	before a golden image is snapshotted and pushed: the VM's hardware in vCenter and Windows inside it (agent, Tools, domain, activation, DHCP, restart pending, FSLogix) - READY or NOT READY	no
Horizon - image push plan	`horizon_image_push_plan.yml`	the plan for a new golden image: pools, VM, snapshot, start (job 1 of the image push workflow)	no
Horizon - push the approved image	`horizon_image_push_approved.yml`	after the approval: schedules exactly the approved push (job 2)	yes

Every job reads first and says what it found. A dry run (Job type **Check**) changes nothing and says what it would do. No job emails anything unless `report_email_to` is set on its template.

Your Horizon version

The jobs do not need to know it. Horizon's REST API has a version in each path (`/rest/inventory/v2/machines`), and newer releases add newer versions. For each path a job asks the newest version first (`horizon_api_newest`, v9) and works down to v1. The first version that answers is used, and the reports print which ones answered. If your release does not have a part at all (the license on older releases, for example), the jobs leave it out and say so once.

Run *Horizon - API test* first. It prints a line for each part of the API:

```
PASS machines: rest/inventory/v2/machines - 412 record(s) and more
----  license: not in this Horizon (HTTP 404 at every API version, v9 to v1)
FAIL sessions: the account may not read rest/inventory/v1/sessions (HTTP 403): give its Horizon
  role the privileges in docs/HORIZON.md
```

`----` is fine: that part is not in your release. `FAIL` means the part is there but the account may not read it (the role below), or something else went wrong (the line says what).

What was built from the API documentation and not yet tried on a real Horizon. The tests run against a stand-in (`tests/horizon/hzmock.py`) written from the Horizon Server REST API reference. Check these on yours. Your Connection Server documents its own API at `https://<connection-server>/rest/swagger-ui.html`.

- **Paths.** The jobs use:
- `monitor/connection-servers`, `gateways`, `virtual-centers` (with its `datastores` and `hosts`), `ad-domains`, `event-database`, `saml-authenticators`, `true-sso`
- `config/connection-servers` (and each by its ID, for `ldap_backup_info`), `config/settings/general`, `config/settings/security`, `config/pre-logon-settings`
- `external/audit-events`, filtered by `time` (Between, milliseconds)
- `config/licenses` (also tried: `config/license`, `monitor/licenses`)

- `inventory/desktop-pools`, `machines`, `sessions`, `farms`
- `external/base-vms`, `base-snapshots`, `ad-users-or-groups`
- the actions: `inventory/v1/machines/action/{recover,reset,restart,rebuild}`, `DELETE inventory/v1/machines` (remove), `inventory/v1/sessions/action/{logoff,disconnect}`, `inventory/v1/desktop-pools/{id}/action/schedule-push-image`
- **Field names.** Each value is looked for under the names the API versions use, for example `pattern_naming_settings.max_number_of_machines`, `provisioning_status_data.instant_clone_pending_image_state`, `session_state` and `disconnected_time`; the desktops check also reads each desktop's `managed_machine_data` (`host_name`, `clone_error_message`, `missing_in_vcenter`, `create_time`, `last_maintenance_time`, `base_vm_snapshot_id`) and `agent_ipv4_address`. A missing value is never an error, but a report column can stay empty and a check can find nothing. If one does, tell us the field name your swagger page shows.
- **The user search.** `external/ad-users-or-groups` is searched with a filter on `login_name`, and also on `name` for versions that take that instead. *API test* with `horizon_test_user: <someone>` shows whether your release finds users that way.
- **A push already running.** A pool counts as busy when `instant_clone_pending_image_state` or `instant_clone_operation` is set (and not `NONE`). The plan refuses a busy pool.
- **The actions answer.** Horizon answers each ID of a bulk action with `status_code` and `errors`. A refusal is shown with Horizon's own reason.

Step 1. The service account and its Horizon role

Ask for an AD account (for example `svc-horizon-aap`) whose password does not expire, or put it on your rotation. Then, in Horizon Console, **Settings › Administrators**:

- **For the reports and the API test**: the built-in role **Administrators (Read only)** on the root access group `/`. It reads everything and changes nothing.
- **For the jobs that change something** (fix, user help, session cleanup, image push): a role of your own, under **Roles › Add Role**, named for example `AAP automation`, with these privileges:
- **Console Interaction** (to log in)
- **Manage Machine** and **Manage Reboot Operation** (reset, restart, recover, remove)
- **Manage Sessions** (log off, disconnect)
- **Manage Desktop Pool** (schedule an image push)
- **Manage Sessions** also sends messages (*Horizon - message users*, the host maintenance start), and **Manage Machine** puts desktops into and out of maintenance mode

Give it on the access group of the pools the jobs may change, or on `/` for all of them. Privilege names differ a little between releases: pick the closest ones your Console lists.

Two accounts, each with one credential, keep the reports read-only: a read-only one for the reports and the API test, the other for the jobs that act. One account with the second role also works.

From the execution environment, the Connection Server (or the load balancer in front of the Connection Servers) must answer on **443**. Its certificate must be trusted by the execution environment (your DoD CA in the EE, docs/EXECUTION_ENVIRONMENT.md), or set `horizon_ca_path`.

Step 2. The credential type and the credentials

1. **Automation Execution › Infrastructure › Credential Types › Create credential type**, name `Horizon API`. Paste the `inputs` and `injectors` blocks of aap/credential_types/horizon_api.yml.
2. **Credentials › Create credential**, type `Horizon API`:
   - **Connection Server URL** e.g. `https://horizon.example.mil`
   - **AD domain** the NetBIOS name, e.g. `CORP`
   - **User name** without the domain
   - **Password**
   - **Verify the Connection Server's certificate** ticked

A second credential, e.g. `Horizon API (read only)`, for the read-only account.

Step 3. The job templates

Create one template per row: **Inventory** any (the jobs run on the AAP side, against Horizon), **Project** this repository, the **Playbook**, the credential. Paste the template's file from `aap/extra_vars/` into **Variables** and switch on what you change.


Template	Credential	Survey	Notes
Horizon - API test	read only	`horizon_test_user` (text, optional)	run it after any change to the account or the Connection Server
Horizon - health report	read only	none	
Horizon - capacity report	read only	none	
Horizon - events report	read only	none	
Horizon - settings report	read only	none	`horizon_settings_baseline` on its Variables (Settings report below)
Horizon - sessions report	read only	none	`horizon_client_min_versions` on its Variables
Horizon - logon times report	read only	none	the account needs Help Desk read rights (Logon times report below)
Horizon - internal VMs report	read only, and a *VMware vCenter* credential (read-only)	none	
Horizon - FSLogix profiles report	the *Windows file share* credential, not Horizon API	none	`horizon_fslogix_shares` on its Variables; the account needs Read on each share

Template	Credential	Survey	Notes
Horizon - message users	acting	`horizon_message` (text, **required**), `horizon_message_type` (multiple choice: `INFO`, `WARNING`, `ERROR`), `horizon_message_pools` (text: pool names, commas), `horizon_message_users` (text, optional)	
Horizon - host maintenance plan	read only	none: the survey is on the workflow	
Horizon - host maintenance start	acting	none	**Prompt on launch** unticked for Variables
Horizon - host maintenance end	acting	none: the last node of the workflow (it gets the start job's list)	**Prompt on launch** unticked for Variables; alone only with `horizon_maint_end_all: true` and `horizon_maint_host`
Horizon - desktops check	read only	none	`horizon_desktops_mode: approval` when it is the workflow's first node
Horizon - fix the approved desktops	acting	none	**Prompt on launch** unticked for Variables; Job type: tick Prompt on launch to rehearse with Check
Horizon - user help	acting	`horizon_user` (text, **required**), `horizon_user_action` (multiple choice: `look`, `logoff`, `disconnect`, `reset`, `restart`, `recover`; default `look`)	give the service desk Execute on this template only
Horizon - session cleanup	acting	none	first run it as Check
Horizon - golden image check	*VMware vCenter* and *Machine* (Windows) credentials, not Horizon API	none	the **Limit**: the golden VM as the Windows inventory names it
Horizon - image push plan	read only	none: the survey is on the workflow	
Horizon - push the approved image	acting	none	**Prompt on launch** unticked for Variables

The protected pools, `horizon_protected_pools` (e.g. `[VIP-*]`), belong in `playbooks/group_vars/all.yml`. No job fixes, logs off or pushes an image to those pools.

Every acting job reads first and stops, before any action, when Horizon did not give a part in full (a refused or failed page, for example): with half the pools or sessions, the protected pools cannot be checked. The job says `Nothing was changed: Horizon did not give ...`; run it again. A desktop or session whose pool is not among the pools read is left alone, with that reason. The health report and the API test go on and say what is missing.

Workflow: fix broken desktops, with an approval



1. **Templates › Create template › Create workflow job template**, name `Horizon - fix broken desktops (workflow)`. Save, and the visualizer opens.
2. **Add step**: *Horizon - desktops check*. Its Variables already say `horizon_desktops_mode: approval`, from Step 3.
3. On it, **+** › **Run on fail** › **Approval**:
   - name `Fix these desktops?`
   - timeout e.g. 60 minutes
   - description `Open the desktops check job: the NEEDS APPROVAL line lists each desktop and its fix.`
4. On the approval, **+** › **Run on success** › *Horizon - fix the approved desktops*. **Save**.

What happens:

- **Nothing broken**: the check is green, and the workflow ends there.
- **Desktops to fix**: the check fails on purpose with `NEEDS APPROVAL: 3 broken desktop(s) to fix - w11-004 (AGENT_UNREACHABLE: recover), ...` and hands the list to the next steps (`set_stats horizon_desktops_fix`). The approver reads it and approves or denies.
- **After the approval**, the fix job reads each desktop again and makes every check of the check job again on what Horizon says now: still broken, no session on it, the pool it is in now not protected, not excluded, recover only on instant clones, remove only while no user is assigned - with exactly the approved action. A desktop that recovered, moved or was assigned meanwhile is left alone, and the report says so.

A check that fails for another reason, a refused login for example, also takes the "Run on fail" path. Its approval then shows no NEEDS APPROVAL line, and the fix job refuses with `Nothing to fix: no approved list`. Deny it, and fix the login.

Which desktops.

- **Broken**: a state of `horizon_broken_states` (agent unreachable, already used, error, provisioning error...).
- **Not in vCenter**: Horizon lists the desktop, vCenter has no such VM any more (`missing_in_vcenter`). Its record is removed (`horizon_fix_ghost_action`; `""` leaves it for a person).
- **Stuck**: in a passing state (being made, customized, deleted, maintenance, waiting for the agent) for `horizon_stuck_hours` (4) or more, counted from when it was made or its last maintenance. Listed for a person unless `horizon_fix_stuck_actions` names an action for that state, e.g. `{CUSTOMIZING: recover}`.

What fixes a desktop.

- **Recover** (`horizon_fix_default_action`): the instant clone is deleted and made again from the pool's image.
- **By state** (`horizon_fix_actions`): another action for some states, `restart` for `AGENT_ERR_NEED_REBOOT` by default.
- **Held back for a person**:
- a desktop with a session on it
- one in a protected pool
- **many broken on one ESXi host**: `horizon_fix_host_threshold` (5) or more broken desktops on the same host are all held, and the report says to look at the host first (Broadcom KB 431732). A recover would only make new clones on the same host.
- **AD down**: while a Connection Server cannot reach or bind to an AD domain, every recover and rebuild waits (a new clone could not join the domain). Restarts still go. `horizon_fix_ad_gate: false` turns it off.
- **a clone error a recover would repeat**: Horizon's clone error is sorted into domain, network, datastore, activation, timeout or other (the report has a *Clone errors* table). Domain, network and datastore errors are not recovered (`horizon_fix_hold_error_kinds`); add your own kinds with `horizon_clone_error_kinds`, e.g. `{security_agent: "carbon black|tanium"}`.
- one in a pool that is not instant clones (recover is for instant clones)
- `remove` of a desktop assigned to a user
- anything over `horizon_fix_max` (20 per run)

The fix job after the approval makes every one of these checks again on what Horizon says then: if AD went down or the host failed since the approval, those desktops are left alone, and the report says why.

Schedule the workflow e.g. every hour in working hours. For a list without the approval, make a second template, *Horizon - desktops check (report)*: the same playbook, without `horizon_desktops_mode` in its Variables (`report` is the default), on its own schedule. The workflow's template keeps `approval`.

Rehearse it. Tick **Prompt on launch** for Job type on *Horizon - fix the approved desktops*. In the visualizer, set its node's Job type to **Check**. Run the workflow and approve: the fix job prints `w11-004: would recover (a dry run)` and changes nothing.


Golden image check

Horizon - golden image check says whether a golden image is ready before you shut it down, snapshot it and push it. It changes nothing. Attach the **VMware vCenter** and **Machine** (Windows) credentials. Put the golden VM in the **Limit**, as the Windows inventory names it; `horizon_image_vm` is its vCenter name (empty: the Limit's short name).

Check	FAIL	WARN
VM found	not found, or found twice	a vCenter not read
Network adapters	none	not VMXNET3; not connected at power on
CD/DVD	on an ISO or host drive, connected	
Floppy, serial, parallel	on a host device	present
vTPM	on the golden image (add it at the pool)	
Hardware version, snapshots		older than `horizon_image_hw_min` (14); a chain deeper than `horizon_image_snapshot_warn` (5)
VMware Tools	not installed or not running	old
Horizon Agent, Instant Clone Agent	missing or disabled	
Tools before the agent		Tools installed after the agent
Domain, activation		workgroup; MAK before Horizon 2212; retail or OEM
DHCP, restart pending	a fixed address; a restart pending	file renames only
Windows Update busy, FSLogix		busy; FSLogix missing

The Windows side runs one read-only PowerShell script over WinRM (Constrained Language Mode too). With no Limit, or WinRM down, the vCenter part still reports and the report says why (NOT READY, unless `horizon_image_guest: false`). The job stays green; `horizon_image_check_fail: true` fails it on a FAIL. Run it before the image push workflow.

Workflow: push a new golden image, with an approval



1. Create a workflow job template, `Horizon - image push (workflow)`, with this **survey**:
   - `horizon_push_pools`: textarea, required. The pools, one per line.
   - `horizon_push_base_vm`: text, required. The golden image VM as vCenter names it.

- `horizon_push_snapshot`: text, required. The snapshot's name, or its path when two snapshots have that name.
- `horizon_push_start`: text, optional. Empty = once approved. Or `2026-11-01 22:00` (UTC).
- `horizon_push_logoff_policy`: multiple choice, `WAIT_FOR_LOGOFF` (default) or `FORCE_LOGOFF`.

2. Nodes: *Horizon - image push plan* › **Run on success** › **Approval** › **Run on success** › *Horizon - push the approved image*. The approval: name `Push this image?`, timeout e.g. 8 hours, description `Open the image push plan job: the READY FOR APPROVAL line says what, where and when.`
3. **Rehearse it** before the first real push: tick **Prompt on launch** for Job type on *Horizon - push the approved image*, set its node's Job type to **Check**, launch and approve. It prints what it would schedule and schedules nothing.

The plan job checks everything in Horizon:

- each pool is an instant-clone pool, not protected, with no push already scheduled or running
- the VM and the snapshot are found in each pool's vCenter, and Horizon does not flag either as one it cannot push (powered on, no snapshot, an OS or hardware version it does not take)
- the start is not in the past

It warns the approver when the snapshot's vGPU profile is not the pool's, and when a pool's datastore has less free space than the new image's replica needs.

A plan with a problem **fails**, and nothing reaches the approval. A good plan prints `READY FOR APPROVAL: Push W11-Gold / /2026-10/2026-11 to IC-Win11, IC-Finance, starting ...; users: each desktop is replaced when its user logs off.` It also prints any warnings, such as Horizon flagging the VM or the same image being pushed again.

The plan reaches the push job as the job artifact `horizon_push_plan` (on the plan job: **Details** > **Artifacts**). The push job reads each pool again and schedules exactly the approved push. A start time that has passed by the approval starts in a minute. Progress is in Horizon Console (the pool's **Summary**), and the next health report shows a failed push in red.

User help (the service desk)

Horizon - user help with `horizon_user` = `jdoe`, `CORP\jdoe`, `jdoe@corp.example.mil` or a SID:

```
CORP\jdoe (Jane Doe), S-1-5-21-...: 2 session(s), 1 desktop(s)
Session: desktop on w11-002 (pool IC-Win11), connected, started 2026-10-20 08:02 UTC, from
  LAPTOP-12, BLAST
Session: application on (an RDS host) (pool farm RDS-Farm), disconnected since 2026-10-19 17:30
  UTC
Desktop: w11-002 (pool IC-Win11) is CONNECTED
```

Then, with `horizon_user_action`:

- **logoff**: all their sessions; a locked one too, `horizon_session_forced_logoff`
- **disconnect**: their connected sessions
- **reset**: their desktops, like the power button
- **restart**: their desktops; the OS shuts down first
- **recover**: their instant-clone desktops, made again from the image

It never acts on a desktop another user has a session on, nor on a desktop or session in a protected pool. The domain counts: `LAB\jdoe` is never `CORP\jdoe` - when Horizon knows no such user in that domain, the

job says which domains have one. When Horizon's AD user search does not answer, the job stops rather than guess by the name a session carries. A user with no session and no desktop is usually not entitled to a pool: the job says where to look.

Session cleanup

Horizon - session cleanup logs off every session disconnected for `horizon_session_max_disconnected_hours` (8) or more. Such a session holds a desktop, and an instant clone is only made fresh at log off. The oldest are logged off first, at most `horizon_session_cleanup_max` (100) per run.

It never logs off sessions in these:

- a protected pool
- `horizon_session_cleanup_exclude_pools`
- `horizon_session_cleanup_exclude_users`, given as login names or SIDs

Nor a session whose disconnect time Horizon does not give. It sends no message first: no one sees a message in a disconnected session.

Run it as Check first. Then schedule it, e.g. every night at 02:00. For a list only, set `horizon_session_cleanup_report_only: true`.

Events report

Horizon - events report reads Horizon's event database through the REST API (`external/audit-events`) for the last `horizon_events_hours` (24):

- **Failed logons by user**: how many, why (bad password, locked account, not entitled, not authorized), from which client address, the last one. Amber for a user with `horizon_events_failed_warn` (5) or more.
- **Errors by type**: events of `horizon_events_error_severities` (ERROR, AUDIT_FAIL) - launch failures, pools empty or overloaded, desktops that cannot connect, provisioning errors - with the pools and the last message.
- **What administrators changed**: Horizon's own audit of its console and API (event module `Vlsi`), for the audit review.

It needs an event database (the health report says when there is none). The read-only account reads it.

Settings report

Horizon - settings report compares Horizon's settings with `horizon_settings_baseline`: each line `area.setting: value`, with area `general`, `security` or `pre_logon` (Horizon's global settings) or `connection_server` (checked on every Connection Server). A value is the value, or `{min: N}`, `{max: N}`, `{contains: text}`, `{one_of: [...]}` or `{not: value}`.

Run it first without a baseline: the report lists **every setting read**, with Horizon's own names, which differ a little between releases. Copy the ones to watch into the baseline. A starting point for a DoD site (check each name against that list, and the values against your STIG and policy):

```yaml
horizon_settings_baseline:
  general.client_idle_session_timeout_policy: TIMEOUT_AFTER
  general.client_idle_session_timeout_minutes: {max: 15}
  general.display_pre_login_message: true
  general.pre_login_message: {contains: "You are accessing a U.S. Government"}
  pre_logon.display_pre_login_admin_banner: true
  connection_server.fips_mode_enabled: true
  connection_server.smart_card_support: REQUIRED
  connection_server.logoff_when_remove_smart_card: true
```

A setting that differs is red (`DRIFT`); one Horizon did not give is amber (`NOT READ`).

Sessions report

Horizon - sessions report looks at every session Horizon has:

- **Old Horizon Clients**: older than `horizon_client_min_versions`, per client type as Horizon names it (`WINDOWS`, `MAC`, `LINUX`, `IOS`, `ANDROID`, `HTML_ACCESS`...) and `'*'` for the rest, in the numbers Horizon shows for the client: `{WINDOWS: '8.13', '*': '8.12'}`. Without it the report lists the versions in use.
- **Pending sessions**: pending for `horizon_session_pending_minutes` (10): a launch that never finished. Log it off with *Horizon - user help*.
- **Sessions on a broken desktop**: the user may be stuck; log off, and the desktops check fixes the desktop.
- **Long sessions** (started `horizon_session_long_hours`, 72, ago or more), **users with two or more desktop sessions**, and sessions on a protocol other than `horizon_session_protocols` (`[BLAST]`).

Logon times report

Horizon - logon times report reads the logon timing Horizon's Help Desk keeps for each desktop session started in the last `horizon_logon_hours` (24), at most `horizon_logon_max` (200, the newest): the whole logon and each phase - brokering, power-on, tunnel, protocol, profile load, GPO, shell. Per pool: the median, the 95th percentile and the slowest phase on average; then the slowest logons. A pool's 95th percentile at `horizon_logon_warn_s` (60 s) is amber, at `horizon_logon_crit_s` (120 s) red.

Two things to set up once:

- **The timing profiler**, on each Connection Server (an administrator's command prompt): `vdmadmin -I -timingProfiler -enable`. Without it the report says no session has timing.
- **Help Desk read rights**: if the report says HTTP 403 for `helpdesk/.../logon-segment`, give the read-only account the built-in **Help Desk Administrator (Read only)** role as well.

Horizon says the timing's format may change between releases: the job reads any names and durations it finds. If the phases look wrong, tell us what your Connection Server returns.

Internal VMs report

Instant clones leave internal VMs in vCenter: cp-template, cp-replica and cp-parent (newer releases may name them by UUID only, in ClonePrep folders). After a pool is deleted, a host fails, or a delete runs while vCenter is down, some stay behind and use datastore space. *Horizon - internal VMs report* lists them; it changes nothing. It needs both credentials: *VMware vCenter* and *Horizon API*.

For each VM: the host, datastores, space on disk, power and connection state, when it was made, its golden image VM and snapshot, and the pool, farm or desktops that still use it.

- **Red**: inaccessible, orphaned or disconnected.
- **Amber**: probably left over - always with the reason (no pool, pending image, farm or desktop uses its golden image and snapshot).
- **Not decided**: Horizon could not be read, a pool's golden image was not found in vCenter, or the VM is newer than `horizon_internal_min_age_hours` (24).

Another Horizon pod on the same vCenters: put its pod ID in `horizon_internal_other_pods` (each VM's pod is in the job's artifacts); its VMs are listed, never called left over.

To clean up, on a Connection Server (`C:\Program Files\Omnissa\Horizon\Server\tools\bin`, or VMware's on older releases): `iccleanup.cmd -vc <vcenter> -uid <user>`, then `list`, `unprotect -I <index>`, `delete -I <index>`.

FSLogix profiles report

Horizon - FSLogix profiles report lists the shares that hold the desktops' FSLogix profile containers (`horizon_fslogix_shares`, one `\\server\share\folder` per line). It reads them over SMB from the AAP side, with the *Windows file share* credential. It only lists folders: no container is opened, nothing is written or locked.


For each container it gives the user and SID (from the folder name), profile or ODFC, its size against the cap (`horizon_fslogix_size_mb`, FSLogix's SizeInMBs, 30000), when it was last written, and whether it is in use. It flags containers near the cap (85 %) or over it (95 %), stale ones (`horizon_fslogix_stale_days`, 90: space to reclaim, once you know the user left), two containers for one user, folders with no container, a differencing disk left behind, and names FSLogix would not find. It gives each share's free space (amber under 15 %, red under 5 %).

With FlipFlopProfileDirectoryName set: `horizon_fslogix_folder_pattern: "%username%_%sid%"`. The size is the file's size: a dynamic disk shrinks only when FSLogix compacts it; a fixed disk always reads 100 %. "In use: likely" is a guess from the last write time.

Message users

Horizon - message users sends `horizon_message` (`horizon_message_type`: INFO, WARNING or ERROR) to the sessions of `horizon_message_pools`, the desktops on ESXi host `horizon_message_host`, `horizon_message_users` (login names or SIDs), or everyone (`horizon_message_all: true`). Disconnected sessions get it too: the user sees it when back. Run it as **Check** to see who would get it.

Workflow: ESXi host maintenance



Before you put an ESXi host into maintenance mode in vCenter:

1. Create a workflow job template, `Horizon - host maintenance (workflow)`, with this **survey**:
   - `horizon_maint_host`: text, required. The ESXi host as vCenter names it (its short name works).
   - `horizon_maint_message`: textarea, optional. What the users on its desktops read; empty = no message. The default asks them to save their work and log off in 15 minutes.
2. Nodes: *Horizon - host maintenance plan* › **Run on success** › **Approval** (`Start the host maintenance?`) › **Run on success** › *Horizon - host maintenance start* › **Run on success** › **Approval** (`Is the host back?`, no timeout) › **Run on success** › *Horizon - host maintenance end*.

The plan lists the host's desktops (as Horizon has them: each desktop's ESXi host), the free ones that go into **Horizon maintenance mode** (no new user is given them), the sessions that get the message, and what is held back: a desktop in a protected pool, a desktop with a session on it (it gets the message; run the start job again later to put it in maintenance once free). A host Horizon has no desktop on stops the plan.

After the approval the start job reads the desktops again, sends the message to the sessions on the host's desktops now, and puts the planned desktops still free into maintenance mode. Then put the host into maintenance in vCenter (DRS moves the running desktops). When the host is back, approve `Is the host back?`: the end job brings out of maintenance mode only the desktops the start job put there (the start job hands their list on, `horizon_maint_done`), wherever DRS moved them; a desktop someone put in maintenance mode for another reason stays there. Run on its own, without that list, the end job stops; `horizon_maint_end_all: true` with `horizon_maint_host`, put in the end template's Variables for one run (and taken out after), brings back every desktop in maintenance mode on the host instead (as before 1.22.0).

On Horizon before 2306, or a pool that still uses parent VMs (`cp-parent-*`), the parent VMs block the host's maintenance mode: run `IcMaint.cmd -vc <vcenter> -uid <user> -hostName <host> -maintenance ON` on

a Connection Server first, and `OFF` afterwards (Broadcom KB 322191).

Reports and schedules

Template	Schedule (suggested)	Red when
Horizon - health report	every day 06:00	a Connection Server, service, gateway or vCenter link down; a certificate within `horizon_cert_crit_days` (7) or not valid; the event database not connected; the license expired; a pool that stopped provisioning or whose image failed; a datastore under `horizon_datastore_crit_pct` (5 %) free. Amber: a self-signed Connection Server certificate, a configuration backup older than `horizon_backup_max_hours` (26), an ESXi host not connected, a datastore under 15 % free, a new image held, agents of two versions in a pool, desktops left on an older image, 169.254 or duplicate addresses
Horizon - events report	every day 06:10	the event database could not be read. Amber: a user with 5 or more failed logons, error events
Horizon - capacity report	every Monday 07:00	a pool at `horizon_capacity_crit_pct` (95 %) in use, or with no free desktop (amber at 80 %, or fewer free desktops than its spares)
Horizon - settings report	every Monday 07:10	a setting that differs from `horizon_settings_baseline`
Horizon - sessions report	every day 07:30	never red. Amber: old clients, pending sessions, sessions on broken desktops, other protocols
Horizon - internal VMs report	every Monday 07:30	an internal VM inaccessible, orphaned or disconnected. Amber: probably left over
Horizon - FSLogix profiles report	every Monday 07:20	a container at `horizon_fslogix_crit_pct` (95 %) of its cap, a share under 5 % free or not readable. Amber: 85 %, two containers for one user, odd names, a differencing disk left behind
Horizon - logon times report	every day 10:00 (after the morning logons)	a pool's 95th percentile logon at `horizon_logon_crit_s` (120 s); amber at 60 s

They stay green when they find problems: the report says what. With `horizon_health_fail: true` the job turns **red** when it finds a problem: put a notification on the template (its **Notifications** tab: on failure) to hear about it. The *ServiceNow tickets* job does not take this report's results - it only works after the checks that hand it findings (JOB_TEMPLATES.md, "What one job hands to the next"). To email them, set `report_email_to` on the template (EMAIL_REPORTS.md).

Messages and what to do

Message	What to do
`No Horizon connection: attach a credential of type "Horizon API"`	attach the credential to the template
`Horizon did not answer at https://...: ...`	the address, a firewall (443 from the execution environment), or the certificate (`horizon_ca_path`)
`Horizon refused the login of CORP\svc-... (HTTP 401 ...)`	the password, the domain, or the account has no Horizon role (Step 1)
`the account may not read rest/... (HTTP 403)`	the role lacks a privilege for that part (Step 1)
`Horizon refused N action(s) ...` / `REFUSED - recover refused (HTTP 400): ...`	Horizon's own reason follows; often the desktop is busy (a task already running): the next run tries again
`Nothing to fix: no approved list` / `Nothing to push: no approved plan`	the job was started outside its workflow, or the check failed for another reason: run the workflow
`2 users are sam (CORP\sam, LAB\sam): write it DOMAIN\user`	give the domain

All settings of these jobs, with their defaults: horizon.

Appendix: credential types to paste into AAP

Each block below is one file in `aap/credential_types/`. In AAP: **Automation Execution > Infrastructure > Credential Types > Create credential type**. Paste the part under `inputs:` into **Input configuration** and the part under `injectors:` into **Injector configuration** (without those two top-level lines). Copy from the repository file where you can; PDF copy can change spaces.

ServiceNow API (servicenow_api.yml)

Used by playbooks/servicenow_tickets.yml, servicenow_health.yml and servicenow_test_ticket.yml (REST Table API, basic auth only). The same variable names as the certified servicenow.itsm collection, so this credential also works if you move to that collection later.

YAML

```yaml
inputs:
  fields:
    - id: instance
      type: string
      label: Instance URL
      help_text: e.g. https://servicenow.example.mil
    - id: username
      type: string
      label: API user name
    - id: password
      type: string
      label: API password
      secret: true
  required: [instance, username, password]
injectors:
  env:
    SN_HOST: "{{ instance }}"
    SN_USERNAME: "{{ username }}"
    SN_PASSWORD: "{{ password }}"
```

ServiceNow node stats login (servicenow_node_stats_login.yml)

Used by playbooks/servicenow_health.yml with servicenow_node_stats_auth: form only (a self-hosted instance whose nodes answer stats.do only in a logged-in session: single sign-on in front, no basic auth). The check logs in at the node's own address through the instance's local login page (side_door.do), reads the stats page and logs out. A dedicated LOCAL account of the instance with only a role that may read stats.do - not a person's account, not an admin, not the ServiceNow API account. Each run is one UI login per node address (node and port) in the instance's login history. The login goes over HTTPS to the node's own name, or to 127.0.0.1 on the node, also over plain HTTP. docs/SERVICENOW_SETUP.md, "The node stats login".

```yaml
inputs:
  fields:
    - id: username
      type: string
      label: User name
      help_text: A local account of the instance (not a single sign-on one) that may read stats.do
    - id: password
      type: string
      label: Password
      secret: true
  required: [username, password]
injectors:
  env:
    SN_STATS_USERNAME: "{{ username }}"
    SN_STATS_PASSWORD: "{{ password }}"
```

MariaDB monitor (mariadb_monitor.yml)

For the mariadb health check. Needed when MariaDB runs in a container (the official images give root a password); optional on a host install, where the check can log in as root through the local socket. The password reaches the client only through its environment (MYSQL_PWD), never a command line. The account needs no data access at all (docs/MARIADB.md section 4 has the GRANT).

```yaml
inputs:
  fields:
    - id: username
      type: string
      label: Monitor account
    - id: password
      type: string
      label: Password
      secret: true
  required: [username, password]
injectors:
  env:
    MARIADB_MONITOR_USER: "{{ username }}"
    MARIADB_MONITOR_PASSWORD: "{{ password }}"
```

Keystore password (keystore_password.yml)

Optional, for the certs check on a PKCS12 keystore (JKS keystores list without a password). In the inventory, name the variable, never the password: check_certs_keystores: [{path: /path/to/keystore, password_env: KEYSTORE_PASSWORD}]

```yaml
inputs:
  fields:
    - id: password
      type: string
      label: Keystore password
      secret: true
  required: [password]
injectors:
  env:
    KEYSTORE_PASSWORD: "{{ password }}"
```

STIG Manager API (stigman_api.yml)

Optional, for the STIG Manager cross-check in playbooks/poam_status.yml, the checklist comparison in playbooks/stig_drift_report.yml and the STIG recheck (all only read): a client with the client-credentials grant, the scope stig-manager:collection:read and a grant in the collections to read. Workflow 37's playbooks/stigman_update.yml gets a second credential of this type: a client that may write reviews (the scope stig-manager:collection). Both clients are created by your Keycloak realm owner - this repository never changes the realm.

YAML

```yaml
inputs:
  fields:
    - id: token_url
      type: string
      label: Token URL
      help_text: https://keycloak.example.mil/realms/<realm>/protocol/openid-connect/token
    - id: client_id
      type: string
      label: Client ID
    - id: client_secret
      type: string
      label: Client secret
      secret: true
  required: [token_url, client_id, client_secret]
injectors:
  env:
    STIGMAN_TOKEN_URL: "{{ token_url }}"
    STIGMAN_CLIENT_ID: "{{ client_id }}"
    STIGMAN_CLIENT_SECRET: "{{ client_secret }}"
```

ACT model key (act_model_key.yml)

YAML

```yaml
inputs:
  fields:
    - id: genai_key
      type: string
      label: GenAI API key
      secret: true
    - id: asksage_key
      type: string
      label: AskSage API key
      secret: true
injectors:
  env:
    GENAI_KEY: "{{ genai_key }}"
    ASKSAGE_API_KEY: "{{ asksage_key }}"
```

ACT GenAI beta key (act_genai_beta_key.yml)

Only for ACT with site_act_provider=genai-beta (the GenAI.mil beta proxy). A separate type, so an "ACT model key" type that is already in use does not have to change (AAP refuses to change the fields of a credential type that credentials use). Attach it next to "ACT model key".

YAML

```
inputs:
  fields:
    - id: genai_beta_key
      type: string
      label: GenAI beta API key
      secret: true
  required: [genai_beta_key]
injectors:
  env:
    GENAI_BETA_KEY: "{{ genai_beta_key }}"
```

STIG Manager database (stigman_database.yml)

YAML

```
inputs:
  fields:
    - id: mysql_root_password
      type: string
      label: MySQL root password
      secret: true
      help_text: Used only when the database is first created (MYSQL_ROOT_PASSWORD_FILE).
    - id: stigman_db_password
      type: string
      label: STIG Manager database user password
      secret: true
  required: [mysql_root_password, stigman_db_password]
injectors:
  env:
    STIGMAN_MYSQL_ROOT_PASSWORD: "{{ mysql_root_password }}"
    STIGMAN_DB_PASSWORD: "{{ stigman_db_password }}"
```

TLS certificate (tls_certificate.yml)

AAP writes each value to a private temporary file inside the job's execution environment and puts the file's PATH in the environment variable; the playbook copies the files to the host.

```yaml
inputs:
  fields:
    - id: certificate
      type: string
      label: Certificate (PEM; server certificate first, then intermediates)
      multiline: true
    - id: private_key
      type: string
      label: Private key (PEM)
      multiline: true
      secret: true
    - id: ca_chain
      type: string
      label: CA chain (PEM) - also used to trust your Keycloak/other internal services
      multiline: true
  required: [certificate, private_key]
injectors:
  file:
    template.cert: "{{ certificate }}"
    template.key: "{{ private_key }}"
    template.ca: "{{ ca_chain }}"
  env:
    TLS_CERT_FILE: "{{ tower.filename.cert }}"
    TLS_KEY_FILE: "{{ tower.filename.key }}"
    TLS_CA_FILE: "{{ tower.filename.ca }}"
```

Container registry login (hosts) (registry_login.yml)

For podman on the MANAGED HOSTS (the built-in "Container Registry" credential type is for pulling execution-environment images on AAP itself, not for the hosts).

```yaml
inputs:
  fields:
    - id: registry
      type: string
      label: Registry (e.g. docker.io, quay.io)
    - id: username
      type: string
      label: Username
    - id: password
      type: string
      label: Password or access token
      secret: true
  required: [registry, username, password]
injectors:
  env:
    REGISTRY_HOST: "{{ registry }}"
    REGISTRY_USERNAME: "{{ username }}"
    REGISTRY_PASSWORD: "{{ password }}"
```

Teams webhook (teams_webhook.yml)

```yaml
inputs:
  fields:
    - id: webhook_url
      type: string
      label: Teams Workflows webhook URL
      secret: true
  required: [webhook_url]
injectors:
  env:
    TEAMS_WEBHOOK_URL: "{{ webhook_url }}"
```

SMTP relay (smtp_relay.yml)

Only when your mail relay needs a login to send. The jobs that email a report (report_email_to, roles/site_email) read SMTP_USERNAME / SMTP_PASSWORD from it. A relay that accepts mail from the AAP server without a login needs no credential.

```yaml
inputs:
  fields:
    - id: username
      type: string
      label: SMTP user name
    - id: password
      type: string
      label: SMTP password
      secret: true
  required: [username, password]
injectors:
  env:
    SMTP_USERNAME: "{{ username }}"
    SMTP_PASSWORD: "{{ password }}"
```

Report website (report_web.yml)

The login for the report website (roles/site_email, docs/WEB_REPORTS.md): - on a Windows server (report_web_host): the user name (DOMAIN\user) and password the job logs in with over WinRM to write the pages - without this credential, the template's Machine credential; - for uploads (report_web_dest: https://...): a token, sent as "Authorization: Bearer <token>", or the user name and password, as basic authentication; - on a Windows file share (report_web_dest: \\fileserver\share\folder): the account (DOMAIN\user) that writes the pages there over SMB - Modify on that folder. A report folder (a mounted share) needs no credential.

```yaml
inputs:
  fields:
    - id: username
      type: string
      label: User name (DOMAIN\user for a Windows server or a file share)
    - id: password
      type: string
      label: Password
      secret: true
    - id: token
      type: string
      label: Upload token (instead of a user name and password)
      secret: true
injectors:
  env:
    REPORT_WEB_USERNAME: "{{ username | default('') }}"
    REPORT_WEB_PASSWORD: "{{ password | default('') }}"
    REPORT_WEB_TOKEN: "{{ token | default('') }}"
```

Horizon API (horizon_api.yml)

Used by playbooks/horizon_*.yml (the Connection Server's REST API, https://<connection-server>/rest/). The account: an AD account with a Horizon administrator role - the least it needs is in docs/HORIZON.md.

```yaml
inputs:
  fields:
    - id: url
      type: string
      label: Connection Server URL
      help_text: e.g. https://horizon.example.mil (a Connection Server, or the load balancer in
        front of them)
    - id: domain
      type: string
      label: AD domain
      help_text: The account's domain, NetBIOS name (e.g. CORP)
    - id: username
      type: string
      label: User name
      help_text: The account's login name, without the domain (e.g. svc-horizon-aap)
    - id: password
      type: string
      label: Password
      secret: true
    - id: verify_ssl
      type: boolean
      label: Verify the Connection Server's certificate
      default: true
  required: [url, domain, username, password]
injectors:
  env:
    HORIZON_URL: "{{ url }}"
    HORIZON_DOMAIN: "{{ domain }}"
    HORIZON_USERNAME: "{{ username }}"
    HORIZON_PASSWORD: "{{ password }}"
    HORIZON_VERIFY_SSL: "{{ verify_ssl }}"
```

Report database (report_database.yml)

The report database (docs/REPORT_DATABASE.md): MySQL 8.4 in its own container on the STIG Manager host, apart from STIG Manager's database (port 3309 on the host). Ticket insights writes its figures there each run (servicenow_insights_db: true) and reads the last 12 months back for the page's trend. The account: report_writer (SELECT, INSERT, UPDATE, DELETE, CREATE, ALTER, INDEX, CREATE VIEW, SHOW VIEW on site_reports). Plain TCP unless Use TLS is ticked; then the CA (optional) checks the server's certificate. The password reaches the job only through its environment, never a command line or an extra variable.

YAML

```
inputs:
  fields:
    - id: host
      type: string
      label: Database host (the STIG Manager host's name)
    - id: port
      type: string
      label: Port
      default: "3309"
    - id: database
      type: string
      label: Database
      default: site_reports
    - id: username
      type: string
      label: User
      default: report_writer
    - id: password
      type: string
      label: Password
      secret: true
    - id: use_tls
      type: boolean
      label: Use TLS
      default: false
    - id: ca
      type: string
      label: CA certificate (PEM) - with Use TLS, the CA that signed the server's certificate
        (empty = the EE's trust store)
      multiline: true
  required: [host, database, username, password]
injectors:
  file:
    template.ca: "{{ ca | default('') }}"
  env:
    REPORT_DB_HOST: "{{ host }}"
    REPORT_DB_PORT: "{{ port | default('3309') }}"
    REPORT_DB_NAME: "{{ database }}"
    REPORT_DB_USER: "{{ username }}"
    REPORT_DB_PASSWORD: "{{ password }}"
    REPORT_DB_TLS: "{{ use_tls | default(false) }}"
    REPORT_DB_CA_FILE: "{{ tower.filename.ca if ca | default('') else '' }}"
```