

Thursday Quiz

1. [0.5 point] After applying the Girvan-Newman algorithm, we delete the edge that has the smallest betweenness value.


Answer- False

2. [0.5 point] In Affiliation Graph Model (AGM), if two nodes u, v share no community then the edge probability $P(u, v)$ is very high.

Answer - False

3. [2.5 points] For node E, use the Girvan-Newman algorithm to calculate the betweenness of each edge (do this for node E ONLY). Write down the edges and their betweenness values in the format below:

(Edge1, Edge2) = Betweenness Value



Answer-

(A,C) - 0.5 [0.5 points]

(A,D) - 0.5 [0.5 points]

(B,C) - 1 [0.5 points]

(C,E) - 2.5 [0.5 points]

(D,E) - 1.5 [0.5 points]

4. [2 point] How is edge betweenness used to find communities in Girvan-Newman?

Answer -

- Edge betweenness: Number of shortest paths passing over the edge.
 - Betweenness scores for edges of a graph behave something like a distance metric.
 - Not a true distance metric.
 - Could cluster by taking edges in increasing order of betweenness and adding to graph one at a time.
 - At each step, connected components of graph form clusters.
 - Girvan-Newman: Start with the graph and all its edges and remove edges with highest betweenness
5. Consider the following matrix F that represents the Node community membership strengths. For each of the possible pairs of edges, what is the probability of that edge? Here, u, v and w are your nodes.

F_u 0 1.3 0 0.8

Fv	0.9	0	0	1.4
Fw	0	1.6	1	0

Answer-

$$P(u,v) = 1 - \exp(-0.8 \cdot 1.4) = 0.673 \text{ [0.5 points]}$$

$$P(v,w) = 1 - \exp(-0) = 0 \text{ [0.5 points]}$$

$$P(w,u) = 1 - \exp(-1.3 \cdot 1.6) = 0.875 \text{ [0.5 points]}$$

6. [1 point] Differentiate between overlapping and non-overlapping communities.

Answer-

In overlapping communities, communities can share nodes with other communities where as in non-overlapping communities, communities do not share nodes with other Communities. Edge Density in overlapping community is higher

7. [1+1 points] What do you mean by modularity when talking about network communities. What is its use?

Modularity is measure of how well a network is partitioned into communities. It takes the value between the range $[-1,1]$. It is positive when the number of edges within groups exceeds the expected number. It is useful for selecting the number of clusters