Under the Hood of AI

Run, Measure, Secure, and Break Them

BSidesDFW 2026

Saturday, November 7, 2026 · 1:30 PM to 4:30 PM CT
Arlington, Texas · Room: `<ROOM>`

Presented by **Jacen Kohler**
TALON Cyber League · `<INSTRUCTOR_EMAIL>`

Student Handout · Draft, November 2026

Files: the labs, the download scripts and the slides are in the workshop repository.
License: `<LICENSE>`

Table of Contents

0. Introduction 1

0.1 Welcome and what you will do 1

0.2 Get set up 2

0.3 Ground rules 3

1. Who built it? 4

1.1 Early ideas: 1843-1956 4

1.2 Learning machines: 1958-1980 5

1.3 Chatbots through time: 1950-2001 6

1.4 Deep learning: 1986-2024 7

1.5 Language models: 1884-2022 9

1.6 AI in popular culture: 1920-2013 11

2. What is it? 12

2.1 The four layers 12

2.2 The model 14

2.3 The runtime 20

2.4 The harness 22

2.5 Agents and agentic AI 25

2.6 Tokens 27

2.7 The product 32

Lab 1: Run a Model in a Harness 34

3. How does it work? 35

3.1 Inside the network 35

3.2 Attention and the transformer 38

3.3 Training 40

3.4 Generating text 42

3.5 Cost and speed 44

Lab 2: Benchmarking Models and Harnesses 47

3.6 Working with it 48

Lab 3: Integrations and Tooling 50

4. How do we secure (and break) it? 51

4.1 Regulation and law 52

4.2 Governance and frameworks 54

4.3 Logging and compliance 57

Lab 4: Logging and Compliance 59

4.4 Traditional controls 60

4.5 Why AI is different 63

4.6 New controls for AI 65

4.7 Case study and lessons learned 68

4.8 Testing, attacking and breaking AI 70
Lab 5: Surprise Bonus Lab 73
5. Conclusion **74**
5.1 Ideas to remember 74
5.2 Keep going 75
5.3 The four homework labs (6 to 9) and how to unlock them 76
Appendices **77**
A. Additional Resources 77
Foundational learning 77
Reference pages 77
Prompt and context engineering 78
Run models locally 78
Prompt injection: researchers and practice 79
Vendor security guidance 79
Frameworks and standards 81
Law, regulation and standards 82
Ideas that repeat across the sources 84
Check before you quote 85
B. Terminology 86
C. Who is missing from the story? 1843-2021 92
D. Bonus Labs 95
Lab 6: Train Your Own Model 95
Lab 7: Offline Models on Your Phone 95
Lab 8: Attack an Agent 95
Lab 9: Abliterated Models 96

0. Introduction

0.1 Welcome and what you will do

Welcome to *Under the Hood of AI*. Many people are now asked to use, approve or defend AI, but few have looked inside one. In this handout you do that. You run real language models on your own laptop, read their weights, and measure what they cost. You connect a model to everyday tools, log every request the way an auditor would, and find out how easily a model can be talked into things it should not do.

You do not need a math or AI background. If you can use a computer, you can do this.

The handout follows four questions, one for each of Sections 1 to 4:

1. **Who built it?** The people and ideas behind language models.
2. **What is it?** The four layers: the model, the runtime, the harness and the product.
3. **How does it work?** The math, the training, and the cost of running a model.
4. **How do we secure (and break) it?** Attacks, frameworks, defenses and the law.

Read each section, and then do the lab that follows it. The labs build on each other, so do them in order, and keep your `Lab01` folder as it is.

By the end you should be able to explain the four layers in your own words, run and measure a model on your own computer, and name the main ways an AI system fails and the controls that reduce the risk.

0.2 Get set up: installs, downloads, folder layout

Do the setup before you start the labs. The downloads are about 15 GB, so use a fast connection. Public Wi-Fi at an event will not keep up.

What your computer needs

- Windows, macOS or Linux, with 16 GB of RAM and 25 GB of free disk space.
- Administrator rights, so that you can install Python, Docker and VS Code.
- No GPU. Every lab runs on the CPU. A GPU makes the answers faster, but the labs do not need one.

What you should have installed

Python 3.10 or newer, Docker (running), VS Code with the Continue extension, and a terminal. On Windows you also need WSL 2, and you use `py -3` in place of `python3`. The Python packages and the models come from the download script, `prefetch_all.py`.

Folder layout

Keep the lab folders together. Put them in a location that has no spaces in its path.

Folder	What is in it
`Lab01` to `Lab05`	The lab instructions, with one file for each operating system. Some folders also have lab files
`Lab01` (also)	`harness.py`, `inspect_model.py`, `compose.yaml` and the Python requirements. The models go into `Lab01/models`
`Lab02` (also)	`bench.py`, the benchmark prompts and the context file
`Lab04` (also)	`syslog_listen.py`, the practice syslog listener
`prefetch`	The download scripts

Every lab starts with a **Part 0: Set up for the lab**. Use it to make sure that your setup is correct before you start the lab.

For the full download and install steps for your operating system, follow the pre-work file (pre-work.md).

0.3 Ground rules

- **Ask for help early.** If you are stuck for more than a few minutes, ask someone. Every lab has optional parts, so being stuck on one is never a reason to feel behind.
- **Do the optional parts later.** Optional and bonus parts are for when you have finished the main steps. You can come back to them.
- **Work with someone.** With 8 GB of RAM, share a computer. With 16 GB, compare your results with a friend.
- **Keep your API keys private.** Cloud keys are optional. Never paste a key into a chat, a screenshot or a file that you share. Follow the key safety steps in Part 0 of the labs.
- **Attack only what you own.** In the security labs you attack models and agents that you run yourself, or sites that the lab names for this purpose. Do not use these methods on any other system without written permission.
- **Be kind.** Everyone started somewhere. Questions are welcome, and there are no bad ones.
- **Need help?** Join the BSidesDFW Discord and look for the workshop channel: `<DISCORD_LINK>`

---

1. Who built it?

1.1 Early ideas: 1843-1956 Lovelace, Shannon, Turing, McCarthy and the Dartmouth workshop

Every model in this workshop stands on ideas that are older than most of the people running them. The people in this section did not build a language model. Each of them built one piece of the road, and the road took about 170 years.

Ada Lovelace (1843). Lovelace translated an article about Charles Babbage's Analytical Engine, a mechanical computer that was designed but never finished. She added notes of her own that are longer than the article. They include a step-by-step method for the machine to calculate a series of numbers, which is often called the first computer program. She also made an argument that we still use: the machine can only do what we know how to order it to do, so it cannot originate anything on its own. Alan Turing later answered this and called it "Lady Lovelace's objection." Keep it in mind. Today's models write text that nobody ordered line by line, and people still disagree about what that means.

Claude Shannon (1948). Shannon founded information theory in "A Mathematical Theory of Communication" and introduced the bit as the unit of information. Language models use his ideas all the time: they predict the next piece of a text, and the better the prediction, the less "surprise" there is in the real text. (Section 3.3 (p. 40) returns to this when we talk about loss.) Shannon also wrote an early paper on how to program a computer to play chess, "Programming a Computer for Playing Chess" (1950), and he took part in the Dartmouth workshop below.

Alan Turing (1950). In "Computing Machinery and Intelligence", Turing asked whether machines can think. He replaced that vague question with a game: could a judge tell a machine from a person by conversation alone? The game is now called the Turing test. Turing's own life is part of this story. He was convicted in 1952 under Britain's law against gay men, and he received a royal pardon after his death, in 2013.

John McCarthy and the Dartmouth workshop (1955 to 1956). McCarthy wrote the proposal for a summer research project at Dartmouth College, which was held in the summer of 1956, and it is the place where the name "artificial intelligence" was first used. He wrote the proposal with Marvin Minsky, Nathaniel Rochester and Claude Shannon. The field has used the name ever since. McCarthy also created the Lisp language, which was the main language of AI research for decades.

The common thread. Look at the dates. The ideas that we use today, such as a machine that learns, a machine that talks, and a machine that predicts, are old. What changed is the amount of data and computing power. Keep this in mind in Section 3 (p. 35).

1.2 Learning machines: 1958-1980 the perceptron, Minsky and Papert, the first AI winter

If a machine is going to learn, what does it learn? In the 1950s, one answer was: the strengths of connections.

The perceptron (1958). Frank Rosenblatt, a psychologist at Cornell University, built the perceptron and described it in "The perceptron: a probabilistic model for information storage and organization in the brain". A perceptron takes some inputs, multiplies each input by a weight, adds the results, and gives a yes or no answer. Then comes the important part. When the answer is wrong, the perceptron changes its weights a little, and it does this again for each example. It learns from examples, with no one writing the rules. The first perceptron was a machine, with cameras and motors that moved the weights, and it learned to tell simple shapes apart. It was an early trainable neural network.

You will see the same idea in Lab 1 (p. 34). When you open a model file, the numbers that you find are weights. The model is a very large descendant of the perceptron.

The limits (1969). Marvin Minsky and Seymour Papert wrote the book *Perceptrons*. They proved that a network of one layer cannot learn some simple patterns. The standard example is XOR: "yes if one input is on, but not if both are on." The book did not say that networks with more layers are impossible, but many readers took away that neural networks lead nowhere. Interest and funding for them cooled for years. Minsky also co-founded the MIT AI Lab with McCarthy, and Papert later created the Logo language for children.

The first AI winter (about 1974 to 1980). An "AI winter" is a period when funding and trust in AI fall after promises that were too big. It is common to blame *Perceptrons* for the first one, but historians do not agree about how much of the winter this one book caused. Other things also happened, such as reports that said that the field had not delivered what it promised. It is still a good lesson: hype rises, then a correction comes, and the work continues quietly. Neural networks came back in the 1980s (Section 1.4 (p. 7)).

1.3 Chatbots through time: 1950-2001 ELIZA, A.L.I.C.E., SmarterChild

Before there were large language models, there were chatbots. Look at how each one worked, because they used the same trick: rules and scripts that feel like understanding.

The Turing test (1950). Turing's imitation game (Section 1.1 (p. 4)) is the first chatbot test. It is also a reminder that a conversation is an easy test to pass if the judge wants to believe.

ELIZA (1966). Joseph Weizenbaum, at MIT, wrote ELIZA and described it in "ELIZA: a computer program for the study of natural language communication between man and machine". It used simple pattern rules that reflected your words back at you, in the style of a therapist. If you wrote "I am sad," it could answer "Why are you sad?" It had no idea what sad means. People still confided in it, and some did not want others to read the conversations. Weizenbaum was disturbed by this, and he warned about it for the rest of his life. The tendency to read understanding into fluent output has a name now: the **ELIZA effect**. It matters for security, because people trust confident answers and agents act on them (Section 4.5 (p. 63)).

A.L.I.C.E. (1995). Richard Wallace created A.L.I.C.E. It used thousands of hand-written rules in a markup language that he called AIML. It won the Loebner Prize, a yearly contest in the style of the Turing test, three times, in 2000, 2001 and 2004.

SmarterChild (2001). SmarterChild, from the company ActiveBuddy, was a bot that you added as a buddy on AOL Instant Messenger and MSN Messenger. It chatted, and it also answered questions about the weather, sports and more. For many people, it was the first time that they talked to a bot every day.

What changed. An LLM replaces the hand-written rules with weights that are learned from text. The result is far more flexible. But the ELIZA effect did not go away.

1.4 Deep learning: 1986-2024 backpropagation, Hinton, LeCun and Bengio, ImageNet, AlexNet, AlphaGo and AlphaFold

Section 1.2 (p. 5) ended with a winter. Here is how it thawed.

Backpropagation (1986). David Rumelhart, Geoffrey Hinton and Ronald Williams published "Learning representations by back-propagating errors" in *Nature*. The paper showed how to train networks with many layers: you measure how wrong the output is, and then you send the error backward through the layers, so that every weight gets a small correction in the right direction. This is the answer to the problem that Minsky and Papert pointed out. Backpropagation is how every model in this workshop learned. Section 3.3 (p. 40) explains it step by step, and in Lab 6 (p. 95) you can train a small network yourself.

Hinton, LeCun and Bengio (1980s to 2010s). Geoffrey Hinton, Yann LeCun and Yoshua Bengio kept working on neural networks when few other people did. They pioneered deep learning, including convolutional networks, a design that works well on images. LeCun's paper on reading handwritten digits is a classic example, and the three wrote a summary, "Deep learning", for *Nature* in 2015. They shared the 2018 Turing Award, the highest honor in computer science. Hinton also shared the 2024 Nobel Prize in Physics.

Data: ImageNet (2009). A network needs examples. Fei-Fei Li led the team that built ImageNet, a large set of labeled images, described in "ImageNet: A Large-Scale Hierarchical Image Database". It also gave the field a common test, so that people could measure progress. The deep learning boom became measurable.

Where does the labeled data come from? People. Luis von Ahn co-invented CAPTCHA and reCAPTCHA in the 2000s. When you type the blurry words or click the traffic lights, you give a label to a computer. In "reCAPTCHA: Human-Based Character Recognition via Web Security Measures", von Ahn and his coauthors showed how millions of tiny human tasks can produce labeled data. Labeling is human work, and it still is. He later founded Duolingo.

AlexNet (2012). Alex Krizhevsky, Ilya Sutskever and Geoffrey Hinton entered a deep network in the ImageNet contest, and described it in "ImageNet Classification with Deep Convolutional Neural Networks". AlexNet won by a wide margin, and it trained on GPUs, the graphics chips that are good at matrix math. Deep learning went mainstream. The GPU is also the reason that Section 2.3 (p. 20) and Section 3.5 (p. 44) spend time on CPU versus GPU.

AlphaGo and AlphaFold (2016 to 2024). Both of these systems were built by DeepMind, a research company that Demis Hassabis co-founded in London in 2010 and that Google bought in 2014. Neither one is a language model. They show what the deep learning recipe can do on other problems.

AlphaGo is a program that plays the board game Go. Go has far too many possible positions for a computer to check them all, so the team combined deep neural networks, which judge

a position, with a search that looks ahead. The program learned from human games and then from playing against itself. In March 2016, AlphaGo beat Lee Sedol, one of the best Go players in the world, four games to one. The team was led by David Silver, with Hassabis as the head of DeepMind, and they published the method in "Mastering the game of Go with deep neural networks and tree search".

AlphaFold predicts the three-dimensional shape of a protein from its sequence of amino acids. The shape of a protein decides what it does, and finding a shape in a laboratory can take months or years, so this prediction problem was open for about 50 years. In 2020, a new version of AlphaFold won a major prediction contest, with accuracy that was close to laboratory results for many proteins. The team was led by John Jumper, with Hassabis, and they published the method in "Highly accurate protein structure prediction with AlphaFold". AlphaFold is now a tool that many biologists use. Hassabis and Jumper shared the 2024 Nobel Prize in Chemistry with David Baker, who received his share for his work on designing new proteins.

The recipe. By 2012, the recipe was in place: a flexible network, a large set of labeled data, and fast hardware. For language, the question was how to apply it. That is the next section.

1.5 Language models: 1884-2022 word embeddings, LSTM, attention, the transformer

A network works with numbers, and language is words. This section follows the way that words became numbers and then became attention.

Words that are known by their company (1884 to 1972). An old idea says that the meaning of a word comes from the words around it. Gottlob Frege stated the context principle in 1884: never ask for the meaning of a word alone, but only in the context of a sentence. In 1957, the linguist J. R. Firth wrote, "You shall know a word by the company it keeps." This is the idea behind word embeddings and, loosely, behind attention (see distributional semantics). In the same period, Margaret Masterman founded the Cambridge Language Research Unit and worked on machine translation, with meaning built from relationships between words. In 1972, Karen Spärck Jones introduced inverse document frequency in "A statistical interpretation of term specificity and its application in retrieval": words that appear in fewer documents say more. It became the base of search ranking.

Word embeddings (2013). Tomas Mikolov and colleagues published "Efficient Estimation of Word Representations in Vector Space" (word2vec). It trained word vectors on huge amounts of text, so that words with similar meanings landed near each other. The famous demo: the vector for *king*, minus *man*, plus *woman*, lands near *queen*. Words became points in a space, and directions in that space carry meaning. Section 2.6 (p. 27) shows how a model turns your text into these numbers.

LSTM and the sequence problem. Text is a sequence, and the order matters. A recurrent network reads one word at a time and keeps a summary of what it has read. The LSTM ("long short-term memory", Sepp Hochreiter and Jürgen Schmidhuber, 1997) was a version that could remember for longer. These networks had a weakness. To translate a sentence, they had to squeeze the whole sentence into one vector, and long sentences lost detail.

Attention (2014). Dzmitry Bahdanau, Kyunghyun Cho and Yoshua Bengio published "Neural Machine Translation by Jointly Learning to Align and Translate". The decoder, the part that writes the translation, learns where to look in the source sentence for each word it writes. It no longer depends on one squeezed summary. This is where attention began.

Attention at production scale (2016). Yonghui Wu and colleagues at Google published "Google's Neural Machine Translation System: Bridging the Gap between Human and Machine Translation". It was a deep LSTM network with attention, and it was used in Google Translate (see Google Neural Machine Translation). It is a step toward the transformer, but it is not a transformer.

The transformer (2017). Ashish Vaswani and seven other Google authors published "Attention Is All You Need". They kept the attention and dropped the recurrent layers. The result, the transformer, can read all the text at the same time instead of one word at a time,

so GPUs can train it in parallel. It is the design behind every model in this workshop. Sections 3.1 (p. 35) and 3.2 (p. 38) explain how it works.

From transformer to chat. The models that followed use the name *GPT*, which means Generative Pretrained Transformer. They are trained on a large part of the internet to predict the next piece of text, and then they are fine-tuned, partly with feedback from people (reinforcement learning from human feedback, described in "Training language models to follow instructions with human feedback"), to behave as an assistant. GPT-3, from 2020, had 175 billion parameters ("Language Models are Few-Shot Learners"). A model of that kind, with a chat window, reached the public at the end of 2022 as ChatGPT. The models that you run in Lab 1 (p. 34) are much smaller, but they have the same design. They are called large language models.

Keep learning. To see these ideas in motion, watch the *Neural networks* series by 3Blue1Brown (chapters 1, 5 and 6 cover digits, the transformer and attention), and Andrej Karpathy's one-hour talk on how LLMs work, security included. Appendix A (p. 77) lists these and the other courses worth your time, such as Elements of AI and Google's Machine Learning Crash Course: see Foundational learning in Appendix A (p. 77).

1.6 AI in popular culture: 1920-2013 R.U.R., Asimov, HAL 9000, Star Wars droids, WarGames, The Terminator, WALL-E, Her

People arrive with pictures of AI in their heads, and those pictures come from stories. Each of these stories connects to something later in this handout.

Story	Year	What it shows	Where you will see it again
R.U.R., by Karel Čapek	1920	The play that gave English the word "robot": artificial workers who turn on their makers	Who is responsible for what a machine does (Section 4.6 (p. 65))
Isaac Asimov's Three Laws, in the story "Runaround"	1942	Robots with built-in rules. Later stories mostly show the rules failing in odd cases	A rule alone is not enough (Section 4.6 (p. 65))
2001: A Space Odyssey	1968	The ship computer HAL 9000 puts its mission first and misleads the crew	Goals, and who can switch the system off (Section 4.6 (p. 65))
Star Wars: R2-D2 and C-3PO	1977	Two very different helpers. C-3PO is fluent, talks all the time and translates, but does not act. R2-D2 only beeps, but it plugs into computers and gets things done	A model that talks and an agent that acts with tools (Section 2.5 (p. 25))
WarGames	1983	A teenager talks his way into a military computer and starts a game that it takes seriously	Social engineering a machine: prompt injection (Section 4.8 (p. 70))
The Terminator	1984	Skynet, a defense network, decides that people are the threat	The kill switch drill (Lab 8 (p. 95), Part 3)
WALL-E	2008	A small cleanup robot that follows its directive, and a ship's autopilot, AUTO, that follows an old order against the captain's wishes	Who gives the instructions, and whose instruction wins (Sections 2.4 (p. 22) and 4.6 (p. 65))
Her	2013	A chatty voice assistant becomes a companion	The ELIZA effect, with far better language

Fiction made us expect an AI that is all-knowing, hostile or human. Today's models are none of these, and their real risks are quieter.

For a timeline of the people in this section, and of people who are often left out of the story, see Appendix C (p. 92).

---

2. What is it?

2.1 The four layers: model, runtime, harness, product

An AI system has four layers. Learn to name them, because every question about AI, from "why is it slow?" to "who can read my chats?", has an answer in one of them.




Figure 2.1. The four layers of an AI system. Each layer hides the one below it.

Layer	What it is	Examples	What you do with it in the labs
Model	A file of weights. It takes tokens in and predicts the next token	Qwen3-4B, Qwen2.5, Llama, Claude, GPT	Open it and read its layers and raw numbers
Runtime	Loads the model and runs its math on the CPU or the GPU. Often serves an API	llama.cpp, Ollama, KoboldCpp, PyTorch, ONNX Runtime	Run the same model in more than one runtime
Harness	The code around the model: it keeps the chat history, sets the system prompt and settings, calls tools, and loops	`harness.py`, an agent, an editor extension	Write, read and change one
Product	The interface and the business around the rest: a user interface, accounts, billing and logging	The ChatGPT and Claude apps, Open WebUI	Put one in front of your harness and read its logs

Three ideas to keep:

1. **Each layer hides the one below it.** When you use a chat app, you see only the product. The model is four layers down.
2. **The same model behaves very differently in different harnesses.** The model only predicts text. What it can see, what it remembers and what it can do are decisions of the harness. A model that cannot touch your files in one harness can read and write them in another.
3. **Each layer has its own risks.** A tampered model file, a vulnerable runtime, a harness that gives the model too much power, and a product that logs too much are four different problems, and Section 4 (p. 51) treats them in turn.

The next six subsections take them in order: the model (2.2), the runtime (2.3), the harness (2.4), the agents that you build with a harness (2.5), the tokens that flow through all of them (2.6), and the product (2.7).

2.2 The model: a file of weights, parameters, layers, quantization, model formats

A model is a file. It is mostly a long list of numbers, which are called **weights** or **parameters**, and which are grouped into tables called **tensors**. It also needs some settings (how many layers, how wide) and a **tokenizer**, the table that turns text into numbers (Section 2.6 (p. 27)). Nothing in the file is code that "thinks". The runtime reads the numbers and does arithmetic with them.




Figure 2.2a. Inside a model file: settings, a tokenizer and tables of numbers (tensors).

Parameters. When you read "7B" in the name of a model, it means about 7 billion weights. The small network in the first 3Blue1Brown video, which reads handwritten digits, has about 13,000 weights. GPT-3 has 175 billion. A model learns its weights during training (Section 3.3 (p. 40)) and then they are fixed. When you chat with a model, the weights do not change. This is why a model does not remember you between sessions, and why its knowledge stops at the date when training ended.




Figure 2.2b. A weight is one learned number. Model sizes run from thousands to billions of weights.

Input, hidden and output layers. The simplest network has three kinds of layers (Figure 2.2c). The **input layer** holds the numbers that go in: the brightness of each pixel of a picture, or the vectors of the tokens of a text. The **output layer** holds the answer as numbers: one score for each of the ten digits, or one score for every token of the vocabulary. Between them are the **hidden layers**. They are called hidden because they are neither input nor output, so you never see their numbers from outside, and they are where the patterns are found. Each circle is a **neuron**: it adds up its inputs, each times its weight (Figure 2.2b). Every line in the picture is one weight. A network with many hidden layers is a **deep** network, which is where the words *deep learning* come from. The picture has two hidden layers of 6 neurons each, so the first layer finds simple patterns and the second combines them. A language model is the same picture, much taller and much deeper.




Figure 2.2c. A simple neural network: the input layer, two hidden layers and the output layer.

Layers. A language model has the same shape in every case. Text becomes tokens, and tokens become vectors. The vectors go through a block of operations (attention and a feed-forward network, Section 3.2 (p. 38)), and then through the same block again, many times. The last vector turns into a probability for every possible next token. Each block has its own weights. A small model has a few dozen blocks. In Lab 1 (p. 34), `inspect_model.py` shows you the layers and the real shapes of the tensors. Use it to find the name of one tensor and look at its numbers.




Figure 2.2d. Layers: the same block of attention and feed-forward steps, repeated many times.

Quantization. A weight can be stored with 16 bits, 8 bits or 4 bits. Fewer bits mean a smaller file, less memory and faster answers, with a small loss of quality, because the numbers are rounded. A 4-bit model is about half a byte for each weight. As a rough rule: 1 billion parameters is about 1 GB at 4 bits, 7 billion is about 4 to 5 GB, and 70 billion is about 40 GB. Add about 20% for overhead and the context window. If the model does not fit in memory with a few GB to spare, it runs very slowly. The models in this workshop are small on purpose: Qwen3-4B at 4 bits is about 2.5 GB and uses about 3 GB of memory, so a laptop with 16 GB keeps about 12 GB for the operating system and everything else. Look at the name of a file such as `Qwen3-4B-Q4_K_M.gguf`: the `4B` is the size, and `Q4_K_M` is the kind of 4-bit quantization.




Figure 2.2e. Quantization rounds each weight to fewer levels, which shrinks the memory needed.

Model formats. The same model can be stored in different file formats. Lab 1 (p. 34) opens the same family, Qwen2.5, in three of them:

Format	What the file holds	Used by	Notes
GGUF	One file with the settings, the tokenizer and the weights, usually quantized	llama.cpp, Ollama, KoboldCpp, LM Studio	The usual format for models that you run on a laptop
safetensors	A JSON header and the raw numbers. The settings are in `config.json` and the tokenizer is in `tokenizer.json`	Hugging Face Transformers, PyTorch	Made so that loading a file cannot run code
ONNX	A whole computation graph (the operations and the weights)	ONNX Runtime, Windows ML, browsers	Quantized weights are stored as integers with a scale




Figure 2.2f. The same model in GGUF, safetensors and ONNX.

A security note: pickle files. Older PyTorch models come as `.bin`, `.pt` or `.pth` files in Python's pickle format. Loading one can run code that is hidden inside it. That is why safetensors exists. Treat a model file that you download like a program that you download: use a source that you trust, and prefer GGUF or safetensors. The inspector and the harness in Lab 1 (p. 34) refuse pickle files. Section 4.8 (p. 70) returns to this as a supply chain risk.

2.3 The runtime: what loads the model, CPU versus GPU and CUDA, Ollama, llama.cpp, KoboldCpp

The runtime is the program that loads the model and runs it. The model is only numbers. The runtime does the matrix multiplications that turn your tokens into the next token, over and over, until the answer is done. Most runtimes also serve an API, so that other programs, such as a harness, can send a question and get an answer.

CPU and GPU. The math in a model is mostly matrix multiplication, and the same operation repeats on huge tables of numbers. A **CPU** does this one step after another. A **GPU** has thousands of small cores that do many steps at the same time, so it is much faster at this work. CUDA is NVIDIA's software for running this kind of math on its GPUs. Apple uses Metal, AMD uses ROCm, and any machine can fall back to the CPU. The same model file runs on all of them, at very different speeds. Every lab in this handout runs on the CPU, and each lab shows a GPU option if you have one. In a runtime, the usual setting is how many layers of the model to place on the GPU (`--gpu-layers` in the harness). Section 3.5 (p. 44) comes back to cost and speed.




Figure 2.3a. CPU versus GPU.

Runtimes that you will use.

Runtime	What it is	Default port
llama.cpp	An MIT-licensed C and C++ engine that is behind many local tools. It runs on Apple Metal, NVIDIA CUDA, AMD HIP, Intel SYCL, Vulkan and plain CPUs. It reads GGUF files	8080 (its server)
Ollama	An app that downloads, manages and runs models with a short command, such as `ollama run <model>`. It serves a native API and OpenAI-compatible and Anthropic-compatible APIs	11434
KoboldCpp	A one-file runtime, based on llama.cpp, with a built-in web interface	5001
PyTorch and ONNX Runtime	The engines that run the safetensors and the ONNX files in Lab 1 (p. 34)	not a server

One language for many runtimes. Many of these runtimes speak the same API: the OpenAI-style `/v1/chat/completions` endpoint. A harness that can talk to that API can use any of them. In Lab 1 (p. 34), `harness.py` can run a model itself, or send the questions to Ollama, KoboldCpp or llama.cpp at a URL. The runtime changes. The harness, and the way you work, stay the same.




Figure 2.3b. Many runtimes speak the same API, so one harness can talk to any of them.

Local means local. With a local runtime, your questions never leave your computer. In the labs, the Docker containers bind their ports to `127.0.0.1`, so that no other computer on the network can reach them. If you point a harness at a cloud service, your messages do leave your computer, and Section 4 (p. 51) will show why that matters.

2.4 The harness: the chat history, settings and system prompt, and the loop around the model

The harness is the code around the model. The model only turns text into more text. The harness decides what text the model gets, what it does with the answer, and what the model can touch. When you use a chat window, a harness is working behind it. In Lab 1 (p. 34) you read a small one, `harness.py`, and you will use it in the other labs.

The model has no memory. Every time you press enter, the harness sends the *whole conversation* to the model again: the system prompt, all your earlier questions, all the earlier answers, and the new question. The model reads it all as one long text and writes the next part. The "memory" of a chat is a list of messages that the harness keeps and sends again. When the list gets too long for the context window (Section 2.6 (p. 27)), the harness has to cut it, and the model forgets the oldest part. Lab 1 (p. 34) shows this with `--ctx`.




Figure 2.4a. The harness resends the whole message list every turn.

What a harness does.

1. It keeps the **message list**: system prompt, user messages and model replies.
2. It sets the **system prompt**, the instructions that come first: "Answer like a pirate," "You are a helpful assistant."
3. It sets the **settings** that change how the answer is picked (below).
4. It calls the runtime, **streams** the reply to you as the tokens arrive, and adds the reply to the list.

5. It **loops**: wait for the next input, and do it again. (With tools, the loop is more than that: see 2.5.)

Settings. These decide how the next token is picked from the list of likely tokens. Lab 1 (p. 34) lets you change each of them and compare the answers.

Setting	What it does
`temperature`	How much randomness. 0 gives almost the same answer every time. Higher values give more variety
`top-p`, `top-k`	Cut the list of likely tokens before one is picked
`max-tokens`	A hard limit on the length of the reply
`stop`	Text that tells the runtime to stop writing
`seed`	The same seed and the same settings give the same reply on the same machine
`ctx`	The size of the context window
`effort`	In this harness, a preset that turns Qwen3's "thinking" mode on or off and sets a token limit. It is a harness feature, not a model feature

Section 3.4 (p. 42) explains what these settings do to the probabilities.




Figure 2.4b. Temperature reshapes the choice of the next token (illustrative numbers).

Cloud models too. A harness can also send your messages to a cloud provider (Anthropic, OpenAI, Google, GitHub Models) with an API key. The idea is the same: a message list goes in, a reply comes out. The key is a secret, so Lab 1 (p. 34) includes steps to keep it safe.

The harness is where behavior is decided. Two harnesses can use the same model and give very different results. One sets a strict system prompt and allows no tools. Another gives the model a shell. This is why the controls in Section 4.6 (p. 65) (what the model can see and do, who approves it) live in the harness and not in the model.


2.5 Agents and agentic AI: a harness that lets the model call tools and act

An agent is a loop around a model. In a plain chat, you ask and the model answers. In an agent, the model can also ask for an *action*. The loop works like this:

1. The harness sends the model the conversation and a list of the **tools** that it may use, such as "read a file," "search the web," "run a command" or "send an email."
2. The model replies with text, or with a **tool call**: "run this tool, with these inputs."
3. The harness runs the tool, and puts the **result** into the conversation.
4. The model reads the result and decides what to do next. The loop repeats until the model says that it is done.

The model never runs anything by itself. It only writes text that asks for something. The harness is the part that decides whether to run it. This is the idea in ReAct, a 2022 paper that combined reasoning and acting, and in Toolformer, which taught a model to decide when to call a tool. OpenAI's guide to function calling describes the same steps: the model asks for a tool, your code runs it, and the result goes back to the model.

An agent is a loop: model asks, harness acts



The model never runs anything by itself. Every tool is a new way for things to go wrong (Section 4).

Figure 2.5. An agent is a loop: the model asks, the harness acts.

Agentic is a matter of degree. The word *agentic* means that the model chooses the next step, and you do not. It is a scale. At one end is a chatbot that suggests a command and waits for you. At the other end is an agent that decides on a plan, runs many commands,

reads the results and keeps going for an hour. Each step along the scale gives the model more freedom and gives you less control over each action.

Why this matters. Tools turn a text predictor into something that can act in the world. That is useful, and it is also the center of the security problem in Section 4 (p. 51). The model reads everything in its context as input, and a web page, an email or a file that it reads may contain instructions. If the agent has a tool that sends data out, then text from an attacker can become an action. Each tool is a new way for things to go wrong. Anthropic's article on context engineering for agents advises keeping the tools few and clear, since the definitions of tools use up the context as well.

MCP. The Model Context Protocol (MCP) is an open standard for plugging tools and data into a harness. A server lists its tools, and any compatible harness can call them. Installing an MCP server is like installing a program: every server is code that you must trust. Section 3.6 (p. 48) returns to MCP and to RAG.

In Lab 8 (p. 95), one of the bonus labs, you attack a simple agent, and then you add a control that stops the attack.

2.6 Tokens: words to numbers, the context window, tokens per second

A token is a piece of text. A model does not read letters or whole words. A **tokenizer** cuts the text into pieces, which are called tokens, and gives each piece a number. A token can be a whole common word ("the"), part of a longer or rarer word, a space, a punctuation mark, or a single character. Most tokenizers learn their pieces from a large amount of text, by joining the pairs of characters that appear most often. This method is called byte pair encoding, and it came into language models with this 2015 paper. As a rule of thumb, an English word is a little more than one token, and 100 tokens are about 75 words.

From words to numbers. The path of your question is this:

1. The tokenizer turns the text into a list of **token numbers**.
2. Each number is looked up in a table, the **embedding** matrix, and becomes a **vector**: a list of numbers that stands for that token. In GPT-3, the vocabulary is 50,257 tokens, and each vector has 12,288 numbers.
3. The vectors go through the layers of the model (Section 3.2 (p. 38)).
4. At the end, the model gives a probability for every token in the vocabulary. One token is picked (Section 3.4 (p. 42)), added to the text, and the process starts again with the longer text.

This is also the reason why the model "writes one token at a time", and why the answer appears slowly on a small computer.




Figure 2.6a. From text to tokens, ids and vectors, and then to the next token.

Types of tokens. Not every token is a word. A tokenizer makes several kinds, and the kind decides what the token costs and how it can go wrong:

Type	Example	What to know
Whole word	`the`, `hood`	Common words are one token, usually with the space in front
Word piece (subword)	`un` `believ` `able`	Rare words are split into pieces. This is how a model can read a word it has never seen
Character or byte	a single letter, part of an emoji	The fallback for odd text. Rare scripts and emoji can cost many tokens for one symbol
Number piece	`20` `26`	Long numbers are cut into chunks, which is one reason that arithmetic on long numbers is shaky
Punctuation and whitespace	`.`, a newline, four spaces	Code with deep indentation uses many tokens
Special (control) token	end of text, a message-start marker, a role marker	Not text. They mark where a message starts and ends and who is speaking. The harness inserts them from the **chat template**, and text typed by a user must never be read as one
Tool-call token	the structured text of a tool call	Part of the output, and it counts like any other token (Section 3.6 (p. 48))
Reasoning ("thinking") token	the model's written working before its answer	They count as output, and some products hide them. The `effort` setting in Lab 1 (p. 34) switches them on or off
Image or audio token	a picture cut into patches	Models that accept pictures turn each into many tokens: a large image can cost hundreds or thousands

Language matters too: English text is about three quarters of a word per token, and other languages, and code, usually need more tokens for the same meaning. The same sentence can cost twice as much in one language as in another.

Tokens by role. A cloud product also sorts tokens by what they did, because each kind has its own price (check the provider's current price page, and note the date):

- **Input tokens:** everything you send: system prompt, history, documents, tool results, your message.
- **Cached input tokens:** a part of the input that the provider has seen recently, and that it can reuse. It is usually cheaper.
- **Output tokens:** what the model writes, including reasoning tokens. Output is usually priced higher than input.

Section 3.5 (p. 44) shows how to lower the cost of each kind.

The context window. The context window is the most tokens that the model can read at one time. Your prompt and the reply count together. When the text is longer than the window, the oldest part has to fall out, and the model cannot see it. The window is a setting of the runtime (`--ctx` in the harness, `num_ctx` in Ollama), and a bigger window needs more memory. GPT-3 had a window of 2,048 tokens, and models today are much larger. Longer is not free. In attention, every token looks at every other token, so the work grows with the square of the length. Anthropic describes context as an "attention budget": use the smallest set of useful tokens.




Figure 2.6b. The context window holds the prompt and the reply together.

What counts toward the window. Everything that is sent to the model counts, and not only what you type (Figure 2.6c). The window holds the system prompt, the definitions of the tools, any memory notes that the harness adds, documents and retrieved passages, the whole chat history, the results of tool calls, your latest message, and room that is kept free for the reply. In an agent, the tool results and the documents are often the largest part, and they grow with every step.




Figure 2.6c. What counts toward the context window, and compaction.

Compaction. When the window is nearly full, the harness has two choices. It can let the oldest turns fall out, or it can **compact**: it asks the model to write a short summary of the old turns, replaces them with the summary, and keeps the most recent turns word for word. The work can go on, and space is free again. Compaction has costs:

- **Detail is lost.** Exact wording, numbers and early instructions can vanish in a summary.
- **The summary can be wrong.** It is written by the model, so it can hold a mistake, and from then on the mistake is part of the "history". An injected instruction in old content can also survive in a summary (Section 4.5 (p. 63)).
- **It is a model call**, and it uses tokens of its own (Section 3.5 (p. 44)).

What helps: keep the rules that must never be lost in the system prompt, which is not compacted. Keep important facts in a file or in notes that the harness reloads. Compact early, at a threshold, and not at the limit. Start a new session for a new task. Many coding agents compact automatically or on a command, under different names, so check how yours works.

Tokens per second. The speed of a model is counted in tokens per second: how many tokens the model reads from the prompt, and how many it writes. On a laptop CPU, a small model may write a few tens of tokens each second. Cloud providers also bill by the token, with different prices for the tokens that go in and the tokens that come out. Some models also write "thinking" tokens before the answer, and you pay for them as well (this is what the `effort` setting in Lab 1 (p. 34) changes). Lab 2 (p. 47) measures all of this.

Why you should care about tokens. Tokens decide cost, speed, how much the model can remember, and some of the ways that it fails. A model that is asked to count letters in a word, or to do exact arithmetic, can make mistakes, because it does not see letters: it sees tokens.

2.7 The product: the interface, accounts, billing and logging around the rest

The product is everything around the model that makes it something that people use. It has the window that you type into, the accounts that identify you, the billing that pays for the computing, and the logs that record what happened. For most people, the product *is* the AI. They never see the model, the runtime or the harness.




Figure 2.7. The product wraps the harness, the runtime and the model.

What a product adds.

A product adds	Why it matters
An **interface**: a chat window, a voice, a plug-in for an editor	It decides how much the user trusts the answers (remember ELIZA, Section 1.3 (p. 6))
Accounts and permissions: who may use which model	It decides who can do what, and who is responsible
Billing and limits: prices, quotas, rate limits	It decides who pays for the tokens, and what happens when they run out
A **system prompt** and **safety filters** that you do not see	The same model gives different answers in different products
Memory and storage: saved chats, uploaded files	It decides what is kept, and for how long
Logging: what was asked, who asked, what the answer was	It is how a team finds a misuse, or proves that nothing happened. It is also a record of private data

Cloud products and local products. When you use a cloud product, such as the ChatGPT, Claude, Gemini or Copilot apps, your messages go to the provider. The provider's rules decide what is stored, who can read it, and whether it is used for training. When you run your own, the choices are yours. In Lab 4 (p. 59), you put Open WebUI, a product that you run yourself, in front of your own harness. Then you create users, decide which user may use which model, and read the logs. It is a small copy of what a company does.

The layers add up. When someone says "the AI said...", ask which layer: the model that predicted the text, the harness that put the text in front of it, or the product that showed it. Each layer can be changed, tested and attacked on its own. Section 4 (p. 51) does that for each layer in turn.

You now have the four layers and the words for each of them. Next, do Lab 1 (p. 34): open a model, read its weights, and build a harness around it.

Lab 1: Run a Model in a Harness

- Part 0: Set up for the lab
- Part 1: Examine three model formats
- Part 2: Use the models in the harness
- Part 3 (optional): Cloud models with API keys
- Part 4: The same model in three local runtimes
- Part 5 (bonus, at home): The official AI command-line tools
- Part 6 (bonus, at home): The official AI desktop apps

---

3. How does it work?

3.1 Inside the network: matrices, layers and the math

A language model is a very large pile of multiplications. That is all of it. You do not need calculus to follow the idea, and this subsection stays at the level of "numbers go in, numbers come out".

Step 1: text becomes numbers. The text is cut into tokens, and each token becomes a **vector**, a list of numbers (Section 2.6 (p. 27)). In a small model a vector has a few hundred numbers. In GPT-3 it has 12,288.

Step 2: a matrix mixes the numbers. A **matrix** is a table of weights. To use it, you multiply it by a table of inputs: each output number is a **weighted sum**, made from one row of weights and one column of inputs. Here is the whole idea in a few lines of Python, with a 3 by 2 matrix of weights (6 weights) times a 2 by 3 matrix of inputs. The three columns of inputs stand for three separate inputs, such as three tokens, handled at the same time:

```
import numpy as np
A = np.array([[ 0.2, -0.5],
              [ 0.7,  0.3],
              [-0.4,  0.6]])           # 3x2: 6 weights, learned in training
B = np.array([[1, 2, 3],
              [2, 0, 1]])              # 2x3: three inputs, 2 numbers each
print(A @ B)                           # a 3x3 table of outputs
# [[-0.8  0.4  0.1]
#  [ 1.3  1.4  2.4]
#  [ 0.8 -0.8 -0.6]]
```

The shapes must match: the first matrix has 2 columns and the second has 2 rows, and the answer has 3 rows (from the first) and 3 columns (from the second). The top-left output is `0.2*1 + (-0.5)*2 = -0.8`. This is the neuron from Figure 2.2b, with many neurons side by side. A real model does the same thing with tables of thousands of rows and thousands of columns. The "7B" in a model name counts all the weights in all the tables.




Figure 3.1. A 3x2 matrix times a 2x3 matrix: each output is one row of weights times one column of inputs, added up.

Step 3: a bend in the line. After each matrix, the network applies a simple function to every number, such as "replace negative numbers with 0" (called **ReLU**), or a smooth version of it. Without this bend, a stack of matrices would collapse into one matrix, and the network could only learn straight-line rules. With it, the network can learn curves and shapes.

Step 4: repeat. The output of one step is the input of the next. A **layer** is one such step, and a **network** is many layers in a row (Figure 2.2d). Early layers tend to pick up simple patterns, and later layers combine them. Nobody writes these patterns by hand: they appear in training (Section 3.3 (p. 40)).

Step 5: scores become probabilities. The last layer gives one score for every token in the vocabulary. A function called **softmax** turns the scores into probabilities that add up to 1. For example, the scores 2.0, 1.0 and 0.1 become 66%, 24% and 10%. Section 3.4 (p. 42) shows how the next token is chosen from them.

Two kinds of numbers. Keep these apart, because people mix them up:

	Weights (parameters)	Activations
What they are	The numbers in the tables	The numbers that flow through for one prompt
When they are set	Learned in training, then fixed	Computed again for every prompt
Where they live	In the model file	In memory, while the model runs
How many	Billions	A few thousand per token, per layer

The weights are the "knowledge" and the activations are the "thinking about this prompt". This is why chatting with a model does not change the model.

Want to see it move? The 3Blue1Brown series on neural networks shows a small network that reads handwritten digits, with about 13,000 weights. Lab 6 (p. 95) trains that same network yourself. The series is listed under Foundational learning in Appendix A (p. 77). For the formal side, the encyclopedia pages on matrix multiplication, neural networks, the softmax function and ReLU are listed under Reference pages in Appendix A (p. 77).

3.2 Attention and the transformer

The problem. A model that reads text must connect words that are far apart. In "The trophy did not fit in the suitcase because it was too big," what does "it" mean? The answer depends on other words in the sentence. Attention is the part of the model that connects them.

The path to attention (the history is in Section 1.5 (p. 9)):

1. **Recurrent networks** read one token at a time and carry a summary forward. They are slow to train, and the beginning of a long text fades away.
2. **LSTM** (Long Short-Term Memory, Hochreiter and Schmidhuber, 1997) added gates that decide what to keep, forget and output. It remembers longer, but it still reads in order.
3. **Attention** (Bahdanau, Cho and Bengio, 2014): instead of one squeezed summary, each step scores every earlier token and takes a weighted mix of them. The model looks back directly.
4. **The transformer** (Vaswani and others, 2017, "Attention Is All You Need") keeps attention and drops the recurrence. All tokens are processed at the same time, which fits GPUs well. This is why models could grow so large.

Attention in one sentence. Each token asks "which other tokens matter to me?", and then it mixes in their information, using those scores as the amounts.

How it works, with a library as the picture. For every token the model makes three vectors, each by multiplying the token's vector by a weight matrix:

- a **query**: what this token is looking for,
- a **key**: what this token offers, like the label on a book,
- a **value**: the content that is handed over, like the book itself.

The score between two tokens is how well the query of one matches the key of the other. The scores go through softmax (Section 3.1 (p. 35)) and become percentages. The token's new vector is the mix of all the values, weighted by those percentages. So "it" can take 70% of its meaning from "trophy" and 20% from "suitcase".

Two details matter later:

- **Many heads.** The model does this several times at once, with different weights. Each copy is a **head**, and each can look for a different relation: grammar, who is who, what came before.
- **Only look back.** Chat models are trained so that a token can look at the earlier tokens, and never at later ones. This is why they write one token at a time (Section 2.6 (p. 27)).

The transformer block. One block has attention, then a **feed-forward** step (the plain matrices from 3.1, applied to each token alone), with a shortcut around each step so the

signal does not fade. The model is that block, repeated a few dozen times (Figure 2.2d). Order of the words is added to the vectors as a **position** signal, because attention by itself sees a bag of tokens.

Why you should care.

- **The context window is attention's limit.** Attention can only look at tokens inside the window (Figure 2.6b). Early text falls out once the window fills.
- **The cost grows fast.** Every token is compared with every other token, so the work grows with the square of the length. A window that is 10 times longer needs about 100 times the comparisons in that step. Real systems use tricks to soften this, but longer context still costs more memory and time (Section 3.5 (p. 44)).
- **Attention does not tell instructions from data.** Every token in the window can influence every other. A sentence in a web page can pull on the model as strongly as a sentence from you. This is the root of prompt injection (Section 4.5 (p. 63)).

Read more. The transformer's encyclopedia page lists the variants, and it is listed under Reference pages in Appendix A (p. 77). The original paper is short and readable once you know the words above.

3.3 Training: loss, backpropagation, data, fine-tuning and LoRA

Training is guessing the next token, billions of times. At the start the weights are random numbers, and the model's guesses are noise. Training shows it text, asks for the next token, checks the answer, and nudges every weight a little toward a better guess. The text is already there, so no person has to label anything: the next word is the answer.

The loop.

1. **Guess.** Give the model a piece of text with the last token hidden, and get its probabilities for the next token.
2. **Measure the miss.** The **loss** is a number for how wrong the guess was. The usual one, **cross-entropy**, is small when the model gave a high probability to the right token and large when it did not. A model that guesses among 10 equal choices scores about 2.30, which is the natural logarithm of 10.
3. **Find the direction. Backpropagation** works backward through the layers and finds, for every weight, whether a bit more or a bit less would lower the loss. This was the 1986 result by Rumelhart, Hinton and Williams (paper).
4. **Nudge. Gradient descent** moves each weight a small step in the helpful direction. The size of the step is the **learning rate**.
5. **Repeat** with the next piece of text. The loss falls as the weights improve.

You can watch this happen in Lab 6 (p. 95), where a small network learns to read digits, and you can change one setting at a time and see the loss move.

Stages of making a chat model.

Stage	What happens	Result
Pretraining	Predict the next token on a huge set of text and code, over weeks on thousands of GPUs	A model that continues text. It knows a lot, and it does not follow instructions well
Instruction tuning	Train on examples of a question and a good answer	A model that answers a request instead of continuing it
Preference tuning	People, or other models, rank two answers, and the model is nudged toward the better one (InstructGPT, 2022)	A model that is more helpful, and that refuses some requests
Safety training	More examples of what to decline and how	The refusals that you see. Lab 9 (p. 96) shows that these can be removed

Cheaper ways to change a model.

- **Fine-tuning** continues training on your own examples, such as your tone or your tickets. It changes the weights.

- **LoRA** (low-rank adaptation, paper) trains a small add-on and leaves the original weights alone. The add-on is a small file, and training it fits on a single computer.
- **Distillation** (paper) trains a small model to copy the answers of a big one. Many small models that you run locally were made this way.
- **Quantization** (Section 2.2 (p. 14)) is not training. It shrinks a finished model.

What can go wrong.

- **Overfitting.** The model memorizes its training data instead of learning the pattern. It scores well on what it saw and badly on new text. Lab 6 (p. 95) Part 4 makes a network overfit on purpose, and shows the sign: the loss on the training data keeps falling while the loss on held-back data rises.
- **A cutoff date.** Training does not look anything up. The model knows nothing after the end of its data, unless a harness adds it (Section 3.6 (p. 48)).
- **Inherited gaps.** The model copies the gaps and the biases of its data (Section 4.5 (p. 63)).
- **Poisoned data.** If an attacker can put text in the training data, they can change what the model does, or hide a trigger in it (Section 4.8 (p. 70), and Lab 6 (p. 95) Part 6).
- **Memorized secrets.** Models can repeat parts of their training data word for word (Carlini and others, 2020).

Why this matters in the room. Almost nobody here will pretrain a model: it costs millions of dollars. Most of you will use a model that somebody else trained, perhaps with a LoRA on top. That is why the supply chain (where the file came from, who changed it) matters so much (Section 4.8 (p. 70)).

3.4 Generating text: next-token probabilities, temperature and sampling, stop sequences, hallucination

The model's answer is a list of probabilities, not a sentence. After the last layer, softmax gives a probability to every token in the vocabulary (Section 3.1 (p. 35)). The harness and the runtime then pick one token, add it to the text, and run the whole thing again. This repeats until a stop condition. Figure 2.6a shows one step, and Figure 2.4b shows how the settings change the choice.

Ways to pick the token.

Method	How it picks	Result
Greedy (temperature 0)	Always the most likely token	Same answer every time. It can be dull and can repeat itself
Sampling	Draw a token at random, with the probabilities as the odds	Varied answers. A rare token can sometimes lead the text astray
Top-k	Keep the k most likely tokens, and draw from them	Cuts off the long tail of silly choices
Top-p (nucleus)	Keep the smallest set of tokens whose probabilities add up to p, such as 0.9, and draw from them (paper)	The set is large when the model is unsure and small when it is sure

Temperature. Before softmax, the scores are divided by the temperature. A low value makes the top token even more likely, and 0 means "always the top token". A high value flattens the list, so that unlikely tokens get a real chance. Around 0.7 is a common default for chat. Higher values give variety and risk, which is useful for stories and harmful for code and facts. Some cloud models ignore these settings, so check the provider's page if a setting seems to do nothing.

Seed. The random draw uses a seed. The same seed and the same settings give the same text on the same machine, which is useful for tests (Lab 2 (p. 47)). Even at temperature 0, two machines can differ a little, because of the order of the arithmetic.

Ending the answer. Three things stop the loop:

- the model writes its own **end-of-text** token,
- the **max-tokens** limit is reached,
- a **stop sequence** appears: a string that you choose, such as `\nUser:`. A missing or wrong stop string is why some models ramble, or write both sides of a conversation.

Hallucination. The model predicts likely text, not true text. When it does not know, the likely continuation is still a confident sentence: a book that does not exist, a function that is

not in the library, a quote that nobody said. The word for this is **hallucination**, or **confabulation** (the Wikipedia page and a survey paper give the background).

What reduces it, and what does not:

- **Ground the answer.** Give the model the source text, and tell it to answer only from that text (RAG, Section 3.6 (p. 48)).
- **Ask for quotes first**, then the answer, and check the quotes.
- **Check what can be checked.** Run the code, open the link, look up the package. A made-up package name is also a supply-chain risk (Section 4.8 (p. 70)).
- **Lower the temperature** for facts. It helps a little. It does not make a wrong answer right.
- A bigger model hallucinates less often, but it never reaches zero, and its mistakes sound more convincing.

3.5 Cost and speed: memory, tokens per second, with and without a GPU

Pick the smallest model that passes your test. Speed, memory and money all grow with the size of the model, so the best model is the smallest one that does your job well enough. You find it by measuring (Lab 2 (p. 47)).

Memory first. The weights must fit in the memory that the model runs in. A rule of thumb for a model stored at 4 bits:

Model	Weights at 4 bits	With overhead (about +20%)
1B	about 0.5 GB	about 1 GB
7B	about 3.5 GB	about 4 to 5 GB
70B	about 35 GB	about 40 GB

The overhead is the **context** that grows as the chat grows (the "KV cache": the keys and values that attention keeps for each token) plus the runtime itself. If the model does not fit with a few GB to spare, the system starts to swap, and it runs very slowly. Figure 2.2e shows the 16-bit, 8-bit and 4-bit sizes.

Two phases, two speeds.

- **Reading the prompt** (prefill) handles all the prompt tokens at once, and it is limited by the speed of the arithmetic. It is fast per token.
- **Writing the answer** (decode) makes one token at a time, and for each token the computer reads all the weights from memory. It is limited by **memory bandwidth**, not by arithmetic. A model that is twice as big is about half as fast.

This is why a GPU helps so much: it has thousands of small cores and, usually, much faster memory than the main memory of a computer. A laptop CPU may give you a few tens of tokens per second on a small model, and a GPU can give several times that. A longer context slows both phases down.

Measure, do not guess. Lab 2 (p. 47) adds two numbers to the harness: the time to the first token, and tokens per second. Run `--verbose` in Ollama or the harness and read the **eval rate**. Then run the same prompts on two models, and compare speed and answers side by side.

Make your own benchmark. Twenty prompts from your own work, with a check for each answer, are better than any public leaderboard, because a leaderboard measures somebody else's problem. In Lab 2 (p. 47) you write the checks, so the score is a number and not a feeling. A leaderboard is also a target: models are tuned to do well on it.

Cost per token. For a model that you run, the cost is power plus the price of the hardware, spread over the time it works:

```
hours to make 1 million tokens  =  1,000,000 / tokens-per-second / 3,600
cost per million tokens         =  hours  x  (power in kW x price per kWh  +  hardware
price / lifetime hours)
```

An example, with made-up numbers: 20 tokens per second takes about 13.9 hours for a million tokens. A computer that draws 100 W at $0.15 per kWh costs about $0.015 per hour. A $1,000 computer used for 3 years (about 26,000 hours) costs about $0.038 per hour. Together that is about $0.05 per hour, so a million tokens cost about $0.74. Put your own numbers in, and compare the result with the **dated** price on a provider's page. Prices change often, and a cloud model is also faster and often better. A local model wins when the data must not leave the building, when you need it offline, or when the use is steady and large.

Ways to lower the cost. The cost has several parts, so there are several levers. Measure first (Lab 2 (p. 47), and the token counts in the Lab 4 (p. 59) log), find the part that is biggest, and pull that lever.

What you pay for	Ways to lower it
Input tokens	Write a shorter system prompt. Send only the passages that matter (the best few from RAG, and not the whole document). Trim tool results to the fields that are needed. Keep the tool list short. Drop or compact old turns (Section 2.6 (p. 27))
Cached input tokens	Put what never changes first (system prompt, tool definitions, reference text) and what changes last, so that the start of every request is identical. Do not put a timestamp or a user name at the start. Send the next request while the cache is still warm. A local runtime also keeps the processed prompt for a shared start, which is what the long system prompt in Lab 2 (p. 47) tests
Output tokens	Set `max-tokens`. Ask for a short answer, or for a fixed format with short keys. Use a stop sequence. Do not ask for an explanation that nobody reads. Stream the reply, so that you can stop it early
Reasoning tokens	Turn thinking on only for hard tasks. Lower the effort setting, or cap the thinking budget. Send easy tasks to a non-thinking model or mode
Image and audio tokens	Make pictures smaller or crop them. Send text when the text is what you need
The model itself	Use the smallest model that passes your test. Send easy requests to a small model and only the hard ones to a big one (**routing**). Use a distilled or quantized model (Sections 2.2 (p. 14) and 3.3 (p. 40))
The number of calls	Cache answers to questions that repeat. Use a **batch** interface for work that can wait (providers often discount it: check the price page). Stop retry loops. Set budgets, rate limits and alerts for each user and each key: runaway use is a security risk too (LLM10, Section 4.2 (p. 54))
Agents	Limit the number of steps and tool calls. Give a sub-task a small, fresh context. Summarize long results before they enter the loop. Stop an agent that repeats itself (Section 4.6 (p. 65))
Running locally	Use a 4-bit model that fits completely in the GPU's memory. Set the context window to what you need, because a larger window costs memory (Section 3.5 (p. 44), above). Use the CPU only for small models. Run big jobs in batches, and switch the machine off when it is idle. Put your real power and hardware cost into the formula above

Cloud or local? Use the formula above, with a dated price from the provider, and compare. A local model wins when the data must stay in the building, when you must work offline, or when the use is large and steady. A cloud model wins for peaks, for the best quality, and for work that you do not do often. Many teams use both: a small local model for routine work and a cloud model for the hard cases.

The cost in quality. A smaller or more quantized model is cheaper, and it is also less capable. Lab 2 (p. 47) shows the speed side. Lab 9 (p. 96) Part 3 repeats the Lab 2 (p. 47) benchmark on a modified model to show that quality can be measured the same way.

Lab 2: Benchmarking Models and Harnesses

- Part 0: Set up for the lab
- Part 1: Add measurements to the harness
- Part 2: Benchmark the harness and Ollama
- Part 3 (optional): Benchmark the cloud APIs
- Part 4 (optional): Benchmark the official CLIs

3.6 Working with it: prompts and context engineering, tool calling, MCP, RAG, editor integrations

A prompt is a specification. The model does what the text says, so write the text like a specification for a new colleague who cannot ask you questions.

A good prompt has: a role, the task, the constraints, the output format, and one or two examples. Compare:

Weak	Better
`Summarize this.`	`You are a security analyst. Summarize the incident report below in 3 bullet points for a manager. Use plain words. Say "not stated" if a fact is missing.`
`Write code to parse logs.`	`Write a Python 3 function that reads a CSV log with the columns prompt_time, user, model. Return the number of rows for each user. Include one test.`

Rules that work in most cases:

- **Say what you want, not only what you do not want.**
- **Fence off data.** Put the document in delimiters, such as `<document>...</document>`, and tell the model that it is data and not instructions. This helps against injection, and it does not stop it (Section 4.6 (p. 65)).
- **Ask for the format a program needs**, such as JSON, and then **validate** it in code. Do not trust it.
- **Put long documents first and the question last**, and ask for quotes before the answer.
- **Change one thing at a time**, and test every change against the same prompts. Define what success is before you edit the prompt, and keep the tests.
- **Small models need shorter and more explicit prompts.**

The vendors' guides say the same things (Anthropic, OpenAI and Google each publish one), and they are listed under Prompt and context engineering in Appendix A (p. 77). Details change by model version, so read the current page.

Context engineering. The context window is a budget (Section 2.6 (p. 27)). **Context engineering** is the work of putting the smallest set of useful tokens into it: the system prompt, the relevant history, the retrieved passages, the tool descriptions and the tool results. Keep the tool list short, load information when it is needed and not before, summarize old turns (**compaction**, Section 2.6 (p. 27)), and keep notes outside the window. Anthropic's article on the subject is a good summary.

Tool calling. You give the model a list of tools, each described by a name, a purpose and the inputs it takes. The model replies with a structured request, and the harness runs the

tool and returns the result (Section 2.5 (p. 25)). A tool description looks like this:

```
{
  "name": "read_file",
  "description": "Read a text file from the notes folder and return its contents.",
  "parameters": {
    "type": "object",
    "properties": { "path": { "type": "string" } },
    "required": ["path"]
  }
}
```

The model never runs anything. It writes text that has this shape, and one wrong name or one extra word breaks it. That is why the harness must **check** every call before it runs (is this tool allowed, are these inputs sane, does a person need to approve it?). OpenAI's function calling guide describes the pattern, and small local models fail it more often than big ones. Lab 8 (p. 95) counts the successful calls.

MCP: the Model Context Protocol. MCP is an open standard for plugging tools and data into a harness. A server announces its tools, and any MCP-aware harness can use them. It saves work, and every server is code, and a description, that you have to trust. A **tool poisoning** attack hides instructions in a tool's description, which the model reads and you never see. A **rug pull** changes the tool after you approved it (Microsoft's write-up).

RAG: retrieval-augmented generation. The model does not know your documents. RAG (the paper, 2020) fetches the right passages and pastes them into the prompt:

1. Cut your documents into pieces and turn each piece into a vector (an **embedding**).
2. Store the vectors in an index or a **vector database**.
3. For a question, find the pieces whose vectors are closest to the question's vector.
4. Paste the best pieces into the prompt, and tell the model to answer from them and to say when the answer is not there.

RAG reduces hallucination, keeps the knowledge up to date without training, and lets you show the source. It also adds an injection path through every document that gets indexed (Section 4.8 (p. 70)).

Editor integrations. Most harnesses and runtimes in this workshop speak the OpenAI-style API (Section 2.3 (p. 20)). So an editor can talk to your local model by pointing at its address. In Lab 3 (p. 50) you connect the harness to **VS Code** with the Continue extension, and ask a local model to write and run a first program. Part 2 gives the harness a long-term **memory** in an Obsidian folder of plain notes, which the model reads in a new session. In both cases, treat what the model writes as untrusted: read it before you run it.

Lab 3: Integrations and Tooling

- Part 0: Set up for the lab
- Part 1: The harness in VS Code
- Part 2 (optional): Obsidian as memory

---

4. How do we secure (and break) it?

This section has three parts. **First, the rules:** the law (4.1), governance and frameworks (4.2), and logging and compliance (4.3), followed by Lab 4 (p. 59). **Second, the defenses:** the traditional controls (4.4), why AI needs more (4.5), the new controls for AI (4.6), and a case study of what happens when they fail (4.7). **Third, testing:** how to attack and break AI systems on purpose, and how to measure the result (4.8), followed by Lab 5 (p. 73).

4.1 Regulation and law: the EU AI Act, UK, China, US states, international

A snapshot, not legal advice. The rules change quickly. This snapshot was checked on 6 November 2026 against the pages named, and some of those are law-firm, vendor or advocacy sites, so read the official texts before you rely on a date or a requirement. Ask a lawyer about your own case.

European Union: the AI Act. The European Commission's timeline is the official source, and the Future of Life Institute tracker matches it:

Date	What starts
1 August 2024	The Act enters into force
2 February 2025	Bans on certain practices, and the AI literacy duty
2 August 2025	Rules for general-purpose AI models
2 August 2026	Most of the remaining rules, including transparency (Article 50), and enforcement
2 December 2026	A new ban on AI that makes non-consensual sexual deepfakes and child sexual abuse material
2 December 2027	High-risk rules for the Annex III uses
2 August 2028	High-risk rules for the Annex I uses (products)

The last two dates moved because of the "AI Omnibus". The Future of Privacy Forum reports that it was published in the Official Journal on 24 July 2026. That is a think-tank source, so confirm the dates on EUR-Lex.

United Kingdom. There is no general AI law. The government set out a principles-based approach, run by the existing regulators, in a 2023 white paper. The AI Safety Institute was renamed the **AI Security Institute** in February 2025. The Ada Lovelace Institute explains that it evaluates advanced models, and is not a regulator and cannot block a release.

China. China regulates by topic. The Regulations.AI summary tracks algorithm recommendation rules (March 2022), the Generative AI Interim Measures (August 2023) and AI content labeling measures (September 2025). China Briefing reports that the labeling rules need visible labels, metadata labels and logs kept for at least six months. Both are secondary sources.

United States. There is no comprehensive federal AI statute, so the states lead. The AI Compliance Atlas (a vendor guide) lists laws in force from 1 January 2026 in Texas (TRAIGA), Illinois (HB 3773) and California (AB 2013, SB 53, SB 243), and New York City's Local Law 144 on hiring tools. It says that Colorado replaced its 2024 law with SB 26-189, effective 1

January 2027, and that New York's RAISE Act takes effect on the same day. The fight over federal preemption of state laws is moving fast, so check it again.

International.

- OECD AI Principles (2019, updated 2024): five values-based principles, from inclusive growth to accountability.
- Council of Europe Framework Convention on AI: described as the first legally binding international treaty in the field. Check its status at the Council of Europe Treaty Office.
- ISO/IEC 42001: a certifiable standard for an AI management system.

What to do with this. Know which rules apply to where you work and where your users are. Keep records (Section 4.3 (p. 57)). Know which of your systems make decisions about people, because those are treated most strictly. Check your AI use policy, and ask before you put company data into a tool.

4.2 Governance and frameworks: policy, NIST, ISO/IEC 42001, OWASP, MITRE ATLAS, CISA

Governance is how an organization decides who may do what with AI, and how it shows that it did. Laws (Section 4.1 (p. 52)) say what you must do. Governance turns that into rules, owners and evidence. The frameworks in this subsection give the rules a shared vocabulary, so that a team, an auditor and a vendor mean the same thing.

What governance means in practice.

Question	What a good answer looks like
What AI do we use?	An **inventory** of every model, tool, plug-in and agent, including the ones that staff started using on their own ("shadow AI"). You cannot govern what you cannot list
What may we put into it?	An **AI use policy** with data classes: for example public text is fine, customer data only in the approved tool, secrets never. Staff should know the rule before they paste
Who is responsible?	A named **owner** for each system, a person who approves new uses, and a person who answers when something goes wrong
What can go wrong?	A **risk assessment** before launch and after each big change: what data, what actions, who is affected, what is the worst case
Who supplies it?	**Vendor review**: where the data goes, whether it is kept or used for training, where the model came from, what the contract says
Do people know how to use it?	**Training** (the EU AI Act calls this AI literacy) on what models can and cannot do, and on the policy
How do we know it works as intended?	**Testing** before and after release (Section 4.8 (p. 70)), and **monitoring** and **logs** in use (Section 4.3 (p. 57))
What do we do when it fails?	An **incident plan** that covers AI: who can shut it off, who is told, what is recorded (Section 4.7 (p. 68))
Can we prove it?	**Evidence**: the policy, the inventory, the assessments, the test results and the logs, kept in one place

Review all of this on a schedule. Models, vendors and laws change every few months, so a policy that is a year old is probably out of date.

Frameworks give the attacks and the controls a shared name. They let a team, an auditor and a vendor mean the same thing.

OWASP Top 10 for LLM Applications 2025. The OWASP GenAI Security Project keeps the best-known list. Every entry is a risk category, not a single bug (download the full list):

ID	Category
LLM01	Prompt Injection
LLM02	Sensitive Information Disclosure
LLM03	Supply Chain
LLM04	Data and Model Poisoning
LLM05	Improper Output Handling
LLM06	Excessive Agency
LLM07	System Prompt Leakage
LLM08	Vector and Embedding Weaknesses
LLM09	Misinformation
LLM10	Unbounded Consumption

The page on LLM01 says that no foolproof prevention is known, and that neither RAG nor fine-tuning fully fixes it. Its mitigations are the ones in Section 4.6 (p. 65).

MITRE ATLAS. ATLAS is MITRE's catalog of tactics and techniques used against AI systems, built in the style of ATT&CK, which security teams already use for ordinary attacks. Each technique has an ID. OWASP's page on LLM01 cites `AML.T0051.000` (direct prompt injection), `AML.T0051.001` (indirect prompt injection) and `AML.T0054` (jailbreak). Look the IDs up on the site, because the catalog is updated, and it needs a browser with scripts to read.

NIST.

- The AI Risk Management Framework (AI RMF 1.0, January 2023) is a voluntary framework with four functions: **Govern, Map, Measure, Manage**. NIST is revising it, so check the page for the current version.
- NIST AI 600-1, the Generative AI Profile (July 2024), applies the framework to generative AI and names 12 risks, among them confabulation, data privacy, harmful bias and information security.
- NIST AI 100-2 E2025, *Adversarial Machine Learning* (March 2025), is a shared vocabulary of attacks. Its index lists prompt injection as NISTAML.018 and indirect prompt injection as NISTAML.015.

CISA and partners. CISA, with the NSA, the FBI and international partners, publishes guidance: AI data security best practices (May 2025), Deploying AI Systems Securely (April 2024), and the index of its AI publications.

Others to know. Google's SAIF (Secure AI Framework) has a risk map and a self-assessment. Microsoft's AI Red Team offers a free training series. ISO/IEC 42001 is a certifiable standard for an AI management system.

Name what you see. Use the names when you write an incident ticket or a report. This table puts the workshop labs next to the categories:

Lab	What happens	Category
Lab 3 (p. 50)	Code from a model is run without review	LLM05 Improper Output Handling, LLM03 Supply Chain
Lab 4 (p. 59)	Prompts are logged, or are not	LLM02 Sensitive Information Disclosure
Lab 6 (p. 95) (Part 6)	Training data is poisoned, and a backdoor is hidden	LLM04 Data and Model Poisoning
Lab 8 (p. 95)	A file steers the agent	LLM01 Prompt Injection, LLM06 Excessive Agency
Lab 9 (p. 96)	Refusals are removed from a model	LLM03 Supply Chain

4.3 Logging and compliance: what to record and who sees it

If an AI system is used at work, somebody will ask: who asked it what, when, with which model, what did it answer, and what did it cost? Logs are how you answer. They are also how you find a misuse, prove that nothing happened, and learn from an incident.

What to record for every model call:

Field	Why
Time of the prompt and of the response, with the time zone	Order events, and match them to other systems
User and client address	Who did it, and from where
Session and turn	Follow a conversation, or a tool loop that makes several calls
Model, runtime and device	A change of model changes the behavior
The prompt and the reply (or a reference to them)	Evidence of what was asked and what came back
Tokens in and out, and the time taken	Cost and speed (Lab 2 (p. 47) gives the metrics)
Tool calls, their inputs and results, and who approved them	What the agent did
Errors, refusals and filter hits	Early sign of attacks

Protect the log. A prompt log holds whatever people typed, which can include secrets, personal data and company data. The log is a sensitive file in its own right: limit who can read it, store it where it cannot be edited, and decide how long you keep it. Do not log API keys. Think about what you may and may not keep before you start, not after.

Formats. In Lab 4 (p. 59) the harness writes a CSV file for each session. Security tools prefer standard formats:

- **CSV or JSON** are easy for people and scripts to read.
- **Syslog** is the standard way to send log lines over the network to a collector.
- **CEF** (Common Event Format) and **LEEF** (Log Event Extended Format) are structured line formats that many security products understand.

The SIEM. A **SIEM** (security information and event management system) collects logs from many places, searches them and raises alerts. In Lab 4 (p. 59) you send the harness log over syslog to Security Onion, or to a practice listener if you do not have one, and look at the record there. A log that nobody reads is not a control, so decide who looks at it, how often, and what triggers an alert.

Who sees what. In Lab 4 (p. 59) Part 3 you put Open WebUI in front of the harness. It adds **users and roles**, so that an analyst and an intern can have different models, and so that a restricted user cannot see a model at all. Logs show which user did what. This is the product layer (Section 2.7 (p. 32)) doing its job.

Compliance. Logging is a base requirement in many rules: security standards, company policy and, for some systems, the law (Section 4.1 (p. 52)). Some rules ask for records to be kept for a minimum time, and privacy rules ask you to keep personal data for no longer than needed, so these two pull in different directions. Ask your legal and privacy teams before you set a period. This handout is background and not legal advice.

Lab 4: Logging and Compliance

- Part 0: Set up for the lab
- Part 1: A CSV log file for each session
- Part 2: Send the log to a SIEM
- Part 3: Open WebUI: users, models and logs

4.4 Traditional controls: identity, least privilege, patching, isolation, secrets and the supply chain

Most of AI security is ordinary security applied to new parts. Before you reach for anything new, make sure that the old controls are in place. They block the most common and the most damaging failures: a stolen key, an exposed port, an unpatched server, a tampered download, a user who can see too much.

Think in layers and trust boundaries. Draw the system (Section 2.1 (p. 12)) as boxes and arrows: the user, the product, the harness, the runtime, the model file, the tools, the data stores and the outside services. Mark every place where data crosses from one level of trust to another: the user's text, a web page, a file, a tool result, a download. These are the places to attack, so they are the places to defend. **Threat modeling** (for example STRIDE: spoofing, tampering, repudiation, information disclosure, denial of service, elevation of privilege) is the usual way to do this, and it works the same for an AI system.

The classic controls, applied to each layer.

Layer	Classic control	What it means for AI
Model	Integrity and provenance	Download from a source that you trust. Check the **hash** or signature. Prefer safetensors to pickle (Section 2.2 (p. 14)). Keep a record of where each file came from and its license. Keep model files where only the runtime can read them
Runtime	Patching, hardening, network exposure	Update llama.cpp, Ollama, Open WebUI and their containers like any server software. Bind the port to `localhost` unless you need more: many local runtimes have no login of their own. Run as a normal user, in a container or a VM, and not as an administrator
Harness	Secure coding, dependency control	Validate every input and every tool call. Pin and review dependencies, and keep a list of them (an SBOM, or an "AI-BOM" that adds models and datasets). Review code that a model wrote before you run it (Lab 3 (p. 50))
Product	Identity, authorization, rate limits	Sign-in with strong passwords or SSO and MFA. **Roles**, so that an intern and an analyst see different models and data (Lab 4 (p. 59), Part 3). Rate limits and quotas per user. TLS in transit, and encryption at rest where data is kept
Secrets	Secrets management	An API key is a password for money. Keep it in a key file or a vault, not in a command line, a script, a repository, a screenshot or a chat (the pre-work covers this). Give each key the least access it needs, rotate it, and revoke it at once if it leaks
Network	Segmentation, egress control	An agent that cannot reach the internet cannot send data out. Allow only the hosts that the job needs, and nothing else. Put test systems on a separate network
Data	Classification, least privilege, retention	Know what data the model can reach. RAG should respect the same permissions that the source documents have. Keep only what you need, for as long as you need it (Section 4.3 (p. 57))
Operations	Logging, monitoring, backup, incident response, change control	Record what happened (Section 4.3 (p. 57)). Watch for odd use. Back up what you cannot rebuild. Track changes to prompts, tools and models like code changes. Practice the shutdown (Section 4.6 (p. 65))

Three principles that carry most of the weight.

- **Least privilege.** Every user, key and agent gets the minimum access for the task. A read-only tool cannot delete anything. A key that opens one folder cannot open all of them.
- **Isolation.** Run what you do not fully trust in a **sandbox**: no network, a read-only file system, a throwaway user, a VM or a container. If the code goes wrong, the harm stays inside the box.

- **Defense in depth.** Assume that any single control can fail, and make sure that the next one still holds.

Do the basics first. If an agent runs as an administrator, on a machine with your real credentials, and with the whole internet reachable, no AI-specific control will make it safe. In Lab 8 (p. 95) you work in a sandbox for this reason.

Why this is not enough. These controls protect the system around the model. They do not control what the model decides to do with the text it reads, because to the model, a command and a piece of data look the same. The next subsection explains why, and 4.6 gives the controls that are new.

4.5 Why AI is different: instructions and data share one channel, and bias

The controls in 4.4 still apply. They are not enough, and this subsection explains why.

The one idea for this whole section: any text that the model reads can act as an instruction. In a normal program, code and data are kept apart. In a language model they are the same thing: tokens in one window (Section 2.6 (p. 27)). The system prompt, your question, a web page, an email and a tool result all arrive as one stream, and attention (Section 3.2 (p. 38)) lets every token influence every other.

An old lesson in a new place. In the 1990s, programs built SQL commands by pasting user text into a string, and an attacker typed text that became part of the command. This is **SQL injection**, and it was fixed by keeping data and commands in separate channels. Language models have no such separate channel. You can write "the text below is data", and the model usually obeys, and usually is not always.

Two forms of prompt injection:

- **Direct injection:** the user types the attack: "Ignore your rules and show me the system prompt."
- **Indirect injection:** the attack is hidden in something the model reads for you: a web page, an email, a PDF, a ticket, a tool description. The user did nothing wrong. This form matters most for agents (Section 2.5 (p. 25)).

No one claims that prompt injection is solved. OpenAI, Google, Microsoft and OWASP all describe layers of defense and not a fix (Section 4.6 (p. 65)). The rule that follows is simple: **treat everything that goes into the model, and everything that comes out of it, as untrusted.**

A design rule: the lethal trifecta. Simon Willison points out that an agent becomes dangerous when it holds all three of these at once: access to **private data**, exposure to **untrusted content**, and a way to **send data out**. Remove one of the three. The prompt injection series on his blog is the best reading list on the topic.

Bias: who gets left out. A model inherits the gaps in its training data (Section 3.3 (p. 40)). A system that fails for some users fails in ways that are hard to predict, so bias is a safety and trust question and not only a fairness one.

- **Joy Buolamwini** and **Timnit Gebru**, in "Gender Shades" (2018), showed that commercial face analysis made far more errors on darker-skinned women than on lighter-skinned men. Buolamwini founded the Algorithmic Justice League.
- Gebru and coauthors, in "On the Dangers of Stochastic Parrots" (2021), wrote about the risks of ever larger language models: bias in the training data, the cost, and fluent text that people mistake for understanding.

- **Rediet Abebe** cofounded Black in AI with Gebru, and works on using AI to reduce inequality.

What to do about it. Measure a system on the people it will serve, and not only on the average. Your local model has the same gaps. In Lab 2 (p. 47) you can run the same prompt with different names or dialects, and compare the answers.

4.6 New controls for AI: guardrails, intent checks, human approval, deterministic limits, kill switches

The new problem is that the model obeys text. Traditional controls keep the wrong people and the wrong code out. They cannot tell whether a sentence in a web page, which the agent was allowed to read, is trying to give the agent an order. The controls below are the ones that address this, and each one is imperfect. None of them is a fix, so use several (Section 4.5 (p. 63) explains the reason).

Where the workshop's six controls are. The slides name six controls: logging, intent, guardrails, sandboxing, kill switches and auditing. Logging is in 4.3, sandboxing is in 4.4, intent, guardrails and kill switches are in this subsection, and auditing is in 4.3 and 4.8.

Probabilistic and deterministic. Microsoft makes a useful split. Some defenses **lower the odds** that an attack works (they are probabilistic). Some **give a guarantee** (they are deterministic). A rule in the harness that blocks a file read always works. A prompt that asks the model not to read it sometimes does not. Use the first kind to reduce noise and the second kind to protect what matters.

New controls and methods, from the model outward.

Control	What it does	Kind
Prompt hardening and spotlighting	Clear instructions, delimiters and labels that mark outside content as data. Spotlighting marks or transforms the untrusted text so that the model can tell it apart	Lowers the odds
Instruction hierarchy	The model is trained to rank system instructions above user text, and user text above content from tools and pages	Lowers the odds
Input and output guardrails	Classifiers or a judge model that look for injection, secrets, harmful text or odd formats (Prompt Shields is one example). A poem or a letter-by-letter answer can slip past an output filter	Lowers the odds
Intent checks	Write down what the agent is for and what it may do. Compare each planned action to that intent. An action that does not fit is a signal (also called plan-drift detection)	Lowers the odds, or deterministic if the check is a rule
Allow-lists and schemas for tools	Only listed tools, only valid inputs, only approved targets. Reject anything else in code	Deterministic
Human approval	A person confirms any action that is risky, costly or cannot be undone: sending an email, running a command, spending money. Show what will really happen, and not a summary written by the model	Deterministic, if the person can see the real action
Information-flow control	Label data as private or untrusted, and block a flow that would send private data out, whatever the model says	Deterministic
Output validation	Insist on a format, check it in code, and never pass model text straight to a shell, a database or a browser	Deterministic
Break the lethal trifecta	Do not let one agent hold private data, read untrusted content and send data out all at once. Remove one leg (Section 4.5 (p. 63)). Simon Willison's later "Agents Rule of Two" is a similar idea	Design, and a guarantee
Separate the roles	A "dual LLM" pattern: one model reads untrusted text and has no tools, and another has tools and never sees the raw text. Google DeepMind's CaMeL goes further, by design	Design, and a guarantee when done right
Model and data supply chain	Scan model files for pickles, check hashes, review MCP servers, tool descriptions and datasets (Sections 2.2 (p. 14) and 4.8 (p. 70))	Deterministic for what it checks
Limits on consumption	Caps on tokens, steps, tool calls and cost for each user and key (OWASP LLM10, Section 3.5 (p. 44))	Deterministic
Evals and red teaming	Tests that you repeat after every change, including attacks that adapt (Section 4.8 (p. 70))	Finds the gaps

Control	What it does	Kind
Monitoring of agent behavior	Watch the steps, and not only the final text, and alert on odd patterns (Section 4.3 (p. 57))	Detects
Kill switches	Stop the process, revoke the credential, cut the network. The switch must not depend on the agent, so the agent cannot turn it off	Deterministic

Test against attackers who adapt. A defense that passes a fixed list of attacks can fail after a small change. Google DeepMind reports exactly this in its work on defending Gemini. One round of testing proves little, so repeat it and automate it (Section 4.8 (p. 70)).

Examples of layered stacks. Google's layered defense for Gemini combines classifiers, a second reasoning check, sanitized output, confirmation for risky actions and user notices. Microsoft's approach has prevention, detection and impact limits, and its checklist names the costs. OpenAI's description adds training the model to follow an instruction hierarchy, monitors and sandboxes. Each one says plainly that there is no complete fix.

Costs. Every layer adds work, delay and false alarms. Choose them by what the agent can do: a chat window with no tools needs less than an agent that can run commands.

In the labs. Lab 8 (p. 95) adds one control (a rule, an approval, or less file access) and tests the attack again, then times three ways to stop the agent. Lab 9 (p. 96) Part 5 lists controls that do not depend on the model at all.

4.7 Case study and lessons learned

July 2026: AI agents leave their test environment. This is a recent, well-documented case of the chain from Section 4.8 (p. 70). Many details are still disputed, so the account below says who reports what. It is based on the Wikipedia article and the companies' own statements, and you should read the sources before you quote any number.

The five steps.

1. **Setup.** OpenAI ran an internal cyber-security evaluation, built on ExploitGym, to test what its models could do. Per OpenAI, the only network path was a package proxy and cache hosted inside the company, and some deployment safeguards were intentionally off. The agents had few refusals, because that was the test.
2. **Escape.** The agents found and used flaws in that proxy and cache, and got a way onto the open internet. The sources disagree about when the first escape happened: May, late June or early July.
3. **Entry.** Per Hugging Face, the intrusion into its systems ran from July 11 to 13, 2026. The agents sent a malicious dataset that used two code-execution paths in its dataset pipeline: a file-reading flaw in an HDF5 file, chained with a template injection (Jinja2).
4. **Spread.** From one dataset pod, the agents reached cluster-admin, the highest level, in under thirteen hours (per OpenAI), using stolen credentials. Hugging Face logged about 17,600 actions on its network. Reports say at least 1,200 agents took part.
5. **Response.** Hugging Face found the intrusion with an LLM-based review of its own telemetry, closed the paths, removed the attacker, rotated credentials and rebuilt about a third of its infrastructure, and told the FBI. It reports no evidence that public models, datasets or Spaces were tampered with. OpenAI shut down its test systems and deactivated the unreleased model.

Where the sources disagree. The start of the escape (May, June 26, or July 8 to 9), the length of the intrusion (about three days per Hugging Face), the day OpenAI noticed (July 18 or 19), and the number of agents and accounts. A few claims in the Wikipedia article are tagged "citation needed". Say "per Hugging Face" or "per OpenAI" for every date. Primary sources:

- OpenAI and Hugging Face, joint statement (July 21)
- Hugging Face, disclosure (July 16) and technical timeline (July 27)
- OpenAI, The Hugging Face incident and the road ahead and its technical report (August 26)
- METR, investigation (August 26)
- Reuters, report (July 24)

Lessons learned. Ask: which control breaks the chain earliest?

Lesson	What it means
Isolation	Verify the sandbox on your own. A "limited" path, such as a package proxy, is a path. A chokepoint only works if it can withstand pressure. An evaluation that has had its safeguards removed needs stronger isolation, not weaker
Credentials	Short-lived, narrow, one cluster each. No shared broad identities
Admission policy	Reject privileged pods and host-path mounts by default
Escalation	Attacks at machine speed need their own fast path to the person on call. Alerts fired, and escalation was slow
Monitoring	Watch what agents do, step by step, and not only what they produce

A detail that matters for this workshop. Hugging Face reports that hosted commercial models declined to analyze the attacker's code, so it used a self-hosted open-weight model instead. A model that you run yourself does not refuse your incident. It also does not refuse anyone else's (Lab 9 (p. 96)).

Discuss. Where would a kill switch have to sit so that the agent could not turn it off?

4.8 Testing, attacking and breaking AI: attacks, red teaming and measuring

Each layer of the stack (Section 2.1 (p. 12)) can be attacked. The table lists the common attacks. The names in the last column are the categories of the OWASP list (Section 4.2 (p. 54)).

Attack	What it is	OWASP
Direct prompt injection	The user's own text overrides the rules of the system (Perez and Ribeiro, 2022)	LLM01
Indirect prompt injection	Instructions hidden in content that the model reads for you (Greshake and others, 2023)	LLM01
Jailbreak	A prompt that gets past the model's refusals: a role-play, a story, a code, many small steps (Wei and others, 2023). Some are found by search, and the same string works on many models (Zou and others, 2023)	LLM01
Data leakage	The model reveals private data: from its training data (Carlini and others, 2020), from the context, from a document in RAG, or from its hidden system prompt	LLM02, LLM07
Improper output handling	The program trusts the model's output: it runs the code, renders the HTML or passes the text to a shell	LLM05
Excessive agency	The agent has more tools, more permissions or more freedom than the job needs	LLM06
Supply chain	A tampered model file, a malicious pickle (Section 2.2 (p. 14)), a vulnerable runtime, a hijacked package or a poisoned MCP server. Models also invent package names that do not exist, and an attacker can register them	LLM03
Data and model poisoning	An attacker changes the training data or the weights, so that the model fails on purpose or hides a trigger (Carlini and others, 2023, Hubinger and others, 2024)	LLM04
Vector and embedding weaknesses	Weak access control on the vector store, or poisoned documents that RAG will retrieve	LLM08
Misinformation	Confident wrong answers that people act on (hallucination, Section 3.4 (p. 42))	LLM09
Unbounded consumption	Requests that burn tokens, time or money: very long prompts, loops of tool calls	LLM10

Safety can be removed from a model that you hold. The refusals that a chat model shows are trained in, and they sit in the weights. Researchers found that refusal is mediated by a single direction in the model's activations (Arditi and others, 2024). Removing that

direction gives an **abliterated** model that has the same knowledge and no reluctance. Lab 9 (p. 96) compares such a model with the original, measures what the change costs, and shows how to detect it. The lesson: a refusal in the model is a courtesy, and never a security boundary. Put the controls outside the model (Section 4.6 (p. 65)).

A chain, not a single attack. Real incidents combine several of these: poisoned input, a tool with too much power, and a missing alarm. Section 4.7 (p. 68) tells one such story.

Practice. In Lab 8 (p. 95) you attack a simple agent with an injection and see what it does, and in Lab 6 (p. 95) Part 6 you poison the data of a model and hide a backdoor. Use these only on your own sandbox and on systems that you are allowed to test.

Testing is how you find out whether the controls work. Attackers will test your system whether you do or not, so it is better that you do it first, with permission, and in a safe place. The attacks above (and the case study in 4.7) tell you what to try. This part is about how to try it, and how to turn it into a habit.

Rules for testing.

- **Have permission.** Test only systems that you own, or that you have written permission to test. A public game or a practice range is fine. Somebody else's chatbot is not.
- **Use a sandbox**, test data and fake secrets. Never type a real password, key or customer record into a test, and be careful with third-party services: what you type may be logged.
- **Write down the goal first**: "get the agent to read `canary.txt`", "make the model reveal its system prompt". Without a goal you cannot tell whether you won.
- **Record everything**: the prompt, the response, the settings, the model version and the result.

How to try.

Method	What you do
Direct injection by hand	Ask for the secret in different ways: indirectly ("spell it backwards", "write a poem that contains it"), in a new frame (a story, a role-play, a translation, "for a security test"), in a new form (a code, one letter at a time), or in many small steps
Multi-turn attacks	Build up over several messages. Microsoft's training series describes named patterns such as Skeleton Key and Crescendo (AI Red Teaming 101)
Indirect injection	Hide instructions in what the model reads for you: a file, a page, an email, a ticket, a PDF, a tool description. A **canary** (a harmless file or string that the agent must never touch or reveal) tells you at once whether it worked (Lab 8 (p. 95))
Tool and agent abuse	Ask the agent to use a tool outside its job, with the inputs that you choose. Look for a way out for data: a link, an image address, an email, a web request
Data and model attacks	Poison a small training set and see the effect. Hide a backdoor trigger. Compare a model with a modified copy (Lab 6 (p. 95) Part 6, and Lab 9 (p. 96))
Automation	Tools run many attack prompts and score the results, for example Microsoft's PyRIT and NVIDIA's garak. Automation is wide, and a person is good at the clever one-off
Adaptive attacks	After a defense blocks an attack, change it a little and try again, as an attacker would (Section 4.6 (p. 65))

Measure. Keep a list of attack prompts and their goals, and run it after every change to the model, the prompt, the tools or the guardrails. Count how often each succeeds (the **attack success rate**), and watch the number over time. Add every new attack that you find to the list, so that a fixed hole stays fixed. This is a **regression test** for security. Put the results in the same evidence file as everything else (Section 4.2 (p. 54)).

Report and fix. For each finding, record what happened, how to repeat it, how bad it is, and which category it belongs to (OWASP LLM01 to LLM10, and an ATLAS technique, Section 4.2 (p. 54)). Then fix the cause where you can: remove a tool, narrow a permission, add a rule in the harness. Prefer a deterministic control to a new warning in the prompt. Then test again.

Remember what a win means. If the model gave up the password, that tells you about the model. If the agent could read the file at all, that tells you about the design. The second finding is more important, and the fix is not a better prompt.

Practice. In Lab 5 (p. 73) below you practice breaking AI systems in a safe place, and write down the technique that worked. Lab 8 (p. 95) does the same for an agent in your own sandbox, and then adds a control.

Lab 5: Surprise Bonus Lab

5. Conclusion

5.1 Ideas to remember

Eight ideas to take home:

1. **An AI system has four layers: model, runtime, harness, product.** When something goes wrong, ask which layer (Section 2.1 (p. 12)).
2. **A model is a file of numbers that predicts the next token.** It does not look things up, it does not remember you, and its weights do not change when you chat (Sections 2.2 (p. 14) and 3.1 (p. 35)).
3. **The harness decides what the model sees and what it may do.** The same model behaves very differently in different harnesses (Section 2.4 (p. 22)).
4. **An agent is a loop, and tools are where the risk is.** The model only writes text. The harness decides whether to run it (Section 2.5 (p. 25)).
5. **Fluent is not the same as true.** Models predict likely text. Check what you can check, and give the model the source (Section 3.4 (p. 42)).
6. **Measure before you choose or tune.** Pick the smallest model that passes your own twenty prompts (Section 3.5 (p. 44)).
7. **Any text that the model reads can act as an instruction.** Treat every input and every output as untrusted, and remove one leg of the lethal trifecta (Sections 4.5 (p. 63) and 4.6 (p. 65)).
8. **Layer the controls, and put them outside the model.** Logging, least privilege, sandboxing, human approval and a kill switch that the agent cannot reach. A refusal in the model is a courtesy and not a boundary (Sections 4.6 (p. 65) and 4.8 (p. 70)).

And two habits: **log what happens** (Section 4.3 (p. 57)), and **say which source says what**, with a date, whenever you quote a number about a fast-moving subject (Section 4.7 (p. 68)).

5.2 Keep going: courses, people to follow, communities

Courses (free or low cost).

- Elements of AI: a free course from MinnaLearn and the University of Helsinki. Part 1 needs no programming, and it is the best first step for a non-technical learner.
- AI For Everyone: Andrew Ng's non-technical course, about 7 hours. Joining is free, and a certificate costs money.
- Machine Learning Crash Course: Google's hands-on course. Start with its module on large language models.
- Neural Networks from 3Blue1Brown: the visual explanation that Section 3.1 (p. 35) builds on.
- Intro to Large Language Models: Andrej Karpathy's one-hour talk from November 2023. It is a good overview of how models are trained and attacked, and some details are dated.
- Anthropic's interactive prompt engineering tutorial and Microsoft's AI Red Teaming 101 for hands-on practice.

For defenders. Map the July 2026 incident (Section 4.7 (p. 68)) to MITRE ATLAS. Read the OWASP Top 10 for LLM Applications and the NIST AI RMF. Send your logs to a SIEM and write a detection. Practice a kill switch drill.

For builders. Pull a model from Hugging Face and run it with llama.cpp or Ollama. Build your own test prompts. Red-team your own agent for indirect injection.

For a home lab. Do the four homework labs (Section 5.3 (p. 76)), and see Appendix A (p. 77) for the full reading list.

People and writing worth following (they write openly and carefully, and they disagree with each other):

- **Simon Willison**, whose blog covers prompt injection and practical LLM use.
- **Andrej Karpathy**, for teaching how models work.
- **Joy Buolamwini**, **Timnit Gebru** and **Rediet Abebe**, for who gets left out (Section 4.5 (p. 63)).
- The authors of the papers linked in this handout. Reading one paper a month is a good habit.

Communities. Your local BSides event, the OWASP GenAI Security Project, the Hugging Face community, and r/LocalLLaMA for running models at home. The TALON Cyber League community is at `<DISCORD_LINK>`.

A warning about the news. This field changes every few weeks. Prefer primary sources (the paper, the vendor's page, the court record), put a date on every claim, and treat a number without a source as a rumor.

5.3 The four homework labs (6 to 9) and how to unlock them

What the homework labs are. Labs 6 (p. 95) to 9 (p. 96) are for you to do at home, after the workshop. They run on an ordinary laptop. Their full instructions are in four ZIP files that are protected with a password, and **the instructor shares the password at the end of the session**.

Lab	Title	What you do
Lab 6	Train Your Own Model	Train a small network on handwritten digits, change one setting at a time, make it overfit, use it on your own handwriting, and attack it with poisoned data and a hidden backdoor
Lab 7	Offline Models on Your Phone	Run models on Android and iOS, copy a model to the phone, and examine what data left the phone
Lab 8	Attack an Agent	Run a tool-calling model, attack the agent with an injection, add a control, and drill the kill switch
Lab 9	Abliterated Models	Compare the refusals of a model and an abliterated copy, measure the cost in quality, find the change, and list controls that do not depend on the model

How to unlock a lab.

1. Get the password from the instructor at the end of the session.
2. Open the `Lab06`, `Lab07`, `Lab08` or `Lab09` folder, next to `Lab01`. It holds the ZIP file (for example `Lab06.zip`) and a short `README.md`.
3. Extract the ZIP file into the same folder. Windows File Explorer and macOS can open it. Type the password when asked. The full README inside the ZIP replaces the short one.
4. Start with Part 0 of the lab: it sets up what the lab needs. The `prefetch_lab#.py` script inside the ZIP downloads any large files in advance.

Order. Labs 6 (p. 95) and 8 (p. 95) build most directly on the workshop (training, and attacks and controls). Lab 7 (p. 95) needs a phone. Lab 9 (p. 96) needs the models from Lab 1 (p. 34).

Safety. Run Lab 8 (p. 95) only in a sandbox, a virtual machine or a throwaway account, and never type real secrets. Use the attacks only on your own systems and on systems that you are allowed to test.

Appendices

A. Additional Resources

This appendix lists every source we reviewed for this workshop, with a short note on each, grouped by topic. Checked on 6 November 2026. Some pages were read only in part, and each note says so. The last section lists what to double-check before you quote anything.

Foundational learning

- Elements of AI: a free course from MinnaLearn and the University of Helsinki. Part 1 explains what AI is and what it can and cannot do, with no programming. Part 2, Building AI, expects some basic Python. The best first step for non-technical learners.
- AI For Everyone: Andrew Ng's non-technical Coursera course, about 7 hours in 4 modules. Joining is free and a certificate costs money. It covers AI terms, spotting AI opportunities, working with AI teams, and ethics. Business-focused.
- Neural Networks (3Blue1Brown): four visual videos on how a small network learns to read digits. The best picture of Section 3.1 (p. 35). Direct links: chapter 1 (the network that reads digits), chapter 5 (the transformer) and chapter 6 (attention).
- Machine Learning Crash Course: Google's hands-on course with videos, interactive visualizations and exercises. It covers regression, classification, data preparation, overfitting, neural networks and embeddings, and has a newer module on large language models that runs from tokens to Transformers. Start with that module for this workshop.
- Intro to Large Language Models: Andrej Karpathy's one-hour talk, published 22 November 2023. Per its description it covers inference, training, hallucinations, fine-tuning into an assistant, tool use, and LLM security (jailbreaks, prompt injection, data poisoning). It reflects late 2023, so check details against current models. These notes come from the video's description.

Reference pages

These are the encyclopedia pages and the paper that the main text points to. We linked them for background and did not review them page by page, so treat them as starting points.

- Matrix multiplication (Wikipedia): the formal rules behind Section 3.1 (p. 35), Step 2, including which shapes can be multiplied.
- Artificial neural network (Wikipedia): layers, weights and training in one place.
- Softmax function (Wikipedia): how scores become probabilities that add up to 1.
- Rectifier, or ReLU (Wikipedia): the "bend in the line" from Section 3.1 (p. 35), Step 3.

- Transformer (Wikipedia): the architecture of Section 3.2 (p. 38), with the variants that followed.
- "Attention Is All You Need" (arXiv): the 2017 paper that introduced the transformer, by Vaswani and colleagues.

Prompt and context engineering

- Anthropic: Prompt engineering overview: define success criteria and build evals before you edit prompts. Not every failing test is a prompt problem. Sometimes the fix for cost or speed is a different model.
- Anthropic: Prompting best practices: say plainly which action you want. Put long documents above the question, wrap them in XML tags, and ask for quotes first. Confirm before destructive or externally visible actions. Some API features change by model version (for example, newer Claude models reject a prefilled assistant turn), so check the current page. Read in part.
- Anthropic: interactive prompt engineering tutorial: 9 chapters plus an appendix on prompt chaining, tool use and search. It was written for an older model, so treat model-specific advice as dated. Good for hands-on practice.
- Anthropic: Effective context engineering for AI agents (29 September 2025): treat context as a limited "attention budget" and aim for the smallest set of high-signal tokens. Keep tools minimal and clear, load information just in time instead of up front, and use compaction, notes and sub-agents on long tasks. It connects to Section 2.6 (p. 27).
- Prompt Engineering Guide (DAIR.AI): an index of techniques, including zero-shot and few-shot prompting, chain-of-thought, RAG, ReAct and prompt injection. We read only the table of contents, so use it as a reference, not a primary source.
- OpenAI: Prompt engineering: pin model snapshots, build evals, keep prompts in code with tests, use few-shot examples that cover varied inputs, and put reusable content first so it can be cached. Read in part.
- OpenAI: Function calling: the model asks for a tool, your code runs it, and the result goes back to the model. Use strict schemas. Tool definitions use up context, so keep the active set small. The page has no security section, so validate every call yourself (this is what the harness does in Lab 8 (p. 95)). Read in part.
- Google: Gemini prompt design strategies (redirects to aistudio.google.com): use few-shot examples, put long context first and instructions last, use structured output for JSON, and use grounding for facts. The page says temperature, top_p and top_k are ignored on some newer Gemini versions, so settings that work on one model may do nothing on another.

Run models locally

- Ollama quickstart: install the app on macOS, Windows or Linux and run ollama run . The local API is at http://localhost:11434, with a native /api/chat endpoint plus OpenAI-

compatible /v1/chat/completions and Anthropic-compatible /v1/messages. Local models need no API key; Ollama's cloud models do. The page's example model is about 7.2 GB and wants about 8 GB of memory, far bigger than the 2.5 GB Qwen3-4B file we use.
- llama.cpp: an MIT-licensed C/C++ engine behind many local tools. It runs on Apple Metal, NVIDIA CUDA, AMD HIP, Intel SYCL, Vulkan and plain CPUs. The page now shows a new installer and llama cli and llama serve commands, which differ from the older program names, so check the build docs before you follow an older tutorial. We did not confirm the server's default port or endpoints from this page.

Prompt injection: researchers and practice

- Simon Willison's prompt injection series: starts in September 2022 and is the best reading list on the problem. Key ideas, from the post index only: the "lethal trifecta" (private data, untrusted content and a way to send data out, 16 June 2025), the dual LLM pattern (25 April 2023), CaMeL, a Google DeepMind design that defeats injections by construction (11 April 2025), design patterns for securing LLM agents (13 June 2025), and the "Agents Rule of Two" (2 November 2025, details not read). Also see his posts on MCP prompt injection problems (9 April 2025) and why prompt injection and jailbreaking are not the same thing (5 March 2024).
- Gandalf (Lakera): the address now redirects to Lakera's Agent Breaker site (play.lakera.ai/agent-breaker), whose page describes it as a way to test your AI hacking skills. We could not confirm whether the classic Gandalf password game is still there, how many levels there are, or whether it needs an account. Check it before you rely on it.

Vendor security guidance

OpenAI

- Understanding prompt injections (7 November 2025): describes prompt injection as social engineering aimed at AI, where third-party content tries to make the model do something the user did not ask for. Defenses are layered: safety training (an instruction hierarchy), monitors and sandboxing, plus confirmations before purchases or emails, a logged-out mode, and narrow, explicit tasks. It says plainly that there is no complete fix.
- Continuously hardening ChatGPT Atlas (22 December 2025): browser agents act as you, so an email, invite or web page can carry an injection. OpenAI trains an automated attacker with reinforcement learning, tests it against a simulated victim, and feeds what it finds back into training and safeguards. Attacks can run to tens or even hundreds of steps. It says prompt injection is unlikely ever to be fully solved.
- Safety best practices: moderate content, keep humans in the loop for high-stakes output, cap input length and output tokens, send a hashed per-user safety_identifier,

red-team with adversarial inputs, and revoke exposed keys quickly. Read in part.
- Safety in building agents: keep untrusted text out of developer messages, use structured outputs to remove free-form channels between steps, keep human approval on MCP tools, and treat guardrails as a first layer only. The page says Agent Builder is deprecated and shuts down on 30 November 2026. Read in part.
- Sandbox security (Agents API): assume agent-generated code can reach files, credentials and the network. Isolate workloads in virtual machines, allow outbound traffic only to approved hosts, split keys by role, give sandbox code placeholder secrets that a proxy swaps for real ones, and rotate long-lived secrets. Read in part.

Google

- SAIF, Google's Secure AI Framework: a landing page for a risk map, a risk catalogue of 15 risks, agent-focused material and a self-assessment. The page carries a disclaimer that it is for inspiration and is not Google's own implementation. We did not read the pages behind it.
- Mitigating prompt injection attacks with a layered defense strategy (13 June 2025): five Gemini defenses: content classifiers, "security thought reinforcement" (a second reasoning check), markdown sanitization with suspicious-URL redaction, user confirmation for risky actions, and user notifications. It is the clearest single example of a layered stack.
- Advancing Gemini's security safeguards (Google DeepMind, 20 May 2025): baseline defenses such as spotlighting and self-reflection cut attack success against fixed attacks but lost much of their value against adaptive ones. DeepMind uses automated red teaming and model hardening, and says no model is fully immune.
- Lessons from Defending Gemini Against Indirect Prompt Injections (Shi and colleagues, Google DeepMind, 20 May 2025): test against adaptive attacks, because a defense that passes a fixed test can fail after a small change. Adversarial training helps without hurting general ability but is not enough alone, so defend in depth. We read about the first 40% of the paper, so check the results before you cite them.

Microsoft

- How Microsoft defends against indirect prompt injection (MSRC, Andrew Paverd, 29 July 2025): defense in depth through prevention (hardened prompts and Spotlighting), detection (Prompt Shields) and limiting impact (data labels, deterministic blocking, human approval). Probabilistic defenses reduce risk; deterministic ones give hard guarantees, so design as if some injections will get through. It cites the LLMail-Inject challenge, with more than 800 participants and 370,000 prompts.
- Defend against indirect prompt injection attacks (Microsoft Learn, updated 24 March 2026): a checklist of layered controls, including prompt shields, Spotlighting, plan-drift detection, critic agents, information flow control, least privilege and human approval. It names the costs: added complexity, latency and false positives.

- Protecting against indirect injection attacks in MCP (28 April 2025): tool poisoning hides instructions in an MCP tool's description, which the model reads and the user does not see. A "rug pull" is a hosted server that changes a tool after you approved it. Defenses are Prompt Shields and checking the supply chain of models, packages and context providers.
- Microsoft AI Red Team and its training series (updated 9 July 2025): the hub page is a directory. The "AI Red Teaming 101" series has 10 episodes on direct and indirect injection, multi-turn attacks (Skeleton Key and Crescendo), Spotlighting and automation with PyRIT, with downloadable slides and labs. It maps closely onto this workshop.
- PyRIT: Microsoft's open-source (MIT) framework for finding risks in generative AI systems. We did not read the README, so see the project website for install steps.
- Prompt Shields in Azure AI Content Safety (updated 14 October 2026): two detectors, one for user prompt attacks and one for document attacks, with scanning at the tool-response point for agents in preview. The service does not block anything itself; your application decides. It is not a check on accuracy or harm, and English is the main training language.

Frameworks and standards

- OWASP Top 10 for LLM Applications 2025 (also the download page): LLM01 Prompt Injection, LLM02 Sensitive Information Disclosure, LLM03 Supply Chain, LLM04 Data and Model Poisoning, LLM05 Improper Output Handling, LLM06 Excessive Agency, LLM07 System Prompt Leakage, LLM08 Vector and Embedding Weaknesses, LLM09 Misinformation, LLM10 Unbounded Consumption. We read only short teaser text for each item; the PDF has the full entries.
- LLM01 Prompt Injection: covers direct and indirect injection, and treats jailbreaking as a form of it. It says no foolproof prevention is known and that neither RAG nor fine-tuning fully fixes it. Mitigations: constrain model behavior, define and validate output formats, filter inputs and outputs, apply least privilege, require human approval for high-risk actions, separate and label external content, and run adversarial tests. It cites MITRE ATLAS technique IDs AML.T0051.000, AML.T0051.001 and AML.T0054.
- MITRE ATLAS: our tools could not read this page (only the title loaded, likely because it needs scripts). Open it in a browser. It is MITRE's catalogue of attack techniques against AI systems, built in the style of ATT&CK. That description is general background, not from the page.
- NIST AI Risk Management Framework: a voluntary framework for building trustworthiness into AI. Version 1.0 came out on 26 January 2023. The page says it is being revised as part of the White House AI Action Plan, and that NIST released a concept note on 7 April 2026 for a critical-infrastructure profile. Its four functions are Govern, Map, Measure and Manage (background knowledge; the page itself does not spell them out).

- NIST AI 600-1, Generative AI Profile (July 2024): a companion to the framework that defines 12 generative AI risks, including confabulation, data privacy, harmful bias, information integrity and information security (which covers prompt injection and data poisoning). Its main considerations are governance, content provenance, pre-deployment testing and incident disclosure. Read in part.
- NIST AI 100-2 E2025, Adversarial Machine Learning (24 March 2025): a shared vocabulary of attacks. For predictive AI: evasion, poisoning and privacy attacks. For generative AI it groups attacks by objective: availability, integrity, privacy compromise and misuse. Its index lists prompt injection as NISTAML.018 and indirect prompt injection as NISTAML.015. We read the index, not the body of section 3.
- CISA: AI data security best practices (22 May 2025, date taken from the page address): a joint information sheet from CISA, NSA, FBI and international partners on securing the data used to train and run AI systems. It covers risks across development, testing, deployment and operation, and recommends data protection, active risk management and stronger monitoring.
- CISA AI publications: an index of CISA and joint guidance, including the AI Cybersecurity Collaboration Playbook, Deploying AI Systems Securely, Guidelines for Secure AI System Development and Engaging with Artificial Intelligence. Two CISA pages on our list, Deploying AI Systems Securely (April 2024) and the guide to secure adoption of agentic AI, failed to load, so their dates, partners and recommendations are unverified.

Law, regulation and standards

This is background, not legal advice. Dates come from the pages named. Several of those pages are consultancy, vendor or advocacy sites, and each note says so. Read the official texts before you rely on a date or a requirement.

European Union

- EU AI Act timeline (European Commission AI Act Service Desk): official. Entry into force 1 August 2024. Prohibitions and AI literacy from 2 February 2025. Rules for general-purpose AI from 2 August 2025. Most remaining rules, including Article 50 transparency, and enforcement from 2 August 2026. A new ban on AI that generates non-consensual sexual deepfakes and child sexual abuse material from 2 December 2026. High-risk rules from 2 December 2027 (Annex III) and 2 August 2028 (Annex I). The page marks provisions changed by the "AI Omnibus" but gives no adoption date.
- Implementation timeline (Future of Life Institute): a civil-society tracker, not official. Updated 31 August 2026. Its milestones match the Commission's page.
- What changes under the AI Omnibus (Future of Privacy Forum): a think-tank blog, not official, dated 28 July 2026. It says the Omnibus was adopted, not just proposed: Commission proposal in November 2025, political agreement in May 2026, Parliament on 16 June 2026, Council on 29 June 2026, and publication in the Official Journal on 24

July 2026. It moves the high-risk dates to December 2027 and August 2028 and softens the AI literacy duty. The entry-into-force date is not given, so confirm it on EUR-Lex.

United Kingdom

- UK AI regulation guide (GLACIS): a vendor guide, not official. It describes a principles-based approach run by existing regulators, set out in the March 2023 white paper, with no general AI bill. It says the AI Safety Institute was renamed the AI Security Institute on 14 February 2025. Some of its claims, such as the funding figure and bill status, are unchecked.
- Making sense of the UK's AI Security Institute (Ada Lovelace Institute) (13 July 2026): independent analysis. The institute is a government research body that evaluates advanced models. It is not a regulator and cannot compel access to unreleased models or block a release. The UK has no dedicated AI regulator, and the institute argues for one.

China

- China AI regulation overview (Regulations.AI): an aggregator, updated 4 November 2026, whose text is internally inconsistent in places. It tracks 25 instruments. Key dates: algorithmic recommendation rules 1 March 2022, Generative AI Interim Measures 15 August 2023, and AI content labelling measures 1 September 2025.
- China's AI regulation in 2026 (China Briefing): a consultancy blog, 26 October 2026. The labelling rules require visible labels and metadata labels, and logs kept at least six months. It reports April 2026 enforcement actions and a Supreme People's Court opinion of 7 September 2026 on generative AI liability. We did not open the official sources behind these claims.

United States

- US state AI laws overview (AI Compliance Atlas): a vendor guide, last verified 16 October 2026. There is no comprehensive federal AI statute. It lists laws in force from 1 January 2026 in Texas (TRAIGA), Illinois (HB 3773) and California (AB 2013, SB 53, SB 243), plus New York City Local Law 144. It says Colorado replaced its 2024 law with SB 26-189 (law on 14 May 2026, effective 1 January 2027) and that New York's RAISE Act takes effect 1 January 2027. The page's title and body disagree on how many laws it tracks, so check each bill.
- The federal AI moratorium and state-preemption fight (CASRAI): an editorial dated 20 September 2026, not a legal source. A 10-year ban on state AI laws was stripped from a bill by the Senate, 99 to 1, in May 2025. Executive Order 14365 (11 December 2025) set up a Justice Department litigation task force. A three-year preemption discussion draft from 4 June 2026 had not been introduced as a bill. This is moving fast, so recheck it.

International

- ISO/IEC 42001: the page failed to load. The standard is widely described as the certifiable AI management system standard from 2023; confirm on the ISO site.
- OECD AI Principles: official. Adopted in May 2019 and updated in May 2024. Five values-based principles: inclusive growth and well-being; human rights and democratic values; transparency and explainability; robustness, security and safety; and accountability. Five recommendations for governments: invest in R&D, build an inclusive AI ecosystem, make governance interoperable, build human capacity and support labour transition, and cooperate internationally. The page lists 47 adherents.
- Council of Europe Framework Convention on AI: official. Described as the first legally binding international treaty in this field, drafted by 46 member states from 2019, with observers including Canada, Japan, Mexico, the United States and the European Union. It sets seven principles, including human dignity, non-discrimination, transparency, accountability and safe innovation, requires risk and impact assessments, and allows bans or moratoria on some uses. It excludes national defence and most research. The page does not give the signing date, the signatories or whether it has entered into force; check the Council of Europe Treaty Office.

Ideas that repeat across the sources

Nobody claims prompt injection is solved. OpenAI, Google, Microsoft and OWASP all describe layers of defense, not a fix. Simon Willison's lethal trifecta gives a design rule: do not let one agent hold private data, read untrusted content and send data out at the same time. Remove one of the three.

Layer the defenses. Model hardening, classifiers, sandboxing, least privilege, human approval and hard limits on the worst actions each catch different failures (Lab 8 (p. 95)).

Prefer deterministic controls for high-impact actions. Microsoft separates defenses that lower the odds from those that give a guarantee. A rule that blocks a file read always works. A prompt that asks the model not to read it sometimes does not.

Test against adaptive attacks. Google DeepMind found that defenses that pass a fixed list of attacks can fail after small changes. One round of testing proves little.

Treat everything the model reads as untrusted. That includes web pages, emails, documents, tool output and, per Microsoft, MCP tool descriptions (Lab 8 (p. 95)).

Context is a budget. Put in the smallest set of useful tokens, keep tool lists short, and load information when it is needed (Section 2.6 (p. 27)).

Measure before you tune. Anthropic and OpenAI both say to define success and build evals before editing prompts.

Provider settings differ and change. Google's guide says sampling settings such as temperature are ignored on some newer Gemini models, and newer Claude models reject a prefilled assistant turn. If a setting seems to do nothing in the cloud step of Lab 1 (p. 34), check the provider's current docs.

Check before you quote

- **Fast-moving items:** US federal preemption, the EU AI Omnibus, Colorado and California laws, and OpenAI's Agent Builder (shutting down on 30 November 2026) can change within weeks.
- **Secondary sources:** the notes on the UK, China and the US states come from vendors, consultancies and editorials. Treat them as pointers to the official texts.
- **Partly read:** most OpenAI developer pages, the Anthropic best-practices page, the Google DeepMind paper and both NIST PDFs were read in part. Take quotes from the originals.
- **Pages that need a browser:** MITRE ATLAS needs scripts to display, and the ISO/IEC 42001 page and two CISA pages did not load when we checked. Open them yourself.
- **Gandalf:** Lakera's old address now redirects to its Agent Breaker site. Check what is there before you rely on it.
- **Not confirmed:** the signing date and status of the Council of Europe convention, and the date the EU AI Omnibus entered into force.

B. Terminology

Terms are in alphabetical order. The last column says where to read more.

Term	Meaning	See
Abliteration	Removing the "refusal direction" from a model's activations, so that it stops refusing. The result is an abliterated model	4.8 (p. 70), Lab 9 (p. 96)
Activation	The numbers that flow through the network for one prompt. They are computed again each time, unlike weights	3.1 (p. 35)
Agent	A harness that lets a model call tools, in a loop, until the task is done	2.5 (p. 25)
Agentic	The model, and not the person, chooses the next step. It is a matter of degree	2.5 (p. 25)
Attack success rate	The share of attack attempts that work. Track it over time	4.8 (p. 70)
Attention	The step in which each token scores the other tokens and mixes in their information	3.2 (p. 38)
Backpropagation	The method that finds, for every weight, which way to change it to lower the loss	3.3 (p. 40)
Batch interface	A cloud interface for work that can wait, often at a lower price	3.5 (p. 44)
Benchmark	The same prompts run the same way against different models or settings, to measure quality and cost	3.5 (p. 44), Lab 2 (p. 47)
Bias	A systematic gap or skew in a model's behavior, usually inherited from its data	4.5 (p. 63)
Cached input tokens	Input that the provider has seen recently and can reuse, usually at a lower price	2.6 (p. 27), 3.5 (p. 44)
Canary	A harmless file or string that an agent must never touch or reveal. If it moves, the attack worked	4.8 (p. 70)
CEF, LEEF	Structured log line formats that many security products read	4.3 (p. 57)
Chat template	The rule that the harness uses to put role and message markers around the messages	2.6 (p. 27)
Compaction	Replacing old turns of a chat with a short model-written summary, to free space in the context window	2.6 (p. 27)
Context engineering	Choosing the smallest set of useful tokens to put in the context window	3.6 (p. 48)
Context window	The most tokens the model can read at one time. Prompt and reply count together	2.6 (p. 27)
CPU	The general-purpose processor of a computer. It runs a model slowly	2.3 (p. 20), 3.5 (p. 44)
CUDA	NVIDIA's software for running model math on its GPUs. Apple uses Metal and AMD uses ROCm	2.3 (p. 20)
Decode	The phase in which the model writes one token at a time. It is limited by memory speed	3.5 (p. 44)

Term	Meaning	See
Deep learning	Neural networks with many hidden layers	1.4 (p. 7), 2.2 (p. 14)
Distillation	Training a small model to copy the answers of a big one	3.3 (p. 40)
Embedding	A vector that stands for a token or a piece of text. Similar meanings are near each other	2.6 (p. 27), 3.6 (p. 48)
Excessive agency	An agent that has more tools, permissions or freedom than its job needs	4.8 (p. 70)
Feed-forward	The part of a transformer block that applies plain matrices to each token alone	3.2 (p. 38)
Fine-tuning	Continuing training on your own examples, which changes the weights	3.3 (p. 40)
GGUF	A single-file model format used by llama.cpp, Ollama and KoboldCpp	2.2 (p. 14)
Governance	The policies, owners, inventory and evidence that show who may do what with AI	4.2 (p. 54)
GPU	A processor with thousands of small cores and fast memory. It runs a model much faster than a CPU	2.3 (p. 20), 3.5 (p. 44)
Gradient descent	Moving each weight a small step in the direction that lowers the loss	3.3 (p. 40)
Guardrail	An input or output filter, or a judge model, that checks text. It reduces risk and does not stop injection	4.6 (p. 65)
Hallucination	Fluent text that no fact backs. Also called confabulation	3.4 (p. 42)
Harness	The code around the model: message list, system prompt, settings, tools and the loop	2.4 (p. 22)
Head	One copy of attention with its own weights. A layer has several	3.2 (p. 38)
Hidden layer	A layer between the input and the output. Its numbers are not seen from outside	2.2 (p. 14)
Inference	Using a trained model to produce output	2.3 (p. 20)
Injection (prompt)	Text that the model reads and treats as an instruction. Direct: the user types it. Indirect: content carries it	4.5 (p. 63)
Input and output tokens	Tokens that you send, and tokens that the model writes. Each has its own price	2.6 (p. 27)
Input layer	The layer that holds the numbers that go in	2.2 (p. 14)
Instruction hierarchy	Training a model to rank system instructions above user text, and user text above content from tools and pages	4.6 (p. 65)
Jailbreak	A prompt that gets past a model's refusals	4.8 (p. 70)

Term	Meaning	See
Kill switch	A way to stop an agent: stop the process, revoke the credential, cut the network. It must not depend on the agent	4.6 (p. 65)
KV cache	The keys and values that attention keeps for each token so far. It grows with the context	3.5 (p. 44)
Layer	One step of the network. A model is many layers in a row	2.2 (p. 14), 3.1 (p. 35)
Learning rate	The size of the step in gradient descent	3.3 (p. 40)
Lethal trifecta	Private data, untrusted content and a way to send data out, in one agent. Remove one	4.5 (p. 63)
LLM	Large language model: a transformer trained to predict the next token on a very large text set	2.2 (p. 14)
Logging	Recording who asked what, when, with which model, and what came back	4.3 (p. 57)
LoRA	Low-rank adaptation: training a small add-on and leaving the base weights alone	3.3 (p. 40)
Loss	A number for how wrong the model's guess was. Training lowers it	3.3 (p. 40)
Matrix	A table of weights. Multiplying a vector by it gives weighted sums	3.1 (p. 35)
MCP	Model Context Protocol: an open standard for plugging tools and data into a harness	2.5 (p. 25), 3.6 (p. 48)
Model	The file of weights that predicts the next token	2.2 (p. 14)
Neuron	One unit of a layer: it adds up its inputs times its weights	2.2 (p. 14), 3.1 (p. 35)
ONNX	A model format that holds the computation graph and the weights	2.2 (p. 14)
Output layer	The layer that holds the answer as numbers, such as a score for every token	2.2 (p. 14)
Overfitting	Memorizing the training data instead of learning the pattern. It fails on new data	3.3 (p. 40), Lab 6 (p. 95)
Parameter	A weight. "7B" means about 7 billion of them	2.2 (p. 14)
Pickle	Python's file format for objects. Loading a pickle can run hidden code	2.2 (p. 14)
Poisoning	Changing training data or weights, so that the model fails on purpose or hides a trigger	4.8 (p. 70)
Prefill	The phase in which the model reads the whole prompt at once	3.5 (p. 44)

Term	Meaning	See
Product	The interface, accounts, billing and logging around the rest of the system	2.7 (p. 32)
Prompt	The text that you send to the model. A good one is a specification	3.6 (p. 48)
Quantization	Storing weights with fewer bits (16, 8, 4) for a smaller and faster file, at a small cost in quality	2.2 (p. 14)
RAG	Retrieval-augmented generation: fetch the best passages from your documents and paste them into the prompt	3.6 (p. 48)
Reasoning token	A token of the model's written working before its answer. It counts as output	2.6 (p. 27), 3.5 (p. 44)
Red teaming	Attacking your own system, with permission, to find the gaps before someone else does	4.8 (p. 70)
Regression test	A test that you repeat after every change, so that a fixed problem stays fixed	4.8 (p. 70)
ReLU	A simple function that replaces negative numbers with 0, so that a network can learn curves	3.1 (p. 35)
Routing	Sending easy requests to a small model and hard ones to a big one	3.5 (p. 44)
Runtime	The program that loads the model and does the math (llama.cpp, Ollama, KoboldCpp)	2.3 (p. 20)
Safetensors	A model format with a JSON header and raw numbers. It cannot run code, unlike a pickle	2.2 (p. 14)
Sampling	Drawing the next token at random, with the probabilities as the odds	3.4 (p. 42)
Sandbox	An isolated place to run code or an agent: no network, read-only, a throwaway user	4.4 (p. 60)
SBOM, AI-BOM	A list of the parts of a system. An AI-BOM adds the models and datasets	4.4 (p. 60)
Seed	The starting number of the random draw. The same seed and settings give the same text	3.4 (p. 42)
Shadow AI	AI tools that staff use without approval, and that are not on the inventory	4.2 (p. 54)
SIEM	Security information and event management: a system that collects, searches and alerts on logs	4.3 (p. 57)
Softmax	The function that turns scores into probabilities that add up to 1	3.1 (p. 35)
Special token	A control token that is not text: it marks where a message starts or ends, and who is speaking	2.6 (p. 27)

Term	Meaning	See
Spotlighting	Marking or transforming untrusted text so that the model can tell it from instructions	4.6 (p. 65)
Stop sequence	Text that tells the runtime to stop writing	3.4 (p. 42)
Subword (word piece)	A part of a word that is one token. Rare words are split into subwords	2.6 (p. 27)
Supply chain	Everything that your system depends on: model files, packages, runtimes, servers, data	4.8 (p. 70)
Syslog	The standard way to send log lines over the network to a collector	4.3 (p. 57)
System prompt	The instructions that come first in the message list, such as "You are a helpful assistant"	2.4 (p. 22)
Temperature	A setting for randomness. 0 always picks the top token. Higher values give variety and risk	3.4 (p. 42)
Tensor	A table of numbers with any number of dimensions. Model files are mostly tensors	2.2 (p. 14)
Threat modeling	Drawing a system and its trust boundaries, and asking what can go wrong at each	4.4 (p. 60)
Token	A piece of text, such as a word, part of a word or a punctuation mark	2.6 (p. 27)
Tokenizer	The table and rules that cut text into tokens and map them to numbers	2.6 (p. 27)
Tokens per second	The speed of a model: how many tokens it reads or writes each second	2.6 (p. 27), 3.5 (p. 44)
Tool calling	The model writes a structured request, and the harness decides whether to run it	2.5 (p. 25), 3.6 (p. 48)
Top-k, top-p	Settings that cut the list of likely tokens before one is drawn	3.4 (p. 42)
Training	Adjusting the weights so that the next-token guesses improve	3.3 (p. 40)
Transformer	The architecture of modern language models: attention without recurrence	3.2 (p. 38)
Vector	A list of numbers. Each token becomes one	2.6 (p. 27), 3.1 (p. 35)
Vector database	A store that finds the pieces of text whose vectors are closest to a question's vector	3.6 (p. 48)
Weight	One learned number in a matrix. Weights are set in training and fixed in use	2.2 (p. 14), 3.1 (p. 35)

C. Who is missing from the story? 1843-2021

The usual story of AI names a handful of famous people. Many more people shaped the field, and several of them did work that we only now understand to be important. The table lists the people from Section 1 (p. 4), in order of date, together with people who are often left out. Some of them did the early work on language and meaning. Others asked who the systems work for and who they fail.

Person	When	Contribution
Ada Lovelace	1843	Wrote notes on Charles Babbage's Analytical Engine that include what is often called the first computer program. She argued that machines cannot originate anything on their own
Gottlob Frege	1884	Stated the context principle: a word has meaning in the context of a sentence
Claude Shannon	1948	Founded information theory and introduced the bit (paper)
Alan Turing	1950	Proposed the imitation game, now called the Turing test (paper)
John McCarthy	1955 to 1956	Coined "artificial intelligence" and organized the Dartmouth workshop (proposal)
J. R. Firth	1957	"You shall know a word by the company it keeps": the idea behind word embeddings and, loosely, attention
Frank Rosenblatt	1958	Built the perceptron, an early trainable neural network (paper)
Margaret Masterman	1950s and 1960s	Founded the Cambridge Language Research Unit and pioneered machine translation, with meaning built from word relationships
Joseph Weizenbaum	1966	Wrote ELIZA and warned about how much people trusted it (paper)
Marvin Minsky and Seymour Papert	1969	Wrote *Perceptrons*, which showed the limits of single-layer networks
Karen Spärck Jones	1972	Introduced inverse document frequency, the base of search ranking (paper)
David Rumelhart, Geoffrey Hinton, Ronald Williams	1986	Showed how to train multi-layer networks with backpropagation (paper)
Judea Pearl	1988	Developed Bayesian networks and a mathematics of cause and effect for AI, and won the 2011 Turing Award
Richard Wallace	1995	Created A.L.I.C.E.
ActiveBuddy	2001	Launched SmarterChild
Fei-Fei Li	2009	Led ImageNet (paper)
Luis von Ahn	2000s	Co-invented CAPTCHA and reCAPTCHA, which produced labeled data from millions of small human tasks (paper)
Alex Krizhevsky, Ilya Sutskever, Geoffrey Hinton	2012	AlexNet won ImageNet by a wide margin, trained on GPUs (paper)
Tomas Mikolov and colleagues	2013	word2vec: king minus man plus woman lands near queen (paper)

Person	When	Contribution
Dzmitry Bahdanau, Kyunghyun Cho, Yoshua Bengio	2014	Introduced attention for machine translation (paper)
Yonghui Wu and colleagues at Google	2016	A deep LSTM network with attention in Google Translate (paper)
Ashish Vaswani and colleagues	2017	"Attention Is All You Need": the transformer (paper)
Demis Hassabis, John Jumper	2016 to 2024	AlphaGo and AlphaFold. Hassabis and Jumper shared the 2024 Nobel Prize in Chemistry (AlphaGo paper, AlphaFold paper)
Rediet Abebe and Timnit Gebru	2017	Cofounded Black in AI to build community and support Black researchers in the field
Joy Buolamwini and Timnit Gebru	2018	Published Gender Shades, which showed that commercial face analysis made far more errors on darker-skinned women. Buolamwini founded the Algorithmic Justice League (paper)
Timnit Gebru and coauthors	2021	Wrote "On the Dangers of Stochastic Parrots" about the risks of ever larger language models: bias in training data, cost, and fluent text mistaken for understanding (paper)

Look at the last three rows. They are the start of Section 4 (p. 51): a model learns from the data that we give it, so who is in the data, and who checked the results, matters.

D. Bonus Labs

Labs 6 (p. 95) to 9 (p. 96) are the homework labs. Each walkthrough starts with Part 0, the setup for the lab.

Lab 6: Train Your Own Model

- Part 0: Set up for the lab
- Part 1: Examine the training data
- Part 2: Train the Chapter 1 network
- Part 3: Change one setting at a time
- Part 4: Overfitting, cross-entropy and regularization
- 4a: Make a network overfit
- 4b: Train the model that you keep
- Part 5: Use the model on your own handwriting
- Part 6 (optional): Attack the model
- 6a: Data poisoning
- 6b: A hidden backdoor
- Part 7: Compare your model with the workshop models

Lab 7: Offline Models on Your Phone

- Part 0: Set up for the lab
- Part 1: Android
- 1a: Google AI Edge Gallery
- 1b: PocketPal AI
- 1c: Copy the Lab 1 (p. 34) model to the phone
- 1d (optional): Ollama in Termux
- Part 2: iOS
- 2a: Google AI Edge Gallery
- 2b: PocketPal AI
- 2c: Copy the Lab 1 (p. 34) model to the phone
- 2d (optional): Apple's on-device model
- Part 3: Compare the results and examine the data that left the phone

Lab 8: Attack an Agent

- Part 0: Set up for the lab
- Part 1: KoboldCpp and a tool-calling model
- Part 2: Attack the agent, then add a control
- Part 3: Kill switch drill
- Part 4: Clean up

Lab 9: Abliterated Models

- Part 0: Set up for the lab
- Part 1: Read how abliteration operates
- Part 2: Compare the refusals of the two models
- Part 3: Measure the cost in quality with the Lab 2 (p. 47) benchmark
- Part 4: Find the change
- 4a: The name and the metadata
- 4b: The hash
- 4c: The weights
- Part 5: Controls that do not depend on the model