

```
1 close all; clear all;
2
3 %% A simple example using MATLAB
4 load score_data % input N score
5
6 N=input('  number of student:  ');
7 score=zeros(2,N);
8
9 % input the name and score of the student evaluate the average score
10 for i=1:N
11     str1= input('student name:', 's');
12     eval(['name',int2str(i),'=str1;']);
13 %     if (i==1)
14 %         name=str1;
15 %     else
16 %         name=char(name,str1); % Create a character array.
17 %     end
18 score(1,i)=input('math score:  ');
19 score(2,i)=input('english score:  ');
20 avg(i)=(score(1,i)+score(2,i))/2; % avg(i) = sum(score(:,i))/2;
21 end
22
23 % output value
24 for i=1:N
25     eval(['str1=name',int2str(i),';']);
26 fprintf('the average score of %s is %3.2f \n',str1,avg(i));
27 end
28 save score_data N score
29
30 %% prog 2.3-1  Variable stored as array
31 % Array (scalar, vector, matrix) in matlab
32 % vectors, and matrices...
33
34
35 N = 5 % a scalar
36 v = [1 0 0] % a row vector
37 v = [1;2;3] % a column vector
38 v = v' % transpose a vector (row to column or column to row)
39 v = [1:.5:3] % a vector in a specified range:
40 v = pi*[-4:4]/4 % [start:stepsize:end]
41 v = [] % empty vector
42
43
44 m = [1 2 3; 4 5 6] % a matrix: 1ST parameter is ROWS
45 % 2ND parameter is COLS
```

```
46 m = zeros(2,3)           % a matrix of zeros
47 v = ones(1,3)            % a matrix of ones
48 m = eye(3)               % identity matrix
49 v = rand(3,1)            % rand matrix (see also randn)
50 save matrix_data m       % save the variable m to a file named matrix_data.mat
51
52 clear all                % clear all variables currently used by MATLAB
53
54 load matrix_data         % read data from the saved file
55 m                        % display it - it is still there!
56
57 v = [1 2 3];            % access a vector element
58 length(v)               % length of a vector
59 v(2:3)                  % vector(number)
60
61
62 % 2.3.5 subscripts
63 a=[ 1 2 3 4 5 6 7 8];
64 a(2:6)
65 a(2:2:6)
66
67 m = [1 2 3; 4 5 6;7 8 9]
68 m(1,3)                  % access a matrix element
69                          % matrix(rownumber, columnnumber)
70 m(2,:)                  % access a matrix row (2nd row)
71 m(:,1)                  % access a matrix column (1st row)
72
73
74 size(m)                 % size of a matrix
75 size(m,1)               % number rows
76 size(m,2)               % number of columns
77
78
79 % to chane the value by finding the subscript
80
81 [i j]=find(m>=3);
82 disp([i j]);
83
84 pp=find(m>=3);
85 m(pp)=0
86
87
88 m1 = zeros(size(m))      % create a new matrix with size of m
89
90 who                     % list of variables
```

```
91 whos                % list/size/type of variables
92
93 %% chap2.5-1 Array operations
94 % (A) Pointwise (element by element) Operations:
95
96 % addition of vectors/matrices and multiplication by a scalar
97 % are done "element by element"
98 a  = [1 2 3 4];      % vector
99 2 * a                % scalar multiplication
100 a / 4                % scalar multiplication
101 b  = [5 6 7 8];      % vector
102 a + b                % pointwise vector addition
103 a - b                % pointwise vector addition
104 a .^ 2               % pointwise vector squaring (note .)
105 a .* b               % pointwise vector multiply (note .)
106 a ./ b               % pointwise vector multiply (note .)
107
108 log( [1 2 3 4] )     % pointwise arithmetic operation
109 round( [1.5 2; 2.2 3.1] ) % pointwise arithmetic operation
110
111
112 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
113 % (B) Vector Operations (no for loops needed)
114 % Built-in matlab functions operate on vectors, if a matrix is given,
115 % then the function operates on each column of the matrix
116
117 a  = [1 4 6 3]        % vector
118 sum(a)                % sum of vector elements
119 mean(a)               % mean of vector elements
120 var(a)                % variance (sigma^2)
121 std(a)                % standard deviation (sigma)
122 max(a)                % maximum
123
124
125 a  = [1 2 3; 4 5 6]   % matrix
126 mean(a)                % mean of each column
127 max(a)                 % max of each column
128 max(max(a))            % to obtain max of matrix
129 max(a(:))              % another way to obtain max of matrix
130
131
132 xx = linspace(0, pi/2, 10)
133
134 yy = logspace(0, 2, 10)
135 % ddy=diff(yy);
```

```
136 % yyl=yy(1:end-1+ddy./2);
137 % figure(1);plot(yyl,ddy)
138
139 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
140 % (C) Matrix Operations:
141
142 [1 2 3] * [4 5 6]'           % row vector 1x3 times column vector 3x1
143                               % results in single number, also
144                               % known as dot product or inner product
145
146 [1 2 3]' * [4 5 6]           % column vector 3x1 times row vector 1x3
147                               % results in 3x3 matrix, also
148                               % known as outer product
149
150 a = rand(3,2)                % 3x2 matrix
151 b = rand(2,4)                % 2x4 matrix
152 c = a * b                    % 3x4 matrix
153
154 a = [1 2; 3 4; 5 6]          % 3 x 2 matrix
155 b = [5 6 7];                % 3 x 1 vector
156 b * a                        % matrix multiply
157 a' * b'                      % matrix multiply
158
159 %%
160 %(D) Saving your work
161
162 save mysession                % creates session.mat with all variables
163 save mysession a b           % save only variables a and b
164
165
166 clear a b                    % clear variables a and b
167 clear all                    % clear all variables
168
169 load mysession               % load session
170 a
171 b
172
173
174 %% Prog 2.6 format , disp statement
175
176 format long % (1) short e ; (2) bank (3) compact
177 x=[ 1e3 1 1e-4]
178
179 % 2.7-1 p. 58 square roots with newton's method
180 a = 2;
```

```
181 % a=input('input a number for the computation:');
182 x = a/2;
183 % display a variable
184 disp(['The approach to sqrt(a) for a =', num2str(a)]) % an str variable
185 for i = 1:6
186 x = (x + a / x) / 2;
187 disp( x )
188 end
189 disp( 'Matlab''s value: ' )
190 disp( sqrt(a) )
191
192 aa=[1:4] % row vector
193 bb=[5:8]
194 disp([aa' bb']) % a matrix variable of 4*2 matrix
195
196 aa=[-pi:0.25*pi:pi]
197 disp([ aa' sin(aa)'] ) % math. expression
198
199 format
200
201 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
202 % 2.7 Prog 2.7-1 Repeating with for statements
203
204 % Example: given a vector v, create a new vector with values equal to
205 % v if they are greater than 0, and equal to 0 if they less than or
206 % equal to 0.
207
208
209 v = [3 5 -2 5 -1 0]; % 1: FOR LOOPS
210 % initialize; generate zero matrix with same dimension
211 u = zeros( size(v) );
212 for i = 1:length(v)
213     disp([i v(i)]); % i=1 then [i v(i)]=[ 1 3 ]
214     if( v(i) > 0 )
215         u(i) = v(i);
216     end
217 end
218 u
219
220 v = [3 5 -2 5 -1 0] % 2: NO FOR LOOPS
221 u2 = zeros( size(v) ); % initialize
222 ind = find( v>0 ) % index into >0 elements
223 u2(ind) = v( ind )
224
225 %% Exercise For loop p.78 translate between Celsius and Fahrenheit
```

```
226
227 % input
228 %   the initial value of the temperture in degree C : 20
229 %   the final value of the temperture in degree C : 30
230 %   the step of the temperture in degree C f: 2
231
232 % output using fprintf
233 %   Celsius 20.00 Fahrenheit 68.00
234 %   Celsius 22.00 Fahrenheit 71.60
235 %   Celsius 24.00 Fahrenheit 75.20
236 %   Celsius 26.00 Fahrenheit 78.80
237 %   Celsius 28.00 Fahrenheit 82.40
238 %   Celsius 30.00 Fahrenheit 86.00
239
240
241 %%=====
242 Avoid "for" loops by vectorizing
243 %%=====
244
245 t0 = clock;
246 s = 0;
247 for n = 1:100000
248 s = s + n;
249 end
250 etime(clock, t0)
251
252 t0 = clock;
253 n = 1:100000;
254 s = sum( n );
255 etime(clock, t0)
256
257 %%=====
258 %%=====
259 % pp. 62 : sum(1/n^2) for n=1:100000
260 tic
261 s = 0;
262 for n = 1:100000
263 s = s + 1/n^2;
264 end
265 toc
266
267 % n is a vector
268 tic
269 n = 1:100000;
270 s = sum( 1./n.^2 );
```

```
271 toc
272
273
274 %%=====
275 %%=====
276
277 % p.63
278 sign = -1;
279 s = 0;
280 for n = 1:9999
281 sign = -sign;
282 s = s + sign / n;
283 end
284 display(s);
285
286 % n is a vector
287 n = 1:2:9999;
288 s = sum( 1./n - 1./(n+1) )
289
290 %% Exercise
291
292 % input the number of the student
293 clear all;close all;
294 N=input(' number of student: ');
295 score=zeros(2,N);
296 % input the name and score of the student evaluate the average score
297 MAXN=10;
298 name=zeros(MAXN,10);
299 for i=1:N
300 name(i,:)= input('student name:','s');
301 score(1,i)=input('math score: ');
302 score(2,i)=input('english score: ');
303 avg(i)=(score(1,i)+score(2,i))/2;% avg(i) = sum(score(:,i))/2;
304 end
305 % output value
306 for i=1:N
307 fprintf('the average score of %s is %3.2f \n',name(i,:),avg(i));
308 end
309
310
311 %%=====
312 % 2.8.2 p. 66 if-else statement
313 %%=====
314 % Relational operations p.65 table 2,4
315 x= (3>2)
```

```
316 x= (2>3)
317 x= (3==3)
318
319 bal = 10000 * rand;
320 if bal < 5000 % relational
321     rate = 0.09;
322 else
323     rate = 0.12;
324 end
325 newbal = bal + rate * bal;
326 disp( 'New balance after interest compounded is:')
327 format bank
328 disp( newbal )
329
330
331 %%=====
332 % 2.8.4 p. 67 elseif statement
333 %%=====
334
335
336 bal = 15000 * rand;
337 if bal < 5000
338     rate = 0.09;
339 elseif bal < 10000
340     rate = 0.12;
341 else
342     rate = 0.15;
343 end
344 newbal = bal + rate * bal;
345 format bank
346 disp( 'New balance is:' )
347 disp( newbal )
348
349
350
351
352 %%=====
353 % multiple logical condition
354 %%=====
355 bal=7000;
356 rate=0;
357 if ((5000 < bal) & (bal< 10000))% if 5000 < bal < 10000 (wrong)
358     rate = 0.12;
359 end
360 newbal = bal + rate * bal;
```



```
361 format bank
362 disp( 'New balance is:' )
363 disp( newbal )
364
365
366
367 %%=====
368 % 2.8.9 p. 71 switch elseif statement
369 %%=====
370
371 d = floor(3*rand) + 1
372 switch d
373 case 1
374 disp('That''s a 1!');
375 case 2
376 disp( 'That''s a 2!');
377 otherwise
378 disp( 'Must be 3!');
379 end
380
381
382
383 d = floor(10*rand);
384 switch d
385 case {2, 4, 6, 8}
386 disp( 'Even' );
387 case {1, 3, 5, 7, 9}
388 disp( 'Odd' );
389 otherwise
390 disp( 'Zero' );
391 end
392
393 %% Exercise
394 % (1) score case.
395 % (2) Hw. 1
396 % (3) To write the code for the root of quadratic equation in p. 94
397 %%=====
398 % complex number p. 72
399 %%=====
400
401 i=sqrt(-1);
402 circle = exp( 2*i*[1:360]*pi/360 );
403 figure, plot(circle)
404 % axis([-1 1 -2 2])
405 axis('equal')
```

```
406 axis([-2 2 -2 2])
407
408 a=3;
409 b=5;
410 a=[a b];
411 b=a(1);
412 a(1)=[]
413 %%=====
414 %%=====
415
416 a = [1+i 2+2i; 3+3i 4+4i]
417 a'
418 a.'
419
420
421 %%=====
422 %%=====
423 tic
424 k=1:40000;
425 s=sum(1./k.^2);
426 disp(sqrt(6*s))
427 toc
428
429
430 clc;clear;close all
431
432 money=50;%%本金
433 newBalance = zeros(1,12);
434
435 for k=1:12 %% 月份
436     money = money *1.01;%%本金加利息
437     newBalance(k)=money;%%每月存款結算
438     money=money+50;%%每月定存
439 end
440
441 display(['Month' ' New Balance']);
442 display(num2str([ (1:12)' newBalance' ]));
443
444
445 %% Exercise answer
446 close all;clear all;
447
448 aa = floor(100*rand(20,1)) + 1
449 for i=1:length(aa)
450     bb(i)='n';
```

```
451     if (aa (i) >= 60)
452         bb(i)='p';
453     end
454     disp([ '      ' num2str(aa(i)) '      ' bb(i) ]);
455 end
456
457
458
```