


Micro-Fit 3.0 Connector System Product Family

molex

Ordering Information

Series No.	Component	
43030	Female Terminal (Available in: 0.25µm Select Tin, 0.38µm and 0.76µm Select Gold)(18 - 30AWG)	
46235	Reduced Mating Force (RMF) Female Terminal, available with or without Lubricant (Available in: 0.25µm Select Tin, 0.38µm and 0.76µm Select Gold)(20 - 30AWG)	
203951	RMF Female Terminal (Available in: 0.25µm Select Tin)(18 AWG)	
43031	Male Terminal (Available in: 0.25µm Select Tin, 0.38µm and 0.76µm Select Gold)(18 - 30AWG)	
43031-5XXX	TPA Plug Male Terminal (Used with: Housing Series 200875)(Available in: Preplated Tin 1µm - 2.5µm, 0.38µm Min Selective Gold Over 2.5µm Min Selective Tin Over 1.27µm Overall Nickel, 0.76µm Min Selective Gold Over 2.5µm Min Selective Tin Over 1.27µm Overall Nickel, 2.5µm Min Matte Tin Over 1.27µm Overall Nickel)(20 - 30AWG)	
43025	Dual-Row Receptacle Housing (mates with 43020, 43045, 44914, 44242) (Available in: UL 94V-0, Glow Wire, Low-Halogen)(2 - 24 Circuits)	
43020	Dual-Row Plug (mates with 43025, 45132, 245132, 172952) (Available in: UL 94V-0, Glow Wire, Low-Halogen) (Panel/Non-Panel Mount)(2 - 24 Circuits)	
43045	Dual-Row Header (mates with 43025, 45132, 245132, 172952) (Available in: 0.25µm Select Tin, 0.38µm and 0.76µm Select Gold)(2 - 24 Circuits) (Right Angle and Vertical Orientations; Surface Mount, Through Hole - Kinked Pin and Through Hole Termination Interface Style)	
43645	Single-Row Receptacle (mates with 43640, 43650) (Available in: UL 94V-0, Glow Wire, Low-Halogen)(2 - 12 Circuits)	
43640	Single-Row Plug (mates with 43645, 171850) (Available in: UL 94V-0, Glow Wire, Low-Halogen)(2 - 12 Circuits) (Panel Mount and Non-Panel Mount)	
200875	Single Row TPA Plug (Mates with Micro-Fit 171850 and 43645) (UL94V-0)(Low Halogen)(Color - Black)(2-7 Circuits)	
43650	Single-Row Header (mates with 43645, 171850) (Available in: 0.25µm Select Tin, 0.38µm and 0.76µm Select Gold)(2 - 12 Circuits) (Right Angle and Vertical Orientations; Surface Mount, Through Hole - Kinked Pin and Through Hole Termination Interface Style)	
171850	TPA Single-Row Receptacle (mates with 43640, 43650) (Available In: UL 94V-0, Low-Halogen)(2 - 7 Circuits)	
172952	TPA Dual-Row Receptacle (2 TPA parts required for each receptacle) (mates with 43020, 43045, 44914) (Available In: UL 94V-0, 94V-2, Glow Wire, Low-Halogen)(4 - 22 Circuits) (Black and Natural Color)	
203632	TPA Dual-Row Plug (Mates with 172952 and 43025)	
172953	TPA Retainer (2 TPA parts required for each receptacle) (Available In: Low-Halogen)(4 - 22 Circuits) (Black and Natural Color)	
45132	Off-the-Shelf Micro-Fit TPA Discrete Wire Cable Assemblies (Available in: 4 - 8 Circuits)(1.0M, 150.00mm, 300.00mm Lengths)	

Micro-Fit 3.0 Connector System Product Family

molex

Ordering Information

Series No.	Component	
44133	BMI Dual Row, Panel Mount Receptacle Housing (mates with 44300, 44432, 44428, 45280) (Available In: UL 94V-0, Halogen-Free)(4 - 24 Circuits)	
44300	BMI Dual Row, Panel Mount Plug Housing (mates with 44133, 44769, 44764) (Available In: 4 - 24 Circuits)	
44428	BMI Dual Row, Surface Mount Compatible, Right Angle Headers (mates with 44769, 44764, 44133) (Available In: Tin, 0.38µm and 0.76µm Select Gold; Low-Halogen)(4 - 24 Circuits)	
44432	BMI Dual Row, Surface Mount Compatible, Vertical Header (mates with 44769, 44764, 44133) (Available In: Tin, 0.38µm and 0.76µm Select Gold; Low-Halogen)(4 - 24 Circuits)	
44764	BMI Dual Row, Right Angle PCB Receptacle Header with Press-fit Plastic Pegs (mates with 44300, 44428, 44432, 45280) (Available In: Tin, 0.38µm and 0.76µm Select Gold; Low-Halogen)(4 - 24 Circuits)	
44769	BMI Dual Row, Vertical Receptacle Header with Press-fit Plastic Pegs (mates with 44300, 44432, 45280, 44428) (Available In: Tin, 0.38µm and 0.76µm Select Gold; Low-Halogen)(4 - 24 Circuits)	
45280	BMI Vertical Compliant Pin Header, Dual Row (mates with 44769, 44764, 44133) (Available In: Tin, 0.38µm and 0.76µm Select Gold; UL 94V-0)(4 - 24 Circuits)	
44914	Compliant Pin Vertical Header, Dual Row (mates with 43025, 172952) (Available In: Tin, 0.38µm and 0.76µm Select Gold; Glow Wire)(4 - 24 Circuits)	
46622	BMI Single Row Header (mates with 46623, 46625) (Available in Tin, 0.38µm and 0.76µm Select Gold; UL 94V-0, Halogen-Free; Right Angle, Vertical)(2 - 7 Circuits)	
46623	BMI Single Row Panel Mount Receptacle (mates with 46622) (UL 94V-0; Halogen-Free)(2 - 7 Circuits)	
46625	BMI Single Row Panel Mount Plug (mates with 46622) (UL 94V-0; Halogen-Free)(2 - 7 Circuits)	

Custom Product	Description
Contact Molex	Customized Micro-Fit Overmolded Cable Assemblies
	Customized Micro-Fit Discrete Wire Cable Assemblies

www.molex.com/link/microfit30.html

Molex is a registered trademark of Molex, LLC in the United States of America and may be registered in other countries; all other trademarks listed herein belong to their respective owners.