



APPLICATION GUIDE

FAMILY OF PRODUCTS

- Concrete Repair
- Self-Leveling
- Grouts

FEATURES

PRODUCT	RWB Patcher 1776	RWB 321 Old School Mix	RWB Smoother	RWB Strongcrete	RWB Strongcrete FD	RWB Strongcrete LST	RWB Rapid Anchor	RWB Flowtopper	RWB Flowsmooth	RWB Struccrete CI	RWB Swiftset	RWB Repairer	RWB Repairer F-1	RWB Repairer VOR, CI	RWB Seal Coat	RWB Freedom Grout	RWB Liberty Grout	RWB Patriot Grout	RWB Bonding Agent & Admix	RWB Acrylic Latex BAA	RWB Bonding Agent OTR	RWB Rapid Plug
Aggregate Extendable for Deep Repair	●			●		●		●	●	●		●	●			●	●	●				
Yield, Ft ³	<div>Neat Extended</div> <div>.43 .56</div>	<div>.43 NA</div>	<div>.40 NA</div>	<div>.43 .56</div>	<div>.50 NA</div>	<div>.43 .56</div>	<div>.43 NA</div>	<div>.43 .56</div>	<div>.43 .56</div>	<div>.43 .56</div>	<div>.43 NA</div>	<div>.43 .56</div>	<div>.43 .56</div>	<div>.43 NA</div>	<div>.43 NA</div>	<div>.43 .56</div>	<div>.43 .56</div>	<div>.43 .56</div>	<div>NA NA</div>	<div>NA NA</div>	<div>NA NA</div>	<div>NA NA</div>
Lifts								●	●		●		●	●								
Min Thickness F = Feather Edge	F	F	F	1/2"	1"	1/2"	1"	F	F	1/2"	1/8"	1/2"	F	1/8"	F	1"	1"	1"	NA	NA	NA	NA
Max Thickness	<div>Neat Extended</div> <div>1" 4"</div>	<div>1/8" NA</div>	<div>1/2" NA</div>	<div>3" 8"</div>	<div>NA 8"</div>	<div>3" 8"</div>	<div>8" NA</div>	<div>1/2" 2"</div>	<div>1" 2"</div>	<div>3" 8"</div>	<div>2" NA</div>	<div>3" 8"</div>	<div>1" 4"</div>	<div>2" NA</div>	<div>1/16" NA</div>	<div>3" 8"</div>	<div>3" 8"</div>	<div>3" 8"</div>	<div>NA NA</div>	<div>NA NA</div>	<div>NA NA</div>	<div>NA NA</div>
Working Time	:60	:90	:50	:30	:12	:45	:10	:20	:30	:25	:24	:20	:30	:20	3:00	3:00	1:45	2:30	NA	NA	NA	NA
Final Set	2:00	5:00	2:00	:55	:45	1:45	:20	1:30	1:30	1:45	:50	1:05	1:20	:45	5:00	6:00	5:30	5:30	NA	NA	NA	:05
Temperatures	← MINIMUM 40° MAXIMUM 90° →																					
Strengths (PSI)	5,000	4,000	2,000	7,000	6,500	6,000	5,000	5,400	3,000	9,000	6,000	7,000	4,500	5,500	3,500	6,000	7,000	7,500	NA	NA	NA	5,500
Structural				●	●	●				●		●				●	●	●				
Cosmetic	●	●	●					●			●		●	●	●							●
Walkways	●										●		●									
Garages	●			●	●	●						●	●									
Commercial Floor	●			●	●	●		●	●			●	●									
Industrial	●			●	●	●						●						●				●
Horizontal Repair	●			●	●	●		●	●	●		●	●									
Traffic	●			●	●	●		●		●		●										
Vertical/Overhead		●	●			●				●	●			●	●							●
Form and Pour						●				●												
Low Pressure Spray																			●	●	●	
Underlayment									●													
Self-leveling								●	●													
Cementitious	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				●
2-Component	●																					
Non-Sag Trowelable											●			●								
Self-Consolidation Pumpable						●				●						●	●	●				
Flowable	●			●	●	●	●	●	●	●		●	●			●	●	●				
Coating Acceptability		●	●												●							
Corrosion Inhibitor										●				●								
Shrinking Compensation																●	●	●				
Polymer Modified	●	●	●					●	●		●	●	●	●	●							
Light Color	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●							●
Smooth Texture			●																			
Feather Edge Repairs	●	●	●					●	●				●		●							

Exclusively manufactured for JANELL, INC. by US SPEC



Distributed by JANELL, INC.

CINCINNATI, OH
6130 Cornell Rd
45242
513-489-9111

DAYTON, OH
801 E 1st St
45402
937-866-9111

NORWOOD, OH
4686 Paddock Rd
45229
513-651-9111

COLUMBUS, OH
831 Harmon Ave
43223
614-224-9111

ERLANGER, KY
2930 Crescent Sprgs
41018
859-341-9111

LEXINGTON, KY
970 New Circle Rd
40511
859-254-9111

