

C Operator Precedence Table

This page lists C operators in order of *precedence* (highest to lowest). Their *associativity* indicates in what order operators of equal precedence in an expression are applied.

Operator	Description	Associativity
() [] . -> ++ --	Parentheses (function call) (see Note 1) Brackets (array subscript) Member selection via object name Member selection via pointer Postfix increment/decrement (see Note 2)	left-to-right
++ -- + - ! ~ (type) * & sizeof	Prefix increment/decrement Unary plus/minus Logical negation/bitwise complement Cast (convert value to temporary value of <i>type</i>) Dereference Address (of operand) Determine size in bytes on this implementation	right-to-left
* / %	Multiplication/division/modulus	left-to-right
+ -	Addition/subtraction	left-to-right
<< >>	Bitwise shift left, Bitwise shift right	left-to-right
< <= > >=	Relational less than/less than or equal to Relational greater than/greater than or equal to	left-to-right
== !=	Relational is equal to/is not equal to	left-to-right
&	Bitwise AND	left-to-right
^	Bitwise exclusive OR	left-to-right
	Bitwise inclusive OR	left-to-right
&&	Logical AND	left-to-right
	Logical OR	left-to-right
? :	Ternary conditional	right-to-left
= += -= *= /= %= &= ^= = <<= >>=	Assignment Addition/subtraction assignment Multiplication/division assignment Modulus/bitwise AND assignment Bitwise exclusive/inclusive OR assignment Bitwise shift left/right assignment	right-to-left
,	Comma (separate expressions)	left-to-right
<p>Note 1: Parentheses are also used to group sub-expressions to force a different precedence; such parenthetical expressions can be nested and are evaluated from inner to outer.</p> <p>Note 2: Postfix increment/decrement have high precedence, but the actual increment or decrement of the operand is delayed (to be accomplished sometime before the statement completes execution). So in the statement <code>y = x * z++</code>; the current value of <code>z</code> is used to evaluate the expression (i.e., <code>z++</code> evaluates to <code>z</code>) and <code>z</code> only incremented after all else is done. See postinc.c for another example.</p>		