
Functional Dependencies and Normalization for Relational Databases

Dr. Ali Obaidi
CS-450 Fall 2002

Informal Design Guidelines for Relational Databases

- ◆ Relational database design: The grouping of attributes to form "good" relation schemas
- ◆ Two levels of relation schemas:
 - The logical "user view" level
 - The storage "base relation" level
- ◆ Design is concerned mainly with base relations
- ◆ Criteria for "good" base relations:
 - Discuss informal guidelines for good relational design
 - Discuss formal concepts of functional dependencies and normal forms 1NF 2NF 3NF BCNF

Semantics of the Relation Attributes

- ◆ Each tuple in a relation should represent one entity or relationship instance
 - Only foreign keys should be used to refer to other entities
 - Entity and relationship attributes should be kept apart as much as possible
 - Design a schema that can be explained easily relation by relation. The semantics of attributes should be easy to interpret.

Figure 14.1 Simplified version of the COMPANY relational database schema.

EMPLOYEE

ENAME	<u>SSN</u>	BDATE	ADDRESS	DNUMBER
-------	------------	-------	---------	---------

p.k.

DEPARTMENT

DNAME	<u>DNUMBER</u>	DMGRSSN
-------	----------------	---------

p.k.

DEPT_LOCATIONS

<u>DNUMBER</u>	<u>DLOCATION</u>
----------------	------------------

p.k.

PROJECT

PNAME	<u>PNUMBER</u>	PLOCATION	DNUM
-------	----------------	-----------	------

p.k.

WORKS_ON

<u>SSN</u>	<u>PNUMBER</u>	HOURS
------------	----------------	-------

p.k.

EMPLOYEE

ENAME	<u>SSN</u>	BDATE	ADDRESS	DNUMBER
Smith,John B.	123456789	1965-01-09	731 Fondren,Houston,TX	5
Wong, Franklin T.	333445555	1955-12-08	638 Voss,Houston,TX	5
Zelaya,Alicia J.	999887777	1968-07-19	3321 Castle, Spring,TX	4
Wallace,Jennifer S.	987654321	1941-06-20	291 Berry,Bellaire,TX	4
Narayan,Remesh K.	666884444	1962-09-15	975 Fire Oak,Humble,TX	5
English,Joyce A.	453453453	1972-07-31	5631 Rice,Houston,TX	5
Jabbar,Ahmad V.	987987987	1969-03-29	980 Dallas,Houston,TX	4
Borg,James E.	888665555	1937-11-10	450 Stone,Houston,TX	1

DEPARTMENT

DNAME	<u>DNUMBER</u>	DMGRSSN
Research	5	333445555
Administration	4	987654321
Headquarters	1	888665555

DEPT_LOCATIONS

<u>DNUMBER</u>	<u>DLOCATION</u>
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

WORKS_ON

<u>SSN</u>	<u>PNUMBER</u>	HOURS
123456789	1	32.5
123456789	2	7.5
666884444	3	40.0
453453453	1	20.0
453453453	2	20.0
333445555	2	10.0
333445555	3	10.0

PROJECT

PNAME	<u>PNUMBER</u>	PLOCATION	DNUM
ProductX	1	Bellaire	5
ProductY	2	Sugarland	5
ProductZ	3	Houston	5
Computerization	10	Stafford	4
Reorganization	20	Houston	1
Newbenefits	30	Stafford	4

Redundant Information in Tuples and Update Anomalies

- ◆ Mixing attributes of multiple entities may cause problems
 - Information is stored redundantly wasting storage
 - Problems with update anomalies:
 - Insertion anomalies
 - Deletion anomalies
 - Modification anomalies


(a)

EMP_DEPT



(b)

EMP_PROJ



EMP_DEPT

ENAME	<u>SSN</u>	BDATE	ADDRESS	DNUMBER	DNAME	DMGRSSN
Smith,John B.	123456789	1965-01-09	731 Fondren,Houston,TX	5	Research	333445555
Wong, Franklin T.	333445555	1955-12-08	638 Voss,Houston,TX	5	Research	333445555
Zelaya, Alicia J.	999887777	1968-07-19	3321 Castle, Spring,TX	4	Administration	987654321
Wallace, Jennifer S.	987654321	1941-06-20	291 Berry,Bellaire,TX	4	Administration	987654321
Narayan,Ramesh K.	666884444	1962-09-15	975 FireOak,Humble,TX	5	Research	333445555
English, Joyce A.	453453453	1972-07-31	5631 Rice,Houston,TX	5	Research	333445555
Jabbar,Ahmad V.	987987987	1969-03-29	980 Dallas,Houston,TX	4	Administration	987654321
Borg,James E.	888665555	1937-11-10	450 Stone,Houston,TX	1	Headquarters	888665555

EMP_PROJ

<u>SSN</u>	<u>PNUMBER</u>	HOURS	ENAME	PNAME	PLOCATION
123456789	1	32.5	Smith,John B.	ProductX	Bellaire
123456789	2	7.5	Smith,John B.	ProductY	Sugarland
666884444	3	40.0	Narayan,Ramesh K.	ProductZ	Houston
453453453	1	20.0	English,Joyce A.	ProductX	Bellaire
453453453	2	20.0	English,Joyce A.	ProductY	Sugarland
333445555	2	10.0	Wong, Franklin T.	ProductY	Sugarland
333445555	3	10.0	Wong, Franklin T.	ProductZ	Houston
333445555	10	10.0	Wong, Franklin T.	Computerization	Stafford

EXAMPLE OF AN UPDATE ANOMALY

Consider the relation:

EMP_PROJ (Emp#, Proj#, Ename, Pname, No_hours)

■ Update Anomaly

- Changing the name of project number P1 from “Billing” to “Customer-Accounting” may cause this update to be made for all 100 employees working on project P1

■ Insert Anomaly

- Cannot insert a project unless an employee is assigned to .
- Inversely- Cannot insert an employee unless he/she is assigned to a project.

EXAMPLE OF AN UPDATE ANOMALY (2)

■ Delete Anomaly

- When a project is deleted, it will result in deleting all the employees who work on that project. Alternately, if an employee is the sole employee on a project, deleting that employee would result in deleting the corresponding project.
- ◆ Design a schema that does not suffer from the insertion, deletion and update anomalies. If there are any present, then note them so that applications can be made to take them into account

Null Values in Tuples

- ◆ Relations should be designed such that their tuples will have as few NULL values as possible
 - Attributes that are NULL frequently could be placed in separate relations (with the primary key)
 - Reasons for nulls:
 - a. attribute not applicable or invalid
 - b. attribute value unknown (may exist)
 - c. value known to exist, but unavailable

Spurious Tuples

- ◆ Bad designs for a relational database may result in erroneous results for certain JOIN operations
- ◆ The "lossless join" property is used to guarantee meaningful results for join operations
- ◆ The relations should be designed to satisfy the lossless join condition. No spurious tuples should be generated by doing a natural-join of any relations

(a)

EMP_LOCS

<u>ENAME</u>	<u>PLOCATION</u>
--------------	------------------

p.k.

EMP_PROJ1

<u>SSN</u>	<u>PNUMBER</u>	HOURS	PNAME	PLOCATION
------------	----------------	-------	-------	-----------

p.k.

(b)

EMP_LOCS

ENAME	PLOCATION
Smith, John B.	Bellaire
Smith, John B.	Sugarland
Narayan, Ramesh K.	Houston
English, Joyce A.	Bellaire
English, Joyce A.	Sugarland
Wong, Franklin T.	Sugarland
Wong, Franklin T.	Houston
Wong, Franklin T.	Stafford

Zelaya, Alicia J.	Stafford
Jabbar, Ahmad V.	Stafford
Wallace, Jennifer S.	Stafford
Wallace, Jennifer S.	Houston
Borg, James E.	Houston

EMP_PROJ1

SSN	PNUMBER	HOURS	PNAME	PLOCATION
123456789	1	32.5	Product X	Bellaire
123456789	2	7.5	Product Y	Sugarland
666884444	3	40.0	Product Z	Houston
453453453	1	20.0	Product X	Bellaire
453453453	2	20.0	Product Y	Sugarland
333445555	2	10.0	Product Y	Sugarland
333445555	3	10.0	Product Z	Houston
333445555	10	10.0	Computerization	Stafford
333445555	20	10.0	Reorganization	Houston

999887777	30	30.0	Newbenefits	Stafford
999887777	10	10.0	Computerization	Stafford
987987987	10	35.0	Computerization	Stafford
987987987	30	5.0	Newbenefits	Stafford
987654321	30	20.0	Newbenefits	Stafford
987654321	20	15.0	Reorganization	Houston
888665555	20	null	Reorganization	Houston

Functional Dependencies

- ◆ Functional dependencies (FDs) are used to specify *formal measures* of the "goodness" of relational designs
- ◆ FDs and keys are used to define **normal forms** for relations
- ◆ FDs are **constraints** that are derived from the *meaning* and *interrelationships* of the data attributes

Functional Dependencies (2)

- ◆ A set of attributes X *functionally determines* a set of attributes Y if the value of X determines a unique value for Y
- ◆ $X \rightarrow Y$ holds if whenever two tuples have the same value for X , they *must have* the same value for Y
If $t1[X]=t2[X]$, then $t1[Y]=t2[Y]$ in any relation instance $r(R)$
- ◆ $X \rightarrow Y$ in R specifies a *constraint* on all relation instances $r(R)$
- ◆ FDs are derived from the real-world constraints on the attributes

Examples of FD constraints

- ◆ Social Security Number determines employee name
 $SSN \rightarrow ENAME$
- ◆ Project Number determines project name and location
 $PNUMBER \rightarrow \{PNAME, PLOCATION\}$
- ◆ Employee SSN and project number determines the hours per week that the employee works on the project
 $\{SSN, PNUMBER\} \rightarrow HOURS$

Functional Dependencies (3)

- ◆ An FD is a property of the attributes in the schema R
- ◆ The constraint must hold on *every relation instance* $r(R)$
- ◆ If K is a key of R , then K functionally determines all attributes in R (since we never have two distinct tuples with $t1[K]=t2[K]$)

Inference Rules for FDs

- ◆ Given a set of FDs F , we can *infer* additional FDs that hold whenever the FDs in F hold
- ◆ Armstrong's inference rules
 - A1. (Reflexive) If Y subset-of X , then $X \rightarrow Y$
 - A2. (Augmentation) If $X \rightarrow Y$, then $XZ \rightarrow YZ$
(Notation: XZ stands for $X \cup Z$)
 - A3. (Transitive) If $X \rightarrow Y$ and $Y \rightarrow Z$, then $X \rightarrow Z$
- ◆ A1, A2, A3 form a *sound* and *complete* set of inference rules

Additional Useful Inference Rules

- ◆ Decomposition
 - If $X \rightarrow YZ$, then $X \rightarrow Y$ and $X \rightarrow Z$
- ◆ Union
 - If $X \rightarrow Y$ and $X \rightarrow Z$, then $X \rightarrow YZ$
- ◆ Psuedotransitivity
 - If $X \rightarrow Y$ and $WY \rightarrow Z$, then $WX \rightarrow Z$
- ◆ **Closure** of a set F of FDs is the set F^+ of all FDs that can be inferred from F

Introduction to Normalization

- ◆ **Normalization:** Process of decomposing unsatisfactory "bad" relations by breaking up their attributes into smaller relations
- ◆ **Normal form:** Condition using keys and FDs of a relation to certify whether a relation schema is in a particular normal form
 - 2NF, 3NF, BCNF based on keys and FDs of a relation schema
 - 4NF based on keys, multi-valued dependencies

First Normal Form

- ◆ Disallows composite attributes, multivalued attributes, and **nested relations**; attributes whose values *for an individual tuple* are non-atomic
- ◆ Considered to be part of the definition of relation

(a)

DEPARTMENT

DNAME	<u>DNUMBER</u>	DMGRSSN	DLOCATIONS
-------	----------------	---------	------------

(b)

DEPARTMENT

DNAME	<u>DNUMBER</u>	DMGRSSN	DLOCATIONS
Research	5	333445555	{Bellaire, Sugarland, Houston}
Administration	4	987654321	{Stafford}
Headquarters	1	888665555	{Houston}

(c)

DEPARTMENT

DNAME	<u>DNUMBER</u>	DMGRSSN	<u>DLOCATION</u>
Research	5	333445555	Bellaire
Research	5	333445555	Sugarland
Research	5	333445555	Houston
Administration	4	987654321	Stafford
Headquarters	1	888665555	Houston

(a)

EMP_PROJ

SSN	ENAME	PROJS	
		PNUMBER	HOURS

(b)

EMP_PROJ

SSN	ENAME	PNUMBER	HOURS
123456789	Smith,John B.	1	32.5
		2	7.5
666884444	Narayan,Ramesh K.	3	40.0
453453453	English,Joyce A.	1	20.0
		2	20.0
333445555	Wong,Franklin T.	2	10.0
		3	10.0
		10	10.0
		20	10.0
999887777	Zelaya,Alicia J.	30	30.0
		10	10.0
987987987	Jabbar,Ahmad V.	10	35.0
		30	5.0
987654321	Wallace,Jennifer S.	30	20.0
		20	15.0
888665555	Borg,James E.	20	null

(c)

EMP_PROJ1

<u>SSN</u>	ENAME
------------	-------

EMP_PROJ2

<u>SSN</u>	PNUMBER	HOURS
------------	---------	-------

Second Normal Form


- ◆ Uses the concepts of FDs, primary key
- ◆ Definitions:
 - **Prime attribute** - attribute that is member of the primary key K
 - **Full functional dependency** - a FD $Y \rightarrow Z$ where removal of any attribute from Y means the FD does not hold any more

Examples


Second Normal Form

- ◆ $\{SSN, PNUMBER\} \rightarrow HOURS$ is a full FD since neither $SSN \rightarrow HOURS$ nor $PNUMBER \rightarrow HOURS$ hold
- ◆ $\{SSN, PNUMBER\} \rightarrow ENAME$ is *not* a full FD (it is called a *partial dependency*) since $SSN \rightarrow ENAME$ also holds
- ◆ A relation schema R is in **second normal form (2NF)** if every non-prime attribute A in R is fully functionally dependent on the primary key
- ◆ R can be decomposed into 2NF relations via the process of 2NF normalization

(a)



2NF NORMALIZATION




(b)




3NF NORMALIZATION




(a)




(b)



(c)



(d)



Third Normal Form

◆ Definition

- **Transitive functional dependency** – if there a set of attribute Z that are neither a primary or candidate key and both $X \rightarrow Z$ and $Y \rightarrow Z$ holds.

◆ Examples:

- $SSN \rightarrow DMGRSSN$ is a transitive FD since $SSN \rightarrow DNUMBER$ and $DNUMBER \rightarrow DMGRSSN$ hold
- $SSN \rightarrow ENAME$ is *non-transitive* since there is no set of attributes X where $SSN \rightarrow X$ and $X \rightarrow ENAME$


3rd Normal Form

A relation schema R is in **third normal form (3NF)** if it is in 2NF *and* no non-prime attribute A in R is transitively dependent on the primary key

BCNF (Boyce-Codd Normal Form)

- ◆ A relation schema R is in **Boyce-Codd Normal Form (BCNF)** if whenever an FD $X \rightarrow A$ holds in R , then X is a superkey of R
 - Each normal form is strictly stronger than the previous one:
 - Every 2NF relation is in 1NF
 - Every 3NF relation is in 2NF
 - Every BCNF relation is in 3NF
 - There exist relations that are in 3NF but not in BCNF
 - The goal is to have each relation in BCNF (or 3NF)

(a)



BCNF Normalization


LOTS1AX



LOTS1AY



(b)



TEACH

STUDENT	COURSE	INSTRUCTOR
Narayan	Database	Mark
Smith	Database	Navathe
Smith	Operating Systems	Ammar
Smith	Theory	Schulman
Wallace	Database	Mark
Wallace	Operating Systems	Ahamad
Wong	Database	Omiecinski
Zelaya	Database	Navathe

BCNF

- ◆ $\{ \text{Student}, \text{course} \} \rightarrow \text{Instructor}$
- ◆ $\text{Instructor} \rightarrow \text{Course}$
- ◆ Decomposing into 2 schemas
 - $\{ \underline{\text{Student}}, \underline{\text{Instructor}} \} \quad \{ \underline{\text{Student}}, \underline{\text{Course}} \}$
 - $\{ \text{Course}, \underline{\text{Instructor}} \} \quad \{ \underline{\text{Student}}, \underline{\text{Course}} \}$
 - $\{ \text{Course}, \underline{\text{Instructor}} \} \quad \{ \underline{\text{Instructor}}, \underline{\text{Student}} \}$

Example

◆ Given the relation

Book(Book_title, Authorname, Book_type,
Listprice, Author_affil, Publisher)

The FDs are

Book_title \rightarrow Publisher, Book_type

Book_type \rightarrow Listprice

Authorname \rightarrow Author_affil



Example

- ◆ What normal form the relation in?