OSOROM Peripheral Reference

The Moroso Project

 $\mathrm{July}\ 13,\ 2015$

Contents

1	Onb	poard Peripherals	2
	1.1	Introduction	2
	1.2	Peripheral Reference	2
	1.3	Timer	2
	1.4	Serial Port	4
	1.5	Video Controller	4
	1.6	SD Card Controller	4
	1.7	USB Controller	4

Chapter 1

Onboard Peripherals

1.1 Introduction

The OSOROM will include several onboard peripherals:

- A programmable timer
- A serial port
- A video controller
- An SD card controller
- A USB controller?

Access to all peripherals is through memory mapped registers; each peripheral has its own page of physical address space for control registers.

1.2 Peripheral Reference

1.2.1 Register Map

	TIMER_COUNT	00000008x0
Timer	TIMER_TOP	0x80000004
	TIMER_CONTROL	80000008x0
Serial Port		0x80001000
Video Controller		0x80002000
SD Controller		0x80003000
USB Controller		0x80004000

1.3 Timer

Each clock tick, the TIMER_COUNT register is incremented. If this value matches the value in the TIMER_TOP register, TIMER_COUNT is cleared and the TIMER_INT bit in TIMER_CONTROL is set.

1.3.1 Registers

TIMER_COUNT

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16
	TIMER_COUNT														
rw	rw r														
15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
	TIMER_COUNT														
rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw

Bits 31:0 TIMER_COUNT: The current count, incremented each tick and reset to 0 when it matches the value in TIMER_TOP.

$TIMER_TOP$

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16
	TIMER_TOP														
rw	rw rw rw rw rw rw rw rw														
15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
	TIMER_TOP														
rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw

Bits 31:0 TIMER_TOP: The top value for the timer. When TIMER_COUNT is equal to this value, TIMER_COUNT will be reset to 0 and the TIMER_INT bit of TIMER_CONTROL will be set.

TIMER_CONTROL

(reserved)	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16
(reserved)		(reserved)														

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
	(reserved)												TIMER_EN	TIMER_INT_EN	TIMER_INT
					(16	SCI V	eu)						rw	rw	rw

- Bit 2 TIMER_EN: Timer enable bit. The counter will be paused if this bit is set to 0.
- Bit 1 TIMER_INT_EN: Timer interrupt enable. If this bit and TIMER_INT are both set, a timer interrupt will be generated.
- Bit 0 TIMER_INT: Timer interrupt flag. Set by hardware when TIMER_COUNT is equal to TIMER_TOP.

- 1.4 Serial Port
- 1.5 Video Controller
- 1.6 SD Card Controller
 - 1.7 USB Controller