



The Unix Shell

Permissions



shell




**Centre for Environmental
Data Analysis**
SCIENCE AND TECHNOLOGY FACILITIES COUNCIL
NATURAL ENVIRONMENT RESEARCH COUNCIL



**National Centre for
Atmospheric Science**
NATURAL ENVIRONMENT RESEARCH COUNCIL





**National Centre for
Earth Observation**
NATURAL ENVIRONMENT RESEARCH COUNCIL



shell

`pwd, mkdir, cp, ...`






shell

`pwd, mkdir, cp, ...`

*




Centre for Environmental
Data Analysis
SCIENCE AND TECHNOLOGY FACILITIES COUNCIL
NATURAL ENVIRONMENT RESEARCH COUNCIL



National Centre for
Atmospheric Science
NATURAL ENVIRONMENT RESEARCH COUNCIL



National Centre for
Earth Observation
NATURAL ENVIRONMENT RESEARCH COUNCIL




shell

`pwd, mkdir, cp, ...`

`*`

`>, |`




Centre for Environmental
Data Analysis
SCIENCE AND TECHNOLOGY FACILITIES COUNCIL
NATURAL ENVIRONMENT RESEARCH COUNCIL



National Centre for
Atmospheric Science
NATURAL ENVIRONMENT RESEARCH COUNCIL



National Centre for
Earth Observation
NATURAL ENVIRONMENT RESEARCH COUNCIL




shell

`pwd, mkdir, cp, ...`

`*`

`>, |`


Who can see what?





change






shell

`pwd, mkdir, cp, ...`

`*`

`>, |`



Who can see what?

change

run

Simplified version of Unix permissions

Simplified version of Unix permissions

Windows uses similar concepts...

Simplified version of Unix permissions

Windows uses similar concepts...

...but there is no exact translation between the two



user



user

Has unique *user name* and *user ID*



user

Has unique *user name* and *user ID*

User name is text: "imhotep", "larry", "vlad", ...



user

Has unique *user name* and *user ID*

User name is text: "imhotep", "larry", "vlad", ...

User ID is numeric (easier for computer to store)



user



group



user



group

Has unique *group name* and *group ID*



user



group

Has unique *group name* and *group ID*

User can belongs to zero or more groups



group

List is usually stored in `/etc/group`



user



group



all



user



group



all

Everyone else



user



group



all



Has user and group IDs



	user	group	all
read			





	user	group	all
read			
write			




	user	group	all
read			
write			
execute			



	user	group	all
read	✓	✓	✗
write	✓	✗	✗
execute	✗	✗	✗

File's owner can read and write it



	user	group	all
read	✓	✓	✗
write	✓	✗	✗
execute	✗	✗	✗

File's owner can read and write it

Others in group can read



	user	group	all
read	✓	✓	✗
write	✓	✗	✗
execute	✗	✗	✗

File's can read and write it

Others in group can read

That's all



	user	group	all
read	✓	✓	✗
write	✓	✗	✗
execute	✗	✗	✗


```
$ cd labs
```

```
$ ls
```

```
safety.txt      setup      waiver.txt
```

```
$
```

```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$
```

```
$ cd labs
```

```
$ ls
```

```
safety.txt      setup          waiver.txt
```

```
$ ls -F
```

```
safety.txt      setup*         waiver.txt
```

```
$
```

means "executable"

```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

↑
name

```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

last modified

```
$ cd labs
```

\$ 1s

safety.txt *setup* *waiver.txt*

\$ 1s - F

safety.txt *setup** *waiver.txt*

\$ 1s -1

```
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
```

```
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
```

```
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
```

\$

size (in bytes)


```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

group owner

```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

↑
user owner


```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

↑
permissions

```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

-rwxr-xr-x

-rwxr-xr-x

```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

-*rwxr-xr-x*



file type

```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

-*rwXr-Xr-X*

↑
file type

↗ '-' for regular

```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

-*rwxr-xr-x*

↑
file type → '-' for regular
'd' for directory


```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

-rwxr-xr-x



user owner permissions

```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

`-rwx``r-x``r-x`



group owner permissions

```
$ cd labs
$ ls
safety.txt      setup          waiver.txt
$ ls -F
safety.txt      setup*         waiver.txt
$ ls -l
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```

`-rwxr-xr-x`



everyone else's permissions

```
$ ls -a -l
```

```
drwxr-xr-x 1 vlad bio      0  2010-08-14 09:55 .  
drwxr-xr-x 1 vlad bio  8192 2010-08-27 23:11 ..  
-rw-rw-r-- 1 vlad bio  1158 2010-07-11 08:22 safety.txt  
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup  
-rw-rw-r-- 1 vlad bio  2312 2010-07-11 08:23 waiver.txt
```

```
$
```

```
$ ls -a -l
```

```
drwxr-xr-x 1 vlad bio      0  2010-08-14 09:55 .  
drwxr-xr-x 1 vlad bio 8192  2010-08-27 23:11 ..  
-rw-rw-r-- 1 vlad bio 1158  2010-07-11 08:22 safety.txt  
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup  
-rw-rw-r-- 1 vlad bio 2312  2010-07-11 08:23 waiver.txt
```

```
$
```

drwxr-xr-x
drwxr-xr-x

```
drwxr-xr-x 1 vlad bio 0 2010-08-14 09:55 .
drwxr-xr-x 1 vlad bio 8192 2010-08-27 23:11 ..
-rw-rw-r-- 1 vlad bio 1158 2010-07-11 08:22 safety.txt
-rwxr-xr-x 1 vlad bio 31988 2010-07-23 20:04 setup
-rw-rw-r-- 1 vlad bio 2312 2010-07-11 08:23 waiver.txt
$
```


What does "execute" mean for directories?

What does "execute" mean for directories?

Gives the right to *traverse*

the directory


the directory



What does "execute" mean for directories?

Gives the right to *traverse*

the directory




the directory



What does "execute" mean for directories?

Gives the right to *traverse*

the directory




What does "execute" mean for directories?

Gives the right to *traverse*


the directory

```
$ ls venus venus/notes ✓
```



the directory

```
$ ls mars mars/notes ✓
```




What does "execute" mean for directories?

Gives the right to *traverse*

the directory

```
$ ls venus venus/notes ✓
```


```
$ ls mars mars/notes ✓
```



What does "execute" mean for directories?

Gives the right to *traverse*
the directory


```
$ ls venus venus/notes ✓  
$ ls mars mars/notes ✓  
$ ls pluto ✗
```



What does "execute" mean for directories?


Gives the right to *traverse*
the directory

```
$ ls venus venus/notes ✓  
$ ls mars mars/notes ✓  
$ ls pluto ✗  
$ ls pluto/notes
```



Gives the right to *traverse*
the directory

```
$ ls venus venus/notes ✓
$ ls mars mars/notes ✓
$ ls pluto ✗
$ ls pluto/notes ✓
```



Change permission with `chmod` (change mode)

Change permission with `chmod` (change mode)

```
$ ls -l final.grd
```

```
-rwxrwxrwx 1 vlad bio 4215 2010-08-29 22:30 final.grd
```

Change permission with `chmod` (change mode)

```
$ ls -l final.grd
```

```
-rw-rw-rwx 1 vlad bio 4215 2010-08-29 22:30 final.grd
```

↑
Everyone can read it

Change permission with `chmod` (change mode)

```
$ ls -l final.grd
```

```
-rwxrwxrwx 1 vlad bio 4215 2010-08-29 22:30 final.grd
```

↑
Everyone can read it
Modify it

Change permission with `chmod` (change mode)

```
$ ls -l final.grd
```

```
-rwxrwxrwx 1 vlad bio 4215 2010-08-29 22:30 final.grd
```



Everyone can read it

Modify it

Try to run it (which probably doesn't make sense)

Change permission with `chmod` (change mode)

```
$ ls -l final.grd
```

```
-rwxrwxrwx 1 vlad bio 4215 2010-08-29 22:30 final.grd
```

```
$ chmod u=rw final.grd
```

```
$
```

Change permission with chmod (change mode)

```
$ ls -l final.grd
```

```
-rwxrwxrwx 1 vlad bio 4215 2010-08-29 22:30 final.grd
```

```
$ chmod u=rw final.grd
```

```
$
```

↑
User (u) has read-write (rw)

Change permission with `chmod` (change mode)

```
$ ls -l final.grd
```

```
-rwxrwxrwx 1 vlad bio 4215 2010-08-29 22:30 final.grd
```

```
$ chmod u=rw final.grd
```

```
$ ls -l final.grd
```

```
-rw-rwxrwx 1 vlad bio 4215 2010-08-30 08:19 final.grd
```

```
$
```

Change permission with `chmod` (change mode)

```
$ ls -l final.grd
```

```
-rwxrwxrwx 1 vlad bio 4215 2010-08-29 22:30 final.grd
```

```
$ chmod u=rw final.grd
```

```
$ ls -l final.grd
```

```
-rw-rwxrwx 1 vlad bio 4215 2010-08-30 08:19 final.grd
```

```
$ chmod g=r final.grd; ls -l final.grd
```

```
-rw-r--rw- 1 vlad bio 4215 2010-08-30 08:19 final.grd
```

\$

Change permission with chmod (change mode)

```
$ ls -l final.grd
-rwxrwxrwx 1 vlad bio 4215 2010-08-29 22:30 final.grd
$ chmod u=rw final.grd
$ ls -l final.grd
-rw-rwxrwx 1 vlad bio 4215 2010-08-30 08:19 final.grd
$ chmod g=r final.grd; ls -l final.grd
-rw-r--rw- 1 vlad bio 4215 2010-08-30 08:19 final.grd
$
```

Use ';' to put multiple commands
on a single line

Change permission with chmod (change mode)

```
$ ls -l final.grd
```

```
-rwxrwxrwx 1 vlad bio 4215 2010-08-29 22:30 final.grd
```

```
$ chmod u=rw final.grd
```

```
$ ls -l final.grd
```

```
-rw-rwxrwx 1 vlad bio 4215 2010-08-30 08:19 final.grd
```

```
$ chmod g=r final.grd; ls -l final.grd
```

```
-rw-r--rw- 1 vlad bio 4215 2010-08-30 08:19 final.grd
```

```
$ chmod a= final.grd; ls -l final.grd
```

```
-rw-r----- 1 vlad bio 4215 2010-08-30 08:20 final.grd
```

Change permission with chmod (change mode)

```
$ ls -l final.grd
-rwxrwxrwx 1 vlad bio 4215 2010-08-29 22:30 final.grd
$ chmod u=rw final.grd
$ ls -l final.grd
-rw-rwxrwx 1 vlad bio 4215 2010-08-30 08:19 final.grd
$ chmod g=r final.grd; ls -l final.grd
-rw-r--rw- 1 vlad bio 4215 2010-08-30 08:19 final.grd
$ chmod a= final.grd; ls -l final.grd
-rw-r----- 1 vlad bio 4215 2010-08-30 08:20 final.grd
```

No permissions at all

Again, things are different on Windows

Again, things are different on Windows

Permissions defined by Access Control Lists (ACLs)

Again, things are different on Windows

Permissions defined by Access Control Lists (ACLs)

A list of (who, what) pairs

Again, things are different on Windows

Permissions defined by Access Control Lists (ACLs)

A list of (who, what) pairs

More flexible...

Again, things are different on Windows

Permissions defined by Access Control Lists (ACLs)

A list of (who, what) pairs

More flexible...

...but more complex to administer and understand

Again, things are different on Windows

Permissions defined by Access Control Lists (ACLs)

A list of (who, what) pairs

More flexible...

...but more complex to administer and understand

Some flavors of Unix provide ACLs, but hardly
anyone uses them

Create your own commands

Create your own commands

```
$ cat > smallest
```


Create your own commands

```
$ cat > smallest
```



No input file specified, so read from keyboard

Create your own commands

```
$ cat > smallest
```



Send output to a file called `smallest`

Create your own commands

```
$ cat > smallest
```

```
wc -l *.pdb | sort | head -1
```

Create your own commands

```
$ cat > smallest
```

```
wc -l *.pdb | sort | head -1
```

```
^D
```

```
$
```

Create your own commands

```
$ cat > smallest
```

```
wc -l *.pdb | sort | head -1
```

```
^D
```

```
$
```



Ctrl-D means "end of input" in Unix

Create your own commands

```
$ cat > smallest
```

```
wc -l *.pdb | sort | head -1
```

```
^D
```

```
$
```



Ctrl-D means "end of input" in Unix

Ctrl-Z does the same thing in Windows

Create your own commands

```
$ cat > smallest
```

```
wc -l *.pdb | sort | head -1
```

```
^D
```

```
$ chmod u+x smallest
```

```
$
```

Create your own commands

```
$ cat > smallest
```

```
wc -l *.pdb | sort | head -1
```

```
^D
```

```
$ chmod u+x smallest
```

```
$
```



Give the user owner permission to run this file

Create your own commands

```
$ cat > smallest
```

```
wc -l *.pdb | sort | head -1
```

```
^D
```

```
$ chmod u+x smallest
```

```
$ ./smallest
```

Create your own commands

```
$ cat > smallest
```

```
wc -l *.pdb | sort | head -1
```

```
^D
```

```
$ chmod u+x smallest
```

```
$ ./smallest
```



Put ./ at the front to be sure of running
the `smallest` that it's *this* directory

Create your own commands

```
$ cat > smallest
```

```
wc -l *.pdb | sort | head -1
```

```
^D
```

```
$ chmod u+x smallest
```

```
$ ./smallest
```

```
9  methane.pdb
```

```
$
```

Create your own commands

```
$ cat > smallest
wc -l *.pdb | sort | head -1
^D
$ chmod u+x smallest
$ ./smallest
  9  methane.pdb
$
```

Try doing *that* with a desktop full of GUIs



created by

Greg Wilson

August 2010



Copyright © Software Carpentry 2010

This work is licensed under the Creative Commons Attribution License

See <http://software-carpentry.org/license.html> for more information.