

剪枝和再次训练

GUPAO TECH

秋如此愿景

推动每一次人才升级

我如此使命


让每个人的职业生涯不留遗憾

前请 入在 请在此处 文此 插入二维 字处 码




TAO 架构图

为应用在计算机视觉领域的深度学习工作流程,提供了全方位的便利工具





TAO 架构图





剪枝模型

```
!mkdir -p $LOCAL_EXPERIMENT_DIR/experiment_dir_pruned
```

```
!tao yolo_v4_tiny prune -m $USER_EXPERIMENT_DIR/experiment_dir_unpruned/weights/yolov4_cspdarknet_tiny_epoch_$EPOCH.tlt \
-e $SPECS_DIR/yolo_v4_tiny_train_kitti.txt \
-o $USER_EXPERIMENT_DIR/experiment_dir_pruned/yolov4_cspdarknet_tiny_pruned.tlt \
-eq intersection \
-pth 0.1 \
-k $KEY
```



在训练剪枝模型配置

7. Retrain pruned models

- · Model needs to be re-trained to bring back accuracy after pruning
- · Specify re-training specification
- . WARNING: training will take several hours or one day to complete

```
# Printing the retrain spec file.
# Here we have updated the spec file to include the newly pruned model as a pretrained weights.
!sed -i 's, EXPERIMENT_DIR,' "$USER_EXPERIMENT_DIR"',' $LOCAL_SPECS_DIR/yolo_v4_tiny_retrain_kitti.txt
!cat $LOCAL_SPECS_DIR/yolo_v4_tiny_retrain_kitti.txt
```

!mkdir -p \$LOCAL_EXPERIMENT_DIR/experiment_dir_retrain



在训练剪枝模型配置2

batch_size: 1

image_directory_path: "/workspace/tao-experiments/data/pingpang.v2i.coco/"

```
image_extension: "jpg"
target_class_mapping {
    key: "pingpang"
    value: "pingpang"
```



用剪枝后的模型做预训练模型在次训练

Now check the evaluation stats in the csv file and pick the model with highest eval accuracy.
!cat \$LOCAL_EXPERIMENT_DIR/experiment_dir_retrain/yolov4_training_log_cspdarknet_tiny.csv
%set_env EPOCH=080



评估模型

8. Evaluate retrained model

```
: !tao yolo_v4_tiny evaluate -e $SPECS_DIR/yolo_v4_tiny_retrain_kitti.txt \
-m $USER_EXPERIMENT_DIR/experiment_dir_retrain/weights/yolov4_cspdarknet_tiny_epoch_$EPOCH.tlt \
-k $KEY
```



验证推理数据准备

data





推理数据

9. Visualize inferences

In this section, we run the infer tool to generate inferences on the trained models and visualize the results.



谢谢观赏

GUPAO TECH



秋如此應景

推动每一次人才升级

我细的使命

让每个人的职业生涯不留遗憾

諭 请 入 在 请在此处 文 此 插入二维 字 处 码