192.168.3.202

docker run --name nginx-test -p 80:80 -d nginx
docker exec -it nginx-test /bin/bash
echo "192.168.3.202" >/usr/share/nginx/html/index.html

192.168.3.203

docker run --name nginx-test -p 80:80 -d nginx
docker exec -it nginx-test /bin/bash
echo "192.168.3.203" >/usr/share/nginx/html/index.html

lvs负载均衡器 系统: centos7.6 ip: 192.168.3.204

vip: 192.168.3.234

web服务器RS1 系统: centos7.6 ip: 192.168.3.205

web服务器RS2 系统: centos7.6 ip: 192.168.3.206

lvs负载均衡器

```
1 #注意 enp0s3 是网卡名称可以根据 ip a 查询
2 ifconfig enp0s3:0 192.168.3.234 netmask
255.255.255.0 up
3 #验证
4 ifconfig enp0s3:0
```

web服务器RS1

```
1 #安装Apache 服务器
 2 yum install -y httpd
 3 #验证
4 rpm -qa | grep httpd
 5 #启动服务
6 systemctl start httpd
 7 #新增index网页信息
8 echo "<h1>RS1<h1>" >/var/www/html/index.html
9 #抑制ARP
10 echo "1" >/proc/sys/net/ipv4/conf/lo/arp_ignore
11 echo "2" >/proc/sys/net/ipv4/conf/lo/arp_announce
12 echo "1" >/proc/sys/net/ipv4/conf/all/arp_ignore
13 echo "2"
   >/proc/sys/net/ipv4/conf/all/arp_announce
14 #添加回环地址
15 | ifconfig 10:0 192.168.3.234 netmask
   255.255.255.255 up
16 #验证
17 ifconfig lo:0
18
```

web服务器RS2

```
1 #安装Apache 服务器
  yum install -y httpd
 2
 3 #验证
 4 rpm -qa | grep httpd
  #启动服务
 6 systemctl start httpd
 7 #新增index网页信息
 8 echo "<h1>RS2<h1>" >/var/www/html/index.html
9 #抑制ARP
10 echo "1" >/proc/sys/net/ipv4/conf/lo/arp_ignore
11 echo "2" >/proc/sys/net/ipv4/conf/lo/arp_announce
12 echo "1" >/proc/sys/net/ipv4/conf/all/arp_ignore
  echo "2"
13
   >/proc/sys/net/ipv4/conf/all/arp_announce
14 #添加回环地址
15 ifconfig 10:0 192.168.3.234 netmask
   255.255.255.255 up
16 #验证
17 ifconfig lo:0
```

lvs负载均衡器

```
1 #清楚配置
2 ipvsadm -C
3
4 ipvsadm --set 30 5 60
5 ipvsadm -A -t 192.168.3.234:80 -s wrr
6 ipvsadm -a -t 192.168.3.234:80 -r
192.168.3.205:80 -g -w 1
7 ipvsadm -a -t 192.168.3.234:80 -r
192.168.3.206:80 -g -w 1
8 #验证
9 ipvsadm -L -n
10 #验证请求的地址
11 ipvsadm -Lc
```

周边语法

Lvs上删除虚拟服务

ipvsadm -D -t 192.168.3.234:80