
# Kirk-Rudy, Inc.

## Instruction and Parts Manual KR 618 Tilt Conveyor



#### Manufactured by Kirk-Rudy, Inc.

Before using this machine, all operators must study this manual to understand and follow the <u>safety warnings and instructions</u>. Keep these instructions with the machine for future reference. If you have any questions, contact your local Kirk-Rudy, Inc. Distributor.

		,

## TABLE OF CONTENTS

<u>SECTION</u>	DESCRIPTION	PAGE					
1	1 IMPORTANT SAFETY INSTRUCTIONS						
2	SPECIFICATIONS	4					
3	INSTALLATION 3.1 UNCRATING AND UNPACKING	5 5					
4	OPERATING INSTRUCTIONS 4.1 OPERATION	6 6					
5	MAINTENANCE 5.1 GENERAL MAINTENANCE 5.2 REPLACING AND ADJUSTING BELTS	7 7					
6	MECHANICAL PARTS AND DIAGRAMS	8					
7	ELECTRICAL SCHEMATIC	8					
8	APPENDIX	9					
9	NOTES	10					
10	WARRANTY AND SERVICE INFORMATION	11					

NOTE: FIGURES AND DIAGRAMS ARE NOT INCLUDED IN PAGE NUMBERS.

### 1 Important Safety Instructions

<u>Intended Use Statement:</u> The Kirk-Rudy Inc. 618 Tilt Conveyor is intended to be used with a Philipsburg Inserter at 90° and tilted to desired angle. The KR 618 can also be right-hand or left-hand.

#### SAVE THESE INSTRUCTIONS. Read all instructions before using this product.



## WARNING

- \* NEVER OPERATE THE MACHINE WITHOUT ALL GUARDS OR SAFETY DEVICES IN PLACE.
- \* ALWAYS TURN POWER OFF WHEN MAKING ADJUSTMENTS.
- \* ALWAYS DISCONNECT THE POWER SUPPLY BEFORE ANY MAINTENANCE OR SERVICE WORK.
- \* NEVER START THE MACHINE WITHOUT FIRST CHECKING ALL PERSONNEL ARE CLEAR OF MOVING PARTS.
- \* KEEP FINGERS CLEAR OF ALL MOVING PARTS.
- \* NEVER REMOVE THE PRODUCT FROM THE MACHINE WHILE MACHINE IS RUNNING.
- \* SHOULD MISFED PRODUCT JAM THE MACHINE AND STOP IT FROM RUNNING, ALWAYS PRESS THE STOP BUTTON BEFORE CLEARING PRODUCT. IF THE STOP BUTTON IS NOT PRESSED AND THE JAM IS CLEARED, THE MACHINE WILL BEGIN RUNNING.
- \* IT IS NOT RECOMMENDED THAT LOOSE CLOTHING, JEWELRY AND LONG HAIR BE WORN WHILE OPERATING THIS MACHINERY.
- \* ALWAYS USE AN EXPERIENCED ELECTRICIAN WHEN TROUBLE-SHOOTING ELECTRICAL PROBLEMS.
- \* CHANGES OR MODIFICATIONS TO THIS UNIT NOT EXPRESSLY APPROVED BY THE PARTY RESPONSIBLE FOR COMPLIANCE COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.

## **SPECIFICATIONS**

PRODUCT SIZE RANGE	English	Metric
Minimum Size:	3.5" W x 6" L	89 mm W x 152 mm L
Maximum Size:	6" W x 9" L	152 mm W x 229 mm L
MACHINE DATA	English	Metric
Length	75"	190.5 cm
Width	18"	45.7 cm
Height	28"-34.5"	71.1 cm - 87.6 cm
Tilt Angle from horizontal	approx. 60 degrees	
	<del>-</del>	
ELECTRICAL DATA		

110 AC, 60 Hz, Single Phase, 1 amp MDL

## 3 INSTALLATION

#### 3.1 UNCRATING AND UNPACKING



## **WARNING**

Read and follow all Safety Instructions in Section 1, Page 3 before proceeding.

- 1. Remove conveyor from crate.
- 2. Inspect for damage.
- 3. Locate and open spare parts box (usually shipped inside main machine).
- 4. Compare packing list with the enclosed items
- 5. Roll conveyor into place using the casters provided.

## 4 OPERATING INSTRUCTIONS

#### 4.1 **OPERATION**



## **WARNING**

Read and follow all Safety Instructions in Section 1, Page 3 before proceeding.

- 1. Roll conveyor 90° to other machine and lock castors.
- 2. Adjust height with bolts on conveyor legs to desired height.
- 3. Adjust tilt with bolts on conveyor support bracket (part #527530).
- 4. Plug into wall socket.
- 5. Turn conveyor on at electrical box.

#### 5 MAINTENANCE

#### 5.1 GENERAL MAINTENANCE



## **WARNING**

Read and follow all Safety Instructions in Section 1, Page 3 before proceeding.

Keep conveyor and moving parts free of dirt, dust and trash. Periodically lubricate chain with chain lubrication. Lightly oil rollers to prevent rusting. Replace belts as necessary.

#### 5.2 REPLACING AND ADJUSTING BELTS

- 1. Remove whale tail (part #531459-01).
- 2. Move the end roller in by loosening adjustment screws on both sides on conveyor.
- 3. Hold belts at joint and pull inward to provide slack.
- 4. Pull out wire in joint.
- 5. Reverse procedure to install new belt and remove slack from belts by tightening adjustment screws on end roller.


## 6 PARTS LIST AND DIAGRAMS


This section contains the assembly diagrams.


## 7 ELECTRICAL SCHEMATIC

The electrical schematic for the KR 618 conveyor is drawing #200 163 00 110.

		T .												• ***																۵			<del></del>		
- 0 -	ECN BY													(	~ ~			K			_(	(12)								D WHERE USED	NC .	OKGIA			241-01
7000	DESCRIPTION															/								7			مِـا	•		REO.D	KIRK - RUDY,	SAW, GE		I CONVEYOR	5385
	REV DATE NO				(	(1)		)					_					<b>,</b> -					// 			\		,			AND CONFIDENTIAL  OF THIS DRAWING  OOR REPRODUCED	TTEN PERMISSION	6A 30144 USA	AUUY, IIL	
					(	· ·	·)				_ <b>-</b> 1	//			,   	/		\						\	_	\ \_		( و			NO PORTION C	EXPRESS WRI	KENNE SAW,		DRAWING R
						( 14 )		/	Æ	<u>/</u>			[] []	L	) \	\		<u></u>						_			(15	)			THIRD ANGLE PROJECTION	‡ •	MODEL: V. V. V.	× × ×	SHEET NO.
			ı	<del></del>		T		(2)	\ 	1	T	1				(,		_					(,	_							× ×		NONE		XXX
							RT	LOCKING								LEGS	- 1	N N						(-	-		(	$\widehat{\mathbb{S}}$	)		MATERIAL:	HEAT TREAT.			
	N	22 . 500B NK	YOR	~	OUTFEED ROLLER	INFEED ROLLER	CONVEYOR SUPPORT			CONVEYOR SLIDE	OR	, CONVEYOR	WHALE TAIL	BELT GUIDE SHAFT	PLATE	VE YOR	ELEC. BOX	1 1 7 1 X N 1									<b>*</b>		0.125	1	DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED	.XX XXX ANG.	MOVE ALL BURRS AND	SHARP EDGES UNLESS OTHERWISE NOTED	ALL DIMENSIONS ARE FINISHED DIMENSIONS DO NOT SCALE - WORK TO DIMENSIONS ONLY
	DESCRIPTION	SPRKT, 35B22	18	ARM, ROLLER	ASSY, OUTF	١.	닏	100	MOTOR 1/15	CHANNEL, C	₩	SIDE GUIDE,	WLDMNT, WH	- 1	$\sim$			BELI, FLAI									1	5	SCALE		075 UNL		_00-		
	PART #	110758	527510	527513	527515			1-019061		527529-1	_	531456-01	531459-01					H	<u> </u>	4	)		(	7				<u> </u>			SCALE	DATE	13-Apr	oraci	
	I TEM OTY F	_	2 1 5	3 4	4	5	2			9 2 6			12 1 5	13 -	_	_		4													DRAWN BY:	CHECKED BY:		TOACO	











RSH REG'D WHERE USED 8 538236-0 6586 538236-0 S S S SHAFT CORRECTED PART 527533 WAS 527521 DESCRIPTION 90 I DE DRAWING . BELT 9-SEPT-00 DATE PROPRIETARY AND CONFIDENTIAL
NO PORTION OF THE PRODUCED
NAY BE OUGTED OR REPRODUCED
EXPRESS WITH THE PERMISSION
KINK NOTEN HIC.
KENESS WAS ASSOCIATED TO THE PERMISSION
KENESS WAS ASSOCIATED TO THE PERMISSION TO THE P 윤 ASSY, DRAWING . THIRD ANGLE PROJECTION SHEET NO. **(** ~  $\overset{\times}{\times}\overset{\times}{\times}$  $\times$   $\times$  $\times$   $\times$ HEAT TREAT: FINISH REMOVE ALL BURRS AND SHARP EDGES UNLESS OTHERWISE DIED ALL DIMENSIONS ARE FINISHED DIMENSIONS DO NOT SCALE - WORK TO DIMENSIONS ONLY DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED AMG. SPACER, BELT GUIDE . 005 SHAFT, BELT GUIDE ASSY, BELT GUIDE <u>-0</u> 11. DESCRIPTION 20 - Apr - 00 500 SCALE 0 . C MASTER 527522-A 527533 527534 PART JL 6 I TEM OTY CHECKED BY: TRACED BY: DRAWN BY:

DESCRIPTION	527522-A	DESCRIPTION ECK BY	KIRK - RUDY, INC.  KENNESAW, GEORGIA  BELT GUIDE  527522-A
DIMENSIONAL TOLERANCES  UNLESS OTHERWISE NOTE  I DIMENSIONAL TOLERANCES  I NT NT NMG.  I OSS STATE BURRS AND STATE BURRS AND STATE BURRS AND STATE BURS AND			CCTION PROPRIETARY AND CONFIDENTIAL NAT BE OUTTOON THIS DRAWING NAT HANT ORW. WITHOUT THE EXPRESSION OF KIRK-ROUT INC. KENNESAW, GA 30144 USA 1116:  DRAWING 1
		125x	MATERIAL: HEAT TREAT: FINISH:









.

## 8 APPENDIX

9	NOTES
***************************************	
**************************************	

#### 10 WARRANTY AND SERVICE

#### WARRANTY

**Warranty:** Kirk-Rudy, Inc., warrants to the original retail purchaser that this product is free from defects in the material and workmanship, and agrees to repair or replace, at Kirk-Rudy's option, any defective product within (90) days from the date of purchase. This warranty is not transferable. It covers damage resulting from defects in material or workmanship, and it does not cover conditions or malfunctions resulting from normal wear, neglect, abuse or accident.

THIS WARRANTY IS IN LIEU OF ALL OTHER EXPRESSED WARRANTIES ANY IMPLIED WARRANTY OF MERCHANTABLITIY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.

**Limitation of Remedies:** If product is proven to be defective within the warranty period stated above, THE EXCLUSIVE REMEDY, AT KIRK-RUDY'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE PRODUCT, provided that the defective product is, at Kirk-Rudy's choice, returned immediately to Kirk-Rudy or authorized service representative designated by Kirk-Rudy, or made available at user's premises in a location suitable for servicing.

**Limitation of Liability:** Kirk-Rudy shall not otherwise be liable for any losses or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted, including contract, negligence, warranty, or strict liability.

To obtain replacement parts and service, contact an Authorized Kirk-Rudy Dealer. Use Kirk-Rudy part numbers when ordering.

USE ONLY GENUINE KIRK-RUDY REPLACEMENT PARTS

*KIRK-RUDY, INC.*2700 KENNESAW DUE WEST ROAD
KENNESAW, GA. 30144
770-427-4203
FAX 770-427-4036