```
状态更新可以定义三个状态:Ready/NotReady/Error,代码中可以定义一个默认班级的容量:
比如 10 人,如果 ClassSize 小于 10,状态为 NotReady,
ClassSize 等于 10,状态为 Ready,
ClassSize 大于 10 状态为 Error。
```

```
apiVersion: school.crd.io/v1
kind: Class
motedate:
name: student
snee:
# Add fields here
className: "计算机应用二班"
eteacherName: "杰克"
replicas: 8
image: gdsz.harbor.com/library/myhttp:v1

ougon:school-operator JackHengs kubectl apply -f deploy/crds/school.crd.io_v1_class_cr.yaml
class.school.crd.io/student configured
```

## 小于 10 的状态为:NotReady

## 等于 10 的状态为:Ready

```
Class Name: 计算机应用二班
Class Page: gdsz.harbor.com/library/myhttp:v1
Replicas: 10
Teacher Name: 杰克
 us:

us:

us:

student-6b7597f46b-gb6k

student-6b7597f46b-k7hm-

student-6b7597f46b-mVpz

student-6b7597f46b-mVpz

student-6b7597f46b-nrVpz

student-6b7597f46b-ppp6

student-6b7597f46b-ppp6
```

## 大于 10 的状态为:Err

```
Labels: <none>
Annotations: kubectl.kubernetes.io/last-applied-configuration:
{"apiVersion":"school.crd.io/v1", "kind":"Class", "metadata":{"annotations":{}, "name":"student", "namespace":"default"}, "spec":{"className":"...
API Version: school.crd.io/v1
Kind: Class
Metadata:
Creation Timestown again.
     tetadata: Creation Timestamp: 2021-01-12T00:39:42Z

Generation: 18

Resource Version: 12275609

Self Link: 4apis/school.crd.io/Vl/namespaces/default/classes/student
UID: 8ec73c75-2829-4566-9412-faZef96a318b
   UID: 8ec73c75-2829-4566-9412-fa2etipec:
Class Name: 计算机应用二班
Image: gdsz.harbor.com/library/myhttp:vl
Replicas: 20
Teacher Name: 杰克
ictutus:
Pod Names:
student-6b7597f46b-6ffxr
student-6b7597f46b-7c66v
student-6b7597f46b-7c66v
student-6b7597f46b-7grtn
student-6b7597f46b-paz/k
student-6b7597f46b-paz/k
student-6b7597f46b-jbsff
student-6b7597f46b-jbsff
student-6b7597f46b-jbsff
student-6b7597f46b-mvlpz
student-6b7597f46b-mvlpz
student-6b7597f46b-nrvz
student-6b7597f46b-nrvz
```