Absolute scale velocity determination combining visual and inertial measurements for micro aerial vehicles

Jacques Kaiser
Supervised by Dr. Agostino Martinelli

INRIA

June 24, 2015

Micro aerial vehicles

Micro aerial vehicles

Micro aerial vehicles

Micro aerial vehicles



Micro aerial vehicles

Localization in **various environments**

Micro aerial vehicles

Localization in **various environments**

Micro aerial vehicles

Global Frame

A basic state vector:

$$X = \begin{bmatrix} position \\ velocity \\ orientation \end{bmatrix}$$

Localization in **various environments**

Micro aerial vehicles

Global Frame

A basic state vector:

$$X = \begin{bmatrix} position \\ velocity \\ orientation \end{bmatrix}$$

Localization in **various environments**

The goal of sensor fusion for state estimation is to **recover** X

Visual-inertial sensor fusion

Filter based method



Visual-inertial sensor fusion

Filter based method



Visual-inertial sensor fusion



Visual-inertial sensor fusion

Filter based method



How to recover the **initial state**?

Visual-inertial sensor fusion

Filter based method



How to recover the **initial state**?
We need a **deterministic solution**

Deterministic solutions in Computer Vision



Deterministic solutions in Computer Vision



But the relative **translation** and **distance to features** are recovered only **up to scale**

Absolute scale from visual measurements

How big is this building?

Absolute scale from visual measurements

Methods to recover the absolute scale

Methods to recover the absolute scale



Methods to recover the absolute scale



Methods to recover the absolute scale

Not suited to unknown environments



Not precise, works only in hover

Does not work in GPS denied environments

Inertial Measurement Unit (IMU)

The IMU consists of two sensors providing **physical quantities**:

- Accelerometer: linear acceleration (and gravity) (m/s^2);
- Gyroscope: angular velocity (rad/s).

Back to the title

Absolute scale velocity determination combining visual and inertial measurements for micro aerial vehicles

Back to the title

Absolute scale velocity determination combining visual and inertial measurements for micro aerial vehicles

Visual

Measurements

Inertial

Back to the title

Absolute scale velocity determination combining visual and inertial measurements for micro aerial vehicles



Back to the title

Absolute scale velocity determination combining visual and inertial measurements for micro aerial vehicles



Table of Contents

The closed-form solution

Transactions on Robotics (T-RO) 2012
International Journal of Computer Vision (IJCV) 2014

The Closed-Form Solution

Requires:

- Calibrated camera;
- Inertial Measurement Unit (IMU);
- External Camera IMU transformation.

Output:

- Initial velocity;
- Distance to point-features;
- Roll, pith.

The Closed-Form Solution

Requires:

- Calibrated camera;
- Inertial Measurement Unit (IMU);
- External Camera IMU transformation.

Output:

- Initial velocity;
- Distance to point-features;
- Roll, pith.

$$\Xi X = S$$

The Closed-Form Solution

Requires:

- Calibrated camera;
- Inertial Measurement Unit (IMU);
- External Camera IMU transformation.

Output:

- Initial velocity;
- Distance to point-features;
- Roll, pith.

$$\Xi X = S$$

Test setup

Test setup



Test setup



Test setup



Test setup



Test setup


Virtual
point-features
Speed ground
truth
Error
Speed
estimation

Test setup



Test setup



Problem: not robust in practice



Problem: not robust in practice



50% relative error on speed and distance estimation

Problem: not robust in practice



50% relative error on speed and distance estimation

"**A closed-form solution** *for state estimation with a visual-inertial system that does not require initialization was presented. However, this approach is* **not suitable for systems that rely on noisy sensor data**"

— Matthias Faessler, ICRA 2015

Improving the performance

What makes the estimations so bad?

Possible bottlenecks

- Motion;

Improving the performance

What makes the estimations so bad?

Possible bottlenecks

- Motion;
- Observed features;

Improving the performance

What makes the estimations so bad?

Possible bottlenecks

- Motion;
- Observed features;
- Noisy sensors.

Improving the performance

What makes the estimations so bad?

Possible bottlenecks

- Motion;
- Observed features;
- Noisy sensors.

Sensors provide measurements affected by a Gaussian noise:

$$N(\mu + B, \sigma^2)$$

Improving the performance

What makes the estimations so bad?

Possible bottlenecks

- Motion;
- Observed features;
- Noisy sensors.

Sensors provide measurements affected by a Gaussian noise:

$$N(\mu + B, \sigma^2)$$

We considered:

- Biased accelerometer;
- Biased gyroscope.

Biased inertial measurements

Speed estimation error



Varying accelerometer bias



Varying gyroscope bias

Estimating the gyroscope bias

Reminder: $\Xi X = S$

Estimating the gyroscope bias

Reminder: $\Xi X = S$

- Insert the gyro bias B in X;

Estimating the gyroscope bias

Reminder: $\Xi X = S$

- ~~Insert the gyro bias B in X;~~

Estimating the gyroscope bias

Reminder: $\Xi X = S$

- ~~Insert the gyro bias B in X;~~
- Alternative: non-linear minimization of the residual

$$cost(B) = \underset{X}{\operatorname{argmin}} ||\Xi X - S||^2$$

With:
B the gyroscope bias,

Ξ and S computed with respect to B

Estimating the gyroscope bias

Reminder: $\Xi X = S$

- ~~Insert the gyro bias B in X;~~
- Alternative: non-linear minimization of the residual

$$cost(B) = \underset{X}{\operatorname{argmin}} ||\Xi X - S||^2$$

With:
B the gyroscope bias,

Ξ and S computed with respect to B

Estimating the gyroscope bias

Reminder: $\Xi X = S$

- ~~Insert the gyro bias B in X;~~
- Alternative: non-linear minimization of the residual

$$cost(B) = \underset{X}{\operatorname{argmin}} ||\Xi X - S||^2$$

With:
B the gyroscope bias,

Ξ and S computed with respect to B



Cost function: residual with respect to gyroscope bias

Estimating the gyroscope bias

Reminder: $\Xi X = S$

- ~~Insert the gyro bias B in X;~~
- Alternative: non-linear minimization of the residual

$$cost(B) = \underset{X}{\operatorname{argmin}} ||\Xi X - S||^2$$

With:
B the gyroscope bias,

Ξ and S computed with respect to B



Cost function: residual with respect to gyroscope bias

Symmetry induced by the strong weight of the gravity

Dealing with the symmetry



Dealing with the symmetry



Dealing with the symmetry



Dealing with the symmetry



We tweak the cost function:

$$cost(B) = \underset{X}{\text{argmin}} \, ||\Xi X - S||^2 + \lambda \times |B|$$

Dealing with the symmetry



We tweak the cost function:

$$cost(B) = \underset{X}{\operatorname{argmin}} ||\Xi X - S||^2 + \lambda \times |B|$$



Regularized cost function with $\lambda = 3$

Results


Speed estimation error
Original CF
Modified CF
Kalman Filter
Error
Time (s)
1
0.9
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
13 14 15 16 17 18 19 20 21 22 23 24 25 26 27

Results



Moreover, our technique:

- Does not require initialization;
- Provides the gyroscope bias.

Conclusion

Conclusion

Theory:

Visual

Inertial

Conclusion

Theory:

Visual

Inertial

Practice:



Conclusion

Theory:

Visual

Inertial

Practice:

Acclerometer bias?



Gyroscope bias?



Conclusion

Theory:

Visual

Inertial

Practice:

Optimization to recover the gyroscope bias



Future work

Implementation on a real platform

Thank you for your attention,
Any question?

The Closed-Form Solution

Requires:

- Calibrated camera;
- Inertial Measurement Unit (IMU);
- External Camera IMU transformation.

Output:

- Initial velocity;
- Distance to point-features;
- Attitude.

The Closed-Form Solution

Requires:

- Calibrated camera;
- Inertial Measurement Unit (IMU);
- External Camera IMU transformation.

Output:

- Initial velocity;
- Distance to point-features;
- Attitude.

$$S_j = \lambda_1^i \mu_1^i - V t_j - G \frac{t_j^2}{2} - \lambda_j^i \mu_j^i$$

The Closed-Form Solution

Requires:

- Calibrated camera;
- Inertial Measurement Unit (IMU);
- External Camera IMU transformation.

Output:

- Initial velocity;
- Distance to point-features;
- Attitude.

$$S_j = \lambda_1^i \mu_1^i - V t_j - G \frac{t_j^2}{2} - \lambda_j^i \mu_j^i$$

The Overconstrained Linear System

$$S_j = \lambda_1^i \mu_1^i - V t_j - G \frac{t_j^2}{2} - \lambda_j^i \mu_j^i$$

Valid for every point-feature i at any time t_j:

The Overconstrained Linear System

$$S_j = \lambda_1^i \mu_1^i - V t_j - G \frac{t_j^2}{2} - \lambda_j^i \mu_j^i$$

Valid for every point-feature i at any time t_j:

$$\begin{bmatrix} S_2 = \lambda_1^1 \mu_1^1 - V t_2 - G \frac{t_2^2}{2} - \lambda_2^1 \mu_2^1 \\ S_2 = \lambda_1^2 \mu_1^2 - V t_2 - G \frac{t_2^2}{2} - \lambda_2^2 \mu_2^2 \\ \vdots \\ S_3 = \lambda_1^1 \mu_1^1 - V t_3 - G \frac{t_3^2}{2} - \lambda_3^1 \mu_3^1 \\ \vdots \\ S_N = \lambda_1^{n_i} \mu_1^{n_i} - V t_N - G \frac{t_N^2}{2} - \lambda_N^{n_i} \mu_N^{n_i} \end{bmatrix}$$

The Overconstrained Linear System

$$S_j = \lambda_1^i \mu_1^i - V t_j - G \frac{t_j^2}{2} - \lambda_j^i \mu_j^i$$

Valid for every point-feature i at any time t_j:

$$\begin{bmatrix} S_2 = \lambda_1^1 \mu_1^1 - V t_2 - G \frac{t_2^2}{2} - \lambda_2^1 \mu_2^1 \\ S_2 = \lambda_1^2 \mu_1^2 - V t_2 - G \frac{t_2^2}{2} - \lambda_2^2 \mu_2^2 \\ \vdots \\ S_3 = \lambda_1^1 \mu_1^1 - V t_3 - G \frac{t_3^2}{2} - \lambda_3^1 \mu_3^1 \\ \vdots \\ S_N = \lambda_1^{n_i} \mu_1^{n_i} - V t_N - G \frac{t_N^2}{2} - \lambda_N^{n_i} \mu_N^{n_i} \end{bmatrix}$$

$$\Xi X = S$$

Gyroscope bias estimation

Optimized Closed-form solution





Original Closed-form solution



Numerical stability

$$\left[\begin{array}{lcl} S_j & = & \lambda_1^1\mu_1^1 - Vt_j - G\frac{t_j^2}{2} - \lambda_j^1\mu_j^1 \\ 0_3 & = & \lambda_1^1\mu_1^1 - \lambda_j^1\mu_j^1 - \lambda_1^i\mu_1^i + \lambda_j^i\mu_j^i \end{array}\right.$$

$$S_j = \lambda_1^i\mu_1^i - Vt_j - G\frac{t_j^2}{2} - \lambda_j^i\mu_j^i$$