



CI/CD Pipelines

JAROD LATTA

SYSTEMS ARCHITECT, VISIMO



Who am I?

Jarod Latta


Graduated from Pitt, Fall 2020

BS of Computer Science from SCI

Minor in Linguistics

Certificate for Russian, Eastern European, and Eurasian
Studies

jarod@visimo.ai

The background of the slide features a close-up photograph of industrial infrastructure. It shows several large, horizontal pipes painted in a dark brown or black color. A vertical pipe runs along the right side of the frame. A pressure gauge with a white face and black markings is mounted on one of the horizontal pipes. The lighting is somewhat dim, creating a moody, industrial atmosphere.

What are
“pipelines”?

Introduction to Pipelines

Formally: “A CI/CD pipeline is a series of steps that must be performed in order to deliver a new version of software.” ~ [RedHat.com](https://www.redhat.com/en/topics/devops/continuous-integration-and-delivery)

Continuous Integration and Continuous Delivery (CI/CD) is a well-defined set of operating principles that enable application code to be delivered more frequently and more reliably.

- The implementation of CI/CD principles is called a **CI/CD pipeline**.
- Guiding idea: determine what must be done, automate it so that you never have to think about it again.

A **step** is a command. Example: `javac *.java`

Software **versions** are the artifact result of a pipeline. They are compiled source code, a built package, a Docker container, etc.

What does a
pipeline look
like?

In code...

Typically, pipelines are defined in YAML files

YAML is a file format that acts as a *superset* of JSON

- All JSON is valid YAML
- Not all YAML is valid JSON
- Consists of key value pairs
 - Values may be primitives (string, int, etc.) or objects

```
1  default:
2    image: python:3.9
3
4  stages:
5    - build
6    - test
7    - package
8    - deploy
9
10 variables:
11   PIP_CACHE_DIR: $CI_PROJECT_DIR/.cache/pip
12   PYTHON_PACKAGE_DIR: $CI_PROJECT_DIR/.cache/python-packages
13   REQUIREMENTS: requirements.txt
14   DEV_REQUIREMENTS: dev.requirements.txt
15
16 .pythonpath: &pythonpath
17 before_script:
18   - export PYTHONPATH="$PYTHON_PACKAGE_DIR"
19
20 .cache: &cache
21   key: $CI_COMMIT_REF_SLUG
22   policy: pull
23   paths:
24     - $PIP_CACHE_DIR
25     - $PYTHON_PACKAGE_DIR
26
27 build-dependencies:
28   stage: build
29   cache:
30     <<: *cache
31     policy: pull-push
32   artifacts:
33     expire_in: 1 day
34   paths:
35     - $PIP_CACHE_DIR
36     - $PYTHON_PACKAGE_DIR
37   before_script:
38     - pip install --upgrade pip
39     - rm -rf ${PIP_CACHE_DIR} ${PYTHON_PACKAGE_DIR}
40     - export PYTHONPATH="$PYTHON_PACKAGE_DIR"
41   script:
42     - pip install --progress-bar off --no-cache-dir --target ${PYTHON_PACKAGE_DIR} --requirement ${REQUIREMENTS}
```


Rendered graphically

Notice we are divided into 4 **stages** and each stage has at least one **job**.

A group of related **steps** (single commands) grouped together make up a **job**.

A group of **stages** make up the **pipeline**.

When two or more jobs share the same stage, they are independent of each other and may run *concurrently*.



How do we choose our steps?

Do it without the pipeline first!

Determine the minimum set of commands to accomplish three tasks:

- **Build** the testing environment from the external dependencies
 - These are Java Packages or Jar files, Python packages, C libraries, etc.
- **Test** the source code in the testing environment
 - In the simplest CI/CD pipelines, this is accomplished with unit tests
 - More complex examples include integration/end-to-end testing
- **Build** the source code into an artifact
 - In this context, an artifact is what the end user should be given access to such as a Jar file or a .class file
- **Publish/deploy** the artifact
 - This could be as simple as uploading your source code to GitHub in a .zip file as a “release” or more complicated like uploading to some sort of package registry

So, what do
we do with
this?