



API REFERENCE

TekTravels (TBO) Flight API

Request and response reference for all 19 flight APIs.

Prepared for	JackpotsWorld Tours & Travels
Supplier	TekTravels / Travel Boutique Online (TBO)
Version	1.0
Date	16 September 2026

Authentication and Logout are on `Sharedapi.tektravels.com`. The other 17 APIs are on `api.tektravels.com`. Every call is an HTTP POST with a JSON body and Content-Type: `application/json`.

All credentials, tokens, Tracelds, ResultIndex values, PNRs, booking ids and ticket numbers in the examples are placeholders. Use the credentials issued to the JackpotsWorld API account.

The largest responses — Search, SSR, Book, Ticket and GetBookingDetails — are shortened where a live payload repeats a structure. Each place this happens is marked.

Contents

API #1 — Authenticate	2
API #2 — Logout	4
API #3 — GetAgencyBalance	5
API #4 — Search	6
API #5 — Fare Upsell	10
API #6 — Advance Search	12
API #7 — Price RBD	14
API #8 — GetCalendarFare	16
API #9 — Update Calendar Fare of the Day	18
API #10 — FareRule	20
API #11 — FareQuote	22
API #12 — SSR	24
API #13 — Book	27
API #14 — Ticket	31
API #15 — GetBookingDetails	35
API #16 — ReleasePNRRequest	38
API #17 — SendChangeRequest	40
API #18 — GetChangeRequestStatus	42
API #19 — GetCancellationCharges	44

1

API #1 — Authenticate

POST

Endpoint	http://Sharedapi.tektravels.com/SharedData.svc/rest/Authenticate
Method	POST
Purpose	Returns the TokenId that every other API needs.
Call when	At start-up, and again when a call fails because the session has expired.

REQUEST JSON

```
{
  "ClientId": "ApiIntegrationNew",
  "UserName": "<agency-api-username>",
  "Password": "<agency-api-password>",
  "EndUserIp": "192.168.1.100"
}
```

RESPONSE JSON

```
{
  "Status": 1,
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "Error": {
    "ErrorCode": 0,
    "ErrorMessage": ""
  },
  "Member": {
    "MemberId": 111,
    "AgencyId": 222,
    "FirstName": "Operations",
    "LastName": "Desk",
    "Email": "ops@jackpotsworld.example",
    "LoginName": "jackpots-api",
    "LoginDetails": "Login Success",
    "isPrimaryAgent": false
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
ClientId	string	Yes	Constant supplied by TBO with the API account. Sandbox and production use different values.
UserName	string	Yes	API user name for the agency. This is not the B2B portal login.
Password	string	Yes	API password.
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.

OUTPUT FIELDS

Field	Type	Description
Status	int	1 means the login succeeded. Any other value means it failed.
TokenId	string	Session token. Send it in all 18 other APIs.
Error.ErrorCode	int	0 when there is no error.
Error.ErrorMessage	string	Reason for the failure.
Member.MemberId	int	Send as TokenMemberId in Logout.

Field	Type	Description
<code>Member.AgencyId</code>	int	Send as TokenAgencyId in Logout.
<code>Member.LoginName</code>	string	The account that was authenticated.
<code>Member.LoginDetails</code>	string	Login Success on a new session.
<code>Member.isPrimaryAgent</code>	bool	Whether this account is the primary agent.

WHERE THE VALUES COME FROM

Value	Comes from
<code>ClientId</code> , <code>UserName</code> , <code>Password</code>	Application configuration
<code>EndUserIp</code>	The server making the call

NEXT API

Search

NOTES

Cache the TokenId and reuse it. Do not authenticate on every search.

If a call fails with a session error, authenticate again and retry that call once.

2

API #2 — Logout

POST

Endpoint http://Sharedapi.tektravels.com/SharedData.svc/rest/Logout**Method** POST**Purpose** Closes the session and invalidates its TokenId.**Call when** On shutdown, or to force a new session.

REQUEST JSON

```
{
  "ClientId": "ApiIntegrationNew",
  "TokenAgencyId": "222",
  "TokenMemberId": "111",
  "EndUserIp": "192.168.1.100"
}
```

RESPONSE JSON

```
{
  "Status": 1,
  "Error": {
    "ErrorCode": 0,
    "ErrorMessage": ""
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
ClientId	string	Yes	Same constant used in Authenticate.
TokenAgencyId	string	Yes	Agency id of the session being closed.
TokenMemberId	string	Yes	Member id of the session being closed.
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.

OUTPUT FIELDS

Field	Type	Description
Status	int	1 means the session was closed.
Error.ErrorCode	int	0 when there is no error.
Error.ErrorMessage	string	Reason for the failure.

WHERE THE VALUES COME FROM

Value	Comes from
TokenAgencyId	Authenticate → Member.AgencyId
TokenMemberId	Authenticate → Member.MemberId

NEXT API

Authenticate, when a session is needed again

NOTES

One token is shared by the whole application. Calling Logout ends every search in progress, so do not call it between customer sessions.

3

API #3 — GetAgencyBalance

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/GetAgencyBalance
Method	POST
Purpose	Returns the agency deposit balance available for ticketing.
Call when	Before ticketing, and on a schedule for low-balance alerts.

REQUEST JSON

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5"
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": {
      "ErrorCode": 0,
      "ErrorMessage": ""
    },
    "Balance": 500000.00,
    "Currency": "INR"
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
Response.Balance	decimal	Funds available for ticketing.
Response.Currency	string	Currency of the balance, normally INR.
Response.Error	object	Error code and message.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId

NEXT API

Ticket

NOTES

Check the balance against the FareQuote OfferedFare before taking payment from the customer.

4

API #4 — Search

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/Search
Method	POST
Purpose	Returns the available flights and fares for a route and date. It also returns the TraceId and the ResultIndex values that the later calls need.
Call when	When the customer submits the search form.

REQUEST JSON

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "AdultCount": "1",
  "ChildCount": "0",
  "InfantCount": "0",
  "DirectFlight": false,
  "OneStopFlight": false,
  "JourneyType": "1",
  "PreferredAirlines": null,
  "Segments": [
    {
      "Origin": "HYD",
      "Destination": "DEL",
      "FlightCabinClass": "2",
      "PreferredDepartureTime": "2026-10-10T00:00:00",
      "PreferredArrivalTime": "2026-10-10T00:00:00"
    }
  ],
  "Sources": null
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "Origin": "HYD",
    "Destination": "DEL",
    "Results": [
      {
        "ResultIndex": "0B1",
        "Source": 6,
        "IsLCC": true,
        "IsRefundable": true,
        "IsPanRequiredAtBook": false,
        "IsPassportRequiredAtBook": false,
        "GSTAllowed": true,
        "ResultFareType": "RegularFare",
        "LastTicketDate": null,
        "TicketAdvisory": null,
        "Fare": {
          "Currency": "INR",
          "BaseFare": 5000,
          "Tax": 900,
          "YQTax": 0,
          "OtherCharges": 0,
          "Discount": 0,
          "PublishedFare": 5900,
          "CommissionEarned": 0,
          "PLBEarned": 0,

```

```

    "OfferedFare": 5900,
    "ServiceFee": 0,
    "TotalBaggageCharges": 0,
    "TotalMealCharges": 0,
    "TotalSeatCharges": 0
  },
  "FareBreakdown": [
    {
      "Currency": "INR",
      "PassengerType": 1,
      "PassengerCount": 1,
      "BaseFare": 5000,
      "Tax": 900,
      "YQTax": 0,
      "AdditionalTxnFeeOfrd": 0,
      "AdditionalTxnFeePub": 0
    }
  ],
  "Segments": [
    [
      {
        "TripIndicator": 1,
        "SegmentIndicator": 1,
        "Baggage": "15 KG",
        "CabinBaggage": "7 KG",
        "CabinClass": 2,
        "NoOfSeatAvailable": 9,
        "Duration": 130,
        "StopOver": false,
        "Airline": {
          "AirlineCode": "6E",
          "AirlineName": "IndiGo",
          "FlightNumber": "6523",
          "FareClass": "R0IP",
          "OperatingCarrier": "6E"
        },
        "Origin": {
          "Airport": {
            "AirportCode": "HYD",
            "AirportName": "Rajiv Gandhi International",
            "Terminal": "1",
            "CityCode": "HYD",
            "CityName": "Hyderabad",
            "CountryCode": "IN",
            "CountryName": "India"
          },
          "DepTime": "2026-10-10T06:15:00"
        },
        "Destination": {
          "Airport": {
            "AirportCode": "DEL",
            "AirportName": "Indira Gandhi International",
            "Terminal": "3",
            "CityCode": "DEL",
            "CityName": "Delhi",
            "CountryCode": "IN",
            "CountryName": "India"
          },
          "ArrTime": "2026-10-10T08:25:00"
        }
      }
    ]
  ],
  "MiniFareRules": [
    {
      "JourneyPoints": "HYD-DEL",
      "Type": "Cancellation",
      "From": "0",
      "To": "72",
    }
  ]
}

```

```

        "Unit": "Hours",
        "Details": "3500"
    }
  ]
}
]
}
}
}

```

Shortened to one flight with one segment. A live response contains every flight from every supplier enabled on the account.

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
AdultCount	string	Yes	12 years and above. Minimum 1.
ChildCount	string	Yes	2 to 11 years. Send "0" if there are none.
InfantCount	string	Yes	Under 2 years. Cannot be more than AdultCount.
DirectFlight	bool	No	true returns non-stop flights only.
OneStopFlight	bool	No	true returns flights with at most one stop.
JourneyType	string	Yes	1 One way, 2 Return, 3 Multi-stop, 4 Advance search, 5 Special return.
PreferredAirlines	string[]	No	Airline codes to restrict the search to, for example ["6E","AI"]. null returns all airlines.
Segments[].Origin	string	Yes	IATA code of the departure airport.
Segments[].Destination	string	Yes	IATA code of the arrival airport.
Segments[].FlightCabinClass	string	Yes	1 All, 2 Economy, 3 Premium Economy, 4 Business, 5 Premium Business, 6 First.
Segments[].PreferredDepartureTime	datetime	Yes	Departure date. The time part is normally 00:00:00.
Segments[].PreferredArrivalTime	datetime	Yes	Same as the departure date for a one-way leg.
Sources	string[]	No	Supplier sources to restrict the search to. null searches all enabled sources.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
Response.TraceId	string	Search session id. Required in FareRule, FareQuote, SSR, Book and Ticket.
Response.Results	array[][]	The outer array is the journey leg. The inner array holds the flight options for that leg.
..ResultIndex	string	Identifies one flight option.
..Source	int	Supplier code. Needed by ReleasePNRRequest.
..IsLCC	bool	true means a low-cost carrier: call Ticket directly. false means call Book first, then Ticket.
..IsRefundable	bool	Whether the fare is refundable.

Field	Type	Description
<code>..ResultFareType</code>	string	Fare brand, for example RegularFare.
<code>..IsPassportRequiredAtBook</code>	bool	true means passport fields are required in Book.
<code>..Fare.PublishedFare</code>	decimal	Gross fare before agency markup.
<code>..Fare.OfferedFare</code>	decimal	Net fare payable by the agency after commission and discount.
<code>..FareBreakdown[]</code>	array	Fare split by passenger type. Copy the matching entry into each passenger object in Book and Ticket.
<code>..Segments[][]</code>	array	The flight legs.
<code>....Airline.FlightNumber</code>	string	Flight number.
<code>....Origin.DepTime</code>	datetime	Departure time, local to the origin.
<code>....Destination.ArrTime</code>	datetime	Arrival time, local to the destination.
<code>....Baggage</code>	string	Checked baggage included in the fare.
<code>..MiniFareRules[]</code>	array	Short cancellation and change slabs, enough for a fare summary without calling FareRule.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId
Segments, passenger counts, JourneyType	The customer search form
EndUserId	The server making the call

NEXT API

FareRule, then FareQuote

NOTES

The Traceld expires after roughly 15 minutes. Run Search again if the customer has been idle on the results page.

Results is a two-dimensional array. For a return journey from an LCC source, Results[0] holds the onward options and Results[1] holds the return options.

Search fares are indicative. FareQuote confirms the fare before booking.

5

API #5 — Fare Upsell

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/FareUpsell
Method	POST
Purpose	Returns the other fare brands available on the selected flight, such as a flexible fare or one that includes baggage and a meal.
Call when	After the customer selects a flight, if you want to offer an upgrade.
Availability	Optional. Check that it is enabled on the account before building a flow that uses it.

REQUEST JSON

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
  "ResultIndex": "OB1"
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "Results": [
      {
        "ResultIndex": "OB1",
        "FareType": "RegularFare",
        "IsRefundable": true,
        "Fare": {
          "Currency": "INR",
          "BaseFare": 5000,
          "Tax": 900,
          "PublishedFare": 5900,
          "OfferedFare": 5900
        }
      },
      {
        "ResultIndex": "OB1-FLEX",
        "FareType": "FlexiFare",
        "IsRefundable": true,
        "Fare": {
          "Currency": "INR",
          "BaseFare": 6500,
          "Tax": 900,
          "PublishedFare": 7400,
          "OfferedFare": 7400
        }
      }
    ]
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
TraceId	string	Yes	TraceId of the Search that returned this ResultIndex.

Field	Type	Req	Description
ResultIndex	string	Yes	The flight the customer selected.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
Response.TraceId	string	The search session.
Response.Results[]	array	One entry per fare brand.
..ResultIndex	string	The ResultIndex for this brand. It replaces the original one if the customer selects it.
..FareType	string	Brand name to display.
..IsRefundable	bool	Whether this brand is refundable.
..Fare	object	Fare for this brand, same shape as in Search.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId
TraceId	Search → Response.TraceId
ResultIndex	Search → the flight the customer selected

NEXT API

FareQuote, using the ResultIndex of the selected brand

NOTES

If the customer changes brand, send the ResultIndex from that entry to FareQuote. Sending the original one prices the original fare.

6

API #6 — Advance Search

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/AdvanceSearch
Method	POST
Purpose	Search with booking-class level control, for corporate fares, a specific RBD, or negotiated inventory.
Call when	Only for flows that need class-level control. Normal B2C traffic uses Search.
Availability	Optional. Check that it is enabled on the account before building a flow that uses it.

REQUEST JSON

```
{
  "EndUserId": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "AdultCount": "1",
  "ChildCount": "0",
  "InfantCount": "0",
  "JourneyType": "1",
  "PreferredAirlines": ["6E"],
  "Segments": [
    {
      "Origin": "HYD",
      "Destination": "DEL",
      "FlightCabinClass": "2",
      "PreferredDepartureTime": "2026-10-10T00:00:00",
      "PreferredArrivalTime": "2026-10-10T00:00:00"
    }
  ]
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "Results": [
      {
        "ResultIndex": "0B1",
        "Source": 6,
        "IsLCC": true,
        "AirlineCode": "6E",
        "FlightNumber": "6523",
        "RBD": "R",
        "Fare": {
          "Currency": "INR",
          "BaseFare": 5000,
          "Tax": 900,
          "OfferedFare": 5900
        }
      }
    ]
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
EndUserId	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.

Field	Type	Req	Description
AdultCount	string	Yes	12 years and above. Minimum 1.
ChildCount	string	Yes	2 to 11 years.
InfantCount	string	Yes	Under 2 years.
JourneyType	string	Yes	1 One way, 2 Return, 3 Multi-stop, 4 Advance search, 5 Special return.
PreferredAirlines	string[]	No	Airline codes to restrict the search to.
Segments[]	array	Yes	Same segment object as Search: Origin, Destination, FlightCabinClass, PreferredDepartureTime, PreferredArrivalTime.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
Response.TraceId	string	Search session id for the later calls.
Response.Results[]	array	Matching flights.
..ResultIndex	string	Identifies one flight option.
..Source	int	Supplier code.
..IsLCC	bool	Selects the Ticket-only or Book-then-Ticket path.
..RBD	string	Booking class the fare was returned in.
..Fare	object	Fare for the flight.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId
Search criteria	The customer form, plus the class constraint

NEXT API

Price RBD, then FareQuote

NOTES

This API is not enabled on every account. Check before building a flow that uses it.

7

API #7 — Price RBD

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/PriceRBD
Method	POST
Purpose	Prices a specific booking class on a flight returned by Advance Search.
Call when	Between Advance Search and FareQuote, when the booking class matters.
Availability	Optional. Check that it is enabled on the account before building a flow that uses it.

REQUEST JSON

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
  "ResultIndex": "0B1"
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "Results": [
      {
        "ResultIndex": "0B1",
        "RBD": "Y",
        "CabinClass": 2,
        "NoOfSeatAvailable": 9,
        "Fare": {
          "Currency": "INR",
          "BaseFare": 5000,
          "Tax": 900,
          "PublishedFare": 5900,
          "OfferedFare": 5900
        }
      }
    ]
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
TraceId	string	Yes	TraceId of the Search that returned this ResultIndex.
ResultIndex	string	Yes	The flight the customer selected.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
Response.Results[].RBD	string	The booking class that was priced.
..CabinClass	int	1 All, 2 Economy, 3 Premium Economy, 4 Business, 5 Premium Business, 6 First.

Field	Type	Description
<code>..NoOfSeatAvailable</code>	int	Seats bookable in this class.
<code>..Fare</code>	object	Fare for the class.

WHERE THE VALUES COME FROM

Value	Comes from
<code>TokenId</code>	Authenticate → <code>TokenId</code>
<code>TraceId</code>	Advance Search → <code>Response.TraceId</code>
<code>ResultIndex</code>	Advance Search → <code>Results[].ResultIndex</code>

NEXT API

FareQuote

8

API #8 — GetCalendarFare

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/GetCalendarFare
Method	POST
Purpose	Returns the lowest fare per departure date across a range, for a flexible-date view or a cheapest-day calendar.
Call when	On the search page, when the customer has not fixed a date.
Availability	Optional. Check that it is enabled on the account before building a flow that uses it.

REQUEST JSON

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "JourneyType": "1",
  "Segments": [
    {
      "Origin": "HYD",
      "Destination": "DEL",
      "FlightCabinClass": "2",
      "PreferredDepartureTime": "2026-10-10T00:00:00",
      "PreferredArrivalTime": "2026-10-10T00:00:00"
    }
  ]
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "CalendarFare": [
      { "DepartureDate": "2026-10-10", "Fare": 5900, "Currency": "INR" },
      { "DepartureDate": "2026-10-11", "Fare": 5400, "Currency": "INR" },
      { "DepartureDate": "2026-10-12", "Fare": 4800, "Currency": "INR" },
      { "DepartureDate": "2026-10-13", "Fare": 6100, "Currency": "INR" }
    ]
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
JourneyType	string	Yes	1 One way, 2 Return, 3 Multi-stop, 4 Advance search, 5 Special return.
Segments[].Origin	string	Yes	IATA code of the departure airport.
Segments[].Destination	string	Yes	IATA code of the arrival airport.
Segments[].FlightCabinClass	string	Yes	1 All, 2 Economy, 3 Premium Economy, 4 Business, 5 Premium Business, 6 First.
Segments[].PreferredDepartureTime	datetime	Yes	The anchor date. The response covers the dates around it.
Segments[].PreferredArrivalTime	datetime	Yes	Same as the anchor date.

OUTPUT FIELDS

Field	Type	Description
<code>Response.ResponseStatus</code>	int	1 means the call succeeded.
<code>Response.CalendarFare[]</code>	array	One entry per departure date.
<code>..DepartureDate</code>	date	The date the fare applies to.
<code>..Fare</code>	decimal	Lowest fare found for that date.
<code>..Currency</code>	string	Currency of the fare.

WHERE THE VALUES COME FROM

Value	Comes from
<code>TokenId</code>	Authenticate → <code>TokenId</code>
<code>Route and cabin</code>	The customer search form

NEXT API

Search, for the date the customer picks

NOTES

Calendar fares are cached and indicative. Run a normal Search for the selected date to get a bookable fare.

9

API #9 — Update Calendar Fare of the Day

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/UpdateCalendarFareOfDay
Method	POST
Purpose	Refreshes the cached calendar fare for one date.
Call when	When a calendar entry is stale, or on a scheduled refresh of the routes the site promotes.
Availability	Optional. Check that it is enabled on the account before building a flow that uses it.

REQUEST JSON

```
{
  "EndUserId": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "JourneyType": "1",
  "Segments": [
    {
      "Origin": "HYD",
      "Destination": "DEL",
      "FlightCabinClass": "2",
      "PreferredDepartureTime": "2026-10-12T00:00:00",
      "PreferredArrivalTime": "2026-10-12T00:00:00"
    }
  ]
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "CalendarFare": {
      "DepartureDate": "2026-10-12",
      "Fare": 4800,
      "Currency": "INR"
    }
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
EndUserId	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
JourneyType	string	Yes	1 One way, 2 Return, 3 Multi-stop, 4 Advance search, 5 Special return.
Segments[]	array	Yes	One segment giving the route, cabin and the date to refresh.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
Response.CalendarFare	object	The refreshed fare for that date.
..DepartureDate	date	The date that was refreshed.

Field	Type	Description
..Fare	decimal	Updated fare.
..Currency	string	Currency of the fare.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId
Date and route	The calendar entry being refreshed

NEXT API

Search, for the refreshed date

10

API #10 — FareRule

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/FareRule
Method	POST
Purpose	Returns the airline fare rules for the selected flight: cancellation and change penalties, no-show terms and the fare basis code.
Call when	When the customer opens the fare rules panel.

REQUEST JSON

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
  "ResultIndex": "0B1"
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "FareRules": [
      {
        "Airline": "6E",
        "Origin": "HYD",
        "Destination": "DEL",
        "FareBasisCode": "R0IP",
        "FareRestriction": null,
        "FareFamilyCode": "",
        "FareRuleDetail": "CANCELLATION: INR 3500. NO SHOW: nil refund. CHANGE: INR 3000 + fare diff."
      }
    ]
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
TraceId	string	Yes	TraceId of the Search that returned this ResultIndex.
ResultIndex	string	Yes	The flight the customer selected.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
Response.FareRules[]	array	One entry per priced sector.
..Airline	string	Airline the rule belongs to.
..Origin	string	Origin of the sector the rule applies to.
..Destination	string	Destination of the sector.

Field	Type	Description
<code>..FareBasisCode</code>	string	Fare basis the rule was filed under. Worth storing on the booking record.
<code>..FareRestriction</code>	string	Restrictions on the fare, when filed.
<code>..FareRuleDetail</code>	string	The rule text. Free text written by the airline, often with line breaks and HTML.

WHERE THE VALUES COME FROM

Value	Comes from
<code>TokenId</code>	Authenticate → <code>TokenId</code>
<code>TraceId</code>	Search → <code>Response.TraceId</code>
<code>ResultIndex</code>	Search → the flight the customer selected

NEXT API

FareQuote

NOTES

Sanitise `FareRuleDetail` before displaying it. It arrives with embedded markup.

Do not read refund amounts out of the rule text. Use `GetCancellationCharges` for that.

11

API #11 — FareQuote

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/FareQuote
Method	POST
Purpose	Re-prices the selected flight against live inventory and confirms it is still available at that fare.
Call when	Before showing the payment screen. Required.

REQUEST JSON

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
  "ResultIndex": "0B1"
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "IsPriceChanged": false,
    "Results": {
      "ResultIndex": "0B1",
      "Source": 6,
      "IsLCC": true,
      "IsRefundable": true,
      "IsPanRequiredAtBook": false,
      "IsPassportRequiredAtBook": false,
      "IsPassportRequiredAtTicket": false,
      "IsGSTMandatory": false,
      "ResultFareType": "RegularFare",
      "LastTicketDate": null,
      "Fare": {
        "Currency": "INR",
        "BaseFare": 5000,
        "Tax": 900,
        "YQTax": 0,
        "OtherCharges": 0,
        "Discount": 0,
        "PublishedFare": 5900,
        "OfferedFare": 5900,
        "ServiceFee": 0
      }
    },
    "FareBreakdown": [
      {
        "Currency": "INR",
        "PassengerType": 1,
        "PassengerCount": 1,
        "BaseFare": 5000,
        "Tax": 900,
        "YQTax": 0,
        "AdditionalTxnFeeOfrd": 0,
        "AdditionalTxnFeePub": 0
      }
    ],
    "Segments": [[ "... same shape as Search ..." ]]
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
TraceId	string	Yes	TraceId of the Search that returned this ResultIndex.
ResultIndex	string	Yes	The flight the customer selected.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
Response.IsPriceChanged	bool	true means the fare has changed since Search.
Results.ResultIndex	string	Confirmed flight identifier. Use this one from here on.
Results.IsLCC	bool	true means call Ticket directly. false means call Book first, then Ticket. Use this value rather than the one from Search.
Results.IsRefundable	bool	Whether the confirmed fare is refundable.
Results.IsPanRequiredAtBook	bool	true means PAN is required in Book.
Results.IsPassportRequiredAtBook	bool	true means passport details are required in Book.
Results.IsPassportRequiredAtTicket	bool	true means passport details are required in Ticket.
Results.IsGSTMandatory	bool	true means GST details are required.
Results.LastTicketDate	datetime	Deadline for ticketing a held Non-LCC booking.
Results.Fare.OfferedFare	decimal	Confirmed net fare. Reconcile the agency debit against this.
Results.FareBreakdown[]	array	Fare by passenger type. Copy the matching entry into each passenger object in Book and Ticket.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId
TraceId	Search → Response.TraceId
ResultIndex	Search, or Fare Upsell if the customer changed brand

NEXT API

SSR if you offer extras, then Ticket for LCC or Book for Non-LCC

NOTES

If IsPriceChanged is true, show the new fare and get the customer to confirm before charging.

IsPanRequiredAtBook, IsPassportRequiredAtBook and IsGSTMandatory tell you which fields the passenger form has to collect. Read them here instead of hard-coding rules per airline.

12

API #12 — SSR

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/SSR
Method	POST
Purpose	Returns the seats, meals and extra baggage available for purchase on the flight, with prices and codes.
Call when	After FareQuote, on the extras screen.

REQUEST JSON

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
  "ResultIndex": "0B1"
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "SeatDynamic": [
      {
        "SegmentSeat": [
          {
            "RowSeats": [
              {
                "Seats": [
                  {
                    "AirlineCode": "6E",
                    "FlightNumber": "6523",
                    "Origin": "HYD",
                    "Destination": "DEL",
                    "Code": "12A",
                    "RowNo": "12",
                    "SeatNo": "A",
                    "SeatType": 1,
                    "SeatWayType": 2,
                    "AvailabilityType": 1,
                    "Price": 350,
                    "Currency": "INR"
                  }
                ]
              }
            ]
          }
        ]
      }
    ],
    "MealDynamic": [
      {
        "AirlineCode": "6E",
        "FlightNumber": "6523",
        "Origin": "HYD",
        "Destination": "DEL",
        "Code": "VGML",
        "Description": 2,
        "AirlineDescription": "Vegetarian Meal",
        "Quantity": 1,
        "Price": 250,
        "Currency": "INR"
      }
    ]
  }
}
```

```

    }
  ],
  "Baggage": [
    [
      {
        "AirlineCode": "6E",
        "FlightNumber": "6523",
        "Origin": "HYD",
        "Destination": "DEL",
        "Code": "XBPD",
        "Description": 2,
        "Weight": 5,
        "Price": 1000,
        "Currency": "INR"
      }
    ]
  ]
}

```

The seat map is nested four levels deep: SeatDynamic, SegmentSeat, RowSeats, Seats. Flatten it per segment before rendering.

INPUT FIELDS

Field	Type	Req	Description
EndUserId	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
TraceId	string	Yes	TraceId of the Search that returned this ResultIndex.
ResultIndex	string	Yes	The flight the customer selected.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
Response.SeatDynamic[]	array	Seat map, nested by segment and row. Empty if the airline does not sell seats through the API.
..Code	string	Seat code, for example 12A.
..RowNo	string	Row number.
..SeatNo	string	Seat letter.
..AvailabilityType	int	Whether the seat can be sold. Occupied seats are returned as well.
..Price	decimal	Seat charge, added to the fare.
Response.MealDynamic[][]	array	Meals available, per segment.
..Code	string	Meal code, for example VGML. Send it back unchanged in Book or Ticket.
..AirlineDescription	string	Label to display to the customer.
Response.Baggage[][]	array	Extra baggage units, per segment.
..Code	string	Baggage code. Send it back unchanged in Book or Ticket.
..Weight	int	Extra weight in kilograms.
..Price	decimal	Charge for the unit.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId
TraceId	Search → Response.TraceId
ResultIndex	The flight confirmed by FareQuote

NEXT API

Ticket for LCC, or Book for Non-LCC

NOTES

Every extra the customer selects has to be included in the matching passenger object in Book or Ticket. Extras that are not sent are not sold.

Empty SeatDynamic, MealDynamic and Baggage arrays are normal. Some airlines do not sell extras through the API.

Book and Ticket return SSRDenied. The airline can accept the booking and still refuse an extra.

13

API #13 — Book

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/Book
Method	POST
Purpose	Creates the airline PNR and holds the seats for a Non-LCC flight. It does not issue a ticket.
Call when	For Non-LCC flights only, after FareQuote. LCC flights skip this call.

REQUEST JSON

```
{
  "EndUserId": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
  "ResultIndex": "0B1",
  "Passengers": [
    {
      "Title": "Mr",
      "FirstName": "Rahul",
      "LastName": "Kumar",
      "PaxType": 1,
      "DateOfBirth": "1992-05-10T00:00:00",
      "Gender": 1,
      "PassportNo": "",
      "PassportExpiry": "",
      "AddressLine1": "Plot 14, Banjara Hills",
      "AddressLine2": "",
      "City": "Hyderabad",
      "CountryCode": "IN",
      "CountryName": "India",
      "Nationality": "IN",
      "ContactNo": "9876543210",
      "Email": "rahul@example.com",
      "IsLeadPax": true,
      "FFAirlineCode": null,
      "FFNumber": "",
      "GSTCompanyName": "",
      "GSTNumber": "",
      "GSTCompanyAddress": "",
      "GSTCompanyContactNumber": "",
      "GSTCompanyEmail": "",
      "Fare": {
        "Currency": "INR",
        "BaseFare": 5000,
        "Tax": 900,
        "YQTax": 0,
        "AdditionalTxnFeeOfrd": 0,
        "AdditionalTxnFeePub": 0,
        "PGCharge": 0
      }
    }
  ]
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "IsPriceChanged": false,
    "IsTimeChanged": false,
    "SSRDenied": false,
    "SSRMessage": ""
  }
}
```

```

"Status": 1,
"FlightItinerary": {
  "BookingId": 1288527,
  "PNR": "ABC123",
  "IsDomestic": true,
  "Source": 4,
  "Origin": "HYD",
  "Destination": "DEL",
  "AirlineCode": "AI",
  "ValidatingAirlineCode": "AI",
  "LastTicketDate": "2026-10-08T23:59:00",
  "IsLCC": false,
  "NonRefundable": false,
  "Fare": {
    "Currency": "INR",
    "BaseFare": 5000,
    "Tax": 900,
    "PublishedFare": 5900,
    "OfferedFare": 5900
  },
  "Passenger": [
    {
      "PaxId": 1,
      "Title": "Mr",
      "FirstName": "Rahul",
      "LastName": "Kumar",
      "PaxType": 1,
      "IsLeadPax": true,
      "Ticket": null
    }
  ],
  "Segments": [ "... same shape as Search ..." ]
}
}
}

```

INPUT FIELDS

Field	Type	Req	Description
EndUserId	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
TraceId	string	Yes	TraceId of the Search that returned this ResultIndex.
ResultIndex	string	Yes	The flight the customer selected.
Passengers[].Title	string	Yes	Mr, Mrs, Ms, Miss or Mstr. It has to agree with Gender and PaxType.
Passengers[].FirstName	string	Yes	Given name as printed on the ID.
Passengers[].LastName	string	Yes	Surname as printed on the ID.
Passengers[].PaxType	int	Yes	1 Adult, 2 Child, 3 Infant.
Passengers[].DateOfBirth	datetime	Yes	Required for child and infant, and for most international adult fares.
Passengers[].Gender	int	Yes	1 Male, 2 Female.
Passengers[].PassportNo	string	Cond.	Required when FareQuote returned IsPassportRequiredAtBook as true.
Passengers[].PassportExpiry	datetime	Cond.	Required with PassportNo.
Passengers[].AddressLine1	string	Yes	Billing address.
Passengers[].City	string	Yes	Billing city.

Field	Type	Req	Description
<code>Passengers[].CountryCode</code>	string	Yes	Two-letter country code, e.g. IN.
<code>Passengers[].CountryName</code>	string	Yes	Country name.
<code>Passengers[].Nationality</code>	string	Cond.	Two-letter code. Required on international flights.
<code>Passengers[].ContactNo</code>	string	Yes	Contact number for the lead passenger.
<code>Passengers[].Email</code>	string	Yes	Contact email for the lead passenger.
<code>Passengers[].IsLeadPax</code>	bool	Yes	Exactly one passenger in the array must be true.
<code>Passengers[].FFAirlineCode</code>	string	No	Frequent flyer airline code.
<code>Passengers[].FFNumber</code>	string	No	Frequent flyer number.
<code>Passengers[].GSTNumber</code>	string	Cond.	Required with the other GST fields when <code>IsGSTMandatory</code> is true.
<code>Passengers[].Fare</code>	object	Yes	The <code>FareBreakdown</code> entry from <code>FareQuote</code> for this passenger type, not the whole-flight fare.

OUTPUT FIELDS

Field	Type	Description
<code>Response.ResponseStatus</code>	int	1 means the call succeeded.
<code>Response.Status</code>	int	0 Failed, 1 Successful, 2 Not saved, 3 Not created, 4 Not allowed, 5 Flown, 6 Partially cancelled, 7 Cancelled.
<code>Response.IsPriceChanged</code>	bool	true means the fare changed. The PNR is held at the new fare.
<code>Response.IsTimeChanged</code>	bool	true means the schedule changed.
<code>Response.SSRDenied</code>	bool	true means the booking succeeded but one or more extras were refused.
<code>Response.SSRMessage</code>	string	Which extras were refused, and why.
<code>FlightItinerary.BookingId</code>	int	TBO booking id. Store it against the order.
<code>FlightItinerary.PNR</code>	string	Airline record locator for the held booking.
<code>FlightItinerary.Source</code>	int	Supplier code. Needed by <code>ReleasePNRRequest</code> .
<code>FlightItinerary.LastTicketDate</code>	datetime	Deadline for ticketing. The airline cancels the hold after this.
<code>FlightItinerary.IsLCC</code>	bool	false for any booking made through this API.
<code>FlightItinerary.Passenger[].PaxId</code>	int	Per-passenger id, used for a partial cancellation.
<code>FlightItinerary.Passenger[].Ticket</code>	object	null at this point. It is filled in after <code>Ticket</code> succeeds.

WHERE THE VALUES COME FROM

Value	Comes from
<code>TokenId</code>	Authenticate → <code>TokenId</code>
<code>TraceId</code>	Search → <code>Response.TraceId</code>
<code>ResultIndex</code>	FareQuote → <code>Results.ResultIndex</code>
<code>Passengers[].Fare</code>	FareQuote → <code>Results.FareBreakdown[]</code> for that <code>PaxType</code>
Passenger details	The passenger form
SSR selections	SSR → the codes the customer chose

NEXT API

Ticket, or ReleasePNRRRequest if the booking will not be ticketed

NOTES

Book is for Non-LCC only. Calling it for an LCC flight fails.

A held booking has to end in either a Ticket call or a ReleasePNRRRequest. Store BookingId, Source and LastTicketDate, and release holds that are near the deadline.

Passenger names must match the ID document. Name changes are chargeable and some airlines do not allow them at all.

14

API #14 — Ticket

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/Ticket
Method	POST
Purpose	Issues the ticket. For LCC it books and issues in one call. For Non-LCC it issues against the PNR that Book created.
Call when	LCC: after FareQuote and SSR. Non-LCC: after Book, before LastTicketDate.

REQUEST JSON — LCC (BOOKS AND ISSUES IN ONE CALL)

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
  "ResultIndex": "0B1",
  "IsPriceChangeAccepted": false,
  "Passengers": [
    {
      "Title": "Mr",
      "FirstName": "Rahul",
      "LastName": "Kumar",
      "PaxType": 1,
      "DateOfBirth": "1992-05-10T00:00:00",
      "Gender": 1,
      "AddressLine1": "Plot 14, Banjara Hills",
      "City": "Hyderabad",
      "CountryCode": "IN",
      "CountryName": "India",
      "Nationality": "IN",
      "ContactNo": "9876543210",
      "Email": "rahul@example.com",
      "IsLeadPax": true,
      "Fare": {
        "Currency": "INR",
        "BaseFare": 5000,
        "Tax": 900,
        "YQTax": 0,
        "AdditionalTxnFeeOfrd": 0,
        "AdditionalTxnFeePub": 0
      },
      "Baggage": [
        {
          "AirlineCode": "6E",
          "FlightNumber": "6523",
          "Origin": "HYD",
          "Destination": "DEL",
          "Code": "XBPD",
          "Weight": 5,
          "Price": 1000,
          "Currency": "INR"
        }
      ],
      "MealDynamic": [
        {
          "AirlineCode": "6E",
          "FlightNumber": "6523",
          "Origin": "HYD",
          "Destination": "DEL",
          "Code": "VGML",
          "AirlineDescription": "Vegetarian Meal",
          "Quantity": 1,
          "Price": 250,
          "Currency": "INR"
        }
      ]
    }
  ],
}
```

```

    "SeatDynamic": [
      {
        "AirlineCode": "6E",
        "FlightNumber": "6523",
        "Origin": "HYD",
        "Destination": "DEL",
        "Code": "12A",
        "RowNo": "12",
        "SeatNo": "A",
        "Price": 350,
        "Currency": "INR"
      }
    ]
  }
}

```

REQUEST JSON — NON-LCC (ISSUES AGAINST A HELD PNR)

```

{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
  "PNR": "ABC123",
  "BookingId": 1288527,
  "IsPriceChangeAccepted": false,
  "Passport": []
}

```

RESPONSE JSON

```

{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "IsPriceChanged": false,
    "IsTimeChanged": false,
    "SSRDenied": false,
    "SSRMessage": "",
    "Status": 1,
    "FlightItinerary": {
      "BookingId": 1288527,
      "PNR": "ABC123",
      "IsDomestic": true,
      "Source": 6,
      "Origin": "HYD",
      "Destination": "DEL",
      "AirlineCode": "6E",
      "ValidatingAirlineCode": "6E",
      "IsLCC": true,
      "NonRefundable": false,
      "Fare": {
        "Currency": "INR",
        "BaseFare": 5000,
        "Tax": 900,
        "PublishedFare": 5900,
        "OfferedFare": 5900,
        "TotalBaggageCharges": 1000,
        "TotalMealCharges": 250,
        "TotalSeatCharges": 350
      }
    },
    "Passenger": [
      {
        "PaxId": 1,
        "Title": "Mr",
        "FirstName": "Rahul",
        "LastName": "Kumar",

```

```

    "PaxType": 1,
    "IsLeadPax": true,
    "Ticket": {
      "TicketId": 1569310,
      "TicketNumber": "0982416789012",
      "Status": "Ticketed",
      "IssueDate": "2026-09-16T11:42:00",
      "ValidatingAirline": "6E"
    }
  ],
  "Segments": [ "... same shape as Search ..." ]
}
}
}

```

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
TraceId	string	Yes	TraceId of the Search that returned this ResultIndex.
ResultIndex	string	LCC	LCC only. The flight confirmed by FareQuote.
Passengers[]	array	LCC	LCC only. Same passenger object as Book, plus Baggage, MealDynamic and SeatDynamic holding the selected extras.
PNR	string	Non-LCC	Non-LCC only. The record locator from Book.
BookingId	int	Non-LCC	Non-LCC only. The booking id from Book.
Passport	array	Cond.	Non-LCC. Passport details when the fare requires them at ticketing.
IsPriceChangeAccepted	bool	No	Send true only when the customer has agreed to a fare increase.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
Response.Status	int	0 Failed, 1 Successful, 2 Not saved, 3 Not created, 4 Not allowed, 5 Flown, 6 Partially cancelled, 7 Cancelled.
Response.IsPriceChanged	bool	true means the fare changed at issue time. Nothing is issued unless IsPriceChangeAccepted was true.
Response.IsTimeChanged	bool	true means the schedule changed.
Response.SSRDenied	bool	true means an extra was refused by the airline.
FlightItinerary.BookingId	int	TBO booking id.
FlightItinerary.PNR	string	Airline record locator.
FlightItinerary.Fare.OfferedFare	decimal	Final net amount debited, including extras.
Passenger[].Ticket.TicketId	int	Per-passenger ticket id. Needed for a partial cancellation.
Passenger[].Ticket.TicketNumber	string	E-ticket number to print on the itinerary.
Passenger[].Ticket.Status	string	Ticketed when the ticket was issued.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId
TraceId	Search → Response.TraceId
ResultIndex (LCC)	FareQuote → Results.ResultIndex
PNR, BookingId (Non-LCC)	Book → FlightItinerary
Passengers[] .Fare	FareQuote → Results.FareBreakdown[] for that PaxType
Baggage, MealDynamic, SeatDynamic	SSR → the codes the customer chose

NEXT API

GetBookingDetails

NOTES

Do not retry Ticket after a timeout or a connection error. Call GetBookingDetails with the TraceId or BookingId to check whether the ticket was issued.

Make the call idempotent in your own code. Write an intent row keyed on the order before calling, and refuse a second call on the same key.

Send IsPriceChangeAccepted as true only when the customer has agreed to the new fare.

15

API #15 — GetBookingDetails

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/GetBookingDetails
Method	POST
Purpose	Returns the current state of a booking: itinerary, fare, passengers and ticket numbers.
Call when	After ticketing, when the customer opens My Bookings, and after any Book or Ticket call that timed out.

REQUEST JSON — BY BOOKINGID

```
{
  "EndUserId": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "BookingId": 1288527
}
```

REQUEST JSON — BY PNR, OR BY TRACEID AFTER A TIMEOUT

```
{
  "EndUserId": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "PNR": "ABC123",
  "FirstName": "Rahul",
  "LastName": "Kumar"
}

{
  "EndUserId": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31"
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "FlightItinerary": {
      "BookingId": 1288527,
      "PNR": "ABC123",
      "IsDomestic": true,
      "Source": 6,
      "Origin": "HYD",
      "Destination": "DEL",
      "AirlineCode": "6E",
      "ValidatingAirlineCode": "6E",
      "IsLCC": true,
      "NonRefundable": false,
      "Status": 1,
      "InvoiceNo": "JW/26-27/001284",
      "InvoiceCreatedOn": "2026-09-16T11:43:10",
      "Fare": {
        "Currency": "INR",
        "BaseFare": 5000,
        "Tax": 900,
        "PublishedFare": 5900,
        "OfferedFare": 5900,
        "TotalBaggageCharges": 1000,
        "TotalMealCharges": 250,
        "TotalSeatCharges": 350
      },
      "Passenger": [
        {

```

```

    "PaxId": 1,
    "Title": "Mr",
    "FirstName": "Rahul",
    "LastName": "Kumar",
    "PaxType": 1,
    "DateOfBirth": "1992-05-10T00:00:00",
    "Gender": 1,
    "ContactNo": "9876543210",
    "Email": "rahul@example.com",
    "IsLeadPax": true,
    "Baggage": [ "... as purchased ..." ],
    "MealDynamic": [ "... as purchased ..." ],
    "SeatDynamic": [ "... as purchased ..." ],
    "Ticket": {
      "TicketId": 1569310,
      "TicketNumber": "0982416789012",
      "Status": "Ticketed",
      "IssueDate": "2026-09-16T11:42:00",
      "ValidatingAirline": "6E"
    }
  },
  "Segments": [ "... same shape as Search ..." ]
}
}
}

```

INPUT FIELDS

Field	Type	Req	Description
EndUserId	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
BookingId	int	One of	TBO booking id. The most reliable lookup key.
PNR	string	One of	Airline record locator. Send it with FirstName and LastName.
FirstName	string	Cond.	Required when looking up by PNR.
LastName	string	Cond.	Required when looking up by PNR.
TraceId	string	One of	Search session id. Use this when Book or Ticket timed out before returning a BookingId.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
FlightItinerary.BookingId	int	TBO booking id.
FlightItinerary.PNR	string	Airline record locator.
FlightItinerary.Status	int	0 Failed, 1 Successful, 2 Not saved, 3 Not created, 4 Not allowed, 5 Flown, 6 Partially cancelled, 7 Cancelled.
FlightItinerary.InvoiceNo	string	Agency invoice number, once raised.
FlightItinerary.Fare	object	Final fare, including extras.
Passenger[].Ticket.TicketNumber	string	E-ticket number. Absent or null means the booking is held but not ticketed.
Passenger[].Ticket.TicketId	int	Needed for a partial cancellation.
Passenger[].Baggage	array	Extra baggage actually issued.
Passenger[].MealDynamic	array	Meals actually issued.

Field	Type	Description
<code>Passenger[].SeatDynamic</code>	array	Seats actually issued.
<code>Segments[]</code>	array	Confirmed flight legs and times.

WHERE THE VALUES COME FROM

Value	Comes from
<code>TokenId</code>	Authenticate → <code>TokenId</code>
<code>BookingId</code>	Book or Ticket → <code>FlightItinerary.BookingId</code>
<code>PNR</code>	Book or Ticket → <code>FlightItinerary.PNR</code>
<code>TraceId</code>	Search → <code>Response.TraceId</code>

NEXT API

None in the booking flow

NOTES

Use the `TraceId` form to find out what happened when a Ticket call timed out, before deciding whether to retry or refund.

Compare the `Baggage`, `MealDynamic` and `SeatDynamic` arrays against what the customer paid for, and refund the difference if an extra was refused.

16

API #16 — ReleasePNRRequest

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/ReleasePNRRequest
Method	POST
Purpose	Releases a held Non-LCC PNR that will not be ticketed and returns the seats to the airline.
Call when	When the customer abandons payment, or when a held booking is close to its LastTicketDate.

REQUEST JSON

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "BookingId": 1288527,
  "Source": "4"
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31"
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
BookingId	int	Yes	The held booking to release.
Source	string	Yes	Supplier code of the booking, from the Book response.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the hold was released.
Response.Error	object	Error code and message.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId
BookingId	Book → FlightItinerary.BookingId
Source	Book → FlightItinerary.Source

NEXT API

None. The booking is closed.

NOTES

This works on held bookings only. A ticketed booking is cancelled with SendChangeRequest.

There is no refund, because no payment was taken. Holds that are left unreleased attract supplier penalties.

17

API #17 — SendChangeRequest

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/SendChangeRequest
Method	POST
Purpose	Raises a cancellation or reissue request on a ticketed booking. The request is queued with the supplier and does not settle immediately.
Call when	After the customer has seen the charges from GetCancellationCharges and confirmed.

REQUEST JSON — FULL CANCELLATION

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "BookingId": 1907823,
  "RequestType": 1,
  "CancellationType": 3,
  "Remarks": "Customer requested cancellation"
}
```

REQUEST JSON — PARTIAL CANCELLATION

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "BookingId": 1288166,
  "RequestType": 2,
  "CancellationType": 3,
  "Sectors": [
    {
      "Origin": "HYD",
      "Destination": "DEL"
    }
  ],
  "TicketId": [1567415],
  "Remarks": "One passenger cancelling, others travelling"
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "TicketCRInfo": [
      {
        "ChangeRequestId": 195187,
        "TicketId": 1567415,
        "Status": 1,
        "ChangeRequestStatus": 4,
        "CancellationCharge": 793,
        "RefundedAmount": 304,
        "Remarks": "Successful"
      }
    ]
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.

Field	Type	Req	Description
TokenId	string	Yes	Session token from Authenticate.
BookingId	int	Yes	The ticketed booking.
RequestType	int	Yes	1 Full cancellation, 2 Partial cancellation, 3 Reissuance.
CancellationType	int	Yes	1 No show, 2 Flight cancelled, 3 Normal cancellation.
Sectors[]	array	Cond.	Required for a partial cancellation. The Origin and Destination of each sector being cancelled.
TicketId[]	int[]	Cond.	Required for a partial cancellation. The ticket ids of the passengers being cancelled.
Remarks	string	Yes	Reason for the request. It is read by the supplier support desk.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the request was accepted.
TicketCRInfo[].ChangeRequestId	int	Id of the request. Store it, because it is the only way to check the outcome.
TicketCRInfo[].TicketId	int	The ticket this entry refers to.
TicketCRInfo[].ChangeRequestStatus	int	1 Unassigned, 2 Assigned, 3 Acknowledged, 4 Completed, 5 Rejected, 6 Closed, 7 Pending. It is rarely 4 on the first response.
TicketCRInfo[].CancellationCharge	decimal	Charge levied. Indicative until the request completes.
TicketCRInfo[].RefundedAmount	decimal	Amount to be refunded. Indicative until the request completes.
TicketCRInfo[].Remarks	string	Supplier note on the request.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId
BookingId	GetBookingDetails → FlightItinerary.BookingId
TicketId[]	GetBookingDetails → Passenger[].Ticket.TicketId
Sectors[]	GetBookingDetails → Segments[]

NEXT API

GetChangeRequestStatus

NOTES

The amounts in this response are indicative. Refund the customer against the figures from GetChangeRequestStatus once the status reaches 4.

The request cannot be withdrawn once raised. Confirm the charges with the customer first.

18

API #18 — GetChangeRequestStatus

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/GetChangeRequestStatus
Method	POST
Purpose	Returns the status of a change request and the final refund amount and cancellation charge.
Call when	On a schedule after SendChangeRequest, until the status is final.

REQUEST JSON

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "ChangeRequestId": 199350
}
```

RESPONSE JSON

```
{
  "ResponseStatus": 1,
  "Error": { "ErrorCode": 0, "ErrorMessage": "" },
  "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
  "ChangeRequestId": 199350,
  "ChangeRequestStatus": 4,
  "CancellationCharge": 100,
  "RefundedAmount": 3560,
  "ServiceTaxOnRAF": 12.36
}
```

This response is not wrapped in a Response object, unlike the other Air service calls. Read the fields at the top level.

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
ChangeRequestId	int	Yes	The request to check.

OUTPUT FIELDS

Field	Type	Description
ResponseStatus	int	1 means the call succeeded.
ChangeRequestId	int	The request being checked.
ChangeRequestStatus	int	1 Unassigned, 2 Assigned, 3 Acknowledged, 4 Completed, 5 Rejected, 6 Closed, 7 Pending. Only 4, 5 and 6 are final.
CancellationCharge	decimal	Final charge levied.
RefundedAmount	decimal	Final amount refunded to the agency. Settle the customer refund against this.
ServiceTaxOnRAF	decimal	Service tax on the refund administration fee.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId
ChangeRequestId	SendChangeRequest → TicketCRInfo[].ChangeRequestId

NEXT API

None. Release the customer refund when the status is 4.

NOTES

Poll with a back-off rather than a tight loop. Airline refunds can take several days, and status 7 can persist for a while.

19

API #19 — GetCancellationCharges

POST

Endpoint	http://api.tektravels.com/BookingEngineService_Air/AirService.svc/rest/GetCancellationCharges
Method	POST
Purpose	Returns the cancellation charge and the refund amount for a ticketed booking. It does not cancel anything.
Call when	When the customer opens the cancel screen, before any confirmation.

REQUEST JSON

```
{
  "EndUserIp": "192.168.1.100",
  "TokenId": "705d0324-56eb-48a0-9e8e-bd6ed9f853d5",
  "BookingId": 1583080,
  "RequestType": 1,
  "BookingMode": 5
}
```

RESPONSE JSON

```
{
  "Response": {
    "ResponseStatus": 1,
    "Error": { "ErrorCode": 0, "ErrorMessage": "" },
    "TraceId": "d1f3a9c0-5b2e-4f88-9a10-7c6e2b4d0a31",
    "CancellationCharge": 8532,
    "RefundAmount": 2413,
    "Currency": "INR",
    "Remarks": "Cancellation charges as per airline fare rule"
  }
}
```

INPUT FIELDS

Field	Type	Req	Description
EndUserIp	string	Yes	Public IP address of the server making the call. It must be whitelisted with TBO.
TokenId	string	Yes	Session token from Authenticate.
BookingId	int	Yes	The ticketed booking.
RequestType	int	Yes	1 Full cancellation, 2 Partial cancellation, 3 Reissuance.
BookingMode	int	Yes	How the booking was made. 5 is an API booking.

OUTPUT FIELDS

Field	Type	Description
Response.ResponseStatus	int	1 means the call succeeded.
Response.CancellationCharge	decimal	Total charge the airline and supplier will levy.
Response.RefundAmount	decimal	Amount the agency gets back. Deduct the agency service fee before quoting the customer.
Response.Currency	string	Currency of both amounts.
Response.Remarks	string	Supplier note on the calculation.

WHERE THE VALUES COME FROM

Value	Comes from
TokenId	Authenticate → TokenId
BookingId	GetBookingDetails → FlightItinerary.BookingId

NEXT API

SendChangeRequest

NOTES

This call only quotes. It is safe to call whenever the cancel screen opens.

Penalty slabs are time-based, so the quote can change. Re-check it just before raising the change request.