



## Flex Trim Product Data Sheet

### Product Information

Flex Trim is made with a high density polyurethane composite resin that is flexible but also highly durable. Flex Trim polyurethane products have a closed cell structure, which provides supreme protection from most solvents and renders it almost completely hydrophobic (it will not rot). In addition to its flexibility and superior longevity, Flex Trim flexible moulding offers superior performance compared to real wood. It provides the beauty and appearance of real wood but will not rot, swell, or deteriorate over time and is ideal for indoor or outdoor use.

### Company Information

Flex Trim has facilities in Lexington, North Carolina and Provo, Utah in order to more efficiently serve our customers nationwide.

Flex Trim East (HQ)  
117 Cedar Lane Drive  
Lexington, NC 27292

Flex Trim West  
533 South 500 West  
Provo, UT 84601

### Product Characteristics

| Nominal Physical Properties        |     |
|------------------------------------|-----|
| Property                           |     |
| Filler content, weight percentage  | 40  |
| Nominal Density, g/cm <sup>3</sup> | 1.3 |
| Shore A Hardness                   | 85  |
| Tensile Strength, psi              | 950 |
| Elongation, %                      | 170 |
| Graves Tear Strength, lb/in        | 175 |
| Split Tear Strength, lb/in         | 90  |

### Advantages of Flex Trim

- The appearance of real wood
- Ease of installation using standard wood working equipment – cut, sand, shape, miter and finish like real wood
- Seamless construction without lamination defects
- Moisture proof, insect proof, can withstand extreme hot and cold temperatures without warping, cracking or deteriorating

## INSTALLATION

**MACHINING** - Conventional woodworking tools can be used with this material. Material can be cut, sanded and shaped with ease. Miter saws work well when trimming this material. As with all types of trim material, use care when marking and cutting.

**IMPORTANT: SANDING THE FACE OF STAIN GRADE FLEXIBLE MOULDING WILL REMOVE THE GRAIN TEXTURE.**

**FASTENING** - Always install moulding material in a relaxed position. Use construction or panel adhesive or mastic type glue continuously on back side and nails to secure moulding material in place until adhesive bonds.

- DO NOT use staples to fasten material.
- Keep nails to a minimum, no closer than 6" between nails.
- Do not nail closer than 3/8" from the edge of the moulding.

**CLEANING** - Prior to finishing, clean the moulding by wiping with a cloth using soap and water, paint thinner or any mild solvent to clean any dirt or grease that may have accumulated during installation.

**PAINT & STAINING** - All Flex Trim material is paint grade and most profiles have grain and can be stained. Inspect for grain or call for information on compatibility of staining. Staining of Flex Trim material requires the use of a gel type stain. You should paint or stain the product after installation or the finishing material may crack if the moulding is flexed.

### What makes our product “green?”

- Low Global Impact
  - The polyurethane elastomer contains 100% solids (no solvents, trace Volatile Organic Compounds (VOCs)).
- Resource Efficiency
  - Regional manufacturing facilities allow us to support our customers on a more localized basis, which reduces fuel consumption and pollution.
  - Our products are cast in-place, which can reduce the quantity of materials and waste (minimizes material cuts).
  - The manufacture of our product requires significantly less energy to make as compared to wood moulding or other wood products.
  - Our mouldings are durable and offer reduced maintenance (long lasting can mean less waste generated, lower cost of ownership, extended service life – high potential for salvaging and reuse, and reduced environmental impact from disposal).
  - Flex Trim flexible moulding replaces traditional wood moulding, which supports rot, pests, and fungal growth. Since polyurethane moulding does not provide a food source for insects, there is a potential for fewer applications of pesticides, which can improve indoor air quality.
  - The polyurethane elastomer is manufactured from 0.7% renewable resources (replaces petroleum-based products).
  - Polyurethane molding is an alternative material to wood, which saves our forests.