PRODUCT DATA SHEET AND SAFETY DATA SHEET

RIGID CAST FR-RFRV8

Cast Architectural Molding

ASTM E84 class “C” fire rated

Version: 4.0 Date:1/20/2025

SECTION 1: CHEMICAL PRODUCT / COMPANY IDENTIFICATION

PRODUCT INFORMATION:

Product Identifier: Rigid Cast FR
Product Code: FR-RFRV8

RECOMMENDED USE:

- Used for Architectural Moulding and Decorative Trim applications where ASTM E84 Class C Fire Rating is Required.

RESTRICTIONS ON USE:

- Not a Structural Component
- Fire Rating limited to ASTM E84 Class C.

COMPANY IDENTIFICATION / MAILING ADDRESS:

Flex Trim West 533 South 500 West
Provo, UT 84601
(877)877-4595

SECTION 2: HAZARD(S) IDENTIFICATION

HAZARD CLASSIFICATION:

- No Need for Classification According to GHS Criteria for this product.

SIGNAL WORD:

- Caution

HAZARD STATEMENTS:

- Dust from grinding operations may aggravate existing lung disorders when proper protection is not used.

PRECAUTIONARY STATEMENTS:

- Acute: None known from solid article Fumes from hot wire cutting can be irritating and lead to coughing. These fumes could contain traces of MDI, other isocyanates, and/or curatives. Exposure to isocyanates may produce an asthma-like reaction, with shortness of breath, wheezing or cough, which may occur after re-exposure to very low levels. Chronic: Animal studies indicate that chronic inhalation or overexposure of dusts may cause inflammation of the lungs, fibrosis, and airway destruction.

GHS CLASSIFICATION:

- NO GHS CLASSIFICATIONS INDICATED

GHS LABEL ELEMENTS, INCLUDING PICTOGRAMS:

- NO GHS LABEL ELEMENTS OR PICTOGRAMS INDICATED

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAMES AND COMPOSITION:

Substance/Mixture:

- Mixture

Chemical Name(s) and Composition:

Chemical Name	Common Name	Composition Value % By Weight	CAS Number
4,4'-Methylenediphenyl Diisocyanate	Isocyanate	39-46%	0000101-68-8
Diethylene Glycol	Polyol	39-46%	0000111-46-6
Alumina Trihydrate	ATH	1-5%	21645-51-2
Sodium Potassium Aluminum Silicate	Perlite	5-11%	93763-70-3
Brominated Alcohol	Bromine	1-5%	Proprietary (Not Disclosed)*
Silicon Oxide	MS4A	1-5%	7631-86-9
Expandable Graphite	Graphene	1-5%	12777-87-6

- Composition Value % by Weight is a trade secret and, therefore has been presented as a range per OSHA 1910.1200(i)
- *The Chemical Manufacturer has withheld the CAS number as Proprietary.

SECTION 4: FIRST AID PROCEDURES

DESCRIPTION OF FIRST AID MEASURES:

- Flush eyes with water if dust from grinding causes irritation.
- Consult physician if aggravation of Lung Disorders results from cutting without a mask.

MOST IMPORTANT SYMPTOMS/EFFECTS:

- Acute

IMMEDIATE MEDICAL ATTENTION:

- See Description of First Aid Measures

SECTION 5: FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

- Flash Point: Not Applicable
- Flammable Limits: LEL: Not Applicable UEL: Not Applicable
- Specific Hazards Arising from the Chemical: Not applicable

EXTINGUISHING MEDIA:

- Water, dry chemical, foam, or carbon dioxide

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Evacuate non-emergency personnel to a safe area. Firefighters should use self-contained breathing apparatus. Avoid breathing smoke, fumes, and decomposition products. Use water spray to quench smoldering elastomers. Burning may produces toxic gases, such as carbon monoxide, oxides of nitrogen, and traces of hydrogen cyanide.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

- Not Applicable as No Special containment Required.

PROTECTIVE EQUIPMENT:

- Protective Eyewear and N-95 Mask when processing for Installation

EMERGENCY PROCEDURES:

- See Section 4: First Aid Measures

CONTAINMENT AND CLEANING UP:

- Sweep into disposal container and dispose per local regulations.

SECTION 7: HANDLING AND STORAGE

HANDLING:

- No Handling Precautions

STORAGE:

- No Storage Requirements

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

INDIVIDUAL PROTECTION MEASURES:

- PPE including Gloves, Eye Protection and N-95 Mask when processing for installation

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:

- Light Grey Specked with Black Flecks to a Charcoal Grey color

ODOR:

- N/A

FLAMMABILITY:

- ASTM E84 Class C Rating

RELATIVE DENSITY:

- .9405 g/cm3

SHORE HARDNESS:

- D65+/-5

MELTING POINT:

- 380-460 Degrees F.
- May Degrade above 300 Degrees F.

SOLUBILITY:

- Insoluble in Water

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY:

- No specific Data

CHEMICAL STABILITY:

- Product is stable under normal conditions

CONDITIONS TO AVOID:

- No Specific Data

INCOMPATIBLE MATERIALS:

- No specific Data

HAZARDOUS DECOMPOSITION PRODUCTS:

- Under normal storage conditions Hazardous Decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS:

- See Section 4: First Aid Measures

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL DATA:

Under normal conditions not applicable

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

- Any disposal practices must be in compliance with all Federal, State and Local laws and regulations.

SECTION 14: TRANSPORT INFORMATION

TRANSPORTATION INFORMATION:

- Not DOT/Non RCRA Regulated

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

- EPA SARA Title III hazard class: none.
- EPA SARA Title III Section 313 (40CFR372) Toxic Chemicals present in quantities greater than the "*de minimis*" level are: none.
- No need for classification according to GHS Criteria for this product.

SECTION 16: OTHER INFORMATION

DATE OF PREPARATION OR LAST REVISION:

- Revision 2, September 5, 2024
- Revision 3, December 11, 2024 – Updates based on flammability drip testing

DISCLAIMER:

- Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purpose or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose.