



Aspersor A&P 2014

1/2"

Caudal GPM: 1,68 - 2,37

Diametro a 0.50 m: 20,14 - 22,89 mts

Presion de trabajo: 25 - 50 psi



Aspersor ajustable amarillo A&P

1/2"

boq 4,00 mm

Caudal M3/h: 0,6 - 1,2

Diametro a 0.50 m: 9,00 - 12,00

Presion de trabajo: 1 - 4 bar



Aspersor capucha azul A&P

1/2"

boq 3,5 mm

Caudal : 510 - 800 L/h

0,510 -0,800 M3/h

Diametro a 0.50 m: 19 - 22,00 mts

Presion de trabajo: 1,5 - 4 bar



Aspersor A&P 5023

1/2"

boq 2,8mm

Caudal GPM: 1,98 - 2,70

Diametro a 0.50 m: 18 - 20,30 mts

Presion de trabajo: 30 - 60 psi





Mini wobbler A&P Angulo Bajo

1/2"

boq 2,78 mm

Caudal L/h: 295 - 384

Diametro a 0.46 m: 10,7 - 11,70

Diametro a 0.91 m: 12,50 - 13,1

Presion de trabajo: 15 - 35 psi



Mini wobbler A&P Angulo Alto

1/2"

boq 2,78 mm

Caudal L/h: 295 - 384

Diametro a 0.50 m: 13,2 - 14,60

Presion de trabajo: 15 - 35 psi



Excel wobbler A&P

1/2"

Caudal GPM: 1,06 - 1,84

Diametro a 0.50 m: 10,68 - 13,73

Presion de trabajo: 10 - 30 psi



Wobbler A&P

3/4"

boq 2,78mm

Caudal L/H: 241 - 418

Diametro a 0.46 m: 9,6 - 13.90

Presion de trabajo: 0,69 - 2,07 bar



Aspersor ajustable A&P

1 1/2"

Caudal GPM: 20,68 - 63,40

Diametro a 0.50 m: 12,00 - 30,00 mts

Presion de trabajo: 2 - 4 bar

Aspersor ajustable A&P

1"

boq 7,5*2,8 mm

Caudal : 3,67 - 4,23 M3/h

Diametro a 0.50 m: 18,80 - 21,20

Presion de trabajo: 3 - 4 bar



Aspersor A&P 8025

1 1/4"

Caudal GPM: 36,8 - 53,9

Diametro a 0.50 m: 41,5 - 51,30 mts

Diametro a 2,0 m: 46,4 - 53,40 mts

Presion de trabajo: 35 - 75 psi





Aspensor A&P 3020

3/4"

Caudal M3/H: 0,8 - 2,3

Diametro a 0.50 m: 15,00 - 17,00 mts

Presion de trabajo: 1 - 4 bar

Aspensor A&P 7025

1"

Caudal GPM: 19,60 - 27,70

Diametro a 0.50 m: 37,8 - 46,70 mts

Diametro a 2,0 m: 40,50 - 47,30 mts

Presion de trabajo: 35 - 70 psi





Smooth drive A&P

1 1/2"

Caudal GPM: 1,68 - 2,12

Diametro a 0.50 m: 18,43 - 19,90 mts

Presion de trabajo: 25 - 40 psi

Microaspersor A&P

1/2"

Caudal L/H: 40

Diametro a 0.50 m: 2,5 - 5 mts

Presion de trabajo: 1,5 - 4 bar



Triad A&P

Caudal GPM: 0,94 - 8,32

Trayectoria 0° : 2.90 -5.33

Trayectoria 30° : 5.33 - 10.52

Presion de trabajo: 1,5 - 4 bar

