

ECE326

PROGRAMMING LANGUAGES

Lecture 13 : Introduction to Rust

Kuei (Jack) Sun

ECE

University of Toronto

Fall 2020

Introduction

- Designed and developed at Mozilla Research
 - By Graydon Hoare
- First released in Summer 2010
 - Stable since Spring 2015
- Focused on *safety*
 - Memory safety, type safety, thread safety

Memory Safety

- Protection from invalid memory access
- Memory *unsafe* languages
 - Allows arbitrary pointer arithmetic (C/C++)
- Memory errors
 - Buffer overflow
 - Use after free (dangling pointers)
 - Double free
- Solution
 - runtime error detection (e.g. Java)
 - Static program analysis (e.g. Rust)

Type Safety

- Protection from incorrect use of a value

- Example

- untagged union (C/C++)
- Union
 - All member variables share *the same* memory location
 - Can lead to type-unsafe usage!
- Solution: tagged union
 - Adds a tag field to indicate which member is in use

```
union Foo {  
    int i;  
    float f;  
};
```

```
// in main()  
Foo u;  
u.i = atoi(argv[argc-1]);  
printf("%f\n", u.f);
```

```
> ./union 1237864534  
1640970.750000
```

Thread Safety

- Protection from incorrect use of shared data
 - Only applicable to multi-threaded code
- Thread
 - Independent sequence of program instructions
- Thread unsafe operation can cause data corruption
 - Leads to data loss, security vulnerability, etc.
- Rust ensures data cannot be improperly shared

Rust

- A System programming language
 - Performance comparable to C/C++
- Compiler performs extensive safety checks
 - Compile time much slower than C/C++ compilers
- Syntactically similar to C/C++ and Haskell
- Multi-paradigm
 - Functional programming
 - Generic programming
 - NOT object-oriented programming

Installation

- Custom installed on UG machines
- Add RUSTUP_HOME to environment variable
 - `setenv RUSTUP_HOME /cad2/ece326f/rust` # add to ~/.cshrc
 - `export RUSTUP_HOME=/cad2/ece326f/rust` # add to ~/.bashrc
- Run `rustc --version`
 - Make sure you get this output:
 - `rustc 1.47.0 (18bf6b4f0 2020-10-07)`
- <https://rustup.rs/>
 - Installs latest version of Rust
 - Follow its instruction to install for your home machine

Alias in Rust


- No aliases
 - Except when it is 100% safe
 - Compiler can deduce when to free memory
 - Guarantees memory safety without garbage collection
- Ownership
 - All variables have unique owners
 - E.g. the owner of local variables is their function
 - When the owner goes out of scope, it frees what it owns
 - Without alias, no cycles can be formed
 - Memory ownership will take the shape of a tree

Ownership

```
struct Foo {  
    int * array;  
    Foo() : array(new int[5]) {}  
};
```

```
int bar(int y) {  
    Foo f;  
    int x = y + 3;  
    /* ownership diagram */  
    return x + f.array[0];  
}
```

```
int main() {  
    int * w = new int(5);  
    int z = bar(*w);  
    return z;  
}
```




Ownership

```
struct Foo {  
    int * array;  
    Foo() : array (new int[5]) {}  
    ~Foo() { delete array; }  
};
```

```
int bar(int y) {  
    Foo f;  
    int x = y + 3;  
    return x + f.array[0];  
}
```

```
int main() {  
    int * w = new int(4);  
    int z = bar(*w);  
    delete w;  
    return z;  
}
```

delete
statements
automatically
inserted by
compiler after
static analysis
of ownership




Passing Variable

```
struct Foo {  
    int * array;  
    Foo() : array(new int[5]) {}  
};
```

```
int bar(int * y) {  
    Foo f;  
    int x = *y + 3;  
    return x + f.array[0];  
}
```

```
int main() {  
    int * w = new int(5);  
    int z = bar(w);  
    return z;  
}
```

Who owns the
integer, 5, now?




1. Takeover (Move)

```
struct Foo {  
    int * array;  
    Foo() : array(new int[5]) {}  
};
```

```
int bar(int * y) {  
    Foo f;  
    int x = *y + 3;  
    delete y;  
    return x + f.array[0];  
}
```

```
int main() {  
    int * w = new int(5);  
    int z = bar(w);  
    /* cannot use w anymore */  
    return z;  
}
```

By default, bar takes over ownership.




2. Borrow

```
struct Foo {  
    int * array;  
    Foo() : array(new int[5]) {}  
};
```

```
int bar(borrowed int * y) {  
    Foo f,  
    int x = *y + 3;  
    return x + f.array[0];  
}
```

```
int main() {  
    int * w = new int(5);  
    int z = bar(w);  
    delete w;  
    return z;  
}
```



bar can also
“borrow” 5’s
ownership
from main

Passing Variable

- Borrow
 - Lender must *outlive* borrower
- Order of options
 - If parameter declared as borrow, lend variable *if possible*
 - If variable can be copied (e.g. primitive types), pass by value
 - Otherwise, performs a move (give up ownership)

Hello World

- Like in C/C++, requires a main function
- Function declared using **fn** keyword
- `println!` is a *macro* function (denoted by `!` symbol)
- To compile, call `rustc -o hello main.rs`
 - `hello` is the name of executable

```
/* main.rs */  
// Rust uses same as C/C++ comments  
fn main() {  
    println!("hello world");  
}
```

Function

- General syntax

```
fn funcname(argname: argtype...) -> returntype {  
    ... statements ...  
    returnvalue  
}
```

- In Rust, the last expression (no semicolon) is returned

```
fn foo(a: f64, b: f64) -> f64 {  
    a * b                // return value  
}  
  
fn baz(a: f64, b: f64) -> f64 {  
    return a * b;        // same as above  
}
```


Variable

- Variable declaration in Rust is a *statement*
- Type can usually be automatically deduced
 - If assigned a literal, it has the type of the literal
 - If assigned a return value from a function, the return type

```
fn baz(a: f64, b: f64) -> f64 {  
    return a * b;    // same as above  
}
```

```
let a = 20;           // an integer type (e.g. i32 or i64)  
let b: i64 = 30;      // explicitly specified as i64  
let c = baz(2.0, 3.0); // f64 by type inference
```

Primitive Types

- Boolean
 - bool: true or false
- Floating Point
 - f32 or f64
- Integer
 - signed: i8, i16, i32, i64, isize
 - unsigned: u8, u16, u32, u64, usize
 - usize and isize depends on architecture (either 32 or 64 bits)
- Character
 - char
 - Can be unicode characters as well. Not just ASCII.
 - i.e. Unlike char in C, not guaranteed to be 1 byte

String Literal

- utf-8 encoded (thus supports unicode characters)
- String literal
 - The type is `&str` (reference to a string slice)

```
let s: &str = "hello world";
```

- String slice
 - Reference to immutable string data somewhere
 - String literals are stored in program binary
 - Similar to `const char *` in C++

Println Format

- Similar to Python's `string.format()`
- Each set of curly braces is an argument
- Type conversion automatically done
 - Argument needs to implement `Display` or `Debug` trait
 - Similar to overriding `__str__` or `__repr__` in Python

```
let s = "hello world";
```

```
let a = 5;
```

```
println!("{}", {}, s, a);
```

```
hello world, 5
```

Immutability

- By default, variables in Rust are immutable
- If you want to change it, use **mut** keyword

```
let x = 5;  
println!("The value of x is: {}", x);  
x = 6;           // BAD!
```

error: cannot assign twice to immutable variable

```
let mut x = 5;  
x = 6;           // OK
```

Shadowing

- Rust allows same name to be used multiple times
- Previous bindings are “shadowed”, cannot be accessed
- Useful once code becomes more complex

```
let x = 5;  
let x = x + 1;  
let x = x * 2;  
println!("The value of x is: {}", x);
```

The value of x is: 12

```
let spaces = "  ";  
let spaces = spaces.len();    // OK to change type as well
```

Constant

- A compile-time expression
- Can be declared in global scope (unlike **let**)
- Type must be specified

```
const MAX_POINTS: u32 = 100_000;
```

- underscore in literal has no semantic meaning
 - It helps programmer read bigger numbers more easily

Mutable String

- String type
 - mutable string, content can be updated

```
let mut s1 = String::from("foo"); // convert to mutable
s1.push_str("bar");               // append "bar" to s
>> foobar
let mut s2 = "lo".to_string();    // another way to convert
s2.push('l');                     // push a single character
>> lol
```


Mutable String

- String type
 - mutable string, content can be updated

```
let mut s1 = String::from("foo"); // convert to mutable
s1.push_str("bar");               // append "bar" to s

let mut s2 = "lo".to_string();    // another way to convert
s2.push('l');                     // push a single character

let mut s3 = String::new();       // creates an empty string

// formatted string (created from a macro function)
let s = format!("{}", s1, s2, s3);
>> foobar-lol-
```

Tuple

- Rust has built-in tuple type, similar to Python

```
let tup: (i32, f64, u8) = (500, 6.4, 1);
```

- Allows for unpacking

```
let tup = (500, 6.4, 1);  
let (x, y, z) = tup;
```

- Also allows access to each element

```
let a = tup.0;  
let b = tup.1;  
let c = tup.2;
```

Array

- Similar in syntax to C array
- Tracks its own length, similar to Java array
 - Performs compile-time bound checking

```
let a = [1, 2, 3];  
let months = ["January", "February", "March", "April", ...];  
let first = a[0];    // uses index operator  
let [x, y, z] = a;    // supports unpacking too
```

```
// array does not support Display trait, must use {:?}  
println!("{:?}: {}", a, a.len());
```

```
[1, 2, 3]: 3
```

Casting

- Rust has strict type conversion rules
 - All type conversion must be explicit
- `as` operator
 - Casts one type to another (if allowed)
- Example: array index must be the type `usize`

```
let a = [1, 2, 3];  
let b: i32 = 1;  
let c = a[b]; // error: slice indices are of type `usize`  
let c = a[b as usize]; // OK  
println!("{}", c);  
>> 2
```

Function

- Does not support function overloading
- Does not support default parameters
- Like in C, uses block scope
- Blocks are expressions in Rust!

```
let y = {  
    let x = 3;  
    x + 1  
};
```

```
println!("The value of y is: {}", y);    // 4
```

Unit Type

- `()`
 - The value looks like an empty tuple
 - Its type is the unit type
 - Purpose is to be “useless”
- Almost everything in Rust is an expression
 - A property of functional programming languages
- A function without return type returns it
 - Similar to None in Python