

ECE326

PROGRAMMING LANGUAGES

Lecture 20 : C++ Template Metaprogramming

Kuei (Jack) Sun

ECE

University of Toronto

Fall 2020

Template Metaprogramming

- Part of a language that generates code
 - More powerful and complex than generics
- Allows compile-time polymorphism
 - Executing code at compile-time!
- Template instantiation
 - By substituting *template* parameters
 - Generates type-safe code
 - Each instantiation generates new code
 - Abuse can result in very large executable size

C++ Template

- Syntax

```
template<template parameter, ...>  
function or class definition
```

- **typename** (or class)

- Indicates the following identifier is a type

```
template<class T>    // T is a type  
T min(T a, T b) {  
    return a < b ? a : b;  
}
```

```
template<typename T> // T is a type  
class Foo {  
    T var;  
};
```

Template Instantiation

- When template is used, code is generated by compiler
 - Performs type-safe template argument substitution

```
template<typename T> // T is a type           // template instantiated
T min(T a, T b) {
    return a < b ? a : b;
}

                                min<int>
                                →
int min(int a, int b) {
    return a < b ? a : b;
}
```

```
// in main
std::cout << min<int>(4, 9); // prints 4
```

```
// for template function only, you can omit <int>
std::cout << min(3, 7); // template parameter inferred
```

C++ Template

- Type must support all used operations in template
 - E.g. `operator<` must be supported by type `T`
- No trait bounds
 - Must read template body to see what type `T` must do
 - Compiler error for templates is very hard to read

```
template<typename T>
T min(T a, T b) {
    // template assumes T supports the less than operator
    return a < b ? a : b;
}
```

Code Organization

- Review
 - `#include` *copy-pastes* content of file into current file
- Convention
 - Put class definition and function *declaration* in header file (.h)
 - Put function and method *definition* in source file (.cpp)
- Template
 - Put all template definition in header file
 - Unless you do not want other source file to have access to it

Template Parameter

- Template parameter can be *anything*
 - Does not have to be a type
 - E.g. can be int or float
- Template arguments must be *compile-time* values
 - Types or constants

```
template<typename T, int X>
void normalize(T array[], int size) {
    for (int i = 0; i < size; i++) {
        array[i] /= (T)X; // X is a compile-time constant int
    }
}
```

Multiple Parameters

- Template functions can have multiple type parameters
 - Instantiation may require disambiguation

```
template<typename T, typename F>
T convert(F v) {
    return (T)v;
}

double foo(double d) {
    int i = convert<int>(d);    // from double to int
    char c = convert<char>(i); // from int to char

    /* instantiate convert<double, char> */
    double(*func)(char) = convert; // function pointer
    return func(c) + 1.2;
}
```


Template Specialization

- Specialization for a particular template argument
- Benefit
 - Code does not make it to executable if not used!

```
template<typename T>  
T min(T a, T b) {  
    return a < b ? a : b;  
}
```

```
template<> // this syntax signifies specialization  
const char * min(const char * a, const char *b) {  
    // use strcmp to compare c-strings  
    return strcmp(a, b) < 0 ? a : b;  
}
```

Template Class

- You have used many in ECE297
 - `std::vector`
 - `std::priority_queue`
 - `std::unordered_map`
- Unlike template functions, type cannot be inferred.
 - Must explicitly specify template arguments

```
std::vector<int> v = {1, 2, 3};  
// auto keyword will type inference, otherwise compiler-error  
for (auto it = v.begin(); it != v.end(); it++) {  
    std::cout << *it << std::endl;  
}
```

Template Class

```
template<class T> // same as typename T
class Stack {
public:
    Stack(unsigned cnt=8);
    ~Stack() { delete [] array; }
    bool push(const T &); // push element to top of stack
    bool pop();           // remove current top of stack
    T * top();            // return current top of stack
    int empty() const { return end == -1; }
    int full() const { return end == count - 1; }
private:
    int count; // capacity of stack
    int end;   // points to top of stack
    T * array;
} ;
```

Member Functions

- Can be defined outside of class template
 - But must be defined together, preferably in same header file

```
template<class T>
Stack<T>::Stack(unsigned cnt) : count((int)cnt), end(-1),
    array(new T[cnt]) {}
```

```
template<class T>
bool Stack<T>::push(const T & item) {
    if (full()) return false;
    array[++end] = item;
    return true;
}
```

Member Functions

```
template<class T>
bool Stack<T>::pop() {
    if(empty()) return false;
    --end;
    return true;
}

// general rule of thumb:
// return a pointer if you want to indicate error with nullptr
// return by reference (T &) if no error is possible, OR
// if you plan to crash the program upon error
template<class T>
T * Stack<T>::top() {
    if (empty()) return nullptr;
    return &array[end];
}
```

typedef

- Creates an alias for the type name
- Common use
 - Indicate different usage
 - E.g. `size_t` instead of unsigned long confer context
 - reduce length of type names, or improve appeal
- Again, do not abuse this feature

```
/* this is bad - hides the fact that it's a pointer */  
typedef char * cstring;  
typedef Stack<double> DoubleStack;  
typedef vector<int, allocator<int> > IntVector;  
typedef int (* compare_f)(int, int);
```

Sample Use

```
DoubleStack ds = DoubleStack();
double * dp, d = 1.1;
cout << "Pushing elements onto stack" << endl;
while (ds.push(d)) {
    cout << d << ' '; d += 0.7;
}
cout << endl << "stack full" << endl
    << endl << "Popping elements from stack" << endl ;
while ((dp = ds.top())) {
    cout << *dp << ' '; ds.pop();
}
cout << endl << "stack empty" << endl ;
```

Pushing elements onto stack

1.1 1.8 2.5 3.2 3.9 4.6 5.3 6

stack full

Popping elements from stack

6 5.3 4.6 3.9 3.2 2.5 1.8 1.1

stack empty

Default Template Parameter

- Template parameters can take defaults too

```
template<class T=int, int C=16>
class Stack {
    int end;
    T array[C]; // static array size
public:
    Stack() : end(-1) {}

    bool push(const T &);
    bool pop();
    T * top();

    int empty() const { return end == -1; }
    int full() const { return end == C - 1; }
};
```


Partial Specialization

- Specialize only some of the template parameters

```
template<class K, class V, int S>
class Map {
    struct Pair { K key; V value; } array[S];
public:
    ...
    V * find(const K & k) {
        int i;
        for (i = 0; i < S; i++) {           // time complexity is O(n)
            if (array[i].key == k)
                return &array[i].value;
        }
        return nullptr;
    }
};
```

Partial Specialization

- Specialize only some of the template parameters

```
template<class V, int S>
class Map<int, V, S>           // e.g. key is an int
{
    V values[S];
public:
    ...
    V * find(int k) {          // time complexity now O(1)
        if (k < 0 || k >= S)
            return nullptr;
        return &values[i];
    }
};
```

Template Aliases

- Similar to typedef, but also works for partial templates
- Not the same as partial specialization
 - Only gives a different name to templates

```
template<class K, class V, int S>  
class Map { ... };
```

```
template<class K, int S>  
using StringMap = Map<K, std::string, S>;
```

Template in Template

- Templates can use other templates

```
template<class T=char, size_t C=8>
class Stack {
    std::vector<T> array;
public:
    Stack() {}

    bool push(const T &);
    bool pop(); T * top();

    int empty() const { return array.size() == 0; }
    int full() const { return array.size() >= C; }
};
```

Template as Template Argument

- Templates arguments can take parameterized types

```
Stack<vector<char>> st = Stack<vector<char>>();  
std::vector<char> * vp, v = { 'a' };
```

```
cout << "Pushing elements onto stack" << endl;  
while (st.push(v)) {  
    cout << v << ' '; v[0] += 2;  
}
```

```
cout << "Popping elements from stack" << endl;  
while ((vp = st.top())) {  
    cout << *vp << ' '; st.pop();  
}
```

Recursive Template

- Template using a different instantiation of itself
 - Can be used to generate compile-time expression

```
template<int F>
struct Factorial {
    enum { value = F * Factorial<F - 1>::value };
};
```

```
template<> // base case template specialization
struct Factorial<1> {
    enum { value = 1 };
};
```

```
// e.g. Factorial<3>::value = 3 * Factorial<2>::value
//      Factorial<2>::value = 2 * Factorial<1>::value
//      Factorial<1>::value = 1
```