

ECE326 – Fall 2019: Week 6 Exercise Questions

1. True or False [1 mark each]

Circle T is true, otherwise circle F for false.

1. In Python, types are reified at runtime. **T** **F**
2. The decorator function is called every time the decorated function is called. **T** **F**
3. C++11 supports static reflection. **T** **F**
4. In multiple inheritance, TypeError is raised when there is a shared base metaclass. **T** **F**
5. `type` is to classes as `object` is to instances. **T** **F**

2. Multiple Answers [2 marks each]

Pick all answer(s) that are correct. You will lose 1 mark per wrong choice, down to 0 marks.

1. Which of the following statements about descriptors or properties are true?
 - (a) A descriptor can manage multiple attributes at once, a property can only manage one.
 - (b) A descriptor with only `__get__` can be overwritten or deleted, a property with only getter cannot.
 - (c) A descriptor can manage a method, a property cannot (data attribute only).
 - (d) A descriptor keeps data within its own instance, a property uses that of the parent instance.
 - (e) A descriptor with only `__set__` has the same behaviour as a property with only setter.
2. Which of the following statements about class decorators or metaclasses are true?
 - (a) Both class decorators and metaclasses require only a callable object to work.
 - (b) Both class decorators and metaclasses must return a class (new or existing).
 - (c) Class decorators do not support inheritance, metaclasses do.
 - (d) Class decorators modifies a class only after it is created, metaclasses modifies a class only before and during class creation.
 - (e) Metaclass is the only way to overload operators for classes.

3. Decorator [10 marks]

Create a decorator, memoize, that will cache results of the decorated function. You may assume:

1. The decorated function will be a pure function.
2. Only positional arguments are used by the decorated function, no keyword arguments.
3. All arguments are hashable types

4. Metaclass [10 marks]

Write a metaclass, `MethodCounter`, that will add the functionality to a class such that it counts how many times a method is called by any instance of the class. For example, if *a* called `foo` twice and *b* called `foo` once, then the count for `foo` should be three (both *a* and *b* are instances of the class that inherits your metaclass). Remember that it should keep a separate count for each method. Hint: use the built-in function `callable` to check if an attribute is callable.

5. Descriptor [10 marks]

Write a descriptor that will check the type and the range of the managed attribute before allowing it to be stored. The descriptor should also disallow deletion of the managed attribute. Here is how your descriptor is used:

```
class Foo:
    likelihood = Attr(type=float, minimum=0.0, maximum=1.0)
```

Note that omitting any one of the checks results in not making that check. For example, if type is omitted, then type checking is disabled. Similarly, if maximum is omitted, then upper bound is unlimited (not checked). Raise `AttributeError` if the check fails.