

# ECE326

## PROGRAMMING LANGUAGES

### **Lecture 19 : Traits and Iterators**

Kuei (Jack) Sun

ECE

University of Toronto

Fall 2020

# Trait Object

- Rust's equivalent of abstract base class
- Allows for runtime polymorphism
- Use `dyn` keyword to use objects as trait objects
  - Must be placed inside a `Box<T>`

```
fn random_animal(random_number: f64) -> Box<dyn Animal> {  
    if random_number < 0.5 {  
        Box::new(Sheep {})  
    } else {  
        Box::new(Cow {})  
    }  
}  
  
let animal = random_animal(0.234);  
println!("It says {}", animal.noise());
```

```
trait Animal {  
    fn noise(&self)  
        -> &'static str;  
}
```

# Generic Traits

- A trait that takes type parameter
  - Same as other generics, can also have trait bounds
- Enables function overloading
  - Same name, different parameters

```
trait Out<T> {  
    fn write(&mut self, value: T);  
}  
  
impl Out<i64> for ByteArray {  
    fn write(&mut self, value: i64) {  
        let bytes = value.to_be_bytes();  
        self.buffer.extend_from_slice(&bytes);  
    }  
}
```

# Return Type Polymorphism

- Calls different trait method depending on the type of the variable the method's return value is assigned to
  - Type inference does not work in this case
  - C++ does not support this

```
trait In<T> : Buffer {  
    fn from_raw(&mut self) -> T;  
}
```

```
impl In<i32> for ByteArray { ... }  
impl In<i64> for ByteArray { ... }
```

```
// calls ByteArray::In<i32>::from_raw. must specify type here  
let numcols: i32 = bytearray.from_raw();
```

This means the trait `In<T>` requires the trait `Buffer` to also be implemented.

# where

- Allows specifying trait bounds more expressively

```
impl <A: TraitB + TraitC, D: TraitE> MyTrait<A, D> for YourType {}
```

```
// Expressing bounds with a `where` clause
```

```
impl <A, D> MyTrait<A, D> for YourType where A: TraitB + TraitC,  
      D: TraitE {}
```

- Can specify bounds that contains the type parameter

```
trait PrintInOption {  
    fn print_in_option(self);  
}  
impl<T> PrintInOption for T where Option<T>: Debug {  
    fn print_in_option(self) {  
        println!("{}", Some(self));  
    }  
}
```

“Option<T>: Debug”  
is the trait bound  
because that is  
what's being printed.

# Associated Type

- Defines generic types as internal types
  - And not as parameters
- Used by arithmetic operator traits
  - e.g. `Add<Output=T>`

```
struct Imaginary { i: f64, }
struct Complex { r: f64, i: f64, }

impl ops::Add<f64> for Imaginary {
    type Output = Complex;
    fn add(self, rhs: f64) -> Self::Output {
        Complex { i: self.i, r: rhs }
    }
}
```

# Drop trait

- Same as a destructor in C++
- Use if your structure does something special upon drop
- `drop()` function
  - Deletes object immediately

```
struct Droppable { name: &'static str, }  
impl Drop for Droppable {  
    fn drop(&mut self) { println!("> Dropping {}", self.name); }  
}  
  
fn main() {  
    let a = Droppable { name: "a" };  
    drop(a); // `a` deleted here  
            // instead of here  
}
```

# Iterator

- An object which performs the act of iterating
  - An agent which operates on an *iterable*
- Iterable
  - An object that can be iterated (e.g. container such as list)
- Stream
  - Sequence of data made available over time
  - Can have potentially infinite data
  - Example
    - Network connection, Rust range: (x..y), Python range(x, y)



# Iterator

- Two requirements
  1. A way to retrieve the next element
  2. A way to signal end of iteration
- Python iterator
  - `iter()` built-in function

`next()` function will retrieve the next element from iterator, or raise `StopIteration`

```
numbers = [2, 3, 5, 7]
it = iter(numbers)
while True:
    try:
        print(next(it))
    except StopIteration:
        print("End of List")
        break
```

Output:

```
2
3
5
7
End of List
```

# Iterator trait

- Rust iterator implements Iterator trait

```
struct Fibonacci<T> { curr: T, next: T, }  
  
impl<T: Copy + Add<Output=T>> Iterator for Fibonacci<T> {  
    type Item = T;  
    fn next(&mut self) -> Option<T> {  
        let new_next = self.curr + self.next;  
        self.curr = self.next;  
        self.next = new_next;  
        Some(self.curr)  
    }  
}  
  
fn fibonacci() -> Fibonacci<u32> {  
    Fibonacci { curr: 0, next: 1 }  
}  
  
for i in fibonacci() { println!("{}", i); } // infinite loop
```

Rust uses Option  
to determine  
when iteration  
ends (i.e., when  
None is returned)

Iterators are used by  
for loop automatically

# IntoIterator trait

- Containers are *iterables*, not iterators
- But for loop requires an *iterator*
- `into_iter()` method turns containers into iterators
- for loop is just a syntactic sugar

```
let v = vec![2, 3, 5, 7];
let mut iter = v.into_iter();
loop {
    match iter.next() {
        Some(x) => { /* body of for loop */ },
        None => break,
    }
}
```

```
for x in v {
    /* body */
}
```

# Iterator Adapters

- Enjoyed by functional programmers
- Operates on iterators
- `map(closure)`: transforms each element
  - Can even return a different type
- `collect()`: collects elements in iterator into container
  - With ambiguous integers, must specify type

```
let v = vec![3, 6, 8];  
let c = v.iter().map(|&x| { x + 2 }).collect::println!("{}", c); // [5, 8, 10]
```

# Iterator Adapters

- `filter(closure)`: keeps element if closure returns true
- `flatten()`: turns nested vectors into a flattened vector
- `take(n)`: only iterate up to  $n$  times
- `skip(n)`: skip the first  $n$  iterations
- `zip(it)`: takes another iterator *it* and returns a list of tuples where each tuple contains the  $n$ th element of both iterators
  - Use `iter_mut()` if the elements need to be updated

# Sieve of Eratosthenes

```
let starter: Vec<i32> = vec![2, 3, 5, 7];
let largest = 50;

// each integer in starter was mapped into a vector of i32
let composites = starter.iter().map(|&x| -> Vec<i32> {
    ((x+1)..largest).filter(|&y| y % x == 0).collect()
}).collect::<Vec<Vec<i32>>>();
println!("{}", composites);
```

```
[
  [4, 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36,
    38, 40, 42, 44, 46, 48],
  [6, 9, 12, 15, 18, 21, 24, 27, 30, 33, 36, 39, 42, 45, 48],
  [10, 15, 20, 25, 30, 35, 40, 45],
  [14, 21, 28, 35, 42, 49]
]
```

# fold

- Known as `reduce()` in Python
- `fold(accumulator, closure)`
  - Accumulator: an aggregate value of a collection
    - E.g. sum, max, min, average, etc.
    - The argument is the initial value of the accumulator
  - Closure takes two parameters
    - `acc`: the accumulator
    - `x`: each element of the iterator

acc	x	ret
0	1	1
1	2	3
3	3	6

```
let a = [1, 2, 3];  
let sum = a.iter().fold(0, |acc, &x| acc + x); // sum = 6
```

# Higher-order Function

- A function that either/or both:
  - Takes one or more functions as parameters
  - Returns a function as its result
- Normal functions are called “first-order” functions

```
fn twice<A>(function: impl Fn(A) -> A) -> impl Fn(A) -> A {  
    move |a| function(function(a))  
}  
  
fn plusthree(x: i32) -> i32 { x + 3 }  
  
fn main() {  
    let g = twice(plusthree);  
    println!("{}", g(7)); // sum = 13  
}
```

Fn trait is implemented  
by all functions and  
closures without  
mutable references.