

RAP 309 Safety Policy

From Rovipedia, the Rovisys encyclopedia

Approved

Table of Contents

- 1) [MISSION STATEMENT](#)
 - 2) [ROLE RESPONSIBILITY](#)
 - 3) [SAFETY COMMITTEE CHARTER](#)
 - 4) [WORKPLACE SAFETY](#)
 - 5) [TRAINING & EDUCATION](#)
 - 6) [HAZARD COMMUNICATION PROGRAM](#)
 - 7) [IDENTIFYING & CONTROLLING HAZARDS](#)
 - 8) [MEDICAL ASSISTANCE](#)
 - 9) [INCIDENT REPORTING & ANALYSIS](#)
 - 10) [APPENDIX A - OFFICE SPECIFIC INFORMATION](#)
-

1) MISSION STATEMENT

To All Employees,

Employee Safety is one of the most vital aspects of our Company's operations. No operation at our company is significant enough to be done in an unsafe or unhealthy manner. The safer our workplace, the more efficient and profitable our operation is. Our policy is designed to maintain the highest level of safety and minimize accidents.

Our primary goal is zero accidents and injuries in our workplace.

John W. Robertson, CEO

2) ROLE RESPONSIBILITY

Employee Responsibility

Every employee is expected to contribute to a safe and healthy workplace and encourage others to do the same. Contribution includes following safety policy, awareness of potential safety hazards, and alerting management to identified hazards. Employees have the right to expect that they will be provided with a work environment that provides the proper machines and tools to perform their job without possible harm to life and health.

Company Administration Responsibility

Management is ultimately responsible for the safe operation of the business, and delegates authority through Project Managers, Group Managers, the Safety Committee, and safety policy (training/procedures).

Project Manager Responsibility

Project Managers are responsible for obtaining safety requirements from the customer and communicating safety information with employees assigned to their projects. The safety requirements for the job will be documented in the client kickoff meeting minutes and reviewed periodically through the project. Project Managers are ultimately responsible for the safety of their project spaces, coordinating with the project team to mitigate safety issues should they arise in the work space.

Group Manager Responsibility

Group Managers are the primary management contact for most employees, therefore are expected to communicate employee concerns to other areas of management. Group Managers are responsible for disciplining employees not in compliance with policy.

Safety Committee Responsibility

The Safety Committee is responsible for maintaining safety policy, coordinating with RoviSys Continuing Education (RCE) Training for safety training updates, and periodic review of work space compliance.

3) SAFETY COMMITTEE CHARTER

The purpose of the safety committee is to evaluate if company operations follow established policy and to revise policy when needs arise. The committee is responsible for providing information to employees, provide training in coordination with RCE, and soliciting feedback from employees to improve policy.

Safety Committee

Safety Committee includes employees committed to ensuring a safe work environment. Every office must have a safety committee. Responsibilities for Safety Committee members include:

1. Participation in monthly building inspections
2. Participation in safety training and events (e.g. First Aid/CPR training, fire drills)
3. Participation in committee meetings, at the office or enterprise level.
4. Providing input for safety policy or training enhancement.
5. Communicating office-specific safety items to impacted employees.
6. Maintain each office's Hazardous Chemical List and SDSs.

Safety Committee members have no term-limits, but can be excused/appointed as needs arise.

Safety Director

The Safety Committee Leader is responsible for running quarterly enterprise level meetings, verifying that monthly inspections occur for all facilities, addressing action items from inspections, revising policy changes, and communicating information to the company. The Safety Committee Leader is also responsible for coordinating with Human Resources (HR) regarding Occupational Safety and Health Administration (OSHA) requirements.

The active Safety Director is [Pete Madonia](#)

Safety Committee Meetings - Office Level

Each office's safety committee will review the results of monthly inspections, evacuation drills, and other safety-related events and determine if any follow-up action is required. If a meeting is required to discuss and resolve issues, the minutes will be shared with the Safety Committee Leader.

Safety Committee Meetings - Enterprise Level

Quarterly meetings will be held with some members of each office's safety committee and the Safety Committee Leader. The purpose of enterprise level meetings is to review accident reports, discuss identified safety problems, and modify safety policy to address issues.

Contacting the Safety Committee

For any safety related questions or concerns, please contact the safety committee through email at safety@rovisys.com. To find your office's safety committee representative, please visit our [Geographic Locations page](#).

4) WORKPLACE SAFETY

Building Inspections

Every office's safety committee will be responsible for executing inspections of the work place. Rented offices should have a limited scope to items that pertain to the space, however resolution of issues may require coordination with building management. Company management reserves the right to perform periodic, unscheduled building inspections and report violations to the Safety Committee. Building inspections must be conducted monthly and include the following:

1. External doors – verify that exit doors are free of obstruction
2. Fire extinguishers – verify that fire extinguishers are charged, dials showing a safe operating pressure, and initial and date the extinguisher tags. Tags should be reviewed that they are in annual service compliance. Inspection must review every extinguisher in the building and clear any obstruction to access.
3. Emergency lighting – verify that emergency lighting works in the event of power loss (e.g. press test button or identify electrical breakers that can be flipped to test). Inspection must document location of every emergency light/signage in the building.
4. Evacuation route signage – verify that evacuation path signage is up to date in posted locations. Inspection must document location of every sign in the building.
5. Utility inspection – verify that safety-associated utilities are in normal operating condition (e.g. fire sprinkler valve is locked open). Some systems may have tags indicating annual service compliance.
6. Parking lot condition – identify lighting issues, pavement damage, or other hazardous conditions.
7. Shelving safety – identify flimsy conditions or poorly distributed weight on shelves.
8. Dock plate – verify that dock plate can be operated safely
9. Electrical panels – verify that breaker panels are free of obstruction
10. Water heater – verify that tank is free of obstruction
11. Medical station – verify that the medical station is stocked, perform a self-test on the AED, and verify that AED pads are not expired.
12. Employees are encouraged to receive all proper vaccinations if they are comfortable doing so.
13. Safety signage – in places where safety signage is used, verify that signs are visible. Inspection may result in identifying signage need.
14. Generator – verify with IT that generator self-diagnostic messages are operating normally.
15. Review of cubicle/office/checkout work spaces – Cubicle, office and checkout spaces must be reviewed for the following known hazards:
 - Clutter/debris that crowd electrical components or egress paths
 - Electrical cabling that may be damaged and/or show exposed inner cables
 - Places where extension cords are daisy-chained

Evacuation Procedures

Every office's safety committee will be responsible for maintaining an evacuation plan for their building. All employees are expected to follow evacuation procedures should one be ordered. Rented office spaces may be subject to building management plans, but committees still need a company-specific plan for the work space. Evacuations may be ordered by management and emergency response teams per RAP 122. Evacuation plans must be tested yearly and include the following:

1. Documented evacuation paths and muster point(s) – signage must be posted throughout the building, especially in areas visitors typically occupy (e.g. conference rooms). Building floor plans should include fire extinguisher locations.
2. Muster Point organization – a method to account for employees based in the building (e.g. line up by group manager). Methods may differ between offices, but all should include a plan for visitors.
3. Drill-specific procedures – additional steps to be taken in the event of a drill (e.g. coordination with local police/fire/security vendor/building management). Local jurisdictions may require annual drills with police/fire witness.

Office Fire Safety

Every office's Safety Committee will be responsible for training select employees in the use of portable fire extinguishers on an annual basis. Untrained employees are not expected to operate extinguishers. Fire extinguisher are in locations marked throughout each office.

Extinguishers are labeled A, B, C, or D, according to whether the type of fire it can extinguish is ignited on wood or cloth, flammable liquids, or electrical or metal sources. A multi-purpose, dry chemical labeled ABC suppresses most fires including wood, paper, cloth, flammable-liquid, and electrical fires.

Extinguishers come in a dry chemical, foam, carbon dioxide, water, or halon types. The extinguisher should be labeled. The higher the number rating on the extinguisher, the larger the fire it can suppress. High-rated ones are often, but not always, the heavier models. Employees should only operate extinguishers that are within their physical means to wield.

To operate the extinguisher:

1. Pull -- Pull the pin.
2. Aim -- Aim the extinguisher nozzle (horn or hose) at the base of the fire.
3. Squeeze -- Squeeze or press the handle.
4. Sweep -- Sweep from side to side at the base of the fire. Watch for re-flash. Discharge the contents of the extinguisher.

5) TRAINING & EDUCATION

The primary source of safety training will be done in coordination with RoviSys Continuing Education (RCE). Safety training is done as part of the new hire on-boarding process and done periodically with existing employees. The RCI team will manage training based on the policies maintained by the Safety Committee. Reference [RAP 117](#) for more information about RCE.

Based on project requirements, additional training or certification may be required. The Project Manager will be responsible for identifying and coordinating this training with customers. Typically, employees will be required to attend the Onsite Safety training as required for their level of access customer facilities and prior to onsite engineering services. All employees are expected to observe and follow safety rules and regulations of the customer facilities they visit, as well as in the office, and reporting any identified hazards to management and/or the Safety Committee to be investigated. Additionally, the Safety procedure covers the process on how to conduct an internal investigation and the requirements of each employee during investigations.

Current curriculum for Safety Training includes the following:

- [Confined Space Entry Awareness Training](#)
- [Hazard Communication Training](#)
- [Lock Out Tag Out \(LOTO\) Awareness Training](#)
- [NFPA 70E Overview Presentation](#)
- [Personal Protective Equipment \(PPE\) Training](#)
- [Safe Driving](#)

The training record must include name, date, and subject of training.

6) HAZARD COMMUNICATION PROGRAM

In compliance with OSHA Hazard Communication Standard, Title 29 CFR Part 1910.1200, the company maintains a hazardous chemicals list, corresponding Safety Data Sheets (SDSs), labeled containers, and providing adequate

training for their use. This program applies to all work operations in our Company where one may be exposed to hazardous substances under normal working conditions or during an emergency.

The Safety Director is the program coordinator and carries overall responsibility for implementation. The Safety Director will review and update the program as necessary and can be contacted for written copies.

All employees will be trained in Hazard Communication, be informed of the occupational hazards they may encounter, and the measures needed to protect themselves.

Hazardous Chemicals List

The Safety Committees will maintain a list of all hazardous chemicals and related work practices used in their facility and will update the document accordingly. A list is posted and available for each work area, which identifies all the chemicals used in the space. Each list also identifies the corresponding SDS for each chemical. Copies of each office list and chemical SDSs will be maintained by and is available from the Safety Director.

Chemical Safety Data Sheets (SDSs)

Chemical SDSs provide specific information on the chemicals encountered in the workplace. The SDS will be a fully completed OSHA Form 174 or equivalent, and can be obtained from each office's Safety Committee. The Project Manager will validate that onsite Hazard Communication is made available to employees working at customer locations. Employees also have the right to ask a client for site specific SDS.

Labels and Other Forms of Warning

The Safety Committee will ensure that all hazardous chemicals in our building are properly labeled and updated. Chemicals should not be brought by vendors or other employees without adequate hazard labeling, corresponding SDS, and name and address of the manufacturer, importer, or other responsible party. Labels identifying hazards in the office or onsite dangers at customer locations are not to be removed or defaced by employees. Words, pictures symbols, or combinations thereof can be used to address the appropriate hazard warnings.

Non-Routine Tasks

When required to perform hazardous, non-routine tasks (e.g. cleaning tanks, entering confined spaces, etc.), adequate training is required prior to task execution. This training must include information about hazardous chemicals and the proper precautions to take to reduce or avoid exposure.

Exposure

Upon discovery of an exposure to a hazardous chemical (e.g. natural gas) within a work space, all employees are to suspend work immediately, evacuate the area, and inform the Safety Director and the office's Safety Committee. Access to the area will be suspended until the hazard has been mitigated.

Training

For the majority of company employees, chemical hazards within the office settings are limited primarily to janitorial and other cleaning supplies. Employees that visit customer facilities have the potential of exposure to any chemical in those locations, and typically are provided safety training that includes SDS information prior to starting work activities. The Project Manager is responsible for coordinating time for this training to occur as part of the project schedule. When new hazards are introduced in either the office or a customer facility, training and awareness must be provided and communicated.

Contractors

The Safety Committee and/or Safety Director will personally advise outside contractors of any chemical hazards that may be encountered in the normal course of their work on the premises. The brief should cover the labeling system in use, the protective measures to be taken, and safe handling procedures to be used. In addition, the Safety Director will notify these individuals of the location and availability of SDSs. Each contractor bringing chemicals onsite must provide the company with appropriate hazard information on these substances, including the labels

used and the precautionary measures to be taken in working with these chemicals. Project Managers that are managing contractors within project scope must communicate the same expectations of company employees: that contractors are expected to follow the safety rules of client facility and receive adequate training to perform their tasks.

Additional Information

All employees, or their designated representatives, can obtain further information on this written program, the hazard communication standard, applicable SDSs, and chemical information lists from the Safety Director.

All employees must be proficient in English so safety signage can be understood and heeded.

7) IDENTIFYING & CONTROLLING HAZARDS

It is the responsibility of all employees to be aware of their surroundings and to identify hazards that pose a danger to themselves and others. Employees should only perform tasks that they are physically capable of executing and that the employee has adequate equipment to complete safely.

General Safety Rules

1. Good housekeeping is essential and must be maintained at all times.
2. All employees must know the location of emergency equipment and emergency exits for the work spaces they occupy.
3. Employees who feel ill should inform their supervisor.
4. Operation of any equipment or machinery is prohibited unless proper instructions have been given and proper authorization obtained.
5. Horseplay or scuffling on company property is prohibited.
6. Only tools or equipment approved by an authorized supervisor shall be used.
7. Persons whose work requires them to go to other companies must familiarize themselves with and must observe safety rules governing that company.
8. Firearms or weapons of any type are not permitted within company buildings.
9. Intoxicants or persons under the influence of intoxicants will not be permitted within the company buildings.
10. Climbing or standing on machinery is prohibited unless special permission is given by the manager of the work to be done.
11. Compressed air may be used for purposes of cleaning equipment or machinery only when specific authorization is given. Compressed air is never to be directed at a person.
12. Lifting beyond one's means or lifting improperly can cause serious injury. Lift with back straight. If the weight is excessive -- get help.
13. All safety guards must be in place before any machine is operated, unless direct consent is given by one's immediate supervisor.
14. Protective equipment of an approved type must be worn at all times where designated.
15. Exits, corridors, stairways and passageways must be kept lighted and clear at all times.
16. Volatile liquids are to be stored in a designated area and are not to be used as cleaning agents, except when approved by the Safety Committee.
17. Unauthorized changing or removal of safety guards is prohibited.
18. Any treatment of injuries while on company property must be done by authorized personnel only.
19. If the conditions of a region create a special danger to employees, then the area is to be protected by ropes, guards, and/or signs. Admittance to or passage through this area is prohibited, except to employees authorized to work in that area or by permission of the job manager.
20. Running on company property is prohibited, except in case of emergency or authorized recreation.
21. Operation of equipment or machinery having "Danger Do Not Operate" tags is prohibited. These tags are for control where there is a safety hazard involved. Use lock out tags when working on machinery.

22. Use ladders safely. Make sure ladders are safe before using. Ladder rungs, cleats, and steps shall be parallel, level, and uniformly spaced, when the ladder is in position for use. Ladders shall be inspected by a safety committee for visible defects on a periodic basis and after any occurrence that could compromise their safe use. Ladders are to be placed on a stable, level surface. Employees are not to stand above two rungs or the top of step ladders. Employees shall not carry anything in their hands that may cause injury, in case of a fall, and must face the ladder when ascending or descending. The ladder side rails shall extend at least 3 feet (.9m) above the upper landing surface. Extension ladders shall be placed on a 4:1 ratio. When ladders are not able to be extended then the ladder shall be secured at its top to a rigid support that will not deflect. Ladders shall not be loaded beyond the maximum intended load for which they were built, or beyond the manufacturer's rated capacity. Ladders shall be used only for the purpose for which they are designed. Defective ladders will be tagged and removed from service
23. All employees have the right to stop work if they see a situation on the job that is unsafe or if they observe others engage in unsafe actions/behaviors. Employees are trained to recognize potential hazards and stop work immediately if they perceive a potential hazard. Employees also have the right to stop work when the control of a safety/hazardous risk is not clearly understood. If an employee recognizes a potential hazard on the job, they shall notify the Project Manager (PM) immediately. Employees who stop work due to a potential risk will not be subject to discipline. All areas of the potential hazard must be marked appropriately to alert employees of the hazard. The PM will review all employee concerns related to the stop work authority and assess whether work can be safely resumed without modification. If the conditions are deemed hazardous then, the PM will stop work until proper modifications have been made to ensure employee and environmental safety. Once the conditions have been deemed safe, then work may resume and the PM will follow up with the employee(s). The PM will communicate the safety concern to their Group Manager (GM) who will communicate employee concerns with the rest of the management team to better ensure safety needs are addressed in the future. All stop work authority cases will be documented by the employee in writing and submitted to Safety Committee for review. The Safety Committee will help address, investigate, and follow up on all safety concerns brought to the attention of the committee.
24. Spill prevention: All Chemical substances should be stored in proper containers to minimize the potential for a spill. Whenever possible, chemicals shall be kept in closed containers and stored so they are not exposed to stormwater. Due to the nature of our work at RoviSys, our engineers and developers are rarely exposed to or handle chemicals. However, in the event a spill takes place at a customer site, employees shall follow the customer's safety policies to safely clean up the spill or alert the appropriate department. If a spill occurs in the office and is deemed safe to clean up, an employee shall have reasonable access to materials to clean the spill such as paper towelettes, etc. Supplies shall be easily accessible when required, and considerations must be made for both the type and quantity of materials. If management deems training necessary for an employee to undergo spill prevention training, then the employee shall complete spill prevention, response and procedures training. If a spill happens that may cause injury, property damage, and/or environmental harm the employee is to immediately notify their project manager of the spill. From there, the project manager may notify environmental authorities if applicable.

Personal Protective Equipment

Personal protection equipment is required where administrative controls cannot be used or when engineering controls are not feasible. Project managers are responsible for meeting with customers to conduct a hazard assessment before onsite work for that customer has begun. Once the project manager and client identify and address any potential onsite hazards, the project manager is responsible for verifying that the project team has access to the required safety equipment and procuring them in cases where the customer does not (e.g. Fire-protection overalls, oxygen (O2) deficiency monitors). Employees will be informed when and what PPE is necessary, including the proper use and fit of PPE. Training will also include the limitations, proper care and maintenance, the useful life and disposal of PPE, and signage associated with different types of PPE. Employees will be retrained on PPE if deemed necessary by the project manager.

Typically, employees are issued head, eye, and ear protection prior to the first visit onsite or task requiring them. Employees must acquire their own pair of safety shoes that can be expensed to the Safety project. Each employee is responsible for maintaining their PPE, and requesting/returning checked out PPE assets. Employees can request replacement PPE in the event their current equipment is not in working order. If PPE is defective, damaged, or broken, it will be removed from service. PPE should be inspected before every use to check for wear and tear. If PPE is faulty, they should not be used and new equipment should be acquired.

Each office has a location where PPE is stored, and a person assigned to manage the PPE inventory.

Regarding specific types of PPE, the following types of equipment must meet the requirements of the American National Standards Institute (ANSI) or OSHA standard listed:

- Eye and Face Protection – ANSI Z87.1-1989
- Head Protection – ANSI Z89.1-1986, ANSI Z89.2-1971 in high-voltage applications
- Hearing Protection – OSHA 29 CFR Part 1910.95
- Foot Protection – ANSI Z41-1991

Other PPE types may be required for onsite activities. This includes but isn't limited to:

- Body Protection (e.g. Fire Resistant outer clothing)
- Respiratory Protection (e.g. Air-purifying mask)

Any employees not using personal protection equipment where required will be subject to a warning, and if repeated offenses are committed, the more penalizing action of layoff without pay, and finally, termination.

Policy:

First Offense -- Verbal Warning.

Second Offense -- Warning letter and a discussion with Group Manager about the violation.

Third Offense -- One-day suspension without pay.

Fourth Offense -- Five-day suspension without pay.

Fifth Offense -- Termination.

General PPE Requirements

To ensure the greatest possible protection for employees in the workplace, the cooperative efforts of both employers and employees will help in establishing and maintaining a safe and healthful work environment.

In general, employers are responsible for:

- Performing a hazard assessment of the workplace to identify and control physical and health hazards.
- Identifying and providing appropriate **PPE** for employees.
- Training employees in the use and care of **PPE**.
- Maintaining **PPE**, including replacing worn or damaged **PPE**. PPE Should be inspected before every use!!
- Periodically reviewing, updating, and evaluating the effectiveness of the **PPE** program.

In general, employees should:

- Properly wear **PPE**.
- Attend training sessions on **PPE**.
- Care for, clean, and maintain **PPE**.
- Inform a supervisor of the need to repair or replace **PPE**.

It is the responsibility of the project manager to obtain the safety requirements from the customer and communicate them to the project team. Team members are expected to properly prepare for their current project

work environment.

Hearing Protection

Employee exposure to noise depends upon several factors:

- The loudness of the noise measured in decibels (dB).
- The duration of each employee's exposure to the noise.
- Whether the employee moves between work areas with different noise levels.
- Whether the noise is generated from more than one source.

Some types of hearing protection include:

- Single-Use Earplugs – Made of cotton, foam or rubber. When inserted properly, work almost as well as molded earplugs.
- Pre-formed or molded earplugs – Must be individually fitted by a professional and can be reusable. Reusable plug should be cleaned after each use.
- Earmuffs – Require a perfect seal around the ear. Glasses, facial hair or facial movement such as chewing may reduce effectiveness.

Generally, the louder the noise, the shorter the exposure time before hearing protection is required. The table below shows the permissible noise exposures that require hearing protection for employees exposed to occupational noise at specific decibel levels for specific time periods. Noise is considered continuous if the interval between the occurrences is one second or less. Noises not meeting this description are considered impact or impulse noise, and exposure to this type of noise must not exceed 140 dB.

Employees exposed to loud and frequent noises that can cause ear damage may receive annual training on hearing protection and related **PPE** devices.

If an employee is exposed to noise that is 85 dBA or louder on an eight hour time weighted average (TWA), then the employee must wear proper **PPE** to prevent hearing loss during the work day.

Permissible Noise Exposures

Duration per day, in hours:	*Sound Level (dB)
8	90
6	92
4	95
3	97
2	100
1 1/2	102
1	105
1/2	110
1/4 or less	115

Source: 29 CFR 1910.95, Table G-16.

More info found in [Personal Protective Equipment Training](#)

Combustibles

1. Limit the storage of combustible materials inside buildings to a one-day supply only.
2. Quantity storage should be outside of building in an area approved by a City Fire Marshall.

3. Make sure that a container used to store flammable liquids inside a building is an approved safety can and stored in a clearly marked area. Keep the area free of paper, rags, or any debris.
4. Familiarize all personnel in the general work area with the areas to store and use material, proper handling, and what to do in the event of explosion or fire.

Machinery

Machinery or work connected with machine operation has long been the source of many serious and disabling accidents. The most effective approach to eliminating accidents involving machinery is the same approach we should use to eliminate any potential injury source.

Remove the hazard. If this is not possible, then one should:

- Provide adequate protection against the hazard, as to shield the operator from pinch points and safeguard the point of operation.
- Educate associated personnel in the effective use of safeguards provided.

Hand Tools

Injuries resulting from the misuse of tools, or use of defective tools, account for numerous injuries each year. The disabilities include loss of vision, puncture wounds from flying chips and slivers from concussion tools, severed tendons and arteries from cutting tools, broken bones from slipping wrenches, and many others.

There are six safe practices that will eliminate most powered, hand tool accidents.

1. **Personal Protective Equipment.** Employees using hand tools should wear appropriate PPE, including eye, hand, and ear protection. Head and breathing protection may be required, depending on the application. Do NOT remove metal shavings with exposed hands.
2. **Use the right tool for the right job, and use it correctly.** Do not misuse tools. Some examples of misuse are using a file for a pry bar, a wrench for a hammer, or pliers instead of a proper wrench. If an employee is unsure of how to use a tool, ask a knowledgeable resource or contact the Project Manager if one cannot be identified. Keep moving tools free of objection (e.g. rags, wires, etc.). Some machines may pose a risk if adjusted while in motion, so stop movement and use of the tool prior to adjustment.
3. **Keep tools in safe repair** - all hand and power tools shall be maintained in a safe condition. Examples of poor tools that should not be used and repaired or discarded include: wrenches with worn jaws, screwdrivers with cracked handles or sharp points, worn extension cords or electric tools with broken plugs, and chisels with mushroomed heads.
4. **Reporting of defective tools.** A periodic check for defective tools should be made by all supervisors. Damaged tools shall be taken out of service or "locked out". In addition, all employees should be instructed to report inadequate tools to their supervisor.
5. **Guarding.** While an applicable tool is in use, guards shall be in place and operable at all times without need to manipulate the guard and possibly, compromise its intended use.
6. **Train employees in proper use and care of tools.** A tool designed and selected as a safe tool can be the cause of serious injury if used improperly. An example would be a screwdriver or drill applied, with force, to an object in a direction toward a part of the body. Improper handling or storage of tools can also present hazards such as extension cords on floor, a hand screwdriver or file carried in the pocket, and placing heavy tools near the edge of one's work table.

Material Handling & Lifting

Manual handling and lifting of materials

Accidents that occur while manually handling materials are primarily the result of one of the following:

- Unsafe working habits.
- Improper lifting.
- Lifting and/or carrying too heavy a load.
- Improper grasp when raising/carrying an item.
- Bad housekeeping.

Principles to be observed when lifting and carrying an object:

1. First, make a preliminary "heft" to be sure that the load is within one's lifting capacity. If it is not, acquire help.
2. Set feet solidly and well apart, with one foot slightly ahead of the other. In some cases, it may be easier to bend one knee, almost to the floor, while keeping the other leg bent at a 90-degree angle.
3. Crouch as close to the load as possible, with the legs bent at about a 90-degree angle at the knees.
4. Keep the back as straight as possible. It should not be arched.
5. Get a firm grip on the object. If necessary, lift one end slightly to secure a hand under it. Grip the load in a fashion that ensures that hands will be protected and that it will not slip while being carried.
6. To lift the object, straighten the legs, keeping the back straight.
7. Before lifting a load to be carried, determine the distance to be traveled and the length of time needed to maintain a grip.
8. A firm grip should be made and the object should not be shifted after being raised to a carrying position. If the load must be shifted, rest the end of the object on a support while doing so.
9. Supervisors may periodically evaluate current work station configurations and employees' work techniques to assess the potential for and prevention of injuries.

Employees will be trained on proper lifting technique based on their supervisors discretion. If an employee is working at a customer location that requires frequent or heavy lifting, RoviSys management will review the manual lifting steps highlighted above with its employees.

Lowering an object to the floor is essentially the reverse of lifting it. Keep the back straight and bend the legs to lower the object to the floor. Heavy objects should be stored at about waist height.

If an employee sustains an injury while lifting an object, management may conduct an investigation to determine the exact cause of injury. This investigation will evaluate the employees lifting technique highlighted above and may include interviews with witnesses. The goal of the investigation is to educate our employees on proper lifting technique to avoid future injuries. Any findings from the investigation may be reported to the RoviSys Safety Committee for future training to prevent injuries.

When deemed necessary by RoviSys management, supervisors may periodically evaluate work station configuration and employee's work techniques to assess the potential for and prevention of injuries.

Material Handling -- Equipment and Machinery. While mechanical equipment eliminates a great number of sprains and strains, these devices bring about another nature of safety problems. Improper use of mechanical equipment can result in even more serious injuries than the manual handling of materials.

Industrial - Power Lift Trucks - General:

1. Defective flooring is a major cause of accidents involving material handling by trucks. Report unsafe floor or road conditions without delay.
2. If there is uncertainty about the weight of an object or the strength of a floor support, request information from a supervisor.
3. Do not overload or overfill racks or bins used for storage.

4. Do not stack or pile materials too high, especially items that are likely to tip easily and fall.
5. Obstructions protruding into aisles or passageways should be removed before they cause accidents. Take time to move such materials or notify a supervisor.
6. Defective equipment should be reported without delay. Never operate faulty accessories.
7. Use special care when carrying or placing materials near unit heaters, electric wiring, lights, pipes, and other fragile or dangerous equipment.

Bridge Plates (crossover ramp from dock to vehicle):

1. Be sure that the bridge plate is strong enough to carry the load (Note: carrying capacity is often marked on the plate).
2. It should be secured in place so that there is no chance of it shifting or slipping.
3. It should be inspected regularly.
4. The end edges should have substantial contact with the dock, loading platform, carrier, etc., so that there will be no rocking or sliding.

Heat Illness Safety

RoviSys requires all obligated employees to review heat illness safety prevention annually. All employees who are working in manufacturing areas shall inquire on the demands needed to adhere to Heat Illnesses safety policy.

There are several different types of Heat Illnesses that employees can be affected by while working on a job. The types of Heat Illnesses are heat stroke, heat exhaustion, heat syncope, heat cramps, and heat rash. Heat illness is caused by the body not being able to properly cool itself down via sweating. These heat related stresses can be avoided if employees and managers take the proper precautions to avoid them. Employees who work in hot and humid condition are especially at risk for heat illness. An employee's risk increases if he or she is performing high exerting tasks or wearing PPE.

To avoid and prevent heat related illnesses employees should take the following precautions:

- Employees must have access to and the ability to drink water every 15 minutes.
- Take time to rest in a cool place, such as a shaded area, to cool down.
- If possible, wear a hat and light-colored clothing.
- Remember to build up tolerance for the strenuous work, and to not overdue it.

Employees and managers should be aware of their surroundings and keep an eye on fellow workers so that a victim of any type of heat illness receives proper care as soon as possible. If deemed necessary, management may receive heat illness prevention training prior to supervising employees if it is necessary for a customer project.

Below are the symptoms and proper first aid procedures for each heat illness according to the CDC:

The symptoms of Heat Stroke are:

- Hot, dry skin or profuse sweating
- Hallucinations
- Chills
- Throbbing headache
- High body temperature
- Confusion and or dizziness
- Slurred speech

The proper first aid for Heat Stroke is:

- Call 911 immediately and notify the manager

- Attempt to cool the worker down

The symptoms of Heat Exhaustion are:

- Heavy sweating
- Extreme weakness or fatigue
- Confusion and or dizziness
- Nausea
- Clammy, moist skin
- Pale or flushed complexion
- Muscle cramps
- Slightly elevated body temperature
- Fast and shallow breathing

The proper first aid for Heat Exhaustion is:

- Have the affected worker rest in a cool area
- Have them rehydrate with water or other cool nonalcoholic beverages
- Have the worker take a cool shower, bath or sponge bath

The symptoms of Heat Syncope are:

- Light-headedness
- Dizziness
- Fainting

The proper first aid for Heat Syncope is:

- When the employee starts to feel symptoms have them relax in a cool place
- Have them hydrate themselves with water or another nonalcoholic beverage

The symptoms of Heat Cramps are:

- Muscle pain or spasms
- Usually located in abdomen, legs, or arms

The proper first aid for Heat Cramps is:

- Stop all activity immediately and relax in a cool place
- Hydrate with a clear juice or sports drink
- Do not participate in strenuous activities for several hours after the cramps subside
- Contact medical personnel if the employee has heart problems, is on a low sodium diet, or if cramps do not subside within one (1) hour

The symptoms of Heat Rash are:

- It looks like a red cluster of pimples
- It is likely to occur on the neck and upper chest, in the groin area, under the breasts, and in and around the elbows

The proper first aid for Heat Rash is:

- Try to have the employee work in a cooler less humid environment if possible

- Keep the affected area dry
- Use dusting powder to increase comfort and dryness

All management personal is required to understand the signs and symptoms listed above to heat illness and how to treat it.

If deemed necessary for a project or work environment, management may ensure personal factors that contribute to heat related illness are taken into consideration before assigning a task where there is the possibility of a heat-related illness occurring. The most common personal factors that can contribute to heat related illness are age, weight/fitness, drug/alcohol use, prior heat-related illness, etc.

Ammonia Awareness

Ammonia Awareness

Possible Exposures Examples:

- (1) Working on/near industrial refrigeration machinery rooms, equipment and/or piping.
- (2) Working in petroleum refineries; or
- (3) Working with/near agricultural fertilizer.

Ammonia is a colorless gas under normal conditions. It can be a liquid under pressure. It has a pungent, suffocating odor. Anhydrous Ammonia is attracted to water and at ambient temperature is mainly a gas.

High concentrations of ammonia gas, liquid ammonia and solutions of ammonia can cause harm if inhaled or if they come into contact with eyes or skin.

Exposure of the eyes to ammonia may cause burning, tearing, temporary blindness and severe eye damage. Exposure of the skin to ammonia may cause severe burns and blistering. Exposure of the respiratory tract (mouth, nose and throat) to ammonia may cause runny nose, coughing, chest pain, severe breathing difficulties, severe burns and death.

Employees will be provided with and required to use impervious clothing, gloves, face shields and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid anhydrous ammonia or aqueous solutions of ammonia containing more than 10% by weight of ammonia. Similar precautions should be taken to prevent the skin from becoming frozen from contact with vessels containing liquid anhydrous ammonia.

Employees should be aware of clients' contingency plans and provisions. Employees must be informed when ammonia is used in the host facility and aware of additional plant safety rules.

If release of Ammonia:

There is no antidote for ammonia poisoning. First aid consists of decontamination, maintaining open airway, and respiration support followed by rapid transport to an advanced medical care facility. After decontamination no special protective clothing is required for those caring for the injured.

If ammonia is released, immediately put on a suitable respirator and leave the area until the severity of the release is determined. In case of leaks or spills, escape-type respiratory protective equipment should be available in the work area. Never work alone with this chemical.

Vehicle Safety

The Company's largest potential for monetary loss and the greatest exposure of its employees to major injuries, even fatalities, lie within the operation of motor vehicles.

A safe driver training course will be provided to all employees.

Fall Protection

- Training can be provided for each employee who might be exposed to fall hazards. The training will enable each employee to recognize the hazards of falling and the procedures to follow to minimize these hazards. Records showing participants, training dates and signatures of instructors must be maintained.
- Re-training will be provided when there are deficiencies in training, when work practices are changed or when fall protection equipment is modified.
- Fall protection is required whenever employees are potentially exposed to falls from heights that exceed applicable regulatory thresholds. Guard rails, safety nets, or personal or fall arrest systems should be used. Some applicable regulatory thresholds may include:

General Industry 1910.28(b)(1)(i) - Protection for wall openings and holes. Every wall opening from which there is a drop of more than 4 feet shall be guarded.

Construction Industry 1926.501(b)(1) - Unprotected sides and edges. Each employee on a walking/working surface (horizontal and vertical surface) with an unprotected side or edge which is 6 feet (1.8 m) or more above a lower level shall be protected from falling by the use of guardrail systems, safety net systems, or personal fall arrest systems.

Marine Terminals 1917.112(b)(1) - Guardrails shall be provided at locations where employees are exposed to floor or wall openings or waterside edges, including bridges or gangway-like structures leading to pilings or vessel mooring or berthing installations, which present a hazard of falling more than 4 feet (1.22 m) or into the water.

Shipyard Industry 1915.73(d) - When employees are exposed to unguarded edges of decks, platforms, flats, and similar flat surfaces, more than 5 feet above a solid surface, the edges shall be guarded by adequate guardrails.

Steel Erection 1926.760(a)(1) - Each employee engaged in a steel erection activity who is on a walking/working surface with an unprotected side or edge more than 15 feet (4.6 m) above a lower level shall be protected from fall hazards by guardrail systems, safety net systems, personal fall arrest systems, positioning device systems or fall restraint systems.

- Incidents will be investigated. The investigation will look at the fall protection plan to see if any updates are needed to keep the incident from happening again.
- Equipment and services for prompt rescue of fallen workers must be available before elevated work begins. Local fire departments may not have the means to perform safe and efficient rescue, so do not assume they are able to do so.

8) MEDICAL ASSISTANCE

The company maintains training for several first-responders (CPR/First Aid/Bloodborne Pathogen). Training is provided by either through Cintas or Swift First Aid depending on location. Reference [this page](#) for the current list. Even the smallest injury, if not given proper attention, may result in a serious infection. Serious injuries, such as fractures or severed blood vessels, can result in greater injury where movement of the patient or improper treatment is administered. Employees are not required or expected to provide emergency care to others during the normal course of their work, and first aid treatment should be administered by qualified employees only. When in doubt, do not move the injured party and call an ambulance.

First Aid Kits

First aid kits sent to job sites shall have their contents checked before being sent to the site and will be checked weekly while at the job site to ensure that expended items are replaced.

First Aid Station

Each Office maintains a location for first aid supplies for minor injuries and ailments (bandages, pain relievers, eye wash station, cough-drops, etc.). These stations are reviewed as part of office inspections by the Safety Committee and are resupplied by an outside vendor. Employees can use these stations whenever self-care is needed. If the employee need help tending to the injury, every station includes a list of trained first responders and their contact info.

Medical Treatment

If professional medical care is necessary for an employee due to a work-related injury, the employee may choose a location/physician of their choice, otherwise the nearest hospital/emergency room will be selected. In locations where regional emergency response services are unavailable, the Project Manager is responsible for identifying contact information for nearby hospital and ambulance services. The record of treatment must be communicated to HR, and HR will route non-confidential information to the employee's Division Director. Reimbursement for medical emergency services may be requested in coordination with HR and the Division Director.

Bloodborne Pathogens

Bloodborne Pathogens means pathogenic microorganisms that are present in human blood and can cause disease in humans. These pathogens include, but are not limited to, hepatitis B virus (HBV) and human immunodeficiency virus (HIV).

Consistent with Title 29, part 1910 of the Code of Federal Regulations, which became effective on March 6, 1992, it is company policy to limit all occupational exposure to blood or other potentially infectious materials, since any exposure could result in transmission of bloodborne pathogens which could lead to disease or death. "Good Samaritan" acts, such as assisting a co-worker with a nosebleed, would not be considered occupational exposure.

Training will be done on a continual basis, at least annually, for those employees who may have incidence of occupational exposure. These training records, containing the date and contents of training, will be maintained for a minimum of three years. Medical records shall be maintained for the duration of employment plus thirty years.

Occupational Exposure encompasses any reasonably anticipated skin, eye, mucous membrane, or parenteral contact with blood or other potentially infectious materials that may result from the performance of an employee's duties.

The company does not have occupational exposure risk for all job functions, but has taken the initiative to create an exposure control plan. This written plan is available to all employees [through Rovipedia](#) and the Human Resources Department. The company is also not required to implement work practice controls or antiseptic hand washing areas. However, the company provides hand cleansers and towelettes in our first aid cabinet for any employee to use. Containers for handling, transport, and storage are also not applicable. However should containers be applicable, leak proof bags/containers would need to be used for the handling, storage and transport of specimens of blood or other potentially infectious materials.

This exposure determination is made without regard to personal protective equipment, which may or may not be available. Should PPE become required, The company would provide this at no cost to the employee. Should an occupational exposure be determined in the future, the hepatitis B vaccine would be made available to all employees that have the aforementioned exposure at no monetary cost.

Employees are expected to avoid contact with blood and body fluids of others since all bodily fluids should be considered potentially infectious. Employees should direct the cleaning of blood or other infectious materials to someone who can contact professionals skilled in these matters, such as any member of the Safety Committee or to the on-site Project Manager.

The company ensures that all records required by this section shall be made available for examination & copying upon request of employees, the Assistant Secretary, and the Director. Medical records must have written consent of employee before released. When transferring records, the employer shall comply with the requirements set forth in 29 CFR 1910.1020(h).

9) INCIDENT REPORTING & ANALYSIS

All incidents will be subject to investigation. The purpose of investigation is to understand the chain of events that led to the incident. While determining the root cause of the incident, the PM may interview the employee(s) responsible, interview witnesses, and access the environment/location (equipment being used, lighting, noise, etc.) of the incident. PM's will be supplied with the appropriate equipment to conduct an internal investigation such as, paper/pen, measuring tape, and may view security cameras at the customers discretion. Any tangible evidence related to the incident may be collected for record keeping by PM. The PM will gather all information related to the incident and compile the facts into a written report that will be sent to the Group Manager (GM) and Safety committee for record keeping and investigation. Record-keeping is essential in preventing occupational injuries, illnesses, and fatalities because it allows safety and health professionals to identify and eliminate hazards. All occupational injuries and illnesses meeting the OSHA definition for a recordable injury will be recorded on an OSHA Form 300. The current year's OSHA Form 300 is available in the Sales project under **Sales > RoviSys Commercial Information > OSHA 300 Logs**.

Incident Definition

Per OSHA Form 300, the company must record information about every work-related injury, illness, or death that involves the following:

1. Loss of consciousness
2. Restricted work activity or job transfer
3. Days away from work
4. Medical treatment beyond first-aid
5. Injuries/illnesses diagnosed by a physician or licensed health care professional.

OSHA Form 301 or the equivalent state form will be used to report accidents to management. The form must be filled out within seven calendar days once an incident has been reported to management. The form will be filled out with the Safety Director the injured party, and a Human Resources representative. If the incident occurred during project related activities, the Project Manager must be present. If the injured party cannot be present for reporting, the injured party's Group Manager must be present.

Completed 301 forms will be reviewed by the Safety Committee as part of revised training consideration on an annual basis. OSHA Form 300 must be utilized to post a summary of all recordable accidents and injuries from February 1st through April 30th for the year that is being summarized. OSHA Form 300A will be signed by a company official. Human Resources is responsible for maintaining OSHA Form 300. All records must be maintained for five years following the end of the calendar year to which they relate. Additional records will be kept, if essential, to comply with other Local, State, and Federal requirements.

Hazard Analysis

Accidents and injuries may be analyzed to identify trends and specific areas to address accident prevention. This review is an optional recommendation of OSHA Form 300 and will be performed during the form's preparation in the event recordable incidents have occurred.

OSHA Serious Event Reporting

The Occupational Safety and Health Administration requires reporting of Serious Events. Serious Events are identified as:

1. Incidents that result in work-related, in-patient hospitalization, amputation, or loss of an eye. These incidents must be reported within 24 hours to OSHA and the client facility.
2. Incidents that result in a fatality must be reported within 8 hours.

Incidents that do not require reporting include the following:

1. Motor vehicle accidents on public street or highway (except for construction/work zones)
2. Incidents in commercial or public transportation systems (e.g. airplane, bus)
3. Hospitalization for diagnostic testing or observation

The Safety Director will be responsible for meeting OSHA reporting requirements in coordination with the Project Manager, if applicable. The reporting party must be prepared to supply the following:

- Business name
- Name(s) of employees affected
- Location and time of the incident
- A brief description of the incident
- Company contact person and phone number

To make a report to OSHA, use one of the following methods.

1. Call the nearest OSHA office, reference the Appendix A below.
2. Call the OSHA 24-hour hotline at 1-800-321-6742
3. [Report online](https://www.osha-slc.gov) at osha.gov.

10) APPENDIX A - OFFICE SPECIFIC INFORMATION

Danner

- First Aid Station: North Checkout next to Janitor's Closet
- PPE Location: North Checkout Printer Area
- [Inspection Form](#)
- [Evacuation Plan](#)
- OSHA Office – Cleveland Area Office, Essex Place, 6393 Oak Tree Blvd., Suite 203, Independence, Ohio 44131-6964. (216) 447-4194

Holly Springs

- First Aid Station: Next to water fountain by Fitness Room & bathrooms
- PPE Location: Contact [Cyndi Conway](#)
- [Inspection Form](#)
- [Evacuation Plan](#)
- OSHA Office – The North Carolina State Plan exercises jurisdiction over all public and private employers. Raleigh State Plan Office, 111 Hillsborough Street, Raleigh, NC 27601. (919) 779-8560

Campus

- First Aid Station: Checkout, near the vending machines
- PPE Location: Checkout
- [Inspection Form](#)
- [Evacuation Plan](#)

- OSHA Office – Cleveland Area Office, Essex Place, 6393 Oak Tree Blvd., Suite 203, Independence, Ohio 44131-6964. (216) 447-4194

Boston

- First Aid Station: Kitchen, opposite the refrigerator
- PPE Location: TBD
- [Inspection Form](#)
- Evacuation Plan: TBD
- OSHA Office - Springfield Area Office, 1441 Main Street, Room 550, Springfield, MA 01103-1493. (413)785-0123

Houston

- First Aid Station: In Kitchen, on wall adjacent to refrigerator
- PPE Location: Stored in server room.
- [Inspection Form](#)
- [Evacuation Plan](#)
- OSHA Office - Houston North Area Office, 690 S. Loop 336 W., Suite 400, Conroe, Texas 77304. (936) 760-3800

Netherlands

- First Aid Station: First aid stations are located in the kitchen cabinets at each office. Marked with a Green and white cross on the outside of the door.
- PPE Location: PPE is located in the large shelves at the Reactorweg 301 office.
- [Inspection Form](#)
- [Evacuation Plan](#)
- OSHA Office – Netherlands is under the jurisdiction of the European Agency for Safety and Health at Work and the Ministry of Social Affairs and Employment of the Netherlands.

Thousand Oaks

- First Aid Station: Outside of checkout bathroom
- PPE Location: CO1 Shelves
- [Inspection Form](#)
- [Evacuation Plan](#)
- OSHA Office - The California State Plan exercises jurisdiction over all public and private employers. San Diego State Plan Office, 7575 Metropolitan Drive, Suite 207, San Diego, CA 92108. (619) 767-2280.

Atlanta

- First Aid Station: Column near CR1
- PPE Location: Storage Cabinet in Checkout Area
- [Inspection Form](#)
- [Evacuation Plan](#)
- OSHA Office – 2296 Henderson Mill Rd, Atlanta, GA 30345 (770) 493-6644

Michigan

- First Aid Station: TBD
- PPE Location: STBD

- Inspection Form: TBD
- Evacuation Plan: TBD
- OSHA Office – TBD

Dublin

- First Aid Station: TBD
- PPE Location: TBD
- Inspection Form: TBD
- Evacuation Plan: TBD
- OSHA Office – TBD

Page History

Revision	Action/Comment	Date	User
r84 (this)	Approve	30-Jun-2023 1:07 UTC	Austin Beamish
r84 (this)	Create/Edit <i>Addition of Dublin office</i>	23-May-2023 2:52 UTC	Stephen Troutner
r83	Approve	15-Mar-2023 7:25 UTC	Beverly Kiglics
r83	Create/Edit <i>Updated for Netherlands</i>	1-Feb-2023 12:29 UTC	Ty Rinholm
r82	Approve	3-Jan-2023 4:54 UTC	Joshua Hilewick
r82	Create/Edit <i>Fixed Typo</i>	3-Jan-2023 4:13 UTC	Beverly Kiglics
r81	Approve	3-Jan-2023 3:52 UTC	Beverly Kiglics
r81	Create/Edit <i>restore corrupted content (rev78/79 b...</i>	3-Jan-2023 2:06 UTC	Joshua Hilewick
r79	Approve	9-Nov-2022 6:04 UTC	Joshua Hilewick
r80	Create/Edit <i>Typo, pretty sure it's supposed to sa...</i>	5-May-2022 10:43 UTC	Alan Deng
r79	Create/Edit <i>added safety email and locations of c...</i>	15-Nov-2021 4:38 UTC	Nick Bennett
r78	Approve	18-Sep-2021 12:36 UTC	Dick Ciammaichella
r78	Create/Edit <i>Added a few missing words and a comma</i>	17-Sep-2021 1:33 UTC	Georgice Zula
r77	Create/Edit <i>Added a few missing words and a comma</i>	17-Sep-2021 1:33 UTC	Georgice Zula
r76	Approve	16-Aug-2021 1:57 UTC	Taylor Burger
r76	Create/Edit <i>Noise Table</i>	11-Aug-2021 1:27 UTC	Jared deVries
r75	Approve	27-Jul-2021 3:45 UTC	Taylor Burger
r75	Create/Edit <i>PPE & Hearing addition</i>	27-Jul-2021 3:40 UTC	Jared deVries
r74	Approve	27-Jul-2021 3:29 UTC	Taylor Burger
r73	Approve	27-Jul-2021 3:29 UTC	Taylor Burger
r74	Create/Edit <i>PPE Inspections</i>	27-Jul-2021 2:37 UTC	Jared deVries
r73	Create/Edit <i>Ammonia Awareness</i>	27-Jul-2021 2:22 UTC	Jared deVries
r72	Approve	19-May-2021 6:24 UTC	Pete Madonia

Revision	Action/Comment	Date	User
r72	Create/Edit <i>Fall Protection, Colonial Pipeline re...</i>	18-May-2021 11:55 UTC	Jared deVries
r71	Approve	31-Mar-2021 6:49 UTC	Pete Madonia
r71	Create/Edit <i>Vaccine revision</i>	29-Mar-2021 2:54 UTC	Jared deVries
r70	Approve	13-Aug-2020 7:53 UTC	Paul Bodmann
r70	Create/Edit <i>update heat illness</i>	13-Aug-2020 7:42 UTC	Nick Bennett
r69	Approve	24-Apr-2020 5:26 UTC	Kevin McFeaters
r69	Create/Edit <i>Spill revision 3</i>	24-Apr-2020 5:10 UTC	Nick Bennett
r68	Create/Edit <i>Spill revision 2</i>	24-Apr-2020 2:32 UTC	Nick Bennett
r67	Create/Edit <i>Spill prevention added</i>	23-Apr-2020 6:29 UTC	Nick Bennett
r66	Approve	16-Apr-2020 4:54 UTC	Kevin McFeaters
r66	Create/Edit <i>Manual lifting update 2</i>	16-Apr-2020 4:03 UTC	Nick Bennett
r65	Approve	15-Apr-2020 1:26 UTC	Kevin McFeaters
r65	Create/Edit <i>updated manual lifting</i>	15-Apr-2020 12:24 UTC	Nick Bennett
r64	Create/Edit <i>Updated lifting and carrying section...</i>	14-Apr-2020 3:49 UTC	Nick Bennett
r63	Create/Edit <i>Updated Atlanta Office Information</i>	27-Feb-2020 10:12 UTC	Ronald Rodriguez
r62	Create/Edit <i>Added Atlanta Office Information</i>	27-Feb-2020 10:10 UTC	Ronald Rodriguez
r61	Create/Edit <i>Added Atlanta Office Information</i>	27-Feb-2020 9:59 UTC	Ronald Rodriguez
r60	Approve	13-Feb-2020 4:06 UTC	Pete Madonia
r60	Create/Edit <i>heat illness safety revision</i>	13-Feb-2020 3:42 UTC	Nick Bennett
r59	Approve	11-Feb-2020 8:34 UTC	Gary Humble
r59	Create/Edit <i>revised heat illness</i>	11-Feb-2020 8:33 UTC	Nick Bennett
r55	Approve	29-Jan-2020 8:09 UTC	Gary Humble
r58	Approve	29-Jan-2020 8:09 UTC	Gary Humble
r57	Approve	29-Jan-2020 8:09 UTC	Gary Humble
r58	Create/Edit <i>safety revisions PPE</i>	28-Jan-2020 4:28 UTC	Nick Bennett

Revision	Action/Comment	Date	User
r57	Create/Edit <i>PPE Revision</i>	28-Jan-2020 4:21 UTC	Nick Bennett
r56	Approve	24-Jan-2020 9:32 UTC	Taylor Burger
r56	Create/Edit <i>revised hand cleanser</i>	24-Jan-2020 9:31 UTC	Nick Bennett
r55	Create/Edit <i>hand cleanser update</i>	24-Jan-2020 3:39 UTC	Nick Bennett
r54	Approve	23-Jan-2020 7:42 UTC	Taylor Burger
r54	Create/Edit <i>added note about ladders</i>	23-Jan-2020 7:40 UTC	Nick Bennett
r53	Approve	21-Jan-2020 8:45 UTC	Gary Humble
r52	Approve	21-Jan-2020 8:45 UTC	Gary Humble
r51	Approve	21-Jan-2020 8:45 UTC	Gary Humble
r50	Approve	21-Jan-2020 8:45 UTC	Gary Humble
r53	Create/Edit <i>PPE Revision</i>	21-Jan-2020 8:37 UTC	Nick Bennett
r52	Create/Edit <i>edited to include eye wash station</i>	21-Jan-2020 4:20 UTC	Nick Bennett
r51	Create/Edit <i>edited to include eye wash station</i>	21-Jan-2020 4:10 UTC	Nick Bennett
r50	Create/Edit <i>first aid safety training provided by...</i>	21-Jan-2020 4:03 UTC	Nick Bennett
r49	Approve	20-Jun-2019 5:16 UTC	Tommy O'Brien
r49	Create/Edit <i>Added to stop work authority</i>	20-Jun-2019 5:15 UTC	Nick Bennett
r48	Create/Edit <i>Added to stop work authority</i>	20-Jun-2019 5:09 UTC	Nick Bennett
r47	Create/Edit <i>Added to stop work authority</i>	20-Jun-2019 5:09 UTC	Nick Bennett
r46	Approve	12-Apr-2019 6:30 UTC	George Calvin
r46	Create/Edit <i>Added internal investigation training...</i>	12-Apr-2019 6:16 UTC	Nick Bennett
r45	Approve	11-Apr-2019 2:59 UTC	Gary Humble
r45	Create/Edit <i>Added information relating to inciden...</i>	11-Apr-2019 2:52 UTC	Nick Bennett
r44	Approve	10-Apr-2019 7:32 UTC	Pete Madonia
r44	Create/Edit <i>Stop work authority added under Gener...</i>	10-Apr-2019 7:28 UTC	Nick Bennett
r43	Approve	18-Feb-2019 3:12 UTC	Taylor Burger
r43	Create/Edit <i>osha posting dates updated, signed by...</i>	14-Feb-2019 4:54 UTC	Nicole Repko

Revision	Action/Comment	Date	User
r42	Approve	16-Jan-2019 11:03 UTC	Jeff Marshall
r42	Create/Edit <i>Added page anchors</i>	16-Jan-2019 6:48 UTC	Devon Graves
r41	Create/Edit <i>Formatting changes</i>	10-Jan-2019 4:20 UTC	Devon Graves
r40	Create/Edit <i>Formatting updates</i>	8-Jan-2019 10:20 UTC	Chris Engelmann
r39	Approve	13-Dec-2018 5:06 UTC	Jeff Marshall
r39	Create/Edit <i>"Incidents that to not require report..."</i>	29-Nov-2018 5:12 UTC	Brandon O'Hara
r38	Create/Edit <i>Formatting Changes</i>	28-Nov-2018 9:43 UTC	Martin Gonzalez
r37	Approve	6-Jun-2018 5:20 UTC	John Turk
r37	Create/Edit <i>Updated appendix A, Houston info</i>	14-May-2018 9:37 UTC	Christopher Evans
r36	Approve	26-Mar-2018 12:56 UTC	Pete Madonia
r35	Approve	26-Mar-2018 12:55 UTC	Pete Madonia
r34	Approve	26-Mar-2018 12:55 UTC	Pete Madonia
r33	Approve	26-Mar-2018 12:55 UTC	Pete Madonia
r32	Approve	26-Mar-2018 12:55 UTC	Pete Madonia
r31	Approve	26-Mar-2018 12:55 UTC	Pete Madonia
r30	Approve	26-Mar-2018 12:54 UTC	Pete Madonia
r29	Approve	26-Mar-2018 12:53 UTC	Pete Madonia
r28	Approve	26-Mar-2018 12:53 UTC	Pete Madonia
r36	Create/Edit <i>Revised Holly Springs Office Info</i>	22-Mar-2018 3:56 UTC	MaryJo Chelmins
r35	Create/Edit <i>Revised CA inspection form link to do...</i>	22-Mar-2018 3:40 UTC	MaryJo Chelmins
r34	Create/Edit <i>Thousand Oaks Updates</i>	2-Jan-2018 11:22 UTC	Adam Kelly
r33	Create/Edit <i>Thousand Oaks Updates</i>	2-Jan-2018 11:22 UTC	Adam Kelly

Revision	Action/Comment	Date	User
r32	Create/Edit <i>Updated Appendix A, Houston evacuatio...</i>	26-Dec-2017 8:30 UTC	MaryJo Chelmins
r31	Create/Edit <i>updated Campus Inspection Plan</i>	26-Dec-2017 7:33 UTC	MaryJo Chelmins
r30	Create/Edit <i>updated Campus Inspection Plan</i>	26-Dec-2017 7:32 UTC	MaryJo Chelmins
r29	Create/Edit <i>Updated links for Danner/Campus Evac...</i>	26-Dec-2017 4:07 UTC	MaryJo Chelmins
r28	Create/Edit <i>Updated Danner Evac Plan link in Appe...</i>	26-Dec-2017 3:07 UTC	MaryJo Chelmins
r27	Approve	3-Nov-2017 5:45 UTC	Pete Madonia
r27	Create/Edit <i>Named SD, PECII please review roles &...</i>	19-Oct-2017 9:07 UTC	MaryJo Chelmins
r26	Approve	29-Sep-2017 3:34 UTC	Dave Smrdel
r26	Create/Edit <i>Policy section combine & clean-up, ma...</i>	12-Sep-2017 5:34 UTC	MaryJo Chelmins
r25	Approve	7-Jul-2016 4:02 UTC	Jeff Marshall
r25	Create/Edit <i>Update title of John W. Robertson to CEO</i>	15-Jun-2016 3:09 UTC	Malec Kennedy
r24	Create/Edit <i>Fixed two typos in the Bloodborne Pat...</i>	17-May-2016 3:19 UTC	Adam Davis
r23	Approve	12-Jan-2016 10:31 UTC	Pete Madonia
r23	Create/Edit <i>changed "hot, dry skim" to "hot, dry...</i>	5-Jan-2016 5:46 UTC	Georgia Houghton
r22	Approve	17-Aug-2015 7:31 UTC	Pete Madonia
r21	Approve	17-Aug-2015 7:31 UTC	Pete Madonia
r20	Approve	17-Aug-2015 7:30 UTC	Pete Madonia
r19	Approve	17-Aug-2015 7:29 UTC	Pete Madonia
r18	Approve	17-Aug-2015 7:26 UTC	Pete Madonia
r17	Approve	17-Aug-2015 7:26 UTC	Pete Madonia
r22	Create/Edit <i>uploaded link again</i>	4-Aug-2015 12:49 UTC	Taylor Burger
r21	Create/Edit <i>linked to the CPR/First Aid/AED and B...</i>	4-Aug-2015 12:47 UTC	Taylor Burger
r20	Create/Edit <i>linked the Safe Driving Article</i>	3-Aug-2015 8:53 UTC	Taylor Burger
r19	Create/Edit <i>Updated with heat illness, ECP, and g...</i>	30-Jul-2015 4:17 UTC	Natalie Saling
r18	Create/Edit <i>Foot Protection - Two specification d...</i>	9-Jul-2015 1:40 UTC	MaryJo Chelmins

Revision	Action/Comment	Date	User
r17	Create/Edit <i>Foot Protection - Updated requirements</i>	9-Jul-2015 1:20 UTC	MaryJo Chelmins
r16	Approve	22-Aug-2014 6:47 UTC	Pete Madonia
r16	Create/Edit <i>added wording on general suggestion/c...</i>	22-Aug-2014 3:50 UTC	Taylor Burger
r15	Approve	3-Dec-2013 4:09 UTC	Pete Madonia
r15	Create/Edit <i>Updated NC First Aid Cabinet location.</i>	19-Nov-2013 3:42 UTC	Graham Staples
r14	Create/Edit <i>Updated Apex Safety Inspection Form</i>	19-Nov-2013 3:08 UTC	Graham Staples
r13	Create/Edit <i>Updated Apex Safety Inspection Form</i>	19-Nov-2013 3:08 UTC	Graham Staples
r12	Approve	12-Nov-2013 9:01 UTC	Pete Madonia
r12	Create/Edit <i>Updated for MA Office</i>	7-Nov-2013 3:09 UTC	Ben Sias
r11	Approve	18-Oct-2013 2:06 UTC	Pete Madonia
r11	Create/Edit <i>Updated Links to Safety Forms in Gran...</i>	9-Sep-2013 3:05 UTC	MaryJo Chelmins
r10	Approve	11-Jan-2013 2:31 UTC	Jeff Marshall
r10	Create/Edit <i>Fixed tags</i>	11-Jan-2013 2:26 UTC	Dave Hermann
r9	Create/Edit <i>Grammatical and structural changes</i>	25-Nov-2012 9:25 UTC	Ruoth, Joel
r8	Approve	17-May-2012 12:44 UTC	Pete Madonia
r8	Create/Edit <i>added inspection forms</i>	5-Apr-2012 4:05 UTC	Haren, Michael
r7	Create/Edit <i>Include accidents in reporting and no...</i>	13-Dec-2011 6:57 UTC	Pete Madonia
r6	Approve	8-Dec-2011 2:03 UTC	Pete Madonia
r5	Approve	8-Dec-2011 2:03 UTC	Pete Madonia
r4	Approve	8-Dec-2011 2:03 UTC	Pete Madonia
r3	Approve	8-Dec-2011 2:03 UTC	Pete Madonia
r2	Approve	8-Dec-2011 2:03 UTC	Pete Madonia
r1	Approve	8-Dec-2011 2:03 UTC	Pete Madonia
r6	Create/Edit <i>Updated PM, PPE, safety manager</i>	16-Nov-2011 7:11 UTC	Dave Hermann
r5	Approve	16-Nov-2011 1:42 UTC	Pete Madonia
r4	Approve	16-Nov-2011 1:42 UTC	Pete Madonia

Revision	Action/Comment	Date	User
r3	Approve	16-Nov-2011 1:42 UTC	Pete Madonia
r2	Approve	16-Nov-2011 1:42 UTC	Pete Madonia
r1	Approve	16-Nov-2011 1:42 UTC	Pete Madonia
r5	Create/Edit <i>import complete</i>	4-Nov-2011 3:18 UTC	Haren, Michael
r4	Create/Edit <i>30% done with Word doc import</i>	31-Oct-2011 8:28 UTC	Haren, Michael
r3	Approve	7-Mar-2011 2:18 UTC	John Turk
r3	Create/Edit <i>added pdf</i>	28-Jan-2011 8:49 UTC	Tom Grulkowski
r2	Create/Edit <i>added pdf link</i>	28-Jan-2011 8:48 UTC	Tom Grulkowski
r1	Create/Edit <i>import pdf of ver.c from GV</i>	28-Jan-2011 8:46 UTC	Tom Grulkowski

Note: This is a snapshot of a living document. Please check online for the latest revision.

Edited: 23-May-2023 2:52 UTC **Printed:** 20-Oct-2023 6:54 UTC

Document Number: 183 **Revision:** r84