

II. RELATED WORK

Existing studies on NGSO–GSO coexistence have investigated several interference mitigation strategies for reducing NGSO downlink interference toward GSO systems. In this chapter, related works are reviewed in three categories: progressive pitch and beam shutdown, joint power and tilt control, and beamforming-based interference mitigation. The characteristics and limitations of these methods are discussed to clarify the motivation of this work.

A. Progressive Pitch and Beam Shutdown

Progressive pitch is one representative attitude-based interference avoidance strategy for NGSO–GSO coexistence. In this approach, the LEO satellite gradually adjusts its attitude when it approaches low-latitude regions, where its downlink direction may become close to the line-of-sight direction from the GSO ground station to the target GSO satellite. By changing the satellite pointing direction, the LEO downlink beam can be shifted away from this line-of-sight direction, thereby increasing the angular separation observed at the GSO ground station. When attitude adjustment alone is insufficient to satisfy the interference constraint, some high-risk user beams may be shut down to further reduce interference.

Li et al. [19] studied the progressive pitch strategy of the OneWeb constellation. Their results show that progressive pitch can effectively reduce interference to GSO systems in many regions. However, the combination of satellite tilting and partial beam shutdown may also reduce coverage continuity and create service blind areas during certain periods. This indicates that interference avoidance based only on attitude adjustment and beam shutdown may still affect the service availability of LEO users.

B. Joint Power and Tilt Control

Another type of interference mitigation method combines transmit power control with satellite tilt control. Power control reduces the transmit power of LEO satellites when they approach high-risk regions near the GSO ground station, so that the interference received at the GSO ground station can be lowered. Compared with progressive pitch methods that follow a predefined attitude adjustment strategy, joint power and tilt control formulates the mitigation process as an optimization problem. The transmit power and tilt angle of LEO satellites are jointly adjusted to satisfy the EPFD constraint while improving user demand satisfaction.

Jalali et al. [18] proposed a joint power and tilt control method for NGSO–GSO interference mitigation. Their method optimizes LEO transmit power and satellite tilt angle under the aggregate EPFD constraint. Compared with direct beam shutdown, this approach provides a more flexible way to reduce interference and preserve user service. However, when the interference constraint is strict, the transmit power of critical satellites may still need to be significantly reduced, which can limit the achievable service quality of LEO users during critical periods.

C. Beamforming and Beam Steering

Beamforming-based methods provide another interference mitigation direction for NGSO satellite systems equipped with phased-array antennas. Instead of only reducing transmit power or adjusting satellite attitude, beamforming controls antenna weight vectors to steer signals toward intended LEO users and suppress emissions toward GSO ground stations. In this way, the NGSO system can improve its downlink transmission while reducing co-channel interference to the GSO system.

Jalali et al. [20] investigated downlink beamforming strategies for interference-aware NGSO satellite systems. They proposed an aggregate interference-constrained beamforming method to limit the interference received at GSO ground stations while satisfying the service requirements of LEO users. This approach shows that beamforming can be an effective interference mitigation technique for advanced NGSO payloads. However, beamforming generally requires phased-array antennas, channel state information or average channel state information, and higher computational complexity. Since this work focuses on a fixed multi-beam LEO system, beamforming-based control is not considered in this thesis.

D. Summary and Research Gap

The above studies show that NGSO–GSO interference can be mitigated through satellite attitude adjustment, transmit power control, beam shutdown, or antenna-domain beamforming. These methods reduce the interference received at GSO ground stations from different perspectives. However, when mitigation actions reduce the available resources of LEO satellites, the service quality of LEO users may still be affected. In particular, users originally served by beams that are shut down during critical periods require additional service recovery support.

Existing studies have not addressed how neighboring LEO satellite beams can be used to recover the service of users affected by beam shutdown under the GS EPFD constraint. This motivates the proposed EABR framework, which exploits predictable coverage overlap among neighboring LEO satellites for service recovery while maintaining EPFD compliance.

REFERENCES

- [1] M. Giordani and M. Zorzi, “Non-terrestrial networks in the 6g era: Challenges and opportunities,” *IEEE Network*, vol. 35, no. 2, pp. 244–251, 2021.
- [2] X. Lin, S. Cioni, G. Charbit, R. Chuberre, S. Hellsten, and J.-F. Boutillon, “On the path to 6g: Embracing the next wave of low earth orbit satellite access,” *IEEE Communications Magazine*, vol. 59, no. 5, pp. 36–42, 2021.
- [3] E. Juan, M. Lauridsen, J. Wigard, and P. Mogensen, “Handover solutions for 5g low-earth orbit satellite networks,” *IEEE Access*, vol. 10, pp. 93 309–93 325, 2022.
- [4] M. Al-Ansi, J. Querol, M. Alsenwi, E. Lagunas, and S. Chatzinotas, “Enhancing handover performance in LEO satellite networks with multi-connectivity and conditional handover approach,” in *Proceedings of the International Conference on Software, Telecommunications and Computer Networks (SoftCOM)*, 2024.
- [5] A. Gonzalez-Garrido, J. Querol, H. Wymeersch, and S. Chatzinotas, “Joint communication and navigation from LEO multi-beam satellite,” *IEEE Open Journal of the Communications Society*, vol. 6, pp. 4384–4404, 2025.
- [6] D. Christopoulos, S. Chatzinotas, J. Krause, and B. Ottersten, “Multi-user detection in multibeam mobile satellite systems: A fair performance evaluation,” *IEEE Transactions on Communications*, vol. 61, no. 12, pp. 4963–4974, 2013.

- [7] X. Zhu and C. Jiang, "Integrated satellite-terrestrial networks toward 6g: Architectures, applications, and challenges," *IEEE Internet of Things Journal*, vol. 9, no. 1, pp. 437–461, 2022.
- [8] O. B. Al-Hraishawi, H. Chaaban, S. Kisseleff, E. Lagunas, and S. Chatzinotas, "A survey on non-geostationary satellite systems: The communication perspective," *IEEE Communications Surveys & Tutorials*, vol. 25, no. 1, pp. 101–132, 2023.
- [9] ITU-R, "Radio regulations," International Telecommunication Union, Geneva, Switzerland, 2020, see Article 22 for NGSO–GSO interference limits and EPFD framework.
- [10] —, "Functional description to be used in developing software tools for determining conformity of non-geostationary-satellite orbit fixed-satellite service systems or networks with limits contained in article 22 of the radio regulations," International Telecommunication Union Radiocommunication Sector (ITU-R), Geneva, Switzerland, Recommendation S.1503-3, 2018.
- [11] International Telecommunication Union Radiocommunication Sector (ITU-R), "Satellite antenna radiation patterns for non-geostationary orbit satellite antennas operating in the fixed-satellite service below 30 ghz," ITU-R, Geneva, Switzerland, Recommendation S.1528, 2001.
- [12] ITU-R, "Reference fss earth-station radiation patterns for use in interference assessment involving non-gso satellites in frequency bands between 10.7 ghz and 30 ghz," ITU-R, Geneva, Switzerland, Recommendation S.1428-1, 2001.
- [13] —, "Calculation of free-space attenuation," International Telecommunication Union Radiocommunication Sector, Geneva, Switzerland, Recommendation P.525.
- [14] —, "Attenuation by atmospheric gases and related effects," International Telecommunication Union Radiocommunication Sector, Geneva, Switzerland, Recommendation P.676.
- [15] ETSI, "5g; system architecture for the 5g system (5gs) (3gpp ts 23.501 version 16.14.0 release 16)," European Telecommunications Standards Institute, ETSI TS 123 501 V16.14.0, Sep. 2022, 3GPP TS 23.501 version 16.14.0 Release 16.
- [16] C. Braun, A. M. Voicu, L. Simić, and P. Mähönen, "Should we worry about interference in emerging dense NGSO satellite constellations?" in *Proc. IEEE Int. Symp. Dyn. Spectr. Access Netw. (DySPAN)*, 2019, pp. 1–10.
- [17] A. Hills, J. M. Peha, and J. Munk, "Feasibility of using beam steering to mitigate ku-band leo-to-geo interference," *IEEE Access*, vol. 10, pp. 74 023–74 032, 2022.
- [18] M. Jalali, F. Ortiz, E. Lagunas, S. Kisseleff, L. Emiliani, and S. Chatzinotas, "Joint power and tilt control in satellite constellation for NGSO–GSO interference mitigation," *IEEE Open Journal of Vehicular Technology*, vol. 4, pp. 545–557, 2023.
- [19] T. Li, J. Jin, W. Li, Z. Ren, and L. Kuang, "Research on interference avoidance effect of oneweb satellite constellation's progressive pitch strategy," *International Journal of Satellite Communications and Networking*, vol. 39, no. 5, pp. 524–538, 2021.
- [20] M. Jalali, E. Lagunas, A. Haqiqatnejad, S. Kisseleff, and S. Chatzinotas, "Downlink beamforming strategies for interference-aware NGSO satellite systems," *IEEE Open Journal of the Communications Society*, vol. 5, pp. 3468–3483, 2024.
- [21] G. Cocco, M. Angelone, and A. I. Pérez-Neira, "Co-channel interference cancellation at the user terminal in multibeam satellite systems," in *Proceedings of the IEEE International Conference on Communications (ICC)*, 2014, pp. 3992–3997.
- [22] C. E. Shannon, "A mathematical theory of communication," *Bell System Technical Journal*, vol. 27, no. 3, pp. 379–423, 1948.
- [23] J. Lei and M. A. Vázquez-Castro, "Multibeam satellite frequency/time duality study and capacity optimization," *Journal of Communications and Networks*, vol. 13, no. 5, pp. 472–480, 2011.
- [24] WorldVu Satellites Limited, "Oneweb non-geostationary satellite system," FCC IBFS File No. SAT-LOI-20160428-00041, Technical Attachment, Washington, DC, USA, 2016, oneWeb NGSO system description.
- [25] Federal Communications Commission, "Space Exploration Holdings, LLC, Request for Modification of the Authorization for the SpaceX NGSO Satellite System," Order and Authorization and Order on Reconsideration, FCC 21-48, Washington, DC, USA, Apr. 2021.
- [26] —, "Space Station Applications Accepted for Filing," Public Notice, Report No. SAT-01632, Washington, DC, USA, May 2022.
- [27] Analytical Graphics, Inc., "Systems tool kit (stk)," <https://www.agi.com/products/stk>, 2023, online; accessed 21-Jul-2025.
- [28] The MathWorks, Inc., "Matlab r2023b," <https://www.mathworks.com/products/matlab.html>, 2023, online; accessed 21-Jul-2025.
- [29] ITU-R, "Interference mitigation techniques and frequency sharing in the bands 37.5–42.5 ghz and 47.2–50.2 ghz between geostationary-satellite fixed-satellite service networks and non-geostationary-satellite fixed-satellite service systems," ITU-R, Geneva, Switzerland, Recommendation S.1655-0, 2003.