S 1 Text. Component-wise recalibration: detailed methods and complete comparison scope

This supplement accompanies *Spatial-filter refitting improves limited-label EEG decoding beyond classifier recalibration*. It integrates the original frozen comparison and the later school-HPC discovery rounds while preserving the original datasets, model identities, endpoint roles and result files. The original submission's scientific and provenance supplements remain available at their versioned paths.

S 1. Study layers and statistical units

Layer	Participants	Scientific role	Model/seed information	Selection status
Original comparison	18, partitioned as six development and 12 primary	Full CSP/LDA minus frozen was the primary contrast; full minus LDA-only was secondary	Original EEGNet reference: three seeds and 54 source models	Original pipeline and endpoint hierarchy frozen before primary performance calculation; prior exploratory exposure retained in the record
V2 discovery	The same six development participants	Candidate covariance mixture versus EA-CSP; support-budget and neural diagnostics	18 separately versioned individual sources	Development data had already been exposed
V3 discovery	The same six development participants	Prespecified candidate comparisons and exploratory component mechanisms	Read-only reuse of 18 V2 sources; three new pooled sources; all fixed seeds	Data had already been exposed; all resulting hypotheses remain discovery findings
Mechanism simulation	No human participants	Known-mechanism estimator stress tests	384 scenarios × 50 paired draws × nine methods	Synthetic, with soft-ware_validation_only=true; separate from real EEG evidence

Participant was the independent unit for real-EEG endpoint intervals. Seeds were averaged within session and sessions within participant. The neural source conditions share participants; pooled teachers are also shared across participant evaluations. Neither model counts nor repeated target predictions supply additional independent participants. Bootstrap uncertainty for pooled teachers is conditional on those fitted teachers.

S 2. Exact data access and endpoint definition

The original source-training set comprised session 0/runs 0–1, validation run 2, and source query run 3. The first whole run of each later session supplied support, with subsequent whole runs reserved for query. The chronological support prefixes were capped at 4/8/12/16/20 complete trials in V2/V3; the last cap retained 19 if only 19 complete support windows were available. A prefix containing one class was preserved. Future labels were never used to balance it, choose a policy, select a model or replace a missing class.

The original conventional update comparison pooled 40 source-training trials with the 19/20 current-support trials. Neural fine-tuning in V3 optimized current support only, starting from the specified source checkpoint. The functional constraint additionally evaluated the participant's 40 source-training examples as fixed prediction anchors. Source validation selected source epochs; it did not select target adaptation epochs. The pooled source regime used the six participants' source training/validation sets, not their query data.

All methods compared within a saved query identity used the same ordered trial IDs and true labels. Importing EA-CSP from V2 required actual ordered trial/label agreement, because versioned query-hash conventions differed. A successful hash comparison alone was not substituted for identity alignment.

BA required both true classes. Participant target endpoints required all five sessions and all scheduled neural seeds. Undefined groups remained explicit rather than disappearing from the mean. Source-query metrics were reported separately. The original trial exclusions and window lengths were not changed to improve a new score.

Cue-window interpretation

Seven thousand one hundred fifty-six complete sample windows were retained from 7,200 exported events; 44 crossed recording boundaries. The event-code documentation and MOABB interval establish the released cue-anchored convention. Reconstructing phase-pure motor imagery for each window would additionally require original marker arrays, task-end/feedback boundaries and the precise derivative-conversion lineage. The variable online trial duration alone establishes neither a cutting error nor the behavioral meaning of each partial event.

S 3. Original prediction-transition and sensitivity definitions

For binary labels c∈{0, 1}, define C_c as the proportion of true-class-c trials that change from incorrect under A to correct under B, and E_c for the reverse transition. Then

$$\Delta BA = \tfrac{1}{2}(C_0 + C_1) - \tfrac{1}{2}(E_0 + E_1).$$

The two contributions were averaged over five sessions within each participant before cohort inference. They exactly reconstruct the saved BA difference. The 73.7% spatial-component share is the ratio of cohort-average full-minus-LDA-only to full-minus-frozen, not an independently estimated causal proportion of neural adaptation.

Original primary-cohort mean full-minus-LDA-only was 5.47 pp, with corrected-error and introduced-error contributions 16.04 pp and 10.57 pp. Left/right recall changes were 6.16 pp and 4.78 pp, individually with intervals crossingzero. The same component contrast was positive in 10/12 participant averages and all five session means; participant-deletion means ranged 4.39–6.28 pp. These are related descriptions of the same fitted models and predictions.

The pre-existing amplitude flag was 250 µV maximum raw channel peak-to-peak. It flagged 1,512/7,156 complete windows. Saved-prediction/QC matching used trial identity, role, true label and inclusion status. The unflagged target endpoint required both classes in every session; only ten original primary participants met that criterion. Their unflagged full-minus-frozen gain was 5.96 pp[0.99, 11.24] and component gain 3.82 pp[1.11, 6.72]. Their corresponding full-query gains were 6.50 pp and 4.53 pp. Restricting query evaluation did not alter source or support data, and the unflagged subset was not labeled artifact-free.

Original exploratory exact sign-flip tests enumerated all 2^n assignments under a sign-symmetric reference. Four-comparison Holm-adjusted p values were.05859 for full-minus-frozen and.04102 for full-minus-LDA-only in the 12-person primary cohort. These checks were conducted after the original outcomes, and their reference distribution differs from the percentile-bootstrap construction.

S 4. Geometric estimator

Source-fixed feature space

Each trial covariance was trace-normalized and regularized using shrinkage 0.1. Let R_s be the source-training-only reference covariance and

$$z = \mathrm{vech}_{\sqrt{2}}\{\log(R_s^{-1/2} C R_s^{-1/2})\}.$$

The symmetric-vector operator multiplies off-diagonal elements by√2 to preserve the Frobenius inner product. With 22 channels, p=253. The reference remains fixed for every current-session budget and all queries. Trace normalization and identity shrinkage do not confer strict invariance to arbitrary affine sensor transformations.

For a domain d, define class means μ_{d0}, μ_{d1} and

$$m_d = (\mu_{d0} + \mu_{d1})/2, \qquad h_d = (\mu_{d1} - \mu_{d0})/2, \qquad \theta_d = [m_d; h_d].$$

Class feature covariance estimates B_dc use fixed 0.1 shrinkage. With U_dc=B_dc/n_dc, the estimated mean-observation covariance is

$$V_d = \frac{1}{4}\begin{bmatrix} U_{d0} + U_{d1} & U_{d1} - U_{d0} \\ U_{d1} - U_{d0} & U_{d0} + U_{d1} \end{bmatrix}.$$

Separate shift-variation scales are

$$\tau_j^2 = \max\{(\|\theta_{tj} - \theta_{sj}\|^2 - \mathrm{tr}(V_{s,jj} + V_{t,jj}))/p, 0\}, \quad j \in \{m, h\}.$$

Let T=diag(τ_m²I,τ_h²I), M=V_s+T. With both classes observed,

$$\hat{\theta} = \theta_s + M(M + V_t)^{-1}(\theta_t - \theta_s), \qquad P = M - M(M + V_t)^{-1}M.$$

The implementation uses a masked linear-Gaussian update and the Joseph form for P. For a single observed class, the mask retains only that class's observations, unidentifiable shift variation is set tozero, and the unobserved class retains its source mean. A class represented by one support trial uses the fixed source class covariance as its variance proxy. The numerical floor is 10^{-8}.

Conditional result and prediction

Under the specified Gaussian observation/prior model with known fixed noise matrices, completing the square gives the posterior above. For any estimate a, posterior expected squared error is tr(P)+‖a−θ‖²; the posterior mean minimizes that conditional risk. Plug-in covariance estimation, uncertainty in R_s, and uncertainty in source within-class covariance are outside that statement. The implementation propagates conditional class-mean uncertainty, not all representation uncertainty.

For class 0/1, let A_c=[I,−I] or[I, I]. The full candidate scores a Gaussian with mean A_cθ and covariance Q_c=W+A_cPA_cᵀ, using equal class priors and fixed source within-class covariance W. Point prediction uses the same θ and W without P. B/n assumes independent observations; serial-correlation simulations explicitly test violation of that approximation. No BA optimality or target negative-transfer theorem follows from the conditional expected squared-error result.

Complete arm definitions

Saved method ID	Defining difference
source_tangent_frozen	Source-fixed means and within-class covariance
tangent_pooled	Ordinary source/support pooled means; fixed source within-class covariance
tangent_refit	Ordinary source/support refitting of means and within-class covariance
eb_point	Candidate posterior means; prediction uses fixed W without P
eb_predictive	Full candidate posterior means and predictive covariance
eb_isotropic	Isotropic mean-noise replacement, retaining predictive covariance
eb_coupled	One common shift scale instead of separate m/h scales

Saved method ID	Defining difference
eb_no_source_noise	Same estimated T, with source mean-noise covariance removed
eb_no_shift	T=0, retaining finite-sample mean updating

The candidate-minus-tangent_refit cap 20 comparison retains its prespecified primary role. Candidate-minus-saved-V2-EA-CSP is the strong reference. All other budgets and ablations remain descriptive discovery comparisons.

S 5. Neural update modes and optimization

The compact HPC network uses temporal_filters 8, depth_multiplier 2, kernel_length 64, source Dropout 0.25, BN epsilon 0.001 and momentum 0.01. The individual regime reuses 18 V2 checkpoint identities; the pooled regime uses three new shared source checkpoints trained on 240 source-training/120 source-validation examples. These six participants are the same people in both conditions.

All optimizer adaptations use 20 epochs, batch 16, AdamW, learning rate 10^{-4}, weight decay 10^{-4}, cosine scheduling and no AMP. A separate saved sampler controls support order. The methods reset to their own declared teacher before adapting each current-session/budget; they do not accumulate future support. Source normalization is reused rather than refitted from query.

Policy (readable name)	Optimized parameters	Adaptation BN mode	Dropout during adaptation
Frozen	None	Source statistics	Off
Head only, fixed BN	Classifier head	Source statistics	Off
Full, fixed BN	All	Source statistics	Off
Full, adaptive BN	All	Current minibatch statistics; running-state updates	Off
Full, adaptive BN + Dropout	All	Current minibatch statistics; running-state updates	On
BN affine, fixed statistics	BN affine scale/bias only	Source statistics	Off
BN statistics only	No optimizer; one support batch	Running-state update	Off
Full, KL constrained	All, subject to source KL constraint	Source statistics	Off

Canonical policy IDs are retained in the complete machine-readable tables: frozen, head_fixed, full_fixed, full_adaptive_bn, full_adaptive_bn_dropout, bn_affine_fixed,

bn_stats_only and trust_fixed, in the row order above.

Fixed/adaptive BN changes normalization during gradient computation as well as the resulting buffers. Their trained weights need not coincide. Within each budget, initialization, support order, Dropout setting and optimizer exposure are held fixed. Across budgets, both examples and minibatch structure change: batch 16 yields one batch per epoch for caps≤16 and two for 19/20. With three BN modules, 20 epochs correspond to 60 or 120 total batch-counter increments. The cap 20 contrast therefore cannot establish a general monotone relation between label quantity and BN benefit.

The functional policy evaluates teacher-to-candidate mean KL on 40 source-training anchors and enforces δ=0.01 in the core experiment, with separate full runs at 0.001 and 0.1. Up to 12 halvings are attempted for a proposed optimizer step. Rejected proposals restore parameters and Adam state and are counted separately from accepted optimizer updates. This is part of the algorithm, not an automatic restart of a scientific fit. Pinsker and Jensen yield mean anchor total variation ≤√(δ/2); this finite-anchor probability statement does not bound discrete class changes or unseen-target BA.

S 6. Complete reporting, intervals and influence

The supplied machine-readable analysis retains every method, budget, participant, session and seed, including the primary candidate failures. Prespecified roles are separate from the selection of a narrative after results were available. Later pointwise discovery intervals use 10,000 participant resamples and seed 20261023; original intervals use seed 42. They should not be interpreted as a confirmatory multiple-comparison procedure across the discovery matrix.

The cap 20 BN-mode participant-deletion mean ranges were+1.07 to+1.90 pp for individual sources and+1.34 to+2.29 pp for pooled sources. These are descriptions of the same six-person result. The later neural comparison does not promote its smaller positive interval into a new predefined primary hypothesis.

Collapse means a model/session predicts one class on its query set even when both true classes exist. Cap 20 fixed-BN/adaptive-BN collapse counts were 8/16 for individual sources and 0/18 for pooled sources, each out of 90 nested seed/session cells. All were retained in BA. They are not statistically independent events.

S 7. Complete saved synthetic grid

The fixed factorial grid used p∈{16, 64}, source examples per class∈{10, 20,100}, support examples per class∈{1, 2, 5, 10}, shift type∈{none, common, contrast, both}, anisotropy∈{1, 20}, and stationary AR(1) correlation∈{0, 0.5}. Shift scale was.5, with 50 paired draws and 100 query examples per class. All nine methods received the same source/support/query draws within each replicate. The estimator was not given the true serial-correlation parameter as an oracle correction.

All 172,800 saved cells were retained with finite metrics and explicit synthetic/software-validation flags. Cross entropy uses the true-class probability with a numerical lower bound of 10^{-15} before taking the logarithm. Outcomes comprise BA, cross entropy, binary Brier score and two class-mean squared-error definitions. Full-grid averaging gives every frozen scenario equal weight; paired Monte Carlo variation measures the finite

draws in this fixed grid, not uncertainty over EEG participants or all possible mechanisms. Condition-specific findings remain within this known data-generating setup.

The companion figure and saved scenario table display performance by shift, noise anisotropy, dimension, source size and serial correlation. No favorable subset of scenarios replaces the complete-grid result. Probability-based EEG diagnostics are post-hoc saved-output analyses; numerical probability clipping for logarithmic scoring is identified in their analysis record.

S 8. Calibration reliability and retained original limitations

Original source/support probes evaluated low-dimensional power and source-fitted representations, followed by supervised CSP4/LDA controls. The support-half analysis split each class chronologically and retained frozen source transforms. Among 30 sessions, 19 had positive signed source-score orientation in both halves, two were negative in both, and nine changed sign. These observations separate agreement from intended class orientation; they do not define an accepted update gate.

All interpretation retains potential cue/feedback mixing, fixed zero-phase offline filtering, amplitude artifacts in both fitting and query data, one public cohort, prior test exposure and modest independent sample size. Pooled source labels and additional validation labels are reported as information-budget differences. The experiment does not estimate human skill retention, plasticity, clinical efficacy or prospective closed-loop improvement.

S 9. Saved-result provenance and computational scope

The V3 raw received archive is `paper2-results-83cbdfdcfa541b3ab3addfc3.tar.gz`, 40,194,093 bytes, SHA256 `e509c2591efa21fff4dd47236e613ed6b611ca10ad20bac3da37e66e34a9d170`. It comprises three verified GitHub parts at fixed commit `500831c086d9e1d1e8412cf8ebca5fb6a288db7`. Its 49,984 payload files plus manifest matched their lengths and checksums; 126 unique valid task-completion identities matched the frozen queue. The public packet contains no original EEG, optimizer tensors or model weights.

The original three slot jobs were 775309, 775310 and 775311. Each completed 42 tasks with recorded exit 0, no restart; actual slot walltimes show sequential execution. Submission for three available slots was a capacity setting, not evidence of simultaneous execution. Such runtime/storage details establish provenance and completion, not the numerical accuracy of predictions.

This revision reused saved outputs. It did not launch a new fit, load real checkpoint weights, repeat a query forward pass, add seeds, alter support windows or change a source model. Original submitted packages and prior failed/negative results remain at their paths. Reproduction scripts, table definitions, figure inputs and targeted verification are identified in the accompanying revision report.

S 10. Complete V3 cohort means across all frozen budgets

Values are BA percentages. Every row uses all six participants, all five target sessions and all declared seeds where applicable. `core`, `kl0p001` and `kl0p1` are separate frozen variants; no dose or cap has been selected from this table. The saved EA reference is included under the geometric scope after ordered query-identity alignment.

Family / source / variant	Method	Cap 4	Cap 8	Cap 12	Cap 16	Cap 20
Geometry / own / core	EB coupled	57.82	60.33	61.63	66.10	61.35
Geometry / own / core	EB isotropic	62.37	62.72	65.14	66.31	64.57
Geometry / own / core	EB no shift	59.06	57.23	60.62	62.53	60.22
Geometry / own / core	EB no source noise	57.83	59.95	63.01	65.27	61.71
Geometry / own / core	EB point	58.67	60.84	63.84	67.24	66.52
Geometry / own / core	EB pre-dictive	59.11	61.48	63.92	66.63	64.68
Geometry / own / core	Saved V2 EA-CSP	66.79	67.48	67.71	70.86	70.37
Geometry / own / core	Frozen tangent	60.36	60.36	60.36	60.36	60.36
Geometry / own / core	Pooled means	59.46	59.73	61.61	64.46	64.08
Geometry / own / core	Tangent refit	63.50	62.90	66.19	66.97	67.01
Neural / pooled / core	BN affine, fixed statis-tics	55.23	55.02	55.39	55.49	55.46
Neural / pooled / core	BN statis-tics only	55.22	55.24	55.32	55.29	54.95
Neural / pooled / core	Frozen	55.26	55.26	55.26	55.26	55.26
Neural / pooled / core	Full, adaptive BN	55.27	55.61	55.41	55.34	54.31

Family / source / variant	Method	Cap 4	Cap 8	Cap 12	Cap 16	Cap 20
Neural / pooled / core	Full, adaptive BN + Dropout	55.28	55.61	55.39	55.41	54.59
Neural / pooled / core	Full, fixed BN	56.02	55.61	55.90	56.66	56.22
Neural / pooled / core	Head only, fixed BN	55.48	55.41	55.57	55.74	55.54
Neural / pooled / core	Full, KL con-strained	56.02	55.61	55.87	56.66	56.25
Neural / pooled / KL 0.001	Full, KL con-strained	55.77	55.25	55.64	56.45	56.03
Neural / pooled / KL 0.1	Full, KL con-strained	56.02	55.61	55.90	56.66	56.22
Neural / individ-ual / core	BN affine, fixed statis-tics	56.73	56.73	56.76	57.11	57.04
Neural / individ-ual / core	BN statis-tics only	56.73	56.73	56.71	56.73	55.59
Neural / individ-ual / core	Frozen	56.74	56.74	56.74	56.74	56.74
Neural / individ-ual / core	Full, adaptive BN	57.08	57.11	57.26	57.54	56.01
Neural / individ-ual / core	Full, adaptive BN + Dropout	57.25	57.18	57.16	57.43	55.86
Neural / individ-ual / core	Full, fixed BN	56.90	56.77	56.80	57.50	57.51

Family / source / variant	Method	Cap 4	Cap 8	Cap 12	Cap 16	Cap 20
Neural / individual / core	Head only, fixed BN	56.39	56.45	56.84	56.88	56.81
Neural / individual / core	Full, KL constrained	56.91	56.83	56.87	57.50	57.50
Neural / individual / KL 0.001	Full, KL constrained	56.64	56.68	56.83	57.32	57.29
Neural / individual / KL 0.1	Full, KL constrained	56.90	56.77	56.80	57.50	57.51

All paired participant differences, pointwise intervals, negative-participant counts and reference-role labels are retained in the companion comparison table. The full primary geometry and neural candidate outcomes appear in the main text; this complete grid supplies context without changing those roles.

S 11. Complete-grid synthetic method summary

These means give every frozen scenario and paired draw equal weight. Probability scoring uses the saved simulation definitions. They are not human EEG results, and their numerical scales are conditional on the synthetic generator.

Method	BA (%)	Cross entropy	Binary Brier	Mean squared feature error
source_tangent_frozen	74.31	2.9701	0.2276	0.10815
tangent_pooled	75.72	2.5729	0.2134	0.08115
tangent_refit	76.19	2.2408	0.2064	0.08115
eb_point	70.40	3.9747	0.2688	0.26669
eb_predictive	70.36	3.6337	0.2669	0.26669
eb_isotropic	73.29	2.0276	0.2304	0.16210
eb_coupled	70.58	3.5845	0.2646	0.25179
eb_no_source_noise	70.28	3.7042	0.2681	0.25980
eb_no_shift	74.87	2.5946	0.2210	0.13010

The full candidate minus tangent refitting was−5.8255 BA points. Of 384 scenario means, eight favored the candidate and 376 favored refitting. Candidate feature-mean squared error exceeded refitting in every scenario mean. Posterior-predictive versus point candidate prediction changed mean cross entropy by−0.34094, Brier by−0.00191 and BA

by−0.0398 percentage points. These comparisons separate improvements in a probability score from superiority in decoding or estimation.